

Radiated Emission


EUT Information

EUT Model Name:	WiFi Advisor M/N: WFED-300AC
Operation mode:	TX 5825MHz
Test Voltage:	AC 120V/60Hz
Comment:	JDSU

Common Information

Test Site:	SMQ EMC Lab.
Environment Conditions:	
Antenna Polarization:	Horizontal
Operator Name:	
Comment:	802.11ac VHT20---3TX (Non-Beamforming)

Copy of FCC Electric Field Strength 26.5-40GHz



Radiated Emission


EUT Information

EUT Model Name:	WiFi Advisor M/N: WFED-300AC
Operation mode:	TX 5825MHz
Test Voltage:	AC 120V/60Hz
Comment:	JDSU

Common Information

Test Site:	SMQ EMC Lab.
Environment Conditions:	
Antenna Polarization:	Vertical
Operator Name:	
Comment:	802.11ac VHT20---3TX (Non-Beamforming)

Copy of FCC Electric Field Strength 26.5-40GHz



Produkte
 Products

802.11ac VHT40_1TX - Non Beamforming




ACCURATE TECHNOLOGY CO., LTD.
 F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
 Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber
 Tel:+86-0755-26503290
 Fax:+86-0755-26503396

Job No.: PZ #2252	Polarization: Vertical
Standard: FCC Class B 3M Radiated	Power Source: AC 120V/60Hz
Test item: Radiation Test	Date: 14/11/23/
Temp.(C)/Hum.(%) 23 C / 48 %	Time:
EUT: WiFi Advisor	Engineer Signature: PEI
Mode: TX 5755MHz	Distance: 3m
Model: WFED-300AC	
Manufacturer: JDSU	

Note: 802.11ac VHT40---1TX (Non-Beamforming)



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	34.8823	32.26	-10.41	21.85	40.00	-18.15	QP			
2	78.9651	37.22	-16.57	20.65	40.00	-19.35	QP			
3	151.5971	36.99	-15.14	21.85	43.50	-21.65	QP			

Produkte
 Products




ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
 Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber
 Tel:+86-0755-26503290
 Fax:+86-0755-26503396

Job No.: PZ #2253	Polarization: Horizontal
Standard: FCC Class B 3M Radiated	Power Source: AC 120V/60Hz
Test item: Radiation Test	Date: 14/11/23/
Temp.(C)/Hum.(%) 23 C / 48 %	Time:
EUT: WiFi Advisor	Engineer Signature: PEI
Mode: TX 5755MHz	Distance: 3m
Model: WFED-300AC	
Manufacturer: JDSU	

Note: 802.11ac VHT40---1TX (Non-Beamforming)



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	80.3619	38.04	-16.43	21.61	40.00	-18.39	QP			
2	123.2655	33.48	-13.53	19.95	43.50	-23.55	QP			
3	336.0351	41.85	-8.23	33.62	46.00	-12.38	QP			

Produkte
 Products




ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
 Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber
 Tel:+86-0755-26503290
 Fax:+86-0755-26503396

Job No.: PZ #2254	Polarization: Horizontal
Standard: FCC Class B 3M Radiated	Power Source: AC 120V/60Hz
Test item: Radiation Test	Date: 14/11/23/
Temp.(C)/Hum.(%) 23 C / 48 %	Time:
EUT: WiFi Advisor	Engineer Signature: PEI
Mode: TX 5795MHz	Distance: 3m
Model: WFED-300AC	
Manufacturer: JDSU	

Note: 802.11ac VHT40---1TX (Non-Beamforming)



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	80.9274	37.52	-16.31	21.21	40.00	-18.79	QP			
2	119.8555	34.39	-13.14	21.25	43.50	-22.25	QP			
3	336.0350	42.46	-8.23	34.23	46.00	-11.77	QP			

Produkte
 Products




ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
 Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber
 Tel:+86-0755-26503290
 Fax:+86-0755-26503396

Job No.: PZ #2255	Polarization: Vertical
Standard: FCC Class B 3M Radiated	Power Source: AC 120V/60Hz
Test item: Radiation Test	Date: 14/11/23/
Temp.(C)/Hum.(%) 23 C / 48 %	Time:
EUT: WiFi Advisor	Engineer Signature: PEI
Mode: TX 5795MHz	Distance: 3m
Model: WFED-300AC	
Manufacturer: JDSU	

Note: 802.11ac VHT40---1TX (Non-Beamforming)



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	35.0048	32.46	-10.42	22.04	40.00	-17.96	QP			
2	78.1389	38.07	-16.61	21.46	40.00	-18.54	QP			
3	151.0665	37.68	-15.14	22.54	43.50	-20.96	QP			

Produkte
 Products




ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
 Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber
 Tel:+86-0755-26503290
 Fax:+86-0755-26503396

Job No.: PZ #2541	Polarization: Vertical
Standard: FCC Class B 3M Radiated	Power Source: AC 120V/60Hz
Test item: Radiation Test	Date: 14/11/26/
Temp.(C)/Hum.(%) 23 C / 48 %	Time:
EUT: WiFi Advisor	Engineer Signature: PEI
Mode: TX 5755MHz	Distance: 3m
Model: WFED-300AC	
Manufacturer: JDSU	

Note: 802.11ac VHT40---1TX (Non-Beamforming)



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	16891.045	8.83	41.39	50.22	74.00	-23.78	peak			
2	16891.045	-2.05	41.39	39.34	54.00	-14.66	AVG			

Produkte
 Products




ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
 Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber
 Tel:+86-0755-26503290
 Fax:+86-0755-26503396

Job No.: PZ #2542	Polarization: Horizontal
Standard: FCC Class B 3M Radiated	Power Source: AC 120V/60Hz
Test item: Radiation Test	Date: 14/11/26/
Temp.(C)/Hum.(%) 23 C / 48 %	Time:
EUT: WiFi Advisor	Engineer Signature: PEI
Mode: TX 5755MHz	Distance: 3m
Model: WFED-300AC	
Manufacturer: JDSU	

Note: 802.11ac VHT40---1TX (Non-Beamforming)



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	17537.798	6.08	43.88	49.96	74.00	-24.04	peak			
2	17537.798	-3.85	43.88	40.03	54.00	-13.97	AVG			

Produkte
 Products




ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
 Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber
 Tel:+86-0755-26503290
 Fax:+86-0755-26503396

Job No.: PZ #2543	Polarization: Horizontal
Standard: FCC Class B 3M Radiated	Power Source: AC 120V/60Hz
Test item: Radiation Test	Date: 14/11/26/
Temp.(C)/Hum.(%) 23 C / 48 %	Time:
EUT: WiFi Advisor	Engineer Signature: PEI
Mode: TX 5795MHz	Distance: 3m
Model: WFED-300AC	
Manufacturer: JDSU	

Note: 802.11ac VHT40---1TX (Non-Beamforming)



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	16745.214	9.59	40.99	50.58	74.00	-23.42	peak			
2	16745.214	-1.00	40.99	39.99	54.00	-14.01	AVG			

Produkte
 Products




ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
 Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber
 Tel:+86-0755-26503290
 Fax:+86-0755-26503396

Job No.: PZ #2544	Polarization: Vertical
Standard: FCC Class B 3M Radiated	Power Source: AC 120V/60Hz
Test item: Radiation Test	Date: 14/11/26/
Temp.(C)/Hum.(%) 23 C / 48 %	Time:
EUT: WiFi Advisor	Engineer Signature: PEI
Mode: TX 5795MHz	Distance: 3m
Model: WFED-300AC	
Manufacturer: JDSU	

Note: 802.11ac VHT40---1TX (Non-Beamforming)



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	16696.884	9.29	40.85	50.14	74.00	-23.86	peak			
2	16696.884	-1.33	40.85	39.52	54.00	-14.48	AVG			

Produkte
 Products




ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
 Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber
 Tel:+86-0755-26503290
 Fax:+86-0755-26503396

Job No.: PZ #2393	Polarization: Vertical
Standard: FCC Class B 3M Radiated	Power Source: AC 120V/60Hz
Test item: Radiation Test	Date: 14/11/23/
Temp.(C)/Hum.(%) 23 C / 48 %	Time:
EUT: WiFi Advisor	Engineer Signature: PEI
Mode: TX 5755MHz	Distance: 3m
Model: WFED-300AC	
Manufacturer: JDSU	

Note: 802.11ac VHT40---1TX (Non-Beamforming)



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	26397.499	33.84	16.97	50.81	74.00	-23.19	peak			
2	26397.499	22.78	16.97	39.75	54.00	-14.25	AVG			

Produkte
 Products




ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
 Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber
 Tel:+86-0755-26503290
 Fax:+86-0755-26503396

Job No.: PZ #2394	Polarization: Horizontal
Standard: FCC Class B 3M Radiated	Power Source: AC 120V/60Hz
Test item: Radiation Test	Date: 14/11/23/
Temp.(C)/Hum.(%) 23 C / 48 %	Time:
EUT: WiFi Advisor	Engineer Signature: PEI
Mode: TX 5755MHz	Distance: 3m
Model: WFED-300AC	
Manufacturer: JDSU	

Note: 802.11ac VHT40---1TX (Non-Beamforming)



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	26021.678	34.33	16.50	50.83	74.00	-23.17	peak			
2	26021.678	22.46	16.50	38.96	54.00	-15.04	AVG			

Produkte
 Products




ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
 Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber
 Tel:+86-0755-26503290
 Fax:+86-0755-26503396

Job No.: PZ #2395	Polarization: Horizontal
Standard: FCC Class B 3M Radiated	Power Source: AC 120V/60Hz
Test item: Radiation Test	Date: 14/11/23/
Temp.(C)/Hum.(%) 23 C / 48 %	Time:
EUT: WiFi Advisor	Engineer Signature: PEI
Mode: TX 5795MHz	Distance: 3m
Model: WFED-300AC	
Manufacturer: JDSU	

Note: 802.11ac VHT40---1TX (Non-Beamforming)



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	25890.908	34.91	16.50	51.41	74.00	-22.59	peak			
2	25890.908	22.96	16.50	39.46	54.00	-14.54	AVG			

Produkte
 Products




ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
 Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber
 Tel:+86-0755-26503290
 Fax:+86-0755-26503396

Job No.: PZ #2396	Polarization: Vertical
Standard: FCC Class B 3M Radiated	Power Source: AC 120V/60Hz
Test item: Radiation Test	Date: 14/11/23/
Temp.(C)/Hum.(%) 23 C / 48 %	Time:
EUT: WiFi Advisor	Engineer Signature: PEI
Mode: TX 5795MHz	Distance: 3m
Model: WFED-300AC	
Manufacturer: JDSU	

Note: 802.11ac VHT40---1TX (Non-Beamforming)



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	26213.994	33.63	17.09	50.72	74.00	-23.28	peak			
2	26213.994	23.07	17.09	40.16	54.00	-13.84	AVG			

Radiated Emission


EUT Information

EUT Model Name: WiFi Advisor M/N: WFED-300AC
Operation mode: TX 5755MHz
Test Voltage: AC 120V/60Hz
Comment: JDSU

Common Information

Test Site: SMQ EMC Lab.
Environment Conditions:
Antenna Polarization: Horizontal
Operator Name:
Comment: 802.11ac VHT40---1TX (Non-Beamforming)

Copy of FCC Electric Field Strength 26.5-40GHz



Test

1 / 1

Radiated Emission


EUT Information

EUT Model Name:	WiFi Advisor M/N: WFED-300AC
Operation mode:	TX 5755MHz
Test Voltage:	AC 120V/60Hz
Comment:	JDSU

Common Information

Test Site:	SMQ EMC Lab.
Environment Conditions:	
Antenna Polarization:	Vertical
Operator Name:	
Comment:	802.11ac VHT40---1TX (Non-Beamforming)

Copy of FCC Electric Field Strength 26.5-40GHz



Radiated Emission


EUT Information

EUT Model Name:	WiFi Advisor M/N: WFED-300AC
Operation mode:	TX 5795MHz
Test Voltage:	AC 120V/60Hz
Comment:	JDSU

Common Information

Test Site:	SMQ EMC Lab.
Environment Conditions:	
Antenna Polarization:	Horizontal
Operator Name:	
Comment:	802.11ac VHT40---1TX (Non-Beamforming)

Copy of FCC Electric Field Strength 26.5-40GHz



Test

1 / 1

Radiated Emission


EUT Information

EUT Model Name:	WiFi Advisor M/N: WFED-300AC
Operation mode:	TX 5795MHz
Test Voltage:	AC 120V/60Hz
Comment:	JDSU

Common Information

Test Site:	SMQ EMC Lab.
Environment Conditions:	
Antenna Polarization:	Vertical
Operator Name:	
Comment:	802.11ac VHT40---1TX (Non-Beamforming)

Copy of FCC Electric Field Strength 26.5-40GHz



Produkte
 Products

802.11ac VHT40_2TX - Non Beamforming




ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
 Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber
 Tel:+86-0755-26503290
 Fax:+86-0755-26503396

Job No.: PZ #2256	Polarization: Vertical
Standard: FCC Class B 3M Radiated	Power Source: AC 120V/60Hz
Test item: Radiation Test	Date: 14/11/23/
Temp.(C)/Hum.(%) 23 C / 48 %	Time:
EUT: WiFi Advisor	Engineer Signature: PEI
Mode: TX 5755MHz	Distance: 3m
Model: WFED-300AC	
Manufacturer: JDSU	

Note: 802.11ac VHT40---2TX (Non-Beamforming)



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	35.0048	32.14	-10.42	21.72	40.00	-18.28	QP			
2	80.9274	36.13	-16.31	19.82	40.00	-20.18	QP			
3	151.0665	37.26	-15.14	22.12	43.50	-21.38	QP			

Produkte
 Products




ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
 Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber
 Tel:+86-0755-26503290
 Fax:+86-0755-26503396

Job No.: PZ #2257	Polarization: Horizontal
Standard: FCC Class B 3M Radiated	Power Source: AC 120V/60Hz
Test item: Radiation Test	Date: 14/11/23/
Temp.(C)/Hum.(%) 23 C / 48 %	Time:
EUT: WiFi Advisor	Engineer Signature: PEI
Mode: TX 5755MHz	Distance: 3m
Model: WFED-300AC	
Manufacturer: JDSU	

Note: 802.11ac VHT40---2TX (Non-Beamforming)



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	80.6441	38.06	-16.36	21.70	40.00	-18.30	QP			
2	122.4039	33.21	-13.43	19.78	43.50	-23.72	QP			
3	337.2155	41.98	-8.18	33.80	46.00	-12.20	QP			

Produkte
 Products




ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
 Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber
 Tel:+86-0755-26503290
 Fax:+86-0755-26503396

Job No.: PZ #2258	Polarization: Horizontal
Standard: FCC Class B 3M Radiated	Power Source: AC 120V/60Hz
Test item: Radiation Test	Date: 14/11/23/
Temp.(C)/Hum.(%) 23 C / 48 %	Time:
EUT: WiFi Advisor	Engineer Signature: PEI
Mode: TX 5795MHz	Distance: 3m
Model: WFED-300AC	
Manufacturer: JDSU	

Note: 802.11ac VHT40---2TX (Non-Beamforming)



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	80.9274	38.09	-16.31	21.78	40.00	-18.22	QP			
2	121.9753	32.38	-13.38	19.00	43.50	-24.50	QP			
3	334.8589	41.38	-8.26	33.12	46.00	-12.88	QP			

Produkte
 Products




ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
 Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber
 Tel:+86-0755-26503290
 Fax:+86-0755-26503396

Job No.: PZ #2259	Polarization: Vertical
Standard: FCC Class B 3M Radiated	Power Source: AC 120V/60Hz
Test item: Radiation Test	Date: 14/11/23/
Temp.(C)/Hum.(%) 23 C / 48 %	Time:
EUT: WiFi Advisor	Engineer Signature: PEI
Mode: TX 5795MHz	Distance: 3m
Model: WFED-300AC	
Manufacturer: JDSU	

Note: 802.11ac VHT40---2TX (Non-Beamforming)



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	35.1278	32.65	-10.45	22.20	40.00	-17.80	QP			
2	77.5926	36.38	-16.63	19.75	40.00	-20.25	QP			
3	150.5378	37.28	-15.15	22.13	43.50	-21.37	QP			

Produkte
 Products




ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
 Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber
 Tel:+86-0755-26503290
 Fax:+86-0755-26503396

Job No.: PZ #2545	Polarization: Vertical
Standard: FCC Class B 3M Radiated	Power Source: AC 120V/60Hz
Test item: Radiation Test	Date: 14/11/26/
Temp.(C)/Hum.(%) 23 C / 48 %	Time:
EUT: WiFi Advisor	Engineer Signature: PEI
Mode: TX 5755MHz	Distance: 3m
Model: WFED-300AC	
Manufacturer: JDSU	

Note: 802.11ac VHT40---2TX (Non-Beamforming)



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	17087.464	8.18	42.05	50.23	74.00	-23.77	peak			
2	17087.464	-1.29	42.05	40.76	54.00	-13.24	AVG			

Produkte
 Products




ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
 Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber
 Tel:+86-0755-26503290
 Fax:+86-0755-26503396

Job No.: PZ #2546	Polarization: Horizontal
Standard: FCC Class B 3M Radiated	Power Source: AC 120V/60Hz
Test item: Radiation Test	Date: 14/11/26/
Temp.(C)/Hum.(%) 23 C / 48 %	Time:
EUT: WiFi Advisor	Engineer Signature: PEI
Mode: TX 5755MHz	Distance: 3m
Model: WFED-300AC	
Manufacturer: JDSU	

Note: 802.11ac VHT40---2TX (Non-Beamforming)



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	16457.318	10.34	40.27	50.61	74.00	-23.39	peak			
2	16457.318	-0.62	40.27	39.65	54.00	-14.35	AVG			

Produkte
 Products




ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
 Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber
 Tel:+86-0755-26503290
 Fax:+86-0755-26503396

Job No.: PZ #2547	Polarization: Horizontal
Standard: FCC Class B 3M Radiated	Power Source: AC 120V/60Hz
Test item: Radiation Test	Date: 14/11/26/
Temp.(C)/Hum.(%) 23 C / 48 %	Time:
EUT: WiFi Advisor	Engineer Signature: PEI
Mode: TX 5795MHz	Distance: 3m
Model: WFED-300AC	
Manufacturer: JDSU	

Note: 802.11ac VHT40---2TX (Non-Beamforming)



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	16745.214	9.00	40.99	49.99	74.00	-24.01	peak			
2	16745.214	-1.47	40.99	39.52	54.00	-14.48	AVG			

Produkte
 Products




ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
 Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber
 Tel:+86-0755-26503290
 Fax:+86-0755-26503396

Job No.: PZ #2548	Polarization: Vertical
Standard: FCC Class B 3M Radiated	Power Source: AC 120V/60Hz
Test item: Radiation Test	Date: 14/11/26/
Temp.(C)/Hum.(%) 23 C / 48 %	Time:
EUT: WiFi Advisor	Engineer Signature: PEI
Mode: TX 5795MHz	Distance: 3m
Model: WFED-300AC	
Manufacturer: JDSU	

Note: 802.11ac VHT40---2TX (Non-Beamforming)



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	16939.937	8.67	41.53	50.20	74.00	-23.80	peak			
2	16939.937	-1.64	41.53	39.89	54.00	-14.11	AVG			

Produkte
 Products




ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
 Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber
 Tel:+86-0755-26503290
 Fax:+86-0755-26503396

Job No.: PZ #2397	Polarization: Vertical
Standard: FCC Class B 3M Radiated	Power Source: AC 120V/60Hz
Test item: Radiation Test	Date: 14/11/23/
Temp.(C)/Hum.(%) 23 C / 48 %	Time:
EUT: WiFi Advisor	Engineer Signature: PEI
Mode: TX 5755MHz	Distance: 3m
Model: WFED-300AC	
Manufacturer: JDSU	

Note: 802.11ac VHT40---2TX (Non-Beamforming)



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	26417.967	34.40	16.95	51.35	74.00	-22.65	peak			
2	26417.967	23.38	16.95	40.33	54.00	-13.67	AVG			

Produkte
 Products




ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
 Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber
 Tel:+86-0755-26503290
 Fax:+86-0755-26503396

Job No.: PZ #2398	Polarization: Horizontal
Standard: FCC Class B 3M Radiated	Power Source: AC 120V/60Hz
Test item: Radiation Test	Date: 14/11/23/
Temp.(C)/Hum.(%) 23 C / 48 %	Time:
EUT: WiFi Advisor	Engineer Signature: PEI
Mode: TX 5755MHz	Distance: 3m
Model: WFED-300AC	
Manufacturer: JDSU	

Note: 802.11ac VHT40---2TX (Non-Beamforming)



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	25910.983	35.12	16.50	51.62	74.00	-22.38	peak			
2	25910.983	23.25	16.50	39.75	54.00	-14.25	AVG			

Produkte
 Products




ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
 Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber
 Tel:+86-0755-26503290
 Fax:+86-0755-26503396

Job No.: PZ #2399	Polarization: Horizontal
Standard: FCC Class B 3M Radiated	Power Source: AC 120V/60Hz
Test item: Radiation Test	Date: 14/11/23/
Temp.(C)/Hum.(%) 23 C / 48 %	Time:
EUT: WiFi Advisor	Engineer Signature: PEI
Mode: TX 5795MHz	Distance: 3m
Model: WFED-300AC	
Manufacturer: JDSU	

Note: 802.11ac VHT40---2TX (Non-Beamforming)



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	26183.534	35.79	16.50	52.29	74.00	-21.71	peak			
2	26183.534	23.37	16.50	39.87	54.00	-14.13	AVG			

Produkte
 Products




ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
 Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber
 Tel:+86-0755-26503290
 Fax:+86-0755-26503396

Job No.: PZ #2400	Polarization: Vertical
Standard: FCC Class B 3M Radiated	Power Source: AC 120V/60Hz
Test item: Radiation Test	Date: 14/11/23/
Temp.(C)/Hum.(%) 23 C / 48 %	Time:
EUT: WiFi Advisor	Engineer Signature: PEI
Mode: TX 5795MHz	Distance: 3m
Model: WFED-300AC	
Manufacturer: JDSU	

Note: 802.11ac VHT40---2TX (Non-Beamforming)



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	25810.760	35.07	16.50	51.57	74.00	-22.43	peak			
2	25810.760	23.68	16.50	40.18	54.00	-13.82	AVG			

Test

1 / 1

Radiated Emission


EUT Information

EUT Model Name:	WiFi Advisor M/N: WFED-300AC
Operation mode:	TX 5755MHz
Test Voltage:	AC 120V/60Hz
Comment:	JDSU

Common Information

Test Site:	SMQ EMC Lab.
Environment Conditions:	
Antenna Polarization:	Horizontal
Operator Name:	
Comment:	802.11ac VHT40---2TX (Non-Beamforming)

Copy of FCC Electric Field Strength 26.5-40GHz



Test

1 / 1

Radiated Emission


EUT Information

EUT Model Name:	WiFi Advisor M/N: WFED-300AC
Operation mode:	TX 5755MHz
Test Voltage:	AC 120V/60Hz
Comment:	JDSU

Common Information

Test Site:	SMQ EMC Lab.
Environment Conditions:	
Antenna Polarization:	Vertical
Operator Name:	
Comment:	802.11ac VHT40---2TX (Non-Beamforming)

Copy of FCC Electric Field Strength 26.5-40GHz



Radiated Emission


EUT Information

EUT Model Name:	WiFi Advisor M/N: WFED-300AC
Operation mode:	TX 5795MHz
Test Voltage:	AC 120V/60Hz
Comment:	JDSU

Common Information

Test Site:	SMQ EMC Lab.
Environment Conditions:	
Antenna Polarization:	Horizontal
Operator Name:	
Comment:	802.11ac VHT40---2TX (Non-Beamforming)

Copy of FCC Electric Field Strength 26.5-40GHz



Test

1 / 1

Radiated Emission


EUT Information

EUT Model Name: WiFi Advisor M/N: WFED-300AC
Operation mode: TX 5795MHz
Test Voltage: AC 120V/60Hz
Comment: JDSU

Common Information

Test Site: SMQ EMC Lab.
Environment Conditions:
Antenna Polarization: Vertical
Operator Name:
Comment: 802.11ac VHT40---2TX (Non-Beamforming)

Copy of FCC Electric Field Strength 26.5-40GHz



Produkte
 Products

802.11ac VHT40_3TX - Non Beamforming




ACCURATE TECHNOLOGY CO., LTD.
 F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
 Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber
 Tel:+86-0755-26503290
 Fax:+86-0755-26503396

Job No.: PZ #2260	Polarization: Vertical
Standard: FCC Class B 3M Radiated	Power Source: AC 120V/60Hz
Test item: Radiation Test	Date: 14/11/23/
Temp.(C)/Hum.(%) 23 C / 48 %	Time:
EUT: WiFi Advisor	Engineer Signature: PEI
Mode: TX 5755MHz	Distance: 3m
Model: WFED-300AC	
Manufacturer: JDSU	

Note: 802.11ac VHT40---3TX (Non-Beamforming)



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	35.1278	32.29	-10.45	21.84	40.00	-18.16	QP			
2	78.6888	36.84	-16.58	20.26	40.00	-19.74	QP			
3	151.0665	36.59	-15.14	21.45	43.50	-22.05	QP			

Produkte
 Products




ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
 Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber
 Tel:+86-0755-26503290
 Fax:+86-0755-26503396

Job No.: PZ #2261	Polarization: Horizontal
Standard: FCC Class B 3M Radiated	Power Source: AC 120V/60Hz
Test item: Radiation Test	Date: 14/11/23/
Temp.(C)/Hum.(%) 23 C / 48 %	Time:
EUT: WiFi Advisor	Engineer Signature: PEI
Mode: TX 5755MHz	Distance: 3m
Model: WFED-300AC	
Manufacturer: JDSU	

Note: 802.11ac VHT40---3TX (Non-Beamforming)



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	80.9274	37.89	-16.31	21.58	40.00	-18.42	QP			
2	121.1230	33.78	-13.28	20.50	43.50	-23.00	QP			
3	336.0351	41.86	-8.23	33.63	46.00	-12.37	QP			

Produkte
 Products




ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
 Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber
 Tel:+86-0755-26503290
 Fax:+86-0755-26503396

Job No.: PZ #2262	Polarization: Horizontal
Standard: FCC Class B 3M Radiated	Power Source: AC 120V/60Hz
Test item: Radiation Test	Date: 14/11/23/
Temp.(C)/Hum.(%) 23 C / 48 %	Time:
EUT: WiFi Advisor	Engineer Signature: PEI
Mode: TX 5795MHz	Distance: 3m
Model: WFED-300AC	
Manufacturer: JDSU	

Note: 802.11ac VHT40---3TX (Non-Beamforming)



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	80.6440	38.01	-16.36	21.65	40.00	-18.35	QP			
2	119.4360	33.69	-13.15	20.54	43.50	-22.96	QP			
3	333.6865	41.28	-8.28	33.00	46.00	-13.00	QP			

Produkte
 Products




ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
 Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber
 Tel:+86-0755-26503290
 Fax:+86-0755-26503396

Job No.: PZ #2263	Polarization: Vertical
Standard: FCC Class B 3M Radiated	Power Source: AC 120V/60Hz
Test item: Radiation Test	Date: 14/11/23/
Temp.(C)/Hum.(%) 23 C / 48 %	Time:
EUT: WiFi Advisor	Engineer Signature: PEI
Mode: TX 5795MHz	Distance: 3m
Model: WFED-300AC	
Manufacturer: JDSU	

Note: 802.11ac VHT40---3TX (Non-Beamforming)



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	34.8823	32.53	-10.41	22.12	40.00	-17.88	QP			
2	78.9651	36.19	-16.57	19.62	40.00	-20.38	QP			
3	151.0665	37.28	-15.14	22.14	43.50	-21.36	QP			

Produkte
 Products




ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
 Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber
 Tel:+86-0755-26503290
 Fax:+86-0755-26503396

Job No.: PZ #2549	Polarization: Vertical
Standard: FCC Class B 3M Radiated	Power Source: AC 120V/60Hz
Test item: Radiation Test	Date: 14/11/26/
Temp.(C)/Hum.(%) 23 C / 48 %	Time:
EUT: WiFi Advisor	Engineer Signature: PEI
Mode: TX 5755MHz	Distance: 3m
Model: WFED-300AC	
Manufacturer: JDSU	

Note: 802.11ac VHT40---3TX (Non-Beamforming)



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	16504.954	9.76	40.31	50.07	74.00	-23.93	peak			
2	16504.954	-1.48	40.31	38.83	54.00	-15.17	AVG			

Produkte
 Products




ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
 Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber
 Tel:+86-0755-26503290
 Fax:+86-0755-26503396

Job No.: PZ #2550	Polarization: Horizontal
Standard: FCC Class B 3M Radiated	Power Source: AC 120V/60Hz
Test item: Radiation Test	Date: 14/11/26/
Temp.(C)/Hum.(%) 23 C / 48 %	Time:
EUT: WiFi Advisor	Engineer Signature: PEI
Mode: TX 5755MHz	Distance: 3m
Model: WFED-300AC	
Manufacturer: JDSU	

Note: 802.11ac VHT40---3TX (Non-Beamforming)



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	16842.294	9.06	41.26	50.32	74.00	-23.68	peak			
2	16842.294	-1.21	41.26	40.05	54.00	-13.95	AVG			