

Test

1 / 1

Radiated Emission


EUT Information

EUT Model Name:	WiFi Advisor M/N: WFED-300AC
Operation mode:	TX 5825MHz
Test Voltage:	AC 120V/60Hz
Comment:	JDSU

Common Information

Test Site:	SMQ EMC Lab.
Environment Conditions:	
Antenna Polarization:	Horizontal
Operator Name:	
Comment:	802.11an HT20---3TX (Beamforming)

Copy of FCC Electric Field Strength 26.5-40GHz



Test

1 / 1

Radiated Emission


EUT Information

EUT Model Name:	WiFi Advisor M/N: WFED-300AC
Operation mode:	TX 5825MHz
Test Voltage:	AC 120V/60Hz
Comment:	JDSU

Common Information

Test Site:	SMQ EMC Lab.
Environment Conditions:	
Antenna Polarization:	Vertical
Operator Name:	
Comment:	802.11n HT20---3TX (Beamforming)

Copy of FCC Electric Field Strength 26.5-40GHz



2014-11-21

Produkte
 Products




ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
 Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber
 Tel:+86-0755-26503290
 Fax:+86-0755-26503396

Job No.: PZ #2286	Polarization: Horizontal
Standard: FCC Class B 3M Radiated	Power Source: AC 120V/60Hz
Test item: Radiation Test	Date: 14/11/23/
Temp.(C)/Hum.(%) 23 C / 48 %	Time:
EUT: WiFi Advisor	Engineer Signature: PEI
Mode: TX 5755MHz	Distance: 3m
Model: WFED-300AC	
Manufacturer: JDSU	

Note: 802.11an HT40---2TX (Beamforming)



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	80.6441	38.15	-16.36	21.79	40.00	-18.21	QP			
2	118.6013	31.78	-13.14	18.64	43.50	-24.86	QP			
3	336.0351	40.79	-8.23	32.56	46.00	-13.44	QP			

Produkte
 Products




ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
 Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber
 Tel:+86-0755-26503290
 Fax:+86-0755-26503396

Job No.: PZ #2287	Polarization: Vertical
Standard: FCC Class B 3M Radiated	Power Source: AC 120V/60Hz
Test item: Radiation Test	Date: 14/11/23/
Temp.(C)/Hum.(%) 23 C / 48 %	Time:
EUT: WiFi Advisor	Engineer Signature: PEI
Mode: TX 5755MHz	Distance: 3m
Model: WFED-300AC	
Manufacturer: JDSU	

Note: 802.11an HT40---2TX (Beamforming)



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	35.0048	32.54	-10.42	22.12	40.00	-17.88	QP			
2	80.0806	35.87	-16.49	19.38	40.00	-20.62	QP			
3	150.5378	37.44	-15.15	22.29	43.50	-21.21	QP			

Produkte
 Products




ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
 Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber
 Tel:+86-0755-26503290
 Fax:+86-0755-26503396

Job No.: PZ #2288	Polarization: Vertical
Standard: FCC Class B 3M Radiated	Power Source: AC 120V/60Hz
Test item: Radiation Test	Date: 14/11/23/
Temp.(C)/Hum.(%) 23 C / 48 %	Time:
EUT: WiFi Advisor	Engineer Signature: PEI
Mode: TX 5795MHz	Distance: 3m
Model: WFED-300AC	
Manufacturer: JDSU	

Note: 802.11an HT40---2TX (Beamforming)



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	35.1278	32.34	-10.45	21.89	40.00	-18.11	QP			
2	78.6888	36.06	-16.58	19.48	40.00	-20.52	QP			
3	151.0665	37.51	-15.14	22.37	43.50	-21.13	QP			

Produkte
 Products




ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
 Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber
 Tel:+86-0755-26503290
 Fax:+86-0755-26503396

Job No.: PZ #2289	Polarization: Horizontal
Standard: FCC Class B 3M Radiated	Power Source: AC 120V/60Hz
Test item: Radiation Test	Date: 14/11/23/
Temp.(C)/Hum.(%) 23 C / 48 %	Time:
EUT: WiFi Advisor	Engineer Signature: PEI
Mode: TX 5795MHz	Distance: 3m
Model: WFED-300AC	
Manufacturer: JDSU	

Note: 802.11an HT40---2TX (Beamforming)



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	80.6441	37.79	-16.36	21.43	40.00	-18.57	QP			
2	120.2766	33.32	-13.18	20.14	43.50	-23.36	QP			
3	336.0351	41.67	-8.23	33.44	46.00	-12.56	QP			

Produkte
 Products




ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
 Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber
 Tel:+86-0755-26503290
 Fax:+86-0755-26503396

Job No.: PYH2015 #169	Polarization: Vertical
Standard: FCC Class B 3M Radiated	Power Source: AC 120V/60Hz
Test item: Radiation Test	Date: 14/11/28/
Temp.(C)/Hum.(%) 23 C / 48 %	Time:
EUT: WiFi Advisor	Engineer Signature: PEI
Mode: TX 5755MHz	Distance: 3m
Model: WFED-300AC	
Manufacturer: JDSU	

Note: 802.11an HT40---2TX (Beamforming)



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	16504.954	10.05	40.31	50.36	74.00	-23.64	peak			
2	16504.954	-1.28	40.31	39.03	54.00	-14.97	AVG			

Produkte
 Products




ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
 Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber
 Tel:+86-0755-26503290
 Fax:+86-0755-26503396

Job No.: PYH2015 #170	Polarization: Horizontal
Standard: FCC Class B 3M Radiated	Power Source: AC 120V/60Hz
Test item: Radiation Test	Date: 14/11/28/
Temp.(C)/Hum.(%) 23 C / 48 %	Time:
EUT: WiFi Advisor	Engineer Signature: PEI
Mode: TX 5755MHz	Distance: 3m
Model: WFED-300AC	
Manufacturer: JDSU	

Note: 802.11an HT40---2TX (Beamforming)



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	16034.728	10.06	40.02	50.08	74.00	-23.92	peak			
2	16034.728	-0.81	40.02	39.21	54.00	-14.79	AVG			

Produkte
 Products




ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
 Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber
 Tel:+86-0755-26503290
 Fax:+86-0755-26503396

Job No.: PYH2015 #171	Polarization: Horizontal
Standard: FCC Class B 3M Radiated	Power Source: AC 120V/60Hz
Test item: Radiation Test	Date: 14/11/28/
Temp.(C)/Hum.(%) 23 C / 48 %	Time:
EUT: WiFi Advisor	Engineer Signature: PEI
Mode: TX 5795MHz	Distance: 3m
Model: WFED-300AC	
Manufacturer: JDSU	

Note: 802.11an HT40---2TX (Beamforming)



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	16552.729	9.99	40.45	50.44	74.00	-23.56	peak			
2	16552.729	-1.30	40.45	39.15	54.00	-14.85	AVG			

Produkte
 Products




ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
 Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber
 Tel:+86-0755-26503290
 Fax:+86-0755-26503396

Job No.: PYH2015 #172	Polarization: Vertical
Standard: FCC Class B 3M Radiated	Power Source: AC 120V/60Hz
Test item: Radiation Test	Date: 14/11/28/
Temp.(C)/Hum.(%) 23 C / 48 %	Time:
EUT: WiFi Advisor	Engineer Signature: PEI
Mode: TX 5795MHz	Distance: 3m
Model: WFED-300AC	
Manufacturer: JDSU	

Note: 802.11an HT40---2TX (Beamforming)



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	16174.372	10.39	40.10	50.49	74.00	-23.51	peak			
2	16174.372	-1.40	40.10	38.70	54.00	-15.30	AVG			

Produkte
 Products




ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
 Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber
 Tel:+86-0755-26503290
 Fax:+86-0755-26503396

Job No.: PZ #2424	Polarization: Horizontal
Standard: FCC Class B 3M Radiated	Power Source: AC 120V/60Hz
Test item: Radiation Test	Date: 14/11/23/
Temp.(C)/Hum.(%) 23 C / 48 %	Time:
EUT: WiFi Advisor	Engineer Signature: PEI
Mode: TX 5755MHz	Distance: 3m
Model: WFED-300AC	
Manufacturer: JDSU	

Note: 802.11an HT40---2TX (Beamforming)



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	26264.839	35.65	16.50	52.15	74.00	-21.85	peak			
2	26264.839	23.41	16.50	39.91	54.00	-14.09	AVG			

Produkte
 Products




ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
 Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber
 Tel:+86-0755-26503290
 Fax:+86-0755-26503396

Job No.: PZ #2425	Polarization: Vertical
Standard: FCC Class B 3M Radiated	Power Source: AC 120V/60Hz
Test item: Radiation Test	Date: 14/11/23/
Temp.(C)/Hum.(%) 23 C / 48 %	Time:
EUT: WiFi Advisor	Engineer Signature: PEI
Mode: TX 5755MHz	Distance: 3m
Model: WFED-300AC	
Manufacturer: JDSU	

Note: 802.11an HT40---2TX (Beamforming)



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	25860.823	33.93	17.33	51.26	74.00	-22.74	peak			
2	25860.823	22.45	17.33	39.78	54.00	-14.22	AVG			

Produkte
 Products




ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
 Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber
 Tel:+86-0755-26503290
 Fax:+86-0755-26503396

Job No.: PZ #2426	Polarization: Vertical
Standard: FCC Class B 3M Radiated	Power Source: AC 120V/60Hz
Test item: Radiation Test	Date: 14/11/23/
Temp.(C)/Hum.(%) 23 C / 48 %	Time:
EUT: WiFi Advisor	Engineer Signature: PEI
Mode: TX 5795MHz	Distance: 3m
Model: WFED-300AC	
Manufacturer: JDSU	

Note: 802.11an HT40---2TX (Beamforming)



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	26264.839	34.55	17.06	51.61	74.00	-22.39	peak			
2	26264.839	23.35	17.06	40.41	54.00	-13.59	AVG			

Produkte
 Products




ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
 Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber
 Tel:+86-0755-26503290
 Fax:+86-0755-26503396

Job No.: PZ #2427	Polarization: Horizontal
Standard: FCC Class B 3M Radiated	Power Source: AC 120V/60Hz
Test item: Radiation Test	Date: 14/11/23/
Temp.(C)/Hum.(%) 23 C / 48 %	Time:
EUT: WiFi Advisor	Engineer Signature: PEI
Mode: TX 5795MHz	Distance: 3m
Model: WFED-300AC	
Manufacturer: JDSU	

Note: 802.11an HT40---2TX (Beamforming)



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	26102.481	35.20	16.50	51.70	74.00	-22.30	peak			
2	26102.481	23.46	16.50	39.96	54.00	-14.04	AVG			

Test

1 / 1

Radiated Emission


EUT Information

EUT Model Name: WiFi Advisor M/N: WFED-300AC
Operation mode: TX 5755MHz
Test Voltage: AC 120V/60Hz
Comment: JDSU

Common Information

Test Site: SMQ EMC Lab.
Environment Conditions:
Antenna Polarization: Horizontal
Operator Name:
Comment: 802.11an HT40---2TX (Beamforming)

Copy of FCC Electric Field Strength 26.5-40GHz



Test

1 / 1

Radiated Emission


EUT Information

EUT Model Name:	WiFi Advisor M/N: WFED-300AC
Operation mode:	TX 5755MHz
Test Voltage:	AC 120V/60Hz
Comment:	JDSU

Common Information

Test Site:	SMQ EMC Lab.
Environment Conditions:	
Antenna Polarization:	Vertical
Operator Name:	
Comment:	802.11an HT40---2TX (Beamforming)

Copy of FCC Electric Field Strength 26.5-40GHz



Test

1 / 1

Radiated Emission


EUT Information

EUT Model Name:	WiFi Advisor M/N: WFED-300AC
Operation mode:	TX 5795MHz
Test Voltage:	AC 120V/60Hz
Comment:	JDSU

Common Information

Test Site:	SMQ EMC Lab.
Environment Conditions:	
Antenna Polarization:	Horizontal
Operator Name:	
Comment:	802.11an HT40---2TX (Beamforming)

Copy of FCC Electric Field Strength 26.5-40GHz



Test

1 / 1

Radiated Emission


EUT Information

EUT Model Name:	WiFi Advisor M/N: WFED-300AC
Operation mode:	TX 5795MHz
Test Voltage:	AC 120V/60Hz
Comment:	JDSU

Common Information

Test Site:	SMQ EMC Lab.
Environment Conditions:	
Antenna Polarization:	Vertical
Operator Name:	
Comment:	802.11an HT40---2TX (Beamforming)

Copy of FCC Electric Field Strength 26.5-40GHz



Produkte
 Products

802.11n HT40_3TX - Beamforming




ACCURATE TECHNOLOGY CO., LTD.
 F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
 Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber
 Tel:+86-0755-26503290
 Fax:+86-0755-26503396

Job No.: PZ #2290	Polarization: Horizontal
Standard: FCC Class B 3M Radiated	Power Source: AC 120V/60Hz
Test item: Radiation Test	Date: 14/11/23/
Temp.(C)/Hum.(%) 23 C / 48 %	Time:
EUT: WiFi Advisor	Engineer Signature: PEI
Mode: TX 5755MHz	Distance: 3m
Model: WFED-300AC	
Manufacturer: JDSU	

Note: 802.11an HT40---3TX (Beamforming)



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	78.9651	37.89	-16.57	21.32	40.00	-18.68	QP			
2	123.6984	33.87	-13.58	20.29	43.50	-23.21	QP			
3	337.2155	41.26	-8.18	33.08	46.00	-12.92	QP			

Produkte
 Products




ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
 Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber
 Tel:+86-0755-26503290
 Fax:+86-0755-26503396

Job No.: PZ #2291	Polarization: Vertical
Standard: FCC Class B 3M Radiated	Power Source: AC 120V/60Hz
Test item: Radiation Test	Date: 14/11/23/
Temp.(C)/Hum.(%) 23 C / 48 %	Time:
EUT: WiFi Advisor	Engineer Signature: PEI
Mode: TX 5755MHz	Distance: 3m
Model: WFED-300AC	
Manufacturer: JDSU	

Note: 802.11an HT40---3TX (Beamforming)



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	35.0048	32.36	-10.42	21.94	40.00	-18.06	QP			
2	78.6888	36.37	-16.58	19.79	40.00	-20.21	QP			
3	150.5378	37.72	-15.15	22.57	43.50	-20.93	QP			

Produkte
 Products




ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
 Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber
 Tel:+86-0755-26503290
 Fax:+86-0755-26503396

Job No.: PZ #2292	Polarization: Vertical
Standard: FCC Class B 3M Radiated	Power Source: AC 120V/60Hz
Test item: Radiation Test	Date: 14/11/23/
Temp.(C)/Hum.(%) 23 C / 48 %	Time:
EUT: WiFi Advisor	Engineer Signature: PEI
Mode: TX 5795MHz	Distance: 3m
Model: WFED-300AC	
Manufacturer: JDSU	

Note: 802.11an HT40---3TX (Beamforming)



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	34.8823	31.96	-10.41	21.55	40.00	-18.45	QP			
2	80.9274	35.80	-16.31	19.49	40.00	-20.51	QP			
3	151.0665	37.61	-15.14	22.47	43.50	-21.03	QP			

Produkte
 Products




ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
 Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber
 Tel:+86-0755-26503290
 Fax:+86-0755-26503396

Job No.: PZ #2293	Polarization: Horizontal
Standard: FCC Class B 3M Radiated	Power Source: AC 120V/60Hz
Test item: Radiation Test	Date: 14/11/23/
Temp.(C)/Hum.(%) 23 C / 48 %	Time:
EUT: WiFi Advisor	Engineer Signature: PEI
Mode: TX 5795MHz	Distance: 3m
Model: WFED-300AC	
Manufacturer: JDSU	

Note: 802.11an HT40---3TX (Beamforming)



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	82.3588	36.55	-15.98	20.57	40.00	-19.43	QP			
2	120.2766	34.40	-13.18	21.22	43.50	-22.28	QP			
3	336.0350	41.72	-8.23	33.49	46.00	-12.51	QP			

Produkte
 Products




ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
 Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber
 Tel:+86-0755-26503290
 Fax:+86-0755-26503396

Job No.: PYH2015 #173	Polarization: Vertical
Standard: FCC Class B 3M Radiated	Power Source: AC 120V/60Hz
Test item: Radiation Test	Date: 14/11/28/
Temp.(C)/Hum.(%) 23 C / 48 %	Time:
EUT: WiFi Advisor	Engineer Signature: PEI
Mode: TX 5755MHz	Distance: 3m
Model: WFED-300AC	
Manufacturer: JDSU	

Note: 802.11an HT40---3TX (Beamforming)



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	16315.231	10.43	40.19	50.62	54.00	-3.38	peak			
2	16315.231	-0.93	40.19	39.26	54.00	-14.74	AVG			

Produkte
 Products




ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
 Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber
 Tel:+86-0755-26503290
 Fax:+86-0755-26503396

Job No.: PYH2015 #174	Polarization: Horizontal
Standard: FCC Class B 3M Radiated	Power Source: AC 120V/60Hz
Test item: Radiation Test	Date: 14/11/28/
Temp.(C)/Hum.(%) 23 C / 48 %	Time:
EUT: WiFi Advisor	Engineer Signature: PEI
Mode: TX 5755MHz	Distance: 3m
Model: WFED-300AC	
Manufacturer: JDSU	

Note: 802.11an HT40---3TX (Beamforming)



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	16268.142	9.96	40.16	50.12	54.00	-3.88	peak			
2	16268.142	-1.20	40.16	38.96	54.00	-15.04	AVG			

Produkte
 Products




ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
 Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber
 Tel:+86-0755-26503290
 Fax:+86-0755-26503396

Job No.: PYH2015 #175	Polarization: Horizontal
Standard: FCC Class B 3M Radiated	Power Source: AC 120V/60Hz
Test item: Radiation Test	Date: 14/11/28/
Temp.(C)/Hum.(%) 23 C / 48 %	Time:
EUT: WiFi Advisor	Engineer Signature: PEI
Mode: TX 5795MHz	Distance: 3m
Model: WFED-300AC	
Manufacturer: JDSU	

Note: 802.11an HT40---3TX (Beamforming)



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	16034.728	10.12	40.02	50.14	54.00	-3.86	peak			
2	16034.728	-0.85	40.02	39.17	54.00	-14.83	AVG			

Produkte
 Products




ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
 Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber
 Tel:+86-0755-26503290
 Fax:+86-0755-26503396

Job No.: PYH2015 #176	Polarization: Vertical
Standard: FCC Class B 3M Radiated	Power Source: AC 120V/60Hz
Test item: Radiation Test	Date: 14/11/28/
Temp.(C)/Hum.(%) 23 C / 48 %	Time:
EUT: WiFi Advisor	Engineer Signature: PEI
Mode: TX 5795MHz	Distance: 3m
Model: WFED-300AC	
Manufacturer: JDSU	

Note: 802.11an HT40---3TX (Beamforming)



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	16842.294	9.05	41.26	50.31	54.00	-3.69	peak			
2	16842.294	-1.06	41.26	40.20	54.00	-13.80	AVG			

Produkte
 Products




ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
 Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber
 Tel:+86-0755-26503290
 Fax:+86-0755-26503396

Job No.: PZ #2428	Polarization: Horizontal
Standard: FCC Class B 3M Radiated	Power Source: AC 120V/60Hz
Test item: Radiation Test	Date: 14/11/23/
Temp.(C)/Hum.(%) 23 C / 48 %	Time:
EUT: WiFi Advisor	Engineer Signature: PEI
Mode: TX 5755MHz	Distance: 3m
Model: WFED-300AC	
Manufacturer: JDSU	

Note: 802.11an HT40---3TX (Beamforming)



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	26315.783	36.40	16.50	52.90	54.00	-1.10	peak			
2	26315.783	23.12	16.50	39.62	54.00	-14.38	AVG			

Produkte
 Products




ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
 Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber
 Tel:+86-0755-26503290
 Fax:+86-0755-26503396

Job No.: PZ #2429	Polarization: Vertical
Standard: FCC Class B 3M Radiated	Power Source: AC 120V/60Hz
Test item: Radiation Test	Date: 14/11/23/
Temp.(C)/Hum.(%) 23 C / 48 %	Time:
EUT: WiFi Advisor	Engineer Signature: PEI
Mode: TX 5755MHz	Distance: 3m
Model: WFED-300AC	
Manufacturer: JDSU	

Note: 802.11an HT40---3TX (Beamforming)



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	25981.371	34.24	17.25	51.49	54.00	-2.51	peak			
2	25981.371	22.41	17.25	39.66	54.00	-14.34	AVG			

Produkte
 Products




ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
 Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber
 Tel:+86-0755-26503290
 Fax:+86-0755-26503396

Job No.: PZ #2430	Polarization: Vertical
Standard: FCC Class B 3M Radiated	Power Source: AC 120V/60Hz
Test item: Radiation Test	Date: 14/11/23/
Temp.(C)/Hum.(%) 23 C / 48 %	Time:
EUT: WiFi Advisor	Engineer Signature: PEI
Mode: TX 5795MHz	Distance: 3m
Model: WFED-300AC	
Manufacturer: JDSU	

Note: 802.11an HT40---3TX (Beamforming)



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	25981.371	34.43	17.25	51.68	54.00	-2.32	peak			
2	25981.371	22.82	17.25	40.07	54.00	-13.93	AVG			

Produkte
 Products




ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
 Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber
 Tel:+86-0755-26503290
 Fax:+86-0755-26503396

Job No.: PZ #2431	Polarization: Horizontal
Standard: FCC Class B 3M Radiated	Power Source: AC 120V/60Hz
Test item: Radiation Test	Date: 14/11/23/
Temp.(C)/Hum.(%) 23 C / 48 %	Time:
EUT: WiFi Advisor	Engineer Signature: PEI
Mode: TX 5795MHz	Distance: 3m
Model: WFED-300AC	
Manufacturer: JDSU	

Note: 802.11an HT40---3TX (Beamforming)



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	26062.048	34.63	16.50	51.13	54.00	-2.87	peak			
2	26062.048	22.77	16.50	39.27	54.00	-14.73	AVG			

Radiated Emission


EUT Information

EUT Model Name:	WiFi Advisor M/N: WFED-300AC
Operation mode:	TX 5755MHz
Test Voltage:	AC 120V/60Hz
Comment:	JDSU

Common Information

Test Site:	SMQ EMC Lab.
Environment Conditions:	
Antenna Polarization:	Horizontal
Operator Name:	
Comment:	802.11an HT40---3TX (Beamforming)

Copy of FCC Electric Field Strength 26.5-40GHz



Radiated Emission


EUT Information

EUT Model Name: WiFi Advisor M/N: WFED-300AC
Operation mode: TX 5755MHz
Test Voltage: AC 120V/60Hz
Comment: JDSU

Common Information

Test Site: SMQ EMC Lab.
Environment Conditions:
Antenna Polarization: Vertical
Operator Name:
Comment: 802.11an HT40---3TX (Beamforming)

Copy of FCC Electric Field Strength 26.5-40GHz



Radiated Emission


EUT Information

EUT Model Name:	WiFi Advisor M/N: WFED-300AC
Operation mode:	TX 5795MHz
Test Voltage:	AC 120V/60Hz
Comment:	JDSU

Common Information

Test Site:	SMQ EMC Lab.
Environment Conditions:	
Antenna Polarization:	Horizontal
Operator Name:	
Comment:	802.11an HT40---3TX (Beamforming)

Copy of FCC Electric Field Strength 26.5-40GHz



Test

1 / 1

Radiated Emission


EUT Information

EUT Model Name:	WiFi Advisor M/N: WFED-300AC
Operation mode:	TX 5795MHz
Test Voltage:	AC 120V/60Hz
Comment:	JDSU

Common Information

Test Site:	SMQ EMC Lab.
Environment Conditions:	
Antenna Polarization:	Vertical
Operator Name:	
Comment:	802.11an HT40---3TX (Beamforming)

Copy of FCC Electric Field Strength 26.5-40GHz



Produkte
 Products

802.11ac VHT20_2TX - Beamforming




ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
 Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber
 Tel:+86-0755-26503290
 Fax:+86-0755-26503396

Job No.: PZ #2300	Polarization: Vertical
Standard: FCC Class B 3M Radiated	Power Source: AC 120V/60Hz
Test item: Radiation Test	Date: 14/11/23/
Temp.(C)/Hum.(%) 23 C / 48 %	Time:
EUT: WiFi Advisor	Engineer Signature: PEI
Mode: TX 5745MHz	Distance: 3m
Model: WFED-300AC	
Manufacturer: JDSU	

Note: 802.11ac VHT20---2TX (Beamforming)



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	34.8823	32.23	-10.41	21.82	40.00	-18.18	QP			
2	78.1389	36.17	-16.61	19.56	40.00	-20.44	QP			
3	151.0665	37.89	-15.14	22.75	43.50	-20.75	QP			

Produkte
 Products




ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
 Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber
 Tel:+86-0755-26503290
 Fax:+86-0755-26503396

Job No.: PZ #2301	Polarization: Horizontal
Standard: FCC Class B 3M Radiated	Power Source: AC 120V/60Hz
Test item: Radiation Test	Date: 14/11/23/
Temp.(C)/Hum.(%) 23 C / 48 %	Time:
EUT: WiFi Advisor	Engineer Signature: PEI
Mode: TX 5745MHz	Distance: 3m
Model: WFED-300AC	
Manufacturer: JDSU	

Note: 802.11ac VHT20---2TX (Beamforming)



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	80.6441	36.58	-16.36	20.22	40.00	-19.78	QP			
2	81.7832	36.24	-16.12	20.12	40.00	-19.88	QP			
3	336.0351	40.25	-8.23	32.02	46.00	-13.98	QP			

Produkte
 Products




ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
 Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber
 Tel:+86-0755-26503290
 Fax:+86-0755-26503396

Job No.: PZ #2302	Polarization: Horizontal
Standard: FCC Class B 3M Radiated	Power Source: AC 120V/60Hz
Test item: Radiation Test	Date: 14/11/23/
Temp.(C)/Hum.(%) 23 C / 48 %	Time:
EUT: WiFi Advisor	Engineer Signature: PEI
Mode: TX 5785MHz	Distance: 3m
Model: WFED-300AC	
Manufacturer: JDSU	

Note: 802.11ac VHT20---2TX (Beamforming)



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	78.1389	38.70	-16.61	22.09	40.00	-17.91	QP			
2	242.5252	32.08	-10.82	21.26	46.00	-24.74	QP			
3	340.7817	41.22	-8.05	33.17	46.00	-12.83	QP			

Produkte
 Products




ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
 Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber
 Tel:+86-0755-26503290
 Fax:+86-0755-26503396

Job No.: PZ #2303	Polarization: Vertical
Standard: FCC Class B 3M Radiated	Power Source: AC 120V/60Hz
Test item: Radiation Test	Date: 14/11/23/
Temp.(C)/Hum.(%) 23 C / 48 %	Time:
EUT: WiFi Advisor	Engineer Signature: PEI
Mode: TX 5785MHz	Distance: 3m
Model: WFED-300AC	
Manufacturer: JDSU	

Note: 802.11ac VHT20---2TX (Beamforming)



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	35.0048	32.04	-10.42	21.62	40.00	-18.38	QP			
2	78.9651	36.61	-16.57	20.04	40.00	-19.96	QP			
3	151.0665	36.51	-15.14	21.37	43.50	-22.13	QP			

Produkte
 Products




ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
 Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber
 Tel:+86-0755-26503290
 Fax:+86-0755-26503396

Job No.: PZ #2304	Polarization: Vertical
Standard: FCC Class B 3M Radiated	Power Source: AC 120V/60Hz
Test item: Radiation Test	Date: 14/11/23/
Temp.(C)/Hum.(%) 23 C / 48 %	Time:
EUT: WiFi Advisor	Engineer Signature: PEI
Mode: TX 5825MHz	Distance: 3m
Model: WFED-300AC	
Manufacturer: JDSU	

Note: 802.11ac VHT20---2TX (Beamforming)



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	35.1278	30.97	-10.45	20.52	40.00	-19.48	QP			
2	78.9651	35.95	-16.57	19.38	40.00	-20.62	QP			
3	150.5378	36.30	-15.15	21.15	43.50	-22.35	QP			

Produkte
 Products




ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
 Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber
 Tel:+86-0755-26503290
 Fax:+86-0755-26503396

Job No.: PZ #2305	Polarization: Horizontal
Standard: FCC Class B 3M Radiated	Power Source: AC 120V/60Hz
Test item: Radiation Test	Date: 14/11/23/
Temp.(C)/Hum.(%) 23 C / 48 %	Time:
EUT: WiFi Advisor	Engineer Signature: PEI
Mode: TX 5825MHz	Distance: 3m
Model: WFED-300AC	
Manufacturer: JDSU	

Note: 802.11ac VHT20---2TX (Beamforming)



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	78.9651	38.12	-16.57	21.55	40.00	-18.45	QP			
2	120.2766	33.21	-13.18	20.03	43.50	-23.47	QP			
3	336.0351	42.13	-8.23	33.90	46.00	-12.10	QP			