

RF EXPOSURE EVALUATION REPORT



Issued to

Brightstar Corporation

For

Fixed Wireless Phone

Model Name : FXP871
Trade Name : Motorola/AVVIO
Brand Name : Motorola/AVVIO
FCC ID : WVB-FXP871
Standard : 47CFR 2.1091
KDB 447498 D01 General RF
Exposure Guidance v05r01
Test date : 2013-12-26
Issue date : 2014-1-22

by

Shenzhen Morlab Communications Technology Co., Ltd.

FL.3, Building A, FeiYang Science Park, No.8 LongChang Road,Block 67, BaoAn District,
ShenZhen, GuangDong Province, P. R. China 518101

Tested by

Zou Jian
Zou Jian
(Test Engineer)

Date 2014.1.22

Approved by

Zeng Dexin
Zeng Dexin
(Chief Engineer)

Date

2014.1.22

Reviewed by

Zhu Zhan
Zhu Zhan
(SAR Specialist)

Date

2014.1.22



The report refers only to the sample tested and does not apply to the bulk. This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen MORLAB Communication Technology Co., Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for advertising. The client to whom the report is issued may, however, show or send it or a certified copy thereof prepared by the Shenzhen MORLAB Telecommunication Co., Ltd to his customer. Supplier or others persons directly concerned. Shenzhen MORLAB Telecommunication Co., Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report. In the event of the improper use of the report, Shenzhen MORLAB Telecommunication Co., Ltd reserves the rights to withdraw it and to adopt any other remedies which may be appropriate



DIRECTORY

- 1. TESTING LABORATORY 3**
- 1.1 IDENTIFICATION OF THE RESPONSIBLE TESTING LOCATION 3
- 1.2 ACCREDITATION CERTIFICATE 3
- 2. TECHNICAL INFORMATION 4**
- 2.1 IDENTIFICATION OF APPLICANT 4
- 2.2 IDENTIFICATION OF MANUFACTURER..... 4
- 2.3 EQUIPMENT UNDER TEST (EUT) 4
- 2.3.1 PHOTOGRAPHS OF THE EUT 4
- 2.3.2 IDENTIFICATION OF ALL USED EUT 5
- 2.4 APPLIED REFERENCE DOCUMENTS 5
- 3. DEVICE CATEGORY AND RF EXPOSURE LIMIT 6**
- 4. MEASUREMENT OF CONDUCTED PEAK OUTPUT POWER. 7**
- 5. RF EXPOSURE EVALUATION 8**

Change History		
Issue	Date	Reason for change
1.0	Jan. 22, 2013	First edition



1. TESTING LABORATORY

1.1 Identification of the Responsible Testing Location

Name:	Shenzhen Morlab Communications Technology Co., Ltd. Morlab Laboratory
Address:	FL.3, Building A, FeiYang Science Park, No.8 LongChang Road, Block 67, BaoAn District, ShenZhen, GuangDong Province, P. R. China 518101

1.2 Accreditation Certificate

Accredited Testing Laboratory:	No. CNAS L3572
--------------------------------	----------------

2. TECHNICAL INFORMATION

Note: the Following data is based on the information by the applicant.

2.1 Identification of Applicant

Company Name:	Brightstar Corporation
Address:	9725 NW 117th Avenue, #300 Miami, FL 33178

2.2 Identification of Manufacturer

Company Name:	LAKIA Networks CO., LTD
Address:	2/F,Unit A, Technology Service Building, Software Garden, 1phase, Xiamen, Fujian, China Zip: 361005

2.3 Equipment Under Test (EUT)

Model Name:	FXP871
Trade Name:	Motorola/AVVIO
Brand Name:	Motorola/AVVIO
Hardware Version:	FXP871_P1.0
Software Version:	B301_60S_FXP871_EZZ_V0.03
Frequency Bands:	GSM 850MHz; GSM1900MHz
Modulation Mode:	GSM: GMSK
Antenna type:	External Antenna
Development Stage:	Identical prototype
Battery Model:	3xNR44AAA450P
Battery specification:	450mAh3.6V

2.3.1 Photographs of the EUT

Please refer to External Photo for the photographs of the EUT.

2.3.2 Identification of all used EUT

The EUT identity consists of numerical and letter characters, the letter character indicates the test sample, and the Following two numerical characters indicate the software version of the test sample.

EUT Identity	Hardware Version	Software Version
1#	FXP871_P1.0	B301_60S_FXP871_EZZ_V0.03

2.4 Applied Reference Documents

Leading reference documents for testing:

No.	Identity	Document Title
1	47 CFR§2.1091	Radiofrequency Radiation Exposure Evaluation: mobile devices
2	KDB 447498 D01 V05r01	General RF Exposure Guidance

3. Device Category and RF Exposure Limit

Per user manual, this device is a fixed wireless phone with GSM. Based on 47CFR 2.1091, this device belongs to mobile device category with General Population/Uncontrolled exposure.

Mobile Devices:

47CFR 2.1091(b)

For purposes of this section, a mobile device is defined as a transmitting device designed to be used in other than fixed locations and to generally be used in such a way that a separation distance of at least 20 centimeters is normally maintained between the transmitter's radiating structure(s) and the body of the user or nearby persons. In this context, the term "fixed location" means that the device is physically secured at one location and is not able to be easily moved to another location. Transmitting devices designed to be used by consumers or workers that can be easily re-located, such as wireless devices associated with a personal computer, are considered to be mobile devices if they meet the 20 centimeter separation requirement.

GENERAL POPULATION / UNCONTROLLED EXPOSURE

The general population/uncontrolled exposure limits are applicable to situations in which the general public may be exposed or in which persons who are exposed as a consequence of their employment may not be made fully aware of the potential for exposure or cannot exercise control over their exposure. Members of the general public would come under this category when exposure is not employment-related; for example, in the case of a wireless transmitter that exposes persons in its vicinity. Warning labels placed on low-power consumer devices such as cellular telephones are not considered sufficient to allow the device to be considered under the occupational/controlled category, and the general population/uncontrolled exposure limits apply to these devices.

TABLE 1—LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(B) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f ²)	30
30-300	27.5	0.073	0.2	30
300-1500			f/1500	30
1500-100,000			1.0	30

f = frequency in MHz

* = Plane-wave equivalent power density

4. Measurement Of Conducted Peak Output Power.

1. GSM Conducted peak output power

Band	Channel	Frequency (MHz)	Output Power (dBm)
GSM 850	128	824.2	30.389
	190	836.6	30.493
	251	848.8	30.455
PCS 1900	512	1850.2	28.646
	661	1880.0	28.534
	810	1909.8	28.235

5. RF Exposure Evaluation

Standalone transmission MPE evaluation

Bands	Frequency (MHz)	Antenna Gain (dBi)	Conducted Average Power (dBm)	Calculated to ERP (mW)
GSM850MHz	836.6	1.60	22	139.64
GSM1900MHz	1850.2	2.00	20	96.61

Note:

Per 47CFR 2.1091(c)

Mobile device are subject to routine environmental evaluation for RF exposure prior to equipment authorization or use if they operate at frequencies of 1.5 GHz or below and their effective radiated power (ERP) is 1.5 watts or more, or if they operate at frequencies above 1.5 GHz and their ERP is 3 watts or more.

ERP of the GSM is lower than 1.5 watts for GSM850MHz and 3 watts for GSM1900MHz, so standalone MPE evaluation is not required for GSM antenna.

$EIRP = P * G$, $ERP = EIRP - 2.15dB$

Conducted AV power = Conducted peak power – 9.0 dB

Simultaneous transmission MPE evaluation

There are only one GSM transmitter incorporated in this phone, so simultaneous transmission is not required.