



Report No.:SZ12020049E01



FCC TEST REPORT

Issued to

Brightstar Corporation

For

Dual- Fixed Wireless Phone

Model Name: IP-850
 Trade Name: AVVIO
 Brand Name: AVVIO
 FCC ID: WVB-IP850
 Test Rule: 47 CFR Part 15 Subpart B
 Test date: March 2, 2012 – March 9, 2012
 Issue date: March 21, 2012

By

Shenzhen Morlab Communication Technology Co., Ltd.



Tested by

Li Liang
Li Liang

Date

2012.3.21

Approved by

Wei Yanqian
Wei Yanqian

Date

2012.3.21

Review by

Huang Pulong
Huang Pulong

Date

2012.3.21

CTIA Authorized Test Lab

LAB CODE 20081223-00

IEEE 1725

OTA

OFTA

電訊管理局



GCF

Official Member of Global Certification Forum

Bluetooth

BQTF

FCC

Reg. No.

741109

The report refers only to the sample tested and does not apply to the bulk. This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen MORLAB Communication Technology Co., Ltd. It may not be reproduced in its entirety or in part and it may not be used for advertising. The client to whom the report is issued may, however, show or send it, or a certified copy thereof prepared by the Shenzhen MORLAB Telecommunication Co., Ltd to his customer. Supplier or others persons directly concerned, Shenzhen MORLAB Telecommunication Co., Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report. In the event of the improper use of the report, Shenzhen MORLAB Telecommunication Co., Ltd reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.



TABLE OF CONTENTS

- 1. GENERAL INFORMATION3**
- 1.1 EUT Description3**
- 1.2 Test Standards and Results4**
- 1.3 Facilities and Accreditations5**
- 1.3.1 Facilities5
- 1.3.2 Test Environment Conditions.....5
- 1.3.3 Measurement Uncertainty5
- 2. TEST CONDITIONS SETTING.....6**
- 2.1 Test Mode6**
- 2.2 Test Setup and Equipments List.....7**
- 2.2.1 Conducted Emission.....7
- 2.2.2 Radiated Emission.....8
- 3. 47 CFR PART 15B REQUIREMENTS9**
- 3.1 Conducted Emission9**
- 3.1.1 Requirement9
- 3.1.2 Test Description9
- 3.1.3 Test Result9
- 3.2 Radiated Emission 11**
- 3.2.1 Requirement 11
- 3.2.2 Test Description 11
- 3.2.3 Test Result 11

Change History		
Issue	Date	Reason for change
1.0	March 9, 2012	First edition
2.0	March 21, 2012	Second edition



1. GENERAL INFORMATION

1.1 EUT Description

EUT Type Fixed Wireless Phone
Serial No. (n.a., marked #1 by test site)
Hardware Version..... P2
Software Version LKW_11_RK3.00
Applicant..... Brightstar Corporation
9725 NW 117th Avenue, #300 Miami, FL 33178
Manufacturer..... LAKIA Teletech Co., Ltd.
2F, Unit A, Technology Service Building, Software Garden 1,
Xiamen, China
Power supply..... Dry Battery (×3)
Brand Name: 3xNR44AAA800P
Model No.: Li3712T42P3h475248
Serial No.: (n.a. marked #1 by test site)
Capacitance: 800mAh
Rated Voltage: 3.6V
Charge Limit: 4.2V
Ancillary Equipment 1 AC Adapter (Charger for Battery)
Brand Name: INNOV
Model No.: IVP045-050-1000
Serial No.: (n.a. marked #1 by test site)
Rated Input: ~ 100-240V, 200mA, 50/60 ± 3Hz
Rated Output: 4.7~5.3V = 1000mA

NOTE:

Note 1: The EUT is a Fixed Wireless Phone, it supports GSM 850MHz, 1900MHz, GPRS, EGPRS, WCDMA 850MHz, 1900MHz, HSDPA bands.
Note 2: Please refer to the attachments for the photographs of the EUT. For a more detailed description, please refer to Specification or User’s Manual supplied by the applicant and/or manufacturer.

1.2 Test Standards and Results

The objective of the report is to perform testing according to 47 CFR Part 15 Subpart B:

No.	Identity	Document Title
1	47 CFR Part 15 (10-1-09 Edition)	Radio Frequency Devices

Test detailed items/section required by FCC and results are as below:

No.	Section	Description	Result
1	15.107	Conducted Emission	PASS
2	15.109	Radiated Emission	PASS

NOTE: The tests were performed according to the method of measurements prescribed in ANSI C63.4 2009.

1.3 Facilities and Accreditations

1.3.1 Facilities

Shenzhen Morlab Communications Technology Co., Ltd. Morlab Laboratory is a testing organization accredited by China National Accreditation Service for Conformity Assessment (CNAS) according to ISO/IEC 17025. The accreditation certificate number is L3572.

All measurement facilities used to collect the measurement data are located at 3/F, Electronic Testing Building, Shahe Road, Xili, Nanshan District, Shenzhen, 518055 P. R. China. The test site is constructed in conformance with the requirements of ANSI C63.7, ANSI C63.4 and CISPR Publication 22; the FCC registration number is 741109.

1.3.2 Test Environment Conditions

During the measurement, the environmental conditions were within the listed ranges:

Temperature (°C):	15 - 35
Relative Humidity (%):	30 - 60
Atmospheric Pressure (kPa):	86 - 106

1.3.3 Measurement Uncertainty

The uncertainty is calculated using the methods suggested in the "Guide to the Expression of Uncertainty in Measurement" (GUM) published by ISO.

Uncertainty of Conducted Emission:	±1.8dB
Uncertainty of Radiated Emission:	±3.1dB

2. TEST CONDITIONS SETTING

2.1 Test Mode

- (1) The first test mode (Idle)

The EUT configuration of the emission tests is EUT + Battery + Charger.

During the test, The EUT was synchronized to the BCCH, listening to the CCCH and able to respond to paging message. Periodic location updating was disabled.

- (2) The second test mode (USB)

The EUT configuration of the emission tests is TransFlash Card + EUT + Battery + PC.

In this test mode, the EUT with a TransFlash Card embedded is connected with a PC via a special USB cable supplied by applicant. During the measurement, a communication link was established between the EUT and a System Simulator (SS), simultaneity, the data is transmitting between the PC and the TransFlash Card of the EUT.

- (3) The third test mode (Camera)

The EUT configuration of the emission tests is EUT + Battery + Charger.

In this test mode, the EUT's camera function was active and working normally.

- (4) The fourth test mode (FM)

The EUT configuration of the emission tests is EUT + Battery + Charger.

In this test mode, the EUT's FM function was active and working normally.

NOTE: All test modes are performed, the second test mode is the worst case and was recorded in this report.

2.2 Test Setup and Equipments List

2.2.1 Conducted Emission


A. Test Procedure

The EUT system is connected to the power mains through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm coupling impedance for the EUT system. Please refer the block diagram of the test setup and photographs. Both sides of AC line are checked to find out the maximum conducted emission. In order to find the maximum emission levels, the relative positions of equipment and all of the interface cables shall be changed according to FCC ANSI C63.4-2009 on Conducted Emission Measurement.

The bandwidth of test receiver (ESCI) set at 9KHz.

The frequency range from 150KHz to 30MHz is checked.

B. Test Setup:




The EUT is placed on a 0.8m high insulating table, which stands on the grounded conducting floor, and keeps 0.4m away from the grounded conducting wall. The EUT is connected to the power mains through a LISN which provides 50Ω/50μH of coupling impedance for the measuring instrument. The Common Antenna is used for the call between the EUT and the System Simulator (SS). A Pulse Limiter is used to protect the measuring instrument. The factors of the whole test system are calibrated to correct the reading.

C. Equipments List:

Description	Manufacturer	Model	Serial No.	Cal. Date
Receiver	Agilent	E7405A	US44210471	2011.05
LISN	Schwarzbeck	NSLK 8127	812744	2011.05
Pulse Limiter (20dB)	Schwarzbeck	VTSD 9561-D	9391	(n.a.)
System Simulator	Agilent	E5515C	GB43130131	2011.05
Personal Computer	IBM	IBM_T20	(n.a)	(n.a.)
T-Flash Card	SanDisk	256MB	(n.a.)	(n.a.)

2.2.2 Radiated Emission

A. Test Setup:



The test is performed in a 3m Semi-Anechoic Chamber; the antenna factor, cable loss and so on of the site (factors) is calculated to correct the reading. The EUT is placed on a 0.8m high insulating Turn Table, and keeps 3m away from the Test Antenna, which is mounted on a variable-height antenna master tower.

B. Equipments List:

Description	Manufacturer	Model	Serial No.	Cal. Date
Receiver	Agilent	E7405A	US44210471	2011.05
Semi-Anechoic Chamber	Albatross	9m*6m*6m	(n.a.)	2011.05
Test Antenna - Bi-Log	Schwarzbeck	VULB 9163	9163-274	2011.05
Test Antenna - Horn	Schwarzbeck	BBHA 9120C	9120C-384	2011.05
Test Antenna - Loop	R&S	HFH2-Z6	100231	2011.05
Personal Computer	IBM	IBM_T20	(n.a)	(n.a.)

3. 47 CFR PART 15B REQUIREMENTS

3.1 Conducted Emission

3.1.1 Requirement

According to FCC section 15.107, the radio frequency voltage that is conducted back onto the AC power line on any frequency within the band 150kHz to 30MHz shall not exceed the limits in the following table, as measured using a 50 μ H/50 Ω line impedance stabilization network (LISN).

Frequency range (MHz)	Conducted Limit (dB μ V)	
	Quasi-peak	Average
0.15 - 0.50	66 to 56	56 to 46
0.50 - 5	56	46
5 - 30	60	50

NOTE:

- The limit subjects to the Class B digital device.
- The lower limit shall apply at the band edges.
- The limit decreases linearly with the logarithm of the frequency in the range 0.15 - 0.50MHz.

3.1.2 Test Description

See section 2.2.1 of this report.


3.1.3 Test Result

The maximum conducted interference is searched using Peak (PK), Quasi-peak (QP) and Average (AV) detectors; the emission levels more than the AV and QP limits, and that have narrow margins from the AV and QP limits will be re-measured with AV and QP detectors. Tests for both L phase and N phase lines of the power mains connected to the EUT are performed. All test modes are considered, refer to recorded points and plots below.


3.1.3.1 Test Mode

A. Test Plot and Suspicious Points:

NOTE: All test modes are performed, the second test mode is the worst case and was recorded in this report.



(Plot A: L Phase)



(Plot B: N Phase)

Test Result :PASS

3.2 Radiated Emission

3.2.1 Requirement

According to FCC section 15.109, the field strength of radiated emissions from unintentional radiators at a distance of 3 meters shall not exceed the following values:

Frequency range (MHz)	Field Strength		Field Strength Limitation at 3m Measurement Dist	
	$\mu\text{V/m}$	Dist	($\mu\text{V/m}$)	(dBuV/m)
0.009 - 0.490	2400/F(KHz)	300m	10000* 2400/F(KHz)	20log 2400/F(KHz) + 80
0.490 - 1.705	2400/F(KHz)	30m	100* 2400/F(KHz)	20log 2400/F(KHz) + 40
1.705 - 30.00	30	30m	100*30	20log 30 + 40
30.0 - 88.0	100	3m	100	20log 100
88.0 - 216.0	150	3m	150	20log 150
216.0 - 960.0	200	3m	200	20log 200
Above 960.0	500	3m	500	20log 500

As shown in FCC section 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector. When average radiated emission measurements are specified in this part, including emission measurements below 1000MHz, there also is a limit on the radio frequency emissions, as measured using instrumentation with a peak detector function, corresponding to 20dB above the maximum permitted average limit for the frequency being investigated unless a different peak emission limit is otherwise specified in the rules.

Note:

- 1) The tighter limit shall apply at the boundary between two frequency range.
- 2) Limitation expressed in dBuV/m is calculated by $20\log \text{Emission Level}(\mu\text{V/m})$.
- 3) If measurement is made at 3m distance, then F.S Limitation at 3m distance is adjusted by using the formula of $Ld1 = Ld2 * (d2/d1)^2$.

Example:

F.S Limit at 30m distance is $30\mu\text{V/m}$, then F.S Limitation at 3m distance is adjusted as

$$Ld1 = L1 = 30\mu\text{V/m} * (10)^2 = 100 * 30\mu\text{V/m}$$

3.2.2 Test Description

Refer section 2.1 of this report.

3.2.3 Test Result

The maximum radiated emission is searched using PK, QP and AV detectors; the emission levels more than the limits, and that have narrow margins from the limits will be re-measured with AV and

QP detectors. Both the vertical and the horizontal polarizations of the Test Antenna are considered to perform the tests. All test modes are considered, refer to recorded points and plots below.


The amplitude of spurious emissions which are attenuated more than 20 dB below the permissible value need not be reported.

A. Test Plots and Suspicious Points:


NOTE: All test modes are performed, the second test mode is the worst case and was recorded in this report.



(Plot A: 9K – 30M)



(Plot A: Test Antenna Vertical)



(Plot B: Test Antenna Horizontal)

Test Result: PASS

**** END OF REPORT ****