

TEST REPORT

Applicant	Brightstar Corporation
Address:	9725 NW 117th Ave., Miami, Florida, United States

Manufacturer or Supplier	KCMOBILE
Address	#502 Ace Techno Tower 8th ,191-7 Guro 3 Dong,Guro-Gu,Seoul,KOREA (152-780)
Product	mobile phone
Brand Name	Avvio
Model	Avvio 701S/Avvio 701
Additional Model & Model Difference	N/A
Date of tests	Feb. 01, 2013 ~ Mar. 11, 2013

The submitted sample of the above equipment has been tested for according to the requirements of the following standards:

FCC Part 15, Subpart B, Class B

CONCLUSION: The submitted sample was found to COMPLY with the test requirement

Tesed by Kent Liu
Project Engineer / EMC Department

Approved by Sam Tung
Manager/ EMC Department




Date: Mar. 11, 2013

This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification



Table of Contents

RELEASE CONTROL RECORD.....	3
1 SUMMARY OF TEST RESULTS.....	4
1.1 MEASUREMENT UNCERTAINTY	4
2 GENERAL INFORMATION	5
2.1 GENERAL DESCRIPTION OF EUT.....	5
2.2 DESCRIPTION OF TEST MODES	6
2.3 DESCRIPTION OF SUPPORT UNITS.....	7
3 EMISSION TEST.....	8
3.1 CONDUCTED EMISSION MEASUREMENT	8
3.1.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT	8
3.1.2 TEST INSTRUMENTS	8
3.1.3 TEST PROCEDURES	9
3.1.4 DEVIATION FROM TEST STANDARD	9
3.1.5 TEST SETUP	10
3.1.6 EUT OPERATING CONDITIONS	10
3.1.7 TEST RESULTS	11
3.2 RADIATED EMISSION MEASUREMENT	13
3.2.1 LIMITS OF RADIATED EMISSION MEASUREMENT	13
3.2.2 TEST INSTRUMENTS	14
3.2.3 TEST PROCEDURE	15
3.2.4 DEVIATION FROM TEST STANDARD	16
3.2.5 TEST SETUP	16
3.2.6 EUT OPERATING CONDITIONS	16
3.2.7 TEST RESULTS (BELOW 1GHz).....	17
3.2.8 TEST RESULTS (ABOVE 1GHz)	19
4 PHOTOGRAPHS OF THE TEST CONFIGURATION.....	20
5 APPENDIX A – MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB.....	21



**BUREAU
VERITAS**

Test Report No.: FC130201N028

RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
FC130201N028	Original release	Mar. 11, 2013



1 SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

APPLIED STANDARD: FCC Part 15, Subpart B			
Standard Section	Test Item	Result	Remark
15.107	Conducted Emission Test	PASS	Meet the requirement of limit. Minimum passing margin is -13.76dB at 0.41197MHz.
15.109	Radiated Emission Test (30MHz ~ 1GHz)	PASS	Meets Class B Limit Minimum passing margin is -3.4dB at 240MHz
	Radiated Emission Test (Above 1GHz)	PASS	Meets Class B Limit Minimum passing margin is -9.8dB at 6950MHz

1.1 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

MEASUREMENT	FREQUENCY	UNCERTAINTY
Conducted emissions	150kHz ~ 30MHz	+/-2.94 dB
Radiated emissions	30MHz ~ 1GHz	+/-3.64 dB
	1GHz~ 18GHz	+/-2.20 dB



2 GENERAL INFORMATION

2.1 GENERAL DESCRIPTION OF EUT

PRODUCT	mobile phone
MODEL NO.	Avvio 701S/Avvio 701
POWER SUPPLY	5.0Vdc (adapter or host equipment) ; 3.7Vdc (battery)
I/O PORTS	USB Port, Earphone Port
CABLE SUPPLIED	USB Cable: Non-Shielded, Detachable, 1.0m Earphone Cable: Non-shielded, Detachable, 0.9 m
THE HIGHEST OPERATING FREQUENCY	2.5GHz

NOTE:

- 1 The EUT was powered by the following adapter:

Adapter	
BRAND:	LEIDIBAO
MODEL:	LDB-0500500U
INPUT:	AC 100-240V, 50/60Hz, 0.15A
OUTPUT:	DC 5V, 500mA
DC LINE:	N/A

- 2 For a more detailed features description, please refer to the manufacturer's specifications or the user's manual.
- 3 For the test results, the EUT had been tested with all conditions. But only the worst case was shown in test report.



2.2 DESCRIPTION OF TEST MODES

The EUT was tested under the following mode. And the final worst mode is marked in boldface and recorded in this report.

For conducted emission test:

Mode 1	GSM 850 Idle+BT Idle+ WLAN Idle+Battery+Earphone+ Adapter+USB Cable+Camera
Mode 2	PCS1900 Idle+BT Idle+ WLAN Idle+Battery+Earphone+ Adapter+USB Cable+Camera
Mode 3	PCS1900 Idle+BT Idle+ WLAN Idle+Battery+Earphone+ USB Cable+MPEG4

For radiated emission test:

Mode 1	GSM 850 Idle+BT Idle+ WLAN Idle+Battery+Earphone+ Adapter+USB Cable+Camera
Mode 2	PCS1900 Idle+BT Idle+ WLAN Idle+Battery+Earphone+ Adapter+USB Cable+MPEG4
Mode 3	PCS1900 Idle+BT Idle+ WLAN Idle+Battery+Earphone+ USB Cable+MPEG4



2.3 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

NO.	PRODUCT	BRAND	MODEL NO.	SERIAL NO.	FCC ID
1	Universal Radio Communication Tester	R&S	CMU200	123259	N/A
2	Notebook	DELL	5P2PM2X	12400120329	N/A
3	Mouse	Lenovo	MO28UOL	4429690	N/A
4	Printer	HP	hp LaserJet 1300	CNSJF75989	N/A
5	Wireless AP	ABOCOM	WR224GR	060500749P	D43064

NO.	SIGNAL CABLE DESCRIPTION OF THE ABOVE SUPPORT UNITS
1.	N/A
2	N/A
3	USB Line: Unshielded, undetachable, 1.8m.
4	N/A
5	N/A

NOTE:

1. Items 1, 2, 5 acted as communication partners to transfer data.
2. All power cords of the above support units are non-shielded (1.8m).



3 EMISSION TEST

3.1 CONDUCTED EMISSION MEASUREMENT

3.1.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT

FREQUENCY OF EMISSION (MHz)	CONDUCTED LIMIT (dBµV)	
	Quasi-peak	Average
0.15 ~ 0.5	66 to 56	56 to 46
0.5 ~ 5	56	46
5 ~ 30	60	50

- NOTE:**
1. The lower limit shall apply at the transition frequencies.
 2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.
 3. All emanations from a class A/B digital device or system, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strengths specified above.

3.1.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	DATE OF CALIBRATION	DUE DATE OF CALIBRATION
EMI Test Receiver Rohde&Schwarz	ESU 26	100005	May 15,12	May 14,13
Artificial Mains Network Rohde&Schwarz	ENV216	101173	May 15,12	May 14,13
Pulse Limiter	Rohde&Schwarz	ESH3-Z2	May 15,12	May 14,13
Impedance Stabilization Network	TESEQ	ISN T800	Oct.10,12	Oct. 09,13
Test software	ADT_Cond_V7.3.7	N/A	N/A	N/A

- NOTE:**
1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to CEPREI/CHINA and NIM/CHINA
 2. The test was performed in Dongguan Shielded Room 553.



3.1.3 TEST PROCEDURES

- a. The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- c. The frequency range from 150kHz to 30MHz was searched. Emission levels under (Limit - 20dB) was not recorded.


NOTE: All modes of operation were investigated and the worst-case emissions are reported.

3.1.4 DEVIATION FROM TEST STANDARD

No deviation.



3.1.5 TEST SETUP



- Note:**
1. Support units were connected to second LISN.
 2. Both of LISNs (AMN) are 80 cm from EUT and at least 80 cm from other units and other metal planes

For the actual test configuration, please refer to the attached file (Test Setup Photo).

3.1.6 EUT OPERATING CONDITIONS

- a. Turned on the power and connected of all equipment.
- b. EUT was operated according to the type used was description in manufacturer's specifications or the User's Manual.




3.1.7 TEST RESULTS

TEST MODE	Mode 1	6DB BANDWIDTH	9 kHz
TEST VOLTAGE	DC 5V From Adapter Input AC 120V/60Hz	PHASE	Line (L)
ENVIRONMENTAL CONDITIONS	23deg. C, % 40RH	TESTED BY	Bin

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value		Emission Level		Limit		Margin	
			[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.16955	10.59	29.35	15.67	39.94	26.26	64.98	54.98	-25.04	-28.72
2	0.32986	10.4	32.15	21.73	42.55	32.13	59.45	49.45	-16.91	-17.33
3	0.41197	10.35	32.78	23.5	43.13	33.85	57.61	47.61	-14.48	-13.76
4	0.74041	10.16	31.92	19.98	42.08	30.14	56	46	-13.92	-15.86
5	2.22621	10.05	29.1	17.91	39.15	27.96	56	46	-16.85	-18.04
6	3.45395	10.04	23.82	12.1	33.86	22.14	56	46	-22.14	-23.86

REMARKS: The emission levels of other frequencies were very low against the limit.






TEST MODE	Mode 1	6DB BANDWIDTH	9 kHz
TEST VOLTAGE	DC 5V From Adapter Input AC 120V/60Hz	PHASE	Neutral (N)
ENVIRONMENTAL CONDITIONS	23deg. C, % 40RH	TESTED BY	Bin

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value		Emission Level		Limit		Margin	
			[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.18075	10.51	27.62	15.71	38.13	26.22	64.45	54.45	-26.32	-28.23
2	0.33768	10.41	32.29	20.14	42.70	30.55	59.26	49.26	-16.56	-18.71
3	0.40800	10.44	30.90	20.24	41.34	30.68	57.69	47.69	-16.35	-17.01
4	0.71304	9.96	25.16	13.86	35.12	23.82	56.00	46.00	-20.88	-22.18
5	2.23403	9.59	22.73	10.86	32.32	20.45	56.00	46.00	-23.68	-25.55
6	23.87197	10.45	22.29	8.99	32.74	19.44	60.00	50.00	-27.26	-30.56

REMARKS: The emission levels of other frequencies were very low against the limit.





3.2 RADIATED EMISSION MEASUREMENT

3.2.1 LIMITS OF RADIATED EMISSION MEASUREMENT

TEST STANDARD: FCC Part 15, Subpart B (Section: 15.109)

FREQUENCY (MHz)	Class A (at 10m)		Class B (at 3m)	
	uV/m	dBuV/m	uV/m	dBuV/m
30 – 88	90	39.1	100	40.0
88 – 216	150	43.5	150	43.5
216 – 960	210	46.4	200	46.0
960 – 1000	300	49.5	500	54.0

Based on FCC part 15 clause 15.109(g). As an alternative to the radiated emission limits to comply with the standards contained in CISPR 22.

FOR FREQUENCY BELOW 1000 MHz

FREQUENCY (MHz)	Class A (at 10m)	Class B (at 10m)
	dBuV/m	dBuV/m
30 – 230	40	30
230 – 1000	47	37

FREQUENCY RANGE OF RADIATED MEASUREMENT

(For unintentional radiators)

Highest frequency generated or Upper frequency of measurement used in the device or on which the device operates or tunes (MHz)	Range (MHz)
Below 1.705	30
1.705 – 108	1000
108 – 500	2000
500 – 1000	5000
Above 1000	5th harmonic of the highest frequency or 40 GHz, whichever is lower



LIMIT OF RADIATED EMISSION OF FCC PART 15, SUBPART B FOR FREQUENCY ABOVE 1000 MHz

FREQUENCY (MHz)	Class A (dBuV/m) (at 3m)		Class B (dBuV/m) (at 3m)	
	PEAK	AVERAGE	PEAK	AVERAGE
Above 1000	80.0	60.0	74.0	54.0

- Note: (1) The lower limit shall apply at the transition frequencies.
 (2) Emission level (dBuV/m) = 20 log Emission level (uV/m).
 (3) All emanation from a class A/B digital device or system, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strengths specified above.

3.2.2 TEST INSTRUMENTS

For frequency below 1G

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
Spectrum Analyzer	Agilent	E4446A	MY46180622	May 02,12	May 01,13
EMI Test Receiver	Rohde&Schwarz	ESVD	847398/003	May 15,12	May 14,13
Bilog Antenna	Teseq	CBL 6111D	27089	Jul. 16,12	Jul. 15,13
10m Semi-anechoic Chamber	CHANGLING	21.4m*12.1m*8.8m	NSEMC006	Mar. 24,12	Mar. 23,13
Pre-Amplifier (20MHz-3GHz)	EMCI	EMC 330	980095	Nov. 02,12	Nov. 01,13
Test Software	ADT	ADT_Radiated_V7.6.15	N/A	N/A	N/A

For frequency above 1G

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
Horn Antenna	EMCO	3117	00062558	Oct.18,12	Oct.17,13
Horn Antenna	SCHWARZBECK	BBHA 9170	BBHA9170242	Jan. 04,11	Jan. 03,14
Spectrum Analyzer	Agilent	E4446A	MY46180622	May 02,12	May 01,13
Pre-Amplifier (100MHz-26.5 GHz)	Agilent	8449B	3008A00409	May 31,12	May 30,13
Pre-Amplifier (18GHz-40GHz)	EMCI	EMC 184045	980102	Nov. 04,12	Nov. 03,13
Test Software	ADT	ADT_Radiated_V7.6.15	N/A	N/A	N/A

- NOTE:** 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to CEPREI/CHINA and NIM/CHINA.
 2. The test was performed in Dongguan Chamber 10m.



3.2.3 TEST PROCEDURE

<Frequency Range below 1GHz>

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 10 meter open test site. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the turn table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.

NOTE: The resolution bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection (QP) at frequency below 1GHz.

<Frequency Range above 1GHz>

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 10 meter chamber room. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The height of antenna can be varied from one meter-to four meters, the height of adjustment depends on the EUT height and the antenna 3dB beamwidth both, to detect the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.

NOTE:

1. The resolution bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection (QP) at frequency below 1GHz.
2. The resolution bandwidth is 1MHz and video bandwidth of test receiver/spectrum analyzer is 3MHz for Peak detection at frequency above 1GHz. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz for Average detection (AV) at frequency above 1GHz.
3. For measurement of frequency above 1000 MHz, the EUT was set 3 meters away from the receiver antenna.




3.2.4 DEVIATION FROM TEST STANDARD


No deviation

3.2.5 TEST SETUP

<Frequency Range below 1GHz>



<Frequency Range above 1GHz>



3.2.6 EUT OPERATING CONDITIONS

Same as item 3.1.6.




3.2.7 TEST RESULTS (BELOW 1GHZ)

TEST MODE	Mode 3	FREQUENCY RANGE	30-1000MHz
TEST VOLTAGE	DC 5V From PC Input AC 120V/60Hz	DETECTOR FUNCTION & RESOLUTION BANDWIDTH	Quasi-Peak, 120kHz
ENVIRONMENTAL CONDITIONS	22deg. C, 55% RH	TESTED BY: Endy Xie	

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 10 M								
No.	Freq. (MHz)	Correction Factor (dB/m)	Raw Value (dBuV)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (cm)	Table Angle (Degree)
1	156.10	12.42	10.97	23.39	30.00	-6.61	400	359
2	196.52	10.91	13.42	24.33	30.00	-5.67	400	324
3	225.62	11.91	11.66	23.57	30.00	-6.43	400	317
4	240.00	13.53	20.10	33.63	37.00	-3.37	310	132
5	296.75	15.64	11.88	27.52	37.00	-9.48	300	286
6	540.87	22.45	4.92	27.37	37.00	-9.63	230	153

REMARKS: The emission levels of other frequencies were very low against the limit.






TEST MODE	Mode 3	FREQUENCY RANGE	30-1000MHz
TEST VOLTAGE	DC 5V From PC Input AC 120V/60Hz	DETECTOR FUNCTION & RESOLUTION BANDWIDTH	Quasi-Peak, 120kHz
ENVIRONMENTAL CONDITIONS	22deg. C, 55% RH	TESTED BY: Endy Xie	

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 10 M								
No.	Freq. (MHz)	Correction Factor (dB/m)	Raw Value (dBuV)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (cm)	Table Angle (Degree)
1	135.08	13.28	10.67	23.95	30.00	-6.05	100	346
2	165.80	11.80	13.40	25.20	30.00	-4.80	100	292
3	240.00	13.53	17.54	31.07	37.00	-5.93	100	320
4	296.75	15.64	9.65	25.29	37.00	-11.71	101	239
5	343.63	16.94	11.37	28.31	37.00	-8.69	143	185
6	645.95	24.11	2.76	26.87	37.00	-10.13	229	88

REMARKS: The emission levels of other frequencies were very low against the limit.





3.2.8 TEST RESULTS (ABOVE 1GHz)

TEST MODE	Mode 3	FREQUENCY RANGE	1000-13000MHz
TEST VOLTAGE	DC 5V From PC Input AC 120V/60Hz	DETECTOR FUNCTION & RESOLUTION BANDWIDTH	AV/Peak, 1MHz
ENVIRONMENTAL CONDITIONS	22deg. C, 55% RH	TESTED BY: Endy Xie	

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	3040.00	48.2 PK	74.0	-25.8	1.00 H	202	9.56	38.67
2	3040.00	37.7 AV	54.0	-16.3	1.00 H	202	-0.93	38.67
3	4598.00	50.2 PK	74.0	-23.8	1.00 H	153	8.89	41.35
4	4598.00	39.7 AV	54.0	-14.3	1.00 H	153	-1.63	41.35
5	6950.00	54.5 PK	74.0	-19.6	1.00 H	54	8.83	45.62
6	6950.00	44.2 AV	54.0	-9.8	1.00 H	54	-1.44	45.62
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2000.00	47.0 PK	74.0	-27.0	1.00 V	240	10.42	36.57
2	2000.00	39.4 AV	54.0	-14.6	1.00 V	240	2.85	36.57
3	2658.00	39.1 AV	54.0	-15.0	1.00 V	94	1.24	37.81
4	2658.33	51.6 PK	74.0	-22.4	1.00 V	94	13.80	37.81
5	4808.00	42.4 AV	54.0	-11.6	1.00 V	200	0.79	41.61
6	4808.33	51.0 PK	74.0	-23.0	1.00 V	200	9.36	41.61

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.



4 PHOTOGRAPHS OF THE TEST CONFIGURATION

See test setup photo.



**BUREAU
VERITAS**

Test Report No.: FC130201N028

5 APPENDIX A – MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB

No any modifications were made to the EUT by the lab during the test.

---END---