



FCC Test Report

APPLICANT : Brightstar Corporation
EQUIPMENT : Access Point
BRAND NAME : Avvio
MODEL NAME : HT851W
FCC ID : WVBHT851W
STANDARD : FCC 47 CFR FCC Part 15 Subpart B
CLASSIFICATION : Certification

The product was received on Mar. 19, 2011 and completely tested on Apr. 12, 2011. We, SPORTON INTERNATIONAL (KUNSHAN) INC., would like to declare that the tested sample has been evaluated in accordance with the procedures given in ANSI C63.4-2003 and shown the compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL (KUNSHAN) INC., the test report shall not be reproduced except in full.

Reviewed by:

Roy Wu / Manager



SPORTON INTERNATIONAL (KUNSHAN) INC.
No. 3-2, PingXiang Road, Kunshan, Jiangsu Province, P.R.C.



TABLE OF CONTENTS

REVISION HISTORY 3

SUMMARY OF TEST RESULT 4

1. GENERAL DESCRIPTION 5

 1.1. Applicant 5

 1.2. Manufacturer 5

 1.3. Feature of Equipment Under Test 5

 1.4. Test Site 6

 1.5. Applied Standards 6

 1.6. Ancillary Equipment List 7

2. TEST CONFIGURATION OF EQUIPMENT UNDER TEST 8

 2.1. Test Mode 8

 2.2. Connection Diagram of Test System 10

 2.3. Test Software 10

3. TEST RESULT 11

 3.1. Test of AC Conducted Emission Measurement 11

 3.2. Test of Radiated Emission Measurement 15

4. LIST OF MEASURING EQUIPMENT 19

5. UNCERTAINTY OF EVALUATION 20

APPENDIX A. PHOTOGRAPHS OF EUT

APPENDIX B. SETUP PHOTOGRAPHS



SUMMARY OF TEST RESULT

Report Section	FCC Rule	IC Rule	Description	Limit	Result	Remark
3.1	15.107	7.2.2	AC Conducted Emission	< 15.107 limits < RSS-Gen table 2 limits	PASS	Under limit 10.64 dB at 0.36 MHz
3.2	15.109	7.2.3.2	Radiated Emission	< 15.109 limits or < RSS-Gen table 1 limits (Section 6)	PASS	Under limit 2.27 dB at 250.00 MHz

1. General Description

1.1. Applicant

Brightstar Corporation
 9725 NW 117th Ave., Miami, Florida, United States

1.2. Manufacturer

Shanghai Longcheer 3g Technology Co., Ltd.
 No. 1, Building 5, 299 Bisheng Rd., Zhangjiang Hi-Tech Park, Pudong, Shanghai, P.R. China

1.3. Feature of Equipment Under Test

Product Feature & Specification	
Equipment	Access Point
Brand Name	Avvio
Model Name	HT851W
FCC ID	WVBHT851W
Tx Frequency Range	GSM850 : 824 MHz ~ 849 MHz GSM1900 : 1850 MHz ~ 1910 MHz WCDMA Band V : 824 MHz ~ 849 MHz WCDMA Band II : 1850 MHz ~ 1910 MHz WLAN : 2400 MHz ~ 2483.5 MHz
Rx Frequency Range	GSM850 : 869 MHz ~ 894 MHz GSM1900 : 1930 MHz ~ 1990 MHz WCDMA Band V : 869 MHz ~ 894 MHz WCDMA Band II : 1930 MHz ~ 1990 MHz WLAN : 2400 MHz ~ 2483.5 MHz
Antenna Type	WWAN : Fixed External Antenna WLAN : Chip Antenna
HW Version	L0AM092A4-2
SW Version	V1.1
Type of Modulation	GSM / GPRS : GMSK EDGE : 8PSK WCDMA : QPSK HSDPA : QPSK / 16QAM HSUPA : BPSK 802.11b : DSSS (BPSK / QPSK / CCK) 802.11g/n : OFDM (BPSK / QPSK / 16QAM / 64QAM)
EUT Stage	Identical Prototype

Remark: The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.



1.4. Test Site

Test Site	SPORTON INTERNATIONAL (KUNSHAN) INC.	
Test Site Location	No. 3-2, PingXiang Road, Kunshan, Jiangsu Province, P.R.C. TEL: +86-0512-5790-0158 FAX: +86-0512-5790-0958	
Test Site No.	Sporton Site No.	
	CO01-KS	03CH01-KS

1.5. Applied Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- FCC 47 CFR FCC Part 15 Subpart B
- ANSI C63.4-2003
- IC RSS-Gen Issue 3

Remark: All test items were verified and recorded according to the standards and without any deviation during the test.

1.6. Ancillary Equipment List

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	System Simulator	R&S	CMU 200	N/A	N/A	Unshielded, 1.8 m
2.	Notebook	Dell	P08S	QDS-BRCM1030	N/A	AC I/P: Unshielded, 1.84m DC O/P: Shielded, 0.9m
3.	Notebook	Acer	Trave Imate 2413Lci	QDS-BRCM1016	N/A	AC I/P: Unshielded, 1.8m DC O/P: Shielded, 1.8m
4.	Router	Linksys	WRT600N	FQ87-WRT60NV11	N/A	AC I/P: Unshielded, 1.8m DC O/P: Shielded, 1.8m
5.	Phone	BBK	HCD007(6082)TSD	N/A	N/A	N/A
6.	USB	Toshiba	ULP1	N/A	N/A	N/A



2. Test Configuration of Equipment Under Test

2.1. Test Mode

The EUT has been associated with peripherals pursuant to ANSI C63.4-2003 and configuration operated in a manner tended to maximize its emission characteristics in a typical application.

Frequency range investigated: conduction (150 kHz to 30 MHz), radiation (30MHz to the 5th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower).

The following tables are showing the test modes as the worst cases and recorded in this report.

Item	EUT Configuration	Test Condition	
		EMI AC	EMI RE
1.	Charging Mode (EUT with adapter)	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>

Abbreviations:


- EMI AC: AC conducted emissions
- EMI RE : EUT radiated emissions

Test Items	EUT Configure Mode	Function Type
AC Conducted Emission	1	Mode 1 : GSM850 Idle + WLAN Link + Adapter + RJ-11 Link + RJ-45 Link + USB Link Mode 2 : GSM1900 Idle + WLAN Link + Adapter + RJ-11 Link + RJ-45 Link + USB Link Mode 3 : WCDMA Band V Idle + WLAN Link + Adapter + RJ-11 Link + RJ-45 Link + USB Link Mode 4 : WCDMA Band II Idle + WLAN Link + Adapter + RJ-11 Link + RJ-45 Link + USB Link
Radiated Emissions < 1GHz	1	Mode 1 : GSM850 Idle + WLAN Link + Adapter + RJ-11 Link + RJ-45 Link + USB Link Mode 2 : GSM1900 Idle + WLAN Link + Adapter + RJ-11 Link + RJ-45 Link + USB Link Mode 3 : WCDMA Band V Idle + WLAN Link + Adapter + RJ-11 Link + RJ-45 Link + USB Link Mode 4 : WCDMA Band II Idle + WLAN Link + Adapter + RJ-11 Link + RJ-45 Link + USB Link
Radiated Emissions ≥ 1GHz	1	Mode 1 : WCDMA Band V Idle + WLAN Link + Adapter + RJ-11 Link + RJ-45 Link + USB Link

Remark:

1. The worst case of AC is mode 3; only the test data of this mode was reported.
2. The worst case of RE < 1G is mode 3; only the test data of this mode was reported.

2.2. Connection Diagram of Test System



2.3. Test Software

The EUT was in GSM or WCDMA idle mode during the testing. The EUT was synchronized to the BCCH, and is in continuous receiving mode by setting system simulator's paging reorganization.

At the same time, the EUT was linked with notebook via RJ-45 or WLAN function, connected with phone via RJ-11 and active sync files transfer with EUT via USB.

3. Test Result

3.1. Test of AC Conducted Emission Measurement

3.1.1 Limits of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of emission (MHz)	Conducted limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.


3.1.2 Measuring Instruments

See list of measuring instruments of this test report.

3.1.3 Test Procedure

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth with Maximum Hold Mode.


3.1.4 Test Setup





3.1.5 Test Result of AC Conducted Emission

Test Mode :	Mode 3	Temperature :	21~23°C
Test Engineer :	Allen Chang	Relative Humidity :	41~43%
Test Voltage :	120Vac / 60Hz	Phase :	Line
Function Type :	WCDMA Band V Idle + WLAN Link + Adapter + RJ-11 Link + RJ-45 Link + USB Link		
Remark :	All emissions not reported here are more than 10 dB below the prescribed limit.		




Site : C001-KS
 Condition: FCC CLASS-B LISN-100807 LINE

Mode : mode 3

	Freq	Level	Over	Limit	Read	LISN	Cable	Remark
	MHz	dBuV	Limit	Line	Level	Factor	Loss	
			dB	dBuV	dBuV	dB	dB	
1	0.36	38.01	-10.64	48.65	27.91	-0.08	10.18	Average
2	0.36	41.21	-17.44	58.65	31.11	-0.08	10.18	QP
3	0.39	39.01	-19.07	58.08	28.90	-0.08	10.19	QP
4	0.39	35.91	-12.17	48.08	25.80	-0.08	10.19	Average
5	1.75	26.51	-19.49	46.00	16.30	-0.11	10.32	Average
6	1.75	31.01	-24.99	56.00	20.80	-0.11	10.32	QP
7	2.51	36.44	-19.56	56.00	26.20	-0.11	10.35	QP
8	2.51	29.34	-16.66	46.00	19.10	-0.11	10.35	Average
9	2.75	33.05	-22.95	56.00	22.81	-0.12	10.36	QP
10	2.75	30.35	-15.65	46.00	20.11	-0.12	10.36	Average
11	3.78	35.86	-20.14	56.00	25.61	-0.13	10.38	QP
12	3.78	29.66	-16.34	46.00	19.41	-0.13	10.38	Average



Test Mode :	Mode 3	Temperature :	21~23°C
Test Engineer :	Allen Chang	Relative Humidity :	41~43%
Test Voltage :	120Vac / 60Hz	Phase :	Neutral
Function Type :	WCDMA Band V Idle + WLAN Link + Adapter + RJ-11 Link + RJ-45 Link + USB Link		
Remark :	All emissions not reported here are more than 10 dB below the prescribed limit.		



Site : C001-KS
 Condition: FCC CLASS-B LISN-100807 NEUTRAL

Mode : mode 3

	Freq	Level	Over	Limit	Read	LISN	Cable	Remark
	MHz	dBuV	Limit	Line	Level	Factor	Loss	
			dB	dBuV	dBuV	dB	dB	
1	0.35	36.70	-12.30	49.00	26.60	-0.08	10.18	Average
2	0.35	39.00	-20.00	59.00	28.90	-0.08	10.18	QP
3	0.40	38.31	-19.50	57.81	28.20	-0.08	10.19	QP
4	0.40	34.01	-13.80	47.81	23.90	-0.08	10.19	Average
5	0.57	30.54	-15.46	46.00	20.40	-0.08	10.22	Average
6	0.57	35.54	-20.46	56.00	25.40	-0.08	10.22	QP
7	2.51	36.74	-19.26	56.00	26.50	-0.11	10.35	QP
8	2.51	28.94	-17.06	46.00	18.70	-0.11	10.35	Average
9	3.51	37.06	-18.94	56.00	26.80	-0.12	10.38	QP
10	3.51	29.86	-16.14	46.00	19.60	-0.12	10.38	Average
11	4.53	32.66	-23.34	56.00	22.40	-0.13	10.39	QP
12	4.53	26.56	-19.44	46.00	16.30	-0.13	10.39	Average

3.2. Test of Radiated Emission Measurement

3.2.1. Limit of Radiated Emission

The emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3


3.2.2. Measuring Instruments

See list of measuring instruments of this test report.

3.2.3. Test Procedures

1. The EUT was placed on a turntable with 0.8 meter above ground.
2. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
3. The table was rotated 360 degrees to determine the position of the highest radiation.
4. The antenna is a Bi-Log antenna and its height is adjusted between one meter and four meters above ground to find the maximum value of the field strength for both horizontal polarization and vertical polarization of the antenna.
5. For each suspected emission, the EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading.
6. Set the test-receiver system to Peak Detect Function and specified bandwidth with Maximum Hold Mode.
7. If the emission level of the EUT in peak mode was 3 dB lower than the limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be repeated one by one using the quasi-peak method and reported
8. Emission level (dBuV/m) = 20 log Emission level (uV/m)
9. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level


3.2.4. Test Setup of Radiated Emission





3.2.5. Test Result of Radiated Emission

Test Mode :	Mode 3	Temperature :	21~23°C
Test Engineer :	Allen Chang	Relative Humidity :	42~44%
Test Distance :	3m	Polarization :	Horizontal
Function Type :	WCDMA Band V Idle + WLAN Link + Adapter + RJ-11 Link + RJ-45 Link + USB Link		




Site : 03CH01-KS
 Condition: FCC CLASS-B 3m LF_ANT_100803 VERTICAL

Mode : mode 3

	Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp	Ant	Table	
	MHz	dBuV/m	Limit	Line	Level	Loss	Factor	Pos	Pos	Remark
			dB	dBuV/m	dBuV	dB	dB	cm	deg	
1	30.54	31.76	-8.24	40.00	44.30	17.29	0.25	30.08	162	QP
2	73.74	34.96	-5.04	40.00	59.00	5.68	0.34	30.06	---	Peak
3	250.05	41.15	-4.85	46.00	58.32	12.00	0.67	29.84	---	Peak
4	720.00	36.66	-9.34	46.00	45.65	19.52	1.15	29.66	---	Peak
5	840.40	34.19	-11.81	46.00	42.15	20.41	1.28	29.65	---	Peak
6	939.80	33.74	-12.26	46.00	41.25	20.69	1.33	29.53	---	Peak



Test Mode :	Mode 3	Temperature :	21~23°C
Test Engineer :	Allen Chang	Relative Humidity :	42~44%
Test Distance :	3m	Polarization :	Vertical
Function Type :	WCDMA Band V Idle + WLAN Link + Adapter + RJ-11 Link + RJ-45 Link + USB Link		



Site : 03CH01-KS
 Condition: FCC CLASS-B 3m LF_ANT_100803 HORIZONTAL

Mode : mode 3

	Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp	Ant	Table	Remark	
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg	
1	94.26	25.08	-18.42	43.50	45.00	9.66	0.40	29.98	---	---	Peak
2	125.04	27.07	-16.43	43.50	44.84	11.75	0.46	29.98	---	---	Peak
3	250.00	43.73	-2.27	46.00	60.90	12.00	0.67	29.84	100	37	QP
4	720.00	37.96	-8.04	46.00	46.95	19.52	1.15	29.66	---	---	Peak
5	840.40	40.37	-5.63	46.00	48.33	20.41	1.28	29.65	---	---	Peak
6	960.07	43.70	-10.30	54.00	51.11	20.79	1.34	29.54	100	156	QP
7	4874.00	61.67	-12.33	74.00	53.78	35.18	4.98	32.27	100	275	Peak
8	4874.00	45.10	-8.90	54.00	37.21	35.18	4.98	32.27	100	275	Average



4. List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Due Date	Remark
EMI Receiver	R&S	ESCI7	100768	9kHz~7GHz	Jun. 22, 2010	Jun. 21, 2011	Conduction (CO01-KS)
LISN	MessTec	AN3016	60103	9kHz~30MHz	Jan. 07, 2011	Jan. 06, 2012	Conduction (CO01-KS)
LISN	MessTec	AN3016	60105	9kHz~30MHz	Jan. 07, 2011	Jan. 06, 2012	Conduction (CO01-KS)
AC Power Source	Chroma	61602	ABP0000008 11	N/A	Nov. 10, 2010	Nov. 09, 2011	Conduction (CO01-KS)
EMI Test Receiver	R&S	ESCI	100534	9kHz~3GHz	Nov. 16, 2010	Nov. 15, 2011	Radiation (03CH01-KS)
Spectrum Analyzer	R&S	FSP40	100319	9kHz~40GHz	Jan. 07, 2011	Jan. 06, 2012	Radiation (03CH01-KS)
Bilog Antenna	SCHAFFNER	CBL6112D	23182	25MHz~2GHz	Dec. 07, 2010	Dec. 06, 2011	Radiation (03CH01-KS)
Double Ridge Horn Antenna	EMCO	3117	00075959	1GHz~18GHz	Jan. 07, 2011	Jan. 06, 2012	Radiation (03CH01-KS)
Amplifier	Wireless	FPA-6592G	060004	30MHz~2GHz	Dec. 09, 2010	Dec. 08, 2011	Radiation (03CH01-KS)
Amplifier	Agilent	8449B	3008A02370	1GHz~26.5GHz	Jan. 07, 2011	Jan. 06, 2012	Radiation (03CH01-KS)
Active horn antenna	com-power	AHA-118	701023	1G-18GHz	Nov. 09, 2010	Nov. 08, 2011	Radiation (03CH01-KS)
Signal Generator	R&S	SMR40	100455	10MHz~40GHz	Jan. 06, 2011	Jan. 05, 2012	Radiation (03CH01-KS)
SHF-EHF Horn	Schwarzbeck	BBHA 9170	BBHA170249	15-40GHz	Oct. 15, 2010	Oct. 14, 2011	Radiation (03CH01-KS)
Loop Antenna	R&S	HFH2-Z2	860004/001	9 kHz~30 MHz	Jul. 29, 2010	Jul. 28, 2011	Radiation (03CH01-KS)
System Simulator	R&S	CMU200	837587/066	Full-Band	Jan. 07, 2011	Jan. 06, 2012	Radiation (03CH01-KS)

5. Uncertainty of Evaluation

Uncertainty of Conducted Emission Measurement (150 kHz ~ 30 MHz)

Contribution	Uncertainty of X_i		$u(X_i)$
	dB	Probability Distribution	
Receiver Reading	0.10	Normal (k=2)	0.05
Cable Loss	0.10	Normal (k=2)	0.05
AMN Insertion Loss	2.50	Rectangular	0.63
Receiver Specification	1.50	Rectangular	0.43
Site Imperfection	1.39	Rectangular	0.80
Mismatch	+0.34 / -0.35	U-Shape	0.24
Combined Standard Uncertainty $U_c(y)$	1.13		
Measuring Uncertainty for a Level of Confidence of 95% ($U = 2U_c(y)$)	2.26		

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Contribution	Uncertainty of X_i		$u(X_i)$
	dB	Probability Distribution	
Receiver Reading	0.41	Normal (k=2)	0.21
Antenna Factor Calibration	0.83	Normal (k=2)	0.42
Cable Loss Calibration	0.25	Normal (k=2)	0.13
Pre-Amplifier Gain Calibration	0.27	Normal (k=2)	0.14
RCV/SPA Specification	2.50	Rectangular	0.72
Antenna Factor Interpolation for Frequency	1.00	Rectangular	0.29
Site Imperfection	1.43	Rectangular	0.83
Mismatch	+0.39 / -0.41	U-Shape	0.28
Combined Standard Uncertainty $U_c(y)$	1.27		
Measuring Uncertainty for a Level of Confidence of 95% ($U = 2U_c(y)$)	2.54		



Uncertainty of Radiated Emission Measurement (1 GHz ~ 40 GHz)

Contribution	Uncertainty of X_i		$u(X_i)$	C_i	$C_i * u(X_i)$
	dB	Probability Distribution			
Receiver Reading	±0.10	Normal (k=2)	0.10	1	0.10
Antenna Factor Calibration	±1.70	Normal (k=2)	0.85	1	0.85
Cable Loss Calibration	±0.50	Normal (k=2)	0.25	1	0.25
Receiver Correction	±2.00	Rectangular	1.15	1	1.15
Antenna Factor Directional	±1.50	Rectangular	0.87	1	0.87
Site Imperfection	±2.80	Triangular	1.14	1	1.14
Mismatch Receiver VSWR $\Gamma_1 = 0.197$ Antenna VSWR $\Gamma_2 = 0.194$ Uncertainty = $20\text{Log}(1-\Gamma_1*\Gamma_2)$	+0.34 / -0.35	U-Shape	0.244	1	0.244
Combined Standard Uncertainty $U_c(y)$	2.36				
Measuring Uncertainty for a Level of Confidence of 95% ($U = 2U_c(y)$)	4.72				



Appendix A. Photographs of EUT

Please refer to Sporton report number EP131909 as below.