



FCC ID: WWMAN401XV1

AUDIX Technology (Shenzhen) Co., Ltd.

FCC PART 15C TEST REPORT FOR CERTIFICATION  
On Behalf of

Proware Technologies Co., Ltd.

150M Wireless Lite-N Access Point

Model Number: PW-AN401D / M-WA701ND

FCC ID: WWMAN401XV1

Prepared for : Proware Technologies Co., Ltd.  
2<sup>nd</sup> F1 East Wing, South Section, Factory Building 24,  
Science&Technology Park, Shennan Rd, Nanshan  
District, Shenzhen

Prepared By : Audix Technology (Shenzhen) Co., Ltd.  
No. 6, Ke Feng Rd., 52 Block,  
Shenzhen Science & Industrial Park,  
Nantou, Shenzhen, Guangdong, China

Tel: (0755) 26639496

Report Number : ACS-F10283  
Date of Test : Aug.25~Sep.17, 2010  
Date of Report : Sep.25, 2010

## TABLE OF CONTENTS

Description	Page
<b>1. SUMMARY OF STANDARDS AND RESULTS.....</b>	<b>1-1</b>
1.1. Description of Standards and Results .....	1-1
<b>2. GENERAL INFORMATION .....</b>	<b>2-1</b>
2.1. Description of Device (EUT) .....	2-1
2.2. Test Information.....	2-2
2.3. Tested Supporting System Details .....	2-2
2.4. Block diagram of connection between the EUT and simulators .....	2-3
2.5. Test Facility .....	2-3
2.6. Measurement Uncertainty (95% confidence levels, k=2) .....	2-4
<b>3. POWER LINE CONDUCTED EMISSION TEST .....</b>	<b>3-1</b>
3.1. Test Equipments.....	3-1
3.2. Block Diagram of Test Setup.....	3-1
3.3. Power Line Conducted Emission Test Limits.....	3-1
3.4. Configuration of EUT on Test .....	3-2
3.5. Operating Condition of EUT.....	3-2
3.6. Test Procedure.....	3-2
3.7. Power Line Conducted Emission Test Results .....	3-2
<b>4. RADIATED EMISSION TEST .....</b>	<b>4-1</b>
4.1. Test Equipment .....	4-1
4.2. Block Diagram of Test Setup.....	4-1
4.3. Radiated Emission Limit.....	4-2
4.4. EUT Configuration on Test.....	4-3
4.5. Operating Condition of EUT.....	4-3
4.6. Test Procedure.....	4-3
4.7. Radiated Emission Test Results .....	4-4
<b>5. CONDUCTED SPURIOUS EMISSIONS.....</b>	<b>5-1</b>
5.1. Test Equipment .....	5-1
5.2. Limit.....	5-1
5.3. Test Procedure.....	5-1
5.4. Test result.....	5-1
<b>6. BAND EDGE COMPLIANCE TEST .....</b>	<b>6-1</b>
6.1. Test Equipment .....	6-1
6.2. Limit.....	6-1
6.3. Test Produce .....	6-1
6.4. Test Results .....	6-1
<b>7. 6dB Bandwidth Test.....</b>	<b>7-1</b>
7.1. Test Equipment .....	7-1
7.2. Limit.....	7-1
7.3. Test Procedure.....	7-1
7.4. Test Results .....	7-1
<b>8. OUTPUT POWER TEST.....</b>	<b>8-1</b>
8.1. Test Equipment .....	8-1
8.2. Limit (FCC Part 15C 15.247 b(3)).....	8-1
8.3. Test Procedure.....	8-1

8.4.	Test Results .....	8-2
<b>9.</b>	<b>POWER SPECTRAL DENSITY TEST .....</b>	<b>9-1</b>
9.1.	Test Equipment .....	9-1
9.2.	Limit.....	9-1
9.3.	Test Procedure.....	9-1
9.4.	Test Results .....	9-2
<b>10.</b>	<b>ANTENNA REQUIREMENT .....</b>	<b>10-1</b>
<b>11.</b>	<b>DEVIATION TO TEST SPECIFICATIONS.....</b>	<b>11-1</b>
<b>12.</b>	<b>PHOTOGRAPH OF TEST .....</b>	<b>12-1</b>
12.1.	Photos of Power Line Conducted Emission Test.....	12-1
12.2.	Photos of Radiated Emission Test.....	12-3
<b>13.</b>	<b>PHOTOGRAPH OF EUT .....</b>	<b>13-1</b>

## TEST REPORT CERTIFICATION

Applicant : Proware Technologies Co., Ltd.  
Manufacturer : Proware Technologies Co., Ltd.  
EUT Description : 150M Wireless Lite-N Access Point  
FCC ID : WWMAN401XV1  
(A) MODEL NO. : PW-AN401D / M-WA701ND  
(B) SERIAL NO. : N/A  
(C) POWER SUPPLY : DC 9V  
(D) TEST VOLTAGE : DC 9V From Adapter Input AC 120V/60Hz

Tested for comply with:  
FCC Rules and Regulations Part 15 Subpart C:2008

Test procedure used:  
ANSI C63.10:2009

The device described above is tested by AUDIX TECHNOLOGY (SHENZHEN) CO., LTD. to confirm comply with all the FCC Part 15 Subpart C requirements.

The test results are contained in this test report and AUDIX TECHNOLOGY (SHENZHEN) CO., LTD. is assumed full responsibility for the accuracy and completeness of these tests. Also, this report shows that the Equipment Under Test (EUT) is to be technically compliant with the FCC requirements.

This report applies to above tested sample only. This report shall not be reproduced in part without written approval of AUDIX TECHNOLOGY (SHENZHEN) CO., LTD.

Date of Test : Aug.25~ Sep.17, 2010 Report of date: Sep.25,2010

Prepared by : Celia Feng Reviewer by : Jamy Yu  
Celia Feng / Assistant Jamy Yu / Supervisor

Approved & Authorized Signer : \_\_\_\_\_



Ken Lu / Manager

## 1. SUMMARY OF STANDARDS AND RESULTS

### 1.1. Description of Standards and Results

The EUT have been tested according to the applicable standards as referenced below.

EMISSION		
Description of Test Item	Standard	Results
Power Line Conducted Emission	FCC Part 15: 15.207 ANSI C63.10: 2009	PASS
Radiated Emission	FCC Part 15: 15.209 ANSI C63.10: 2009	PASS
Band Edge Compliance	FCC Part 15: 15.247 ANSI C63.10: 2009	PASS
Conducted spurious emissions	FCC Part 15: 15.247 ANSI C63.10: 2009	PASS
6dB Bandwidth	FCC Part 15: 15.247 ANSI C63.10: 2009	PASS
Peak Output Power	FCC Part 15: 15.247 ANSI C63.10: 2009	PASS
Power Spectral Density	FCC Part 15: 15.247 ANSI C63.10: 2009	PASS
Antenna requirement	FCC Part 15: 15.203	PASS

## 2. GENERAL INFORMATION

### 2.1. Description of Device (EUT)

Product Name	:	150M Wireless Lite-N Access Point
Model Number	:	PW-AN401D / M-WA701ND Note: This device will use this two model numbers, and the fact device is same, there is no any difference of this two model numbers.
FCC ID	:	WWMAN401XV1
Operation Frequency	:	IEEE 802.11b: 2412MHz—2462MHz IEEE 802.11g: 2412MHz—2462MHz IEEE 802.11n HT20: 2412MHz—2462MHz IEEE 802.11n HT40: 2422MHz—2452MHz
Channel Number	:	IEEE 802.11b/g, IEEE 802.11n HT20: 11 Channels IEEE 802.11n HT40: 7Channels
Modulation Technology	:	IEEE 802.11b: DSSS(CCK,DQPSK,DBPSK) IEEE 802.11g: OFDM(64QAM, 16QAM, QPSK, BPSK) IEEE 802.11n HT20, HT40: OFDM (64QAM, 16QAM, QPSK,BPSK)
Antenna Assembly Gain	:	Dipole Antenna, 4dBi Gain
Applicant	:	Proware Technologies Co., Ltd. 2 <sup>nd</sup> F1 East Wing, South Section, Factory Building 24, Science&Technology Park, Shennan Rd, Nanshan District, Shenzhen
Manufacturer	:	Proware Technologies Co., Ltd. 2nd F1 East Wing, South Section, Factory Building 24, Science&Technology Park, Shennan Rd, Nanshan District, Shenzhen
Power Adapter	:	Manufacturer: LEADER ELECTRONICS INC. M/N: MU08-6090085-A1 Cable: Unshielded, Undetachable, 1.5m
Date of Test	:	Aug.25~Sep.17, 2010
Date of Receipt	:	Aug.24, 2010
Sample Type	:	Prototype production

## 2.2. Test Information

A special test software was used to control EUT work in Continuous TX mode(100% duty cycle), and select test channel, wireless mode and data rate.

Tested mode, channel, and data rate information			
Mode	data rate (Mbps)(see Note)	Channel	Frequency (MHz)
IEEE 802.11b	11	Low :CH1	2412
	11	Middle: CH6	2437
	11	High: CH11	2462
IEEE 802.11g	54	Low :CH1	2412
	54	Middle: CH6	2437
	54	High: CH11	2462
IEEE 802.11n HT20	6.5	Low :CH1	2412
	6.5	Middle: CH6	2437
	6.5	High: CH11	2462
IEEE 802.11n HT40	13.5	Low :CH1	2422
	13.5	Middle: CH4	2437
	13.5	High: CH7	2452


Note: According exploratory test, EUT will have maximum output power in those data rate, so those data rate were used for all test.

Note: This EUT can powered from adapter directly or from adapter though POE, according to exploratory test, for radiated emissions and power line conducted emissions test, when powered by POE will have worse emissions, so the final test for radiated emissions and power line conducted emissions test were performed with POE. And for all other RF conducted tests, there is no any influence with that two power methods, so all the RF conducted tests were only performed without POE.

## 2.3. Tested Supporting System Details

No.	Description	ACS No.	Manufacturer	Model	Serial Number	Approved type
1	Notebook	-	DELL	PP09S	N/A	<input checked="" type="checkbox"/> FCC DoC <input checked="" type="checkbox"/> BSMI ID: R41108
Power Cord: Unshielded, Detachable, 1.8m Power Adapter: Manufacturer: DELL, M/N: LA65NS1-00 Cable: Unshielded, Detachable, 4.0m(Bond one ferrite core)						

### 2.4. Block diagram of connection between the EUT and simulators



### 2.5. Test Facility

#### Site Description

- |                           |   |  |
|---------------------------|---|--|
| Name of Firm              | : | Audix Technology (Shenzhen) Co., Ltd.<br>No. 6, Ke Feng Rd., 52 Block, Shenzhen<br>Science & Industrial Park, Nantou,<br>Shenzhen, Guangdong, China  |
| 3m Anechoic Chamber       | : | Mar.31, 2009 File on Federal<br>Communication Commission<br>Registration Number: 90454   |
| 3m & 10m Anechoic Chamber | : | Dec. 30, 2009 File on Federal<br>Communication Commission<br>Registration Number: 794232   |
| EMC Lab.                  | : | Certificated by Industry Canada<br>Registration Number: IC 5183A-1<br>Jul. 03, 2009<br>:<br>Accredited by DATech, German<br>Registration Number: DAT-P-091/99-01<br>Feb. 02, 2009<br>Accredited by NVLAP, USA<br>NVLAP Code: 200372-0<br>Apr. 01, 2010 |



2.6.Measurement Uncertainty (95% confidence levels, k=2)


Test Item	Uncertainty
Uncertainty for Conduction emission test in No. 1 Conduction	3.64 dB (9kHz to 150kHz)
	3.22 dB(150kHz to 30MHz)
Uncertainty for Radiation Emission test in 3m chamber	4.20 dB (Polarize: V)
	4.66 dB (Polarize: H)
Uncertainty for Radiated Spurious Emission test in RF chamber	2.70 dB(Bilog antenna 30M~1000MHz)
	2.27 dB(Horn antenna 1000M~12750MHz)
Uncertainty for Conduction Spurious emission test	2.12 dB
Uncertainty for Output power test	0.97 dB
Uncertainty for Power density test	2.21 dB
Uncertainty for Frequency range test	$1 \times 10^{-9}$
Uncertainty for Bandwidth test	$1 \times 10^{-9}$
Uncertainty for DC power test	0.038 %
Uncertainty for test site temperature and humidity	0.3°C
	2%

### 3. POWER LINE CONDUCTED EMISSION TEST

#### 3.1. Test Equipments

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	Test Receiver	Rohde & Schwarz	ESHS10	838693/001	Dec.18, 09	1 Year
2.	L.I.S.N.#1	Rohde & Schwarz	ESH2-Z5	834066/011	Mar.30, 10	1 Year
3.	Terminator	Hubersuhner	50Ω	No. 1	May.08, 10	1 Year
4.	Terminator	Hubersuhner	50Ω	No. 2	May.08, 10	1 Year
5.	RF Cable	Fujikura	3D-2W	LISN Cable 1#	May.08, 10	1 Year
6.	Coaxial Switch	Anritsu	MP59B	M55367	May.08, 10	1 Year
7.	Passive Probe	Rohde & Schwarz	ESH2-Z3	299.7810.52	May.08, 10	1 Year
8.	Pulse Limiter	Rohde & Schwarz	ESH3-Z2	100341	May.08, 10	1 Year

#### 3.2. Block Diagram of Test Setup



#### 3.3. Power Line Conducted Emission Test Limits

Frequency	Maximum RF Line Voltage	
	Quasi-Peak Level dB(μV)	Average Level dB(μV)
150kHz ~ 500kHz	66 ~ 56*	56 ~ 46*
500kHz ~ 5MHz	56	46
5MHz ~ 30MHz	60	50

Notes: 1. \* Decreasing linearly with logarithm of frequency.

2. The lower limit shall apply at the transition frequencies.

### 3.4. Configuration of EUT on Test

The following equipment are installed on Power Line Conducted Emission Test to meet the commission requirement and operating regulations in a manner which tends to maximize its emission characteristics in a normal application.

#### 3.4.1. 150M Wireless Lite-N Access Point (EUT)

Model Number : PW-AN401D / M-WA701ND

Serial Number : N/A

3.4.2. Support Equipment : As Tested Supporting System Details, in Section 2.3.

### 3.5. Operating Condition of EUT

3.5.1. Setup the EUT and simulator as shown as Section 2.4.

3.5.2. Turned on the power of all equipment.

3.5.3. PC run test software to control EUT work in Tx mode.

### 3.6. Test Procedure


The EUT was placed on a non-metallic table, 80cm above the ground plane. The EUT Power Via Notebook connected to the power mains through a line impedance stabilization network (L.I.S.N. 1#). This provides a 50 ohm coupling impedance for the EUT (Please refer the block diagram of the test setup and photographs). The AC line are checked to find out the maximum conducted emission. In order to find the maximum emission levels, the relative positions of equipment and all of the interface cables shall be changed according to ANSI C63.10: 2009 on Conducted Emission Test.

The bandwidth of test receiver (R & S ESHS10) is set at 10kHz.

The frequency range from 150kHz to 30MHz is checked.

### 3.7. Power Line Conducted Emission Test Results

**PASS.** (All emissions not reported below are too low against the prescribed limits.)




Trace: (Discrete)

Site no :1#conduction Data No :5  
 Dis./Ant. :\*\* 2010 ESH2-25 LINE  
 Limit :FCC PART 15 C  
 Env./Ins. :29.5°C/55% Engineer :Sunny-lu  
 EUT :150M Wireless Lite-N Access Point  
 Power Rating :DC 9V From Adapter Input AC 230V/50Hz  
 Test Mode :Tx Mode  
 :PW-AN401D/M-WA701ND  
 NO POE

No	Freq (MHz)	LISN Factor (dB)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV)	Limits (dBuV)	Margin (dB)	Remark
1	0.59775	0.25	9.88	22.89	33.02	46.00	12.98	Average
2	0.59775	0.25	9.88	34.98	45.11	56.00	10.89	QP
3	0.74700	0.25	9.89	23.56	33.70	46.00	12.30	Average
4	0.74700	0.25	9.89	33.92	44.06	56.00	11.94	QP
5	0.86640	0.23	9.89	24.63	34.75	46.00	11.25	Average
6	0.86640	0.23	9.89	37.04	47.16	56.00	8.84	QP
7	1.016	0.22	9.89	23.79	33.90	46.00	12.10	Average
8	1.016	0.22	9.89	35.90	46.01	56.00	9.99	QP
9	13.374	0.49	10.02	28.02	38.53	50.00	11.47	Average
10	13.374	0.49	10.02	38.85	49.36	60.00	10.64	QP
11	14.150	0.50	10.03	30.58	41.11	50.00	8.89	Average
12	14.150	0.50	10.03	39.15	49.68	60.00	10.32	QP

Remarks: 1. Emission Level=LISN Factor+Cable Loss (Include 10dB pulse limit)+Reading.  
 2. If the average limit is met when using a quasi-peak detector, the EUT shall be deemed to meet both limits and measurement with average detector is unnecessary.




Trace: (Discrete)

Site no :1#conduction Data No :4  
 Dis./Ant. :\*\* 2010 ESH2-Z5 NEUTRAL  
 Limit :FCC PART 15 C  
 Env./Ins. :29.5°C/55% Engineer :Sunny-lu  
 EUT :150M Wireless Lite-N Access Point  
 Power Rating :DC 9V From Adapter Input AC 230V/50Hz  
 Test Mode :Tx Mode  
 :PW-AN401D/M-WA701ND  
 NO POE

No	Freq (MHz)	LISN Factor (dB)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV)	Limits (dBuV)	Margin (dB)	Remark
1	0.56790	0.23	9.88	22.80	32.91	46.00	13.09	Average
2	0.56790	0.23	9.88	34.80	44.91	56.00	11.09	QP
3	0.71715	0.24	9.89	25.45	35.58	46.00	10.42	Average
4	0.71715	0.24	9.89	38.41	48.54	56.00	7.46	QP
5	1.016	0.25	9.89	22.48	32.62	46.00	13.38	Average
6	1.016	0.25	9.89	35.87	46.01	56.00	9.99	QP
7	1.881	0.26	9.90	23.45	33.61	46.00	12.39	Average
8	1.881	0.26	9.90	35.89	46.05	56.00	9.95	QP
9	13.374	0.55	10.02	27.75	38.32	50.00	11.68	Average
10	13.374	0.55	10.02	37.79	48.36	60.00	11.64	QP
11	14.150	0.56	10.03	29.42	40.01	50.00	9.99	Average
12	14.150	0.56	10.03	38.09	48.68	60.00	11.32	QP

Remarks: 1. Emission Level=LISN Factor+Cable Loss(Include 10dB pulse limit)+Reading.  
 2. If the average limit is met when using a quasi-peak detector, the EUT shall be deemed to meet both limits and measurement with average detector is unnecessary.




Trace: (Discrete)

Site no :1#conduction Data No :1  
 Dis./Ant. :\*\* 2010 ESH2-Z5 LINE  
 Limit :FCC PART 15 C  
 Env./Ins. :29.5\*C/55% Engineer :Sunny-lu  
 EUT :150M Wireless Lite-N Access Point  
 Power Rating :DC 9V From Adapter Input AC 120V/60Hz  
 Test Mode :Tx Mode  
 :PW-AN401D/M-WA701ND  
 Add POE

No	Freq (MHz)	LISN Factor (dB)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV)	Limits (dBuV)	Margin (dB)	Remark
1	0.68730	0.25	9.89	28.25	38.39	46.00	7.61	Average
2	0.68730	0.25	9.89	36.53	46.67	56.00	9.33	QP
3	12.806	0.47	10.02	31.45	41.94	50.00	8.06	Average
4	12.806	0.47	10.02	38.94	49.43	60.00	10.57	QP
5	13.433	0.49	10.02	30.28	40.79	50.00	9.21	Average
6	13.433	0.49	10.02	41.83	52.34	60.00	7.66	QP
7	14.150	0.50	10.03	30.83	41.36	50.00	8.64	Average
8	14.150	0.50	10.03	41.55	52.08	60.00	7.92	QP
9	16.209	0.51	10.04	28.58	39.13	50.00	10.87	Average
10	16.209	0.51	10.04	39.15	49.70	60.00	10.30	QP
11	26.120	0.92	10.13	26.74	37.79	50.00	12.21	Average
12	26.120	0.92	10.13	35.08	46.13	60.00	13.87	QP

Remarks: 1. Emission Level=LISN Factor+Cable Loss(Include 10dB pulse limit)+Reading.  
 2. If the average limit is met when using a quasi-peak detector, the EUT shall be deemed to meet both limits and measurement with average detector is unnecessary.



Trace: (Discrete)

Site no :1#conduction Data No :2  
 Dis./Ant. :\*\* 2010 ESH2-Z5 NEUTRAL  
 Limit :FCC PART 15 C  
 Env./Ins. :29.5\*C/55% Engineer :Sunny-lu  
 EUT :150M Wireless Lite-N Access Point  
 Power Rating :DC 9V From Adapter Input AC 120V/60Hz  
 Test Mode :Tx Mode  
 :PW-AN401D/M-WA701ND  
 Add POE

No	Freq (MHz)	LISN Factor (dB)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV)	Limits (dBuV)	Margin (dB)	Remark
1	0.59775	0.23	9.88	25.89	36.00	46.00	10.00	Average
2	0.59775	0.23	9.88	36.00	46.11	56.00	9.89	QP
3	0.71715	0.24	9.89	28.42	38.55	46.00	7.45	Average
4	0.71715	0.24	9.89	39.41	49.54	56.00	6.46	QP
5	0.86640	0.25	9.89	26.95	37.09	46.00	8.91	Average
6	0.86640	0.25	9.89	37.02	47.16	56.00	8.84	QP
7	1.016	0.25	9.89	25.96	36.10	46.00	9.90	Average
8	1.016	0.25	9.89	36.87	47.01	56.00	8.99	QP
9	13.374	0.55	10.02	27.75	38.32	50.00	11.68	Average
10	13.374	0.55	10.02	37.79	48.36	60.00	11.64	QP
11	14.150	0.56	10.03	28.84	39.43	50.00	10.57	Average
12	14.150	0.56	10.03	38.09	48.68	60.00	11.32	QP

Remarks: 1. Emission Level=LISN Factor+Cable Loss(Include 10dB pulse limit)+Reading.  
 2. If the average limit is met when using a quasi-peak detector, the EUT shall be deemed to meet both limits and measurement with average detector is unnecessary.

## 4. RADIATED EMISSION TEST

### 4.1. Test Equipment

Frequency rang: 30~1000MHz


Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1	3#Chamber	AUDIX	N/A	N/A	Dec.05,09	1 Year
2	EMI Spectrum	Agilent	E4407B	MY41440292	May.08, 10	1 Year
3	Test Receiver	Rohde & Schwarz	ESVS10	834468/011	May.08, 10	1 Year
4	Amplifier	HP	8447D	2648A04738	May.08, 10	1 Year
5	Bilog Antenna	Schaffner	CBL6111C	2598	Dec.14, 09	1 Year
6	RF Cable	MIYAZAKI	8D-FB	3# Chamber No.1	May.08, 10	1 Year
7	Coaxial Switch	Anritsu	MP59B	M73989	May.08, 10	1 Year

Frequency rang: above 1000MHz

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1	Spectrum Analyzer	Agilent	E4446A	US44300459	May.08, 10	1 Year
2	Horn Antenna	EMCO	3115	9607-4877	Nov.25, 09	1.5 Year
3	Horn Antenna	EMCO	3116	00060089	Nov.25, 09	1.5 Year
4	Amplifier	Agilent	8449B	3008A00863	May.08, 10	1 Year
5	RF Cable	Hubersuhner	SUCOFLEX102	28620/2	May.08, 10	1 Year
6	RF Cable	Hubersuhner	SUCOFLEX102	29091/2	May.08, 10	1 Year


### 4.2. Block Diagram of Test Setup

For frequency range 30MHz-1000MHz





For frequency range 1GHz-6GHz



### 4.3. Radiated Emission Limit

#### 4.3.1. 15.209 limits

FREQUENCY MHz	DISTANCE Meters	FIELD STRENGTHS LIMIT	
		$\mu\text{V}/\text{m}$	$\text{dB}(\mu\text{V})/\text{m}$
30 ~ 88	3	100	40.0
88 ~ 216	3	150	43.5
216 ~ 960	3	200	46.0
960 ~ 1000	3	500	54.0
Above 1000	3	74.0 $\text{dB}(\mu\text{V})/\text{m}$ (Peak) 54.0 $\text{dB}(\mu\text{V})/\text{m}$ (Average)	

- Remark :
- (1) Emission level  $\text{dB}\mu\text{V} = 20 \log$  Emission level  $\mu\text{V}/\text{m}$
  - (2) The smaller limit shall apply at the cross point between two frequency bands.
  - (3) Distance is the distance in meters between the measuring instrument, antenna and the closest point of any part of the device or system.

4.3.2. 15.205 Restricted bands of operation

MHz	MHz	MHz	GHz
0.090 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
<sup>1</sup> 0.495 - 0.505	16.69475 - 16.69525	608 - 614	5.35 - 5.46
2.1735 - 2.1905	16.80425 - 16.80475	960 - 1240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1300 - 1427	8.025 - 8.5
4.17725 - 4.17775	37.5 - 38.25	1435 - 1626.5	9.0 - 9.2
4.20725 - 4.20775	73 - 74.6	1645.5 - 1646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1660 - 1710	10.6 - 12.7
6.26775 - 6.26825	108 - 121.94	1718.8 - 1722.2	13.25 - 13.4
6.31175 - 6.31225	123 - 138	2200 - 2300	14.47 - 14.5
8.291 - 8.294	149.9 - 150.05	2310 - 2390	15.35 - 16.2
8.362 - 8.366	156.52475 - 156.52525	2483.5 - 2500	17.7 - 21.4
8.37625 - 8.38675	156.7 - 156.9	2690 - 2900	22.01 - 23.12
8.41425 - 8.41475	162.0125 - 167.17	3260 - 3267	23.6 - 24.0
12.29 - 12.293	167.72 - 173.2	3332 - 3339	31.2 - 31.8
12.51975 - 12.52025	240 - 285	3345.8 - 3358	36.43 - 36.5
12.57675 - 12.57725	322 - 335.4	3600 - 4400	( <sup>2</sup> )

All the emissions appearing within 15.205 restricted frequency bands shall not exceed the limits shown in 15.209, all the other emissions shall be at least 20dB below the fundamental emissions, or comply with 15.209 limits.

4.4.EUT Configuration on Test

The following equipment are installed on Radiated Emission Test to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

4.4.1. 150M Wireless Lite-N Access Point (EUT)

Model Number : PW-AN401D / M-WA701ND  
 Serial Number : N/A

4.4.2. Support Equipment : As Tested Supporting System Details, in Section 2.3.

4.5.Operating Condition of EUT

4.5.1. Setup the EUT and simulator as shown as Section 2.4.

4.5.2. Turned on the power of all equipment.

4.5.3. PC run test software to control EUT work in test mode.

4.6.Test Procedure

EUT and its simulators are placed on a turn table, which is 0.8 meter high above ground. The turn table can rotate 360 degrees to determine the position of the maximum emission level. Power on the EUT and let it working in test mode, then test it. EUT is set 3 meters away from the receiving antenna, which is mounted on a antenna tower. The antenna can be moved up and down between 1 meter and 4 meters to find out the maximum emission level. Broadband antenna (calibrated bilog antenna) is used as receiving antenna. Both horizontal and vertical polarization of the antenna are set on test.

The bandwidth of the EMI test receiver (R&S ESVS10) is set at 120kHz for frequency range from 30MHz to 1000 MHz.

The bandwidth of the Spectrum's VBW is set at 3MHz and RBW is set at 1MHz for peak emissions measurement above 1GHz and 1MHz RBW, 10Hz VBW for average emissions measure above 1GHz

The frequency range from 30MHz to 10<sup>th</sup> harmonic (25GHz) are checked. and no any emissions were found from 18GHz to 25 GHz, So the radiated emissions from 18GHz to 25GHz were not record.

#### 4.7. Radiated Emission Test Results

**PASS.**

All the emissions from 30MHz to 25 GHz were comply with 15.209 limits.


Note: For emissions above 1GHz, if peak level comply with average limit, then the average level is deemed to comply with average limit.

**Frequency: 30MHz~1GHz**

Data: 3

File: E:\2010 Report Data\P\ACS10Q1499.EM6 (4)


Date: 2010-09-25



Site no. : 3m Chamber Data no. : 3  
 Dis. / Ant. : 3m 2010 CBL6111C Ant. pol. : HORIZONTAL  
 Limit : FCC PART 15 C (3M)  
 Env. / Ins. : 24°C/56% Engineer : Sunny-lu  
 EUT : 150M Wireless Lite-N Access Point  
 Power rating : DC 9V From Adapter input AC 120V/50Hz  
 Test Mode : Tx Mode  
 M-WA701ND/PW-AN401D  
 NO POE

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	30.000	20.00	0.61	9.37	29.98	40.00	10.02	QP
2	59.100	6.22	0.84	19.15	26.21	40.00	13.79	QP
3	350.100	15.10	2.70	15.98	33.78	46.00	12.22	QP
4	524.700	18.35	3.69	7.97	30.01	46.00	15.99	QP
5	701.240	20.79	4.50	16.68	41.97	46.00	4.03	QP
6	892.330	22.88	5.18	12.36	40.42	46.00	5.58	QP


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading.  
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 4  
 Dis. / Ant. : 3m 2010 CBL6111C Ant. pol. : VERTICAL  
 Limit : FCC PART 15 C (3M)  
 Env. / Ins. : 24°C/56% Engineer : Sunny-lu  
 EUT : 150M Wireless Lite-N Access Point  
 Power rating : DC 9V From Adapter input AC 120V/50Hz  
 Test Mode : Tx Mode  
 M-WA701ND/PW-AN401D  
 NO POE

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	30.000	20.00	0.61	13.28	33.89	40.00	6.11	QP
2	131.850	12.16	1.13	23.50	36.79	43.50	6.71	QP
3	175.500	9.65	1.44	23.24	34.33	43.50	9.17	QP
4	350.100	15.10	2.70	11.95	29.75	46.00	16.25	QP
5	516.940	18.37	3.64	10.46	32.47	46.00	13.53	QP
6	701.240	20.79	4.50	14.20	39.49	46.00	6.51	QP


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading.  
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 2  
 Dis. / Ant. : 3m 2010 CBL6111C Ant. pol. : HORIZONTAL  
 Limit : FCC PART 15 C (3M)  
 Env. / Ins. : 24°C/56% Engineer : Sunny-lu  
 EUT : 150M Wireless Lite-N Access Point  
 Power rating : DC 9V From Adapter input AC 120V/50Hz  
 Test Mode : Tx Mode  
 M-WA701ND/PW-AN401D  
 Add POE

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	30.000	20.00	0.61	14.37	34.98	40.00	5.02	QP
2	59.100	6.22	0.84	22.08	29.14	40.00	10.86	QP
3	350.100	15.10	2.70	15.74	33.54	46.00	12.46	QP
4	524.700	18.35	3.69	10.97	33.01	46.00	12.99	QP
5	701.240	20.79	4.50	16.58	41.87	46.00	4.13	QP
6	891.360	22.89	5.17	13.68	41.74	46.00	4.26	QP

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading.  
 2. The emission levels that are 20dB below the official limit are not reported.




Site no. : 3m Chamber Data no. : 1  
 Dis. / Ant. : 3m 2010 CBL6111C Ant. pol. : VERTICAL  
 Limit : FCC PART 15 C (3M)  
 Env. / Ins. : 24°C/56% Engineer : Sunny-lu  
 EUT : 150M Wireless Lite-N Access Point  
 Power rating : DC 9V From Adapter input AC 120V/50Hz  
 Test Mode : Tx Mode  
 M-WA701ND/PW-AN401D  
 Add POE

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	30.000	20.00	0.61	15.46	36.07	40.00	3.93	QP
2	131.850	12.16	1.13	26.66	39.95	43.50	3.55	QP
3	175.500	9.65	1.44	26.48	37.57	43.50	5.93	QP
4	264.740	13.80	2.26	13.50	29.56	46.00	16.44	QP
5	524.700	18.35	3.69	12.47	34.51	46.00	11.49	QP
6	701.240	20.79	4.50	13.91	39.20	46.00	6.80	QP

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading.  
 2. The emission levels that are 20dB below the official limit are not reported.

**Frequency: 1GHz~18GHz**




Site no. : 10m Chamber Data no. : 1  
 Dis. / Ant. : 3m 3115(0911) Ant. pol. : HORIZONTAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 23°C/54% Engineer : Sunny-lu  
 EUT : 150M Wireless Lite-N Access Point  
 Power : DC 9V From Adapter Input AC 120V/60Hz  
 Test mode : IEEE802.11b CH1 2412MHz Tx  
 M/N : PW-AN401D/M-WA701ND

	Ant. Freq. (MHz)	Ant. Factor (dB/m)	Cable loss (dB)	Amp. Factor (dB)	Emission Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	1051.000	25.50	5.60	37.34	46.82	40.58	74.00	33.42	Peak
2	1399.000	26.19	6.49	36.69	44.87	40.86	74.00	33.14	Peak
3	1750.000	27.80	7.33	36.29	40.31	39.15	74.00	34.85	Peak
4	2412.000	29.45	8.72	35.95	96.38	98.60	74.00	-24.60	Peak

Remarks:

1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.






```

Site no.      : 10m Chamber           Data no.   : 2
Dis. / Ant.  : 3m 3115(0911)        Ant. pol.  : VERTICAL
Limit        : FCC PART 15C PEAK
Env. / Ins.  : 23*C/54%             Engineer   : Sunny-lu
EUT          : 150M Wireless Lite-N Access Point
Power        : DC 9V From Adapter Input AC 120V/60Hz
Test mode    : IEEE802.11b CH1 2412MHz Tx
M/N          : PW-AN401D/M-WA701ND
    
```


	Ant. Freq. (MHz)	Ant. Factor (dB/m)	Cable loss (dB)	Amp. Factor (dB)	Emission Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	1051.000	25.50	5.60	37.34	46.82	40.58	74.00	33.42	Peak
2	1399.000	26.19	6.49	36.69	45.94	41.93	74.00	32.07	Peak
3	1750.000	27.80	7.33	36.29	44.53	43.37	74.00	30.63	Peak
4	2412.000	29.45	8.72	35.95	108.67	110.89	74.00	-36.89	Peak

Remarks:

1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 10m Chamber Data no. : 3  
Dis. / Ant. : 3m 3115(0911) Ant. pol. : HORIZONTAL  
Limit : FCC PART 15C PEAK  
Env. / Ins. : 23°C/54% Engineer : Sunny-lu  
EUT : 150M Wireless Lite-N Access Point  
Power : DC 9V From Adapter Input AC 120V/60Hz  
Test mode : IEEE802.11b CH1 2412MHz Tx  
M/N : PW-AN401D/M-WA701ND




Site no. : 10m Chamber Data no. : 4  
 Dis. / Ant. : 3m 3115(0911) Ant. pol. : HORIZONTAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 23°C/54% Engineer : Sunny-lu  
 EUT : 150M Wireless Lite-N Access Point  
 Power : DC 9V From Adapter Input AC 120V/60Hz  
 Test mode : IEEE802.11b CH1 2412MHz Tx  
 M/N : PW-AN401D/M-WA701ND


	Ant.	Cable	Amp.	Emission					
Freq.	Factor	loss	Factor	Reading	Level	Limits	Margin	Remark	
(MHz)	(dB/m)	(dB)	(dB)	(dBuV)	(dBuV/m)	(dBuV/m)	(dB)		
1	4824.000	34.32	12.38	35.25	42.36	53.81	74.00	20.19	Peak
2	4824.000	34.32	12.38	35.25	35.12	46.57	54.00	7.43	Average

Remarks:

1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 10m Chamber Data no. : 5  
Dis. / Ant. : 3m 3115(0911) Ant. pol. : VERTICAL  
Limit : FCC PART 15C PEAK  
Env. / Ins. : 23°C/54% Engineer : Sunny-lu  
EUT : 150M Wireless Lite-N Access Point  
Power : DC 9V From Adapter Input AC 120V/60Hz  
Test mode : IEEE802.11b CH1 2412MHz Tx  
M/N : PW-AN401D/M-WA701ND




Site no. : 10m Chamber Data no. : 6  
 Dis. / Ant. : 3m 3115(0911) Ant. pol. : VERTICAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 23°C/54% Engineer : Sunny-lu  
 EUT : 150M Wireless Lite-N Access Point  
 Power : DC 9V From Adapter Input AC 120V/60Hz  
 Test mode : IEEE802.11b CH1 2412MHz Tx  
 M/N : PW-AN401D/M-WA701ND

	Ant. Freq. (MHz)	Ant. Factor (dB/m)	Cable loss (dB)	Amp. Factor (dB)	Emission Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	4824.000	34.32	12.38	35.25	43.64	55.09	74.00	18.91	Peak
2	4824.000	34.32	12.38	35.25	36.84	48.29	54.00	5.71	Average

Remarks:

1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.




Site no. : 10m Chamber Data no. : 7  
 Dis. / Ant. : 3m 3115(0911) Ant. pol. : VERTICAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 23\*C/54% Engineer : Sunny-lu  
 EUT : 150M Wireless Lite-N Access Point  
 Power : DC 9V From Adapter Input AC 120V/60Hz  
 Test mode : IEEE802.11b CH6 2437MHz Tx  
 M/N : PW-AN401D/M-WA701ND

	Ant. Freq. (MHz)	Ant. Factor (dB/m)	Cable loss (dB)	Amp. Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	1051.000	25.50	5.60	37.34	46.53	40.29	74.00	33.71	Peak
2	1399.000	26.19	6.49	36.69	45.62	41.61	74.00	32.39	Peak
3	1750.000	27.80	7.33	36.29	43.99	42.83	74.00	31.17	Peak
4	2437.000	29.47	8.77	36.06	108.49	110.67	74.00	-36.67	Peak

Remarks:

1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.




Site no. : 10m Chamber Data no. : 8  
 Dis. / Ant. : 3m 3115(0911) Ant. pol. : HORIZONTAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 23°C/54% Engineer : Sunny-lu  
 EUT : 150M Wireless Lite-N Access Point  
 Power : DC 9V From Adapter Input AC 120V/60Hz  
 Test mode : IEEE802.11b CH6 2437MHz Tx  
 M/N : PW-AN401D/M-WA701ND

	Ant. Freq. (MHz)	Ant. Factor (dB/m)	Cable loss (dB)	Amp. Factor (dB)	Emission Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	1051.000	25.50	5.60	37.34	47.72	41.48	74.00	32.52	Peak
2	1399.000	26.19	6.49	36.69	45.61	41.60	74.00	32.40	Peak
3	1750.000	27.80	7.33	36.29	42.42	41.26	74.00	32.74	Peak
4	2437.000	29.47	8.77	36.06	96.33	98.51	74.00	-24.51	Peak


Remarks:

1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.



Site no.	: 10m Chamber	Data no.	: 9
Dis. / Ant.	: 3m 3115(0911)	Ant. pol.	: HORIZONTAL
Limit	: FCC PART 15C PEAK		
Env. / Ins.	: 23°C/54%	Engineer	: Sunny-lu
EUT	: 150M Wireless Lite-N Access Point		
Power	: DC 9V From Adapter Input AC 120V/60Hz		
Test mode	: IEEE802.11b CH6 2437MHz Tx		
M/N	: PW-AN401D/M-WA701ND		







Site no. : 10m Chamber Data no. : 10  
 Dis. / Ant. : 3m 3115(0911) Ant. pol. : HORIZONTAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 23°C/54% Engineer : Sunny-lu  
 EUT : 150M Wireless Lite-N Access Point  
 Power : DC 9V From Adapter Input AC 120V/60Hz  
 Test mode : IEEE802.11b CH6 2437MHz Tx  
 M/N : PW-AN401D/M-WA701ND

	Ant. Freq. (MHz)	Ant. Factor (dB/m)	Cable loss (dB)	Amp. Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	4874.000	34.41	12.44	35.36	42.35	53.84	74.00	20.16	Peak
2	4874.000	34.41	12.44	35.36	35.94	47.43	54.00	6.57	Average

Remarks:  
 1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.  
 2. The emission levels that are 20dB below the official limit are not reported.




Site no.	: 10m Chamber	Data no.	: 11
Dis. / Ant.	: 3m 3115(0911)	Ant. pol.	: VERTICAL
Limit	: FCC PART 15C PEAK		
Env. / Ins.	: 23°C/54%	Engineer	: Sunny-lu
EUT	: 150M Wireless Lite-N Access Point		
Power	: DC 9V From Adapter Input AC 120V/60Hz		
Test mode	: IEEE802.11b CH6 2437MHz Tx		
M/N	: PW-AN401D/M-WA701ND		



Site no. : 10m Chamber Data no. : 12  
 Dis. / Ant. : 3m 3115(0911) Ant. pol. : VERTICAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 23°C/54% Engineer : Sunny-lu  
 EUT : 150M Wireless Lite-N Access Point  
 Power : DC 9V From Adapter Input AC 120V/60Hz  
 Test mode : IEEE802.11b CH6 2437MHz Tx  
 M/N : PW-AN401D/M-WA701ND

	Ant. Freq. (MHz)	Cable Factor (dB/m)	Amp. loss (dB)	Emission Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark	
1	4874.000	34.41	12.44	35.36	43.61	55.10	74.00	18.90	Peak
2	4874.000	34.41	12.44	35.36	36.94	48.43	54.00	5.57	Average

- Remarks:
1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
  2. The emission levels that are 20dB below the official limit are not reported.




Site no. : 10m Chamber Data no. : 13  
 Dis. / Ant. : 3m 3115(0911) Ant. pol. : VERTICAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 23\*C/54% Engineer : Sunny-lu  
 EUT : 150M Wireless Lite-N Access Point  
 Power : DC 9V From Adapter Input AC 120V/60Hz  
 Test mode : IEEE802.11b CH11 2462MHz Tx  
 M/N : PW-AN401D/M-WA701ND

	Ant. Freq. (MHz)	Ant. Factor (dB/m)	Cable loss (dB)	Amp. Factor (dB)	Emission Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	1399.000	26.19	6.49	36.69	44.88	40.87	74.00	33.13	Peak
2	1750.000	27.80	7.33	36.29	43.33	42.17	74.00	31.83	Peak
3	2462.000	29.48	8.82	36.02	110.52	112.80	74.00	-38.80	Peak

Remarks:

1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.




Site no. : 10m Chamber Data no. : 14  
 Dis. / Ant. : 3m 3115(0911) Ant. pol. : HORIZONTAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 23°C/54% Engineer : Sunny-lu  
 EUT : 150M Wireless Lite-N Access Point  
 Power : DC 9V From Adapter Input AC 120V/60Hz  
 Test mode : IEEE802.11b CH11 2462MHz Tx  
 M/N : PW-AN401D/M-WA701ND


	Ant. Freq. (MHz)	Factor (dB/m)	Cable loss (dB)	Amp. Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	1051.000	25.50	5.60	37.34	47.15	40.91	74.00	33.09	Peak
2	1399.000	26.19	6.49	36.69	44.37	40.36	74.00	33.64	Peak
3	1750.000	27.80	7.33	36.29	43.90	42.74	74.00	31.26	Peak
4	2026.000	29.21	7.97	36.12	47.12	48.18	74.00	25.82	Peak
5	2462.000	29.48	8.82	36.02	95.75	98.03	74.00	-24.03	Peak

Remarks:

1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.



Site no.	: 10m Chamber	Data no.	: 15
Dis. / Ant.	: 3m 3115(0911)	Ant. pol.	: VERTICAL
Limit	: FCC PART 15C PEAK		
Env. / Ins.	: 23°C/54%	Engineer	: Sunny-lu
EUT	: 150M Wireless Lite-N Access Point		
Power	: DC 9V From Adapter Input AC 120V/60Hz		
Test mode	: IEEE802.11b CH11 2462MHz Tx		
M/N	: PW-AN401D/M-WA701ND		




Site no. : 10m Chamber Data no. : 16  
 Dis. / Ant. : 3m 3115(0911) Ant. pol. : VERTICAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 23°C/54% Engineer : Sunny-lu  
 EUT : 150M Wireless Lite-N Access Point  
 Power : DC 9V From Adapter Input AC 120V/60Hz  
 Test mode : IEEE802.11b CH11 2462MHz Tx  
 M/N : PW-AN401D/M-WA701ND

	Ant. Freq. (MHz)	Ant. Factor (dB/m)	Cable loss (dB)	Amp. Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	4924.000	34.49	12.50	35.34	43.69	55.34	74.00	18.66	Peak
2	4924.000	34.49	12.50	35.34	37.19	48.84	54.00	5.16	Average


Remarks:

1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.



Site no.	: 10m Chamber	Data no.	: 17
Dis. / Ant.	: 3m 3115(0911)	Ant. pol.	: HORIZONTAL
Limit	: FCC PART 15C PEAK		
Env. / Ins.	: 23°C/54%	Engineer	: Sunny-lu
EUT	: 150M Wireless Lite-N Access Point		
Power	: DC 9V From Adapter Input AC 120V/60Hz		
Test mode	: IEEE802.11b CH11 2462MHz Tx		
M/N	: PW-AN401D/M-WA701ND		






Site no. : 10m Chamber Data no. : 18  
 Dis. / Ant. : 3m 3115(0911) Ant. pol. : HORIZONTAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 23°C/54% Engineer : Sunny-lu  
 EUT : 150M Wireless Lite-N Access Point  
 Power : DC 9V From Adapter Input AC 120V/60Hz  
 Test mode : IEEE802.11b CH11 2462MHz Tx  
 M/N : PW-AN401D/M-WA701ND

	Ant.	Cable	Amp.	Emission					
Freq.	Factor	loss	Factor	Reading	Level	Limits	Margin	Remark	
(MHz)	(dB/m)	(dB)	(dB)	(dBuV)	(dBuV/m)	(dBuV/m)	(dB)		
1 4924.000	34.49	12.50	35.34	42.68	54.33	74.00	19.67	Peak	
2 4924.000	34.49	12.50	35.34	36.75	48.40	54.00	5.60	Average	

Remarks:

1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.




Site no. : 10m Chamber Data no. : 19  
 Dis. / Ant. : 3m 3115(0911) Ant. pol. : HORIZONTAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 23\*C/54% Engineer : Sunny-lu  
 EUT : 150M Wireless Lite-N Access Point  
 Power : DC 9V From Adapter Input AC 120V/60Hz  
 Test mode : IEEE802.11g CH1 2412MHz Tx  
 M/N : PW-AN401D/M-WA701ND

	Ant. Freq. (MHz)	Ant. Factor (dB/m)	Cable loss (dB)	Amp. Factor (dB)	Emission Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	1051.000	25.50	5.60	37.34	46.65	40.41	74.00	33.59	Peak
2	1399.000	26.19	6.49	36.69	45.82	41.81	74.00	32.19	Peak
3	1846.000	28.36	7.51	36.23	48.27	47.91	74.00	26.09	Peak
4	2023.000	29.21	7.97	36.12	47.56	48.62	74.00	25.38	Peak
5	2412.000	29.45	8.72	35.95	97.43	99.65	74.00	-25.65	Peak

Remarks:

1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.




```

Site no.      : 10m Chamber           Data no.   : 20
Dis. / Ant.  : 3m 3115(0911)         Ant. pol.  : VERTICAL
Limit        : FCC PART 15C PEAK
Env. / Ins.  : 23*C/54%              Engineer   : Sunny-lu
EUT          : 150M Wireless Lite-N Access Point
Power        : DC 9V From Adapter Input AC 120V/60Hz
Test mode    : IEEE802.11g CH1 2412MHz Tx
M/N          : PW-AN401D/M-WA701ND
    
```


	Ant. Freq. (MHz)	Ant. Factor (dB/m)	Cable loss (dB)	Amp. Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	1399.000	26.19	6.49	36.69	45.46	41.45	74.00	32.55	Peak
2	1846.000	28.36	7.51	36.23	48.02	47.66	74.00	26.34	Peak
3	2023.000	29.21	7.97	36.12	45.83	46.89	74.00	27.11	Peak
4	2412.000	29.45	8.72	35.95	108.43	110.65	74.00	-36.65	Peak

Remarks:

1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.




Site no.	: 10m Chamber	Data no.	: 21
Dis. / Ant.	: 3m 3115(0911)	Ant. pol.	: HORIZONTAL
Limit	: FCC PART 15C PEAK		
Env. / Ins.	: 23°C/54%	Engineer	: Sunny-lu
EUT	: 150M Wireless Lite-N Access Point		
Power	: DC 9V From Adapter Input AC 120V/60Hz		
Test mode	: IEEE802.11g CH1 2412MHz Tx		
M/N	: PW-AN401D/M-WA701ND		




Site no. : 10m Chamber Data no. : 22  
 Dis. / Ant. : 3m 3115(0911) Ant. pol. : HORIZONTAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 23°C/54% Engineer : Sunny-lu  
 EUT : 150M Wireless Lite-N Access Point  
 Power : DC 9V From Adapter Input AC 120V/60Hz  
 Test mode : IEEE802.11g CH1 2412MHz Tx  
 M/N : PW-AN401D/M-WA701ND

	Ant. Freq. (MHz)	Ant. Factor (dB/m)	Cable loss (dB)	Amp. Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	4824.000	34.32	12.38	35.25	42.16	53.61	74.00	20.39	Peak
2	4824.000	34.32	12.38	35.25	35.84	47.29	54.00	6.71	Average

- Remarks:
1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
  2. The emission levels that are 20dB below the official limit are not reported.




Site no.	: 10m Chamber	Data no.	: 23
Dis. / Ant.	: 3m 3115(0911)	Ant. pol.	: VERTICAL
Limit	: FCC PART 15C PEAK		
Env. / Ins.	: 23°C/54%	Engineer	: Sunny-lu
EUT	: 150M Wireless Lite-N Access Point		
Power	: DC 9V From Adapter Input AC 120V/60Hz		
Test mode	: IEEE802.11g CH1 2412MHz Tx		
M/N	: PW-AN401D/M-WA701ND		



Site no. : 10m Chamber Data no. : 24  
 Dis. / Ant. : 3m 3115(0911) Ant. pol. : VERTICAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 23°C/54% Engineer : Sunny-lu  
 EUT : 150M Wireless Lite-N Access Point  
 Power : DC 9V From Adapter Input AC 120V/60Hz  
 Test mode : IEEE802.11g CH1 2412MHz Tx  
 M/N : PW-AN401D/M-WA701ND

	Ant. Freq. (MHz)	Ant. Factor (dB/m)	Cable loss (dB)	Amp. Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	4824.000	34.32	12.38	35.25	43.25	54.70	74.00	19.30	Peak
2	4824.000	34.32	12.38	35.25	36.42	47.87	54.00	6.13	Average

- Remarks:
1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
  2. The emission levels that are 20dB below the official limit are not reported.




Site no. : 10m Chamber Data no. : 25  
 Dis. / Ant. : 3m 3115(0911) Ant. pol. : VERTICAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 23°C/54% Engineer : Sunny-lu  
 EUT : 150M Wireless Lite-N Access Point  
 Power : DC 9V From Adapter Input AC 120V/60Hz  
 Test mode : IEEE802.11g CH6 2437MHz Tx  
 M/N : PW-AN401D/M-WA701ND

	Ant. Freq. (MHz)	Ant. Factor (dB/m)	Cable loss (dB)	Amp. Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	1399.000	26.19	6.49	36.69	45.89	41.88	74.00	32.12	Peak
2	1846.000	28.36	7.51	36.23	47.36	47.00	74.00	27.00	Peak
3	2023.000	29.21	7.97	36.12	49.38	50.44	74.00	23.56	Peak
4	2437.000	29.47	8.77	36.06	109.47	111.65	74.00	-37.65	Peak

Remarks:

1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.






Site no. : 10m Chamber Data no. : 26  
 Dis. / Ant. : 3m 3115(0911) Ant. pol. : HORIZONTAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 23\*C/54% Engineer : Sunny-lu  
 EUT : 150M Wireless Lite-N Access Point  
 Power : DC 9V From Adapter Input AC 120V/60Hz  
 Test mode : IEEE802.11g CH6 2437MHz Tx  
 M/N : PW-AN401D/M-WA701ND


	Ant. Freq. (MHz)	Ant. Factor (dB/m)	Cable loss (dB)	Amp. Factor (dB)	Emission Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	1051.000	25.50	5.60	37.34	46.47	40.23	74.00	33.77	Peak
2	1399.000	26.19	6.49	36.69	45.44	41.43	74.00	32.57	Peak
3	1846.000	28.36	7.51	36.23	46.59	46.23	74.00	27.77	Peak
4	2023.000	29.21	7.97	36.12	48.74	49.80	74.00	24.20	Peak
5	2437.000	29.47	8.77	36.06	97.72	99.90	74.00	-25.90	Peak

Remarks:

1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.




Site no.	: 10m Chamber	Data no.	: 27
Dis. / Ant.	: 3m 3115(0911)	Ant. pol.	: HORIZONTAL
Limit	: FCC PART 15C PEAK		
Env. / Ins.	: 23°C/54%	Engineer	: Sunny-lu
EUT	: 150M Wireless Lite-N Access Point		
Power	: DC 9V From Adapter Input AC 120V/60Hz		
Test mode	: IEEE802.11g CH6 2437MHz Tx		
M/N	: PW-AN401D/M-WA701ND		




Site no. : 10m Chamber Data no. : 28  
 Dis. / Ant. : 3m 3115(0911) Ant. pol. : HORIZONTAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 23°C/54% Engineer : Sunny-lu  
 EUT : 150M Wireless Lite-N Access Point  
 Power : DC 9V From Adapter Input AC 120V/60Hz  
 Test mode : IEEE802.11g CH6 2437MHz Tx  
 M/N : PW-AN401D/M-WA701ND

	Ant. Freq. (MHz)	Ant. Factor (dB/m)	Cable loss (dB)	Amp. Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	4874.000	34.41	12.44	35.36	41.95	53.44	74.00	20.56	Peak
2	4874.000	34.41	12.44	35.36	35.04	46.53	54.00	7.47	Average

- Remarks:
1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
  2. The emission levels that are 20dB below the official limit are not reported.




Site no.	: 10m Chamber	Data no.	: 29
Dis. / Ant.	: 3m 3115(0911)	Ant. pol.	: VERTICAL
Limit	: FCC PART 15C PEAK		
Env. / Ins.	: 23°C/54%	Engineer	: Sunny-lu
EUT	: 150M Wireless Lite-N Access Point		
Power	: DC 9V From Adapter Input AC 120V/60Hz		
Test mode	: IEEE802.11g CH6 2437MHz Tx		
M/N	: PW-AN401D/M-WA701ND		



Site no. : 10m Chamber Data no. : 30  
 Dis. / Ant. : 3m 3115(0911) Ant. pol. : VERTICAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 23°C/54% Engineer : Sunny-lu  
 EUT : 150M Wireless Lite-N Access Point  
 Power : DC 9V From Adapter Input AC 120V/60Hz  
 Test mode : IEEE802.11g CH6 2437MHz Tx  
 M/N : PW-AN401D/M-WA701ND

	Ant. Freq. (MHz)	Ant. Factor (dB/m)	Cable loss (dB)	Amp. Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	4874.000	34.41	12.44	35.36	43.67	55.16	74.00	18.84	Peak
2	4874.000	34.41	12.44	35.36	36.98	48.47	54.00	5.53	Average

- Remarks:
1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
  2. The emission levels that are 20dB below the official limit are not reported.




Site no. : 10m Chamber Data no. : 31  
 Dis. / Ant. : 3m 3115(0911) Ant. pol. : VERTICAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 23°C/54% Engineer : Sunny-lu  
 EUT : 150M Wireless Lite-N Access Point  
 Power : DC 9V From Adapter Input AC 120V/60Hz  
 Test mode : IEEE802.11g CH11 2462MHz Tx  
 M/N : PW-AN401D/M-WA701ND

	Ant. Freq. (MHz)	Ant. Factor (dB/m)	Cable loss (dB)	Amp. Factor (dB)	Emission Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	1399.000	26.19	6.49	36.69	45.25	41.24	74.00	32.76	Peak
2	1729.000	27.71	7.27	36.36	50.54	49.16	74.00	24.84	Peak
3	1846.000	28.36	7.51	36.23	47.90	47.54	74.00	26.46	Peak
4	2026.000	29.21	7.97	36.12	51.71	52.77	74.00	21.23	Peak
5	2462.000	29.48	8.82	36.02	107.78	110.06	74.00	-36.06	Peak

Remarks:

1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.




Site no. : 10m Chamber Data no. : 32  
 Dis. / Ant. : 3m 3115(0911) Ant. pol. : HORIZONTAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 23°C/54% Engineer : Sunny-lu  
 EUT : 150M Wireless Lite-N Access Point  
 Power : DC 9V From Adapter Input AC 120V/60Hz  
 Test mode : IEEE802.11g CH11 2462MHz Tx  
 M/N : PW-AN401D/M-WA701ND

	Ant. Freq. (MHz)	Ant. Factor (dB/m)	Cable loss (dB)	Amp. Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	1051.000	25.50	5.60	37.34	47.68	41.44	74.00	32.56	Peak
2	1399.000	26.19	6.49	36.69	46.04	42.03	74.00	31.97	Peak
3	1846.000	28.36	7.51	36.23	46.75	46.39	74.00	27.61	Peak
4	2026.000	29.21	7.97	36.12	49.54	50.60	74.00	23.40	Peak
5	2462.000	29.48	8.82	36.02	97.91	100.19	74.00	-26.19	Peak


Remarks:

1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 10m Chamber Data no. : 33  
Dis. / Ant. : 3m 3115(0911) Ant. pol. : VERTICAL  
Limit : FCC PART 15C PEAK  
Env. / Ins. : 23°C/54% Engineer : Sunny-lu  
EUT : 150M Wireless Lite-N Access Point  
Power : DC 9V From Adapter Input AC 120V/60Hz  
Test mode : IEEE802.11g CH11 2462MHz Tx  
M/N : PW-AN401D/M-WA701ND






Site no. : 10m Chamber Data no. : 34  
 Dis. / Ant. : 3m 3115(0911) Ant. pol. : VERTICAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 23°C/54% Engineer : Sunny-lu  
 EUT : 150M Wireless Lite-N Access Point  
 Power : DC 9V From Adapter Input AC 120V/60Hz  
 Test mode : IEEE802.11g CH11 2462MHz Tx  
 M/N : PW-AN401D/M-WA701ND


	Ant. Freq. (MHz)	Ant. Factor (dB/m)	Cable loss (dB)	Amp. Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	4924.000	34.49	12.50	35.34	43.68	55.33	74.00	18.67	Peak
2	4924.000	34.49	12.50	35.34	37.05	48.70	54.00	5.30	Average

Remarks:

1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 10m Chamber Data no. : 35  
Dis. / Ant. : 3m 3115(0911) Ant. pol. : HORIZONTAL  
Limit : FCC PART 15C PEAK  
Env. / Ins. : 23\*C/54% Engineer : Sunny-lu  
EUT : 150M Wireless Lite-N Access Point  
Power : DC 9V From Adapter Input AC 120V/60Hz  
Test mode : IEEE802.11g CH11 2462MHz Tx  
M/N : PW-AN401D/M-WA701ND




Site no. : 10m Chamber Data no. : 36  
 Dis. / Ant. : 3m 3115(0911) Ant. pol. : HORIZONTAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 23°C/54% Engineer : Sunny-lu  
 EUT : 150M Wireless Lite-N Access Point  
 Power : DC 9V From Adapter Input AC 120V/60Hz  
 Test mode : IEEE802.11g CH11 2462MHz Tx  
 M/N : PW-AN401D/M-WA701ND

	Ant.	Cable	Amp.	Emission					
Freq.	Factor	loss	Factor	Reading	Level	Limits	Margin	Remark	
(MHz)	(dB/m)	(dB)	(dB)	(dBuV)	(dBuV/m)	(dBuV/m)	(dB)		
1 4924.000	34.49	12.50	35.34	42.69	54.34	74.00	19.66	Peak	
2 4924.000	34.49	12.50	35.34	36.15	47.80	54.00	6.20	Average	

Remarks:

1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.




```

Site no.      : 10m Chamber           Data no.   : 37
Dis. / Ant.  : 3m 3115(0911)         Ant. pol.  : HORIZONTAL
Limit        : FCC PART 15C PEAK
Env. / Ins.  : 23*C/54%              Engineer   : Sunny-lu
EUT          : 150M Wireless Lite-N Access Point
Power        : DC 9V From Adapter Input AC 120V/60Hz
Test mode    : IEEE802.11n HT20 CH1 2412MHz Tx
M/N          : PW-AN401D/M-WA701ND
    
```

	Ant. Freq. (MHz)	Ant. Factor (dB/m)	Cable loss (dB)	Amp. Factor (dB)	Emission Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	1051.000	25.50	5.60	37.34	47.55	41.31	74.00	32.69	Peak
2	1399.000	26.19	6.49	36.69	46.42	42.41	74.00	31.59	Peak
3	2023.000	29.21	7.97	36.12	47.20	48.26	74.00	25.74	Peak
4	2412.000	29.45	8.72	35.95	95.82	98.04	74.00	-24.04	Peak

Remarks:

1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.




Site no. : 10m Chamber      Data no. : 38  
 Dis. / Ant. : 3m 3115(0911)      Ant. pol. : VERTICAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 23°C/54%      Engineer : Sunny-lu  
 EUT : 150M Wireless Lite-N Access Point  
 Power : DC 9V From Adapter Input AC 120V/60Hz  
 Test mode : IEEE802.11n HT20 CH1 2412MHz Tx  
 M/N : PW-AN401D/M-WA701ND


	Ant.	Cable	Amp.	Emission					
	Freq.	Factor	loss	Factor	Reading	Level	Limits	Margin	Remark
	(MHz)	(dB/m)	(dB)	(dB)	(dBuV)	(dBuV/m)	(dBuV/m)	(dB)	
1	1399.000	26.19	6.49	36.69	45.17	41.16	74.00	32.84	Peak
2	1846.000	28.36	7.51	36.23	47.37	47.01	74.00	26.99	Peak
3	2026.000	29.21	7.97	36.12	50.69	51.75	74.00	22.25	Peak
4	2412.000	29.45	8.72	35.95	108.65	110.87	74.00	-36.87	Peak

Remarks:

1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.




Site no.	: 10m Chamber	Data no.	: 39
Dis. / Ant.	: 3m 3115(0911)	Ant. pol.	: HORIZONTAL
Limit	: FCC PART 15C PEAK		
Env. / Ins.	: 23°C/54%	Engineer	: Sunny-lu
EUT	: 150M Wireless Lite-N Access Point		
Power	: DC 9V From Adapter Input AC 120V/60Hz		
Test mode	: IEEE802.11n HT20 CH1 2412MHz Tx		
M/N	: PW-AN401D/M-WA701ND		



Site no. : 10m Chamber Data no. : 40  
 Dis. / Ant. : 3m 3115(0911) Ant. pol. : HORIZONTAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 23°C/54% Engineer : Sunny-lu  
 EUT : 150M Wireless Lite-N Access Point  
 Power : DC 9V From Adapter Input AC 120V/60Hz  
 Test mode : IEEE802.11n HT20 CH1 2412MHz Tx  
 M/N : PW-AN401D/M-WA701ND


	Ant. Freq. (MHz)	Ant. Factor (dB/m)	Cable loss (dB)	Amp. Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	4824.000	34.32	12.38	35.25	42.36	53.81	74.00	20.19	Peak
2	4824.000	34.32	12.38	35.25	35.84	47.29	54.00	6.71	Average

- Remarks:
1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
  2. The emission levels that are 20dB below the official limit are not reported.



Site no.	: 10m Chamber	Data no.	: 41
Dis. / Ant.	: 3m 3115(0911)	Ant. pol.	: VERTICAL
Limit	: FCC PART 15C PEAK		
Env. / Ins.	: 23°C/54%	Engineer	: Sunny-lu
EUT	: 150M Wireless Lite-N Access Point		
Power	: DC 9V From Adapter Input AC 120V/60Hz		
Test mode	: IEEE802.11n HT20 CH1 2412MHz Tx		
M/N	: PW-AN401D/M-WA701ND		






Site no. : 10m Chamber Data no. : 42  
 Dis. / Ant. : 3m 3115(0911) Ant. pol. : VERTICAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 23°C/54% Engineer : Sunny-lu  
 EUT : 150M Wireless Lite-N Access Point  
 Power : DC 9V From Adapter Input AC 120V/60Hz  
 Test mode : IEEE802.11n HT20 CH1 2412MHz Tx  
 M/N : PW-AN401D/M-WA701ND

	Ant. Freq. (MHz)	Ant. Factor (dB/m)	Cable loss (dB)	Amp. Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	4824.000	34.32	12.38	35.25	43.62	55.07	74.00	18.93	Peak
2	4824.000	34.32	12.38	35.25	36.95	48.40	54.00	5.60	Average

Remarks:

1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.




```

Site no.      : 10m Chamber           Data no.   : 43
Dis. / Ant.   : 3m 3115(0911)        Ant. pol.  : VERTICAL
Limit         : FCC PART 15C PEAK
Env. / Ins.   : 23*C/54%             Engineer   : Sunny-lu
EUT           : 150M Wireless Lite-N Access Point
Power         : DC 9V From Adapter Input AC 120V/60Hz
Test mode     : IEEE802.11n HT20 CH6 2437MHz Tx
M/N           : PW-AN401D/M-WA701ND
    
```

	Ant. Freq. (MHz)	Ant. Factor (dB/m)	Cable loss (dB)	Amp. Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	1399.000	26.19	6.49	36.69	44.67	40.66	74.00	33.34	Peak
2	1846.000	28.36	7.51	36.23	47.17	46.81	74.00	27.19	Peak
3	2026.000	29.21	7.97	36.12	51.58	52.64	74.00	21.36	Peak
4	2437.000	29.47	8.77	36.06	108.69	110.87	74.00	-36.87	Peak

Remarks:

1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.




Site no. : 10m Chamber      Data no. : 44  
 Dis. / Ant. : 3m 3115(0911)      Ant. pol. : HORIZONTAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 23°C/54%      Engineer : Sunny-lu  
 EUT : 150M Wireless Lite-N Access Point  
 Power : DC 9V From Adapter Input AC 120V/60Hz  
 Test mode : IEEE802.11n HT20 CH6 2437MHz Tx  
 M/N : PW-AN401D/M-WA701ND


	Ant. Freq. (MHz)	Ant. Factor (dB/m)	Cable loss (dB)	Amp. Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	1051.000	25.50	5.60	37.34	48.28	42.04	74.00	31.96	Peak
2	1732.000	27.71	7.27	36.36	49.55	48.17	74.00	25.83	Peak
3	2026.000	29.21	7.97	36.12	50.70	51.76	74.00	22.24	Peak
4	2437.000	29.47	8.77	36.06	96.22	98.40	74.00	-24.40	Peak

Remarks:

1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.




Site no.	: 10m Chamber	Data no.	: 45
Dis. / Ant.	: 3m 3115(0911)	Ant. pol.	: HORIZONTAL
Limit	: FCC PART 15C PEAK		
Env. / Ins.	: 23°C/54%	Engineer	: Sunny-lu
EUT	: 150M Wireless Lite-N Access Point		
Power	: DC 9V From Adapter Input AC 120V/60Hz		
Test mode	: IEEE802.11n HT20 CH6 2437MHz Tx		
M/N	: PW-AN401D/M-WA701ND		




Site no. : 10m Chamber Data no. : 46  
 Dis. / Ant. : 3m 3115(0911) Ant. pol. : HORIZONTAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 23°C/54% Engineer : Sunny-lu  
 EUT : 150M Wireless Lite-N Access Point  
 Power : DC 9V From Adapter Input AC 120V/60Hz  
 Test mode : IEEE802.11n HT20 CH6 2437MHz Tx  
 M/N : PW-AN401D/M-WA701ND

	Ant. Freq. (MHz)	Cable Factor (dB/m)	Amp. loss (dB)	Emission Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark	
1	4874.000	34.41	12.44	35.36	42.35	53.84	74.00	20.16	Peak
2	4874.000	34.41	12.44	35.36	35.18	46.67	54.00	7.33	Average

- Remarks:
1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
  2. The emission levels that are 20dB below the official limit are not reported.




Site no. : 10m Chamber Data no. : 47  
Dis. / Ant. : 3m 3115(0911) Ant. pol. : VERTICAL  
Limit : FCC PART 15C PEAK  
Env. / Ins. : 23°C/54% Engineer : Sunny-lu  
EUT : 150M Wireless Lite-N Access Point  
Power : DC 9V From Adapter Input AC 120V/60Hz  
Test mode : IEEE802.11n HT20 CH6 2437MHz Tx  
M/N : PW-AN401D/M-WA701ND



Site no. : 10m Chamber Data no. : 48  
 Dis. / Ant. : 3m 3115(0911) Ant. pol. : VERTICAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 23°C/54% Engineer : Sunny-lu  
 EUT : 150M Wireless Lite-N Access Point  
 Power : DC 9V From Adapter Input AC 120V/60Hz  
 Test mode : IEEE802.11n HT20 CH6 2437MHz Tx  
 M/N : PW-AN401D/M-WA701ND

	Ant. Freq. (MHz)	Ant. Factor (dB/m)	Cable loss (dB)	Amp. Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	4874.000	34.41	12.44	35.36	43.24	54.73	74.00	19.27	Peak
2	4874.000	34.41	12.44	35.36	36.50	47.99	54.00	6.01	Average

- Remarks:
1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
  2. The emission levels that are 20dB below the official limit are not reported.




Site no. : 10m Chamber Data no. : 49  
 Dis. / Ant. : 3m 3115(0911) Ant. pol. : VERTICAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 23\*C/54% Engineer : Sunny-lu  
 EUT : 150M Wireless Lite-N Access Point  
 Power : DC 9V From Adapter Input AC 120V/60Hz  
 Test mode : IEEE802.11n HT20 CH11 2462MHz Tx  
 M/N : PW-AN401D/M-WA701ND

	Ant. Freq. (MHz)	Ant. Factor (dB/m)	Cable loss (dB)	Amp. Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	1399.000	26.19	6.49	36.69	45.76	41.75	74.00	32.25	Peak
2	1750.000	27.80	7.33	36.29	53.49	52.33	74.00	21.67	Peak
3	2023.000	29.21	7.97	36.12	48.99	50.05	74.00	23.95	Peak
4	2462.000	29.48	8.82	36.02	105.86	108.14	74.00	-34.14	Peak

Remarks:

1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.






Site no. : 10m Chamber Data no. : 50  
 Dis. / Ant. : 3m 3115(0911) Ant. pol. : HORIZONTAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 23°C/54% Engineer : Sunny-lu  
 EUT : 150M Wireless Lite-N Access Point  
 Power : DC 9V From Adapter Input AC 120V/60Hz  
 Test mode : IEEE802.11n HT20 CH11 2462MHz Tx  
 M/N : PW-AN401D/M-WA701ND


	Ant. Freq. (MHz)	Ant. Factor (dB/m)	Cable loss (dB)	Amp. Factor (dB)	Emission Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	1051.000	25.50	5.60	37.34	47.02	40.78	74.00	33.22	Peak
2	1399.000	26.19	6.49	36.69	44.92	40.91	74.00	33.09	Peak
3	1846.000	28.36	7.51	36.23	46.86	46.50	74.00	27.50	Peak
4	2026.000	29.21	7.97	36.12	51.86	52.92	74.00	21.08	Peak
5	2462.000	29.48	8.82	36.02	96.97	99.25	74.00	-25.25	Peak

Remarks:

1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.



Site no.	: 10m Chamber	Data no.	: 51
Dis. / Ant.	: 3m 3115(0911)	Ant. pol.	: VERTICAL
Limit	: FCC PART 15C PEAK		
Env. / Ins.	: 23°C/54%	Engineer	: Sunny-lu
EUT	: 150M Wireless Lite-N Access Point		
Power	: DC 9V From Adapter Input AC 120V/60Hz		
Test mode	: IEEE802.11n HT20 CH11 2462MHz Tx		
M/N	: PW-AN401D/M-WA701ND		




Site no. : 10m Chamber      Data no. : 52  
 Dis. / Ant. : 3m 3115(0911)      Ant. pol. : VERTICAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 23°C/54%      Engineer : Sunny-lu  
 EUT : 150M Wireless Lite-N Access Point  
 Power : DC 9V From Adapter Input AC 120V/60Hz  
 Test mode : IEEE802.11n HT20 CH11 2462MHz Tx  
 M/N : PW-AN401D/M-WA701ND


	Ant.	Cable	Amp.	Emission				
Freq.	Factor	loss	Factor	Reading	Level	Limits	Margin	Remark
(MHz)	(dB/m)	(dB)	(dB)	(dBuV)	(dBuV/m)	(dBuV/m)	(dB)	
1 4924.000	34.49	12.50	35.34	44.96	56.61	74.00	17.39	Peak
2 4924.000	34.49	12.50	35.34	38.42	50.07	54.00	3.93	Average

Remarks:

1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 10m Chamber Data no. : 53  
Dis. / Ant. : 3m 3115(0911) Ant. pol. : HORIZONTAL  
Limit : FCC PART 15C PEAK  
Env. / Ins. : 23\*C/54% Engineer : Sunny-lu  
EUT : 150M Wireless Lite-N Access Point  
Power : DC 9V From Adapter Input AC 120V/60Hz  
Test mode : IEEE802.11n HT20 CH11 2462MHz Tx  
M/N : PW-AN401D/M-WA701ND




Site no. : 10m Chamber Data no. : 54  
 Dis. / Ant. : 3m 3115(0911) Ant. pol. : HORIZONTAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 23°C/54% Engineer : Sunny-lu  
 EUT : 150M Wireless Lite-N Access Point  
 Power : DC 9V From Adapter Input AC 120V/60Hz  
 Test mode : IEEE802.11n HT20 CH11 2462MHz Tx  
 M/N : PW-AN401D/M-WA701ND

	Ant. Freq. (MHz)	Ant. Factor (dB/m)	Cable loss (dB)	Amp. Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	4924.000	34.49	12.50	35.34	42.15	53.80	74.00	20.20	Peak
2	4924.000	34.49	12.50	35.34	35.48	47.13	54.00	6.87	Average

Remarks:

1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.




Site no. : 10m Chamber Data no. : 55  
 Dis. / Ant. : 3m 3115(0911) Ant. pol. : HORIZONTAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 23\*C/54% Engineer : Sunny-lu  
 EUT : 150M Wireless Lite-N Access Point  
 Power : DC 9V From Adapter Input AC 120V/60Hz  
 Test mode : IEEE802.11n HT40 CH1 2422MHz Tx  
 M/N : PW-AN401D/M-WA701ND

	Ant. Freq. (MHz)	Ant. Factor (dB/m)	Cable loss (dB)	Amp. Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	1051.000	25.50	5.60	37.34	47.88	41.64	74.00	32.36	Peak
2	1399.000	26.19	6.49	36.69	46.03	42.02	74.00	31.98	Peak
3	2026.000	29.21	7.97	36.12	47.62	48.68	74.00	25.32	Peak
4	2422.000	29.46	8.77	36.01	88.19	90.41	74.00	-16.41	Peak

Remarks:

1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.




```

Site no.      : 10m Chamber           Data no.   : 56
Dis. / Ant.  : 3m 3115(0911)         Ant. pol.  : VERTICAL
Limit        : FCC PART 15C PEAK
Env. / Ins.  : 23*C/54%              Engineer   : Sunny-lu
EUT          : 150M Wireless Lite-N Access Point
Power        : DC 9V From Adapter Input AC 120V/60Hz
Test mode    : IEEE802.11n HT40 CH1 2422MHz Tx
M/N          : PW-AN401D/M-WA701ND
    
```

	Ant. Freq. (MHz)	Ant. Factor (dB/m)	Cable loss (dB)	Amp. Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	1051.000	25.50	5.60	37.34	47.88	41.64	74.00	32.36	Peak
2	1399.000	26.19	6.49	36.69	46.03	42.02	74.00	31.98	Peak
3	2026.000	29.21	7.97	36.12	47.62	48.68	74.00	25.32	Peak
4	2422.000	29.46	8.77	36.01	101.07	103.29	74.00	-29.29	Peak


Remarks:

1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.



Site no.	: 10m Chamber	Data no.	: 57
Dis. / Ant.	: 3m 3115(0911)	Ant. pol.	: HORIZONTAL
Limit	: FCC PART 15C PEAK		
Env. / Ins.	: 23°C/54%	Engineer	: Sunny-lu
EUT	: 150M Wireless Lite-N Access Point		
Power	: DC 9V From Adapter Input AC 120V/60Hz		
Test mode	: IEEE802.11n HT40 CH1 2422MHz Tx		
M/N	: PW-AN401D/M-WA701ND		






```

Site no.      : 10m Chamber           Data no.   : 58
Dis. / Ant.   : 3m 3115(0911)        Ant. pol.  : HORIZONTAL
Limit        : FCC PART 15C PEAK
Env. / Ins.   : 23*C/54%             Engineer   : Sunny-lu
EUT          : 150M Wireless Lite-N Access Point
Power        : DC 9V From Adapter Input AC 120V/60Hz
Test mode    : IEEE802.11n HT40 CH1 2422MHz Tx
M/N         : PW-AN401D/M-WA701ND
    
```


	Ant.	Cable	Amp.	Emission					
Freq.	Factor	loss	Factor	Reading	Level	Limits	Margin	Remark	
(MHz)	(dB/m)	(dB)	(dB)	(dBuV)	(dBuV/m)	(dBuV/m)	(dB)		
1 4844.000	34.35	12.38	35.25	42.16	53.64	74.00	20.36	Peak	
2 4844.000	34.35	12.38	35.25	34.95	46.43	54.00	7.57	Average	

Remarks:

1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.




Site no.	: 10m Chamber	Data no.	: 59
Dis. / Ant.	: 3m 3115(0911)	Ant. pol.	: VERTICAL
Limit	: FCC PART 15C PEAK		
Env. / Ins.	: 23°C/54%	Engineer	: Sunny-lu
EUT	: 150M Wireless Lite-N Access Point		
Power	: DC 9V From Adapter Input AC 120V/60Hz		
Test mode	: IEEE802.11n HT40 CH1 2422MHz Tx		
M/N	: PW-AN401D/M-WA701ND		



Site no. : 10m Chamber Data no. : 60  
 Dis. / Ant. : 3m 3115(0911) Ant. pol. : VERTICAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 23°C/54% Engineer : Sunny-lu  
 EUT : 150M Wireless Lite-N Access Point  
 Power : DC 9V From Adapter Input AC 120V/60Hz  
 Test mode : IEEE802.11n HT40 CH1 2422MHz Tx  
 M/N : PW-AN401D/M-WA701ND

	Ant. Freq. (MHz)	Ant. Factor (dB/m)	Cable loss (dB)	Amp. Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	4844.000	34.35	12.38	35.25	44.01	55.49	74.00	18.51	Peak
2	4844.000	34.35	12.38	35.25	36.87	48.35	54.00	5.65	Average

- Remarks:
1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
  2. The emission levels that are 20dB below the official limit are not reported.




Site no. : 10m Chamber Data no. : 61  
 Dis. / Ant. : 3m 3115(0911) Ant. pol. : VERTICAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 23°C/54% Engineer : Sunny-lu  
 EUT : 150M Wireless Lite-N Access Point  
 Power : DC 9V From Adapter Input AC 120V/60Hz  
 Test mode : IEEE802.11n HT40 CH4 2437MHz Tx  
 M/N : PW-AN401D/M-WA701ND

	Ant. Freq. (MHz)	Ant. Factor (dB/m)	Cable loss (dB)	Amp. Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	1051.000	25.50	5.60	37.34	46.65	40.41	74.00	33.59	Peak
2	1399.000	26.19	6.49	36.69	48.93	44.92	74.00	29.08	Peak
3	1750.000	27.80	7.33	36.29	46.21	45.05	74.00	28.95	Peak
4	1984.000	29.11	7.87	36.06	49.12	50.04	74.00	23.96	Peak
5	2437.000	29.47	8.77	36.06	101.21	103.39	74.00	-29.39	Peak

Remarks:

1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.




```

Site no.      : 10m Chamber           Data no.     : 62
Dis. / Ant.  : 3m 3115(0911)         Ant. pol.   : HORIZONTAL
Limit        : FCC PART 15C PEAK
Env. / Ins.  : 23*C/54%              Engineer    : Sunny-lu
EUT          : 150M Wireless Lite-N Access Point
Power        : DC 9V From Adapter Input AC 120V/60Hz
Test mode    : IEEE802.11n HT40 CH4 2437MHz Tx
M/N         : PW-AN401D/M-WA701ND
    
```


	Ant. Freq. (MHz)	Ant. Factor (dB/m)	Cable loss (dB)	Amp. Factor (dB)	Emission Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	1051.000	25.50	5.60	37.34	47.47	41.23	74.00	32.77	Peak
2	1399.000	26.19	6.49	36.69	49.21	45.20	74.00	28.80	Peak
3	1750.000	27.80	7.33	36.29	45.96	44.80	74.00	29.20	Peak
4	1984.000	29.11	7.87	36.06	47.52	48.44	74.00	25.56	Peak
5	2437.000	29.47	8.77	36.06	88.64	90.82	74.00	-16.82	Peak

Remarks:

1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.



Site no.	: 10m Chamber	Data no.	: 63
Dis. / Ant.	: 3m 3115(0911)	Ant. pol.	: HORIZONTAL
Limit	: FCC PART 15C PEAK		
Env. / Ins.	: 23°C/54%	Engineer	: Sunny-lu
EUT	: 150M Wireless Lite-N Access Point		
Power	: DC 9V From Adapter Input AC 120V/60Hz		
Test mode	: IEEE802.11n HT40 CH4 2437MHz Tx		
M/N	: PW-AN401D/M-WA701ND		




```

Site no.      : 10m Chamber           Data no.   : 64
Dis. / Ant.  : 3m 3115(0911)         Ant. pol.  : HORIZONTAL
Limit        : FCC PART 15C PEAK
Env. / Ins.  : 23*C/54%              Engineer   : Sunny-lu
EUT          : 150M Wireless Lite-N Access Point
Power        : DC 9V From Adapter Input AC 120V/60Hz
Test mode    : IEEE802.11n HT40 CH4 2437MHz Tx
M/N          : PW-AN401D/M-WA701ND
    
```

	Ant. Freq. (MHz)	Ant. Factor (dB/m)	Cable loss (dB)	Amp. Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	4874.000	34.41	12.44	35.36	42.02	53.51	74.00	20.49	Peak
2	4874.000	34.41	12.44	35.36	35.91	47.40	54.00	6.60	Average


Remarks:

1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.



Site no.	: 10m Chamber	Data no.	: 65
Dis. / Ant.	: 3m 3115(0911)	Ant. pol.	: VERTICAL
Limit	: FCC PART 15C PEAK		
Env. / Ins.	: 23°C/54%	Engineer	: Sunny-lu
EUT	: 150M Wireless Lite-N Access Point		
Power	: DC 9V From Adapter Input AC 120V/60Hz		
Test mode	: IEEE802.11n HT40 CH4 2437MHz Tx		
M/N	: PW-AN401D/M-WA701ND		






Site no. : 10m Chamber Data no. : 66  
 Dis. / Ant. : 3m 3115(0911) Ant. pol. : VERTICAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 23°C/54% Engineer : Sunny-lu  
 EUT : 150M Wireless Lite-N Access Point  
 Power : DC 9V From Adapter Input AC 120V/60Hz  
 Test mode : IEEE802.11n HT40 CH4 2437MHz Tx  
 M/N : PW-AN401D/M-WA701ND

	Ant.	Cable	Amp.	Emission					
Freq.	Factor	loss	Factor	Reading	Level	Limits	Margin	Remark	
(MHz)	(dB/m)	(dB)	(dB)	(dBUV)	(dBUV/m)	(dBUV/m)	(dB)		
1 4874.000	34.41	12.44	35.36	43.84	55.33	74.00	18.67	Peak	
2 4874.000	34.41	12.44	35.36	36.94	48.43	54.00	5.57	Average	

Remarks:

1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.




Site no. : 10m Chamber Data no. : 67  
 Dis. / Ant. : 3m 3115(0911) Ant. pol. : VERTICAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 23\*C/54% Engineer : Sunny-lu  
 EUT : 150M Wireless Lite-N Access Point  
 Power : DC 9V From Adapter Input AC 120V/60Hz  
 Test mode : IEEE802.11n HT40 CH7 2452MHz Tx  
 M/N : PW-AN401D/M-WA701ND

	Ant. Freq. (MHz)	Ant. Factor (dB/m)	Cable loss (dB)	Amp. Factor (dB)	Emission Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	1051.000	25.50	5.60	37.34	45.79	39.55	74.00	34.45	Peak
2	1399.000	26.19	6.49	36.69	47.41	43.40	74.00	30.60	Peak
3	1750.000	27.80	7.33	36.29	46.08	44.92	74.00	29.08	Peak
4	1984.000	29.11	7.87	36.06	51.24	52.16	74.00	21.84	Peak
5	2452.000	29.47	8.82	36.06	102.12	104.35	74.00	-30.35	Peak

Remarks:

1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.




Site no. : 10m Chamber Data no. : 68  
 Dis. / Ant. : 3m 3115(0911) Ant. pol. : HORIZONTAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 23\*C/54% Engineer : Sunny-lu  
 EUT : 150M Wireless Lite-N Access Point  
 Power : DC 9V From Adapter Input AC 120V/60Hz  
 Test mode : IEEE802.11n HT40 CH7 2452MHz Tx  
 M/N : PW-AN401D/M-WA701ND


	Ant. Freq. (MHz)	Ant. Factor (dB/m)	Cable loss (dB)	Amp. Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	1051.000	25.50	5.60	37.34	47.57	41.33	74.00	32.67	Peak
2	1399.000	26.19	6.49	36.69	48.06	44.05	74.00	29.95	Peak
3	1750.000	27.80	7.33	36.29	44.99	43.83	74.00	30.17	Peak
4	1984.000	29.11	7.87	36.06	50.17	51.09	74.00	22.91	Peak
5	2452.000	29.47	8.82	36.06	90.08	92.31	74.00	-18.31	Peak

Remarks:

1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.



Site no.	: 10m Chamber	Data no.	: 69
Dis. / Ant.	: 3m 3115(0911)	Ant. pol.	: VERTICAL
Limit	: FCC PART 15C PEAK		
Env. / Ins.	: 23°C/54%	Engineer	: Sunny-lu
EUT	: 150M Wireless Lite-N Access Point		
Power	: DC 9V From Adapter Input AC 120V/60Hz		
Test mode	: IEEE802.11n HT40 CH7 2452MHz Tx		
M/N	: PW-AN401D/M-WA701ND		




```

Site no.      : 10m Chamber           Data no.   : 70
Dis. / Ant.  : 3m 3115(0911)         Ant. pol.  : VERTICAL
Limit        : FCC PART 15C PEAK
Env. / Ins.  : 23*C/54%              Engineer   : Sunny-lu
EUT          : 150M Wireless Lite-N Access Point
Power        : DC 9V From Adapter Input AC 120V/60Hz
Test mode    : IEEE802.11n HT40 CH7 2452MHz Tx
M/N          : PW-AN401D/M-WA701ND
    
```


	Ant. Freq. (MHz)	Ant. Factor (dB/m)	Cable loss (dB)	Amp. Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	4904.000	34.46	12.47	35.27	43.38	55.04	74.00	18.96	Peak
2	4904.000	34.46	12.47	35.27	36.42	48.08	54.00	5.92	Average

Remarks:

1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.



Site no.	: 10m Chamber	Data no.	: 71
Dis. / Ant.	: 3m 3115(0911)	Ant. pol.	: HORIZONTAL
Limit	: FCC PART 15C PEAK		
Env. / Ins.	: 23°C/54%	Engineer	: Sunny-lu
EUT	: 150M Wireless Lite-N Access Point		
Power	: DC 9V From Adapter Input AC 120V/60Hz		
Test mode	: IEEE802.11n HT40 CH7 2452MHz Tx		
M/N	: PW-AN401D/M-WA701ND		



```

Site no.      : 10m Chamber           Data no.   : 72
Dis. / Ant.   : 3m 3115(0911)        Ant. pol.  : HORIZONTAL
Limit        : FCC PART 15C PEAK
Env. / Ins.   : 23*C/54%             Engineer   : Sunny-lu
EUT          : 150M Wireless Lite-N Access Point
Power        : DC 9V From Adapter Input AC 120V/60Hz
Test mode    : IEEE802.11n HT40 CH7 2452MHz Tx
M/N         : PW-AN401D/M-WA701ND
    
```

	Ant.	Cable	Amp.	Emission					
Freq.	Factor	loss	Factor	Reading	Level	Limits	Margin	Remark	
(MHz)	(dB/m)	(dB)	(dB)	(dBuV)	(dBuV/m)	(dBuV/m)	(dB)		
1 4904.000	34.46	12.47	35.27	42.68	54.34	74.00	19.66	Peak	
2 4904.000	34.46	12.47	35.27	35.84	47.50	54.00	6.50	Average	

Remarks:

1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.

## 5. CONDUCTED SPURIOUS EMISSIONS

### 5.1. Test Equipment

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	Spectrum Analyzer	Agilent	E4446A	US44300459	May.08,10	1 Year
2.	Attenuator	Agilent	8491B	MY39262165	May.08,10	1 Year
3.	RF Cable	Hubersuhner	SUCOFLEX102	28618/2	May.08,10	1Year

### 5.2. Limit

In any 100kHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power.

### 5.3. Test Procedure

The transmitter output was connected to a spectrum analyzer, The resolution bandwidth is set to 100 kHz, The video bandwidth is set to 300 kHz and measure all the emissions detected.

### 5.4. Test result



**PASS** (The testing data was attached in the next pages.)




**Conducted emission test data:**

Test Mode: IEEE 802.11b TX


CH1




CH6





CH11








Test Mode: IEEE 802.11g TX  
CH1







CH6







Test Mode: IEEE 802.11n HT20 TX  
CH1




CH6




CH11







Test Mode: IEEE 802.11n HT40 TX  
CH1








CH4



CH7



## 6. BAND EDGE COMPLIANCE TEST

### 6.1. Test Equipment

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	Spectrum Analyzer	Agilent	E4446A	US44300459	May.08,10	1 Year
2.	Horn Antenna	EMCO	3115	9607-4877	Nov.25, 09	1.5 Year
3.	Amplifier	Agilent	8449B	3008A02495	May.08, 10	1 Year
4.	RF Cable	Hubersuhner	SUCOFLEX102	28620/2	May.08,10	1 Year
5.	RF Cable	Hubersuhner	SUCOFLEX102	28618/2	May.08,10	1 Year
6.	RF Cable	Hubersuhner	SUCOFLEX102	28610/2	May.08,10	1 Year

### 6.2. Limit


All the lower and upper band-edges emissions appearing within 2310MHz to 2390MHz and 2483.5MHz to 2500MHz restricted frequency bands shall not exceed the limits shown in 15.209, all the other emissions outside operation frequency band 2400MHz to 2483.5MHz shall be at least 20dB below the fundamental emissions, or comply with 15.209 limits.

### 6.3. Test Produce

1. The EUT is placed on a turntable, which is 0.8m above the ground plane and worked at highest radiated power.
2. The turntable was rotated for 360 degrees to determine the position of maximum emission level.
3. EUT is set 3m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emission.
4. Set the spectrum analyzer in the following setting in order to capture the lower and upper band-edges of the emission:
  - (a) PEAK: RBW=1MHz; VBW=3MHz ;Sweep=AUTO
  - (b) AVERAGE: RBW=1MHz ;VBW=10Hz ; Sweep=AUTO

### 6.4. Test Results

Pass (The testing data was attached in the next pages.)




Site no. : 10m Chamber Data no. : 73  
 Dis. / Ant. : 3m 3115(0911) Ant. pol. : VERTICAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 23°C/54% Engineer : Sunny-lu  
 EUT : 150M Wireless Lite-N Access Point  
 Power : DC 9V From Adapter Input AC 120V/60Hz  
 Test mode : IEEE802.11b CH1 2412MHz Tx  
 M/N : PW-AN401D/M-WA701ND

	Ant. Freq. (MHz)	Ant. Factor (dB/m)	Cable loss (dB)	Amp. Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2390.000	29.44	8.67	36.09	56.82	58.84	74.00	15.16	Peak
2	2397.000	29.44	8.72	36.09	75.97	78.04	74.00	-4.04	Peak
3	2400.000	29.44	8.72	36.09	70.60	72.67	74.00	1.33	Peak
4	2412.960	29.45	8.72	35.95	108.19	110.41	74.00	-36.41	Peak

Remarks:

1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.




Site no. :	10m Chamber	Data no. :	74
Dis. / Ant. :	3m 3115(0911)	Ant. pol. :	VERTICAL
Limit :	FCC PART 15C AV		
Env. / Ins. :	23°C/54%	Engineer :	Sunny-lu
EUT :	150M Wireless Lite-N Access Point		
Power :	DC 9V From Adapter Input AC 120V/60Hz		
Test mode :	IEEE802.11b CH1 2412MHz Tx		
M/N :	PW-AN401D/M-WA701ND		

	Ant. Freq. (MHz)	Ant. Factor (dB/m)	Cable loss (dB)	Amp. Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2385.960	29.44	8.67	36.09	45.14	47.16	54.00	6.84	Average
2	2390.000	29.44	8.67	36.09	47.66	49.68	54.00	4.32	Average
3	2397.240	29.44	8.72	36.09	72.40	74.47	54.00	-20.47	Average
4	2400.000	29.44	8.72	36.09	67.60	69.67	54.00	-15.67	Average
5	2411.160	29.45	8.72	35.95	104.58	106.80	54.00	-52.80	Average

Remarks:

1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.




Site no. : 10m Chamber Data no. : 75  
 Dis. / Ant. : 3m 3115(0911) Ant. pol. : HORIZONTAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 23°C/54% Engineer : Sunny-lu  
 EUT : 150M Wireless Lite-N Access Point  
 Power : DC 9V From Adapter Input AC 120V/60Hz  
 Test mode : IEEE802.11b CH1 2412MHz Tx  
 M/N : PW-AN401D/M-WA701ND

	Ant. Freq. (MHz)	Ant. Factor (dB/m)	Cable loss (dB)	Amp. Factor (dB)	Emission Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2390.000	29.44	8.67	36.09	48.23	50.25	74.00	23.75	Peak
2	2397.360	29.44	8.72	36.09	63.71	65.78	74.00	8.22	Peak
3	2400.000	29.44	8.72	36.09	59.37	61.44	74.00	12.56	Peak
4	2411.040	29.45	8.72	35.95	96.39	98.61	74.00	-24.61	Peak

Remarks:

1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.




Site no. : 10m Chamber Data no. : 76  
 Dis. / Ant. : 3m 3115(0911) Ant. pol. : HORIZONTAL  
 Limit : FCC PART 15C AV  
 Env. / Ins. : 23°C/54% Engineer : Sunny-lu  
 EUT : 150M Wireless Lite-N Access Point  
 Power : DC 9V From Adapter Input AC 120V/60Hz  
 Test mode : IEEE802.11b CH1 2412MHz Tx  
 M/N : PW-AN401D/M-WA701ND

	Ant. Freq. (MHz)	Ant. Factor (dB/m)	Cable loss (dB)	Amp. Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2390.000	29.44	8.67	36.09	36.97	38.99	54.00	15.01	Average
2	2397.240	29.44	8.72	36.09	57.67	59.74	54.00	-5.74	Average
3	2400.000	29.44	8.72	36.09	53.60	55.67	54.00	-1.67	Average
4	2409.240	29.45	8.72	35.95	90.25	92.47	54.00	-38.47	Average

Remarks:

1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.




Site no. : 10m Chamber Data no. : 77  
 Dis. / Ant. : 3m 3115(0911) Ant. pol. : HORIZONTAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 23°C/54% Engineer : Sunny-lu  
 EUT : 150M Wireless Lite-N Access Point  
 Power : DC 9V From Adapter Input AC 120V/60Hz  
 Test mode : IEEE802.11b CH11 2462MHz Tx  
 M/N : PW-AN401D/M-WA701ND

	Ant. Freq. (MHz)	Ant. Factor (dB/m)	Cable loss (dB)	Amp. Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2463.090	29.48	8.82	36.02	95.96	98.24	74.00	-24.24	Peak
2	2483.500	29.49	8.87	35.97	48.58	50.97	74.00	23.03	Peak
3	2500.000	29.50	8.92	36.00	46.52	48.94	74.00	25.06	Peak

Remarks:

1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.






Site no. : 10m Chamber Data no. : 78  
 Dis. / Ant. : 3m 3115(0911) Ant. pol. : HORIZONTAL  
 Limit : FCC PART 15C AV  
 Env. / Ins. : 23°C/54% Engineer : Sunny-lu  
 EUT : 150M Wireless Lite-N Access Point  
 Power : DC 9V From Adapter Input AC 120V/60Hz  
 Test mode : IEEE802.11b CH11 2462MHz Tx  
 M/N : PW-AN401D/M-WA701ND

	Ant. Freq. (MHz)	Ant. Factor (dB/m)	Cable loss (dB)	Amp. Factor (dB)	Reading (dBUV)	Emission Level (dBUV/m)	Limits (dBUV/m)	Margin (dB)	Remark
1	2459.185	29.48	8.82	36.02	93.86	96.14	54.00	-42.14	Average
2	2483.500	29.49	8.87	35.97	38.41	40.80	54.00	13.20	Average
3	2500.000	29.50	8.92	36.00	36.46	38.88	54.00	15.12	Average

Remarks:

1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.




Site no. : 10m Chamber Data no. : 79  
 Dis. / Ant. : 3m 3115(0911) Ant. pol. : VERTICAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 23°C/54% Engineer : Sunny-lu  
 EUT : 150M Wireless Lite-N Access Point  
 Power : DC 9V From Adapter Input AC 120V/60Hz  
 Test mode : IEEE802.11b CH11 2462MHz Tx  
 M/N : PW-AN401D/M-WA701ND

	Ant.	Cable	Amp.	Emission					
	Freq.	Factor	loss	Factor	Reading	Level	Limits	Margin	Remark
	(MHz)	(dB/m)	(dB)	(dB)	(dBuV)	(dBuV/m)	(dBuV/m)	(dB)	
1	2463.090	29.48	8.82	36.02	109.77	112.05	74.00	-38.05	Peak
2	2483.500	29.49	8.87	35.97	59.18	61.57	74.00	12.43	Peak
3	2500.000	29.50	8.92	36.00	52.55	54.97	74.00	19.03	Peak

Remarks:

1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.




Site no. : 10m Chamber Data no. : 80  
 Dis. / Ant. : 3m 3115(0911) Ant. pol. : VERTICAL  
 Limit : FCC PART 15C AV  
 Env. / Ins. : 23°C/54% Engineer : Sunny-lu  
 EUT : 150M Wireless Lite-N Access Point  
 Power : DC 9V From Adapter Input AC 120V/60Hz  
 Test mode : IEEE802.11b CH11 2462MHz Tx  
 M/N : PW-AN401D/M-WA701ND

	Ant. Freq. (MHz)	Ant. Factor (dB/m)	Cable loss (dB)	Amp. Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2461.165	29.48	8.82	36.02	105.27	107.55	54.00	-53.55	Average
2	2483.500	29.49	8.87	35.97	47.30	49.69	54.00	4.31	Average
3	2484.760	29.49	8.87	35.97	48.12	50.51	54.00	3.49	Average
4	2500.000	29.50	8.92	36.00	40.81	43.23	54.00	10.77	Average

Remarks:

1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.




Site no. : 10m Chamber Data no. : 81  
 Dis. / Ant. : 3m 3115(0911) Ant. pol. : VERTICAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 23°C/54% Engineer : Sunny-lu  
 EUT : 150M Wireless Lite-N Access Point  
 Power : DC 9V From Adapter Input AC 120V/60Hz  
 Test mode : IEEE802.11g CH1 2412MHz Tx  
 M/N : PW-AN401D/M-WA701ND

	Ant. Freq. (MHz)	Ant. Factor (dB/m)	Cable loss (dB)	Amp. Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2384.000	29.43	8.67	36.00	63.95	66.05	74.00	7.95	Peak
2	2387.750	29.44	8.67	36.09	66.59	68.61	74.00	5.39	Peak
3	2390.000	29.44	8.67	36.09	61.18	63.20	74.00	10.80	Peak
4	2400.000	29.44	8.72	36.09	86.16	88.23	74.00	-14.23	Peak
5	2417.875	29.45	8.72	35.95	108.70	110.92	74.00	-36.92	Peak

Remarks:

1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.




Site no. : 10m Chamber Data no. : 82  
 Dis. / Ant. : 3m 3115(0911) Ant. pol. : VERTICAL  
 Limit : FCC PART 15C AV  
 Env. / Ins. : 23°C/54% Engineer : Sunny-lu  
 EUT : 150M Wireless Lite-N Access Point  
 Power : DC 9V From Adapter Input AC 120V/60Hz  
 Test mode : IEEE802.11g CH1 2412MHz Tx  
 M/N : PW-AN401D/M-WA701ND

	Ant. Freq. (MHz)	Ant. Factor (dB/m)	Cable loss (dB)	Amp. Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2374.625	29.43	8.67	36.00	42.42	44.52	54.00	9.48	Average
2	2390.000	29.44	8.67	36.09	46.14	48.16	54.00	5.84	Average
3	2400.000	29.44	8.72	36.09	60.54	62.61	54.00	-8.61	Average
4	2413.125	29.45	8.72	35.95	95.32	97.54	54.00	-43.54	Average

Remarks:

1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.




Site no. : 10m Chamber Data no. : 83  
 Dis. / Ant. : 3m 3115(0911) Ant. pol. : HORIZONTAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 23°C/54% Engineer : Sunny-lu  
 EUT : 150M Wireless Lite-N Access Point  
 Power : DC 9V From Adapter Input AC 120V/60Hz  
 Test mode : IEEE802.11g CH1 2412MHz Tx  
 M/N : PW-AN401D/M-WA701ND

	Ant. Freq. (MHz)	Ant. Factor (dB/m)	Cable loss (dB)	Amp. Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2346.250	29.41	8.57	35.99	49.59	51.58	74.00	22.42	Peak
2	2388.125	29.44	8.67	36.09	52.80	54.82	74.00	19.18	Peak
3	2390.000	29.44	8.67	36.09	50.22	52.24	74.00	21.76	Peak
4	2400.000	29.44	8.72	36.09	74.18	76.25	74.00	-2.25	Peak
5	2407.250	29.45	8.72	35.95	96.82	99.04	74.00	-25.04	Peak

Remarks:

1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.




Site no. : 10m Chamber Data no. : 84  
 Dis. / Ant. : 3m 3115(0911) Ant. pol. : HORIZONTAL  
 Limit : FCC PART 15C AV  
 Env. / Ins. : 23°C/54% Engineer : Sunny-lu  
 EUT : 150M Wireless Lite-N Access Point  
 Power : DC 9V From Adapter Input AC 120V/60Hz  
 Test mode : IEEE802.11g CH1 2412MHz Tx  
 M/N : PW-AN401D/M-WA701ND

	Ant. Freq. (MHz)	Ant. Factor (dB/m)	Cable loss (dB)	Amp. Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2390.000	29.44	8.67	36.09	38.35	40.37	54.00	13.63	Average
2	2400.000	29.44	8.72	36.09	45.91	47.98	54.00	6.02	Average
3	2417.250	29.45	8.72	35.95	82.55	84.77	54.00	-30.77	Average

Remarks:

1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.




Site no. : 10m Chamber Data no. : 85  
 Dis. / Ant. : 3m 3115(0911) Ant. pol. : HORIZONTAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 23°C/54% Engineer : Sunny-lu  
 EUT : 150M Wireless Lite-N Access Point  
 Power : DC 9V From Adapter Input AC 120V/60Hz  
 Test mode : IEEE802.11g CH11 2462MHz Tx  
 M/N : PW-AN401D/M-WA701ND

	Ant. Freq. (MHz)	Ant. Factor (dB/m)	Cable loss (dB)	Amp. Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2458.085	29.48	8.82	36.02	98.25	100.53	74.00	-26.53	Peak
2	2483.500	29.49	8.87	35.97	60.98	63.37	74.00	10.63	Peak
3	2487.565	29.50	8.87	36.00	59.23	61.60	74.00	12.40	Peak
4	2500.000	29.50	8.92	36.00	48.09	50.51	74.00	23.49	Peak

Remarks:

1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.






Site no. : 10m Chamber Data no. : 86  
 Dis. / Ant. : 3m 3115(0911) Ant. pol. : HORIZONTAL  
 Limit : FCC PART 15C AV  
 Env. / Ins. : 23°C/54% Engineer : Sunny-lu  
 EUT : 150M Wireless Lite-N Access Point  
 Power : DC 9V From Adapter Input AC 120V/60Hz  
 Test mode : IEEE802.11g CH11 2462MHz Tx  
 M/N : PW-AN401D/M-WA701ND

	Ant. Freq. (MHz)	Ant. Factor (dB/m)	Cable loss (dB)	Amp. Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2458.250	29.48	8.82	36.02	84.32	86.60	54.00	-32.60	Average
2	2483.500	29.49	8.87	35.97	41.72	44.11	54.00	9.89	Average
3	2500.000	29.50	8.92	36.00	36.60	39.02	54.00	14.98	Average

Remarks:

1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.




Site no. : 10m Chamber Data no. : 87  
 Dis. / Ant. : 3m 3115(0911) Ant. pol. : VERTICAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 23°C/54% Engineer : Sunny-lu  
 EUT : 150M Wireless Lite-N Access Point  
 Power : DC 9V From Adapter Input AC 120V/60Hz  
 Test mode : IEEE802.11g CH11 2462MHz Tx  
 M/N : PW-AN401D/M-WA701ND

	Ant. Freq. (MHz)	Ant. Factor (dB/m)	Cable loss (dB)	Amp. Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2466.500	29.48	8.82	36.02	107.95	110.23	74.00	-36.23	Peak
2	2483.500	29.49	8.87	35.97	66.44	68.83	74.00	5.17	Peak
3	2485.500	29.49	8.87	35.97	63.30	65.69	74.00	8.31	Peak
4	2488.115	29.50	8.87	36.00	62.96	65.33	74.00	8.67	Peak
5	2500.000	29.50	8.92	36.00	55.08	57.50	74.00	16.50	Peak

Remarks:

1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.




Site no. : 10m Chamber Data no. : 88  
 Dis. / Ant. : 3m 3115(0911) Ant. pol. : VERTICAL  
 Limit : FCC PART 15C AV  
 Env. / Ins. : 23°C/54% Engineer : Sunny-lu  
 EUT : 150M Wireless Lite-N Access Point  
 Power : DC 9V From Adapter Input AC 120V/60Hz  
 Test mode : IEEE802.11g CH11 2462MHz Tx  
 M/N : PW-AN401D/M-WA701ND

	Ant.	Cable	Amp.	Emission				Remark
Freq.	Factor	loss	Factor	Reading	Level	Limits	Margin	
(MHz)	(dB/m)	(dB)	(dB)	(dBuV)	(dBuV/m)	(dBuV/m)	(dB)	
1 2463.200	29.48	8.82	36.02	93.00	95.28	54.00	-41.28	Average
2 2483.500	29.49	8.87	35.97	47.58	49.97	54.00	4.03	Average
3 2500.000	29.50	8.92	36.00	37.06	39.48	54.00	14.52	Average

Remarks:

1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.




Site no. : 10m Chamber Data no. : 89  
 Dis. / Ant. : 3m 3115(0911) Ant. pol. : VERTICAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 23°C/54% Engineer : Sunny-lu  
 EUT : 150M Wireless Lite-N Access Point  
 Power : DC 9V From Adapter Input AC 120V/60Hz  
 Test mode : IEEE802.11n HT20 CH1 2412MHz Tx  
 M/N : PW-AN401D/M-WA701ND

	Ant. Freq. (MHz)	Ant. Factor (dB/m)	Cable loss (dB)	Amp. Factor (dB)	Emission Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2390.000	29.44	8.67	36.09	65.53	67.55	74.00	6.45	Peak
2	2400.000	29.44	8.72	36.09	86.54	88.61	74.00	-14.61	Peak
3	2414.760	29.45	8.72	35.95	108.53	110.75	74.00	-36.75	Peak

Remarks:

1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.




Site no. : 10m Chamber Data no. : 90  
 Dis. / Ant. : 3m 3115(0911) Ant. pol. : VERTICAL  
 Limit : FCC PART 15C AV  
 Env. / Ins. : 23°C/54% Engineer : Sunny-lu  
 EUT : 150M Wireless Lite-N Access Point  
 Power : DC 9V From Adapter Input AC 120V/60Hz  
 Test mode : IEEE802.11n HT20 CH1 2412MHz Tx  
 M/N : PW-AN401D/M-WA701ND

	Ant.	Cable	Amp.	Emission					
Freq.	Factor	loss	Factor	Reading	Level	Limits	Margin	Remark	
(MHz)	(dB/m)	(dB)	(dB)	(dBuV)	(dBuV/m)	(dBuV/m)	(dB)		
1 2390.000	29.44	8.67	36.09	49.08	51.10	54.00	2.90	Average	
2 2400.000	29.44	8.72	36.09	59.14	61.21	54.00	-7.21	Average	
3 2405.640	29.45	8.72	35.95	92.31	94.53	54.00	-40.53	Average	

Remarks:

1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.




Site no. : 10m Chamber Data no. : 91  
 Dis. / Ant. : 3m 3115(0911) Ant. pol. : HORIZONTAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 23\*C/54% Engineer : Sunny-lu  
 EUT : 150M Wireless Lite-N Access Point  
 Power : DC 9V From Adapter Input AC 120V/60Hz  
 Test mode : IEEE802.11n HT20 CH1 2412MHz Tx  
 M/N : PW-AN401D/M-WA701ND

	Ant. Freq. (MHz)	Ant. Factor (dB/m)	Cable loss (dB)	Amp. Factor (dB)	Reading (dBUV)	Emission Level (dBUV/m)	Limits (dBUV/m)	Margin (dB)	Remark
1	2390.000	29.44	8.67	36.09	53.44	55.46	74.00	18.54	Peak
2	2400.000	29.44	8.72	36.09	74.37	76.44	74.00	-2.44	Peak
3	2408.160	29.45	8.72	35.95	96.38	98.60	74.00	-24.60	Peak

Remarks:

1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.




Site no. : 10m Chamber Data no. : 92  
 Dis. / Ant. : 3m 3115(0911) Ant. pol. : HORIZONTAL  
 Limit : FCC PART 15C AV  
 Env. / Ins. : 23°C/54% Engineer : Sunny-lu  
 EUT : 150M Wireless Lite-N Access Point  
 Power : DC 9V From Adapter Input AC 120V/60Hz  
 Test mode : IEEE802.11n HT20 CH1 2412MHz Tx  
 M/N : PW-AN401D/M-WA701ND

	Ant. Freq. (MHz)	Ant. Factor (dB/m)	Cable loss (dB)	Amp. Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2390.000	29.44	8.67	36.09	39.90	41.92	54.00	12.08	Average
2	2400.000	29.44	8.72	36.09	47.62	49.69	54.00	4.31	Average
3	2405.640	29.45	8.72	35.95	78.70	80.92	54.00	-26.92	Average

Remarks:

1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.




Site no. : 10m Chamber Data no. : 93  
 Dis. / Ant. : 3m 3115(0911) Ant. pol. : HORIZONTAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 23\*C/54% Engineer : Sunny-lu  
 EUT : 150M Wireless Lite-N Access Point  
 Power : DC 9V From Adapter Input AC 120V/60Hz  
 Test mode : IEEE802.11n HT20 CH11 2462MHz Tx  
 M/N : PW-AN401D/M-WA701ND

	Ant. Freq. (MHz)	Ant. Factor (dB/m)	Cable loss (dB)	Amp. Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2463.365	29.48	8.82	36.02	96.78	99.06	74.00	-25.06	Peak
2	2483.500	29.49	8.87	35.97	60.35	62.74	74.00	11.26	Peak
3	2491.910	29.50	8.87	36.00	56.76	59.13	74.00	14.87	Peak
4	2500.000	29.50	8.92	36.00	47.60	50.02	74.00	23.98	Peak

Remarks:

1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.






Site no. : 10m Chamber Data no. : 94  
 Dis. / Ant. : 3m 3115(0911) Ant. pol. : HORIZONTAL  
 Limit : FCC PART 15C AV  
 Env. / Ins. : 23°C/54% Engineer : Sunny-lu  
 EUT : 150M Wireless Lite-N Access Point  
 Power : DC 9V From Adapter Input AC 120V/60Hz  
 Test mode : IEEE802.11n HT20 CH11 2462MHz Tx  
 M/N : PW-AN401D/M-WA701ND

	Ant.	Cable	Amp.	Emission					
Freq.	Factor	loss	Factor	Reading	Level	Limits	Margin	Remark	
(MHz)	(dB/m)	(dB)	(dB)	(dBuV)	(dBuV/m)	(dBuV/m)	(dB)		
1 2455.500	29.48	8.82	36.02	83.15	85.43	54.00	-31.43	Average	
2 2483.500	29.49	8.87	35.97	40.51	42.90	54.00	11.10	Average	
3 2500.000	29.50	8.92	36.00	36.64	39.06	54.00	14.94	Average	

Remarks:

1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.




Site no. : 10m Chamber Data no. : 95  
 Dis. / Ant. : 3m 3115(0911) Ant. pol. : VERTICAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 23°C/54% Engineer : Sunny-lu  
 EUT : 150M Wireless Lite-N Access Point  
 Power : DC 9V From Adapter Input AC 120V/60Hz  
 Test mode : IEEE802.11n HT20 CH11 2462MHz Tx  
 M/N : PW-AN401D/M-WA701ND

	Ant.	Cable	Amp.	Emission					
Freq.	Factor	loss	Factor	Reading	Level	Limits	Margin	Remark	
(MHz)	(dB/m)	(dB)	(dB)	(dBUV)	(dBUV/m)	(dBUV/m)	(dB)		
1 2459.075	29.48	8.82	36.02	106.59	108.87	74.00	-34.87	Peak	
2 2483.500	29.49	8.87	35.97	66.99	69.38	74.00	4.62	Peak	
3 2500.000	29.50	8.92	36.00	53.68	56.10	74.00	17.90	Peak	

Remarks:

1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.




Site no. : 10m Chamber Data no. : 96  
 Dis. / Ant. : 3m 3115(0911) Ant. pol. : VERTICAL  
 Limit : FCC PART 15C AV  
 Env. / Ins. : 23°C/54% Engineer : Sunny-lu  
 EUT : 150M Wireless Lite-N Access Point  
 Power : DC 9V From Adapter Input AC 120V/60Hz  
 Test mode : IEEE802.11n HT20 CH11 2462MHz Tx  
 M/N : PW-AN401D/M-WA701ND

	Ant. Freq. (MHz)	Ant. Factor (dB/m)	Cable loss (dB)	Amp. Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2463.200	29.48	8.82	36.02	89.96	92.24	54.00	-38.24	Average
2	2483.500	29.49	8.87	35.97	47.61	50.00	54.00	4.00	Average
3	2500.000	29.50	8.92	36.00	35.45	37.87	54.00	16.13	Average

Remarks:

1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.




```

Site no.      : 10m Chamber           Data no.   : 97
Dis. / Ant.  : 3m 3115(0911)         Ant. pol.  : VERTICAL
Limit        : FCC PART 15C PEAK
Env. / Ins.  : 23*C/54%              Engineer   : Sunny-lu
EUT          : 150M Wireless Lite-N Access Point
Power        : DC 9V From Adapter Input AC 120V/60Hz
Test mode    : IEEE802.11n HT40 CH1 2422MHz Tx
M/N         : PW-AN401D/M-WA701ND
    
```

	Ant. Freq. (MHz)	Ant. Factor (dB/m)	Cable loss (dB)	Amp. Factor (dB)	Emission Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2390.000	29.44	8.67	36.09	68.27	70.29	74.00	3.71	Peak
2	2400.000	29.44	8.72	36.09	82.26	84.33	74.00	-10.33	Peak
3	2426.370	29.46	8.77	36.01	100.88	103.10	74.00	-29.10	Peak

Remarks:

1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.




Site no. : 10m Chamber Data no. : 98  
 Dis. / Ant. : 3m 3115(0911) Ant. pol. : VERTICAL  
 Limit : FCC PART 15C AV  
 Env. / Ins. : 23°C/54% Engineer : Sunny-lu  
 EUT : 150M Wireless Lite-N Access Point  
 Power : DC 9V From Adapter Input AC 120V/60Hz  
 Test mode : IEEE802.11n HT40 CH1 2422MHz Tx  
 M/N : PW-AN401D/M-WA701ND

	Ant.	Cable	Amp.	Emission					
Freq.	Factor	loss	Factor	Reading	Level	Limits	Margin	Remark	
(MHz)	(dB/m)	(dB)	(dB)	(dBuV)	(dBuV/m)	(dBuV/m)	(dB)		
1 2390.000	29.44	8.67	36.09	48.24	50.26	54.00	3.74	Average	
2 2400.000	29.44	8.72	36.09	54.16	56.23	54.00	-2.23	Average	
3 2420.025	29.46	8.72	36.01	86.92	89.09	54.00	-35.09	Average	

Remarks:

1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.




Site no. : 10m Chamber Data no. : 99  
 Dis. / Ant. : 3m 3115(0911) Ant. pol. : HORIZONTAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 23°C/54% Engineer : Sunny-lu  
 EUT : 150M Wireless Lite-N Access Point  
 Power : DC 9V From Adapter Input AC 120V/60Hz  
 Test mode : IEEE802.11n HT40 CH1 2422MHz Tx  
 M/N : PW-AN401D/M-WA701ND

	Ant. Freq. (MHz)	Ant. Factor (dB/m)	Cable loss (dB)	Amp. Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2381.955	29.43	8.67	36.00	56.91	59.01	74.00	14.99	Peak
2	2390.000	29.44	8.67	36.09	54.33	56.35	74.00	17.65	Peak
3	2393.970	29.44	8.67	36.09	65.05	67.07	74.00	6.93	Peak
4	2400.000	29.44	8.72	36.09	66.18	68.25	74.00	5.75	Peak
5	2411.520	29.45	8.72	35.95	88.15	90.37	74.00	-16.37	Peak

Remarks:

1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.




Site no. : 10m Chamber Data no. : 100  
 Dis. / Ant. : 3m 3115(0911) Ant. pol. : HORIZONTAL  
 Limit : FCC PART 15C AV  
 Env. / Ins. : 23°C/54% Engineer : Sunny-lu  
 EUT : 150M Wireless Lite-N Access Point  
 Power : DC 9V From Adapter Input AC 120V/60Hz  
 Test mode : IEEE802.11n HT40 CH1 2422MHz Tx  
 M/N : PW-AN401D/M-WA701ND

	Ant. Freq. (MHz)	Ant. Factor (dB/m)	Cable loss (dB)	Amp. Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2390.000	29.44	8.67	36.09	39.54	41.56	54.00	12.44	Average
2	2400.000	29.44	8.72	36.09	47.11	49.18	54.00	4.82	Average
3	2413.275	29.45	8.72	35.95	74.42	76.64	54.00	-22.64	Average

Remarks:

1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.




Site no. : 10m Chamber Data no. : 101  
 Dis. / Ant. : 3m 3115(0911) Ant. pol. : HORIZONTAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 23°C/54% Engineer : Sunny-lu  
 EUT : 150M Wireless Lite-N Access Point  
 Power : DC 9V From Adapter Input AC 120V/60Hz  
 Test mode : IEEE802.11n HT40 CH7 2452MHz Tx  
 M/N : PW-AN401D/M-WA701ND

	Ant. Freq. (MHz)	Ant. Factor (dB/m)	Cable loss (dB)	Amp. Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2465.850	29.48	8.82	36.02	90.31	92.59	74.00	-18.59	Peak
2	2483.500	29.49	8.87	35.97	54.59	56.98	74.00	17.02	Peak
3	2487.750	29.50	8.87	36.00	58.69	61.06	74.00	12.94	Peak
4	2500.000	29.50	8.92	36.00	48.04	50.46	74.00	23.54	Peak

Remarks:

1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.






Site no. : 10m Chamber      Data no. : 102  
 Dis. / Ant. : 3m 3115(0911)      Ant. pol. : HORIZONTAL  
 Limit : FCC PART 15C AV  
 Env. / Ins. : 23°C/54%      Engineer : Sunny-lu  
 EUT : 150M Wireless Lite-N Access Point  
 Power : DC 9V From Adapter Input AC 120V/60Hz  
 Test mode : IEEE802.11n HT40 CH7 2452MHz Tx  
 M/N : PW-AN401D/M-WA701ND

	Ant. Freq. (MHz)	Ant. Factor (dB/m)	Cable loss (dB)	Amp. Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2454.000	29.48	8.82	36.02	79.44	81.72	54.00	-27.72	Average
2	2483.500	29.49	8.87	35.97	39.12	41.51	54.00	12.49	Average
3	2500.000	29.50	8.92	36.00	36.59	39.01	54.00	14.99	Average

Remarks:

1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.




Site no. : 10m Chamber Data no. : 103  
 Dis. / Ant. : 3m 3115(0911) Ant. pol. : VERTICAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 23°C/54% Engineer : Sunny-lu  
 EUT : 150M Wireless Lite-N Access Point  
 Power : DC 9V From Adapter Input AC 120V/60Hz  
 Test mode : IEEE802.11n HT40 CH7 2452MHz Tx  
 M/N : PW-AN401D/M-WA701ND

	Ant. Freq. (MHz)	Ant. Factor (dB/m)	Cable loss (dB)	Amp. Factor (dB)	Emission Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2441.250	29.47	8.77	36.06	102.24	104.42	74.00	-30.42	Peak
2	2483.500	29.49	8.87	35.97	63.03	65.42	74.00	8.58	Peak
3	2485.875	29.49	8.87	35.97	65.66	68.05	74.00	5.95	Peak
4	2491.275	29.50	8.87	36.00	64.45	66.82	74.00	7.18	Peak
5	2500.000	29.50	8.92	36.00	52.86	55.28	74.00	18.72	Peak

Remarks:

1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 10m Chamber Data no. : 104  
 Dis. / Ant. : 3m 3115(0911) Ant. pol. : VERTICAL  
 Limit : FCC PART 15C AV  
 Env. / Ins. : 23\*C/54% Engineer : Sunny-lu  
 EUT : 150M Wireless Lite-N Access Point  
 Power : DC 9V From Adapter Input AC 120V/60Hz  
 Test mode : IEEE802.11n HT40 CH7 2452MHz Tx  
 M/N : PW-AN401D/M-WA701ND

	Ant. Freq. (MHz)	Ant. Factor (dB/m)	Cable loss (dB)	Amp. Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2459.775	29.48	8.82	36.02	91.23	93.51	54.00	-39.51	Average
2	2483.500	29.49	8.87	35.97	48.20	50.59	54.00	3.41	Average
3	2500.000	29.50	8.92	36.00	40.03	42.45	54.00	11.55	Average

Remarks:

1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.

## 7. 6dB Bandwidth Test

### 7.1. Test Equipment

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	Spectrum Analyzer	Agilent	E4446A	US44300459	May.08,10	1 Year
2.	Attenuator	Agilent	8491B	MY39262165	May.08,10	1 Year
3.	RF Cable	Hubersuhner	SUCOFLEX102	28618/2	May.08,10	1 Year

### 7.2. Limit

For direct sequence systems, the minimum 6dB bandwidth shall be at least 500kHz

### 7.3. Test Procedure



The transmitter output was connected to a spectrum analyzer, The bandwidth of the fundamental frequency was measured by spectrum analyzer with 100kHz RBW and 300 kHz VBW. The 6dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 6dB.


### 7.4. Test Results

EUT: 150M Wireless Lite-N Access Point		
M/N: PW-AN401D/M-WA701ND		
Test date: 2010-09-07	Pressure: 100.6 kpa	Humidity: 60 %
Tested by: Sunny-lu	Test site: RF Site	Temperature: 25 °C


Cable loss: 0.6 dB		Attenuator loss: 20 dB	Antenna Gain: 4 dBi
Test Mode	CH	6dB bandwidth (MHz)	Limit (KHz)
11b	CH1	12.560	>500
	CH6	13.042	>500
	CH11	12.084	>500
11g	CH1	16.520	>500
	CH6	16.567	>500
	CH11	16.590	>500
11n HT20	CH1	17.791	>500
	CH6	17.715	>500
	CH11	17.698	>500
11n HT40	CH1	36.389	>500
	CH4	36.171	>500
	CH7	36.433	>500
Conclusion: PASS			



Test Mode: IEEE 802.11b TX







Test Mode: IEEE 802.11g TX







Test Mode: IEEE 802.11n HT20 TX









Test Mode: IEEE 802.11n HT40 TX





## 8. OUTPUT POWER TEST

### 8.1. Test Equipment

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	Power meter	Anritsu	ML2487A	6K00002472	Oct.20.09	1 Year
2.	Power sensor	Anritsu	MA2491A	0033005	Oct.20.09	1 Year
3.	Attenuator	Agilent	8491B	MY39262165	May.08,10	1 Year
4.	RF Cable	Hubersuhner	SUCOFLEX 102	28618/2	May.08,10	1 Year
5.	Spectrum Analyzer	Agilent	E4446A	US44300459	May.08,10	1 Year

### 8.2. Limit (FCC Part 15C 15.247 b(3))

For systems using digital modulation in the 2400—2483.5MHz, The Peak out put Power shall not exceed 1W(30dBm)

### 8.3. Test Procedure

- 1, Connected the EUT's antenna port to measure device by 20dB attenuator.
- 2, For IEEE 802.11b/g and IEEE802.11n HT20 mode, use a PK power meter which's bandwidth is above 6dB bandwidth of signal to measure out each test modes' PK output power.
- 3, For IEEE802.11n HT40 mode, because the signal's bandwidth is about 40MHz and above 20MHz bandwidth of power sensor ML2491A. So the channel power measure function of Spectrum Analyzer was used to measure out the PK output power of each test modes'



Note: The cable loss and attenuator loss were offset into measure device as an amplitude offset.


### 8.4. Test Results

EUT:150M Wireless Lite-N Access Point		
M/N:PW-AN401D/M-WA701ND		
Test date:2010-09-07	Pressure: 100.6 kpa	Humidity: 60 %
Tested by:Sunny-lu	Test site: RF Site	Temperature: 25 °C

Cable loss: 0.6dB		Attenuator loss: 20 dB	Antenna Gain: 4 dBi
Test Mode	CH	Peak output Power (dBm)	Limit (dBm)
11b	CH1	22.05	30
	CH6	22.76	30
	CH11	22.56	30
11g	CH1	21.72	30
	CH6	24.25	30
	CH11	18.72	30
11n HT20	CH1	20.60	30
	CH6	24.05	30
	CH11	18.60	30
11n HT40	CH1	17.75	30
	CH4	21.19	30
	CH7	17.62	30
Conclusion: PASS			

Test Mode: IEEE 802.11n HT40





## 9. POWER SPECTRAL DENSITY TEST

### 9.1. Test Equipment

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	Spectrum Analyzer	Agilent	E4446A	US44300459	May.08, 10	1 Year
2.	Attenuator	Agilent	8491B	MY39262165	May.08, 10	1 Year
3.	RF Cable	Hubersuhner	SUCOFLEX102	28618/2	May.08, 10	1Year

### 9.2. Limit

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8dBm in any 3kHz band during any time interval of continuous transmission.

### 9.3. Test Procedure

- 1, Connected the EUT's antenna port to spectrum analyzer device by 20dB attenuator.
- 2, Follow the test procedure as described in ANSI C.10: 2009 Clause 6.11.2.3 to measure out each test modes and chain's power density with 3KHz.



### 9.4. Test Results


EUT: 150M Wireless Lite-N Access Point		
M/N: PW-AN401D/M-WA701ND		
Test date: 2010-09-07	Pressure: 100.6kpa	Humidity: 60 %
Tested by: Sunny-lu	Test site: RF Site	Temperature: 25°C

Cable loss: 0.6 dB		Attenuator loss: 20 dB	Antenna Gain: 4 dBi
Test Mode	CH	Power density (dBm/3KHz)	Limit (dBm/3KHz)
11b	CH1	-9.98	8
	CH6	-8.43	8
	CH11	-9.47	8
11g	CH1	-12.27	8
	CH6	-10.30	8
	CH11	-14.51	8
11n HT20	CH1	-13.80	8
	CH6	-9.46	8
	CH11	-15.30	8
11n HT40	CH1	-17.71	8
	CH4	-13.99	8
	CH7	-17.95	8
Conclusion : PASS			






Test Mode: IEEE 802.11b TX








Test Mode: IEEE 802.11g TX








Test Mode: IEEE 802.11nHT20 TX





Test Mode: IEEE 802.11nHT40 TX





## **10. ANTENNA REQUIREMENT**

### **10.1 STANDARD APPLICABLE**

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

### **10.2 ANTENNA CONNECTED CONSTRUCTION**

The antennas used for this product is dipole antenna with SMA-B connecter and that no antenna other than that furnished by the responsible party shall be used with the device, the maximum peak gain of the transmit antenna is only 4dBi.

## **11.DEVIATION TO TEST SPECIFICATIONS**

[ NONE ]