

FCC PART 15C TEST REPORT FOR CERTIFICATION  
On Behalf of

Proware Technologies Co., Ltd.

150Mbps Wireless N USB Module

Model No.: PW-MN427\_34I

FCC ID: WWMMN427V3

Prepared for : Proware Technologies Co., Ltd.  
2nd F1 East Wing, South Section, Factory Building 24,  
Science&Technology Park, Shennan Rd, Nanshan District,  
Shenzhen

Prepared By : Audix Technology (Shenzhen) Co., Ltd.  
No. 6, Ke Feng Rd., 52 Block,  
Shenzhen Science & Industrial Park,  
Nantou, Shenzhen, Guangdong, China

Tel: (0755) 26639496

Report Number : ACS-F14100  
Date of Test : Feb.20~Mar.29, 2014  
Date of Report : Apr.04, 2014

## TABLE OF CONTENTS

Description	Page
<b>1. SUMMARY OF STANDARDS AND RESULTS .....</b>	<b>1-1</b>
1.1. Description of Standards and Results .....	1-1
<b>2. GENERAL INFORMATION .....</b>	<b>2-1</b>
2.1. Description of Device (EUT) .....	2-1
2.2. Test Information .....	2-2
2.3. Tested Supporting System Details .....	2-3
2.4. Block Diagram of Test Setup .....	2-3
2.5. Test Facility .....	2-4
2.6. Measurement Uncertainty (95% confidence levels, k=2).....	2-4
<b>3. POWER LINE CONDUCTED EMISSION TEST.....</b>	<b>3-1</b>
3.1. Test Equipments .....	3-1
3.2. Block Diagram of Test Setup .....	3-1
3.3. Power Line Conducted Emission Test Limits .....	3-1
3.4. Configuration of EUT on Test.....	3-2
3.5. Operating Condition of EUT .....	3-2
3.6. Test Procedure .....	3-2
3.7. Power Line Conducted Emission Test Results .....	3-2
<b>4. RADIATED EMISSION TEST .....</b>	<b>4-1</b>
4.1. Test Equipment.....	4-1
4.2. Block Diagram of Test Setup .....	4-2
4.3. Radiated Emission Limit .....	4-3
4.4. EUT Configuration on Test .....	4-3
4.5. Operating Condition of EUT .....	4-3
4.6. Test Procedure .....	4-3
4.7. Radiated Emission Test Results .....	4-4
<b>5. CONDUCTED SPURIOUS EMISSIONS .....</b>	<b>5-1</b>
5.1. Test Equipment.....	5-1
5.2. Limit .....	5-1
5.3. Test Procedure .....	5-1
5.4. Test result .....	5-1
<b>6. BAND EDGE COMPLIANCE TEST .....</b>	<b>6-1</b>
6.1. Test Equipment.....	6-1
6.2. Limit .....	6-1
6.3. Test Produce .....	6-1
6.4. Test Results .....	6-1
<b>7. 6dB Bandwidth Test .....</b>	<b>7-1</b>
7.1. Test Equipment.....	7-1
7.2. Limit .....	7-1
7.3. Test Procedure .....	7-1
7.4. Test Results .....	7-1
<b>8. OUTPUT POWER TEST .....</b>	<b>8-1</b>
8.1. Test Equipment.....	8-1
8.2. Limit (FCC Part 15C 15.247 b(3)) .....	8-1
8.3. Test Procedure .....	8-1
8.4. Test Results .....	8-2
<b>9. POWER SPECTRAL DENSITY TEST .....</b>	<b>9-1</b>
9.1. Test Equipment.....	9-1

9.2.	Limit .....	9-1
9.3.	Test Procedure .....	9-1
9.4.	Test Results .....	9-2
<b>10.</b>	<b>MPE ESTIMATION .....</b>	<b>10-1</b>
10.1.	Limit for General Population/ Uncontrolled Exposures .....	10-1
10.2.	Estimation Result.....	10-1
<b>11.</b>	<b>ANTENNA REQUIREMENT .....</b>	<b>11-1</b>
11.1.	STANDARD APPLICABLE .....	11-1
11.2.	ANTENNA CONNECTED CONSTRUCTION .....	11-1
<b>12.</b>	<b>DEVIATION TO TEST SPECIFICATIONS .....</b>	<b>12-1</b>
<b>13.</b>	<b>PHOTOGRAPH OF TEST.....</b>	<b>13-1</b>
13.1.	Photos of Power Line Conducted Emission Test .....	13-1
13.2.	Photos of Radiated Emission Test .....	13-2
<b>14.</b>	<b>PHOTOS OF THE EUT .....</b>	<b>14-1</b>

## TEST REPORT CERTIFICATION

Applicant : Proware Technologies Co., Ltd.  
 Manufacturer : Proware Technologies Co., Ltd.  
 EUT Description : 150Mbps Wireless N USB Module  
 FCC ID : WWMMN427V3  
 (A) MODEL NO. : PW-MN427\_34I  
 (B) SERIAL NO. : N/A  
 (C) POWER SUPPLY : DC 3.3V From PC  
 (D) TEST VOLTAGE : DC 3.3V From PC Input AC 120V/60Hz

Tested for comply with:  
 FCC Rules and Regulations Part 15 Subpart C: 2012

Test procedure used:  
 ANSI C63.10:2009

The device described above is tested by AUDIX TECHNOLOGY (SHENZHEN) CO., LTD. to confirm comply with all the FCC Part 15 Subpart C requirements. The test results are contained in this test report and AUDIX TECHNOLOGY (SHENZHEN) CO., LTD. is assumed full responsibility for the accuracy and completeness of these tests. Also, this report shows that the Equipment Under Test (EUT) is to be technically compliant with the FCC and IC requirements. This report contains data that are not covered by the NVLAP accreditation.

This Report is made under FCC Part 2.1075. No modifications were required during testing to bring this product into compliance.

This report applies to above tested sample only. This report shall not be reproduced in part without written approval of AUDIX TECHNOLOGY (SHENZHEN) CO., LTD..

The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the federal government.

Date of Test : Feb.20~ Mar.29, 2014 Report of date: Apr.04, 2014

Prepared by : Selina Liu Reviewed by : Sunny Lu  
 Selina Liu / Supervisor Sunny Lu / Assistant Manager

信華科技 (深圳) 有限公司  
 Audix Technology (Shenzhen) Co., Ltd.  
 EMC 部門報告專用章  
 Stamp only for EMQ Dept. Report  
 Signature: David Jin 4.9

Approved & Authorized Signer : David Jin  
 David Jin / Manager

## 1. SUMMARY OF STANDARDS AND RESULTS

### 1.1. Description of Standards and Results

The EUT have been tested according to the applicable standards as referenced below.

EMISSION		
Description of Test Item	Standard	Results
Power Line Conducted Emission	FCC Part 15: 15.207 ANSI C63.10: 2009	PASS
Radiated Emission	FCC Part 15: 15.209 ANSI C63.10: 2009	PASS
Band Edge Compliance	FCC Part 15: 15.247 ANSI C63.10: 2009	PASS
Conducted spurious emissions	FCC Part 15: 15.247 ANSI C63.10: 2009	PASS
6dB Bandwidth	FCC Part 15: 15.247 ANSI C63.10: 2009	PASS
Peak Output Power	FCC Part 15: 15.247 ANSI C63.10: 2009	PASS
Power Spectral Density	FCC Part 15: 15.247 ANSI C63.10: 2009	PASS
Antenna requirement	FCC Part 15: 15.203	PASS

## 2. GENERAL INFORMATION

### 2.1. Description of Device (EUT)

Product Name	: 150Mbps Wireless N USB Module
Model Number	: PW-MN427_34I
FCC ID	: WWMMN427V3
Operation Frequency	: IEEE 802.11b: 2412MHz—2462MHz IEEE 802.11g: 2412MHz—2462MHz IEEE802.11n HT20: 2412MHz—2462MHz IEEE802.11n HT40: 2422MHz—2452MHz
Channel Number	: IEEE 802.11b/g, IEEE 802.11n HT20: 11 Channels IEEE 802.11n HT40: 7Channels
Modulation Technology	: IEEE 802.11b: DSSS(CCK,DQPSK,DBPSK) IEEE 802.11g: OFDM(64QAM, 16QAM, QPSK, BPSK) IEEE 802.11n HT20, HT40: OFDM (64QAM, 16QAM, QPSK,BPSK)
Antenna Assembly Gain	: IFA antenna, PK gain 1.8dBi
Applicant	: Proware Technologies Co., Ltd. 2nd F1 East Wing, South Section, Factory Building 24, Science&Technology Park, Shennan Rd, Nanshan District, Shenzhen
Manufacturer	: Proware Technologies Co., Ltd. 2nd F1 East Wing, South Section, Factory Building 24, Science&Technology Park, Shennan Rd, Nanshan District, Shenzhen
Date of Test	: Feb.20~Mar.29, 2014
Date of Receipt	: Feb.19, 2014
Sample Type	: Prototype production

## 2.2. Test Information

A special test software was used to control EUT work in Continuous TX mode(100% duty cycle), and select test channel, wireless mode and data rate.


Tested mode, channel, and data rate information			
Mode	data rate (Mbps)(see Note)	Channel	Frequency (MHz)
IEEE 802.11b	11	Low :CH1	2412
	11	Middle: CH6	2437
	11	High: CH11	2462
IEEE 802.11g	54	Low :CH1	2412
	54	Middle: CH6	2437
	54	High: CH11	2462
IEEE 802.11n HT20	6.5	Low :CH1	2412
	6.5	Middle: CH6	2437
	6.5	High: CH11	2462
IEEE 802.11n HT40	13.5	Low :CH1	2422
	13.5	Middle: CH4	2437
	13.5	High: CH7	2452

Note1: According exploratory test, EUT will have maximum PK output power in those data rate, so those data rate were used for all test.

### 2.3. Tested Supporting System Details

No.	Description	ACS No.	Manufacturer	Model	Serial Number	Approved type
1	Notebook	N/A	DELL	PP09S	N/A	<input checked="" type="checkbox"/> FCC DoC <input checked="" type="checkbox"/> BSMI ID: R41108
Power Cord: Unshielded, Detachable, 1.8m Power Adapter: Manufacturer: DELL, M/N: LA65NS1-00 Cable: Unshielded, Detachable, 4.0m(Bond one ferrite core)						

### 2.4. Block Diagram of Test Setup



**(EUT: 150Mbps Wireless N USB Module)**



## 2.5. Test Facility

### Site Description

Name of Firm : Audix Technology (Shenzhen) Co., Ltd.  
No. 6, Ke Feng Rd., 52 Block, Shenzhen  
Science & Industrial Park,Nantou,  
Shenzhen, Guangdong, China

3m Anechoic Chamber : Certificated by FCC, USA  
Registration Number: 90454  
Valid Date: Feb.22, 2015

3m & 10m Anechoic Chamber : Certificated by FCC, USA  
Registration Number: 794232  
Valid Date: Oct.31, 2015

EMC Lab. : Certificated by Industry Canada  
Registration Number: IC 5183A-1  
Valid Date: Jun.13, 2014

: Certificated by DAkkS, Germany  
Registration No: D-PL-12151-01-00  
Valid Date: Dec.15, 2016

: Accredited by NVLAP, USA  
NVLAP Code: 200372-0  
Valid Date: Mar.31, 2015

## 2.6. Measurement Uncertainty (95% confidence levels, k=2)


Test Item	Uncertainty
Uncertainty for Conduction emission test in No. 1 Conduction	3.08 dB(9KHz to 150KHz)
	3.10 dB(150kHz to 30MHz)
Uncertainty for Radiation Emission test in 3m chamber	3.22 dB(30~200MHz, Polarize: H)
	3.23 dB(30~200MHz, Polarize: V)
	3.49 dB(200M~1GHz, Polarize: H)
	3.39 dB(200M~1GHz, Polarize: V)
Uncertainty for Radiation Emission test in 3m chamber (1GHz-18GHz)	4.97 dB (Distance: 3m Polarize: V)
	4.99 dB (Distance: 3m Polarize: H)
Uncertainty for Radiated Spurious Emission test in RF chamber	3.57 dB
Uncertainty for Conduction Spurious emission test	2.00 dB
Uncertainty for Output power test	0.73 dB
Uncertainty for Power density test	2.00 dB
Uncertainty for Frequency range test	$7 \times 10^{-8}$
Uncertainty for Bandwidth test	83 kHz
Uncertainty for DC power test	0.038 %
Uncertainty for test site temperature and humidity	0.6°C
	3%

### 3. POWER LINE CONDUCTED EMISSION TEST

#### 3.1. Test Equipments

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	1# Shielding Room	AUDIX	N/A	N/A	Apr.18,13	1 Year
2.	Test Receiver	Rohde & Schwarz	ESHS10	838693/001	Oct.31, 13	1 Year
3.	L.I.S.N.#1	Rohde & Schwarz	ESH2-Z5	100429	Jan.22, 14	1 Year
4.	L.I.S.N.#3	Kyoritsu	KNW-242C	8-1920-1	May.08, 13	1 Year
5.	Terminator	Hubersuhner	50Ω	No. 1	May.08, 13	1 Year
6.	Terminator	Hubersuhner	50Ω	No. 2	May.08, 13	1 Year
7.	RF Cable	Hubersuhner	RG58	0100.6954.20#	Jan.22, 14	1 Year
8.	Coaxial Switch	Anritsu	MP59B	M50564	May.08, 13	1 Year
9.	Pulse Limiter	Rohde & Schwarz	ESH3-Z2	101838	Jan.22, 14	1 Year
10.	MPEG2 Measurement Generator	ROHDE&SCHWARZ	DVG	100319	Dec.11, 13	1 Year
11.	TV Transmitter	ROHDE&SCHWARZ	SFQ	100521	May.08, 13	1 Year
12.	Signal Generator	HP	8648A	3625U00573	May.08, 13	1 Year
13.	Pattern Generator	Philiphs	PM5418	LO625020	May.08, 13	1 Year

#### 3.2. Block Diagram of Test Setup



#### 3.3. Power Line Conducted Emission Test Limits

Frequency	Maximum RF Line Voltage	
	Quasi-Peak Level dB(μV)	Average Level dB(μV)
150kHz ~ 500kHz	66 ~ 56*	56 ~ 46*
500kHz ~ 5MHz	56	46
5MHz ~ 30MHz	60	50

Notes: 1. \* Decreasing linearly with logarithm of frequency.

2. The lower limit shall apply at the transition frequencies.

### 3.4. Configuration of EUT on Test

The following equipment are installed on Power Line Conducted Emission Test to meet the commission requirement and operating regulations in a manner which tends to maximize its emission characteristics in a normal application.

#### 3.4.1. 150Mbps Wireless N USB Module (EUT)

Model Number : PW-MN427\_34I  
Serial Number : N/A

3.4.2. Support Equipment: As Tested Supporting System Details, in Section 2.2.

### 3.5. Operating Condition of EUT

3.5.1. Setup the EUT and simulator as shown as Section 3.2.

3.5.2. Turned on the power of all equipment.

3.5.3. PC run test software to control EUT work in Tx mode.

### 3.6. Test Procedure


The EUT was placed on a non-metallic table, 80cm above the ground plane. The EUT Power connected to the power mains through a line impedance stabilization network (L.I.S.N. 1#). This provides a 50 ohm coupling impedance for the EUT (Please refer the block diagram of the test setup and photographs). The AC line are checked to find out the maximum conducted emission. In order to find the maximum emission levels, the relative positions of equipment and all of the interface cables shall be changed according to ANSI C63.10: 2009 on Conducted Emission Test.

The bandwidth of test receiver (R & S ESHS10) is set at 9kHz.

The frequency range from 150kHz to 30MHz is checked.

### 3.7. Power Line Conducted Emission Test Results

**PASS.** (All emissions not reported below are too low against the prescribed limits.)



Trace: (Discrete)

Site no :1#conduction Data No :7

Dis./Ant. :2014 ESH2-25 LINE

Limit :FCC PART 15 C

Env./Ins. :26.5\*C/45% Engineer :Leo-Li

EUT :150Mbps Wireless N USB Module

Power Rating :DC 3.3V From PC Input AC 120V/60Hz

Test Mode :Tx Mode

M/N:PW-MN427\_34I


No	Freq (MHz)	LISN Factor (dB)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV)	Limits (dBuV)	Margin (dB)	Remark
1	0.17985	0.13	9.88	37.52	47.53	64.49	16.96	QP
2	0.26940	0.14	9.88	30.72	40.74	61.14	20.40	QP
3	0.32910	0.14	9.88	29.64	39.66	59.47	19.81	QP
4	0.38880	0.14	9.88	25.63	35.65	58.09	22.44	QP
5	2.807	0.22	9.92	19.86	30.00	56.00	26.00	QP
6	4.419	0.25	9.94	18.29	28.48	56.00	27.52	QP

Remarks: 1.Emission Level=LISN Factor+Cable Loss+Reading.  
 2.If the average limit is met when using a quasi-peak detector. the EUT shall be deemed to meet both limits and measurement with average detector is unnecessary.

Data: 8

File: G:\2014 Report\PI\Proware\ACS14Q0239.EM6 (8)

Date: 2014-03-29



Trace: (Discrete)

Site no :1#conduction Data No :8  
 Dis./Ant. :2014 ESH2-25 NEUTRAL  
 Limit :FCC PART 15 C  
 Env./Ins. :26.5°C/45% Engineer :Leo-Li  
 EUT :150Mbps Wireless N USB Module  
 Power Rating :DC 3.3V From PC Input AC 120V/60Hz  
 Test Mode :Tx Mode  
 M/N:PW-MN427\_34I

No	Freq (MHz)	LISN Factor (dB)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV)	Limits (dBuV)	Margin (dB)	Remark
1	0.20970	0.13	9.88	37.14	47.15	63.22	16.07	QP
2	0.23955	0.13	9.88	34.99	45.00	62.11	17.11	QP
3	0.32910	0.14	9.88	33.33	43.35	59.47	16.12	QP
4	0.56790	0.15	9.88	25.50	35.53	56.00	20.47	QP
5	1.672	0.19	9.90	16.02	26.11	56.00	29.89	QP
6	4.031	0.27	9.94	19.03	29.24	56.00	26.76	QP

Remarks: 1.Emission Level=LISN Factor+Cable Loss+Reading.  
 2.If the average limit is met when using a quasi-peak detector, the EUT shall be deemed to meet both limits and measurement with average detector is unnecessary.

## 4. RADIATED EMISSION TEST

### 4.1. Test Equipment

#### 4.1.1. For frequency range 30MHz~1000MHz (At Anechoic Chamber)


Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1	3#Chamber	AUDIX	N/A	N/A	Nov.24, 13	1 Year
2	EMI Spectrum	Agilent	E4407B	MY41440292	May.08, 13	1 Year
3	Test Receiver	Rohde & Schwarz	ESVS10	834468/011	May.08, 13	1 Year
4	Amplifier	HP	8447D	2648A04738	May.08, 13	1 Year
5	Bilog Antenna	TESEQ	CBL6112D	35375	May.30, 13	1 Year
6	RF Cable	MIYAZAKI	CFD400-NL	3# Chamber No.1	May.08, 13	1 Year
7	Coaxial Switch	Anritsu	MP59B	M74389	May.08, 13	1 Year

#### 4.1.2. For frequency range 1GHz~25GHz (At Anechoic Chamber)


Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1	3#Chamber	AUDIX	N/A	N/A	Nov.24, 13	1 Year
2	Spectrum Analyzer	Agilent	E4407B	MY41440292	May.08, 13	1 Year
3	Horn Antenna	EMCO	3115	9510-4580	May.28,13	1 Year
4	Amplifier	Agilent	8449B	3008A00863	May.08, 13	1 Year
5	RF Cable	Hubersuhner	SUCOFLEX106	77977/6	May.08, 13	1 Year
6	RF Cable	Hubersuhner	SUCOFLEX106	28616/2	May.08, 13	1 Year

### 4.2. Block Diagram of Test Setup

For frequency range 30MHz-1000MHz



For frequency range 1GHz-25GHz



### 4.3. Radiated Emission Limit

#### 4.3.1. 15.209 limits

FREQUENCY MHz	DISTANCE Meters	FIELD STRENGTHS LIMIT	
		μV/m	dB(μV)/m
30 ~ 88	3	100	40.0
88 ~ 216	3	150	43.5
216 ~ 960	3	200	46.0
960 ~ 1000	3	500	54.0
Above 1000	3	74.0 dB(μV)/m (Peak) 54.0 dB(μV)/m (Average)	

Remark : (1) Emission level  $\text{dB}\mu\text{V} = 20 \log \text{Emission level } \mu\text{V}/\text{m}$

(2) The smaller limit shall apply at the cross point between two frequency bands.

(3) Distance is the distance in meters between the measuring instrument, antenna and the closest point of any part of the device or system.

#### 4.3.2. 15.205 Restricted bands of operation

MHz	MHz	MHz	GHz
0.090 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
<sup>1</sup> 0.495 - 0.505	16.69475 - 16.69525	608 - 614	5.35 - 5.46
2.1735 - 2.1905	16.80425 - 16.80475	960 - 1240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1300 - 1427	8.025 - 8.5
4.17725 - 4.17775	37.5 - 38.25	1435 - 1626.5	9.0 - 9.2
4.20725 - 4.20775	73 - 74.6	1645.5 - 1646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1660 - 1710	10.6 - 12.7
6.26775 - 6.26825	108 - 121.94	1718.8 - 1722.2	13.25 - 13.4
6.31175 - 6.31225	123 - 138	2200 - 2300	14.47 - 14.5
8.291 - 8.294	149.9 - 150.05	2310 - 2390	15.35 - 16.2
8.362 - 8.366	156.52475 - 156.52525	2483.5 - 2500	17.7 - 21.4
8.37625 - 8.38675	156.7 - 156.9	2690 - 2900	22.01 - 23.12
8.41425 - 8.41475	162.0125 - 167.17	3260 - 3267	23.6 - 24.0
12.29 - 12.293	167.72 - 173.2	3332 - 3339	31.2 - 31.8
12.51975 - 12.52025	240 - 285	3345.8 - 3358	36.43 - 36.5
12.57675 - 12.57725	322 - 335.4	3600 - 4400	( <sup>2</sup> )

All the emissions appearing within 15.205 restricted frequency bands shall not exceed the limits shown in 15.209, all the other emissions shall be at least 20dB below the fundamental emissions, or comply with 15.209 limits.

### 4.4. EUT Configuration on Test

The configurations of EUT are listed in Section 3.5.

### 4.5. Operating Condition of EUT

Same as Conducted Emission test that is listed in Section 3.6. except the test set up replaced by Section 4.2.

### 4.6. Test Procedure

EUT and its simulators are placed on a turn table, which is 0.8 meter high above ground. The turn table can rotate 360 degrees to determine the position of the maximum emission level. Power on the EUT and let it working in test mode, then test it. EUT is set 3 meters away from the receiving antenna, which is mounted on a antenna tower. The antenna can be moved up and down between 1 meter and 4 meters to find out the maximum emission level. Broadband



antenna (calibrated bilog antenna) is used as receiving antenna. Both horizontal and vertical polarization of the antenna are set on test.

This test was performed with EUT in X, Y, Z position, and the worse case was found when EUT in X position as test photo indicated.

The bandwidth of the EMI test receiver (R&S ESVS10) is set at 120kHz for frequency range from 30MHz to 1000 MHz.

The bandwidth of the Spectrum's VBW is set at 3MHz and RBW is set at 1MHz for peak emissions measurement above 1GHz and 1MHz RBW, 10Hz VBW for average emissions measure above 1GHz

The frequency range from 30MHz to 10<sup>th</sup> harmonic (25GHz) are checked. and no any emissions were found from 18GHz to 25 GHz, So the radiated emissions from 18GHz to 25GHz were not record.

#### 4.7. Radiated Emission Test Results

**PASS.**

All the emissions from 30MHz to 25 GHz were comply with 15.209 limits.


Note: For emissions above 1GHz, if peak level comply with average limit, then the average level is deemed to comply with average limit.

Frequency: 30MHz~1GHz

Data: 2

File: G:\2014 Report\PI\Proware\ACS14Q0239.EM6 (2)


Date: 2014-02-26



Site no. : 3m Chamber Data no. : 2  
 Dis. / Ant. : 3m 2013 CBL6112D 35375 Ant. pol. : HORIZONTAL  
 Limit : FCC PART 15 C (3M)  
 Env. / Ins. : 24°C/65% Engineer : Even\_Deng  
 EUT : 150Mbps Wireless N USB Module  
 Power rating : DC 3.3V From PC Input AC 120V/60Hz  
 Test Mode : TX Mode  
 M/N:PW-MN427\_34I

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	30.000	20.10	0.83	9.45	30.38	40.00	9.62	QP
2	170.650	10.17	1.68	11.79	23.64	43.50	19.86	QP
3	250.190	13.11	1.98	12.05	27.14	46.00	18.86	QP
4	280.260	13.60	2.09	10.18	25.87	46.00	20.13	QP
5	301.600	14.03	2.17	9.61	25.81	46.00	20.19	QP
6	377.260	15.85	2.39	6.85	25.09	46.00	20.91	QP

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading.  
 2. The emission levels that are 20dB below the official limit are not reported.




Site no. : 3m Chamber Data no. : 1  
 Dis. / Ant. : 3m 2013 CBL6112D 35375 Ant. pol. : VERTICAL  
 Limit : FCC PART 15 C (3M)  
 Env. / Ins. : 24°C/65% Engineer : Even\_Deng  
 EUT : 150Mbps Wireless N USB Module  
 Power rating : DC 3.3V From PC Input AC 120V/60Hz  
 Test Mode : TX Mode  
 M/N:PW-MN427\_34I

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	30.000	20.10	0.83	11.51	32.44	40.00	7.56	QP
2	59.100	6.79	1.23	19.06	27.08	40.00	12.92	QP
3	142.520	11.77	1.57	16.37	29.71	43.50	13.79	QP
4	250.190	13.11	1.98	14.25	29.34	46.00	16.66	QP
5	419.940	17.40	2.52	5.63	25.55	46.00	20.45	QP
6	815.700	20.81	3.66	6.48	30.95	46.00	15.05	QP

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading.  
 2. The emission levels that are 20dB below the official limit are not reported.


Frequency: 1GHz~18GHz



Site no. : 3m Chamber Data no. : 1  
 Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : HORIZONTAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 24°C/56% Engineer : Leo-Li  
 EUT : 150Mbps Wireless N USB Module  
 Power Rating : DC 3.3V From PC Input AC 120V/60Hz  
 Test Mode : IEEE802.11b 2412MHz Tx  
 M/N : PW-MN427\_34I

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	1324.000	24.57	4.23	36.44	47.46	39.82	74.00	34.18	Peak
2	2412.000	28.21	5.81	35.70	92.48	90.80	74.00	-16.80	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading - Amp Factor  
 2. The emission levels that are 20dB below the official limit are not reported.




Site no. : 3m Chamber Data no. : 2  
 Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : VERTICAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 24°C/56% Engineer : Leo-Li  
 EUT : 150Mbps Wireless N USB Module  
 Power Rating : DC 3.3V From PC Input AC 120V/60Hz  
 Test Mode : IEEE802.11b 2412MHz Tx  
 M/N : PW-MN427\_34I

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission			Remark
						Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	
1	2412.000	28.21	5.81	35.70	101.97	100.29	74.00	-26.29	Peak
2	3214.000	30.83	6.89	35.70	45.94	47.96	74.00	26.04	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading  
 -Amp Factor  
 2. The emission levels that are 20dB below the official  
 limit are not reported.




Site no. : 3m Chamber Data no. : 7  
Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : HORIZONTAL  
Limit : FCC PART 15C PEAK  
Env. / Ins. : 24°C/56% Engineer : Leo-Li  
EUT : 150Mbps Wireless N USB Module  
Power Rating : DC 3.3V From PC Input AC 120V/60Hz  
Test Mode : IEEE802.11b 2412MHz Tx  
M/N : PW-MN427\_34I



Site no. : 3m Chamber Data no. : 8  
 Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : HORIZONTAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 24°C/56% Engineer : Leo-Li  
 EUT : 150Mbps Wireless N USB Module  
 Power Rating : DC 3.3V From PC Input AC 120V/60Hz  
 Test Mode : IEEE802.11b 2412MHz Tx  
 M/N : PW-MN427\_34I


No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	4824.000	32.88	8.58	35.70	34.12	39.88	54.00	14.12	Average
2	4824.000	32.88	8.58	35.70	44.39	50.15	74.00	23.85	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading - Amp Factor  
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 9  
Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : VERTICAL  
Limit : FCC PART 15C PEAK  
Env. / Ins. : 24°C/56% Engineer : Leo-Li  
EUT : 150Mbps Wireless N USB Module  
Power Rating : DC 3.3V From PC Input AC 120V/60Hz  
Test Mode : IEEE802.11b 2412MHz Tx  
M/N : PW-MN427\_34I







Site no. : 3m Chamber Data no. : 10  
 Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : VERTICAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 24°C/56% Engineer : Leo-Li  
 EUT : 150Mbps Wireless N USB Module  
 Power Rating : DC 3.3V From PC Input AC 120V/60Hz  
 Test Mode : IEEE802.11b 2412MHz Tx  
 M/N : PW-MN427\_34I

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	4824.000	32.88	8.58	35.70	38.07	43.83	54.00	10.17	Average
2	4824.000	32.88	8.58	35.70	45.76	51.52	74.00	22.48	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading - Amp Factor  
 2. The emission levels that are 20dB below the official limit are not reported.




Site no. : 3m Chamber Data no. : 11  
Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : VERTICAL  
Limit : FCC PART 15C PEAK  
Env. / Ins. : 24°C/56% Engineer : Leo-Li  
EUT : 150Mbps Wireless N USB Module  
Power Rating : DC 3.3V From PC Input AC 120V/60Hz  
Test Mode : IEEE802.11b 2437MHz Tx  
M/N : PW-MN427\_34I




Site no. : 3m Chamber Data no. : 12  
 Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : VERTICAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 24°C/56% Engineer : Leo-Li  
 EUT : 150Mbps Wireless N USB Module  
 Power Rating : DC 3.3V From PC Input AC 120V/60Hz  
 Test Mode : IEEE802.11b 2437MHz Tx  
 M/N : PW-MN427\_34I

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	4874.000	32.97	8.63	35.70	45.90	51.80	74.00	22.20	Peak
2	4874.000	32.97	8.63	35.70	36.88	42.78	54.00	11.22	Average

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading - Amp Factor  
 2. The emission levels that are 20dB below the official limit are not reported.




Site no. : 3m Chamber Data no. : 13  
Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : HORIZONTAL  
Limit : FCC PART 15C PEAK  
Env. / Ins. : 24°C/56% Engineer : Leo-Li  
EUT : 150Mbps Wireless N USB Module  
Power Rating : DC 3.3V From PC Input AC 120V/60Hz  
Test Mode : IEEE802.11b 2437MHz Tx  
M/N : PW-MN427\_34I



Site no. : 3m Chamber Data no. : 14  
 Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : HORIZONTAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 24°C/56% Engineer : Leo-Li  
 EUT : 150Mbps Wireless N USB Module  
 Power Rating : DC 3.3V From PC Input AC 120V/60Hz  
 Test Mode : IEEE802.11b 2437MHz Tx  
 M/N : PW-MN427\_34I

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	4874.000	32.97	8.63	35.70	33.63	39.53	54.00	14.47	Average
2	4874.000	32.97	8.63	35.70	44.22	50.12	74.00	23.88	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading - Amp Factor  
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 15  
 Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : HORIZONTAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 24°C/56% Engineer : Leo-Li  
 EUT : 150Mbps Wireless N USB Module  
 Power Rating : DC 3.3V From PC Input AC 120V/60Hz  
 Test Mode : IEEE802.11b 2437MHz Tx  
 M/N : PW-MN427\_34I

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2437.000	28.26	5.85	35.70	87.54	85.95	74.00	-11.95	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading - Amp Factor  
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 16  
 Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : VERTICAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 24°C/56% Engineer : Leo-Li  
 EUT : 150Mbps Wireless N USB Module  
 Power Rating : DC 3.3V From PC Input AC 120V/60Hz  
 Test Mode : IEEE802.11b 2437MHz Tx  
 M/N : PW-MN427\_34I

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission			Remark
						Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	
1	2437.000	28.26	5.85	35.70	98.78	97.19	74.00	-23.19	Peak
2	3250.000	30.90	6.93	35.70	45.11	47.24	74.00	26.76	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading  
 -Amp Factor  
 2. The emission levels that are 20dB below the official  
 limit are not reported.




Site no. : 3m Chamber Data no. : 17  
 Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : VERTICAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 24°C/56% Engineer : Leo-Li  
 EUT : 150Mbps Wireless N USB Module  
 Power Rating : DC 3.3V From PC Input AC 120V/60Hz  
 Test Mode : IEEE802.11b 2462MHz Tx  
 M/N : PW-MN427\_34I

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2462.000	28.32	5.89	35.70	95.06	93.57	74.00	-19.57	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading - Amp Factor  
 2. The emission levels that are 20dB below the official limit are not reported.







Site no. : 3m Chamber Data no. : 18  
 Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : HORIZONTAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 24°C/56% Engineer : Leo-Li  
 EUT : 150Mbps Wireless N USB Module  
 Power Rating : DC 3.3V From PC Input AC 120V/60Hz  
 Test Mode : IEEE802.11b 2462MHz Tx  
 M/N : PW-MN427\_34I

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2462.000	28.32	5.89	35.70	84.34	82.85	74.00	-8.85	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading - Amp Factor  
 2. The emission levels that are 20dB below the official limit are not reported.




Site no. : 3m Chamber Data no. : 23  
Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : VERTICAL  
Limit : FCC PART 15C PEAK  
Env. / Ins. : 24°C/56% Engineer : Leo-Li  
EUT : 150Mbps Wireless N USB Module  
Power Rating : DC 3.3V From PC Input AC 120V/60Hz  
Test Mode : IEEE802.11b 2462MHz Tx  
M/N : PW-MN427\_34I




Site no. : 3m Chamber Data no. : 24  
 Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : VERTICAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 24°C/56% Engineer : Leo-Li  
 EUT : 150Mbps Wireless N USB Module  
 Power Rating : DC 3.3V From PC Input AC 120V/60Hz  
 Test Mode : IEEE802.11b 2462MHz Tx  
 M/N : PW-MN427\_34I

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	4924.000	33.06	8.69	35.70	34.12	40.17	54.00	13.83	Average
2	4924.000	33.06	8.69	35.70	44.58	50.63	74.00	23.37	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading - Amp Factor  
 2. The emission levels that are 20dB below the official limit are not reported.




Site no. : 3m Chamber Data no. : 25  
Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : HORIZONTAL  
Limit : FCC PART 15C PEAK  
Env. / Ins. : 24°C/56% Engineer : Leo-Li  
EUT : 150Mbps Wireless N USB Module  
Power Rating : DC 3.3V From PC Input AC 120V/60Hz  
Test Mode : IEEE802.11b 2462MHz Tx  
M/N : PW-MN427\_34I




Site no. : 3m Chamber Data no. : 26  
 Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : HORIZONTAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 24°C/56% Engineer : Leo-Li  
 EUT : 150Mbps Wireless N USB Module  
 Power Rating : DC 3.3V From PC Input AC 120V/60Hz  
 Test Mode : IEEE802.11b 2462MHz Tx  
 M/N : PW-MN427\_34I

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	4924.000	33.06	8.69	35.70	43.75	49.80	74.00	24.20	Peak
2	4924.000	33.06	8.69	35.70	31.22	37.27	54.00	16.73	Average

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading - Amp Factor  
 2. The emission levels that are 20dB below the official limit are not reported.




Site no. : 3m Chamber Data no. : 27  
Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : HORIZONTAL  
Limit : FCC PART 15C PEAK  
Env. / Ins. : 24°C/56% Engineer : Leo-Li  
EUT : 150Mbps Wireless N USB Module  
Power Rating : DC 3.3V From PC Input AC 120V/60Hz  
Test Mode : IEEE802.11g 2412MHz Tx  
M/N : PW-MN427\_34I



Site no. : 3m Chamber Data no. : 28  
 Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : HORIZONTAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 24°C/56% Engineer : Leo-Li  
 EUT : 150Mbps Wireless N USB Module  
 Power Rating : DC 3.3V From PC Input AC 120V/60Hz  
 Test Mode : IEEE802.11g 2412MHz Tx  
 M/N : PW-MN427\_34I


No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	4824.000	32.88	8.58	35.70	44.03	49.79	74.00	24.21	Peak
2	4824.000	32.88	8.58	35.70	31.25	37.01	54.00	16.99	Average

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading - Amp Factor  
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 29  
Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : VERTICAL  
Limit : FCC PART 15C PEAK  
Env. / Ins. : 24°C/56% Engineer : Leo-Li  
EUT : 150Mbps Wireless N USB Module  
Power Rating : DC 3.3V From PC Input AC 120V/60Hz  
Test Mode : IEEE802.11g 2412MHz Tx  
M/N : PW-MN427\_34I






Site no. : 3m Chamber Data no. : 30  
 Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : VERTICAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 24°C/56% Engineer : Leo-Li  
 EUT : 150Mbps Wireless N USB Module  
 Power Rating : DC 3.3V From PC Input AC 120V/60Hz  
 Test Mode : IEEE802.11g 2412MHz Tx  
 M/N : PW-MN427\_34I

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	4824.000	32.88	8.58	35.70	44.81	50.57	74.00	23.43	Peak
2	4824.000	32.88	8.58	35.70	31.15	36.91	54.00	17.09	Average


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading - Amp Factor  
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 31  
 Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : VERTICAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 24°C/56% Engineer : Leo-Li  
 EUT : 150Mbps Wireless N USB Module  
 Power Rating : DC 3.3V From PC Input AC 120V/60Hz  
 Test Mode : IEEE802.11g 2412MHz Tx  
 M/N : PW-MN427\_34I

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission			Remark
						Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	
1	2412.000	28.21	5.81	35.70	104.15	102.47	74.00	-28.47	Peak
2	3214.000	30.83	6.89	35.70	46.86	48.88	74.00	25.12	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading  
 -Amp Factor  
 2. The emission levels that are 20dB below the official  
 limit are not reported.



Site no. : 3m Chamber Data no. : 32  
 Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : HORIZONTAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 24°C/56% Engineer : Leo-Li  
 EUT : 150Mbps Wireless N USB Module  
 Power Rating : DC 3.3V From PC Input AC 120V/60Hz  
 Test Mode : IEEE802.11g 2412MHz Tx  
 M/N : PW-MN427\_34I

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2412.000	28.21	5.81	35.70	93.56	91.88	74.00	-17.88	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading - Amp Factor  
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 37  
 Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : VERTICAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 24\*C/56% Engineer : Leo-Li  
 EUT : 150Mbps Wireless N USB Module  
 Power Rating : DC 3.3V From PC Input AC 120V/60Hz  
 Test Mode : IEEE802.11g 2437MHz Tx  
 M/N : PW-MN427\_34I

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	1456.000	25.04	4.42	36.30	45.76	38.92	74.00	35.08	Peak
2	2437.000	28.26	5.85	35.70	103.66	102.07	74.00	-28.07	Peak
3	3250.000	30.90	6.93	35.70	45.73	47.86	74.00	26.14	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading - Amp Factor  
 2. The emission levels that are 20dB below the official limit are not reported.




Site no. : 3m Chamber Data no. : 38  
 Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : HORIZONTAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 24°C/56% Engineer : Leo-Li  
 EUT : 150Mbps Wireless N USB Module  
 Power Rating : DC 3.3V From PC Input AC 120V/60Hz  
 Test Mode : IEEE802.11g 2437MHz Tx  
 M/N : PW-MN427\_34I

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2437.000	28.26	5.85	35.70	92.78	91.19	74.00	-17.19	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading - Amp Factor  
 2. The emission levels that are 20dB below the official limit are not reported.




Site no. : 3m Chamber Data no. : 39  
Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : VERTICAL  
Limit : FCC PART 15C PEAK  
Env. / Ins. : 24°C/56% Engineer : Leo-Li  
EUT : 150Mbps Wireless N USB Module  
Power Rating : DC 3.3V From PC Input AC 120V/60Hz  
Test Mode : IEEE802.11g 2437MHz Tx  
M/N : PW-MN427\_34I



Site no. : 3m Chamber Data no. : 40  
 Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : VERTICAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 24°C/56% Engineer : Leo-Li  
 EUT : 150Mbps Wireless N USB Module  
 Power Rating : DC 3.3V From PC Input AC 120V/60Hz  
 Test Mode : IEEE802.11g 2437MHz Tx  
 M/N : PW-MN427\_34I


No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	4874.000	32.97	8.63	35.70	44.57	50.47	74.00	23.53	Peak
2	4874.000	32.97	8.63	35.70	31.27	37.17	54.00	16.83	Average

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading - Amp Factor  
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 41  
Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : HORIZONTAL  
Limit : FCC PART 15C PEAK  
Env. / Ins. : 24°C/56% Engineer : Leo-Li  
EUT : 150Mbps Wireless N USB Module  
Power Rating : DC 3.3V From PC Input AC 120V/60Hz  
Test Mode : IEEE802.11g 2437MHz Tx  
M/N : PW-MN427\_34I






Site no. : 3m Chamber Data no. : 42  
 Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : HORIZONTAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 24°C/56% Engineer : Leo-Li  
 EUT : 150Mbps Wireless N USB Module  
 Power Rating : DC 3.3V From PC Input AC 120V/60Hz  
 Test Mode : IEEE802.11g 2437MHz Tx  
 M/N : PW-MN427\_34I

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	4874.000	32.97	8.63	35.70	43.70	49.60	74.00	24.40	Peak
2	4874.000	32.97	8.63	35.70	31.04	36.94	54.00	17.06	Average


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading - Amp Factor  
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 43  
 Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : HORIZONTAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 24°C/56% Engineer : Leo-Li  
 EUT : 150Mbps Wireless N USB Module  
 Power Rating : DC 3.3V From PC Input AC 120V/60Hz  
 Test Mode : IEEE802.11g 2462MHz Tx  
 M/N : PW-MN427\_34I

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2462.000	28.32	5.89	35.70	86.57	85.08	74.00	-11.08	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading - Amp Factor  
 2. The emission levels that are 20dB below the official limit are not reported.




Site no. : 3m Chamber Data no. : 44  
 Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : VERTICAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 24°C/56% Engineer : Leo-Li  
 EUT : 150Mbps Wireless N USB Module  
 Power Rating : DC 3.3V From PC Input AC 120V/60Hz  
 Test Mode : IEEE802.11g 2462MHz Tx  
 M/N : PW-MN427\_34I

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2462.000	28.32	5.89	35.70	98.14	96.65	74.00	-22.65	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading - Amp Factor  
 2. The emission levels that are 20dB below the official limit are not reported.




Site no. : 3m Chamber Data no. : 49  
Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : HORIZONTAL  
Limit : FCC PART 15C PEAK  
Env. / Ins. : 24°C/56% Engineer : Leo-Li  
EUT : 150Mbps Wireless N USB Module  
Power Rating : DC 3.3V From PC Input AC 120V/60Hz  
Test Mode : IEEE802.11g 2462MHz Tx  
M/N : PW-MN427\_34I




Site no. : 3m Chamber Data no. : 50  
 Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : HORIZONTAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 24°C/56% Engineer : Leo-Li  
 EUT : 150Mbps Wireless N USB Module  
 Power Rating : DC 3.3V From PC Input AC 120V/60Hz  
 Test Mode : IEEE802.11g 2462MHz Tx  
 M/N : PW-MN427\_34I

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	4924.000	33.06	8.69	35.70	44.13	50.18	74.00	23.82	Peak
2	4924.000	33.06	8.69	35.70	31.25	37.30	54.00	16.70	Average

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading - Amp Factor  
 2. The emission levels that are 20dB below the official limit are not reported.




Site no. : 3m Chamber Data no. : 51  
Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : VERTICAL  
Limit : FCC PART 15C PEAK  
Env. / Ins. : 24°C/56% Engineer : Leo-Li  
EUT : 150Mbps Wireless N USB Module  
Power Rating : DC 3.3V From PC Input AC 120V/60Hz  
Test Mode : IEEE802.11g 2462MHz Tx  
M/N : PW-MN427\_34I



Site no. : 3m Chamber Data no. : 52  
 Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : VERTICAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 24°C/56% Engineer : Leo-Li  
 EUT : 150Mbps Wireless N USB Module  
 Power Rating : DC 3.3V From PC Input AC 120V/60Hz  
 Test Mode : IEEE802.11g 2462MHz Tx  
 M/N : PW-MN427\_34I


No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	4924.000	33.06	8.69	35.70	43.73	49.78	74.00	24.22	Peak
2	4924.000	33.06	8.69	35.70	31.24	37.29	54.00	16.71	Average

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading - Amp Factor  
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 53  
Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : HORIZONTAL  
Limit : FCC PART 15C PEAK  
Env. / Ins. : 24°C/56% Engineer : Leo-Li  
EUT : 150Mbps Wireless N USB Module  
Power Rating : DC 3.3V From PC Input AC 120V/60Hz  
Test Mode : IEEE802.11nHT20 2462MHz Tx  
M/N : PW-MN427\_34I







Site no. : 3m Chamber Data no. : 54  
 Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : HORIZONTAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 24°C/56% Engineer : Leo-Li  
 EUT : 150Mbps Wireless N USB Module  
 Power Rating : DC 3.3V From PC Input AC 120V/60Hz  
 Test Mode : IEEE802.11nHT20 2462MHz Tx  
 M/N : PW-MN427\_34I

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	4924.000	33.06	8.69	35.70	43.15	49.20	74.00	24.80	Peak
2	4924.000	33.06	8.69	35.70	32.01	38.06	54.00	15.94	Average

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading - Amp Factor  
 2. The emission levels that are 20dB below the official limit are not reported.




Site no. : 3m Chamber Data no. : 55  
Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : VERTICAL  
Limit : FCC PART 15C PEAK  
Env. / Ins. : 24°C/56% Engineer : Leo-Li  
EUT : 150Mbps Wireless N USB Module  
Power Rating : DC 3.3V From PC Input AC 120V/60Hz  
Test Mode : IEEE802.11nHT20 2462MHz Tx  
M/N : PW-MN427\_34I



Site no. : 3m Chamber Data no. : 56  
 Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : VERTICAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 24°C/56% Engineer : Leo-Li  
 EUT : 150Mbps Wireless N USB Module  
 Power Rating : DC 3.3V From PC Input AC 120V/60Hz  
 Test Mode : IEEE802.11nHT20 2462MHz Tx  
 M/N : PW-MN427\_34I

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	4924.000	33.06	8.69	35.70	44.28	50.33	74.00	23.67	Peak
2	4924.000	33.06	8.69	35.70	31.64	37.69	54.00	16.31	Average


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading - Amp Factor  
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 61  
 Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : VERTICAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 24°C/56% Engineer : Leo-Li  
 EUT : 150Mbps Wireless N USB Module  
 Power Rating : DC 3.3V From PC Input AC 120V/60Hz  
 Test Mode : IEEE802.11nHT20 2462MHz Tx  
 M/N : PW-MN427\_34I

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2462.000	28.32	5.89	35.70	101.22	99.73	74.00	-25.73	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading - Amp Factor  
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 62  
 Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : HORIZONTAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 24°C/56% Engineer : Leo-Li  
 EUT : 150Mbps Wireless N USB Module  
 Power Rating : DC 3.3V From PC Input AC 120V/60Hz  
 Test Mode : IEEE802.11nHT20 2462MHz Tx  
 M/N : PW-MN427\_34I

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2462.000	28.32	5.89	35.70	90.44	88.95	74.00	-14.95	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading - Amp Factor  
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 63  
 Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : HORIZONTAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 24°C/56% Engineer : Leo-Li  
 EUT : 150Mbps Wireless N USB Module  
 Power Rating : DC 3.3V From PC Input AC 120V/60Hz  
 Test Mode : IEEE802.11nHT20 2437MHz Tx  
 M/N : PW-MN427\_34I

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2437.000	28.26	5.85	35.70	89.66	88.07	74.00	-14.07	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading - Amp Factor  
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 64  
 Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : VERTICAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 24°C/56% Engineer : Leo-Li  
 EUT : 150Mbps Wireless N USB Module  
 Power Rating : DC 3.3V From PC Input AC 120V/60Hz  
 Test Mode : IEEE802.11nHT20 2437MHz Tx  
 M/N : PW-MN427\_34I


No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2437.000	28.26	5.85	35.70	99.48	97.89	74.00	-23.89	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading - Amp Factor  
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 65  
Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : HORIZONTAL  
Limit : FCC PART 15C PEAK  
Env. / Ins. : 24°C/56% Engineer : Leo-Li  
EUT : 150Mbps Wireless N USB Module  
Power Rating : DC 3.3V From PC Input AC 120V/60Hz  
Test Mode : IEEE802.11nHT20 2437MHz Tx  
M/N : PW-MN427\_34I







Site no. : 3m Chamber Data no. : 66  
 Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : HORIZONTAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 24°C/56% Engineer : Leo-Li  
 EUT : 150Mbps Wireless N USB Module  
 Power Rating : DC 3.3V From PC Input AC 120V/60Hz  
 Test Mode : IEEE802.11nHT20 2437MHz Tx  
 M/N : PW-MN427\_34I

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	4874.000	32.97	8.63	35.70	43.59	49.49	74.00	24.51	Peak
2	4874.000	32.97	8.63	35.70	31.43	37.33	54.00	16.67	Average

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading - Amp Factor  
 2. The emission levels that are 20dB below the official limit are not reported.




Site no. : 3m Chamber Data no. : 67  
Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : VERTICAL  
Limit : FCC PART 15C PEAK  
Env. / Ins. : 24°C/56% Engineer : Leo-Li  
EUT : 150Mbps Wireless N USB Module  
Power Rating : DC 3.3V From PC Input AC 120V/60Hz  
Test Mode : IEEE802.11nHT20 2437MHz Tx  
M/N : PW-MN427\_34I



Site no. : 3m Chamber Data no. : 68  
 Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : VERTICAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 24°C/56% Engineer : Leo-Li  
 EUT : 150Mbps Wireless N USB Module  
 Power Rating : DC 3.3V From PC Input AC 120V/60Hz  
 Test Mode : IEEE802.11nHT20 2437MHz Tx  
 M/N : PW-MN427\_34I

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	4874.000	32.97	8.63	35.70	44.11	50.01	74.00	23.99	Peak
2	4874.000	32.97	8.63	35.70	31.23	37.13	54.00	16.87	Average


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading - Amp Factor  
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 69  
 Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : HORIZONTAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 24°C/56% Engineer : Leo-Li  
 EUT : 150Mbps Wireless N USB Module  
 Power Rating : DC 3.3V From PC Input AC 120V/60Hz  
 Test Mode : IEEE802.11nHT20 2412MHz Tx  
 M/N : PW-MN427\_34I

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2412.000	28.21	5.81	35.70	90.32	88.64	74.00	-14.64	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading - Amp Factor  
 2. The emission levels that are 20dB below the official limit are not reported.




Site no. : 3m Chamber Data no. : 70  
 Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : VERTICAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 24°C/56% Engineer : Leo-Li  
 EUT : 150Mbps Wireless N USB Module  
 Power Rating : DC 3.3V From PC Input AC 120V/60Hz  
 Test Mode : IEEE802.11nHT20 2412MHz Tx  
 M/N : PW-MN427\_34I

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2412.000	28.21	5.81	35.70	101.33	99.65	74.00	-25.65	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading - Amp Factor  
 2. The emission levels that are 20dB below the official limit are not reported.




Site no. : 3m Chamber Data no. : 75  
Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : VERTICAL  
Limit : FCC PART 15C PEAK  
Env. / Ins. : 24°C/56% Engineer : Leo-Li  
EUT : 150Mbps Wireless N USB Module  
Power Rating : DC 3.3V From PC Input AC 120V/60Hz  
Test Mode : IEEE802.11nHT20 2412MHz Tx  
M/N : PW-MN427\_34I



Site no. : 3m Chamber Data no. : 76  
 Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : VERTICAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 24°C/56% Engineer : Leo-Li  
 EUT : 150Mbps Wireless N USB Module  
 Power Rating : DC 3.3V From PC Input AC 120V/60Hz  
 Test Mode : IEEE802.11nHT20 2412MHz Tx  
 M/N : PW-MN427\_34I


No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	4824.000	32.88	8.58	35.70	44.36	50.12	74.00	23.88	Peak
2	4824.000	32.88	8.58	35.70	32.34	38.10	54.00	15.90	Average

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading - Amp Factor  
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 77  
Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : HORIZONTAL  
Limit : FCC PART 15C PEAK  
Env. / Ins. : 24°C/56% Engineer : Leo-Li  
EUT : 150Mbps Wireless N USB Module  
Power Rating : DC 3.3V From PC Input AC 120V/60Hz  
Test Mode : IEEE802.11nHT20 2412MHz Tx  
M/N : PW-MN427\_34I







Site no. : 3m Chamber Data no. : 78  
 Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : HORIZONTAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 24°C/56% Engineer : Leo-Li  
 EUT : 150Mbps Wireless N USB Module  
 Power Rating : DC 3.3V From PC Input AC 120V/60Hz  
 Test Mode : IEEE802.11nHT20 2412MHz Tx  
 M/N : PW-MN427\_34I

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	4824.000	32.88	8.58	35.70	43.19	48.95	74.00	25.05	Peak
2	4824.000	32.88	8.58	35.70	31.32	37.08	54.00	16.92	Average

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading - Amp Factor  
 2. The emission levels that are 20dB below the official limit are not reported.




Site no. : 3m Chamber Data no. : 79  
Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : HORIZONTAL  
Limit : FCC PART 15C PEAK  
Env. / Ins. : 24°C/56% Engineer : Leo-Li  
EUT : 150Mbps Wireless N USB Module  
Power Rating : DC 3.3V From PC Input AC 120V/60Hz  
Test Mode : IEEE802.11nHT40 2422MHz Tx  
M/N : PW-MN427\_34I




Site no. : 3m Chamber Data no. : 80  
 Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : HORIZONTAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 24°C/56% Engineer : Leo-Li  
 EUT : 150Mbps Wireless N USB Module  
 Power Rating : DC 3.3V From PC Input AC 120V/60Hz  
 Test Mode : IEEE802.11nHT40 2422MHz Tx  
 M/N : PW-MN427\_34I

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	4844.000	32.92	8.60	35.70	44.31	50.13	74.00	23.87	Peak
2	4844.000	32.92	8.60	35.70	31.17	36.99	54.00	17.01	Average

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading - Amp Factor  
 2. The emission levels that are 20dB below the official limit are not reported.




Site no. : 3m Chamber Data no. : 81  
Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : VERTICAL  
Limit : FCC PART 15C PEAK  
Env. / Ins. : 24°C/56% Engineer : Leo-Li  
EUT : 150Mbps Wireless N USB Module  
Power Rating : DC 3.3V From PC Input AC 120V/60Hz  
Test Mode : IEEE802.11nHT40 2422MHz Tx  
M/N : PW-MN427\_34I



Site no. : 3m Chamber Data no. : 82  
 Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : VERTICAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 24°C/56% Engineer : Leo-Li  
 EUT : 150Mbps Wireless N USB Module  
 Power Rating : DC 3.3V From PC Input AC 120V/60Hz  
 Test Mode : IEEE802.11nHT40 2422MHz Tx  
 M/N : PW-MN427\_34I

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	4844.000	32.92	8.60	35.70	45.03	50.85	74.00	23.15	Peak
2	4844.000	32.92	8.60	35.70	32.18	38.00	54.00	16.00	Average


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading - Amp Factor  
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 87  
 Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : VERTICAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 24°C/56% Engineer : Leo-Li  
 EUT : 150Mbps Wireless N USB Module  
 Power Rating : DC 3.3V From PC Input AC 120V/60Hz  
 Test Mode : IEEE802.11nHT40 2422MHz Tx  
 M/N : PW-MN427\_34I

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2422.000	28.23	5.83	35.70	98.95	97.31	74.00	-23.31	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading - Amp Factor  
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 88  
 Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : HORIZONTAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 24°C/56% Engineer : Leo-Li  
 EUT : 150Mbps Wireless N USB Module  
 Power Rating : DC 3.3V From PC Input AC 120V/60Hz  
 Test Mode : IEEE802.11nHT40 2422MHz Tx  
 M/N : PW-MN427\_34I


No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2422.000	28.23	5.83	35.70	88.31	86.67	74.00	-12.67	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading - Amp Factor  
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 89  
Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : VERTICAL  
Limit : FCC PART 15C PEAK  
Env. / Ins. : 24°C/56% Engineer : Leo-Li  
EUT : 150Mbps Wireless N USB Module  
Power Rating : DC 3.3V From PC Input AC 120V/60Hz  
Test Mode : IEEE802.11nHT40 2437MHz Tx  
M/N : PW-MN427\_34I






Site no. : 3m Chamber Data no. : 90  
 Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : VERTICAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 24°C/56% Engineer : Leo-Li  
 EUT : 150Mbps Wireless N USB Module  
 Power Rating : DC 3.3V From PC Input AC 120V/60Hz  
 Test Mode : IEEE802.11nHT40 2437MHz Tx  
 M/N : PW-MN427\_34I


No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	4874.000	32.97	8.63	35.70	43.53	49.43	74.00	24.57	Peak
2	4874.000	32.97	8.63	35.70	31.48	37.38	54.00	16.62	Average

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading - Amp Factor  
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 91  
Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : HORIZONTAL  
Limit : FCC PART 15C PEAK  
Env. / Ins. : 24°C/56% Engineer : Leo-Li  
EUT : 150Mbps Wireless N USB Module  
Power Rating : DC 3.3V From PC Input AC 120V/60Hz  
Test Mode : IEEE802.11nHT40 2437MHz Tx  
M/N : PW-MN427\_34I


Data: 92 File: G:\2014 Report\PI\Proware\ACS14Q0239.EM6 (104) Date: 2014-03-16



Site no. : 3m Chamber Data no. : 92  
 Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : HORIZONTAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 24°C/56% Engineer : Leo-Li  
 EUT : 150Mbps Wireless N USB Module  
 Power Rating : DC 3.3V From PC Input AC 120V/60Hz  
 Test Mode : IEEE802.11nHT40 2437MHz Tx  
 M/N : PW-MN427\_34I

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	4874.000	32.97	8.63	35.70	44.09	49.99	74.00	24.01	Peak
2	4874.000	32.97	8.63	35.70	31.86	37.76	54.00	16.24	Average


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading - Amp Factor  
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 93  
 Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : HORIZONTAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 24°C/56% Engineer : Leo-Li  
 EUT : 150Mbps Wireless N USB Module  
 Power Rating : DC 3.3V From PC Input AC 120V/60Hz  
 Test Mode : IEEE802.11nHT40 2437MHz Tx  
 M/N : PW-MN427\_34I

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2437.000	28.26	5.85	35.70	87.59	86.00	74.00	-12.00	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading - Amp Factor  
 2. The emission levels that are 20dB below the official limit are not reported.




Site no. : 3m Chamber Data no. : 94  
 Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : VERTICAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 24°C/56% Engineer : Leo-Li  
 EUT : 150Mbps Wireless N USB Module  
 Power Rating : DC 3.3V From PC Input AC 120V/60Hz  
 Test Mode : IEEE802.11nHT40 2437MHz Tx  
 M/N : PW-MN427\_34I

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2437.000	28.26	5.85	35.70	97.94	96.35	74.00	-22.35	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading - Amp Factor  
 2. The emission levels that are 20dB below the official limit are not reported.




Site no. : 3m Chamber Data no. : 95  
Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : HORIZONTAL  
Limit : FCC PART 15C PEAK  
Env. / Ins. : 24°C/56% Engineer : Leo-Li  
EUT : 150Mbps Wireless N USB Module  
Power Rating : DC 3.3V From PC Input AC 120V/60Hz  
Test Mode : IEEE802.11nHT40 2452MHz Tx  
M/N : PW-MN427\_34I



Site no. : 3m Chamber Data no. : 96  
 Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : HORIZONTAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 24°C/56% Engineer : Leo-Li  
 EUT : 150Mbps Wireless N USB Module  
 Power Rating : DC 3.3V From PC Input AC 120V/60Hz  
 Test Mode : IEEE802.11nHT40 2452MHz Tx  
 M/N : PW-MN427\_34I


No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	4904.000	33.03	8.66	35.70	43.65	49.64	74.00	24.36	Peak
2	4904.000	33.03	8.66	35.70	31.59	37.58	54.00	16.42	Average

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading - Amp Factor  
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 97  
Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : VERTICAL  
Limit : FCC PART 15C PEAK  
Env. / Ins. : 24°C/56% Engineer : Leo-Li  
EUT : 150Mbps Wireless N USB Module  
Power Rating : DC 3.3V From PC Input AC 120V/60Hz  
Test Mode : IEEE802.11nHT40 2452MHz Tx  
M/N : PW-MN427\_34I






Site no. : 3m Chamber Data no. : 98  
 Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : VERTICAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 24°C/56% Engineer : Leo-Li  
 EUT : 150Mbps Wireless N USB Module  
 Power Rating : DC 3.3V From PC Input AC 120V/60Hz  
 Test Mode : IEEE802.11nHT40 2452MHz Tx  
 M/N : PW-MN427\_34I

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	4904.000	33.03	8.66	35.70	44.23	50.22	74.00	23.78	Peak
2	4904.000	33.03	8.66	35.70	31.41	37.40	54.00	16.60	Average


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading - Amp Factor  
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 99  
 Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : VERTICAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 24°C/56% Engineer : Leo-Li  
 EUT : 150Mbps Wireless N USB Module  
 Power Rating : DC 3.3V From PC Input AC 120V/60Hz  
 Test Mode : IEEE802.11nHT40 2452MHz Tx  
 M/N : PW-MN427\_34I

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission			Remark
						Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	
1	2452.000	28.29	5.87	35.70	94.88	93.34	74.00	-19.34	Peak
2	3271.000	30.94	6.95	35.70	44.73	46.92	74.00	27.08	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading  
 -Amp Factor  
 2. The emission levels that are 20dB below the official  
 limit are not reported.



Site no. : 3m Chamber Data no. : 100  
 Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : HORIZONTAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 24°C/56% Engineer : Leo-Li  
 EUT : 150Mbps Wireless N USB Module  
 Power Rating : DC 3.3V From PC Input AC 120V/60Hz  
 Test Mode : IEEE802.11nHT40 2452MHz Tx  
 M/N : PW-MN427\_34I

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission			Remark
						Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	
1	2452.000	28.29	5.87	35.70	83.77	82.23	74.00	-8.23	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading - Amp Factor  
 2. The emission levels that are 20dB below the official limit are not reported.

## 5. CONDUCTED SPURIOUS EMISSIONS

### 5.1. Test Equipment

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	Spectrum Analyzer	Agilent	N9030A	MY51380221	Oct.31, 13	1Year
2.	Attenuator	Agilent	8491B	MY39262165	May.08,13	1 Year
3.	RF Cable	Hubersuhner	SUCOFLEX102	28618/2	May.08,13	1Year

### 5.2. Limit

In any 100kHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power.


### 5.3. Test Procedure


The transmitter output was connected to a spectrum analyzer, The resolution bandwidth is set to 100 kHz, The video bandwidth is set to 300 kHz and measure all the emissions detected.

### 5.4. Test result


**PASS** (The testing data was attached in the next pages.)


Test Mode: IEEE 802.11b TX  
 Test CH1: 2412MHz





Test CH6: 2437MHz






Test CH11: 2462MHz










Test Mode: IEEE 802.11g TX


Test CH1: 2412MHz











Test CH6: 2437MHz





Test CH11: 2462MHz






Test Mode: IEEE 802.11n HT20 TX  
 Test CH1: 2412MHz









Test CH6: 2437MHz






Test CH11: 2462MHz









Test Mode: IEEE 802.11n HT40 TX


Test CH1: 2422MHz









Test CH4: 2437MHz








Test CH7: 2452MHz





## 6. BAND EDGE COMPLIANCE TEST

### 6.1. Test Equipment

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	Spectrum	Agilent	E4446A	US44300459	May.08, 13	1 Year
2.	Amp	HP	8449B	3008A08495	May.08, 13	1 Year
3.	Antenna	EMCO	3115	9607-4580	May.08, 13	1 Year
4.	HF Cable	Hubersuhne	Sucoflex104	-	May.08, 13	1 Year

### 6.2. Limit


All the lower and upper band-edges emissions appearing within 2310MHz to 2390MHz and 2483.5MHz to 2500MHz restricted frequency bands shall not exceed the limits shown in 15.209, all the other emissions outside operation frequency band 2400MHz to 2483.5MHz shall be at least 20dB below the fundamental emissions, or comply with 15.209 limits.

### 6.3. Test Produce

1. The EUT is placed on a turntable, which is 0.8m above the ground plane and worked at highest radiated power.
2. The turntable was rotated for 360 degrees to determine the position of maximum emission level.
3. EUT is set 3m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emission.
4. Set the spectrum analyzer in the following setting in order to capture the lower and upper band-edges of the emission:
  - (a) PEAK: RBW=1MHz; VBW=3MHz; Sweep=AUTO
  - (b) AVERAGE: RBW=1MHz; VBW=10Hz; Sweep=AUTO

### 6.4. Test Results


Pass (The testing data was attached in the next pages.)



Site no. : 3m Chamber Data no. : 3  
 Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : VERTICAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 24°C/56% Engineer : Leo-Li  
 EUT : 150Mbps Wireless N USB Module  
 Power Rating : DC 3.3V From PC Input AC 120V/60Hz  
 Test Mode : IEEE802.11b 2412MHz Tx  
 M/N : PW-MN427\_34I

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission			
						Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2386.820	28.15	5.78	35.70	49.80	48.03	74.00	25.97	Peak
2	2390.000	28.16	5.78	35.70	48.57	46.81	74.00	27.19	Peak
3	2400.000	28.18	5.80	35.70	52.42	50.70	74.00	23.30	Peak
4	2413.500	28.21	5.82	35.70	102.95	101.28	74.00	-27.28	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading  
 -Amp Factor  
 2. The emission levels that are 20dB below the official  
 limit are not reported.



Site no. : 3m Chamber Data no. : 4  
 Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : VERTICAL  
 Limit : FCC PART 15C AV  
 Env. / Ins. : 24°C/56% Engineer : Leo-Li  
 EUT : 150Mbps Wireless N USB Module  
 Power Rating : DC 3.3V From PC Input AC 120V/60Hz  
 Test Mode : IEEE802.11b 2412MHz Tx  
 M/N : PW-MN427\_34I

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission			Remark
						Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	
1	2390.000	28.16	5.78	35.70	37.10	35.34	54.00	18.66	Average
2	2400.000	28.18	5.80	35.70	42.77	41.05	54.00	12.95	Average
3	2411.200	28.20	5.81	35.70	99.64	97.95	54.00	-43.95	Average


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading - Amp Factor  
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 5  
 Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : HORIZONTAL  
 Limit : FCC PART 15C AV  
 Env. / Ins. : 24°C/56% Engineer : Leo-Li  
 EUT : 150Mbps Wireless N USB Module  
 Power Rating : DC 3.3V From PC Input AC 120V/60Hz  
 Test Mode : IEEE802.11b 2412MHz Tx  
 M/N : PW-MN427\_34I

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission			
						Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2390.000	28.16	5.78	35.70	35.97	34.21	54.00	19.79	Average
2	2400.000	28.18	5.80	35.70	36.94	35.22	54.00	18.78	Average
3	2411.200	28.20	5.81	35.70	88.52	86.83	54.00	-32.83	Average


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading  
 -Amp Factor  
 2. The emission levels that are 20dB below the official  
 limit are not reported.



Site no. : 3m Chamber Data no. : 6  
 Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : HORIZONTAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 24°C/56% Engineer : Leo-Li  
 EUT : 150Mbps Wireless N USB Module  
 Power Rating : DC 3.3V From PC Input AC 120V/60Hz  
 Test Mode : IEEE802.11b 2412MHz Tx  
 M/N : PW-MN427\_34I

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission			Remark
						Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	
1	2385.670	28.15	5.78	35.70	49.44	47.67	74.00	26.33	Peak
2	2390.000	28.16	5.78	35.70	47.55	45.79	74.00	28.21	Peak
3	2400.000	28.18	5.80	35.70	48.39	46.67	74.00	27.33	Peak
4	2410.395	28.20	5.81	35.70	92.25	90.56	74.00	-16.56	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading  
 -Amp Factor  
 2. The emission levels that are 20dB below the official  
 limit are not reported.




Site no. : 3m Chamber Data no. : 19  
 Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : HORIZONTAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 24\*C/56% Engineer : Leo-Li  
 EUT : 150Mbps Wireless N USB Module  
 Power Rating : DC 3.3V From PC Input AC 120V/60Hz  
 Test Mode : IEEE802.11b 2462MHz Tx  
 M/N : PW-MN427\_34I

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2460.320	28.31	5.88	35.70	83.10	81.59	74.00	-7.59	Peak
2	2483.500	28.36	5.92	35.70	47.47	46.05	74.00	27.95	Peak
3	2494.400	28.39	5.93	35.70	49.85	48.47	74.00	25.53	Peak
4	2500.000	28.40	5.94	35.70	47.97	46.61	74.00	27.39	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp Factor  
 2. The emission levels that are 20dB below the official limit are not reported.






Site no. : 3m Chamber Data no. : 20  
 Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : HORIZONTAL  
 Limit : FCC PART 15C AV  
 Env. / Ins. : 24°C/56% Engineer : Leo-Li  
 EUT : 150Mbps Wireless N USB Module  
 Power Rating : DC 3.3V From PC Input AC 120V/60Hz  
 Test Mode : IEEE802.11b 2462MHz Tx  
 M/N : PW-MN427\_34I

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission			Remark
						Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	
1	2459.720	28.31	5.88	35.70	79.53	78.02	54.00	-24.02	Average
2	2483.500	28.36	5.92	35.70	35.66	34.24	54.00	19.76	Average
3	2500.000	28.40	5.94	35.70	35.75	34.39	54.00	19.61	Average


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading  
 -Amp Factor  
 2. The emission levels that are 20dB below the official  
 limit are not reported.



Site no. : 3m Chamber Data no. : 21  
 Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : VERTICAL  
 Limit : FCC PART 15C AV  
 Env. / Ins. : 24°C/56% Engineer : Leo-Li  
 EUT : 150Mbps Wireless N USB Module  
 Power Rating : DC 3.3V From PC Input AC 120V/60Hz  
 Test Mode : IEEE802.11b 2462MHz Tx  
 M/N : PW-MN427\_34I

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission			Remark
						Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	
1	2461.280	28.31	5.89	35.70	91.24	89.74	54.00	-35.74	Average
2	2483.500	28.36	5.92	35.70	36.31	34.89	54.00	19.11	Average
3	2500.000	28.40	5.94	35.70	36.05	34.69	54.00	19.31	Average


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading  
 -Amp Factor  
 2. The emission levels that are 20dB below the official  
 limit are not reported.



Site no. : 3m Chamber Data no. : 22  
 Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : VERTICAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 24\*C/56% Engineer : Leo-Li  
 EUT : 150Mbps Wireless N USB Module  
 Power Rating : DC 3.3V From PC Input AC 120V/60Hz  
 Test Mode : IEEE802.11b 2462MHz Tx  
 M/N : PW-MN427\_34I

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission			Remark
						Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	
1	2460.380	28.31	5.88	35.70	94.79	93.28	74.00	-19.28	Peak
2	2483.500	28.36	5.92	35.70	47.72	46.30	74.00	27.70	Peak
3	2495.180	28.39	5.94	35.70	49.35	47.98	74.00	26.02	Peak
4	2500.000	28.40	5.94	35.70	47.84	46.48	74.00	27.52	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp Factor  
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 33  
 Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : HORIZONTAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 24°C/56% Engineer : Leo-Li  
 EUT : 150Mbps Wireless N USB Module  
 Power Rating : DC 3.3V From PC Input AC 120V/60Hz  
 Test Mode : IEEE802.11g 2412MHz Tx  
 M/N : PW-MN427\_34I

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission			
						Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2389.005	28.16	5.78	35.70	56.85	55.09	74.00	18.91	Peak
2	2390.000	28.16	5.78	35.70	54.47	52.71	74.00	21.29	Peak
3	2399.700	28.18	5.80	35.70	68.77	67.05	74.00	6.95	Peak
4	2400.000	28.18	5.80	35.70	67.35	65.63	74.00	8.37	Peak
5	2404.875	28.19	5.80	35.70	93.37	91.66	74.00	-17.66	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading - Amp Factor  
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 34  
 Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : HORIZONTAL  
 Limit : FCC PART 15C AV  
 Env. / Ins. : 24°C/56% Engineer : Leo-Li  
 EUT : 150Mbps Wireless N USB Module  
 Power Rating : DC 3.3V From PC Input AC 120V/60Hz  
 Test Mode : IEEE802.11g 2412MHz Tx  
 M/N : PW-MN427\_34I

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission			Remark
						Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	
1	2390.000	28.16	5.78	35.70	37.85	36.09	54.00	17.91	Average
2	2400.000	28.18	5.80	35.70	45.38	43.66	54.00	10.34	Average
3	2404.875	28.19	5.80	35.70	83.98	82.27	54.00	-28.27	Average


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading  
 -Amp Factor  
 2. The emission levels that are 20dB below the official  
 limit are not reported.



Site no. : 3m Chamber Data no. : 35  
 Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : VERTICAL  
 Limit : FCC PART 15C AV  
 Env. / Ins. : 24°C/56% Engineer : Leo-Li  
 EUT : 150Mbps Wireless N USB Module  
 Power Rating : DC 3.3V From PC Input AC 120V/60Hz  
 Test Mode : IEEE802.11g 2412MHz Tx  
 M/N : PW-MN427\_34I

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission			Remark
						Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	
1	2390.000	28.16	5.78	35.70	43.21	41.45	54.00	12.55	Average
2	2400.000	28.18	5.80	35.70	55.21	53.49	54.00	0.51	Average
3	2404.875	28.19	5.80	35.70	94.47	92.76	54.00	-38.76	Average


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading  
 -Amp Factor  
 2. The emission levels that are 20dB below the official  
 limit are not reported.



Site no. : 3m Chamber Data no. : 36  
 Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : VERTICAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 24°C/56% Engineer : Leo-Li  
 EUT : 150Mbps Wireless N USB Module  
 Power Rating : DC 3.3V From PC Input AC 120V/60Hz  
 Test Mode : IEEE802.11g 2412MHz Tx  
 M/N : PW-MN427\_34I

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2389.350	28.16	5.78	35.70	65.57	63.81	74.00	10.19	Peak
2	2390.000	28.16	5.78	35.70	63.90	62.14	74.00	11.86	Peak
3	2399.470	28.18	5.80	35.70	79.14	77.42	74.00	-3.42	Peak
4	2400.000	28.18	5.80	35.70	77.50	75.78	74.00	-1.78	Peak
5	2405.105	28.19	5.80	35.70	104.01	102.30	74.00	-28.30	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading - Amp Factor  
 2. The emission levels that are 20dB below the official limit are not reported.




Site no. : 3m Chamber Data no. : 45  
 Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : VERTICAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 24°C/56% Engineer : Leo-Li  
 EUT : 150Mbps Wireless N USB Module  
 Power Rating : DC 3.3V From PC Input AC 120V/60Hz  
 Test Mode : IEEE802.11g 2462MHz Tx  
 M/N : PW-MN427\_34I

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission			Remark
						Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	
1	2455.280	28.30	5.88	35.70	97.93	96.41	74.00	-22.41	Peak
2	2483.500	28.36	5.92	35.70	47.90	46.48	74.00	27.52	Peak
3	2499.380	28.40	5.94	35.70	50.04	48.68	74.00	25.32	Peak
4	2500.000	28.40	5.94	35.70	47.37	46.01	74.00	27.99	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading  
 -Amp Factor  
 2. The emission levels that are 20dB below the official  
 limit are not reported.






Site no. : 3m Chamber Data no. : 46  
 Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : VERTICAL  
 Limit : FCC PART 15C AV  
 Env. / Ins. : 24°C/56% Engineer : Leo-Li  
 EUT : 150Mbps Wireless N USB Module  
 Power Rating : DC 3.3V From PC Input AC 120V/60Hz  
 Test Mode : IEEE802.11g 2462MHz Tx  
 M/N : PW-MN427\_34I

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2454.920	28.30	5.88	35.70	88.74	87.22	54.00	-33.22	Average
2	2483.500	28.36	5.92	35.70	36.90	35.48	54.00	18.52	Average
3	2500.000	28.40	5.94	35.70	36.17	34.81	54.00	19.19	Average


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading - Amp Factor  
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 47  
 Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : HORIZONTAL  
 Limit : FCC PART 15C AV  
 Env. / Ins. : 24°C/56% Engineer : Leo-Li  
 EUT : 150Mbps Wireless N USB Module  
 Power Rating : DC 3.3V From PC Input AC 120V/60Hz  
 Test Mode : IEEE802.11g 2462MHz Tx  
 M/N : PW-MN427\_34I

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2454.800	28.30	5.88	35.70	75.65	74.13	54.00	-20.13	Average
2	2483.500	28.36	5.92	35.70	35.66	34.24	54.00	19.76	Average
3	2500.000	28.40	5.94	35.70	35.72	34.36	54.00	19.64	Average


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading - Amp Factor  
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 48  
 Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : HORIZONTAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 24°C/56% Engineer : Leo-Li  
 EUT : 150Mbps Wireless N USB Module  
 Power Rating : DC 3.3V From PC Input AC 120V/60Hz  
 Test Mode : IEEE802.11g 2462MHz Tx  
 M/N : PW-MN427\_34I

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission			Remark
						Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	
1	2454.920	28.30	5.88	35.70	86.46	84.94	74.00	-10.94	Peak
2	2483.500	28.36	5.92	35.70	48.55	47.13	74.00	26.87	Peak
3	2500.000	28.40	5.94	35.70	48.04	46.68	74.00	27.32	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading  
 -Amp Factor  
 2. The emission levels that are 20dB below the official  
 limit are not reported.



Site no. : 3m Chamber Data no. : 57  
 Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : HORIZONTAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 24°C/56% Engineer : Leo-Li  
 EUT : 150Mbps Wireless N USB Module  
 Power Rating : DC 3.3V From PC Input AC 120V/60Hz  
 Test Mode : IEEE802.11nHT20 2462MHz Tx  
 M/N : PW-MN427\_34I

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2454.320	28.30	5.88	35.70	90.59	89.07	74.00	-15.07	Peak
2	2483.500	28.36	5.92	35.70	48.23	46.81	74.00	27.19	Peak
3	2500.000	28.40	5.94	35.70	47.72	46.36	74.00	27.64	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading - Amp Factor  
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 58  
 Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : HORIZONTAL  
 Limit : FCC PART 15C AV  
 Env. / Ins. : 24°C/56% Engineer : Leo-Li  
 EUT : 150Mbps Wireless N USB Module  
 Power Rating : DC 3.3V From PC Input AC 120V/60Hz  
 Test Mode : IEEE802.11nHT20 2462MHz Tx  
 M/N : PW-MN427\_34I

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2455.100	28.30	5.88	35.70	80.48	78.96	54.00	-24.96	Average
2	2483.500	28.36	5.92	35.70	36.11	34.69	54.00	19.31	Average
3	2500.000	28.40	5.94	35.70	35.73	34.37	54.00	19.63	Average


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading - Amp Factor  
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 59  
 Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : VERTICAL  
 Limit : FCC PART 15C AV  
 Env. / Ins. : 24°C/56% Engineer : Leo-Li  
 EUT : 150Mbps Wireless N USB Module  
 Power Rating : DC 3.3V From PC Input AC 120V/60Hz  
 Test Mode : IEEE802.11nHT20 2462MHz Tx  
 M/N : PW-MN427\_34I

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission			Remark
						Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	
1	2455.100	28.30	5.88	35.70	91.37	89.85	54.00	-35.85	Average
2	2483.500	28.36	5.92	35.70	40.48	39.06	54.00	14.94	Average
3	2500.000	28.40	5.94	35.70	36.81	35.45	54.00	18.55	Average


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading  
 -Amp Factor  
 2. The emission levels that are 20dB below the official  
 limit are not reported.



Site no. : 3m Chamber Data no. : 60  
 Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : VERTICAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 24°C/56% Engineer : Leo-Li  
 EUT : 150Mbps Wireless N USB Module  
 Power Rating : DC 3.3V From PC Input AC 120V/60Hz  
 Test Mode : IEEE802.11nHT20 2462MHz Tx  
 M/N : PW-MN427\_34I

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2454.620	28.30	5.88	35.70	101.47	99.95	74.00	-25.95	Peak
2	2483.500	28.36	5.92	35.70	58.61	57.19	74.00	16.81	Peak
3	2500.000	28.40	5.94	35.70	49.20	47.84	74.00	26.16	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading  
 -Amp Factor  
 2. The emission levels that are 20dB below the official  
 limit are not reported.




Site no. : 3m Chamber Data no. : 71  
 Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : VERTICAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 24°C/56% Engineer : Leo-Li  
 EUT : 150Mbps Wireless N USB Module  
 Power Rating : DC 3.3V From PC Input AC 120V/60Hz  
 Test Mode : IEEE802.11nHT20 2412MHz Tx  
 M/N : PW-MN427\_34I

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission			Remark
						Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	
1	2390.000	28.16	5.78	35.70	56.49	54.73	74.00	19.27	Peak
2	2400.000	28.18	5.80	35.70	67.84	66.12	74.00	7.88	Peak
3	2419.595	28.22	5.83	35.70	101.43	99.78	74.00	-25.78	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp Factor  
 2. The emission levels that are 20dB below the official limit are not reported.






Site no. : 3m Chamber Data no. : 72  
 Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : VERTICAL  
 Limit : FCC PART 15C AV  
 Env. / Ins. : 24°C/56% Engineer : Leo-Li  
 EUT : 150Mbps Wireless N USB Module  
 Power Rating : DC 3.3V From PC Input AC 120V/60Hz  
 Test Mode : IEEE802.11nHT20 2412MHz Tx  
 M/N : PW-MN427\_34I

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2390.000	28.16	5.78	35.70	40.12	38.36	54.00	15.64	Average
2	2400.000	28.18	5.80	35.70	52.08	50.36	54.00	3.64	Average
3	2418.905	28.22	5.82	35.70	91.67	90.01	54.00	-36.01	Average


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading - Amp Factor  
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 73  
 Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : HORIZONTAL  
 Limit : FCC PART 15C AV  
 Env. / Ins. : 24°C/56% Engineer : Leo-Li  
 EUT : 150Mbps Wireless N USB Module  
 Power Rating : DC 3.3V From PC Input AC 120V/60Hz  
 Test Mode : IEEE802.11nHT20 2412MHz Tx  
 M/N : PW-MN427\_34I

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission			Remark
						Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	
1	2390.000	28.16	5.78	35.70	36.27	34.51	54.00	19.49	Average
2	2400.000	28.18	5.80	35.70	41.96	40.24	54.00	13.76	Average
3	2405.105	28.19	5.80	35.70	80.36	78.65	54.00	-24.65	Average


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading  
 -Amp Factor  
 2. The emission levels that are 20dB below the official  
 limit are not reported.



Site no. : 3m Chamber Data no. : 74  
 Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : HORIZONTAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 24°C/56% Engineer : Leo-Li  
 EUT : 150Mbps Wireless N USB Module  
 Power Rating : DC 3.3V From PC Input AC 120V/60Hz  
 Test Mode : IEEE802.11nHT20 2412MHz Tx  
 M/N : PW-MN427\_34I

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission			Remark
						Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	
1	2390.000	28.16	5.78	35.70	48.55	46.79	74.00	27.21	Peak
2	2400.000	28.18	5.80	35.70	56.31	54.59	74.00	19.41	Peak
3	2404.530	28.19	5.80	35.70	90.57	88.86	74.00	-14.86	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading - Amp Factor  
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 83  
 Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : HORIZONTAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 24°C/56% Engineer : Leo-Li  
 EUT : 150Mbps Wireless N USB Module  
 Power Rating : DC 3.3V From PC Input AC 120V/60Hz  
 Test Mode : IEEE802.11nHT40 2422MHz Tx  
 M/N : PW-MN427\_34I

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2386.300	28.15	5.78	35.70	50.20	48.43	74.00	25.57	Peak
2	2390.000	28.16	5.78	35.70	49.55	47.79	74.00	26.21	Peak
3	2400.000	28.18	5.80	35.70	59.01	57.29	74.00	16.71	Peak
4	2405.480	28.19	5.80	35.70	88.69	86.98	74.00	-12.98	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading - Amp Factor  
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 84  
 Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : HORIZONTAL  
 Limit : FCC PART 15C AV  
 Env. / Ins. : 24°C/56% Engineer : Leo-Li  
 EUT : 150Mbps Wireless N USB Module  
 Power Rating : DC 3.3V From PC Input AC 120V/60Hz  
 Test Mode : IEEE802.11nHT40 2422MHz Tx  
 M/N : PW-MN427\_34I

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission			Remark
						Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	
1	2390.000	28.16	5.78	35.70	36.43	34.67	54.00	19.33	Average
2	2400.000	28.18	5.80	35.70	46.07	44.35	54.00	9.65	Average
3	2405.620	28.19	5.81	35.70	78.95	77.25	54.00	-23.25	Average


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading  
 -Amp Factor  
 2. The emission levels that are 20dB below the official  
 limit are not reported.



Site no. : 3m Chamber Data no. : 85  
 Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : VERTICAL  
 Limit : FCC PART 15C AV  
 Env. / Ins. : 24°C/56% Engineer : Leo-Li  
 EUT : 150Mbps Wireless N USB Module  
 Power Rating : DC 3.3V From PC Input AC 120V/60Hz  
 Test Mode : IEEE802.11nHT40 2422MHz Tx  
 M/N : PW-MN427\_34I

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2390.000	28.16	5.78	35.70	39.90	38.14	54.00	15.86	Average
2	2400.000	28.18	5.80	35.70	55.29	53.57	54.00	0.43	Average
3	2405.620	28.19	5.81	35.70	88.44	86.74	54.00	-32.74	Average


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading - Amp Factor  
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 86  
 Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : VERTICAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 24°C/56% Engineer : Leo-Li  
 EUT : 150Mbps Wireless N USB Module  
 Power Rating : DC 3.3V From PC Input AC 120V/60Hz  
 Test Mode : IEEE802.11nHT40 2422MHz Tx  
 M/N : PW-MN427\_34I

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission			
						Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2388.820	28.16	5.78	35.70	55.95	54.19	74.00	19.81	Peak
2	2390.000	28.16	5.78	35.70	54.37	52.61	74.00	21.39	Peak
3	2400.000	28.18	5.80	35.70	68.79	67.07	74.00	6.93	Peak
4	2405.620	28.19	5.81	35.70	98.70	97.00	74.00	-23.00	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading  
 -Amp Factor  
 2. The emission levels that are 20dB below the official  
 limit are not reported.




Site no. : 3m Chamber Data no. : 101  
 Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : HORIZONTAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 24°C/56% Engineer : Leo-Li  
 EUT : 150Mbps Wireless N USB Module  
 Power Rating : DC 3.3V From PC Input AC 120V/60Hz  
 Test Mode : IEEE802.11nHT40 2452MHz Tx  
 M/N : PW-MN427\_34I

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission			Remark
						Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	
1	2436.220	28.26	5.85	35.70	83.19	81.60	74.00	-7.60	Peak
2	2483.500	28.36	5.92	35.70	47.45	46.03	74.00	27.97	Peak
3	2487.305	28.37	5.92	35.70	49.91	48.50	74.00	25.50	Peak
4	2500.000	28.40	5.94	35.70	48.00	46.64	74.00	27.36	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading  
 -Amp Factor  
 2. The emission levels that are 20dB below the official  
 limit are not reported.






Site no. : 3m Chamber Data no. : 102  
 Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : HORIZONTAL  
 Limit : FCC PART 15C AV  
 Env. / Ins. : 24°C/56% Engineer : Leo-Li  
 EUT : 150Mbps Wireless N USB Module  
 Power Rating : DC 3.3V From PC Input AC 120V/60Hz  
 Test Mode : IEEE802.11nHT40 2452MHz Tx  
 M/N : PW-MN427\_34I

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission			Remark
						Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	
1	2435.370	28.26	5.85	35.70	73.78	72.19	54.00	-18.19	Average
2	2483.500	28.36	5.92	35.70	35.88	34.46	54.00	19.54	Average
3	2500.000	28.40	5.94	35.70	35.81	34.45	54.00	19.55	Average


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading - Amp Factor  
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 103  
 Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : VERTICAL  
 Limit : FCC PART 15C AV  
 Env. / Ins. : 24°C/56% Engineer : Leo-Li  
 EUT : 150Mbps Wireless N USB Module  
 Power Rating : DC 3.3V From PC Input AC 120V/60Hz  
 Test Mode : IEEE802.11nHT40 2452MHz Tx  
 M/N : PW-MN427\_34I

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission			Remark
						Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	
1	2435.370	28.26	5.85	35.70	85.14	83.55	54.00	-29.55	Average
2	2483.500	28.36	5.92	35.70	38.57	37.15	54.00	16.85	Average
3	2500.000	28.40	5.94	35.70	36.54	35.18	54.00	18.82	Average

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading  
 -Amp Factor  
 2. The emission levels that are 20dB below the official  
 limit are not reported.



Site no. : 3m Chamber Data no. : 104  
 Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : VERTICAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 24°C/56% Engineer : Leo-Li  
 EUT : 150Mbps Wireless N USB Module  
 Power Rating : DC 3.3V From PC Input AC 120V/60Hz  
 Test Mode : IEEE802.11nHT40 2452MHz Tx  
 M/N : PW-MN427\_34I

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBUV)	Emission Level (dBUV/m)	Limits (dBUV/m)	Margin (dB)	Remark
1	2435.370	28.26	5.85	35.70	94.95	93.36	74.00	-19.36	Peak
2	2483.500	28.36	5.92	35.70	49.65	48.23	74.00	25.77	Peak
3	2500.000	28.40	5.94	35.70	47.67	46.31	74.00	27.69	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading  
 -Amp Factor  
 2. The emission levels that are 20dB below the official limit are not reported.

## 7. 6dB Bandwidth Test

### 7.1. Test Equipment

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	Spectrum Analyzer	Agilent	N9030A	MY51380221	Oct.31, 13	1 Year
2.	Amp	HP	8449B	3008A08495	May.08, 13	1 Year
3.	Antenna	EMCO	3115	9510-4580	May.08, 13	1 Year
4.	HF Cable	Hubersuhner	Sucoflex104	-	May.08, 13	1 Year

### 7.2. Limit

For direct sequence systems, the minimum 6dB bandwidth shall be at least 500kHz

### 7.3. Test Procedure

The transmitter output was connected to a spectrum analyzer, The bandwidth of the fundamental frequency was measured by spectrum analyzer with 300KHz RBW and 1MHz VBW. The 6dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 6dB.

### 7.4. Test Results

EUT: 150Mbps Wireless N USB Module		
M/N: PW-MN427_34I		
Test date: 2014-03-27	Pressure: 101.2±1.0 kpa	Humidity: 51.2±3.0%
Tested by: Leo-Li	Test site: RF Site	Temperature: 21.4±0.6°C

Cable loss: 1 dB		Attenuator loss: 20 dB	
Test Mode	CH	-6dB bandwidth (MHz)	Limit (KHz)
11b	CH1	10.19	>500
	CH6	10.19	>500
	CH11	10.17	>500
11g	CH1	16.59	>500
	CH6	16.72	>500
	CH11	16.48	>500
11n HT20	CH1	17.62	>500
	CH6	17.65	>500
	CH11	17.65	>500
11n HT40	CH1	36.40	>500
	CH4	36.52	>500
	CH7	36.44	>500
Conclusion : PASS			

Test Mode: IEEE 802.11b TX  
 Test CH1: 2412MHz



Test CH6: 2437MHz



Test CH11: 2462MHz




Test Mode: IEEE 802.11g TX  
 Test CH1: 2412MHz




Test CH6: 2437MHz



Test CH11: 2462MHz



Test Mode: IEEE 802.11n HT20 TX  
 Test CH1: 2412MHz




Test CH6: 2437MHz






Test CH11: 2462MHz



Test Mode: IEEE 802.11n HT40 TX


Test CH1: 2422MHz



Test CH4: 2437MHz



Test CH7: 2452MHz



## 8. OUTPUT POWER TEST

### 8.1. Test Equipment

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	Spectrum Analyzer	Agilent	N9030A	MY51380221	Oct.31, 13	1 Year
2.	Amp	HP	8449B	3008A08495	May.08, 13	1 Year
3.	Antenna	EMCO	3115	9510-4580	May.08, 13	1 Year
4.	HF Cable	Hubersuhne	Sucoflex104	-	May.08, 13	1 Year
5.	Power Meter	Anritsu	ML2487A	6K00002472	May.08, 13	1 Year
6.	Power Sensor	Anritsu	MA2491A	033005	May.08, 13	1 Year
7.	Spectrum Analyzer	Agilent	N9030A	MY5138022	May.08, 13	1 Year

### 8.2. Limit (FCC Part 15C 15.247 b(3))

For systems using digital modulation in the 2400—2483.5MHz, The Peak out put Power shall not exceed 1W(30dBm)

### 8.3. Test Procedure

- 1, Use the spectrum analyzer's channel power function.
- 2, Set the RBW=1MHz
- 3, Set the VBW=3MHz
- 4, Set the span to a value that is 5-30% greater than the EBW.
- 5, Detector=Peak
- 6, Sweep time=auto couple
- 7, Trace mode=max hold
- 8, Allow trace to fully stabilize
- 9, Record the measurement power.

### 8.4. Test Results

EUT: 150Mbps Wireless N USB Module			
M/N: PW-MN427_34I			
Test date: 2014-03-26		Pressure: 101.1±1.0 kpa	Humidity: 49.7±3.0%
Tested by: Leo-Li		Test site: RF site	Temperature: 21.2±0.6 °C
Cable loss: 1 dB		Attenuator loss: 20 dB	
Test Mode	CH	Peak output Power (dBm)	Limit (dBm)
11b	CH1	22.33	30
	CH6	21.70	30
	CH11	21.93	30
11g	CH1	25.12	30
	CH6	26.15	30
	CH11	26.18	30
11n HT20	CH1	24.89	30
	CH6	22.73	30
	CH11	23.25	30
11n HT40	CH1	23.81	30
	CH4	23.34	30
	CH7	23.76	30
Conclusion: PASS			

Test Mode: IEEE 802.11b TX

Test CH1: 2412MHz




Test CH6: 2437MHz



Test CH11: 2462MHz



Test Mode: IEEE 802.11g TX  
 Test CH1: 2412MHz




Test CH6: 2437MHz



Test CH11: 2462MHz



Test Mode: IEEE 802.11n HT20 TX  
 Test CH1: 2412MHz




Test CH6: 2437MHz





Test CH11: 2462MHz




Test Mode: IEEE 802.11n HT40 TX


Test CH1: 2422MHz



Test CH4: 2437MHz



Test CH7: 2452MHz



## 9. POWER SPECTRAL DENSITY TEST

### 9.1. Test Equipment

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	Spectrum Analyzer	Agilent	N9030A	MY51380221	Oct.31, 13	1 Year
2.	Amp	HP	8449B	3008A08495	May.08, 13	1 Year
3.	Antenna	EMCO	3115	9607-4580	Aug.28, 13	1 Year
4.	HF Cable	Hubersuhne	Sucoflex104	-	May.08, 13	1 Year

### 9.2. Limit

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8dBm in any 3kHz band during any time interval of continuous transmission.

### 9.3. Test Procedure

1. Connected the EUT's antenna port to spectrum analyzer device by 20dB attenuator.
2. Set the test frequency as center frequency, Set RBW=3KHz, VBW=10KHz, Span large enough capture the entire frequency, Read out maximum peak level frequency
3. Set the frequency read from produce 2 as center frequency, then set the span= 300KHz, Sweep time=Span/RBW, Then Max hold, read out each mode and each chain's Power density.

Note: The cable loss and attenuator loss were offset into measure device as an amplitude.


9.4. Test Results

EUT: 150Mbps Wireless N USB Module			
M/N: PW-MN427_34I			
Test date: 2014-02-20		Pressure: 101.3±1.0 kpa	Humidity: 49.7±3.0%
Tested by: Leo-Li		Test site: RF site	Temperature: 20.2±0.6 °C
Cable loss: 1 dB		Attenuator loss: 20 dB	
Test Mode	CH	Power density ( dBm/3KHz )	Limit ( dBm/3KHz )
11b	CH1	-9.210	8
	CH6	-9.902	8
	CH11	-9.528	8
11g	CH1	-13.070	8
	CH6	-12.582	8
	CH11	-9.630	8
11n HT20	CH1	-11.097	8
	CH6	-15.082	8
	CH11	-14.392	8
11n HT40	CH1	-15.791	8
	CH4	-15.933	8
	CH7	-12.732	8
Conclusion: PASS			


Test Mode: IEEE 802.11b TX  
 Test CH1: 2412MHz




Test CH6: 2437MHz




Test CH11: 2462MHz




Test Mode: IEEE 802.11g TX  
Test CH1: 2412MHz



Test CH6: 2437MHz




Test CH11: 2462MHz



Test Mode: IEEE 802.11n HT20 TX  
 Test CH1: 2412MHz




Test CH6: 2437MHz






Test CH11: 2462MHz




Test Mode: IEEE 802.11n HT40 TX


Test CH1: 2422MHz



Test CH4: 2437MHz



Test CH7: 2452MHz



## 10.MPE ESTIMATION

### 10.1.Limit for General Population/ Uncontrolled Exposures

Frequency	Power density (mW/ cm <sup>2</sup> )	Averaging time(minutes)
300MHz----1.5GHz	F/1500	30
1.5GHz---100GHz	1.0	30

Frequency(MHz)	Power density (mW/ cm <sup>2</sup> )	Averaging time(minutes)
2412	1	30
2437	1	30
2462	1	30

Note: F= Frequency in MHz Estimation Result

EUT: 150Mbps Wireless N USB Module		
M/N: PW-MN427_34I		
Test date: 2014-03-25	Pressure: 101.2±1.0 kpa	Humidity: 51.2±3.0%
Tested by: Leo-Li	Test site: RF site	Temperature:21.3±0.6

Cable loss: 1 dB		Attenuator loss: 20 dB				Antenna Gain: 1.8 dBi	
Test Mode	CH	Frequency ( MHz )	Peak Output Power (dBm)	Output Power (mW)	Antenna Gain (dBi)	Antenna Gain (Linear)	MPE
11b	CH1	2412	22.33	171.00	1.8	1.51	0.0515
	CH6	2437	21.70	147.91	1.8	1.51	0.0446
	CH11	2462	21.93	155.96	1.8	1.51	0.0470
11g	CH1	2412	25.12	325.09	1.8	1.51	0.0979
	CH6	2437	26.15	412.10	1.8	1.51	0.1242
	CH11	2462	26.18	414.95	1.8	1.51	0.1250
11n HT20	CH1	2412	24.89	308.32	1.8	1.51	0.0929
	CH6	2437	22.73	187.50	1.8	1.51	0.0565
	CH11	2462	23.25	211.35	1.8	1.51	0.0637
11n HT40	CH1	2422	23.81	240.44	1.8	1.51	0.0724
	CH4	2437	23.34	215.77	1.8	1.51	0.0650
	CH7	2452	23.76	237.68	1.8	1.51	0.0716

Note:  $MPE = P * G / (4 R^2)$  ; R=20cm

## **11. ANTENNA REQUIREMENT**

### **11.1. STANDARD APPLICABLE**

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

### **11.2. ANTENNA CONNECTED CONSTRUCTION**

The antennas used for this product are IFA antenna that no antenna other than that furnished by the responsible party shall be used with the device, the maximum peak gain of the transmit antenna is 1.8dBi.

## 12. DEVIATION TO TEST SPECIFICATIONS

[ NONE ]