

FCC Test Report

for

TIME RECORDER

Model Number : TR320
FCC ID : WXATR320
Report Number : RF-R020-1203-483
Date of Receipt : April 24, 2012
Date of Report : May 31, 2012

Prepared for

GIGA-TMS INC.

8F., No. 31, Lane 169, Kang-Ning St., Hsi-Chih Dist., New Taipei City, Taiwan

Prepared by



Central Research Technology Co.

EMC Test Laboratory

11, Lane 41, Fushuen St., Jungshan Chiu, Taipei, Taiwan, 104, R.O.C.



NVLAP LAB CODE 200575-0

This report shall not be reproduced, except in full, without the written approval of Central Research Technology Co.. It may be duplicated completely in its entirety for legal use with the permission of the applicant. It should not be used to claim product endorsement by NVLAP, NIST or any U.S. government agency. The test result in the report applies only to the sample tested.

Certification

Equipment Under Test : TIME RECORDER
Model No. : TR320
FCC ID : WXATR320
Applicant : GIGA-TMS INC.
Address : 8F., No. 31, Lane 169, Kang-Ning St., Hsi-Chih Dist., New Taipei City, Taiwan
Applicable Standards : **FCC Part 15, Subpart C**
Date of Testing : May 7 ~ 14, 2012
Deviation : N/A
Condition of Test Sample : Mass Production

We, **Central Research Technology Co.**, hereby certify that one sample of the designated product was tested in our facility during the period mentioned above. The test records, data evaluation and Equipment Under Test (EUT) configurations shown in the present report are true and accurate representation of the measurements of the sample's RF characteristics under the conditions herein specified.

The test results show that the EUT as described in the present report is in compliance with the requirements set forth in the standards mentioned above and apply to the tested sample identified in the present report only. The test report shall not be reproduced, except in its entirety, without the written approval of Central Research Technology Co.

PREPARED BY

: Cathy Chen, **DATE** : May 31, 2012
(Cathy Chen/System Executive)

APPROVED BY

: T. Y. Shih, **DATE** : May 31, 2012
(Tsun-Yu Shih/General Manager)

Contents

1.	General Description	5
1.1	GENERAL DESCRIPTION OF EUT	5
1.2	TEST MODE	6
1.3	TEST METHODOLOGY	6
1.4	APPLIED STANDARDS	7
1.5	THE SUPPORT UNITS	10
1.6	LAYOUT OF THE SETUP	10
1.7	TEST CAPABILITY	11
1.8	MEASUREMENT UNCERTAINTY	13
2.	Field Strength of fundamental Measurement.....	14
2.1	APPLIED STANDARD	14
2.2	TEST INSTRUMENTS	15
2.3	MEASUREMENT PROCEDURE	16
2.4	TEST CONFIGURATION	17
2.5	TEST RESULTS	18
3.	Radiated Emission	22
3.1	APPLIED STANDARD	22
3.2	TEST INSTRUMENTS	23
3.3	MEASUREMENT PROCEDURE	24
3.4	TEST CONFIGURATION	25
3.5	TEST RESULTS	26
4.	Frequency Tolerance	30
4.1	APPLIED STANDARD	30
4.2	TEST INSTRUMENTS	31
4.3	MEASUREMENT PROCEDURE	32
4.4	TEST CONFIGURATION	32
4.5	TEST RESULTS	33
5.	20dB Bandwidth	37
5.1	APPLIED STANDARD	37
5.2	TEST INSTRUMENTS	38
5.3	MEASUREMENT PROCEDURE	39
5.4	TEST CONFIGURATION	39
5.5	TEST RESULTS	40

6.	Conducted Emission Measurement	41
6.1	APPLIED STANDARD	41
6.2	TEST INSTRUMENTS	42
6.3	TEST PROCEDURES	43
6.4	TEST CONFIGURATIONS	44
6.5	TEST RESULTS	45
7.	Antenna Requirement	49
7.1	APPLIED STANDARD	49
7.2	ANTENNA TYPE	49
7.3	APPLICABLE RESULT	49

Attachment 1 – Photographs of the Test Configurations

Attachment 2 – External Photographs of EUT

Attachment 3 – Internal Photographs of EUT

1. General Description

1.1 General Description of EUT

Equipment Under Test	:	TIME RECORDER
Model No.	:	TR320
Power in	:	Supplied by the power adaptor
Power Adapter Specification	:	Model No.: AD41-1200500DU Input : 120Vac~60Hz, 0.2A Output : 12Vdc, 0.5A
Test Voltage	:	110Vac/60Hz to the adaptor
Frequency Range	:	13.56MHz
Channel Numbers	:	1
Function Modulation	:	ASK
Function Description	:	

The EUT is used to transmit and receive signal both. Please refer to the user's manual for the details.

1.2 Test Mode

Normal operating as the specification of manufacturer.

1.3 Test Methodology

For this E.U.T., the radiated emissions and conducted emission measurement performed according to the procedures illustrated in ANSI C63.4:2003 and other required are illustrated in separate sections of this test report for detail.

1.4 Applied standards

(1) Field strength of Fundametal

According to 15.225(a), the field strength of any emissions within the band 13.553 - 13.567 MHz shall not exceed 15,848 microvolts/meter at 30 meters.

(2) Band Edge

According to 15.225(b), Within the bands 13.410-13.553 MHz and 13.567-13.710 MHz, the field strength of any emissions shall not exceed 334 microvolts/meter at 30 meters. According to 15.225(c), Within the bands 13.110-13.410 MHz and 13.710-14.010 MHz the field strength of any emissions shall not exceed 106 microvolts/meter at 30 meters.

(3) Radiation emission

According to 15.225(d), the field strength of any emissions appearing outside of the 13.110-14.010 MHz band shall not exceed the general radiated emission limits in § 15.209.

(4) Frequency tolerance

The frequency tolerance of the carrier signal shall be maintained within +/- 0.01% of the operating frequency over a temperature variation of -20 degrees to +50 degrees C at normal supply voltage, and for a variation in the primary supply voltage from 85% to 115% of the rated supply voltage at a temperature of 20 degrees C. For battery operated equipment, the equipment tests shall be performed using a new battery.

(5) Radiated emission limits, general requirements.

According to 15.209, except as provided elsewhere in this Subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field Strength (uV/m)	Measurement Distance (m)
0.009 - 0.490	2400/F(kHz)	300
0.490 - 1.705	24000/F(kHz)	30
1.705 - 30.0	30	30
30 - 88	100 **	3
88 - 216	150 **	3
216 - 960	200 **	3
Above 960	500	3

** Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this Section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this Part, e.g., Sections 15.231 and 15.241.

(6) 20dB Bandwidth

According to 15.215(c) requires the device must be designed to ensure that the 20 dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates.

(7) Conduction Emission Requirement

For intentional device, according to §15.207(a) line conduction emission limit is as below table.

Frequency of Emission (MHz)	Conducted Limit (dBuV)	
	Quasi-peak	Average
0.15 – 0.5	66 to 56*	56 to 46*
0.5 - 5	56	46
5 - 30	60	50

* Decreases with the logarithm of the frequency.

(8) Restricted Band

Frequency (MHz)	Frequency (MHz)	Frequency (MHz)	Frequency (GHz)
0.090 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
¹ 0.495 - 0.505	16.69475 - 16.69525	608 - 614	5.35 - 5.46
² 1735 - 2.1905	16.80425 - 16.80475	960 - 1240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1300 - 1427	8.025 - 8.5
4.17725 - 4.17775	37.5 - 38.25	1435 - 1626.5	9.0 - 9.2
4.20725 - 4.20775	73 - 74.6	1645.5 - 1646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1660 - 1710	10.6 - 12.7
6.26775 - 6.26825	108 - 121.94	1718.8 - 1722.2	13.25 - 13.4
6.31175 - 6.31225	123 - 138	2200 - 2300	14.47 - 14.5
8.291 - 8.294	149.9 - 150.05	2310 - 2390	15.35 - 16.2
8.362 - 8.366	156.52475 - 156.52525	2483.5 - 2500	17.7 - 21.4
8.37625 - 8.38675	156.7 - 156.9	2690 - 2900	22.01 - 23.12
8.41425 - 8.41475	162.0125 - 167.17	3260 - 3267	23.6 - 24.0
12.29 - 12.293	167.72 - 173.2	3332 - 3339	31.2 - 31.8
12.51975 - 12.52025	240 - 285	3345.8 - 3358	36.43 - 36.5
12.57675 - 12.57725	322 - 335.4	3600 - 4400	(2)
13.36 - 13.41			

¹ Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz.

² Above 38.6


(9) Antenna Requirement

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of Sections 15.211, 15.213, 15.217, 15.219, or 15.221. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with Section 15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this Part are not exceeded.

1.5 The Support Units

No.	Unit	Model No./ Serial No.	FCC ID	Trade Name	Power Cord	Supported by lab.
1	RFID Card	N/A	N/A	N/A	N/A	

1.6 Layout of the Setup



Connecting Cables :

No.	Cable	Length	Shielded	Core	Shielded Backshell	Supported by lab.	Note
A	LAN Cable	>3m				✓	
B	RJ11 Cable	1.8m				✓	floating

Justification:

For both conducted and radiated emission below 1GHz, the system was configured for typical fashion as a customer could use it normally.

For radiated emission, measurement of radiated emission from digital circuit is performed with normal transmitting.

1.7 Test Capability

Test Facility

The test facility used for evaluating the conformance of the EUT with each standard in the present report meets what required in CISPR16-1-4, CISPR16-2-3 and ANSI C63.4: 2003.

Test Room	Type of Test Room	Descriptions
TR1	10m semi-anechoic chamber (23m×14m×9m)	Complying with the NSA requirements set in documents CISPR 22 and ANSI C63.4:2009. For the radiated emission measurement.
TR11	3m semi-anechoic chamber (9m × 6m × 6m)	
TR300	3m fully-anechoic chamber (8m × 5m × 5m)	
TR13	Test site	For the RF conducted emission measurement.
TR5	Shielding Room (8m×5m×4m)	For the conducted emission measurement.

Test Laboratory Competence Information

Central Research Technology Co. has been accredited / filed / authorized by the agencies listed in the following table.

Certificate	Nation	Agency	Code	Mark
Accreditation Certificate	USA	NVLAP	200575-0	ISO/IEC 17025
	R.O.C. (Taiwan)	TAF	0905	ISO/IEC 17025
	R.O.C. (Taiwan)	BSMI	SL2-IN-E-0033, SL2-IS-E-0033, SL2-R1/R2-E-0033, SL2-A1-E-0033 SL2-L1-E-0033	ISO/IEC 17025
Site Filing Document	USA	FCC	474046,TW1053	Test facility list & NSA Data
	Canada	IC	4699A-1,-3	Test facility list & NSA Data
	Japan	VCCI	R-1527,C-1609,T-1441,G-10	Test facility list & NSA Data
Authorization Certificate	Germany	TUV	10021687	ISO/IEC 17025
	Norway	Nemko	ELA 212	ISO/IEC 17025

The copy of each certificate can be downloaded from our web site: www.crc-lab.com

1.8 Measurement Uncertainty

The assessed measurement uncertainty with a suitable coverage factor K to ensure 95% confidence level for the normal distribution are shown as below, the values are less than U_{cispr} in table 1 of CISPR 16-4-2.

Test Item	Measurement Uncertainty	
Frequency error	4.2Hz	
Radiated Emission: (30MHz~200MHz)	Horizontal: 3.8dB ; Vertical: 3.3dB	
Radiated Emission: (200MHz~1GHz)	Horizontal: 4.1dB ; Vertical: 3.7dB	
Conducted Emission	ESH2-Z5	3.1dB
	ENV 4200	2.7dB

2. Field Strength of fundamental Measurement

Test Result : PASS

2.1 Applied Standard

According to 15.225(a), the field strength of any emissions within the band 13.553 – 13.567 MHz shall not exceed 15,848 microvolts/meter at 30 meters.

According to 15.225(b), within the bands 13.410-13.553 MHz and 13.567-13.710 MHz, the field strength of any emissions shall not exceed 334 microvolts/meter at 30 meters.

According to 15.225(c), within the bands 13.110-13.410 MHz and 13.710-14.010 MHz the field strength of any emissions shall not exceed 106 microvolts/meter at 30 meters.

2.2 Test Instruments

Test Site and Equipment	Manufacturer	Model No./ Serial No.	Last Calibration Date	Calibration Due Date
EMI Test Receiver	R&S	ESCI/ 100019	May 25, 2011	May 25, 2012
Loop Antenna	EMCO	6502/ 20558	Aug. 11, 2011	Aug. 11, 2014
TR11 Semi – anechoic Chamber	ETS. LINDGREN	TR11/ 906-A	April 22, 2012	April 22, 2013

Note:

1. The calibrations are traceable to NML/ROC.
2. NCR : No Calibration Required.
3. The calibration date of the semi-anechoic chamber listed above is the date of NSA measurement.

Instrument Setting

RBW	VBW	Detector	Trace	Comment
9kHz	N/A	Quasi-Peak	Maxhold	


Climatic Condition

Ambient Temperature : 26°C ; Relative Humidity : 62%

2.3 Measurement Procedure

- a. The EUT was set up per the test configuration figured in the next section of this chapter to simulate the typical usage per the user's manual.
- b. If the EUT is tabletop equipment, it should be placed on a wooden table with a height of 0.8 meters above the reference ground plane in the semi-anechoic chamber. If the EUT is floor-standing equipment, it should be placed on a non-conducted support with a height of 12 millimeters above the reference ground plane in the semi-anechoic chamber.
- c. The EUT is set at 3m away from the receiving antenna.
- d. Rapidly sweep the signal in the test frequency range by using the receiver through the Quasi-Peak detector.
- e. Rotate the EUT from 0° to 360° and position the receiving loop antenna at 1~4 meters above the reference ground plane to determine the fundamental frequency and and bandedge and record them.
- f. Then measure each frequency found from step e. by using the receiver with rotating the EUT and positioning the receiving antenna height to determine the maximum level.
- g. Finely tune the antenna and turntable around the recorded position of each frequency found from step e.
- h. Record and compare the maximum level with the required limit.
- i. Change the receiving antenna to another polarization to measure field strength of fundamental by following step d. to g. again.

2.4 Test Configuration



2.5 Test Results

Field strength of fundamental



Test Mode : Continuous Transmitting

Tester : Liu

Freq. (MHz)	Polarization	Reading Data (dBuV)	Correction Factor (dB/m)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)
13.56	H	36.48	14.26	50.74	124	73.26
13.56	V	39.55	14.26	53.81	124	70.19

Note :

1. Correction Factor (dB/m) = Cable Loss + Antenna Factor
2. Output Field Strength (dBuV/m) = Reading Data + Correction Factor
3. The limit is 15848 (uV/m)=84dBuV/m @ 30 m , for main frequency < 30MHz, the formula transfers the limit at 30 m to 3m is $L_{30}(\text{dBuV/m}) + 40 = 124 \text{ dBuV/m}$
4. Margin (dB) = Limit – Output Field Strength

H Polarization**V Polarization**

Band Edge



Test Mode : Continuous Transmitting

Tester : Liu

Emission Freq. (MHz)	Polarizational	Reading Data (dBuV)	Correction Factor (dB/m)	Maximum Emission within the band (dBuV/m)	Limit (dBuV/m)	Margin (dB)
13.19	H	11.95	14.29	26.24	80.51	54.27
13.14	V	13.01	14.29	27.30	80.51	53.21
13.50	H	16.04	14.26	30.30	90.47	60.17
13.49	V	16.18	14.26	30.44	90.47	60.03
13.67	H	13.18	14.25	27.43	90.47	63.04
13.62	V	13.98	14.26	28.24	90.47	62.23
13.73	H	12.26	14.25	26.51	80.51	54.00
13.88	V	11.78	14.24	26.02	80.51	54.49

Note :

1. Correction Factor (dB/m) = Cable Loss + Antenna Factor
2. Output Field Strength (dBuV/m) = Reading Data + Correction Factor
3. For main frequency < 30MHz, the formula transfers the limit at 30 m to 3m is $L_{30}(\text{dBuV/m}) + 40$
4. Margin (dB) = Limit – Output Field Strength

H Polarization**V Polarization**

3. Radiated Emission

Test Result : PASS

3.1 Applied Standard

According to 15.225(d), The field strength of any emissions appearing outside of the 13.110-14.010 MHz band shall not exceed the general radiated emission limits in § 15.209.

Frequency (MHz)	Field Strength (uV/m)	Measurement Distance (m)
0.009 - 0.490	2400/F(kHz)	300
0.490 - 1.705	24000/F(kHz)	30
1.705 - 30.0	30	30
30 - 88	100 **	3
88 - 216	150 **	3
216 - 960	200 **	3
Above 960	500	3

** Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this Section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this Part, e.g., Sections 15.231 and 15.241.

3.2 Test Instruments

Test Site and Equipment	Manufacturer	Model No./ Serial No.	Last Calibration Date	Calibration Due Date
EMI Test Receiver	R&S	ESCI/ 100019	May 25, 2011	May 25, 2012
Spectrum Analyzer	Agilent	E4407B/ MY45106795	May 4, 2012	May 4, 2013
Loop Antenna	EMCO	6502/ 20558	Aug. 11, 2011	Aug. 11, 2014
Bi-Log Antenna	EMCO	3142C/ 52088	May 19, 2011	May 19, 2012
Pre-Amplifier	Mini-circuit	ZKL-2/ 004	Feb. 6, 2012	Aug. 6, 2012
RF Cable	N/A	N/A/ C0080	Feb. 6, 2012	Aug. 6, 2012
TR11 Semi - anechoic Chamber	ETS. LINDGREN	TR11/ 906-A	April 22, 2012	April 22, 2013

Note:

1. The calibrations are traceable to NML/ROC.
2. NCR:No Calibration Required.

Instrument Setting

RBW	VBW	Detector	Trace	Comment
9kHz	N/A	Quasi-Peak	Maxhold	Below 30MHz
120kHz	N/A	Quasi-Peak	Maxhold	Below 1GHz

Climatic Condition


Ambient Temperature : 26°C; Relative Humidity : 62%

3.3 Measurement Procedure


- a. The EUT was set up per the test configuration figured in the next section of this chapter to simulate the typical usage per the user's manual.
- b. A software provided by client enabled the EUT to transmit and receive data at specified channel frequencies individually.
- c. If the EUT is tabletop equipment, it was placed on a non-conducted table with a height of 0.8 meters above the reference ground plane in the semi-anechoic chamber. If the EUT is floor-standing equipment, it was placed on a non-conducted support with a height of 12 millimeters above the reference ground plane in the semi-anechoic chamber.
- d. The EUT is set at 3m away from the interference receiving antenna.
- e. Rapidly sweep the signal in the test frequency range by using the spectrum through the Maximum-peak detector.
- f. Rotate the EUT from 0° to 360° and position the receiving antenna at heights from 1 to 4 meters above the reference ground plane continuously to determine at least six frequencies associated with higher emission levels and record them.
- g. For measurement of frequency above 1000MHz, the beamwidth of receiving horn antenna should keep covering EUT when the receiving horn antenna height varied.
- h. Then measure each frequency found from step e. by using the spectrum with rotating the EUT and positioning the receiving antenna height to determine the maximum level.
- i. Finely tune the antenna and turntable around the recorded position of each frequency found from step g.
- j. For measurement of frequency below 1000MHz, set the receiver detector to be Quasi-Peak per CISPR 16-1 to find out the maximum level occurred.
- k. For measurement of frequency above 1000MHz, set the spectrum detector to be Peak or Average to find out the maximum level occurred, if any.
- l. Record frequency, azimuth angle of the turntable, height, and polarization of the receiving antenna and compare the maximum level with the required limit.
- m. Change the receiving antenna to another polarization to measure radiated emission by following step e. to l. again.
- n. If the peak emission level measured from step e. is 4dB lower than the limit specified, then the emission values presented will be the peak value only. Otherwise, accurate Q.P. value will be measured and presented.

3.4 Test Configuration

Radiated Emission Measurement below 30MHz



Radiated Emission Measurement above 30MHz



3.5 Test Results

Test Mode : Continuous Transmitting

Tester : Liu


Frequency Range : 9kHz~30MHz

Polarization : Horizontal

	Freq. (MHz)	Reading Data (dBuV)	Correction Factor (dB/m)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)
1	0.15	42.66	15.80	58.46	104.08	45.62
2	1.85	23.28	15.09	38.37	69.54	31.17
3	4.48	18.97	14.43	33.40	69.54	36.14
4	7.97	18.34	14.45	32.79	69.54	36.75
5	15.55	17.41	14.13	31.54	69.54	38.00
6	18.45	17.21	13.95	31.16	69.54	38.38

Note:

1. Correction Factor (dB/m) = Cable Loss + Antenna Factor
2. Emission Level (dBuV/m) = Reading Data + Correction Factor
3. Margin (dB) = Limit – Emission Level
4. For main frequency < 30MHz, the formula transfers the limit at 30 m to 3m is $L_{30}(\text{dBuV/m}) + 40$



No signal can be detected from 9kHz to 150kHz, so the graphs are omitted below 150kHz.

Test Mode : Continuous Transmitting

Tester : Liu


Frequency Range : 9kHz~30MHz

Polarization : Vertical

	Freq. (MHz)	Reading Data (dBuV)	Correction Factor (dB/m)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)
1	0.15	44.29	15.80	60.09	104.08	43.99
2	3.11	20.18	14.57	34.75	69.54	34.79
3	4.39	18.96	14.44	33.4	69.54	36.14
4	9.79	17.20	14.49	31.69	69.54	37.85
5	17.34	17.06	14.02	31.08	69.54	38.46
6	21.97	17.41	13.50	30.91	69.54	38.63

Note:

1. Correction Factor (dB/m) = Cable Loss + Antenna Factor
2. Emission Level (dBuV/m) = Reading Data + Correction Factor
3. Margin (dB) = Limit – Emission Level
4. For main frequency < 30MHz, the formula transfers the limit at 30 m to 3m is $L_{30}(\text{dBuV/m}) + 40$




No signal can be detected from 9kHz to 150kHz, so the graphs are omitted below 150kHz.

Test Mode : Continuous Transmitting

Tester : Liu

Frequency Range : 30MHz~1GHz

Polarization : Horizontal



	Freq	Level	Read	Limit	Over	Ant	Table		
	MHz	dBuV/m	Level	Factor	Line	Limit	Pos	Pos	Pol/Phase
			dBuV	dB/m	dBuV/m	dB	cm	deg	Remark
1	93.990	32.50	51.21	-18.71	43.50	-11.00	---	---	HORIZONTAL Peak
2	106.950	28.85	47.47	-18.62	43.50	-14.65	---	---	HORIZONTAL Peak
3	148.260	29.42	46.88	-17.46	43.50	-14.08	---	---	HORIZONTAL Peak
4	489.000	40.24	47.67	-7.43	46.00	-5.76	100	300	HORIZONTAL QP
5	569.500	39.14	44.33	-5.19	46.00	-6.86	---	---	HORIZONTAL Peak
6	597.500	39.17	43.86	-4.69	46.00	-6.83	---	---	HORIZONTAL Peak

Note :


1. Correction Factor (dB/m) = Cable Loss + Antenna Factor – Gain of Preamplifier
2. Emission Level (dBuV/m) = Reading Data + Correction Factor

Test Mode : Continuous Transmitting

Tester : Liu

Frequency Range : 30MHz~1GHz

Polarization : Vertical



	Freq	Level	Read	Limit	Over	Ant	Table		
	MHz	dBuV/m	Level	Factor	Line	Limit	Pos	Pos	Pol/Phase
	MHz	dBuV/m	dBuV	dB/m	dBuV/m	dB	cm	deg	Remark
1	43.230	32.60	47.69	-15.09	40.00	-7.40	100	29	VERTICAL
2	69.150	33.62	53.05	-19.43	40.00	-6.38	---	---	VERTICAL
3	148.260	35.71	53.17	-17.46	43.50	-7.79	---	---	VERTICAL
4	678.700	39.54	43.20	-3.66	46.00	-6.46	---	---	VERTICAL
5	706.700	39.12	42.24	-3.12	46.00	-6.88	---	---	VERTICAL
6	787.200	38.71	41.13	-2.42	46.00	-7.29	---	---	VERTICAL

Note :

1. Correction Factor (dB/m) = Cable Loss + Antenna Factor – Gain of Preamplifier
2. Emission Level (dBuV/m) = Reading Data + Correction Factor

4. Frequency Tolerance

Test Result : PASS

4.1 Applied Standard

According to 15.225(e), the frequency tolerance of the carrier signal shall be maintained within +/- 0.01% of the operating frequency over a temperature variation of -20 degrees to +50 degrees C at normal supply voltage, and for a variation in the primary supply voltage from 85% to 115% of the rated supply voltage at a temperature of 20 degrees C. For battery operated equipment, the equipment tests shall be performed using a new battery.

4.2 Test Instruments

Test Site and Equipment	Manufacturer	Model No./ Serial No.	Last Calibration Date	Calibration Due Date
Spectrum Analyzer	Agilent	E4405B/ MY45106706	March 29, 2012	March 29, 2013
Temperature Chamber	Terchy	MHG-800LF/ 920224	Aug. 8, 2011	Aug. 8, 2012
Adjustable AC Power Supply	EXTECH	6110/1102108	NCR	NCR
Test Site	N.A.	TR13	NCR	NCR

Note:

1. The calibrations are traceable to NML/ROC.
2. NCR:No Calibration Required.

Instrument Setting

RBW	VBW	Detector	Trace	Comment
300Hz	300Hz	Peak	Maxhold	


Climatic Condition

Ambient Temperature : 24°C; Relative Humidity : 55%

4.3 Measurement Procedure

- a. The EUT was set up per the test configuration figured in the next section of this chapter to simulate the typical usage described in the user's manual supported by the manufacturer in test site TR13.
- b. Measure the frequency tolerance by using the spectrum analyzer and following the test conditions described in FCC 15.225(e) to perform the normal and extreme conditions test.
- c. Record the value and compare with the required limit.

4.4 Test Configuration



4.5 Test Results

Test Mode : Continuous Transmitting


Tester : Liu

Temperature (°C)	AC Voltage (Volt)	Meas. Frequency (MHz)	Deviation (kHz)	Limit (kHz)	Margin (kHz)
20°C	120	13.56054	NA	1.356	NA
	138	13.56054	0.00	1.356	1.356
	102	13.56054	0.00	1.356	1.356
-20°C	120	13.56063	0.09	1.356	1.266
50°C	120	13.56059	0.05	1.356	1.306


Note:

1. Deviation(kHz) = | Meas. Frequency – Meas. Frequency @20°C/120Vac |
2. Margin (kHz)= Limit – Deviation


20°C, 120Vac




20°C, 138Vac




20°C, 102Vac



-20°C, 120Vac



50°C, 120Vac



5. 20dB Bandwidth

Test Result : PASS

5.1 Applied Standard

According to 15.215(c) requires the device must be designed to ensure that the 20 dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates.

According to 15.225, Operation should within the band 13.110 – 14.010 MHz.

5.2 Test Instruments

Test Site and Equipment	Manufacturer	Model No./ Serial No.	Last Calibration Date	Calibration Due Date
Spectrum Analyzer	Agilent	E4405B/ MY45106706	March 29, 2012	March 29, 2013
Test Site	N.A.	TR13	NCR	NCR

Note:

- 1.The calibrations are traceable to NML/ROC.
- 2.NCR : No Calibration Required.

Instrument Setting

RBW	VBW	Detector	Trace	Comment
300Hz	300Hz	Sample	Maxhold	

Climatic Condition

Ambient Temperature : 24°C; Relative Humidity : 55%

5.3 Measurement Procedure

- a. The EUT was set up per the test configuration figured in the next section of this chapter to simulate the typical usage described in the user's manual supported by the manufacturer in test site TR13.
- b. Measure the 20dB bandwidth by using the spectrum analyzer and following the test conditions described in FCC 15.215.
- c. Record the frequency and compare with the required limit.

5.4 Test Configuration




5.5 Test Results

Test Mode : Continuous Transmitting

Tester : Bill

Operating Frequency (MHz)	Limit (MHz)
13.56	13.110~14.01



6. Conducted Emission Measurement

Test Result : PASS

6.1 Applied Standard

For intentional device, according to §15.207(a) line conduction emission limit is as below table.

Frequency of Emission (MHz)	Conducted Limit (dBuV)	
	Quasi-peak	Average
0.15 – 0.5	66 to 56*	56 to 46*
0.5 - 5	56	46
5 - 30	60	50

* Decreases with the logarithm of the frequency.

Note:

For a device with a permanent antenna operating at or below 30 MHz, the FCC will accept measurements done with a suitable dummy load, in lieu of the permanent antenna under the following conditions: (1) perform the AC line conducted tests with the permanent antenna to determine compliance with the Section 15.207 limits outside the transmitter's fundamental emission band; (2) retest with a dummy load in lieu of the permanent antenna to determine compliance with the Section 15.207 limits within the transmitter's fundamental emission band.

6.2 Test Instruments

Test Site and Equipment	Manufacturer	Model No./ Serial No.	Last Calibration Date	Calibration Due Date
Test Receiver	R&S	ESCS 30/ 836858/021	Jan. 11, 2012	Jan. 11, 2013
LISN	R&S	ESH2-Z5/ 836613/001	June 2, 2011	June 2, 2012
2 nd LISN	R&S	ENV4200/ 833209/010	Jan. 14, 2012	Jan. 14, 2013
50Ω terminator	N/A	N/A/ 001	Aug. 20, 2011	Aug. 20, 2012
RF Switch	N/A	RSU28/ 338965/002	Feb. 20, 2012	Aug. 20, 2012
RF Cable	N/A	N/A/ C0052 ~ 56	Feb. 20, 2012	Aug. 20, 2012
Test Software	Audix	e3/ Ver. 5.2004-2-19k	NCR	NCR
TR5 shielded room	ETS LINDGREN	TR5/ 15353-F	NCR	NCR

Note:

1. The calibrations are traceable to NML/ROC.
2. NCR : No Calibration Required.

Instrument Setting

IF BW	Measurement Time	Detector	Trace	Comment
9kHz	1 second	Quasi-Peak / Average	Maxhold	


Climatic Condition

Ambient Temperature : 25°C; Relative Humidity : 55%

6.3 Test Procedures


- a. The EUT was set up per the test configuration figured in the next section of this chapter to simulate the typical usage per the user's manual.
- b. If the EUT is tabletop equipment, it was placed on a non-conducted table with a height of 0.8 meters above the reference ground plane and 0.4 meters from the conducting wall of the shielded room. Also if the EUT is floor-standing equipment, it was placed on a non-conducted support with a height of 12 millimeters above the reference ground plane.
- c. Connect the EUT's power source to the appropriate power mains through the LISN.
- d. All the other peripherals are connected to the 2nd LISN, if any.
- e. The LISN was placed 0.8 meters from the EUT and at least 0.8 meters from other units and other metal planes.
- f. Measure the conducted emissions on each power line (Neutral Line and Line 1 – Hot side) of the EUT's power source by using the test receiver connected to the coupling RF output port of LISN.
- g. Rapidly scan the signal from 150kHz to 30MHz by using the receiver through the Maximum-Peak detector to determine those frequencies associated with higher emission levels for each measured line.
- h. Then measure the maximum level of conducted disturbance for each frequency found from step g. by using the receiver through the Quasi-Peak and Average detectors per CISPR 16-1.
- i. Record the level for each frequency and compare with the required limit.

6.4 Test Configurations



6.5 Test Results

Test Mode : Continuous Transmitting, with antenna
Tester : CDC **Frequency Range** : 150kHz~30MHz
Phase : Line




	Freq	Level	Factor	Read Level	Limit Line	Over Limit	Pol/Phase	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB		
1	0.150	41.92	0.17	41.75	66.00	-24.08	LINE	QP
2	0.150	16.08	0.17	15.91	56.00	-39.92	LINE	AVERAGE
3	0.188	14.24	0.17	14.07	54.11	-39.87	LINE	AVERAGE
4	0.188	40.55	0.17	40.38	64.11	-23.56	LINE	QP
5	0.277	11.63	0.18	11.45	50.90	-39.27	LINE	AVERAGE
6	0.277	37.33	0.18	37.15	60.90	-23.57	LINE	QP
7	0.383	33.64	0.20	33.44	58.21	-24.57	LINE	QP
8	0.383	9.95	0.20	9.75	48.21	-38.26	LINE	AVERAGE
9	0.502	31.04	0.22	30.82	56.00	-24.96	LINE	QP
10	0.502	8.85	0.22	8.63	46.00	-37.15	LINE	AVERAGE
11 X	13.560	59.09	0.81	58.28	50.00	9.09	LINE	AVERAGE
12	13.560	59.45	0.81	58.64	60.00	-0.55	LINE	QP

Note:

1. Emission Level = reading value + correction factor.
2. Correction factor = cable loss + insertion loss of LISN.
3. Q.P. is abbreviation of quasi-peak.
4. Tx Fundamental(markered 11, 12), for reference only. Please refer to next page.

Test Mode : Continuous Transmitting, with dummy load
Tester : CDC **Frequency Range** : 150kHz~30MHz
Phase : Line




	Freq	Level	Factor	Read	Limit	Over		
	MHz	dBuV	dB	Level	Line	Limit	Pol/Phase	Remark
1	0.150	40.36	0.17	40.19	66.00	-25.64	LINE	QP
2	0.150	15.28	0.17	15.11	56.00	-40.72	LINE	AVERAGE
3	0.195	12.89	0.17	12.72	53.80	-40.91	LINE	AVERAGE
4	0.195	38.32	0.17	38.15	63.80	-25.48	LINE	QP
5	0.274	10.32	0.18	10.14	50.98	-40.67	LINE	AVERAGE
6	0.274	34.34	0.18	34.16	60.98	-26.65	LINE	QP
7	0.371	30.67	0.19	30.48	58.47	-27.80	LINE	QP
8	0.371	9.27	0.19	9.08	48.47	-39.20	LINE	AVERAGE
9	0.817	6.70	0.23	6.47	46.00	-39.30	LINE	AVERAGE
10	0.817	21.80	0.23	21.57	56.00	-34.20	LINE	QP
11	13.560	39.64	0.81	38.83	50.00	-10.36	LINE	AVERAGE
12	13.560	40.16	0.81	39.35	60.00	-19.84	LINE	QP

Note:

1. Emission Level = reading value + correction factor.
2. Correction factor = cable loss + insertion loss of LISN.
3. Q.P. is abbreviation of quasi-peak.

Test Mode : Continuous Transmitting, with antenna
Tester : CDC **Frequency Range** : 150kHz~30MHz
Phase : Neutral




	Freq	Level	Factor	Read Level	Limit Line	Over Limit	Pol/Phase	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB		
1	0.156	42.51	0.16	42.35	65.69	-23.18	NEUTRAL	QP
2	0.156	16.55	0.16	16.39	55.69	-39.14	NEUTRAL	AVERAGE
3	0.258	39.71	0.18	39.53	61.51	-21.81	NEUTRAL	QP
4	0.258	13.44	0.18	13.26	51.51	-38.08	NEUTRAL	AVERAGE
5	0.402	37.01	0.20	36.81	57.81	-20.80	NEUTRAL	QP
6	0.402	11.61	0.20	11.41	47.81	-36.20	NEUTRAL	AVERAGE
7	0.510	10.89	0.22	10.67	46.00	-35.11	NEUTRAL	AVERAGE
8	0.510	35.69	0.22	35.47	56.00	-20.31	NEUTRAL	QP
9	0.573	33.88	0.22	33.66	56.00	-22.12	NEUTRAL	QP
10	0.573	10.21	0.22	9.99	46.00	-35.79	NEUTRAL	AVERAGE
11	13.560	59.19	0.65	58.54	50.00	9.19	NEUTRAL	AVERAGE
12	13.560	59.44	0.65	58.79	60.00	-0.56	NEUTRAL	QP

Note:

1. Emission Level = reading value + correction factor.
2. Correction factor = cable loss + insertion loss of LISN.
3. Q.P. is abbreviation of quasi-peak.
4. Tx Fundamental(markered 11, 12), for reference only. Please refer to next page.

Test Mode : Continuous Transmitting, with dummy load
Tester : CDC **Frequency Range** : 150kHz~30MHz
Phase : Neutral



	Freq	Level	Factor	Read Level	Limit Line	Over Limit	Pol/Phase	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB		
1	0.155	41.75	0.16	41.59	65.74	-23.98	NEUTRAL	QP
2	0.155	16.21	0.16	16.05	55.74	-39.52	NEUTRAL	AVERAGE
3	0.206	13.93	0.17	13.76	53.36	-39.43	NEUTRAL	AVERAGE
4	0.206	40.29	0.17	40.12	63.36	-23.07	NEUTRAL	QP
5	0.282	38.69	0.18	38.51	60.76	-22.08	NEUTRAL	QP
6	0.282	12.42	0.18	12.24	50.76	-38.35	NEUTRAL	AVERAGE
7	0.408	36.69	0.20	36.49	57.68	-20.99	NEUTRAL	QP
8	0.408	11.33	0.20	11.13	47.68	-36.35	NEUTRAL	AVERAGE
9	0.541	35.43	0.22	35.21	56.00	-20.57	NEUTRAL	QP
10	0.541	11.69	0.22	11.47	46.00	-34.31	NEUTRAL	AVERAGE
11	13.560	39.24	0.65	38.59	50.00	-10.76	NEUTRAL	AVERAGE
12	13.560	39.66	0.65	39.01	60.00	-20.34	NEUTRAL	QP

Note:

1. Emission Level = reading value + correction factor.
2. Correction factor = cable loss + insertion loss of LISN.
3. Q.P. is abbreviation of quasi-peak.

7. Antenna Requirement

7.1 Applied Standard

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of Sections 15.211, 15.213, 15.217, 15.219, or 15.221. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with Section 15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this Part are not exceeded.

7.2 Antenna Type

The EUT use a permanently attached antenna.

7.3 Applicable Result

Comply the requirement.