

RF EXPOSURE REPORT

Applicant	Faurecia Clarion Electronics (Xiamen) Co., Ltd.
Address	6F, No.40, Guanri Road, Software Park Stage II, Xiamen, China

Manufacturer or Supplier	Faurecia Clarion Electronics (Xiamen) Co., Ltd.		
Address	6F, No.40, Guanri Road, Software Park Stage II, Xiamen, China		
Product	Audio Display		
Brand Name	Clarion		
Model	PP-4330		
Additional Model & Model Difference	PP4330		
Date of tests	Dec. 14, 2023 ~ Dec. 21, 2023		

- FCC Part 2 (Section 2.1091)
- **KDB 447498 D01 V06**
- **⊠** IEEE C95.1

CONCLUSION: The submitted sample was found to COMPLY with the test requirement

Tested by Andy Zhu Supervisor / EMC Department	Tested by Madison Luo Assistant Manager / EMC Department
Andy	Jan All Control of the Control of th

Date: Jan. 04, 2024

This report is governed by, and incorporates by reference, the Conditions of Testing as posted at the date of issuance of this report at http://www.bureauveritas.com/home/about-us/our-business/cps/about-us/terms-conditions/ and is intended for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided us. Measurement uncertainty is only provided upon request for accredited tests. Statements of conformity are based on simple acceptance criteria without taking measurement uncertainty into account, unless otherwise requested in writing. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence or if you require measurement uncertainty; provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents.

Tel: +86 769 8998 2098 Fax: +86 769 8593 1080

Email: <u>customerservice.dg@cn.bureauveritas.com</u>



Table of Contents

RELE.	ASE CONTROL RECORD	. 3
	CERTIFICATION	
2.	RF EXPOSURE LIMIT	5
3.	MPE CALCULATION FORMULA	5
4.	CLASSIFICATION	5
5.	ANTENNA GAIN	6
6	CALCULATION RESULT OF MAXIMUM CONDUCTED POWER	6

Tel: +86 769 8998 2098 Fax: +86 769 8593 1080

 $\pmb{\text{Email:}} \ \underline{\text{customerservice.dg@cn.bureauveritas.com}}$



RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
FM2008WDG0104	Original release	Oct. 09, 2020
FM2312WDG0114	Based on the original report FM2008WDG0104 changed the company name of the applicant/Manufacturer and added the additional model, canceled the SiriusXM function, changed the front housing plate.	Jan. 04, 2024

Tel: +86 769 8998 2098 Fax: +86 769 8593 1080

Email: customerservice.dg@cn.bureauveritas.com

Page 3 of 7 Report Version 1



1. CERTIFICATION

FCC ID:	WY2-PP4330
PRODUCT:	Audio Display
BRAND NAME:	Clarion
MODEL NO.:	PP-4330
ADDITIONAL NO.: PP4330	
APPLICANT:	Faurecia Clarion Electronics (Xiamen) Co., Ltd.
STANDARDS:	FCC Part 2 (Section 2.1091)
	KDB 447498 D01 V06
	IEEE C95.1

Tel: +86 769 8998 2098 Fax: +86 769 8593 1080

Email: customerservice.dg@cn.bureauveritas.com



2. RF EXPOSURE LIMIT

LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

FREQUENCY RANGE (MHz)	ELECTRIC FIELD STRENGTH (V/m)	POWER DENSITY (mW/cm²)	AVERAGE TIME (minutes)			
LIMITS FOR GENERAL POPULATION / UNCONTROLLED EXPOSURE						
300-1500 F/1500 30						
1500-100,000			1.0	30		

F = Frequency in MHz

3. MPE CALCULATION FORMULA

 $Pd = (Pout*G) / (4*pi*r^2)$

where

Pd = power density in mW/cm²

Pout = output power to antenna in mW

G = gain of antenna in linear scale

Pi = 3.1416

R = distance between observation point and center of the radiator in cm

4. CLASSIFICATION

The antenna of this product, under normal use condition, is at least 20cm away from the body of the user. So, this device is classified as **Mobile Device**.

Tel: +86 769 8998 2098 Fax: +86 769 8593 1080

Email: customerservice.dg@cn.bureauveritas.com



5. ANTENNA GAIN

The antennas provided to the EUT, please refer to the following table:

Transmitter Circuit	Peak Gain (dBi)	Antenna Type
Wi-Fi 2.4GHz	-0.38	PCB Antenna
BT	0	PCB Antenna

6. CALCULATION RESULT OF MAXIMUM CONDUCTED AV POWER

The tuned conducted Average Power (declared by client)

Mode	Frequency (MHz)	Target Power (dBm)	Tolerance (dBm)	Lower Tolerance (dBm)	Upper Tolerance (dBm)
GFSK	2402-2480	-1	+-2	-3	1
8DPSK	2402-2480	-1	+-2	-3	1
802.11b	2412-2462	13	+-2	11	15
802.11g	2412-2462	13	+-2	11	15
802.11n HT20	2412-2462	13	+-2	11	15

The measured conducted Average Power

o measured conducted it orage i one.				
Mode	Frequency (MHz)	Averaged Power (dBm)		
GFSK	2402	-1.22		
8DPSK	2402	-0.29		
802.11b	2462	13.11		
802.11g	2437	12.69		
802.11n HT20	2437	12.38		

Tel: +86 769 8998 2098 Fax: +86 769 8593 1080

Email: customerservice.dg@cn.bureauveritas.com



FREQUENCY BAND (MHz)	MAX AVERAGE POWER (dBm)	ANTENNA GAIN (dBi)	DISTANCE (cm)	POWER DENSITY (mW/cm²)	LIMIT (mW/cm²)
ВТ	1	0	20	0.000250	1
Wi-Fi 2.4GHz	15	-0.38	20	0.005763	1

CONCLUSION:

The BT and WIFI can transmit simultaneously, the formula of calculated the MPE is:

CPD1 / LPD1 + CPD2 / LPD2 +etc. < 1

CPD = Calculation power density

LPD = Limit of power density

(0.000250/1)+(0.005763/1) = 0.006013<1, which is less than the "1" limit.

--- END ---

Tel: +86 769 8998 2098 Fax: +86 769 8593 1080

Email: customerservice.dg@cn.bureauveritas.com