



Test Report No.: FM2008WDG0391

RF EXPOSURE REPORT

Applicant	Clarion Co., Ltd.
Address	6F, No.40, Guanri Road, Software Park Stage II, Xiamen, China.

Manufacturer or Supplier	Clarion Co., Ltd.
Address	6F, No.40, Guanri Road, Software Park Stage II, Xiamen, China.
Product	Audio Display
Brand Name	Clarion
Model	PP-4360
Additional Model & Model Difference	N/A
Date of tests	Sep. 03, 2020 ~ Sep. 25, 2020

FCC Part 2 (Section 2.1091)

KDB 447498 D01

IEEE C95.1

CONCLUSION: The submitted sample was found to COMPLY with the test requirement

Tested by Madison Luo
Assistant Manager / EMC Department

Approved by Chris Chen
Manager / EMC Department

Date: Oct. 09, 2020

This report is governed by, and incorporates by reference, CPS Conditions of Service as posted at the date of issuance of this report at <http://www.bureauveritas.com/home/about-us/our-business/cps/about-us/terms-conditions/> and is intended for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. Measurement uncertainty is only provided upon request for accredited tests. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence or if you require measurement uncertainty; provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents.



Table of Contents

RELEASE CONTROL RECORD	3
1. CERTIFICATION.....	4
2. RF EXPOSURE LIMIT	5
3. MPE CALCULATION FORMULA.....	5
4. CLASSIFICATION	5
5. ANTENNA GAIN	6
6. CALCULATION RESULT OF MAXIMUM CONDUCTED POWER.....	6



BUREAU
VERITAS

Test Report No.: FM2008WDG0391

RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
FM2008WDG0391	Original release	Oct. 09, 2020

Bureau Veritas Shenzhen Co., Ltd.
Dongguan Branch

No. 96, Guantai Road (Houjie Section), Houjie
Town, Dongguan City, Guangdong Province.
523942. People's Republic of China.

Tel: +86 769 8998 2098
Fax: +86 769 8593 1080
Email: customerservice.dg@cn.bureauveritas.com



1. CERTIFICATION

FCC ID:	WY2-PP4360
PRODUCT:	Audio Display
BRAND NAME:	Clarion
MODEL NO.:	PP-4360
ADDITIONAL NO.:	N/A
APPLICANT:	Clarion Co., Ltd.
STANDARDS:	FCC Part 2 (Section 2.1091)
	KDB 447498 D01
	IEEE C95.1



2. RF EXPOSURE LIMIT

LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

FREQUENCY RANGE (MHz)	ELECTRIC FIELD STRENGTH (V/m)	MAGNETIC FIELD STRENGTH (A/m)	POWER DENSITY (mW/cm ²)	AVERAGE TIME (minutes)
LIMITS FOR GENERAL POPULATION / UNCONTROLLED EXPOSURE				
300-1500	F/1500	30
1500-100,000	1.0	30

F = Frequency in MHz

3. MPE CALCULATION FORMULA

$$Pd = (Pout * G) / (4 * pi * r^2)$$

where

Pd = power density in mW/cm²

Pout = output power to antenna in mW

G = gain of antenna in linear scale

Pi = 3.1416

R = distance between observation point and center of the radiator in cm

4. CLASSIFICATION

The antenna of this product, under normal use condition, is at least 20cm away from the body of the user. So, this device is classified as **Mobile Device**.



5. ANTENNA GAIN

The antennas provided to the EUT, please refer to the following table:

Transmitter Circuit	Peak Gain (dBi)	Antenna Type
Wi-Fi 2.4GHz	-1.8	PCB Antenna
BT	0	PCB Antenna

6. CALCULATION RESULT OF MAXIMUM CONDUCTED AV POWER

The tuned conducted Average Power (declared by client)

Mode	Frequency (MHz)	Target Power (dBm)	Tolerance (dBm)	Lower Tolerance (dBm)	Upper Tolerance (dBm)
GFSK	2402-2480	-1	+2	-3	1
8DPSK	2402-2480	-1	+2	-3	1
802.11b	2412-2462	10	+2	8	12
802.11g	2412-2462	10	+2	8	12
802.11n HT20	2412-2462	10	+2	8	12

The measured conducted Average Power

Mode	Frequency (MHz)	Averaged Power (dBm)
GFSK	2402	-1.12
8DPSK	2402	-0.27
802.11b	2462	10.91
802.11g	2437	10.93
802.11n HT20	2437	10.86



FREQUENCY BAND (MHz)	MAX AVERAGE POWER (dBm)	ANTENNA GAIN (dBi)	DISTANCE (cm)	POWER DENSITY (mW/cm ²)	LIMIT (mW/cm ²)
BT	1	0	20	0.000250	1
Wi-Fi 2.4GHz	12	-1.8	20	0.002083	1

CONCLUSION:

The BT and WIFI can transmit simultaneously, the formula of calculated the MPE is:

$$CPD1 / LPD1 + CPD2 / LPD2 + \dots \text{etc.} < 1$$

CPD = Calculation power density

LPD = Limit of power density

$$(0.000250/1)+(0.002083/1) = 0.002333 < 1, \text{ which is less than the "1" limit.}$$

--- END ---