

## TEST REPORT



Applicant	Clarion Co., Ltd.
Address	6F,No.40,Guanri Road, Software Park Stage II, Xiamen, China

Manufacturer or Supplier	Clarion Co., Ltd.
Address	6F, No.40, Guanri Road, Software Park Stage II, Xiamen, China
Product	CAR NAVIGATION
Brand Name	CLARION
Model	QY-8900
Additional Model & Model Difference	QY-8950, QY-8901, QY-8951; See items 3.1
Date of tests	Mar. 01, 2017 ~ Mar. 13, 2017

the tests have been carried out according to the requirements of the following standards:

**FCC Part 15, Subpart C, Section 15.247**

**CONCLUSION: The submitted sample was found to COMPLY with the test requirement**

Tested by Madison Luo Supervisor / EMC Department	Approved by Chris Chen Manager / EMC Department
	  Date: Mar. 17, 2017

This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification

## TABLE OF CONTENTS

RELEASE CONTROL RECORD.....	4
1 SUMMARY OF TEST RESULTS .....	5
2 MEASUREMENT UNCERTAINTY.....	5
3 GENERAL INFORMATION.....	6
3.1 GENERAL DESCRIPTION OF EUT .....	6
3.2 DESCRIPTION OF TEST MODES .....	7
3.2.1. CONFIGURATION OF SYSTEM UNDER TEST.....	8
3.2.2. TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL.....	8
3.3 GENERAL DESCRIPTION OF APPLIED STANDARDS.....	10
3.4 DESCRIPTION OF SUPPORT UNITS.....	10
4 TEST TYPES AND RESULTS .....	11
4.1. RADIATED EMISSION AND BANDEDGE MEASUREMENT .....	11
4.1.1. LIMITS OF RADIATED EMISSION AND BANDEDGE MEASUREMENT .....	11
4.1.2. TEST INSTRUMENTS .....	12
4.1.3. TEST PROCEDURES.....	13
4.1.4. DEVIATION FROM TEST STANDARD .....	13
4.1.5. TEST SETUP .....	14
4.1.6. EUT OPERATING CONDITIONS.....	15
4.1.7. TEST RESULTS.....	16
4.2. NUMBER OF HOPPING FREQUENCY USED .....	24
4.2.1. LIMIT OF HOPPING FREQUENCY USED .....	24
4.2.2. TEST SETUP .....	24
4.2.3. TEST INSTRUMENTS .....	24
4.2.4. TEST PROCEDURES.....	25
4.2.5. DEVIATION FROM TEST STANDARD .....	25
4.2.6. TEST RESULTS.....	25
4.3. DWELL TIME ON EACH CHANNEL .....	28
4.3.1. LIMIT OF DWELL TIME USED.....	28
4.3.2. TEST SETUP .....	28
4.3.3. TEST INSTRUMENTS .....	28
4.3.4. TEST PROCEDURES.....	28
4.3.5. DEVIATION FROM TEST STANDARD .....	28
4.3.6. TEST RESULTS.....	29
4.4. CHANNEL BANDWIDTH.....	32



4.4.1. LIMITS OF CHANNEL BANDWIDTH.....	32
4.4.2. TEST SETUP .....	32
4.4.3. TEST INSTRUMENTS.....	32
4.4.4. TEST PROCEDURE .....	32
4.4.5. DEVIATION FROM TEST STANDARD .....	32
4.4.6. EUT OPERATING CONDITION .....	32
4.4.7. TEST RESULTS.....	33
4.5. HOPPING CHANNEL SEPARATION.....	37
4.5.1. LIMIT OF HOPPING CHANNEL SEPARATION .....	37
4.5.2. TEST SETUP .....	37
4.5.3. TEST INSTRUMENTS.....	37
4.5.4. TEST PROCEDURES.....	37
4.5.5. DEVIATION FROM TEST STANDARD .....	37
4.5.6. TEST RESULTS.....	38
4.6. MAXIMUM OUTPUT POWER .....	42
4.6.1. LIMITS OF MAXIMUM OUTPUT POWER MEASUREMENT .....	42
4.6.2. TEST SETUP .....	42
4.6.3. TEST INSTRUMENTS.....	42
4.6.4. TEST PROCEDURES.....	42
4.6.5. DEVIATION FROM TEST STANDARD .....	42
4.6.6. EUT OPERATING CONDITION .....	42
4.6.7. TEST RESULTS.....	43
4.7. OUT OF BAND EMISSION MEASUREMENT .....	44
4.7.1. LIMITS OF OUT OF BAND EMISSION MEASUREMENT .....	44
4.7.2. TEST INSTRUMENTS.....	44
4.7.3. TEST PROCEDURE .....	44
4.7.4. DEVIATION FROM TEST STANDARD .....	44
4.7.5. EUT OPERATING CONDITION .....	44
4.7.6. TEST RESULTS.....	44
5. PHOTOGRAPHS OF THE TEST CONFIGURATION .....	47
6. APPENDIX A - MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB .....	48



**BUREAU  
VERITAS**

Test Report No.: 170301N002

## RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
RF170301N002	Original release	Mar. 17, 2017



# 1 SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

APPLIED STANDARD: FCC Part 15, Subpart C			
STANDARD SECTION	TEST TYPE AND LIMIT	RESULT	REMARK
15.207	AC Power Conducted Emission	N/A	Powered by battery
15.247(a)(1)(iii)	Number of Hopping Frequency Used	PASS	Meet the requirement of limit.
15.247(a)(1)(iii)	Dwell Time on Each Channel	PASS	Meet the requirement of limit.
15.247(a)(1)	1. Hopping Channel Separation 2. Spectrum Bandwidth of a Frequency Hopping Sequence Spread Spectrum System	PASS	Meet the requirement of limit.
15.247(b)	Maximum Peak Output Power	PASS	Meet the requirement of limit.
15.247(d)& 15.209	Transmitter Radiated Emission	PASS	Meet the requirement of limit.
15.247(d)	Out of band Emission Measurement	PASS	Meet the requirement of limit.
15.203	Antenna Requirement	PASS	No antenna connector is used.

# 2 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

MEASUREMENT	FREQUENCY	UNCERTAINTY
Radiated emissions	9KHz ~ 30MHz	2.90dB
	30MHz ~ 1GMHz	3.83dB
	1GHz ~ 18GHz	4.93dB
	18GHz ~ 40GHz	4.80dB

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.



### 3 GENERAL INFORMATION

#### 3.1 GENERAL DESCRIPTION OF EUT

<b>PRODUCT</b>	CAR NAVIGATION
<b>MODEL NO.</b>	QY-8900
<b>ADDITIONAL MODELS</b>	QY-8950, QY-8901, QY-8951
<b>FCC ID</b>	WY2QY8900
<b>POWER SUPPLY</b>	DC 13.5V from battery
<b>MODULATION TECHNOLOGY</b>	FHSS
<b>MODULATION TYPE</b>	GFSK, 8DPSK, $\pi/4$ DQPSK
<b>OPERATING FREQUENCY</b>	2402MHz~2480MHz
<b>NUMBER OF CHANNEL</b>	79
<b>MAX. OUTPUT POWER</b>	1.208mW (Max. Measured)
<b>ANTENNA TYPE</b>	PCB Antenna, 0dBi Gain
<b>I/O PORTS</b>	Refer to user's manual
<b>CABLE SUPPLIED</b>	Refer to user's manual

**NOTE:**

1. For a more detailed features description, please refer to the manufacturer's specifications or the user's manual.
2. For the test results, the EUT had been tested with all conditions. But only the worst case was shown in test report.
3. Please refer to the EUT photo document (Reference No.: 170301N002) for detailed product photo.
4. Additional models QY-8950, QY-8901, QY-8951 are identical with the test model QY-8900 except the model No. and No BOSE/BOSE for trading purpose.



### 3.2 DESCRIPTION OF TEST MODES

79 channels are provided to this EUT:

CHANNEL	FREQ. (MHz)	CHANNEL	FREQ. (MHz)	CHANNEL	FREQ. (MHz)	CHANNEL	FREQ. (MHz)
0	2402	20	2422	40	2442	60	2462
1	2403	21	2423	41	2443	61	2463
2	2404	22	2424	42	2444	62	2464
3	2405	23	2425	43	2445	63	2465
4	2406	24	2426	44	2446	64	2466
5	2407	25	2427	45	2447	65	2467
6	2408	26	2428	46	2448	66	2468
7	2409	27	2429	47	2449	67	2469
8	2410	28	2430	48	2450	68	2470
9	2411	29	2431	49	2451	69	2471
10	2412	30	2432	50	2452	70	2472
11	2413	31	2433	51	2453	71	2473
12	2414	32	2434	52	2454	72	2474
13	2415	33	2435	53	2455	73	2475
14	2416	34	2436	54	2456	74	2476
15	2417	35	2437	55	2457	75	2477
16	2418	36	2438	56	2458	76	2478
17	2419	37	2439	57	2459	77	2479
18	2420	38	2440	58	2460	78	2480
19	2421	39	2441	59	2461		



### 3.2.1. CONFIGURATION OF SYSTEM UNDER TEST

Please see section 5 photograph of the test configuration for reference.

### 3.2.2. TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates, XYZ axis and antenna ports

The worst case was found when positioned on X axis for radiated emission.

Following channel(s) was (were) selected for the final test as listed below:

EUT CONFIGURE MODE	APPLICABLE TO				DESCRIPTION
	RE<1G	RE≥1G	PLC	APCM	
A	√	√	-	√	Powered by full Battery with Bluetooth link

Where **RE<1G**: Radiated Emission below 1GHz

**RE≥1G**: Radiated Emission above 1GHz

**PLC**: Power Line Conducted Emission

**APCM**: Antenna Port Conducted Measurement

**NOTE**: No need to concern of Conducted Emission due to the EUT is powered by battery.

#### **RADIATED EMISSION TEST (BELOW 1 GHz):**

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, XYZ axis, antenna ports (if EUT with antenna diversity architecture) and packet type.
- Following channel(s) was (were) selected for the final test as listed below.

AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	PACKET TYPE
0 to 78	39	FHSS	GFSK	DH5

For the test results, only the worst case was shown in test report.

#### **RADIATED EMISSION TEST (ABOVE 1 GHz):**

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, XYZ axis, antenna ports (if EUT with antenna diversity architecture) and packet type.
- Following channel(s) was (were) selected for the final test as listed below.

AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	PACKET TYPE
0 to 78	0, 39, 78	FHSS	GFSK	DH5
0 to 78	0, 39, 78	FHSS	8DPSK	DH5





**ANTENNA PORT CONDUCTED MEASUREMENT:**

- This item includes all test value of each mode, but only includes spectrum plot of worst value of each mode.
- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, antenna ports (if EUT with antenna diversity architecture), and packet types.
- Following channel(s) was (were) selected for the final test as listed below.

AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	PACKET TYPE
0 to 78	0, 39, 78	FHSS	GFSK	DH5
0 to 78	0, 39, 78	FHSS	8DPSK	DH5

**TEST CONDITION:**

APPLICABLE TO	ENVIRONMENTAL CONDITIONS	TEST VOLTAGE (SYSTEM)	TESTED BY
RE<1G	25deg. C, 53%RH	DC 13.5V from battery	Eric Fang
RE≥1G	25deg. C, 53%RH	DC 13.5V from battery	Eric Fang
PLC	N/A	N/A	N/A
APCM	20deg. C, 55%RH	DC 13.5V from battery	Sen He



### 3.3 GENERAL DESCRIPTION OF APPLIED STANDARDS

The EUT is a RF Product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

**FCC Part 15, Subpart C. Section 15.247  
ANSI C63.10-2013**

All test items have been performed and recorded as per the above standards.

### 3.4 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

NO.	PRODUCT	BRAND	MODEL NO.	SERIAL NO.	FCC ID
1	DC Source	GUWEI	21405	N/A	N/A

NO.	SIGNAL CABLE DESCRIPTION OF THE ABOVE SUPPORT UNITS
1	N/A



## 4 TEST TYPES AND RESULTS

### 4.1. RADIATED EMISSION AND BANDEDGE MEASUREMENT

#### 4.1.1. LIMITS OF RADIATED EMISSION AND BANDEDGE MEASUREMENT

Radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a). Other emissions shall be at least 20dB below the highest level of the desired power.

FREQUENCIES (MHz)	FIELD STRENGTH (microvolts/meter)	MEASUREMENT DISTANCE (meters)
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

**NOTE:**

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. As shown in 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.

**4.1.2. TEST INSTRUMENTS**

<b>Equipment</b>	<b>Manufacturer</b>	<b>Model No.</b>	<b>Serial No.</b>	<b>Last Cal.</b>	<b>Next Cal.</b>
EMI Test Receiver	Rohde&Schwarz	ESU40	100449	Nov. 04,16	Nov. 03,17
Signal and Spectrum Analyzer	Rohde&Schwarz	FSV7	102331	Nov. 04,16	Nov. 03,17
Bilog Antenna	Teseq	CBL 6111D	30643	Jul. 14, 16	Jul. 13, 17
Horn Antenna (1GHz -18GHz)	ETS -Lindgren	3117	00062558	May 18,16	May 17,17
GPS Generator+ Antenna	TOJOIN	GNSS-5000A	E1-010119	Aug. 08, 16	Aug. 07, 17
3m Semi-anechoic Chamber	ETS-LINDGREN	9m*6m*6m	NSEMC003	Mar. 12,16	Mar. 11,18
Test Software	ADT	ADT_Radiated_V7.6.15.9.2	N/A	N/A	N/A
Horn Antenna	SCHWARZBECK	BBHA 9170	BBHA9170242	Nov. 04,16	Nov. 03,17
Amplifier (9kHz-1GHz)	SONOMA	310D	186955	Mar. 04,17	Mar. 03, 18
Broadband Preamplifier (1GHz~18GHz)	SCHWARZBECK	BBV9718	305	Nov. 04,16	Nov. 03,17
Pre-Amplifier (18GHz-40GHz)	EMCI	EMC 184045	980102	Nov. 04,16	Nov. 03,17
Test Software	ADT	ADT_Radiated_V7.6.15.9.2	N/A	N/A	N/A
BLUETOOTH TESTER	Rohde&Schwarz	CBT32	100811	Aug. 08,16	Aug. 07,17

**NOTE:**

1. The test was performed in 966 Chamber.
2. The calibration interval of the above test instruments are 12, 24 months and the calibrations are traceable to CEPREI/CHINA, GRGT/CHINA and NIM/CHINA.
3. The horn antenna is used only for the measurement of emission frequency above 1GHz if tested.
4. The FCC Site Registration No. is 502831.



#### 4.1.3. TEST PROCEDURES

- a. The EUT was placed on the top of a rotating table 1.5 meters (above 1GHz) and 0.8 meters(below 1GHz) above the ground at a 3 meters semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna is a broadband antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. During the test, each emission was maximized by: having the EUT continuously working, investigated all operating modes, rotated about all 3 axis (X, Y & Z) and considered typical configuration to obtain worst position, manipulating interconnecting cables, For battery operated equipment, the equipment tests shall be perform using fresh batteries. The turntable was rotated to maximize the emission level.

#### **NOTE:**

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection at frequency below 1GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
3. Bluetooth duty factor correction is not correct as it is based on 79 channels, worst case would be with AFH enabled and device using the minimum of 20 channels. Channel hop rate = 800 hops/second (AFH Mode), Adjusted channel hop rate for DH5 mode = 133.33 hops/second, Time per channel hop =  $1 / 133.33$  hops/second = 7.5 ms, Time to cycle through all channels =  $7.5 \times 20$  channels = 150 ms, Number of times transmitter hits on one channel =  $100 \text{ ms} / 150 \text{ ms} = 1$  time(s), Worst case dwell time = 7.5 ms, Duty cycle connection factor =  $20\log_{10}(7.5\text{ms} / 100\text{ms}) = -22.5 \text{ dB}$ . Average value = peak reading +  $20\log(\text{duty cycle})$ .
4. All modes of operation were investigated and the worst-case emissions are reported.
5. The testing of the EUT was performed on all 3 orthogonal axes; the worst-case test configuration was reported on the file test setup photo.


#### 4.1.4. DEVIATION FROM TEST STANDARD

No deviation.




### 4.1.5. TEST SETUP

#### Below 1GHz test setup



For the actual test configuration, please refer to the attached file (Test Setup Photo).

#### Above 1GHz test setup



**Note:** For the actual test configuration, please refer to the attached file (Test Setup Photo).



**BUREAU  
VERITAS**

**Test Report No.: 170301N002**

#### 4.1.6. EUT OPERATING CONDITIONS

Set the transmitter part of EUT under transmission condition continuously at specific channel frequency.



### 4.1.7. TEST RESULTS

#### BELOW 1GHz WORST-CASE DATA:


#### GFSK DH5

CHANNEL	Channel 39	DETECTOR FUNCTION	Quasi-Peak (QP)
FREQUENCY RANGE	30MHz ~ 1GHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	239.86	34.46 QP	46.00	-11.54	1.00 H	0	50.80	-16.34
2	<b>255.40</b>	<b>38.72 QP</b>	<b>46.00</b>	<b>-7.28</b>	<b>1.00 H</b>	<b>0</b>	<b>52.33</b>	<b>-13.61</b>
3	272.50	34.47 QP	46.00	-11.53	1.00 H	0	48.12	-13.65
4	432.61	32.32 QP	46.00	-13.68	1.00 H	0	40.91	-8.59
5	752.84	36.20 QP	46.00	-9.80	1.00 H	0	36.37	-0.17
6	926.94	36.29 QP	46.00	-9.71	1.00 H	0	33.94	2.35

#### REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.








<b>CHANNEL</b>	Channel 39	<b>DETECTOR FUNCTION</b>	Quasi-Peak (QP)
<b>FREQUENCY RANGE</b>	30MHz ~ 1GHz		

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	159.02	26.37 QP	43.50	-17.13	1.00 V	0	43.48	-17.11
2	255.40	29.96 QP	46.00	-16.04	1.00 V	0	43.57	-13.61
3	272.50	27.85 QP	46.00	-18.15	1.00 V	0	41.50	-13.65
4	496.35	30.09 QP	46.00	-15.91	1.00 V	0	36.59	-6.50
5	527.44	35.34 QP	46.00	-10.66	1.00 V	0	40.90	-5.56
6	720.19	33.59 QP	46.00	-12.41	1.00 V	0	35.07	-1.48

**REMARKS:**

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.





ABOVE 1GHz WORST-CASE DATA: GFSK DH5

CHANNEL	TX Channel 0	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	44.50 PK	74.00	-29.50	1.75 H	216	41.45	3.05
2	2390.00	22.00 AV	54.00	-32.00	1.75 H	216	18.95	3.05
3	*2402.00	87.97 PK			1.75 H	216	84.90	3.07
4	*2402.00	65.47 AV			1.75 H	216	62.40	3.07
5	4804.00	52.32 PK	74.00	-21.68	1.26 H	203	47.23	5.09
6	4804.00	29.82 AV	54.00	-24.18	1.26 H	203	24.73	5.09
7	#7206.00	52.97 PK	74.00	-21.03	1.49 H	86	41.07	11.90
8	#7206.00	30.47 AV	54.00	-23.53	1.49 H	86	18.57	11.90

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	37.79 PK	74.00	-36.21	1.14 V	286	34.74	3.05
2	2390.00	15.29 AV	54.00	-38.71	1.14 V	286	12.24	3.05
3	*2402.00	84.96 PK			1.14 V	286	81.89	3.07
4	*2402.00	62.46 AV			1.14 V	286	59.39	3.07
5	4804.00	46.93 PK	74.00	-27.07	1.14 V	328	41.84	5.09
6	4804.00	24.43 AV	54.00	-29.57	1.14 V	328	19.34	5.09
7	#7206.00	48.03 PK	74.00	-25.97	1.12 V	184	36.13	11.90
8	#7206.00	25.53 AV	54.00	-28.47	1.12 V	184	13.63	11.90

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. " \* ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.



CHANNEL	TX Channel 39	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2441.00	85.78 PK			1.49 H	306	82.61	3.17
2	*2441.00	63.28 AV			1.49 H	306	60.11	3.17
3	4882.00	52.28 PK	74.00	-21.72	2.03 H	194	47.05	5.23
4	4882.00	29.78 AV	54.00	-24.22	2.03 H	194	24.55	5.23
5	7323.00	51.98 PK	74.00	-22.02	1.56 H	200	39.62	12.36
6	7323.00	29.48 AV	54.00	-24.52	1.56 H	200	17.12	12.36
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2441.00	81.72 PK			1.95 V	263	78.55	3.17
2	*2441.00	59.22 AV			1.95 V	263	56.05	3.17
3	4882.00	48.58 PK	74.00	-25.42	1.43 V	234	43.35	5.23
4	4882.00	26.08 AV	54.00	-27.92	1.43 V	234	20.85	5.23
5	7323.00	51.55 PK	74.00	-22.45	1.02 V	178	39.19	12.36
6	7323.00	29.05 AV	54.00	-24.95	1.02 V	178	16.69	12.36

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. " \* ": Fundamental frequency.



CHANNEL	TX Channel 78	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2480.00	80.44 PK			1.98 H	223	77.17	3.27
2	*2480.00	57.94 AV			1.98 H	223	54.67	3.27
3	2483.50	41.53 PK	74.00	-32.47	1.98 H	223	38.26	3.27
4	2483.50	19.03 AV	54.00	-34.97	1.98 H	223	15.76	3.27
5	4960.00	53.67 PK	74.00	-20.33	2.03 H	114	48.28	5.39
6	4960.00	31.17 AV	54.00	-22.83	2.03 H	114	25.78	5.39
7	7440.00	52.49 PK	74.00	-21.51	1.32 H	198	39.67	12.82
8	7440.00	29.99 AV	54.00	-24.01	1.32 H	198	17.17	12.82
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2480.00	73.50 PK			1.64 V	231	70.23	3.27
2	*2480.00	51.00 AV			1.64 V	231	47.73	3.27
3	2483.50	38.48 PK	74.00	-35.52	1.64 V	231	35.21	3.27
4	2483.50	15.98 AV	54.00	-38.02	1.64 V	231	12.71	3.27
5	4960.00	50.32 PK	74.00	-23.68	1.94 V	87	44.93	5.39
6	4960.00	27.82 AV	54.00	-26.18	1.94 V	87	22.43	5.39
7	<b>7440.00</b>	<b>54.36 PK</b>	<b>74.00</b>	<b>-19.64</b>	<b>1.75 V</b>	<b>219</b>	<b>41.54</b>	<b>12.82</b>
8	7440.00	31.86 AV	54.00	-22.14	1.75 V	219	19.04	12.82

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. " \* ": Fundamental frequency.



BT\_8DPSK DH5

CHANNEL	TX Channel 0	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	37.97 PK	74.00	-36.03	1.95 H	323	34.92	3.05
2	2390.00	15.47 AV	54.00	-38.53	1.95 H	323	12.42	3.05
3	*2402.00	87.96 PK			1.95 H	323	84.89	3.07
4	*2402.00	65.46 AV			1.95 H	323	62.39	3.07
5	4904.00	49.95 PK	74.00	-24.05	2.27 H	197	44.67	5.28
6	4904.00	27.45 AV	54.00	-26.55	2.27 H	197	22.17	5.28
7	#7206.00	49.53 PK	74.00	-24.47	1.64 H	203	37.63	11.90
8	#7206.00	27.03 AV	54.00	-26.97	1.64 H	203	15.13	11.90

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	38.42 PK	74.00	-35.58	2.16 V	316	35.37	3.05
2	2390.00	15.92 AV	54.00	-38.08	2.16 V	316	12.87	3.05
3	*2402.00	82.73 PK			2.16 V	316	79.66	3.07
4	*2402.00	60.23 AV			2.16 V	316	57.16	3.07
5	4804.00	46.51 PK	74.00	-27.49	2.16 V	223	41.42	5.09
6	4804.00	24.01 AV	54.00	-29.99	2.16 V	223	18.92	5.09
7	#7206.00	49.87 PK	74.00	-24.13	1.64 V	205	37.97	11.90
8	#7206.00	27.37 AV	54.00	-26.63	1.64 V	205	15.47	11.90

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. " \* ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.



CHANNEL	TX Channel 39	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2441.00	84.99 PK			1.64 H	219	81.82	3.17
2	*2441.00	62.49 AV			1.64 H	219	59.32	3.17
3	4882.00	51.14 PK	74.00	-22.86	1.64 H	235	45.91	5.23
4	4882.00	28.64 AV	54.00	-25.36	1.64 H	235	23.41	5.23
5	7323.00	50.97 PK	74.00	-23.03	1.46 H	214	38.61	12.36
6	7323.00	28.47 AV	54.00	-25.53	1.46 H	214	16.11	12.36
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2441.00	79.51 PK			1.64 V	238	76.34	3.17
2	*2441.00	57.01 AV			1.64 V	238	53.84	3.17
3	4882.00	48.42 PK	74.00	-25.58	1.77 V	216	43.19	5.23
4	4882.00	25.92 AV	54.00	-28.08	1.77 V	216	20.69	5.23
5	7323.00	50.30 PK	74.00	-23.70	1.19 V	246	37.94	12.36
6	7323.00	27.80 AV	54.00	-26.20	1.19 V	246	15.44	12.36

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. " \* ": Fundamental frequency.



CHANNEL	TX Channel 78	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2480.00	81.06 PK			1.94 H	302	77.79	3.27
2	*2480.00	58.56 AV			1.94 H	302	55.29	3.27
3	2483.50	42.84 PK	74.00	-31.16	1.94 H	302	39.57	3.27
4	2483.50	20.34 AV	54.00	-33.66	1.94 H	302	17.07	3.27
5	4960.00	53.63 PK	74.00	-20.37	1.14 H	295	48.24	5.39
6	4960.00	31.13 AV	54.00	-22.87	1.14 H	295	25.74	5.39
7	7440.00	51.64 PK	74.00	-22.36	2.16 H	328	38.82	12.82
8	7440.00	29.14 AV	54.00	-24.86	2.16 H	328	16.32	12.82

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2480.00	73.03 PK			1.19 V	326	69.76	3.27
2	*2480.00	50.53 AV			1.19 V	326	47.26	3.27
3	2483.50	38.69 PK	74.00	-35.31	1.19 V	326	35.42	3.27
4	2483.50	16.19 AV	54.00	-37.81	1.19 V	326	12.92	3.27
5	4960.00	47.51 PK	74.00	-26.49	1.25 V	118	42.12	5.39
6	4960.00	25.01 AV	54.00	-28.99	1.25 V	118	19.62	5.39
7	7440.00	52.18 PK	74.00	-21.82	1.56 V	251	39.36	12.82
8	7440.00	29.68 AV	54.00	-24.32	1.56 V	251	16.86	12.82

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. " \* ": Fundamental frequency.




## 4.2. NUMBER OF HOPPING FREQUENCY USED

### 4.2.1. LIMIT OF HOPPING FREQUENCY USED

At least 15 channels frequencies, and should be equally spaced.

### 4.2.2. TEST SETUP



### 4.2.3. TEST INSTRUMENTS

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
Power Sensor	Keysight	U2021XA	MY55060016	May 04,16	May 03,17
Power Sensor	Keysight	U2021XA	MY55060018	May 04,16	May 03,17
Digital Multimeter	FLUKE	15B	A1220010DG	Oct. 13, 16	Oct.12, 17
Humid & Temp Programmable Tester	Haida	HD-2257	110807201	Sep.05,16	Sep. 04,17
Oscilloscope	Agilent	DSO9254A	MY51260160	Nov. 04,16	Nov. 03,17
Signal Analyzer	Rohde & Schwarz	FSV7	102331	Nov. 04,16	Nov. 03,17
Signal Generator	Agilent	N5183A	MY50140980	Nov. 04,16	Nov. 03,17
Agile Signal Generator	Agilent	8645A	Agilent	Aug.08, 16	Aug.07, 17
Spectrum Analyzer	Keysight	N9020A	MY55400499	Apr. 05,16	Apr. 04,17
MXG-B RF Vector Signal Generator	Keysight	N5182B	MY56200288	Dec.05, 16	Dec. 04, 17
BLUETOOTH TESTER	Rohde&Schwarz	CBT32	100811	Aug.08, 16	Aug.07, 17

**NOTE:**

1. The test was performed in RF Oven room.
2. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to CEPREI/CHINA, GRGT/CHINA and NIM/CHINA.





#### 4.2.4. TEST PROCEDURES

- a. Check the calibration of the measuring instrument (SA) using either an internal calibrator or a known signal from an external generator.
- b. Turn on the EUT and connect its antenna terminal to measurement via a low loss cable. Then set it to any one measured frequency within its operating range and make sure the instrument is operated in its linear range.
- c. Set the SA on MaxHold Mode, and then keep the EUT in hopping mode. Record all the signals from each channel until each one has been recorded.
- d. Set the SA on View mode and then plot the result on SA screen.
- e. Repeat above procedures until all frequencies measured were completed.

#### 4.2.5. DEVIATION FROM TEST STANDARD

No deviation.

#### 4.2.6. TEST RESULTS



There are 79 hopping frequencies in the hopping mode. Please refer to next two pages for the test result. On the plots, it shows that the hopping frequencies are equally spaced.



BUREAU VERITAS

Test Report No.: 170301N002

GFSK







**BUREAU  
VERITAS**

Test Report No.: 170301N002

**8DPSK**






### 4.3. DWELL TIME ON EACH CHANNEL

#### 4.3.1. LIMIT OF DWELL TIME USED

The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.

#### 4.3.2. TEST SETUP



#### 4.3.3. TEST INSTRUMENTS

Refer to section 4.3.3 to get information of above instrument.

#### 4.3.4. TEST PROCEDURES

- a. Check the calibration of the measuring instrument (SA) using either an internal calibrator or a known signal from an external generator.
- b. Turn on the EUT and connect its antenna terminal to measurement via a low loss cable. Then set it to any one measured frequency within its operating range and make sure the instrument is operated in its linear range.
- c. Adjust the center frequency of SA on any frequency be measured and set SA to zero span mode. And then, set RBW and VBW of spectrum analyzer to proper value.
- d. Measure the time duration of one transmission on the measured frequency. And then plot the result with time difference of this time duration.
- e. Repeat above procedures until all different time-slot modes have been completed.

#### 4.3.5. DEVIATION FROM TEST STANDARD

No deviation.



### 4.3.6. TEST RESULTS

#### GFSK

Mode	Number of Hopping Channel	Number of transmission in a period(channel number*0.4 sec)				Length of transmission time (msec)	Result (msec)	Limit (msec)	PASS / FAIL
		period (sec)	sweep time (sec)	times in a sweep	times in a period				
DH1	79	31.6	5	51	322.32	0.492	158.58	400	PASS
DH3	79	31.6	5	25	158.00	1.770	279.66	400	PASS
DH5	79	31.6	5	16	101.12	2.992	302.55	400	PASS

#### 8DPSK

Mode	Number of Hopping Channel	Number of transmission in a period(channel number*0.4 sec)				Length of transmission time (msec)	Result (msec)	Limit (msec)	PASS / FAIL
		period (sec)	sweep time (sec)	times in a sweep	times in a period				
DH1	79	31.6	5	51	322.32	0.492	158.58	400	PASS
DH3	79	31.6	5	25	158.00	1.740	274.92	400	PASS
DH5	79	31.6	5	17	107.44	3.056	328.34	400	PASS

**NOTE:** Test plots of the transmitting time slot are shown on next page.



BUREAU VERITAS


Test Report No.: 170301N002

# GFSK





### 8DPSK






#### 4.4. CHANNEL BANDWIDTH

##### 4.4.1. LIMITS OF CHANNEL BANDWIDTH

For frequency hopping system operating in the 2400-2483.5MHz, If the 20dB bandwidth of hopping channel is greater than 25kHz, two-thirds 20dB bandwidth of hopping channel shall be a minimum limit for the hopping channel separation.

##### 4.4.2. TEST SETUP



##### 4.4.3. TEST INSTRUMENTS

Refer to section 4.3.3 to get information of above instrument.

##### 4.4.4. TEST PROCEDURE

- a. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- b. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
- c. Measure the frequency difference of two frequencies that were attenuated 20dB from the reference level. Record the frequency difference as the emission bandwidth.
- d. Repeat above procedures until all frequencies measured were complete.

##### 4.4.5. DEVIATION FROM TEST STANDARD

No deviation.

##### 4.4.6. EUT OPERATING CONDITION

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.






### 4.4.7. TEST RESULTS

#### GFSK

CHANNEL	CHANNEL FREQUENCY (MHz)	20dB BANDWIDTH (MHz)
0	2402	0.933
39	2441	0.934
78	2480	0.932

#### CH 0







BUREAU VERITAS

Test Report No.: 170301N002

CH 39



CH 78






8DPSK

CHANNEL	CHANNEL FREQUENCY (MHz)	20dB BANDWIDTH (MHz)
0	2402	1.26
39	2441	1.26
78	2480	1.26

CH 0







BUREAU VERITAS

Test Report No.: 170301N002

CH 39



CH 78






## 4.5. HOPPING CHANNEL SEPARATION

### 4.5.1. LIMIT OF HOPPING CHANNEL SEPARATION

At least 25kHz or two-third of 20dB hopping channel bandwidth (whichever is greater).

### 4.5.2. TEST SETUP



### 4.5.3. TEST INSTRUMENTS

Refer to section 4.3.3 to get information of above instrument.

### 4.5.4. TEST PROCEDURES

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range.
3. By using the Max Hold function record the separation of two adjacent channels.
4. Measure the frequency difference of these two adjacent channels by SA MARK function. And then plot the result on SA screen.
5. Repeat above procedures until all frequencies measured were complete.

### 4.5.5. DEVIATION FROM TEST STANDARD

No deviation.




### 4.5.6. TEST RESULTS

#### GFSK

CHANNEL	FREQUENCY (MHz)	ADJACENT CHANNEL SEPARATION (MHz)	20dB BANDWIDTH (MHz)	MINIMUM LIMIT (MHz)	PASS / FAIL
0	2402	1.01	0.933	0.622	PASS
39	2441	1.00	0.934	0.623	PASS
78	2480	1.01	0.932	0.621	PASS

**NOTE:** The minimum limit is two-third 20dB bandwidth.

#### CH 0







BUREAU  
VERITAS

Test Report No.: 170301N002

CH 39



CH 78






**8DPSK**

CHANNEL	FREQUENCY (MHz)	ADJACENT CHANNEL SEPARATION (MHz)	20dB BANDWIDTH (MHz)	MINIMUM LIMIT (MHz)	PASS / FAIL
0	2402	1.01	1.26	0.840	PASS
39	2441	1.00	1.26	0.840	PASS
78	2480	1.00	1.26	0.840	PASS

**NOTE:** The minimum limit is two-third 20dB bandwidth.

**CH 0**









BUREAU VERITAS

Test Report No.: 170301N002

CH 39



CH 78






## 4.6. MAXIMUM OUTPUT POWER

### 4.6.1. LIMITS OF MAXIMUM OUTPUT POWER MEASUREMENT

The Maximum Output Power Measurement is 125mW.

### 4.6.2. TEST SETUP



### 4.6.3. TEST INSTRUMENTS

Refer to section 4.3.3 to get information of above instrument.

### 4.6.4. TEST PROCEDURES

A peak power sensor was used on the output port of the EUT. A peak power meter was used to read the response of the peak power sensor. Record the peak power level.

### 4.6.5. DEVIATION FROM TEST STANDARD

No deviation.

### 4.6.6. EUT OPERATING CONDITION

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.



### 4.6.7. TEST RESULTS

#### MAXIMUM PEAK OUTPUT POWER

##### GFSK

CHANNEL	CHANNEL FREQUENCY (MHz)	PK POWER (dBm)	PK POWER (mW)	PK POWER LIMIT (mW)	PASS/FAIL
0	2402	-0.01	0.9977	125	PASS
39	2441	<b>0.82</b>	<b>1.2080</b>	125	PASS
78	2480	0.63	1.1560	125	PASS

##### 8DPSK

CHANNEL	CHANNEL FREQUENCY (MHz)	PK POWER (dBm)	PK POWER (mW)	PK POWER LIMIT (mW)	PASS/FAIL
0	2402	-2.36	0.5808	125	PASS
39	2441	-1.77	0.6653	125	PASS
78	2480	-1.92	0.6427	125	PASS

#### AVERAGE OUTPUT POWER (FOR REFERENCE)

##### GFSK

CHANNEL	CHANNEL FREQUENCY (MHz)	AVERAGE POWER (dBm)	AVERAGE POWER (mW)
0	2402	-1.28	0.745
39	2441	<b>-0.42</b>	<b>0.908</b>
78	2480	-0.61	0.869

##### 8DPSK

CHANNEL	CHANNEL FREQUENCY (MHz)	AVERAGE POWER (dBm)	AVERAGE POWER (mW)
0	2402	-3.89	0.408
39	2441	-2.36	0.581
78	2480	-2.55	0.556



## 4.7. OUT OF BAND EMISSION MEASUREMENT

### 4.7.1. LIMITS OF out of band EMISSION MEASUREMENT

Below -20dB of the highest emission level of operating band (in 100KHz RBW).

### 4.7.2. TEST INSTRUMENTS

Refer to section 4.3.3 to get information of above instrument.

### 4.7.3. TEST PROCEDURE

The transmitter output was connected to the spectrum analyzer via a low loss cable. of Spectrum Analyzer was set RBW to 100 kHz and VBW to 300 kHz with suitable frequency span including 100 MHz bandwidth from band edge. Detector = PEAK and Trace mode = Max Hold. The band edges was measured and recorded.

### 4.7.4. DEVIATION FROM TEST STANDARD

No deviation.

### 4.7.5. EUT OPERATING CONDITION

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.

### 4.7.6. TEST RESULTS


The spectrum plots are attached on the following images. D1 line indicates the highest level. D2 line indicates the 20dB offset below D1. It shows compliance to the requirement.



BUREAU VERITAS

Test Report No.: 170301N002

### GFSK






BUREAU VERITAS

Test Report No.: 170301N002

### 8DPSK





**BUREAU  
VERITAS**

Test Report No.: 170301N002

## 5. PHOTOGRAPHS OF THE TEST CONFIGURATION

Please refer to the attached file (Test Setup Photo).



**BUREAU  
VERITAS**

Test Report No.: 170301N002

## **6. APPENDIX A - MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB**

No any modifications are made to the EUT by the lab during the test.

**---END---**