

FCC TEST REPORT

(PART 22)

Product: LTE phone
Model No.: XP5700
FCC ID: WYPL23V013AA
Applicant: Sonim Technologies, Inc.
Address: 1825 S. Grant St., Suite 200., San Mateo, CA, 94402
Manufacturer: Sonim Technologies (Shenzhen) Limited
Address: 2nd Floor, No. 2 Building Phase B, Daqian Industrial park,
Longchang Road, 67 District, Baoan, Shenzhen, P. R. China
Prepared by: Bureau Veritas Shenzhen Co., Ltd. Dongguan Branch
Lab Location: No. 34, Chenwulu Section, Guantai Rd., Houjie Town,
Dongguan City, Guangdong 523942, China
TEL: +86 769 8593 5656
FAX: +86 769 8593 1080
E-MAIL: customerservice.dg@cn.bureauveritas.com
Report No.: RF160524W004-3
Received Date: May 24, 2016
Test Date: May 25, 2016 ~ Jun. 20, 2016
Issued Date: Jun. 22, 2016

This report should not be used by the client to claim product certification, approval, or endorsement by A2LA or any government agencies.

This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification.



TABLE OF CONTENTS

| | |
|----------------------------------------------------------------|-----------|
| RELEASE CONTROL RECORD | 4 |
| 1 CERTIFICATION | 5 |
| 2 SUMMARY OF TEST RESULTS | 6 |
| 2.1 MEASUREMENT UNCERTAINTY | 6 |
| 2.2 TEST SITE AND INSTRUMENTS | 7 |
| 3 GENERAL INFORMATION | 8 |
| 3.1 GENERAL DESCRIPTION OF EUT | 8 |
| 3.2 CONFIGURATION OF SYSTEM UNDER TEST | 9 |
| 3.3 DESCRIPTION OF SUPPORT UNITS | 10 |
| 3.4 TEST ITEM AND TEST CONFIGURATION | 10 |
| 3.5 EUT OPERATING CONDITIONS | 12 |
| 3.6 GENERAL DESCRIPTION OF APPLIED STANDARDS | 12 |
| 4 TEST TYPES AND RESULTS | 13 |
| 4.1 OUTPUT POWER MEASUREMENT | 13 |
| 4.1.1 LIMITS OF OUTPUT POWER MEASUREMENT | 13 |
| 4.1.2 TEST PROCEDURES | 13 |
| 4.1.3 TEST SETUP | 14 |
| 4.1.4 TEST RESULTS | 15 |
| 4.2 FREQUENCY STABILITY MEASUREMENT | 16 |
| 4.2.1 LIMITS OF FREQUENCY STABILITY MEASUREMENT | 16 |
| 4.2.2 TEST PROCEDURE | 16 |
| 4.2.3 TEST SETUP | 16 |
| 4.2.4 TEST RESULTS | 17 |
| 4.3 OCCUPIED BANDWIDTH MEASUREMENT | 18 |
| 4.3.1 TEST PROCEDURES | 18 |
| 4.3.2 TEST SETUP | 18 |
| 4.3.3 TEST RESULTS | 19 |
| 4.4 BAND EDGE MEASUREMENT | 21 |
| 4.4.1 LIMITS OF BAND EDGE MEASUREMENT | 21 |
| 4.4.2 TEST SETUP | 21 |
| 4.4.3 TEST PROCEDURES | 21 |
| 4.4.4 TEST RESULTS | 22 |
| 4.5 CONDUCTED SPURIOUS EMISSIONS | 23 |
| 4.5.1 LIMITS OF CONDUCTED SPURIOUS EMISSIONS MEASUREMENT | 23 |
| 4.5.2 TEST PROCEDURE | 23 |
| 4.5.3 TEST SETUP | 23 |
| 4.5.4 TEST RESULTS | 24 |
| 4.6 RADIATED EMISSION MEASUREMENT | 27 |



Test Report No.: RF160524W004-3

| | | |
|----------|-------------------------------------------------------------------------------------------|-----------|
| 4.6.1 | LIMITS OF RADIATED EMISSION MEASUREMENT | 27 |
| 4.6.2 | TEST PROCEDURES | 27 |
| 4.6.3 | DEVIATION FROM TEST STANDARD | 27 |
| 4.6.4 | TEST SETUP | 28 |
| 4.6.5 | TEST RESULTS | 29 |
| 4.7 | PEAK TO AVERAGE RATIO..... | 37 |
| 4.7.1 | LIMITS OF PEAK TO AVERAGE RATIO MEASUREMENT..... | 37 |
| 4.7.2 | TEST SETUP..... | 37 |
| 4.7.3 | TEST PROCEDURES | 37 |
| 4.7.4 | TEST RESULTS | 38 |
| 5 | PHOTOGRAPHS OF THE TEST CONFIGURATION..... | 41 |
| 6 | INFORMATION ON THE TESTING LABORATORIES | 42 |
| 7 | APPENDIX A – MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB | 43 |



Test Report No.: RF160524W004-3

RELEASE CONTROL RECORD

| ISSUE NO. | REASON FOR CHANGE | DATE ISSUED |
|----------------|-------------------|---------------|
| RF160524W004-3 | Original release | Jun. 22, 2016 |




Test Report No.: RF160524W004-3

1 CERTIFICATION

PRODUCT: LTE phone
BRAND NAME: Sonim
MODEL NAME: XP5700
APPLICANT: Sonim Technologies, Inc.
TESTED: May 25, 2016 ~ Jun. 20, 2016
TEST SAMPLE: Identical Prototype
TEST STANDARDS: **FCC PART 22, Subpart H**
ANSI/TIA/EIA-603-D

The above equipment has been tested by **Bureau Veritas Shenzhen Co., Ltd. Dongguan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

PREPARED BY :  , **DATE:** Jun. 22, 2016
(Amyee Qian / Engineer)

APPROVED BY :  , **DATE:** Jun. 22, 2016
(William Chung / Manager)

2 SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

| APPLIED STANDARD: FCC Part 22 & Part 2 | | | |
|----------------------------------------|------------------------------|--------|--------------------------------------------------------------------------------------|
| STANDARD SECTION | 1.1.1.1.1 TEST TYPE | RESULT | REMARK |
| 2.1046 22.913 (a) | Effective Radiated Power | PASS | Meet the requirement of limit. |
| 2.1055 22.355 | Frequency Stability | PASS | Meet the requirement of limit. |
| 2.1049 22.917b | Occupied Bandwidth | PASS | Meet the requirement of limit. |
| -- | Peak to average ratio* | PASS | Meet the requirement of limit. |
| 22.917 | Band Edge Measurements | PASS | Meet the requirement of limit. |
| 2.1051 22.917 | Conducted Spurious Emissions | PASS | Meet the requirement of limit. |
| 2.1053 22.917 | Radiated Spurious Emissions | PASS | Meet the requirement of limit. Minimum passing margin is -21.40dB at 37.76MHz. |

* Refer to KDB 971168 D01 Power Meas License Digital Systems v02r02.

2.1 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

| MEASUREMENT | FREQUENCY | UNCERTAINTY |
|---------------------|---------------|-------------|
| Conducted emissions | 9kHz~30MHz | 2.66dB |
| Radiated emissions | 9KHz ~ 30MHz | 2.74dB |
| | 30MHz ~ 1GHz | 3.55dB |
| | 1GHz ~ 18GHz | 4.84dB |
| | 18GHz ~ 40GHz | 1.94dB |

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

2.2 TEST SITE AND INSTRUMENTS

| Equipment | Manufacturer | Model No. | Serial No. | Last Cal. | Next Cal. |
|----------------------------------|-----------------|--------------------------|-------------|-------------|-------------|
| EMI Test Receiver | Rohde&Schwarz | ESR7 | 101494 | Apr. 05,16 | Apr. 04,17 |
| Signal and Spectrum Analyzer | Rohde&Schwarz | FSV40 | 101094 | Apr. 05,16 | Apr. 04,17 |
| Bilog Antenna 1 | Teseq | CBL 6111D | 30643 | Jun. 25,15 | Jun. 24,16 |
| Bilog Antenna 2 | Teseq | CBL 6111D | 27089 | Jun. 25,15 | Jun. 24,16 |
| Horn Antenna | ETS-Lindgren | 3117 | 00062558 | May 30,14 | May 29,17 |
| Horn Antenna (15GHz-40GHz) | SCHWARZBECK | BBHA 9170 | BBHA9170147 | Jan. 21,14 | Jan. 20,17 |
| Amplifier | Burgeon | BPA-530 | 100220 | Apr. 05,16 | Apr. 04,17 |
| Pre-Amplifier | HP | 8449B | 3008A00409 | Apr. 25,15 | Apr. 24,17 |
| Pre-Amplifier (18GHz-40GHz) | EMCI | EMC 184045 | 980102 | Nov. 11,15 | Nov. 10,16 |
| GPS Generator+ Antenna | TOJOIN | GNSS-5000A | E1-010119 | Aug. 08, 14 | Aug. 07, 16 |
| 3m Semi-anechoic Chamber | ETS-LINDGREN | 9m*6m*6m | NSEMC003 | Mar. 12,16 | Mar. 11,18 |
| Test Software | ADT | ADT_Radiated_V7.6.15.9.2 | N/A | N/A | N/A |
| Power Meter | Anritsu | ML2495A | 1139001 | Feb.19,16 | Feb. 18,17 |
| Power Sensor | Anritsu | MA2411B | 1126068 | Feb.19,16 | Feb. 18,17 |
| Power Sensor | Keysight | U2021XA | MY55060016 | May 27,15 | May 25,17 |
| Power Sensor | Keysight | U2021XA | MY55060018 | May 27,15 | May 24,17 |
| Digital Multimeter | FLUKE | 15B | A1220010DG | Oct. 12, 15 | Oct.11, 16 |
| Humid & Temp Programmable Tester | Haida | HD-2257 | 110807201 | Sep.07,15 | Sep. 06,16 |
| Oscilloscope | Agilent | DSO9254A | MY51260160 | Nov. 09,15 | Nov. 08,16 |
| Signal Analyzer | Rohde & Schwarz | FSV7 | 102331 | Nov. 09,15 | Nov. 08,16 |
| Signal Generator | Agilent | N5183A | MY50140980 | Apr. 22, 15 | Apr. 21, 17 |
| ESG Vector Signal Generator | Agilent | E4438C | MY49072505 | Sep. 01,15 | Aug. 31,16 |
| BLUETOOTH TESTER | Rohde&Schwarz | CBT32 | 100811 | Oct. 12, 15 | Oct.11, 16 |

- NOTE:**
1. The calibration interval of the above test instruments is 12 months or 24 months and the calibrations are traceable to CEPREI/CHINA, GRGT/CHINA and NIM/CHINA.
 2. The test was performed in Dongguan 966 Chamber.
 3. The horn antenna are used only for the measurement of emission frequency above 1GHz if tested.
 4. The FCC Site Registration No. is 502831.

3 GENERAL INFORMATION

3.1 GENERAL DESCRIPTION OF EUT

| | | |
|----------------------------|---------------------------------------------------------------------------------------|----------------------|
| EUT | LTE phone | |
| MODEL NAME | XP5700 | |
| TYPE NUMBER | L23V013AA | |
| POWER SUPPLY | 5.0Vdc (adapter or host equipment) 3.7Vdc (Li-ion, battery) | |
| MODULATION TYPE | CDMA BC 0 | GMSK |
| FREQUENCY RANGE | CDMA BC 0 | 824.7MHz ~ 848.31MHz |
| MAX. ERP POWER | CDMA BC 0 | 132mW |
| EMISSION DESIGNATOR | CDMA BC 0 | 1M27F9W |
| HW VERSION | A | |
| SW VERSION | 5A.0.0-00-5.1.1-15.17.0 | |
| ANTENNA TYPE | Fixed Internal Antenna with 2dBi gain | |
| I/O PORTS | Refer to user's manual | |
| DATA CABLE | USB cable: shielded, detachable, 1.1m Earphone Cable: Unshielded, Detachable, 1.2m | |

NOTE:

- For a more detailed features description, please refer to the manufacturer's specifications or the user's manual.
- The EUT was powered by the following adapter:

| ADAPTER | |
|----------------|--------------------|
| BRAND: | Sonim |
| MODEL: | S14C02 |
| INPUT: | AC 100-240V, 200mA |
| OUTPUT: | DC 5V, 1200mA |

- The EUT matched the following USB cable and Earphone:


| USB CABLE | |
|---------------------|-----------|
| BRAND: | Sunway |
| MODEL: | N.A |
| SIGNAL LINE: | 1.1 METER |

| EARPHONE | |
|---------------------|------------|
| BRAND: | Minami |
| MODEL: | ME-816B5-E |
| SIGNAL LINE: | 1.2 METER |


- For the test results, the EUT had been tested with all conditions. But only the worst case was shown in test report.

3.2 CONFIGURATION OF SYSTEM UNDER TEST

FOR RADIATION EMISSION TEST



FOR E.R.P. TEST



3.3 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

| NO. | PRODUCT | BRAND | MODEL NO. | SERIAL NO. | FCC ID |
|-----|-----------|----------|-----------|------------|--------|
| 1 | DC source | LONG WEI | PS-6403D | 010934269 | N/A |
| 2 | PC | HP | A6608CN | 3CR83825X3 | N/A |

| NO. | SIGNAL CABLE DESCRIPTION OF THE ABOVE SUPPORT UNITS |
|-----|-----------------------------------------------------|
| 1 | DC Line: Unshielded, Detachable 1.0m |
| 2 | AC Line: Unshielded, Detachable 1.5m |

NOTE:

1. All power cords of the above support units are non shielded (1.8m).

3.4 TEST ITEM AND TEST CONFIGURATION

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates, XYZ axis and antenna ports. The worst case in ERP and radiated emission was found when positioned on X-plane for CDMA and Z-plane for LTE. Following channel(s) was (were) selected for the final test as listed below:

| EUT CONFIGURE MODE | DESCRIPTION |
|--------------------|-----------------------------------------------------|
| A | EUT + Adapter + Earphone + USB Cable with CDMA BC 0 |
| B | EUT + Battery + Earphone + USB Cable with CDMA BC 0 |

CDMA BC 0 MODE

| EUT CONFIGURE MODE | TEST ITEM | AVAILABLE CHANNEL | TESTED CHANNEL | MODE |
|--------------------|---------------------|-------------------|----------------|-----------|
| B | ERP | 1013 to 777 | 1013, 384, 777 | CDMA BC 0 |
| B | FREQUENCY STABILITY | 1013 to 777 | 384 | CDMA BC 0 |
| B | OCCUPIED BANDWIDTH | 1013 to 777 | 1013, 384, 777 | CDMA BC 0 |
| B | BAND EDGE | 1013 to 777 | 1013, 777 | CDMA BC 0 |
| B | CONDUCTED EMISSION | 1013 to 777 | 1013, 384, 777 | CDMA BC 0 |
| A | RADIATED EMISSION | 1013 to 777 | 1013, 384, 777 | CDMA BC 0 |



**BUREAU
VERITAS**

Test Report No.: RF160524W004-3

TEST CONDITION:

| TEST ITEM | ENVIRONMENTAL CONDITIONS | INPUT POWER | TESTED BY |
|----------------------|--------------------------|----------------------|-------------|
| ERP | 23deg. C, 62%RH | DC 5.0V from adaptor | Yuqiang Yin |
| FREQUENCY STABILITY | 23deg. C, 62%RH | 3.7Vdc from Battery | Yuqiang Yin |
| OCCUPIED BANDWIDTH | 23deg. C, 62%RH | 3.7Vdc from Battery | Yuqiang Yin |
| BAND EDGE | 23deg. C, 62%RH | 3.7Vdc from Battery | Yuqiang Yin |
| CONDCUDETED EMISSION | 23deg. C, 62%RH | 3.7Vdc from Battery | Yuqiang Yin |
| RADIATED EMISSION | 25deg. C, 63.6%RH | DC 5.0V from adaptor | Alex Chen |



Test Report No.: RF160524W004-3

3.5 EUT OPERATING CONDITIONS

The EUT makes a call to the communication simulator. The communication simulator station system controlled a EUT to export maximum output power under transmission mode and specific channel frequency

3.6 GENERAL DESCRIPTION OF APPLIED STANDARDS

The EUT is a RF product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

FCC 47 CFR Part 2

FCC 47 CFR Part 22

KDB 971168 D01 Power Meas License Digital Systems v02r02

ANSI/TIA/EIA-603-D

NOTE: All test items have been performed and recorded as per the above standards.



4 TEST TYPES AND RESULTS

4.1 OUTPUT POWER MEASUREMENT

4.1.1 LIMITS OF OUTPUT POWER MEASUREMENT

Mobile / Portable station are limited to 7 watts e.r.p.

4.1.2 TEST PROCEDURES

EIRP / ERP MEASUREMENT:


- a. All measurements were done at low, middle and high operational frequency range. RBW and VBW is 1MHz for CDMA.
- b. Substitution method is used for E.I.R.P measurement. In the semi-anechoic chamber, EUT placed on the 0.8m height of Turn Table, rotated the table around 360 degrees to search the maximum radiation power and receiver antenna shall be rotated vertical and horizontal polarization and moved height from 1m to 4m to find the maximum polar radiated power. The “Read Value” is the spectrum reading the maximum power value.
- c. The substitution horn antenna is substituted for EUT at the same position and signals generator export the CW signal to the substitution antenna via a tx cable. Rotated the Turn Table and moved receiving antenna to find the maximum radiation power. Adjust output power level of S.G to get a Value of spectrum reading equal to “Read Value” of step b. Record the power level of S.G
- d. $EIRP = \text{Output power level of S.G} - \text{TX cable loss} + \text{Antenna gain of substitution horn.}$
 $E.R.P \text{ power can be calculated form E.I.R.P power by subtracting the gain of dipole, } E.R.P \text{ power} = E.I.P.R \text{ power} - 2.15\text{dBi.}$

CONDUCTED POWER MEASUREMENT:

The EUT was set up for the maximum power with CDMA link data modulation and link up with simulator. Set the EUT to transmit under low, middle and high channel and record the power level shown on simulator.

4.1.3 TEST SETUP

EIRP / ERP MEASUREMENT:



For the actual test configuration, please refer to the attached file (Test Setup Photo).

CONDUCTED POWER MEASUREMENT:



For the actual test configuration, please refer to the attached file (Test Setup Photo).

4.1.4 TEST RESULTS

CONDUCTED OUTPUT POWER (dBm)

| Band | CDMA2000 BC0 | | |
|------------------|--------------|--------|--------|
| | 1013 | 384 | 777 |
| Channel | 824.7 | 836.52 | 848.31 |
| Frequency (MHz) | 824.7 | 836.52 | 848.31 |
| RC1+SO55 | 24.24 | 24.25 | 24.22 |
| RC3+SO55 | 24.37 | 24.31 | 24.36 |
| RC3+SO32(FCH) | 24.23 | 24.19 | 24.29 |
| RC3+SO32(SCH) | 24.22 | 24.17 | 24.28 |
| RC1+SO3,1/8 Rate | 24.31 | 24.29 | 24.36 |
| RTAP 153.6 | 24.23 | 24.26 | 24.28 |
| RETAP 4096 | 24.28 | 24.25 | 24.21 |

ERP POWER (dBm)

CDMA BC 0

| Channel | Frequency (MHz) | LVL (dBm) | Correction Factor(dB) | ERP(dBm) | ERP(mW) | Polarization (H/V) |
|---------|-----------------|-----------|-----------------------|----------|---------------|--------------------|
| 1013 | 824.7 | -10.21 | 33.56 | 21.20 | 131.80 | H |
| 384 | 836.5 | -10.48 | 33.63 | 21.00 | 125.86 | H |
| 777 | 848.3 | -10.84 | 33.57 | 20.58 | 114.24 | H |
| 1013 | 824.7 | -17.28 | 34.24 | 14.81 | 30.24 | V |
| 384 | 836.5 | -18.57 | 34.59 | 13.87 | 24.36 | V |
| 777 | 848.3 | -18.97 | 34.62 | 13.50 | 22.40 | V |

4.2 FREQUENCY STABILITY MEASUREMENT

4.2.1 LIMITS OF FREQUENCY STABILITY MEASUREMENT


1.5 ppm is for base and fixed station. 2.5 ppm is for mobile station.

4.2.2 TEST PROCEDURE

- Device is placed at the oven room. The oven room could control the temperatures and humidity. Power warm up is at least 15 min and power applied should perform before recording frequency error.
- EUT is connected the external power supply to control the DC input power. The test voltage range is from minimum to maximum working voltage. Each step shall be record the frequency error rate.
- The temperature range step is 10 degrees in this test items. All temperature levels shall be hold the $\pm 0.5^{\circ}\text{C}$ during the measurement testing. The each temperature step shall be at least 0.5 hours, consider the EUT could be test under the stability condition.

NOTE: The frequency error was recorded frequency error from the communication simulator.

4.2.3 TEST SETUP





4.2.4 TEST RESULTS

FREQUENCY ERROR VS. VOLTAGE

| VOLTAGE (Volts) | FREQUENCY ERROR (ppm) | LIMIT (ppm) |
|-----------------|-----------------------|-------------|
| | CDMA BC 0 | |
| 3.7 | 0.0025 | 2.5 |
| 3.5 | 0.0023 | 2.5 |
| 4.2 | 0.0028 | 2.5 |

NOTE: The applicant defined the normal working voltage of the battery is from 3.5Vdc to 4.2Vdc.

FREQUENCY ERROR vs. TEMPERATURE.


| TEMP. (°C) | FREQUENCY ERROR (ppm) | LIMIT (ppm) |
|------------|-----------------------|-------------|
| | CDMA BC 0 | |
| -30 | 0.0106 | 2.5 |
| -20 | 0.0106 | 2.5 |
| -10 | 0.0047 | 2.5 |
| 0 | 0.0059 | 2.5 |
| 10 | 0.0094 | 2.5 |
| 20 | 0.0071 | 2.5 |
| 30 | 0.0047 | 2.5 |
| 40 | 0.0035 | 2.5 |
| 50 | 0.0082 | 2.5 |
| 60 | 0.0129 | 2.5 |

4.3 OCCUPIED BANDWIDTH MEASUREMENT

4.3.1 TEST PROCEDURES

The EUT makes a call to the communication simulator. All measurements were done at low, middle and high operational frequency range. The communication simulator station system controlled a EUT to export maximum output power under transmission mode and specific channel frequency. Use OBW measurement function of Spectrum analyzer to measure 99 % occupied bandwidth.


4.3.2 TEST SETUP



4.3.3 TEST RESULTS

CDMA BC 0


| CHANNEL | Frequency (MHz) | 99% OCCUPIED Bandwidth (MHz) |
|---------|-----------------|------------------------------|
| 1013 | 824.70 | 1.27 |
| 384 | 836.52 | 1.27 |
| 777 | 848.31 | 1.27 |





Test Report No.: RF160524W004-3

| CHANNEL | Frequency (MHz) | 26dB Bandwidth (MHz) |
|---------|-----------------|----------------------|
| 1013 | 824.70 | 1.42 |
| 384 | 836.52 | 1.42 |
| 777 | 848.31 | 1.41 |



Bureau Veritas Shenzhen Co., Ltd.
Dongguan Branch

No. 34, Chenwulu Section, Guantai Rd.,
Houjie Town, Dongguan City,
Guangdong 523942, China


Tel: +86 769 8593 5656
Fax: +86 769 8593 1080
Email: customerservice.dg@cn.bureauveritas.com

4.4 BAND EDGE MEASUREMENT

4.4.1 LIMITS OF BAND EDGE MEASUREMENT

Power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB. In the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed.

4.4.2 TEST SETUP




4.4.3 TEST PROCEDURES

- All measurements were done at low and high operational frequency range.
- The center frequency of spectrum is the band edge frequency and span is 3MHz. RBW of the spectrum is 15kHz and VBW of the spectrum is 15kHz (CDMA BC 0).
- Record the max trace plot into the test report.



4.4.4 TEST RESULTS



4.5 CONDUCTED SPURIOUS EMISSIONS


4.5.1 LIMITS OF CONDUCTED SPURIOUS EMISSIONS MEASUREMENT

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB. The emission limit equal to -13dBm .

4.5.2 TEST PROCEDURE

- a. The EUT makes a phone call to the communication simulator. All measurements were done at low, middle and high operational frequency range.
- b. Measuring frequency range is from 9 kHz to 9GHz. 20dB attenuation pad is connected with spectrum. RBW=1MHz and VBW=3MHz is used for conducted emission measurement.

4.5.3 TEST SETUP






BUREAU VERITAS

Test Report No.: RF160524W004-3

4.5.4 TEST RESULTS




Bureau Veritas Shenzhen Co., Ltd.
Dongguan Branch

No. 34, Chenwulu Section, Guantai Rd.,
Houjie Town, Dongguan City,
Guangdong 523942, China

Tel: +86 769 8593 5656
Fax: +86 769 8593 1080
Email: customerservice.dg@cn.bureauveritas.com



Test Report No.: RF160524W004-3



Bureau Veritas Shenzhen Co., Ltd.
 Dongguan Branch


No. 34, Chenwulu Section, Guantai Rd.,
 Houjie Town, Dongguan City,
 Guangdong 523942, China

Tel: +86 769 8593 5656
 Fax: +86 769 8593 1080
 Email: customerservice.dg@cn.bureauveritas.com



BUREAU VERITAS

Test Report No.: RF160524W004-3



Bureau Veritas Shenzhen Co., Ltd.
Dongguan Branch

No. 34, Chenwulu Section, Guantai Rd.,
Houjie Town, Dongguan City,
Guangdong 523942, China

Tel: +86 769 8593 5656
Fax: +86 769 8593 1080
Email: customerservice.dg@cn.bureauveritas.com



4.6 RADIATED EMISSION MEASUREMENT

4.6.1 LIMITS OF RADIATED EMISSION MEASUREMENT

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB. The emission limit equal to -13dBm .

4.6.2 TEST PROCEDURES


- a. Substitution method is used for E.I.R.P measurement. In the semi-anechoic chamber, EUT placed on the 0.8m height of Turn Table, rotated the table around 360 degrees to search the maximum radiation power and receiver antenna shall be rotated vertical and horizontal polarization and moved height from 1m to 4m to find the maximum polar radiated power. The “Read Value” is the spectrum reading the maximum power value.
- b. The substitution horn antenna is substituted for EUT at the same position and signals generator export the CW signal to the substitution antenna via a TX cable. Rotated the Turn Table and moved receiving antenna to find the maximum radiation power. Adjust output power level of S.G to get a Value of spectrum reading equal to “Read Value” of step a. Record the power level of S.G
- c. $\text{EIRP} = \text{Output power level of S.G} - \text{TX cable loss} + \text{Antenna gain of substitution horn}$.
- d. E.R.P power can be calculated form E.I.R.P power by subtracting the gain of dipole,
 $\text{E.R.P power} = \text{E.I.P.R power} - 2.15\text{dBi}$.

NOTE: The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 1MHz/3MHz.

4.6.3 DEVIATION FROM TEST STANDARD

No deviation

4.6.4 TEST SETUP



For the actual test configuration, please refer to the attached file (Test Setup Photo).


4.6.5 TEST RESULTS

BELOW 1GHz WORST-CASE DATA

CDMA2000 BC0:

| | | | |
|----------------------------------------------------------------|-----------------|------------------------|----------------------|
| MODE | TX channel 384 | FREQUENCY RANGE | Below 1000MHz |
| ENVIRONMENTAL CONDITIONS | 26deg. C, 56%RH | INPUT POWER | DC 5.0V from adapter |
| TESTED BY | Alex Chen | | |
| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M | | | |

| | Freq | Level | Read Level | Limit Line | Over Limit | Factor | Remark | Pol/Phase |
|------|---------|--------|------------|------------|------------|--------|--------|------------|
| | MHz | dBm/m | dBm | dBm/m | dB | dB/m | | |
| 1 PP | 37.760 | -34.50 | -46.74 | -13.00 | -21.50 | 12.24 | Peak | Horizontal |
| 2 | 88.200 | -43.42 | -34.62 | -13.00 | -30.42 | -8.80 | Peak | Horizontal |
| 3 | 207.510 | -62.85 | -45.76 | -13.00 | -49.85 | -17.09 | Peak | Horizontal |
| 4 | 310.330 | -69.77 | -56.31 | -13.00 | -56.77 | -13.46 | Peak | Horizontal |
| 5 | 475.230 | -73.23 | -62.83 | -13.00 | -60.23 | -10.40 | Peak | Horizontal |
| 6 | 836.070 | -61.67 | -57.80 | -13.00 | -48.67 | -3.87 | Peak | Horizontal |






Test Report No.: RF160524W004-3

| | | | |
|--------------------------------------------------------------|-----------------|------------------------|----------------------|
| MODE | TX channel 384 | FREQUENCY RANGE | Below 1000MHz |
| ENVIRONMENTAL CONDITIONS | 26deg. C, 56%RH | INPUT POWER | DC 5.0V from adapter |
| TESTED BY | Alex Chen | | |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M | | | |

| | Freq | Level | Read Level | Limit Line | Over Limit | Factor | Remark | Pol/Phase | |
|---|------|---------|------------|------------|------------|--------|--------|-----------|----------|
| | MHz | dBm/m | dBm | dBm/m | dB | dB/m | | | |
| 1 | PP | 37.760 | -34.40 | -33.10 | -13.00 | -21.40 | -1.30 | Peak | Vertical |
| 2 | | 85.290 | -45.17 | -34.77 | -13.00 | -32.17 | -10.40 | Peak | Vertical |
| 3 | | 181.320 | -63.41 | -50.41 | -13.00 | -50.41 | -13.00 | Peak | Vertical |
| 4 | | 441.280 | -68.47 | -59.06 | -13.00 | -55.47 | -9.41 | Peak | Vertical |
| 5 | | 837.040 | -62.62 | -58.40 | -13.00 | -49.62 | -4.22 | Peak | Vertical |






Test Report No.: RF160524W004-3

ABOVE 1GHz DATA

CDMA2000 BC0

| | | | |
|----------------------------------------------------------------|-----------------|------------------------|----------------------|
| MODE | TX channel 1013 | FREQUENCY RANGE | Above 1000MHz |
| ENVIRONMENTAL CONDITIONS | 26deg. C, 56%RH | INPUT POWER | DC 5.0V from adapter |
| TESTED BY | Alex Chen | | |
| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M | | | |

| | Freq | Level | Read Level | Limit Line | Over Limit | Factor | Remark | Pol/Phase |
|---|-------------|--------|------------|------------|------------|--------|--------|------------|
| | MHz | dBm/m | dBm | dBm/m | dB | dB/m | | |
| 1 | 1649.000 | -55.69 | -50.73 | -13.00 | -42.69 | -4.96 | Peak | Horizontal |
| 2 | PP 2474.000 | -44.33 | -42.67 | -13.00 | -31.33 | -1.66 | Peak | Horizontal |






Test Report No.: RF160524W004-3

| | | | |
|--------------------------------------------------------------|-----------------|------------------------|----------------------|
| MODE | TX channel 1013 | FREQUENCY RANGE | Above 1000MHz |
| ENVIRONMENTAL CONDITIONS | 26deg. C, 56%RH | INPUT POWER | DC 5.0V from adapter |
| TESTED BY | Alex Chen | | |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M | | | |

| | Freq | Level | Read Level | Limit Line | Over Limit | Factor | Remark | Pol/Phase |
|------|----------|--------|------------|------------|------------|--------|--------|-----------|
| | MHz | dBm/m | dBm | dBm/m | dB | dB/m | | |
| 1 | 1649.000 | -52.56 | -49.02 | -13.00 | -39.56 | -3.54 | Peak | Vertical |
| 2 PP | 2474.000 | -50.14 | -49.97 | -13.00 | -37.14 | -0.17 | Peak | Vertical |






Test Report No.: RF160524W004-3

| | | | |
|----------------------------------------------------------------|-----------------|------------------------|----------------------|
| MODE | TX channel 384 | FREQUENCY RANGE | Above 1000MHz |
| ENVIRONMENTAL CONDITIONS | 26deg. C, 56%RH | INPUT POWER | DC 5.0V from adapter |
| TESTED BY | Alex Chen | | |
| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M | | | |

| | Freq | Level | Read Level | Limit Line | Over Limit | Factor | Remark | Pol/Phase |
|---|-------------|--------|------------|------------|------------|--------|--------|------------|
| | MHz | dBm/m | dBm | dBm/m | dB | dB/m | | |
| 1 | PP 1666.000 | -53.19 | -48.37 | -13.00 | -40.19 | -4.82 | Peak | Horizontal |
| 2 | 2512.000 | -56.08 | -54.49 | -13.00 | -43.08 | -1.59 | Peak | Horizontal |






Test Report No.: RF160524W004-3

| | | | |
|--------------------------------------------------------------|-----------------|------------------------|----------------------|
| MODE | TX channel 384 | FREQUENCY RANGE | Above 1000MHz |
| ENVIRONMENTAL CONDITIONS | 26deg. C, 56%RH | INPUT POWER | DC 5.0V from adapter |
| TESTED BY | Alex Chen | | |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M | | | |

| | Freq | Level | Read Level | Limit Line | Over Limit | Factor | Remark | Pol/Phase |
|---|-------------|--------|------------|------------|------------|--------|--------|-----------|
| | MHz | dBm/m | dBm | dBm/m | dB | dB/m | | |
| 1 | PP 1666.000 | -53.73 | -50.35 | -13.00 | -40.73 | -3.38 | Peak | Vertical |
| 2 | 2512.000 | -54.82 | -54.70 | -13.00 | -41.82 | -0.12 | Peak | Vertical |






Test Report No.: RF160524W004-3

| | | | |
|----------------------------------------------------------------|-----------------|------------------------|----------------------|
| MODE | TX channel 777 | FREQUENCY RANGE | Above 1000MHz |
| ENVIRONMENTAL CONDITIONS | 26deg. C, 56%RH | INPUT POWER | DC 5.0V from adapter |
| TESTED BY | Alex Chen | | |
| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M | | | |

| | Freq | Level | Read Level | Limit Line | Over Limit | Factor | Remark | Pol/Phase |
|---|-------------|--------|------------|------------|------------|--------|--------|------------|
| | MHz | dBm/m | dBm | dBm/m | dB | dB/m | | |
| 1 | 1696.000 | -56.82 | -52.25 | -13.00 | -43.82 | -4.57 | Peak | Horizontal |
| 2 | PP 2545.000 | -44.97 | -43.50 | -13.00 | -31.97 | -1.47 | Peak | Horizontal |



Bureau Veritas Shenzhen Co., Ltd.
Dongguan Branch

No. 34, Chenwulu Section, Guantai Rd.,
Houjie Town, Dongguan City,
Guangdong 523942, China


Tel: +86 769 8593 5656
Fax: +86 769 8593 1080
Email: customerservice.dg@cn.bureauveritas.com



Test Report No.: RF160524W004-3

| | | | |
|--------------------------------------------------------------|-----------------|------------------------|----------------------|
| MODE | TX channel 777 | FREQUENCY RANGE | Above 1000MHz |
| ENVIRONMENTAL CONDITIONS | 26deg. C, 56%RH | INPUT POWER | DC 5.0V from adapter |
| TESTED BY | Alex Chen | | |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M | | | |

| | Freq | Level | Read Level | Limit Line | Over Limit | Factor | Remark | Pol/Phase |
|------|----------|--------|------------|------------|------------|--------|--------|-----------|
| | MHz | dBm/m | dBm | dBm/m | dB | dB/m | | |
| 1 | 1696.000 | -53.46 | -50.36 | -13.00 | -40.46 | -3.10 | Peak | Vertical |
| 2 PP | 2545.000 | -51.85 | -51.87 | -13.00 | -38.85 | 0.02 | Peak | Vertical |




4.7 PEAK TO AVERAGE RATIO

4.7.1 LIMITS OF PEAK TO AVERAGE RATIO MEASUREMENT

In measuring transmissions in this band using an average power technique, the peak to-average ratio (PAR) of the transmission may not exceed 13 dB

4.7.2 TEST SETUP



4.7.3 TEST PROCEDURES


1. Set resolution/measurement bandwidth \geq signal's occupied bandwidth;
2. Set the number of counts to a value that stabilizes the measured CCDF curve;
3. Record the maximum PAPR level associated with a probability of 0.1%.



4.7.4 TEST RESULTS

CDMA BC 0

| CHANNEL | FREQUENCY (MHz) | PEAK TO AVERAGE RATIO (dB) |
|---------|-----------------|----------------------------|
| 1013 | 824.70 | 4.10 |






Test Report No.: RF160524W004-3

CDMA BC 0

| CHANNEL | FREQUENCY (MHz) | PEAK TO AVERAGE RATIO (dB) |
|---------|-----------------|----------------------------|
| 384 | 836.52 | 4.86 |






Test Report No.: RF160524W004-3

CDMA BC 0

| CHANNEL | FREQUENCY (MHz) | PEAK TO AVERAGE RATIO (dB) |
|---------|-----------------|----------------------------|
| 777 | 848.31 | 4.39 |





Test Report No.: RF160524W004-3

5 PHOTOGRAPHS OF THE TEST CONFIGURATION

Please refer to the attached file (Test Setup Photo).



Test Report No.: RF160524W004-3

6 INFORMATION ON THE TESTING LABORATORIES

We, Bureau Veritas Shenzhen Co., Ltd. Dongguan Branch, were founded in 2002 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are accredited and approved according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

Dongguan EMC/RF Lab:

Tel: +86-769-85935656

Fax: +86-769-85931080

Email: customerservice.dg@cn.bureauveritas.com

Web Site: www.adt.com.tw

The address and road map of all our labs can be found in our web site also.



Test Report No.: RF160524W004-3

7 APPENDIX A – MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB

No any modifications are made to the EUT by the lab during the test.

---END---