



# NFC TEST REPORT

No.I22Z60589-IOT07

for

**Sonim Technologies, Inc.**

**Smart phone**

**Model Name: XP9900(P14001),XP9900(P14002),XP9900(P14003),  
XP9900(P14004),XP9900(P14005),XP9900(P14006),XP9900(P14010)**

**FCC ID: WYPP14010**

with

**Hardware Version: V1.0**

**Software Version: 10.0.0-01-12.0.0-10.62.10**

**Issued Date: 2022-07-25**

**Note:**

The test results in this test report relate only to the devices specified in this report. This report shall not be reproduced except in full without the written approval of CTTL.

The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the U.S.Government.

**Test Laboratory:**

**CTTL-Telecommunication Technology Labs, CAICT**

No. 52, Huayuan North Road, Haidian District, Beijing, P. R. China 100191.

Tel:+86(0)10-62304633-2512, Fax:+86(0)10-62304633-2504

Email: [ctl\\_terminals@caict.ac.cn](mailto:ctl_terminals@caict.ac.cn), website: [www.caict.ac.cn](http://www.caict.ac.cn)



## **REPORT HISTORY**

<b>Report Number</b>	<b>Revision</b>	<b>Description</b>	<b>Issue Date</b>
I22Z60589-IOT07	Rev.0	1 <sup>st</sup> edition	2022-07-25

Note: the latest revision of the test report supersedes all previous version.



## **CONTENTS**

<b>1. TEST LABORATORY .....</b>	<b>4</b>
<b>1.1. INTRODUCTION &amp; ACCREDITATION.....</b>	<b>4</b>
<b>1.2. TESTING LOCATION .....</b>	<b>4</b>
<b>1.3. TESTING ENVIRONMENT .....</b>	<b>5</b>
<b>1.4. PROJECT DATA .....</b>	<b>5</b>
<b>1.5. SIGNATURE.....</b>	<b>5</b>
<b>2. CLIENT INFORMATION.....</b>	<b>6</b>
<b>2.1. APPLICANT INFORMATION.....</b>	<b>6</b>
<b>2.2. MANUFACTURER INFORMATION.....</b>	<b>6</b>
<b>3. EQUIPMENT UNDER TEST (EUT) AND ANCILLARY EQUIPMENT (AE) .....</b>	<b>7</b>
<b>3.1. ABOUT EUT .....</b>	<b>7</b>
<b>3.2. INTERNAL IDENTIFICATION OF EUT .....</b>	<b>7</b>
<b>3.3. INTERNAL IDENTIFICATION OF AE .....</b>	<b>7</b>
<b>3.4. EUT SET-UPS.....</b>	<b>8</b>
<b>4. REFERENCE DOCUMENTS .....</b>	<b>9</b>
<b>4.1. DOCUMENTS SUPPLIED BY APPLICANT .....</b>	<b>9</b>
<b>4.2. REFERENCE DOCUMENTS FOR TESTING.....</b>	<b>9</b>
<b>5. TEST RESULTS .....</b>	<b>10</b>
<b>5.1. SUMMARY OF TEST RESULTS .....</b>	<b>10</b>
<b>5.2. STATEMENTS.....</b>	<b>10</b>
<b>6. TEST FACILITIES UTILIZED .....</b>	<b>11</b>
<b>7. MEASUREMENT UNCERTAINTY .....</b>	<b>12</b>
<b>ANNEX A: EUT PARAMETERS.....</b>	<b>13</b>
<b>ANNEX B: DETAILED TEST RESULTS.....</b>	<b>14</b>
<b>ANNEX C: PERSONS INVOLVED IN THIS TESTING .....</b>	<b>27</b>
<b>ANNEX D: ACCREDITATION CERTIFICATE .....</b>	<b>28</b>



## **1. Test Laboratory**

### **1.1. Introduction & Accreditation**

**Telecommunication Technology Labs, CAICT** is an ISO/IEC 17025:2017 accredited test laboratory under NATIONAL VOLUNTARY LABORATORY ACCREDITATION PROGRAM (NVLAP) with lab code 600118-0, and is also an FCC accredited test laboratory (CN5017), and ISED accredited test laboratory (ISED#: 24849). The detail accreditation scope can be found on NVLAP website.

### **1.2. Testing Location**

Location 1: CTTL(huayuan North Road)

Address: No. 52, Huayuan North Road, Haidian District, Beijing,  
P. R. China 100191


### 1.3. Testing Environment

Normal Temperature: 15-35°C  
Extreme Temperature: -20/+50°C  
Normal Relative Humidity: 20-75%  
Normal Air Pressure 86Kpa-106Kpa

### 1.4. Project data

Testing Start Date: 2022-06-02  
Testing End Date: 2022-07-17

### 1.5. Signature



---

Miao Qing Hua  
(Prepared this test report)



---

Zhou Bin  
(Reviewed this test report)



---

Pang Shuai  
(Approved this test report)



## **2. Client Information**

### **2.1. Applicant Information**

Company Name: Sonim Technologies, Inc.  
Address: 6500 River Place Blvd., Building 7, Suite 250, Austin, TX 78730, USA  
Contact: Avena xu  
Telephone: 1-650-378-8100  
Email: Avena.xu@sonimtech.com

### **2.2. Manufacturer Information**

Company Name: Sonim Technologies, Inc.  
Address: 6500 River Place Blvd., Building 7, Suite 250, Austin, TX 78730, USA  
Contact: Avena xu  
Telephone: 1-650-378-8100  
Email: Avena.xu@sonimtech.com

### 3. Equipment Under Test (EUT) and Ancillary Equipment (AE)

#### 3.1. About EUT

Description	Smart phone
Model Name	XP9900(P14001),XP9900(P14002),XP9900(P14003), XP9900(P14004),XP9900(P14005),XP9900(P14006),XP9900(P14010)
FCC ID	WYPP14010
UMTS Frequency bands	FDD II/IV/V/VIII
E-UTRA Frequency bands	FDD 1/2/3/4/5/7/8/12/13/14/20/25/26/29/30/66/71 TDD 38/39/40/41/42/43/46/48
5G NR Frequency bands	NSA n2/n5/n14/n25/n30/n41/n48/n66/n71/n77/n78
Operating temperature	35°C
Extreme low voltage	3.6 V
Normal voltage	3.9 V
Extreme high voltage	4.45 V

**Note:**

The software of XP9900(P14001) is initial model. The software of XP9900(P14002) and XP9900(P14003) have been modified carrier customization, no RF change. The software of XP9900(P14004) has been modified carrier customization, no RF change, removed OMA DM, FUMO and RTT. The software of XP9900(P14005) has been added Google RCS and TTY, removed OMA-DM, FUMO and RTT. The software of XP9900(P14006) has been added IR 94 video call, Google RCS and TTY, removed OMA-DM and FUMO. The software of XP9900(P14010) has been added Google RCS and TTY, removed OMA-DM and FUMO.

#### 3.2. Internal Identification of EUT

EUT ID*	SN or IMEI	HW Version	SW Version
UT53a	016188000001938	V1.0	10.0.0-01-12.0.0-10.62.10
UT95a	016188000000427	V1.0	10.0.0-01-12.0.0-10.60.10

\*EUT ID: is used to identify the test sample in the lab internally.

#### 3.3. Internal Identification of AE

AE ID*	Description	SN	Remarks
AE1	Battery	/	/
AE2	Charger	/	/
AE3	USB Cable	/	/
AE5	NFC Card		

AE1

Model	BAT-05000-01S
Manufacturer	Dongguan Veken Battery Co., Ltd.

AE2



Model	1-CHUSQ302-097
Manufacturer	HUIZHOU PUAN ELECTRONICS CO.,LTD
AE3	
Model	336278
Manufacturer	SUNTOPS ELECTRONICS CO.,LTD
AE5	
Model	/
Manufacturer	/

\*AE ID: is used to identify the ancillary equipment in the lab internally.

### 3.4. EUT Set-ups

EUT set-up No.	Combination of EUT and AE	Remarks
Set.NFC01	UT95a + AE1 + AE2 + AE3 + NFC Card	Charge
Set.NFC02	UT95a + AE1+ NFC card	NFC
Set.NFC03	UT53a	---

The Transmit State of NFC: the NFC function is on. The EUT will transmit the NFC data and command continuously during the test.

The Transmit state without modulation: The EUT will transmit the CW signal at the operating frequency.



## **4. Reference Documents**

### **4.1. Documents supplied by applicant**

EUT parameters, referring to Annex A for detailed information, are supplied by the client or manufacturer, which are the bases of testing.

### **4.2. Reference Documents for testing**

The following documents listed in this section are referred for testing.

<b>Reference</b>	<b>Title</b>	<b>Version</b>
CFR 47 Part 2	Part 2 — Frequency Allocations and Radio Treaty Matters; General Rules and Regulations.	2019
CFR 47 Part 15	Part 15 — Radio Frequency Devices. Subpart C — Intentional Radiators. § 15.35 Measurement detector functions and bandwidths. § 15.207 Conducted limits. § 15.209 Radiated emission limits, general requirements. § 15.215 Additional provisions to the general radiated emission limitations. § 15.225 Operation within the band 13.110–14.010 MHz.	2019
ANSI C63.10	American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices	2013

## 5. Test Results

### 5.1. Summary of Test Results

No	Test Cases	Clause in Regulation	Section in This Report	Verdict
1	Electric Field Strength of Fundamental Emissions	CFR 47 § 15.225(a)	B.1	P(Set. NFC02)
2	Electric Field Strength of Outside the Allocated Bands	CFR 47 § 15.225(b) CFR 47 § 15.225(c)		P(Set. NFC02)
3	Electric Field Radiated Emissions	CFR 47 § 15.209	B.2	P(Set. NFC02)
		CFR 47 § 15.225(d)	B.3	P(Set. NFC01)
4	Frequency Tolerance	CFR 47 § 15.225(e)	B.4	P(Set. NFC03)
5	20dB Bandwidth	CFR 47 § 15.215(c)	B.5	P(Set. NFC03)
6	Conducted Emissions	CFR 47 § 15.207	B.6	P(Set. NFC01)
The measurement is carried out according to ANSI C63.10. See <b>ANNEX B</b> for details.				

#### Test Conditions:

For this report, all the test cases listed above were tested under normal Temperature, Voltage, humidity and Air Pressure except the Frequency Tolerance test case. The specific conditions of Frequency Tolerance test case are listed in section B.4.3

See **Table 3** for terms for result verdict:

**Table 1 Terms for result verdict**

P	Pass, The EUT complies with the essential requirements in the standard.
NP	Not Perform, The test was not performed by CTTL
NA	Not Applicable, The test was not applicable
F	Fail, The EUT does not comply with the essential requirements in the standard

### 5.2. Statements

The test cases listed in Section 5.1 of this report for the EUT specified in Section 3 were performed by CTTL according to the reference documents in Section 4.

The EUT meets all applicable requirements of the regulations and standards in Section 4.2.



## 6. Test Facilities Utilized

NO.	NAME	TYPE	SERIES NUMBER	PRODUCER	CAL. DUE DATE	CAL. INTERVAL
1.	Spectrum Analyzer	RSA3408A	B010277	Tektronix	2022-10-28	1 Year
2.	Climatic chamber	SH242	93008658	ESPEC	2023-02-21	2 Year
3.	Test Receiver	ESW44	103023	R&S	2022-10-28	1 Year
4.	H-field Antenna	HFH2-Z2	829324/007	R&S	2022-12-23	1 Year
5.	EMI Antenna	VULB 9163	302	SCHWARZBECK	2022-12-28	1 Year
6.	Test Receiver	ESCI	100344	R&S	2023-02-21	1 Year
7.	LISN	ENV216	101200	R&S	2023-05-30	1 Year

## 7. Measurement Uncertainty

Item	Uncertainty
Frequency Tolerance	$U = 77 \text{ Hz}, k=2$
20dB Bandwidth	$U = 77 \text{ Hz}, k=2$
Radiated Emissions(9kHz-30MHz)	$U = 4.92 \text{ dB}, k=2$
Radiated Emissions (30MHz-1GHz)	$U = 5.18 \text{ dB}, k=2$
Radiated Emissions (>1GHz)	$U = 5.54 \text{ dB}, k=2$
Conducted emission	$U = 3.08 \text{ dB}, k=2$



**ANNEX A: EUT parameters**

/

## ANNEX B: Detailed Test Results

### B.1. Electric Field Strength of Fundamental and Outside the Allocated bands

#### B.1.1. Reference

See CFR 47 Part 15 § 15.209

See CFR 47 Part 15 § 15.225

See Clause 4, Clause 5 of ANSI C63.10-2013 generally.

#### B.1.2. Measurement Methods

The transmitter carrier output levels (E-Field) from the EUT are measured in a semi-anechoic chamber. The EUT is placed on a non-conductive stand of 80cm high, and at a measurement distance of 3m from the receiving antenna. The center of the receiving loop antenna is 1.0 meter above the ground. The E-field is measured with a shielded loop antenna connected to a measurement receiver. Detected E-field was maximized by rotating the EUT through 360° and adjusting the receiving antenna polarizations. The maximization processes were repeated with the EUT positioned respectively in its three orthogonal axes. The measurements were performed with the peak detector and if required, the quasi-peak detector.


The measurement bandwidth is:

**Table B-1: Measurement bandwidth**

Frequency of Emission (MHz)	RBW/VBW
12.56-14.56	10/30 kHz

The E-field measured at 3m is calculated as:

$$\text{E-field (dB}\mu\text{V/m)} = \text{Rx (dB}\mu\text{V)} + \text{Cable Loss (dB)} + \text{AF@3m (dB/m)}$$



**Figure B-1: Measurement Setup**

#### B.1.3. EUT Operating Mode and Test Conditions

The measurement of EUT is carried out under the transmit state of NFC(See 3.4).

During the measurements, the ambient temperature of the electromagnetic anechoic chamber is

in the range of 15 ~ 25 °C.

**B.1.4. Limits**

**Table B-2: Limits**

Frequency Range (MHz)	E-field Strength Limit @ 30 m microvolts/meter	E-field Strength Limit @ 3 m (dBµV/m)
13.560 ± 0.007	15,848	124
13.410 to 13.553 13.567 to 13.710	334	90
13.110 to 13.410 13.710 to 14.010	106	81
Other frequency range in 1.705-30	30	70


Note: Where the limits have been defined at one distance, and a signal level measured at another, the limits have been extrapolated using the following formula:  

$$\text{Extrapolation (dB)} = 40 \log_{10} \left( \frac{\text{Measurement Distance}}{\text{Specification Distance}} \right)$$

**B.1.5. Measurement Results**

Measurement results of normal conditions see Figure B-2 for different set-ups of EUT. The results displayed take into account applicable antenna factors and cable losses.

**Conclusions: Set.NFC02, PASS.**



**Figure B-2: Measurement results for Electric Field Strength of Fundamental and Outside the Allocated bands**

## Final\_Result

Frequency (MHz)	MaxPeak (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)
13.559500	57.98	124	66.02

## B.2. Electric Field Radiated Emissions (< 30MHz)

### B.2.1. Reference

See CFR 47 Part 15 § 15.209

See Clause 6.4 of ANSI C63.10-2013 specifically.

See Clause 4 and Clause 5 of ANSI C63.10-2013 generally.

### B.2.2. Measurement Methods


The transmitter carrier output levels (E-Field) from the EUT are measured in a semi-anechoic chamber. The EUT is placed on a non-conductive stand of 80cm high, and at a measurement distance of 3m from the receiving antenna. The center of the receiving loop antenna is 1.0 meter above the ground. The E-field is measured with a shielded loop antenna connected to a measurement receiver. Detected E-field was maximized by rotating the EUT through 360° and adjusting the receiving antenna polarizations. The maximization processes were repeated with the EUT positioned respectively in its three orthogonal axes. The measurements were performed with the peak detector and if required, the quasi-peak detector.

The measurement bandwidth is:

Frequency of Emission (MHz)	RBW/VBW
0.009-0.15	100/300 Hz
0.15-30	10/30 kHz

The E-field measured at 3m is calculated as:

$$\text{E-field (dB}\mu\text{V/m)} = \text{Rx (dB}\mu\text{V)} + \text{Cable Loss (dB)} + \text{AF@3m (dB/m)}$$



**Figure B-3: Measurement Setup**

### B.2.3. EUT Operating Mode and Test Conditions

The measurement of EUT is carried out under the transmit state of NFC(See 3.4).

The EUT is powered by a travel adapter.



During the measurements, the ambient temperature of the electromagnetic anechoic chamber is in the range of 15 ~ 25 °C.

**B.2.4. Limits**

Frequency Range (MHz)	E-field Strength Limit (microvolts/meter)	E-field Strength Limit @ 3m (dBµV/m)
0.009-0.490	2400/F(kHz) @ 300m	129-94
0.490-1.705	24000/F(kHz) @ 30m	74-63
1.705-30	30 @ 30m	70


Note: Where the limits have been defined at one distance, and a signal level measured at another, the limits have been extrapolated using the following formula:

$$\text{Extrapolation (dB)} = 40 \log_{10} \left( \frac{\text{Measurement Distance}}{\text{Specification Distance}} \right)$$

**B.2.5. Measurement Results**

Measurement results of normal conditions see Figure B-4 for different set-ups of EUT. The results displayed take into account applicable antenna factors and cable losses.

**Conclusions:** Set.NFC01, **PASS.**



**Figure B-4: Measurement results for Electric Field Radiated Emissions (< 30MHz)**

**Final\_Result**

Frequency (MHz)	MaxPeak (dBµV/m)	Limit (dBµV/m)	Margin(dB)
13.560113	50.45	69.50	19.05

### **B.3. Electric Field Radiated Emissions ( $\geq 30\text{MHz}$ )**

#### **B.3.1. Reference**

See CFR 47 Part 15 § 15.209

See Clause 6.5 of ANSI C63.10-2013 specifically.


See Clause 4 and Clause 5 of ANSI C63.10-2013 generally.

#### **B.3.2. Measurement Methods**

The electric field radiated emissions from the EUT are measured in a semi-anechoic chamber. The EUT is placed on a non-conductive stand of 80cm high, and at a measurement distance of 10m from the receiving antenna. The receiving antennas connected to a measurement receiver. In order to search for maximum field strength emitted from the EUT, the receiving antenna can be moved between the height of 1.0 m to 4.0 m. Detected E-field was maximized at each frequency by rotating the EUT through  $360^\circ$  and adjusting the receiving antenna positions for both vertical and horizontal antenna polarizations. The maximization processes were repeated with the EUT positioned respectively in its three orthogonal axes. The measurements were performed with the peak detector and if required, the quasi-peak detector.

The measurement bandwidth is:

Frequency of Emission (MHz)	RBW/VBW
30-1000	120kHz



**Figure B-5: Measurement Setup**

#### **B.3.3. EUT Operating Mode and Test Conditions**

The measurement of EUT is carried out under the transmit state of NFC(See 3.4).

The EUT had been connected to a travel adapter.

During the measurements, the ambient temperature of the electromagnetic anechoic chamber is in the range of 15 ~ 25 °C.

**B.3.4. Limits**

Frequency Range (MHz)	E-field Strength Limit @ 3m (microvolts/meter)	E-field Strength Limit @ 10m (dBµV/m)
30-88	100	29.54
88-216	150	33.06
216-960	200	35.56
960-1000	500	43.54


Note: Where the limits have been defined at one distance, and a signal level measured at another, the limits have been extrapolated using the following formula:

$$\text{Extrapolation(dB)} = 40\log_{10}(\text{Measurement Distance} / \text{Specification Distance})$$

**B.3.5. Measurement Results**

Measurement results of normal conditions see Figure B-6 for different set-ups of EUT. The results displayed take into account applicable antenna factors and cable losses.

**Conclusions:** Set.NFC01, **PASS**.



**Figure B-6: Measurement results for Electric Field Radiated Emissions (≥30MHz)**

## Final\_Result

Frequency (MHz)	QuasiPeak (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)
45.811000	10.55	29.54	18.99	108.0	V	135.0
74.329000	17.34	29.54	12.20	275.0	V	315.0
105.951000	22.31	33.06	10.75	302.0	V	137.0
110.025000	23.17	33.06	9.89	183.0	V	135.0
127.679000	15.34	33.06	17.72	175.0	V	162.0
150.183000	7.58	33.06	25.48	225.0	V	188.0

## B.4. Frequency Tolerance


### B.4.1. Reference

See CFR 47 Part 15 § 15.225(e)

See Clause 6.8 of ANSI C63.10-2013 specifically.

See Clause 4 and Clause 5 of ANSI C63.10-2013 generally.

### B.4.2. Measurement Methods



**Figure B-7: Measurement Setup**

The transmitter output signal was picked up by coil antenna connected to the spectrum analyzer. The center frequency was measured with 30Hz RBW and 1kHz span. During the test, the EUT was placed in a thermal chamber until thermal balance and lasting appropriate time.

### B.4.3. EUT Operating Mode and Test Conditions

The measurement of EUT was carried out under the transmit state of without modulation(See 3.4). EUT had not been connected to a travel adapter. The frequency stability was measured with the different voltage and temperature combinations:

- The nominal voltage 3.9V(See 3.1)was used and the temperature was varied from -20°C to +50°C in 10°C increments using an environmental chamber.
- The 20°C was used and the voltages were 3.6V, 3.9V and 4.45V (The extreme low voltage ,the normal voltage and the extreme high voltage defined in section 3.1).

The details were as following:

**Table B-3: Combinations of Voltage and Temperature**

Test items	Voltage	Temperature
Frequency stability with respect to ambient temperature	3.9V	-20°C
		-10°C
		0°C
		10°C
		20°C
		30°C
		40°C
		50°C
Frequency stability when varying supply voltage	3.6 V	20°C
	3.9V	
	4.45V	

#### B.4.4. Test Layouts

See B.4.2.

#### B.4.5. Limits

The frequency tolerance of the carrier signal shall be maintained within +/- 0.01% of the operating frequency.

#### B.4.6. Measurement Results

Measurement results see Table B-4 for different test conditions.

**Conclusions:** Set.NFC03, **PASS**.

**Table B-4: Measurement results for Frequency Tolerance**

Temperature	Voltage	Frequency (MHz)			
		Startup	2 Min Later	5 Min Later	10 Min Later
-20°C	3.9V	13.560046875	13.560046875	13.560046875	13.560046875
-10°C	3.9V	13.560062500	13.560062500	13.560062500	13.560062500
0°C	3.9V	13.560037500	13.560043750	13.560046875	13.560053125
10°C	3.9V	13.560003125	13.560012500	13.560018750	13.560025000
20°C	3.9V	13.559959375	13.559971875	13.559987500	13.559937500
30°C	3.9V	13.559968750	13.559968750	13.559968750	13.559968750
40°C	3.9V	13.559962500	13.559953125	13.559946875	13.559943750
50°C	3.9V	13.559928125	13.559928125	13.559928125	13.559925000
20°C	3.6V	13.560056250	13.560040625	13.560028125	13.560015625
20°C	4.45V	13.560003125	13.560003125	13.560003125	13.560031250

Temperature	Voltage	Frequency Error (%)			
		Startup	2 Min Later	5 Min Later	10 Min Later
-20°C	3.9V	0.000	0.000	0.000	0.000
-10°C	3.9V	0.000	0.000	0.000	0.000
0°C	3.9V	0.000	0.000	0.000	0.000
10°C	3.9V	0.000	0.000	0.000	0.000
20°C	3.9V	0.000	0.000	0.000	0.000
30°C	3.9V	0.000	0.000	0.000	0.000
40°C	3.9V	0.000	0.000	0.000	0.000
50°C	3.9V	-0.001	-0.001	-0.001	-0.001
20°C	3.6V	0.000	0.000	0.000	0.000
20°C	4.45V	0.000	0.000	0.000	0.000

#### B.4.7. Measurement Uncertainty

Measurement uncertainty:  $U = 77 \text{ Hz}$ ,  $k=2$

### B.5. 20dB Bandwidth

#### B.5.1. Reference


See CFR 47 Part 15 § 15.215(c)

See Clause 6.9 of ANSI C63.10-2013 specifically.

See Clause 4 and Clause 5 of ANSI C63.10-2013 generally.

#### B.5.2. Measurement Methods

The transmitter output signal was picked up by coil antenna connected to the spectrum analyzer. The bandwidth of the center frequency was measured with 140Hz RBW, 420Hz VBW and 14kHz span.



**Figure B-8: Measurement Setup**

#### B.5.3. EUT Operating Mode and Test Conditions

The measurement of EUT was carried out under the transmit state of NFC (See 3.4).

EUT had not been connected to a travel adapter.

During the measurements, the ambient temperature was in the range of 15 ~ 25 °C.

### B.5.4. Test Layouts

See B.5.2.

### B.5.5. Limits

The 20dB bandwidth shall be less than 80% of the permitted frequency band. For 13.56 MHz NFC, the permitted frequency band is 14kHz, so the limit is 11.2 kHz.

### B.5.6. Measurement Results

Measurement results see Figure B-9.

**Conclusions:** Set.NFC03, **PASS**.




Figure B-9: Measurement results for 20dB Bandwidth

### B.5.7. Measurement Uncertainty

Measurement uncertainty:  $U = 77 \text{ Hz}$ ,  $k=2$

## **B.6. Conducted emission**

### **B.6.1. Reference**

See CFR 47 Part 15 § 15.207

See Clause 6.2 of ANSI C63.10-2013 specifically.

See Clause 4 and Clause 5 of ANSI C63.10-2013 generally.

### **B.6.2. Measurement Methods**


The conducted emissions from the AC port of the EUT are measured in a shielding room. The EUT is connected to a Line Impedance Stabilization Network (LISN). An overview sweep with peak detection was performed. The measurements were performed with a quasi-peak detector and if required, an average detector.

The conducted emission measurements were made with the following detector of the test receiver: Quasi-Peak / Average Detector.

The measurement bandwidth is:

**Table B-5: Measurement Bandwidth**

Frequency of Emission (MHz)	RBW/VBW
0.15-30	9kHz



**Figure B-10: Measurement Setup**

### **B.6.3. EUT Operating Mode and Test Conditions**

The measurement of EUT is carried out under the transmit state of NFC(See 3.4).

The EUT is powered by a travel adapter.

During the measurements, the ambient temperature is in the range of 15 ~ 25 °C.




**B.6.4. Limits**

Frequency range (MHz)	Quasi-peak Limit (dB $\mu$ V)	Average Limit (dB $\mu$ V)
0.15 to 0.5	66 to 56	56 to 46
0.5 to 5	56	46
5 to 30	60	50

**B.6.5. Measurement Results**

Measurement results see Figure B-11.

**Conclusions:** Set.NFC01, **PASS.**


Note: the spike over the limit is coming from the traffic carrier.

**Figure B-11: Measurement results for Conducted Emission**
**Final Result 1**

Frequency (MHz)	QuasiPeak (dB $\mu$ V)	Line	Corr. (dB)	Margin (dB)	Limit (dB $\mu$ V)
0.250000	41.1	N	19.7	20.7	61.8
0.282000	51.4	N	19.8	9.3	60.8
0.514000	49.1	N	19.8	6.9	56.0
0.978000	40.7	N	19.6	15.3	56.0
1.274000	32.9	N	19.6	23.1	56.0
5.430000	48.5	L1	19.6	11.5	60.0

**Final Result 2**

Frequency (MHz)	Average (dBuV)	Line	Corr. (dB)	Margin (dB)	Limit (dBuV)
0.250000	21.5	N	19.7	30.2	51.8
0.282000	24.3	N	19.8	26.5	50.8
0.570000	43.7	L1	19.7	2.3	46.0
1.746000	32.2	L1	19.6	13.8	46.0
5.166000	37.2	L1	19.6	12.8	50.0
27.122000	35.8	L1	20.1	14.2	50.0

**ANNEX C: Persons involved in this testing**

Test Item	Tester
20dB Bandwidth	Zhou Bin
Frequency Tolerance	Zhou Bin
Electric Field Strength of Fundamental and Outside the Allocated bands	Ding Zai
Electric Field Radiated Emissions (< 30MHz)	Ding Zai
Electric Field Radiated Emissions ( $\geq 30$ MHz)	Ding Zai
Conducted Emissions	Zhang Tianli

**ANNEX D: Accreditation Certificate**

<p>United States Department of Commerce National Institute of Standards and Technology</p> <p><b>NVLAP</b>® </p> <hr/> <p><b>Certificate of Accreditation to ISO/IEC 17025:2017</b></p> <hr/> <p>NVLAP LAB CODE: 600118-0</p> <p><b>Telecommunication Technology Labs, CAICT</b> Beijing China</p> <p><i>is accredited by the National Voluntary Laboratory Accreditation Program for specific services, listed on the Scope of Accreditation, for:</i></p> <p><b>Electromagnetic Compatibility &amp; Telecommunications</b></p> <p><i>This laboratory is accredited in accordance with the recognized International Standard ISO/IEC 17025:2017. This accreditation demonstrates technical competence for a defined scope and the operation of a laboratory quality management system (refer to joint ISO-ILAC-IAF Communique dated January 2009).</i></p> <hr/> <p>2021-09-29 through 2022-09-30 <i>Effective Dates</i></p> <p style="text-align: center;"></p> <p style="text-align: right;"> <i>For the National Voluntary Laboratory Accreditation Program</i></p>	
--	--

**\*\*\*END OF REPORT\*\*\***