

FCC RF Test Report

APPLICANT : Sonim Technologies, Inc.
EQUIPMENT : GSM, WCDMA, LTE Cell Phone
BRAND NAME : Sonim
MODEL NAME : XP5900(P14500)
XP5900(P14600)
XP5900(P14510)
XP5900(P14610)
XP5900(P14501)
XP5900(P14601)
FCC ID : WYPP14510
STANDARD : 47 CFR Part 2, 90(R)
CLASSIFICATION : PCS Licensed Transmitter Held to Ear (PCE)
TEST DATE(S) : Jan. 23, 2022 ~ Feb. 15, 2022

We, Sporton International Inc. (Kunshan), would like to declare that the tested sample has been evaluated in accordance with the procedures given in ANSI C63.26-2015 and shown compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International Inc. (Kunshan), the test report shall not be reproduced except in full.

Jason Jia

Reviewed by: Jason Jia / Supervisor

Alex Wang

Approved by: Alex Wang / Manager



Sporton International Inc. (Kunshan)

**No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300
People's Republic of China**



TABLE OF CONTENTS

REVISION HISTORY... 3
SUMMARY OF TEST RESULT ... 4
1 GENERAL DESCRIPTION ... 5
1.1 Applicant ... 5
1.2 Manufacturer ... 5
1.3 Feature of Equipment Under Test ... 5
1.4 Maximum ERP Power, and Emission Designator ... 6
1.5 Testing Site ... 6
1.6 Test Software ... 6
1.7 Applied Standards ... 7
2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST ... 8
2.1 Test Mode ... 8
2.2 Connection Diagram of Test System ... 9
2.3 Support Unit used in test configuration and system ... 9
2.4 Measurement Results Explanation Example ... 10
3 CONDUCTED TEST ITEMS ... 11
3.1 Measuring Instruments ... 11
3.2 Conducted Output Power and ERP ... 12
3.3 Peak-to-Average Ratio ... 13
3.4 Occupied Bandwidth ... 14
3.5 Conducted Band Edge Measurement ... 15
3.6 Emission Mask ... 16
3.7 Conducted Spurious Emission Measurement ... 17
3.8 Frequency Stability Measurement ... 18
4 RADIATED TEST ITEMS ... 19
4.1 Measuring Instruments ... 19
4.2 Test Setup ... 19
4.3 Test Result of Radiated Test ... 20
4.4 Radiated Spurious Emission Measurement ... 21
5 LIST OF MEASURING EQUIPMENT ... 22
6 UNCERTAINTY OF EVALUATION ... 23
APPENDIX A. TEST RESULTS OF CONDUCTED TEST
APPENDIX B. TEST RESULTS OF RADIATED TEST
APPENDIX C. TEST SETUP PHOTOGRAPHS

SUMMARY OF TEST RESULT

| Report Section | FCC Rule | Description | Limit | Result | Remark |
|----------------|--|--|-------------------------------------|----------------|---|
| 3.2 | §2.1046 | Conducted Output Power | — | Reporting only | - |
| | §90.542 (a)(7) | Effective Radiated Power | ERP < 3Watt | PASS | - |
| 3.3 | - | Peak-to-Average Ratio | — | Reporting only | - |
| 3.4 | §2.1049 | Occupied Bandwidth | — | Reporting only | - |
| 3.5 | §2.1053 §90.543 (e)(2)(3) | Conducted Band Edge Measurement | Refer standard | PASS | - |
| 3.6 | §2.1051 §90.210(n) | Emission Mask | Mask B | PASS | - |
| 3.7 | §2.1053 §90.543 (e)(3) | Conducted Spurious Emission | < 43+10log ₁₀ (P[Watts]) | PASS | - |
| 3.8 | §2.1055 §90.539 (e) | Frequency Stability Temperature & Voltage | < ±1.25 ppm | PASS | - |
| 4.4 | §2.1053 §90.543 (e)(3) §90.543 (f) | Radiated Spurious Emission | < 43+10log ₁₀ (P[Watts]) | PASS | Under limit 12.88 dB at 1576.000 MHz |

Declaration of Conformity:

The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.

Comments and Explanations:

The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.



1 General Description

1.1 Applicant

Sonim Technologies, Inc.

6500 River Place Blvd. Building 7, Suite 250, Austin, TX 78730, USA

1.2 Manufacturer

Sonim Technologies, Inc.

6500 River Place Blvd. Building 7, Suite 250, Austin, TX 78730, USA

1.3 Feature of Equipment Under Test

| Product Feature | |
|---------------------------------|--|
| Equipment | GSM, WCDMA, LTE Cell Phone |
| Brand Name | Sonim |
| Model Name | XP5900(P14500) XP5900(P14600) XP5900(P14510) XP5900(P14610) XP5900(P14501) XP5900(P14601) |
| FCC ID | WYPP14510 |
| Tx Frequency | LTE Band 14: 788 MHz ~ 798 MHz |
| Rx Frequency | LTE Band 14: 758 MHz ~ 768 MHz |
| Bandwidth | 5MHz / 10MHz |
| Maximum Output Power to Antenna | 23.30 dBm |
| Antenna Gain | -2.8 dBi |
| Type of Modulation | QPSK / 16QAM / 64QAM |
| IMEI Code | Conducted: 016107002020002 Radiation: 016107000012711 |
| HW Version | 1.0 |
| SW Version | 5P.2.0-01-11.0.0-10.22.14 |
| EUT Stage | Identical Prototype |

Remark:

1. The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.
2. The different model names are for different market purpose.

1.4 Maximum ERP Power, and Emission Designator

| LTE Band 14 | | QPSK | | 16QAM/64QAM | |
|-------------|-----------------------|----------------|------------------------------|----------------|------------------------------|
| BW (MHz) | Frequency Range (MHz) | Maximum ERP(W) | Emission Designator (99%OBW) | Maximum ERP(W) | Emission Designator (99%OBW) |
| 5 | 790.5~795.5 | 0.0676 | 4M49G7D | 0.0535 | 4M48W7D |
| 10 | 793 | 0.0684 | 9M01G7D | 0.0548 | 9M01W7D |

Note: All modulations have been tested, and only the worst modulation test results of BPSK & QPSK are shown in the report.

1.5 Testing Site

Sporton International Inc. (Kunshan) is accredited to ISO/IEC 17025:2017 by American Association for Laboratory Accreditation with Certificate Number 5145.02.

| | | | |
|---------------------------|--|----------------------------|---------------------------------------|
| Test Firm | Sporton International Inc. (Kunshan) | | |
| Test Site Location | No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300 People's Republic of China TEL : +86-512-57900158 FAX : +86-512-57900958 | | |
| Test Site No. | Sporton Site No. | FCC Designation No. | FCC Test Firm Registration No. |
| | 03CH04-KS TH01-KS | CN1257 | 314309 |

1.6 Test Software

| Item | Site | Manufacturer | Name | Version |
|------|-----------|--------------|------|--------------|
| 1. | 03CH04-KS | AUDIX | E3 | 6.2009-8-24a |

1.7 Applied Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ 47 CFR Part 2, Part 90(R)
- ♦ ANSI C63.26-2015
- ♦ KDB 971168 D01 Power Meas License Digital Systems v03r01
- ♦ KDB 412172 D01 Determining ERP and EIRP v01r01

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.



2 Test Configuration of Equipment Under Test


2.1 Test Mode

Antenna port conducted and radiated test items listed below are performed according to KDB 971168 D01 Power Meas License Digital Systems v03r01 with maximum output power.

Radiated measurements are performed by rotating the EUT in three different orthogonal test planes to find the maximum emission.

| Conducted Test Cases | Band | Bandwidth (MHz) | | | | | | Modulation | | | RB # | | | Test Channel | | |
|-----------------------------|---|-----------------|---|---|----|----|----|------------|-------|-------|------|------|------|--------------|---|---|
| | | 1.4 | 3 | 5 | 10 | 15 | 20 | QPSK | 16QAM | 64QAM | 1 | Half | Full | L | M | H |
| Max. Output Power | 14 | - | - | V | - | - | - | V | V | | V | V | | V | V | V |
| | 14 | - | - | | V | - | - | V | V | V | V | V | V | | V | |
| Peak-to-Average Ratio | 14 | - | - | V | V | - | - | V | V | V | | | V | | V | |
| 26dB and 99% Bandwidth | 14 | - | - | V | | - | - | V | V | | | | V | | V | |
| | 14 | - | - | | V | - | - | V | V | | | | V | | V | |
| Conducted Band Edge | 14 | - | - | V | | - | - | V | V | V | V | | V | | | V |
| | 14 | - | - | | V | - | - | V | V | V | V | | V | | V | |
| Emission Mask | 14 | - | - | V | | - | - | V | V | V | V | | V | V | V | V |
| | 14 | - | - | | V | - | - | V | V | V | V | | V | | V | |
| Conducted Spurious Emission | 14 | - | - | V | | - | - | V | | | V | | | V | V | V |
| | 14 | - | - | | V | - | - | V | | | V | | | | V | |
| Frequency Stability | 14 | - | - | | V | - | - | V | | | | | V | | V | |
| E.R.P | 14 | - | - | V | | - | - | V | V | | V | V | | V | V | V |
| | 14 | - | - | | V | - | - | V | V | V | V | V | | V | | |
| Radiated Spurious Emission | 14 | - | - | V | | - | - | V | | | V | | | V | V | V |
| | | | | | V | | | V | | | V | | | | V | |
| Note | <ol style="list-style-type: none"> The mark "v" means that this configuration is chosen for testing The mark "-" means that this bandwidth is not supported. The device is investigated from 30MHz to 10 times of fundamental signal for radiated spurious emission test under different RB size/offset and modulations in exploratory test. Subsequently, only the worst case emissions are reported. | | | | | | | | | | | | | | | |

2.2 Connection Diagram of Test System



2.3 Support Unit used in test configuration and system

| Item | Equipment | Trade Name | Model No. | FCC ID | Data Cable | Power Cord |
|------|------------------|------------|-----------|--------|------------------|-------------------|
| 1. | LTE Base Station | Anritsu | MT8820C | N/A | N/A | Unshielded, 1.8 m |
| 2. | Power Supply | GWINSTEK | PSS-2002 | N/A | N/A | Unshielded, 1.8 m |
| 3. | Earphone | Lenovo | N/A | N/A | Unshielded, 1.2m | N/A |

2.4 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

The spectrum analyzer offset is derived from RF cable loss.

Offset = RF cable loss.

Following shows an offset computation example with cable loss 4.7dB.

Example :

$$\begin{aligned} \text{Offset(dB)} &= \text{RF cable loss(dB)}. \\ &= 4.7 \text{ (dB)} \end{aligned}$$


3 Conducted Test Items

3.1 Measuring Instruments


See list of measuring instruments of this test report.

3.1.1 Test Setup


3.1.2 Conducted Output Power



3.1.3 Peak-to-Average Ratio, Occupied Bandwidth, Conducted Band-Edge, Emission Mask, and Conducted Spurious Emission



3.1.4 Frequency Stability



3.1.5 Test Result of Conducted Test

Please refer to Appendix A.

3.2 Conducted Output Power and ERP

3.2.1 Description of the Conducted Output Power Measurement and ERP

A base station simulator was used to establish communication with the EUT. Its parameters were set to transmit the maximum power on the EUT. The measured power in the radio frequency on the transmitter output terminals shall be reported.

The ERP of mobile transmitters must not exceed 3 Watts for LTE Band 14.

According to KDB 412172 D01 Power Approach,

$EIRP = P_T + G_T - L_C$, $ERP = EIRP - 2.15$, where

P_T = transmitter output power in dBm

G_T = gain of the transmitting antenna in dBi

L_C = signal attenuation in the connecting cable between the transmitter and antenna in dB

3.2.2 Test Procedures

1. The testing follows ANSI C63.26 Section 5.2
2. The transmitter output port was connected to the system simulator.
3. Set EUT at maximum power through the system simulator.
4. Select lowest, middle, and highest channels for each band and different modulation.
5. Measure and record the power level from the system simulator.



3.3 Peak-to-Average Ratio

3.3.1 Description of the PAR Measurement

Power Complementary Cumulative Distribution Function (CCDF) curves provide a means for characterizing the power peaks of a digitally modulated signal on a statistical basis. A CCDF curve depicts the probability of the peak signal amplitude exceeding the average power level. Most contemporary measurement instrumentation include the capability to produce CCDF curves for an input signal provided that the instrument's resolution bandwidth can be set wide enough to accommodate the entire input signal bandwidth. In measuring transmissions in this band using an average power technique, the peak-to-average ratio (PAR) of the transmission may not exceed 13 dB.

3.3.2 Test Procedures

1. The EUT was connected to spectrum and system simulator via a power divider.
2. Set the CCDF (Complementary Cumulative Distribution Function) option in spectrum analyzer.
3. The highest RF powers were measured and recorded the maximum PAPR level associated with a probability of 0.1 %.
4. Record the deviation as Peak to Average Ratio.

3.4 Occupied Bandwidth

3.4.1 Description of Occupied Bandwidth Measurement

The occupied bandwidth is the width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5% of the total mean transmitted power.

The 26 dB emission bandwidth is defined as the frequency range between two points, one above and one below the carrier frequency, at which the spectral density of the emission is attenuated 26 dB below the maximum in-band spectral density of the modulated signal. Spectral density (power per unit bandwidth) is to be measured with a detector of resolution bandwidth equal to approximately 1.0% of the emission bandwidth.

3.4.2 Test Procedures

1. The testing follows ANSI C63.26 Section 5.4
2. The EUT was connected to spectrum analyzer and system simulator via a power divider.
3. The spectrum analyzer center frequency is set to the nominal EUT channel center frequency. The span range for the spectrum analyzer shall be between two and five times the anticipated OBW.
4. The nominal resolution bandwidth (RBW) shall be in the range of 1 to 5 % of the anticipated OBW, and the VBW shall be at least 3 times the RBW.
5. Set the detection mode to peak, and the trace mode to max hold.
6. Determine the reference value: Set the EUT to transmit a modulated signal. Allow the trace to stabilize. Set the spectrum analyzer marker to the highest level of the displayed trace.
(this is the reference value)
7. Determine the “-26 dB down amplitude” as equal to (Reference Value – X).
8. Place two markers, one at the lowest and the other at the highest frequency of the envelope of the spectral display such that each marker is at or slightly below the “-X dB down amplitude” determined in step 6. If a marker is below this “-X dB down amplitude” value it shall be placed as close as possible to this value. The OBW is the positive frequency difference between the two markers.
9. Use the 99 % power bandwidth function of the spectrum analyzer and report the measured bandwidth.

3.5 Conducted Band Edge Measurement

3.5.1 Description of Conducted Band Edge Measurement

For operations in the 758-768 MHz and the 788-798 MHz bands

- (1) On all frequencies between 769-775 MHz and 799-805 MHz, by a factor not less than $76 + 10 \log (P)$ dB in a 6.25 kHz band segment, for base and fixed stations.
- (2) On all frequencies between 769-775 MHz and 799-805 MHz, by a factor not less than $65 + 10 \log (P)$ dB in a 6.25 kHz band segment, for mobile and portable stations.
- (3) On any frequency between 775-788 MHz, above 805 MHz, and below 758 MHz, by at least $43 + 10 \log (P)$ dB.

3.5.2 Test Procedures

1. The testing follows ANSI C63.26 section 5.7
2. The EUT was connected to spectrum analyzer and system simulator via a power divider.
3. The band edges of low and high channels for the highest RF powers were measured.
4. Set spectrum analyzer with RMS detector.
5. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
6. Checked that all the results comply with the emission limit line.

Example:

$$\begin{aligned} & \text{The limit line is derived from } 43 + 10\log(P)\text{dB below the transmitter power } P(\text{Watts}) \\ & = P(\text{W}) - [43 + 10\log(P)] \text{ (dB)} \\ & = [30 + 10\log(P)] \text{ (dBm)} - [43 + 10\log(P)] \text{ (dB)} = -13\text{dBm}. \end{aligned}$$

3.6 Emission Mask

3.6.1 Description of Emission Mask

<Emission Mask B>.

For transmitters that are equipped with an audio low-pass filter, the power of any emission must be attenuated below the unmodulated carrier power (P) as follows:

- (1) On any frequency removed from the assigned frequency by more than 50 percent, but not more than 100 percent of the authorized bandwidth: At least 25 dB.
- (2) On any frequency removed from the assigned frequency by more than 100 percent, but not more than 250 percent of the authorized bandwidth: At least 35 dB.
- (3) On any frequency removed from the assigned frequency by more than 250 percent of the authorized bandwidth: At least $43 + 10 \log (P)$ dB.

3.6.2 Test Procedures

1. The testing follows ANSI C63.26 section 5.7
2. The EUT was connected to spectrum analyzer and system simulator via a power divider.
3. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
4. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz.
5. Set spectrum analyzer with RMS detector.
6. Taking the record of maximum spurious emission.
7. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
8. The limit line is derived from $43 + 10\log(P)$ dB below the transmitter power P(Watts)
= $P(W) - [43 + 10\log(P)]$ (dB)
= $[30 + 10\log(P)]$ (dBm) - $[43 + 10\log(P)]$ (dB)
= -13dBm.

3.7 Conducted Spurious Emission Measurement

3.7.1 Description of Conducted Spurious Emission Measurement

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB.

It is measured by means of a calibrated spectrum analyzer and scanned from 30MHz up to a frequency including its 10th harmonic.

3.7.2 Test Procedures

1. The testing follows ANSI C63.26 section 5.7
2. The EUT was connected to spectrum analyzer and base station via power divider.
3. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
4. The middle channel for the highest RF power within the transmitting frequency was measured.
5. The conducted spurious emission for the whole frequency range was taken.
6. Make the measurement with the spectrum analyzer's, for under 1GHz RBW = 100kHz, VBW = 300kHz and for above 1GHz RBW = 1MHz, VBW = 3MHz, taking the record of maximum spurious emission.
7. Set spectrum analyzer with RMS detector.
8. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
9. The limit line is derived from $43 + 10\log(P)$ dB below the transmitter power P(Watts)
= P(W)- [43 + 10log(P)] (dB)
= [30 + 10log(P)] (dBm) - [43 + 10log(P)] (dB)
= -13dBm.

3.8 Frequency Stability Measurement

3.8.1 Description of Frequency Stability Measurement

The frequency stability shall be measured by variation of ambient temperature and variation of primary supply voltage to ensure that the fundamental emission stays within the authorized frequency block. The frequency stability of the transmitter shall be maintained within ± 1.25 ppm of the center frequency.

3.8.2 Test Procedures for Temperature Variation

1. The testing follows ANSI C63.26 section 5.6.4
2. The EUT was set up in the thermal chamber and connected with the system simulator.
3. With power OFF, the temperature was decreased to -30°C and the EUT was stabilized before testing. Power was applied and the maximum change in frequency was recorded within one minute.
4. With power OFF, the temperature was raised in 10°C step up to 50°C . The EUT was stabilized at each step for at least half an hour. Power was applied and the maximum frequency change was recorded within one minute.

3.8.3 Test Procedures for Voltage Variation

1. The testing follows ANSI C63.26 section 5.6.5.
2. The EUT was placed in a temperature chamber at $20\pm 5^{\circ}\text{C}$ and connected with the system simulator.
3. The power supply voltage to the EUT was varied from 85% to 115% of the nominal value for other than hand carried battery equipment.
4. For hand carried, battery powered equipment, reduce the primary ac or dc supply voltage to the battery operating end point, which shall be specified by the manufacturer.
5. The variation in frequency was measured for the worst case.

4 Radiated Test Items

4.1 Measuring Instruments


See list of measuring instruments of this test report.

4.2 Test Setup

4.2.1 For radiated test below 30MHz



4.2.2 For radiated test from 30MHz to 1GHz



4.2.3 For radiated test above 1GHz



4.3 Test Result of Radiated Test

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported.

Please refer to Appendix B.

4.4 Radiated Spurious Emission Measurement

4.4.1 Description of Radiated Spurious Emission

The radiated spurious emission was measured by substitution method according to ANSI C63.26.

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB.

For operations in the 758-775 MHz and 788-805 MHz bands, all emissions including harmonics in the band 1559–1610 MHz shall be limited to -70 dBW/MHz equivalent isotropically radiated power (EIRP) for wideband signals, and -80 dBW EIRP for discrete emissions of less than 700 Hz bandwidth. For the purpose of equipment authorization, a transmitter shall be tested with an antenna that is representative of the type that will be used with the equipment in normal operation.

4.4.2 Test Procedures

1. The testing follows ANSI C63.26 Section 5.5
2. The EUT was placed on a turntable with 0.8 meter height for frequency below 1GHz and 1.5 meter height for frequency above 1GHz respectively above ground.
3. The EUT was set 3 meters from the receiving antenna mounted on the antenna tower.
4. The table was rotated 360 degrees to determine the position of the highest spurious emission.
5. The height of the receiving antenna is varied between 1m to 4m to search the maximum spurious emission for both horizontal and vertical polarizations.
6. During the measurement, the system simulator parameters were set to force the EUT transmitting at maximum output power.
7. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz, taking the record of maximum spurious emission.
8. A horn antenna was substituted in place of the EUT and was driven by a signal generator.
9. Tune the output power of signal generator to the same emission level with EUT maximum spurious emission.
10. $EIRP (dBm) = S.G. Power - Tx Cable Loss + Tx Antenna Gain$
11. $ERP (dBm) = EIRP - 2.15$
12. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

The limit line is derived from $43 + 10\log(P)$ dB below the transmitter power P(Watts)
 $= P(W) - [43 + 10\log(P)] (dB)$
 $= [30 + 10\log(P)] (dBm) - [43 + 10\log(P)] (dB)$
 $= -13dBm.$



5 List of Measuring Equipment

| Instrument | Manufacturer | Model No. | Serial No. | Characteristics | Calibration Date | Test Date | Due Date | Remark |
|--------------------------------|--------------|--------------------------------|-----------------|-------------------------|------------------|---------------------------------|---------------|-----------------------|
| Spectrum Analyzer | R&S | FSV40 | 101040 | 10Hz~40GHz | Nov. 01, 2021 | Jan. 23, 2022~ Feb. 15, 2022 | Oct. 31, 2022 | Conducted (TH01-KS) |
| Power divider | STI | STI08-0055 | - | 0.5~40GHz | Aug. 27, 2021 | Jan. 23, 2022~ Feb. 15, 2022 | Aug. 26, 2022 | Conducted (TH01-KS) |
| Temperature & humidity chamber | Hongzhan | LP-150U | H201401144 0 | -40~+150°C 20%~95%RH | Jul. 12, 2021 | Jan. 23, 2022~ Feb. 15, 2022 | Jul. 11, 2022 | Conducted (TH01-KS) |
| EXA Spectrum Analyzer | Keysight | N9010A | MY5515024 4 | 10Hz-44G,MAX 30dB | Apr. 13, 2021 | Feb. 10, 2022 | Apr. 12, 2022 | Radiation (03CH04-KS) |
| Loop Antenna | R&S | HFH2-Z2 | 100321 | 9kHz~30MHz | Nov. 01, 2021 | Feb. 10, 2022 | Oct. 31, 2022 | Radiation (03CH04-KS) |
| Bilog Antenna | TeseQ | CBL6111D | 49922 | 30MHz-1GHz | Jun. 07, 2022 | Feb. 10, 2022 | Jun. 06, 2023 | Radiation (03CH04-KS) |
| Double Ridge Horn Antenna | ETS-Lindgren | 3117 | 75957 | 1GHz~18GHz | Nov. 01, 2021 | Feb. 10, 2022 | Oct. 31, 2022 | Radiation (03CH04-KS) |
| SHF-EHF Horn | Com-power | AH-840 | 101115 | 18GHz~40GHz | Jan. 06, 2022 | Feb. 10, 2022 | Jan. 05, 2023 | Radiation (03CH04-KS) |
| Amplifier | SONOMA | 310N | 187289 | 9KHz-1GHz | Jan. 06, 2022 | Feb. 10, 2022 | Jan. 05, 2023 | Radiation (03CH04-KS) |
| Amplifier | MITEQ | EM18G40G GA | 060728 | 18~40GHz | Jan. 07, 2022 | Feb. 10, 2022 | Jan. 06, 2023 | Radiation (03CH04-KS) |
| high gain Amplifier | MITEQ | AMF-7D-00 101800-30- 10P | 2025788 | 1Ghz-18Ghz | Jan. 06, 2022 | Feb. 10, 2022 | Jan. 05, 2023 | Radiation (03CH04-KS) |
| Amplifier | Keysight | 83017A | MY5728010 6 | 500MHz~26.5G Hz | Oct. 14, 2021 | Feb. 10, 2022 | Oct. 13, 2022 | Radiation (03CH04-KS) |
| AC Power Source | Chroma | 61601 | F104090004 | N/A | NCR | Feb. 10, 2022 | NCR | Radiation (03CH04-KS) |
| Turn Table | ChamPro | EM 1000-T | 060762-T | 0~360 degree | NCR | Feb. 10, 2022 | NCR | Radiation (03CH04-KS) |
| Antenna Mast | ChamPro | EM 1000-A | 060762-A | 1 m~4 m | NCR | Feb. 10, 2022 | NCR | Radiation (03CH04-KS) |

NCR: No Calibration Required



6 Uncertainty of Evaluation

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI 63.26-2015. All the measurement uncertainty value were shown with a coverage K=2 to indicate 95% level of confidence. The measurement data show herein meets or exceeds the CISPR measurement uncertainty values specified in CISPR 16-4-2 and can be compared directly to specified limit to determine compliance.

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

| | |
|---|-------|
| Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y)) | 3.3dB |
|---|-------|

Uncertainty of Radiated Emission Measurement (1GHz ~ 40GHz)

| | |
|---|-------|
| Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y)) | 2.8dB |
|---|-------|

----- THE END -----

Appendix A. Test Results of Conducted Test

Conducted Output Power(Average power)and ERP/EIRP

| BW [MHz] | Modulation | RB Size | RB Offset | Power Low Ch. / Freq. | Power Middle Ch. / Freq. | Power High Ch. / Freq. | ERP(W) | | |
|-----------------|------------|---------|-----------|-----------------------------|--------------------------------|------------------------------|--------|--------|--------|
| Channel | | | | 23330 | | | | | |
| Frequency (MHz) | | | | 793 | | | | M | |
| 10 | QPSK | 1 | 0 | | 23.30 | | | 0.0684 | |
| 10 | QPSK | 1 | 49 | | 23.15 | | | 0.0661 | |
| 10 | QPSK | 50 | 0 | | 22.50 | | | 0.0569 | |
| 10 | 16QAM | 1 | 0 | | 22.34 | | | 0.0548 | |
| 10 | 64QAM | 1 | 0 | | 21.34 | | | 0.0436 | |
| Channel | | | | 23305 | 23330 | 23355 | ERP(W) | | |
| Frequency (MHz) | | | | 790.5 | 793 | 795.5 | L | M | H |
| 5 | QPSK | 1 | 0 | 23.14 | 23.25 | 23.22 | 0.0659 | 0.0676 | 0.0671 |
| 5 | 16QAM | 1 | 0 | 22.19 | 22.23 | 22.20 | 0.0530 | 0.0535 | 0.0531 |




LTE Band 14

Peak-to-Average Ratio

| Mode | LTE Band 14 / 5MHz | | | |
|-----------|--------------------|---------|---------|-------------|
| Mod. | QPSK | 16QAM | 64QAM | Limit: 13dB |
| RB Size | Full RB | Full RB | Full RB | Result |
| Middle CH | 4.81 | 5.68 | 5.54 | PASS |


LTE Band 14 / 5MHz

Middle Channel / Full RB/ QPSK




Date: 15 FEB 2022 12:35:14

Middle Channel / Full RB/ 16QAM



Date: 15 FEB 2022 12:35:38

Middle Channel / Full RB/ 64QAM



Date: 15 FEB 2022 12:35:59




Peak-to-Average Ratio

| Mode | LTE Band 14 / 10MHz | | | |
|-----------|---------------------|---------|---------|-------------|
| Mod. | QPSK | 16QAM | 64QAM | Limit: 13dB |
| RB Size | Full RB | Full RB | Full RB | Result |
| Middle CH | 4.67 | 5.59 | 6.00 | PASS |


LTE Band 14 / 10MHz

Middle Channel / Full RB/ QPSK




Date: 23 JAN 2022 05:01:02

Middle Channel / Full RB/ 16QAM



Date: 23 JAN 2022 05:02:20


Middle Channel / Full RB/ 64QAM



Date: 23 JAN 2022 05:03:33


26dB Bandwidth

| | | |
|-----------|----------------------------|-------|
| Mode | LTE Band 14 : 26dB BW(MHz) | |
| BW | 5MHz | |
| Mod. | QPSK | 16QAM |
| Middle CH | 4.90 | 4.98 |
| Mode | LTE Band 14 : 26dB BW(MHz) | |
| BW | 10MHz | |
| Mod. | QPSK | 16QAM |
| Middle CH | 9.81 | 9.85 |



Occupied Bandwidth

| | | |
|-----------|---------------------------|-------|
| Mode | LTE Band 14 : 99%OBW(MHz) | |
| BW | 10MHz | |
| Mod. | QPSK | 16QAM |
| Middle CH | 4.49 | 4.48 |
| Mode | LTE Band 14 : 99%OBW(MHz) | |
| BW | 10MHz | |
| Mod. | QPSK | 16QAM |
| Middle CH | 9.01 | 9.01 |






Conducted Band Edge


LTE Band 14 / 5MHz / QPSK

Lowest Band Edge / 1 RB




Date: 23 JAN 2022 04:25:28

Highest Band Edge / 1 RB




Date: 23 JAN 2022 04:32:18

Lowest Band Edge / Full RB



Date: 23 JAN 2022 04:20:22

Highest Band Edge / Full RB





Date: 23 JAN 2022 04:27:11



LTE Band 14 / 5MHz / 16QAM

Lowest Band Edge / 1 RB

Highest Band Edge / 1 RB





Date: 23 JAN 2022 04:23:46

Date: 23 JAN 2022 04:30:35

Lowest Band Edge / Full RB

Highest Band Edge / Full RB



Date: 23 JAN 2022 04:22:04



Date: 23 JAN 2022 04:28:53



LTE Band 14 / 5MHz / 64QAM

Lowest Band Edge / 1 RB

Highest Band Edge / 1 RB





Date: 23 JAN 2022 04:35:42

Date: 23 JAN 2022 04:39:07

Lowest Band Edge / Full RB

Highest Band Edge / Full RB



Date: 23 JAN 2022 04:34:00


Date: 23 JAN 2022 04:37:24




LTE Band 14 / 10MHz / QPSK

Lowest Band Edge / 1 RB

Highest Band Edge / 1 RB




Date: 23 JAN 2022 04:45:53



Date: 23 JAN 2022 04:47:34

Band Edge / Full RB





Date: 23 JAN 2022 04:40:49



LTE Band 14 / 10MHz / 16QAM

Lowest Band Edge / 1 RB


Highest Band Edge / 1 RB



Date: 23 JAN 2022 04:44:12

Date: 23 JAN 2022 04:49:16

Band Edge / Full RB





Date: 23 JAN 2022 04:42:30



LTE Band 14 / 10MHz / 64QAM

Lowest Band Edge / 1 RB


Highest Band Edge / 1 RB



Date: 23 JAN 2022 04:52:38

Date: 23 JAN 2022 04:54:20


Band Edge / Full RB



Date: 23 JAN 2022 04:50:57




Conducted Spurious Emission





LTE Band 14 / 10MHz

Middle Channel / QPSK




Date: 23 JAN 2022 05:05:25


MASK

LTE Band 14 / 5MHz / QPSK

Lowest Channel / 1RB




Date: 23 JAN 2022 05:40:55



Date: 23 JAN 2022 05:42:40


Lowest Channel / Full RB




Date: 23 JAN 2022 05:32:39

LTE Band 14 / 5MHz / 16QAM

Lowest Channel / 1RB




Date: 23 JAN 2022 05:39:16



Date: 23 JAN 2022 05:44:20


Lowest Channel / Full RB



Date: 23 JAN 2022 05:34:18

LTE Band 14 / 5MHz / 64QAM

Lowest Channel / 1RB




CF 790.5 MHz 691 pts Span 25.0 MHz

Spectrum Emission Mask Standard: None

| Range Low | Range Up | RBW | Tx Bandwidth | Frequency | Power Abs | Power Rel | ALimit |
|-------------|------------|-------------|--------------|---------------|------------|-----------|-----------|
| -12.500 MHz | -5.000 MHz | 100.000 kHz | 5.000 MHz | 795.46188 MHz | -50.91 dBm | -72.91 dB | -37.81 dB |
| -5.000 MHz | -2.500 MHz | 100.000 kHz | 5.000 MHz | 787.98188 MHz | -20.79 dBm | -42.69 dB | -17.59 dB |
| 2.500 MHz | 5.000 MHz | 100.000 kHz | 5.000 MHz | 793.01812 MHz | -53.93 dBm | -75.82 dB | -50.82 dB |
| 5.000 MHz | 12.500 MHz | 100.000 kHz | 5.000 MHz | 796.06159 MHz | -47.02 dBm | -68.91 dB | -33.91 dB |

Date: 23 JAN 2022 05:37:36




CF 790.5 MHz 691 pts Span 25.0 MHz

Spectrum Emission Mask Standard: None

| Range Low | Range Up | RBW | Tx Bandwidth | Frequency | Power Abs | Power Rel | ALimit |
|-------------|------------|-------------|--------------|---------------|------------|-----------|-----------|
| -12.500 MHz | -5.000 MHz | 100.000 kHz | 5.000 MHz | 794.53941 MHz | -47.67 dBm | -69.40 dB | -34.40 dB |
| -5.000 MHz | -2.500 MHz | 100.000 kHz | 5.000 MHz | 787.07609 MHz | -54.62 dBm | -76.35 dB | -51.35 dB |
| 2.500 MHz | 5.000 MHz | 100.000 kHz | 5.000 MHz | 793.01812 MHz | -20.84 dBm | -42.57 dB | -17.57 dB |
| 5.000 MHz | 12.500 MHz | 100.000 kHz | 5.000 MHz | 795.51812 MHz | -50.18 dBm | -71.91 dB | -36.91 dB |

Date: 23 JAN 2022 05:46:00

Lowest Channel / Full RB



CF 790.5 MHz 691 pts Span 25.0 MHz


Spectrum Emission Mask Standard: None

| Range Low | Range Up | RBW | Tx Bandwidth | Frequency | Power Abs | Power Rel | ALimit |
|-------------|------------|-------------|--------------|---------------|------------|-----------|-----------|
| -12.500 MHz | -5.000 MHz | 100.000 kHz | 5.000 MHz | 785.04710 MHz | -40.93 dBm | -62.05 dB | -27.05 dB |
| -5.000 MHz | -2.500 MHz | 100.000 kHz | 5.000 MHz | 787.98188 MHz | -27.54 dBm | -48.66 dB | -23.66 dB |
| 2.500 MHz | 5.000 MHz | 100.000 kHz | 5.000 MHz | 793.01812 MHz | -26.48 dBm | -49.59 dB | -24.59 dB |
| 5.000 MHz | 12.500 MHz | 100.000 kHz | 5.000 MHz | 795.51812 MHz | -39.54 dBm | -60.66 dB | -25.66 dB |

Date: 23 JAN 2022 05:35:57

LTE Band 14 / 5MHz / QPSK


Middle Channel / 1RB



CF 793.0 MHz 691 pts Span 25.0 MHz

| Range Low | Range Up | RBW | Frequency | Power Abs | Power Rel | ΔLimit |
|-------------|------------|-------------|---------------|------------|-----------|-----------|
| -12.500 MHz | -5.000 MHz | 100.000 kHz | 796.53261 MHz | -48.60 dBm | -71.87 dB | -36.67 dB |
| -5.000 MHz | -2.500 MHz | 100.000 kHz | 790.48188 MHz | -18.71 dBm | -42.38 dB | -17.38 dB |
| 2.500 MHz | 5.000 MHz | 100.000 kHz | 797.29348 MHz | -53.72 dBm | -77.39 dB | -52.39 dB |
| 5.000 MHz | 12.500 MHz | 100.000 kHz | 798.52536 MHz | -46.63 dBm | -69.70 dB | -34.70 dB |

Date: 23 JAN 2022 05:52:46




CF 793.0 MHz 691 pts Span 25.0 MHz

| Range Low | Range Up | RBW | Frequency | Power Abs | Power Rel | ΔLimit |
|-------------|------------|-------------|---------------|------------|-----------|-----------|
| -12.500 MHz | -5.000 MHz | 100.000 kHz | 797.47464 MHz | -45.52 dBm | -69.43 dB | -34.43 dB |
| -5.000 MHz | -2.500 MHz | 100.000 kHz | 788.67029 MHz | -53.26 dBm | -77.17 dB | -52.17 dB |
| 2.500 MHz | 5.000 MHz | 100.000 kHz | 795.51812 MHz | -17.40 dBm | -41.31 dB | -16.31 dB |
| 5.000 MHz | 12.500 MHz | 100.000 kHz | 799.46739 MHz | -46.36 dBm | -72.27 dB | -37.27 dB |

Date: 23 JAN 2022 05:51:01

Middle Channel / Full RB




CF 793.0 MHz 691 pts Span 25.0 MHz

| Range Low | Range Up | RBW | Frequency | Power Abs | Power Rel | ΔLimit |
|-------------|------------|-------------|---------------|------------|-----------|-----------|
| -12.500 MHz | -5.000 MHz | 100.000 kHz | 787.98188 MHz | -35.44 dBm | -58.38 dB | -23.38 dB |
| -5.000 MHz | -2.500 MHz | 100.000 kHz | 790.48188 MHz | -25.19 dBm | -48.12 dB | -23.12 dB |
| 2.500 MHz | 5.000 MHz | 100.000 kHz | 795.51812 MHz | -24.55 dBm | -47.48 dB | -22.48 dB |
| 5.000 MHz | 12.500 MHz | 100.000 kHz | 798.16304 MHz | -32.86 dBm | -55.80 dB | -20.80 dB |


Date: 23 JAN 2022 06:01:17

LTE Band 14 / 5MHz / 16QAM

Middle Channel / 1RB




Date: 23 JAN 2022 05:54:30



Date: 23 JAN 2022 05:49:23


Middle Channel / Full RB




Date: 23 JAN 2022 05:59:31

LTE Band 14 / 5MHz / 64QAM

Middle Channel / 1RB




Date: 23 JAN 2022 05:56:09



Date: 23 JAN 2022 05:47:39


Middle Channel / Full RB




Date: 23 JAN 2022 05:57:47

LTE Band 14 / 5MHz / QPSK

Highest Channel / 1RB




Date: 23 JAN 2022 06:11:14



Date: 23 JAN 2022 06:12:53


Highest Channel / Full RB




Date: 23 JAN 2022 06:02:56

LTE Band 14 / 5MHz / 16QAM

Highest Channel / 1RB




Date: 23 JAN 2022 06:09:34



Date: 23 JAN 2022 06:14:32


Highest Channel / Full RB




Date: 23 JAN 2022 06:04:35

LTE Band 14 / 5MHz / 64QAM

Highest Channel / 1RB




Date: 23 JAN 2022 06 07 54



Date: 23 JAN 2022 06 16 12


Highest Channel / Full RB




Date: 23 JAN 2022 06 06 15

LTE Band 14 / 10MHz / QPSK

Middle Channel / 1RB




Date: 23 JAN 2022 07:02:01



Date: 23 JAN 2022 06:59:42

Middle Channel / Full RB




Date: 23 JAN 2022 07:13:35




LTE Band 14 / 10MHz / 16QAM

Middle Channel / 1RB




Date: 23 JAN 2022 07:04:20



Date: 23 JAN 2022 06:57:23


Middle Channel / Full RB




Date: 23 JAN 2022 07:11:16

LTE Band 14 / 10MHz / 64QAM

Middle Channel / 1RB




Date: 23 JAN 2022 07:06:39



Date: 23 JAN 2022 06:55:05

Middle Channel / Full RB



Date: 23 JAN 2022 07:08:58



Frequency Stability

| Test Conditions | | LTE Band 14 (QPSK) / Middle Channel | Limit |
|------------------|-------------------|-------------------------------------|---------|
| Temperature (°C) | Voltage (Volt) | BW 10MHz | 1.25ppm |
| | | Deviation (ppm) | Result |
| 50 | Normal Voltage | 0.0011 | PASS |
| 40 | Normal Voltage | 0.0022 | |
| 30 | Normal Voltage | 0.0004 | |
| 20(Ref.) | Normal Voltage | 0.0000 | |
| 10 | Normal Voltage | 0.0012 | |
| 0 | Normal Voltage | 0.0034 | |
| -10 | Normal Voltage | 0.0005 | |
| -20 | Normal Voltage | 0.0006 | |
| -30 | Normal Voltage | 0.0023 | |
| 20 | Maximum Voltage | 0.0002 | |
| 20 | Normal Voltage | 0.0000 | |
| 20 | Battery End Point | 0.0024 | |

Note: Normal Voltage =3.85 V. ; Battery End Point (BEP) =3.6 V. ; Maximum Voltage =4.35 V.



Appendix B. Test Results of Radiated Test

Field Strength of Spurious Radiated

| | | | |
|-----------------|------------|---------------------|---------|
| Test Engineer : | Chris Chen | Temperature : | 22~23°C |
| | | Relative Humidity : | 41~42% |

| LTE Band 14 / 5MHz / QPSK | | | | | | | | |
|---------------------------|-------------------|-------------|---------------|-------------------|--------------------|----------------------|-------------------------|--------------------|
| Channel | Frequency (MHz) | ERP (dBm) | Limit (dBm) | Over Limit (dB) | S.G. Power (dBm) | TX Cable loss (dB) | TX Antenna Gain (dBi) | Polarization (H/V) |
| Lowest | 1576 | -58.06 | -42.15 | -15.91 | -60.69 | 1.09 | 5.87 | H |
| | 2368 | -61.34 | -13 | -48.34 | -63.74 | 1.37 | 5.92 | H |
| | 3152 | -59.42 | -13 | -46.42 | -63.31 | 1.64 | 7.68 | H |
| | 1576 | -55.03 | -42.15 | -12.88 | -57.66 | 1.09 | 5.87 | V |
| | 2368 | -59.64 | -13 | -46.64 | -62.04 | 1.37 | 5.92 | V |
| | 3152 | -58.51 | -13 | -45.51 | -62.40 | 1.64 | 7.68 | V |
| Middle | 1584 | -59.43 | -42.15 | -17.28 | -62.06 | 1.09 | 5.87 | H |
| | 2376 | -60.72 | -13 | -47.72 | -63.12 | 1.37 | 5.92 | H |
| | 3160 | -59.21 | -13 | -46.21 | -63.10 | 1.64 | 7.68 | H |
| | 1584 | -56.78 | -42.15 | -14.63 | -59.41 | 1.09 | 5.87 | V |
| | 2376 | -59.22 | -13 | -46.22 | -61.62 | 1.37 | 5.92 | V |
| | 3160 | -58.59 | -13 | -45.59 | -62.48 | 1.64 | 7.68 | V |
| Highest | 1584 | -60.92 | -42.15 | -18.77 | -63.55 | 1.09 | 5.87 | H |
| | 2376 | -61.19 | -13 | -48.19 | -63.59 | 1.37 | 5.92 | H |
| | 3176 | -59.65 | -13 | -46.65 | -63.54 | 1.64 | 7.68 | H |
| | 1584 | -57.02 | -42.15 | -14.87 | -59.65 | 1.09 | 5.87 | V |
| | 2376 | -58.51 | -13 | -45.51 | -60.91 | 1.37 | 5.92 | V |
| | 3176 | -59.35 | -13 | -46.35 | -63.24 | 1.64 | 7.68 | V |

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.

| LTE Band 14 / 10MHz / QPSK | | | | | | | | |
|----------------------------|-------------------|--------------|---------------|-------------------|--------------------|----------------------|-------------------------|--------------------|
| Channel | Frequency (MHz) | EIRP (dBm) | Limit (dBm) | Over Limit (dB) | S.G. Power (dBm) | TX Cable loss (dB) | TX Antenna Gain (dBi) | Polarization (H/V) |
| Middle | 1576 | -61.63 | -42.15 | -19.48 | -64.26 | 1.09 | 5.87 | H |
| | 2368 | -61.06 | -13 | -48.06 | -63.46 | 1.37 | 5.92 | H |
| | 3152 | -59.66 | -13 | -46.66 | -63.55 | 1.64 | 7.68 | H |
| | 1576 | -60.03 | -42.15 | -17.88 | -62.66 | 1.09 | 5.87 | V |
| | 2368 | -59.54 | -13 | -46.54 | -61.94 | 1.37 | 5.92 | V |
| | 3152 | -59.54 | -13 | -46.54 | -63.43 | 1.64 | 7.68 | V |

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.