

EMC TEST REPORT



Applicant:	Sonim Technologies, Inc.
Address:	1825 S. Grant St., Suite 200., San Mateo, CA, 94402

Manufacturer or Supplier	Sonim Technologies (Shenzhen) Limited
Address	2nd Floor, No. 2 Building Phase B, Daqian Industrial park, Longchang Road, 67 District, Baoan, Shenzhen, P. R. China
Product	Mobile Phone
Brand Name	Sonim
Model Name	XP8800
FCC ID	WYPPC4000
Date of tests	Oct. 27, 2017 ~ Nov. 22, 2017

The submitted sample of the above equipment has been tested for according to the requirements of the following standards:

- ☒ **FCC Part 15, Subpart B, Class B**
- ☒ **ANSI C63.4:2014**

CONCLUSION: The submitted sample was found to COMPLY with the test requirement

Issued by Jimmy Yan Engineer / Mobile Department	Approved by Bill Yao Manager / Mobile Department
	
Date: Nov. 23, 2017	Date: Nov. 23, 2017

This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification

TABLE OF CONTENTS

RELEASE CONTROL RECORD	3
1 GENERAL INFORMATION	4
1.1 GENERAL DESCRIPTION OF EUT	4
1.2 SUMMARY OF TEST RESULTS	7
1.3 MEASUREMENT UNCERTAINTY	7
1.4 DESCRIPTION OF TEST MODES	8
1.5 DESCRIPTION OF SUPPORT UNITS	10
1.6 CONFIGURATION OF SYSTEM UNDER TEST	11
2 EMISSION TEST	12
2.1 CONDUCTED EMISSION MEASUREMENT	12
2.1.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT	12
2.1.2 TEST INSTRUMENTS	12
2.1.3 TEST PROCEDURES	13
2.1.4 DEVIATION FROM TEST STANDARD	13
2.1.5 TEST SETUP	14
2.1.6 EUT OPERATING CONDITIONS	14
2.1.7 TEST RESULTS	15
2.2 RADIATED EMISSION MEASUREMENT	17
2.2.1 LIMITS OF RADIATED EMISSION MEASUREMENT	17
2.2.2 TEST INSTRUMENTS	19
2.2.3 TEST PROCEDURE	20
2.2.4 DEVIATION FROM TEST STANDARD	21
2.2.5 TEST SETUP	22
2.2.6 EUT OPERATING CONDITIONS	22
2.2.7 TEST RESULTS	23
3 APPENDIX A – MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB	27



Test Report No.: FV170730W002

RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
FV170730W002	Original release	Nov. 23, 2017

1 GENERAL INFORMATION

1.1 GENERAL DESCRIPTION OF EUT

PRODUCT	Mobile Phone	
BRAND NAME	Sonim	
MODEL NAME	XP8800	
TYPE NUMBER	PC4011/PT4000	
NOMINAL VOLTAGE	5/9Vdc (adapter or host equipment) 3.85Vdc (Li-ion, battery)	
BATTERY	Brand Name: Sonim Model Name: BAT-04900-01S Power Rating: DC 3.85V, 4900mAh, Li-ion	
MODULATION TYPE	WLAN	CCK, DQPSK, DBPSK for DSSS 64QAM, 16QAM, QPSK, BPSK for OFDM
	BT_LE	BT-LE(GFSK) for DTS
	Bluetooth	GFSK, $\pi/4$ -DQPSK, 8DPSK
	GPS/ Glonass	C/A code
	GSM	GMSK
	WCDMA	BPSK/QPSK
	CDMA	GMSK
	LTE	QPSK/16QAM
	NFC	ASK
	FM	FSK
OPERATING FREQUENCY	WLAN	2412 ~ 2472MHz for 11b/g/n(HT20) 2422 ~ 2462MHz for 11n(HT40) 5150 ~ 5250MHz, 5250 ~ 5350MHz, 5470 ~ 5725MHz, 5725 ~ 5825MHz for 11a/n(HT20)/n(HT40)/ac(HT80)
	Bluetooth/BT_LE	2402MHz ~ 2480MHz
	GPS	1575.42MHz
	GLONASS	1602MHz
	GSM	824.2MHz ~ 848.8MHz (FOR GSM 850) 1850.2MHz ~ 1909.8MHz (FOR GSM 1900)
	WCDMA	1852.4MHz ~ 1907.6MHz (FOR WCDMA Band 2) 1710.7MHz ~ 1754.3MHz (FOR WCDMA Band 4) 826.4MHz ~ 846.6MHz (FOR WCDMA Band 5)

OPERATING FREQUENCY	CDMA	806MHz ~ 901MHz (FOR CDMA BC10) 824MHz ~ 849MHz (FOR CDMA BC0) 1850MHz ~ 1910MHz (FOR CDMA BC1)
	LTE	1850.7MHz ~ 1909.3MHz (FOR LTE Band2) 1710.7MHz ~ 1754.3MHz (FOR LTE Band4) 824MHz ~ 849MHz (FOR LTE Band5) 2502.5MHz ~ 2567.5MHz (FOR LTE Band7) 699MHz ~ 716MHz (FOR LTE Band12) 777MHz ~ 787MHz (FOR LTE Band13) 788MHz ~ 798MHz (FOR LTE Band14) 1850MHz ~ 1915MHz (FOR LTE Band25) 814MHz ~ 849MHz (FOR LTE Band26) 2305MHz ~ 2315MHz (FOR LTE Band30) 2570MHz ~ 2620MHz (FOR LTE Band38) 2305MHz ~ 2315MHz (FOR LTE Band40) 2496MHz ~ 2690MHz (FOR LTE Band41) 1710MHz ~ 1780MHz (FOR LTE Band66)
	NFC	13.56MHz
	FM	98MHz
HW VERSION	A	
SW VERSION	8A.0.0-00-7.1.1-00.01.26	
I/O PORTS	Refer to user's manual	
CABLE SUPPLIED	USB cable 1: With shield, detachable, 1.5meter USB cable 2: non-shielded, detachable, 1.0meter	
ACCESSORY DEVICES	Refer to note as below	

NOTE:

- For a more detailed features description, please refer to the manufacturer's specifications or the user's manual.
- The EUT was powered by the following adapter:

ADAPTER	
BRAND:	Sonim
MODEL:	S42A02
INPUT:	AC 100-240V, 500mA
OUTPUT:	DC 5V, 1500mA
	DC 9V, 1500mA
	DC 12V, 1100mA

- The EUT matched the following USB cables:

USB CABLE 1	
BRAND:	N/A
MODEL:	N/A
SIGNAL LINE:	1.5 METER



Test Report No.: FV170730W002

USB CABLE 2	
BRAND:	N/A
MODEL:	N/A
SIGNAL LINE:	1.0 METER

4. For the test results, the EUT had been tested with all conditions. But only the worst case was shown in test report.

1.2 SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

APPLIED STANDARD: FCC Part 15, Subpart B			
Standard Section	Test Item	Result	Remark
FCC Part 15, Subpart B, Class B ANSI C63.4:2014	Conducted Test	PASS	Meets limits minimum passing margin is -13.15dB at 16.360000MHz.
	Radiated Emission Test (30MHz ~ 1GHz)	PASS	Meets Class B Limit Minimum passing margin is -1.2dB at 63.95MHz
	Radiated Emission Test (Above 1GHz)	PASS	Meets Class B Limit Minimum passing margin is -14.44dB at 3585MHz

1.3 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

MEASUREMENT	FREQUENCY	UNCERTAINTY
Conducted emissions	150kHz ~ 30MHz	+/-2.66dB
Radiated emissions	30MHz ~ 1GHz	+/-3.26dB
	1GHz ~ 18GHz	+/-4.48dB

1.4 DESCRIPTION OF TEST MODES

For Conducted Emission evaluation, 240Vac/60Hz & 120/60Hz had been covered during the pre-test. The worst data was found at **120Vac/60Hz** and recorded in the applied test report.

Test Mode	Test Condition
Radiated emission test	
1	GSM850 Idle+ Adapter+ Earphone+ USB cable 1+ BT Idle+ WIFI Idle(2.4G)+ GPS Rx
2	GSM1900 Idle+ Adapter+ Earphone+ USB cable 2+ BT Idle+ WIFI Idle(5G)+ Glonass Rx
3	WCDMA B2 Idle+ Adapter+ Earphone+ USB cable 1+ BT Idle+ WIFI Idle(2.4G)+ GPS Rx
4	WCDMA B4 Idle+ Adapter+ Earphone+ USB cable 2+ BT Idle+ WIFI Idle(5G)+ Glonass Rx
5	WCDMA B5 Idle+ Adapter+ Earphone+ USB cable 1+ BT Idle+ WIFI Idle(2.4G)+ GPS Rx
6	LTE B2 Idle+ Adapter+ Earphone+ USB cable 2+ BT Idle+ WIFI Idle(5G)+ Glonass Rx
7	LTE B4 Idle+ Adapter+ Earphone+ USB cable 1+ BT Idle+ WIFI Idle(2.4G)+ GPS Rx
8	LTE B5 Idle+ Adapter+ Earphone+ USB cable 2+ BT Idle+ WIFI Idle(5G)+ Glonass Rx
9	LTE B7 Idle+ Adapter+ Earphone+ USB cable 2+ BT Idle+ WIFI Idle(5G)+ Glonass Rx
10	LTE B12 Idle+ Adapter+ Earphone+ USB cable 1+ BT Idle+ WIFI Idle(2.4G)+ GPS Rx
11	LTE B13 Idle+ Adapter+ Earphone+ USB cable 2+ BT Idle+ WIFI Idle(5G)+ Glonass Rx
12	LTE B14 Idle+ Adapter+ Earphone+ USB cable 1+ BT Idle+ WIFI Idle(2.4G)+ GPS Rx+ NFC Idle
13	LTE B25 Idle+ Adapter+ Earphone+ USB cable 2+ BT Idle+ WIFI Idle(5G)+ Glonass Rx+ MPEG4
14	LTE B26 Idle+ Adapter+ Earphone+ USB cable 1+ BT Idle+ WIFI Idle(2.4G)+ GPS Rx+ FM Rx
15	LTE B30 Idle+ Adapter+ Earphone+ USB cable 2+ BT Idle+ WIFI Idle(5G)+ Glonass Rx+ Front camera on
16	LTE B38 Idle+ Adapter+ Earphone+ USB cable 1+ BT Idle+ WIFI Idle(2.4G)+ GPS Rx+ Back camera on
17	LTE B40 Idle+ Adapter+ Earphone+ USB cable 2+ BT Idle+ WIFI Idle(5G)+ Glonass Rx
18	LTE B41 Idle+ Adapter+ Earphone+ USB cable 1+ BT Idle+ WIFI Idle(2.4G)+ GPS Rx
19	LTE B66 Idle+ Adapter+ Earphone+ USB cable 1+ BT Idle+ WIFI Idle(2.4G)+ GPS Rx
20	CDMA BC0 Idle + Adapter+ Earphone+ USB cable 2+ BT Idle+ WIFI Idle(5G)+ Glonass Rx
21	CDMA BC1 Idle + Adapter+ Earphone+ USB cable 1+ BT Idle+ WIFI Idle(2.4G)+ GPS Rx
22	CDMA BC10 Idle + Adapter+ Earphone+ USB cable 2+ BT Idle+ WIFI Idle(5G)+ Glonass Rx
Conducted emission test	
1	GSM850 Idle+ Adapter+ Earphone+ USB cable 1+ BT Idle+ WIFI Idle(2.4G)+ GPS Rx
2	GSM1900 Idle+ Adapter+ Earphone+ USB cable 2+ BT Idle+ WIFI Idle(5G)+ Glonass Rx
3	WCDMA B2 Idle+ Adapter+ Earphone+ USB cable 1+ BT Idle+ WIFI Idle(2.4G)+ GPS Rx
4	WCDMA B4 Idle+ Adapter+ Earphone+ USB cable 2+ BT Idle+ WIFI Idle(5G)+ Glonass Rx
5	WCDMA B5 Idle+ Adapter+ Earphone+ USB cable 1+ BT Idle+ WIFI Idle(2.4G)+ GPS Rx
6	LTE B2 Idle+ Adapter+ Earphone+ USB cable 2+ BT Idle+ WIFI Idle(5G)+ Glonass Rx

**Test Report No.: FV170730W002**

7	LTE B4 Idle+ Adapter+ Earphone+ USB cable 1+ BT Idle+ WIFI Idle(2.4G)+ GPS Rx
8	LTE B5 Idle+ Adapter+ Earphone+ USB cable 2+ BT Idle+ WIFI Idle(5G)+ Glonass Rx
9	LTE B7 Idle+ Adapter+ Earphone+ USB cable 2+ BT Idle+ WIFI Idle(5G)+ Glonass Rx
10	LTE B12 Idle+ Adapter+ Earphone+ USB cable 1+ BT Idle+ WIFI Idle(2.4G)+ GPS Rx
11	LTE B13 Idle+ Adapter+ Earphone+ USB cable 2+ BT Idle+ WIFI Idle(5G)+ Glonass Rx
12	LTE B14 Idle+ Adapter+ Earphone+ USB cable 1+ BT Idle+ WIFI Idle(2.4G)+ GPS Rx+ NFC Idle
13	LTE B25 Idle+ Adapter+ Earphone+ USB cable 2+ BT Idle+ WIFI Idle(5G)+ Glonass Rx+ MPEG4
14	LTE B26 Idle+ Adapter+ Earphone+ USB cable 1+ BT Idle+ WIFI Idle(2.4G)+ GPS Rx+ FM Rx
15	LTE B30 Idle+ Adapter+ Earphone+ USB cable 2+ BT Idle+ WIFI Idle(5G)+ Glonass Rx+ Front camera on
16	LTE B38 Idle+ Adapter+ Earphone+ USB cable 1+ BT Idle+ WIFI Idle(2.4G)+ GPS Rx+ Back camera on
17	LTE B40 Idle+ Adapter+ Earphone+ USB cable 2+ BT Idle+ WIFI Idle(5G)+ Glonass Rx
18	LTE B41 Idle+ Adapter+ Earphone+ USB cable 1+ BT Idle+ WIFI Idle(2.4G)+ GPS Rx
19	LTE B66 Idle+ Adapter+ Earphone+ USB cable 2+ BT Idle+ WIFI Idle(5G)+ Glonass Rx

NOTE:

1. For conducted emission test, test mode 1 was the worst case and only this mode was presented in this report.
2. For radiated emission test, test mode 18 was the worst case and only this mode was presented in this report

1.5 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.


FOR EMISSION TESTS

NO.	PRODUCT	BRAND	MODEL NO.	SERIAL NO.	FCC ID
1	Earphone	N/A	N/A	N/A	N/A
2	Notebook	N/A	N/A	N/A	N/A
3	Printer	N/A	N/A	N/A	N/A
4	Bluetooth Earphone	N/A	N/A	N/A	N/A

NO.	SIGNAL CABLE DESCRIPTION OF THE ABOVE SUPPORT UNITS
1	N/A
2	N/A
3	N/A
4	N/A

1.6 CONFIGURATION OF SYSTEM UNDER TEST

Test configuration



2 EMISSION TEST

2.1 CONDUCTED EMISSION MEASUREMENT

2.1.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT

TEST STANDARD: FCC Part 15, Subpart B (Section: 15.107)

FREQUENCY OF EMISSION (MHz)	CONDUCTED LIMIT (dBμV)	
	Quasi-peak	Average
0.15 ~ 0.5	66 to 56	56 to 46
0.5 ~ 5	56	46
5 ~ 30	60	50

- NOTE:**
1. The lower limit shall apply at the transition frequencies.
 2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.
 3. All emanations from a class A/B digital device or system, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strengths specified above.

2.1.2 TEST INSTRUMENTS

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
EMI Test Receiver	Rohde&Schwarz	ESR3	101900	Jun. 28,17	Jun. 27,18
EMC32 test software	Rohde&Schwarz	EMC32	NA	NA	NA
LISN network	Rohde&Schwarz	ENV216	101922	Sep. 18,17	Sep. 17,18

- NOTE:**
1. The test was performed in CE shielded room.
 2. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to CEPREI/CHINA, GRGT/CHINA and NIM/CHINA.

2.1.3 TEST PROCEDURES


- a. The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- c. The frequency range from 150 kHz to 30MHz was searched. Emission levels under (Limit - 20dB) were not recorded.

NOTE: All modes of operation were investigated and the worst-case emissions are reported.

2.1.4 DEVIATION FROM TEST STANDARD

No deviation.

2.1.5 TEST SETUP



**Note: 1.Support units were connected to second LISN.
2.Both of LISNs (AMN) are 80 cm from EUT and at least 80
from other units and other metal planes**

For the actual test configuration, please refer to the attached file (Test Setup Photo).

2.1.6 EUT OPERATING CONDITIONS

- a. Turned on the power and connected of all equipment.
- b. EUT was operated according to the use type described in the manufacturer's specifications or the user's manual.



Test Report No.: FV170730W002


2.1.7 TEST RESULTS

TEST VOLTAGE	DC 5/9V From Adapter Input 120 Vac, 60 Hz	Detector Function & Resolution Bandwidth	Quasi-Peak (QP) / Average (AV), 9 kHz
ENVIRONMENTAL CONDITIONS	23deg. C, 52RH	TESTED BY	Jocan Guo

Frequency (MHz)	QuasiPeak (dB μ V)	CAverage (dB μ V)	Limit (dB μ V)	Margin (dB)	Line	Filter	Corr. (dB)
0.162000	---	22.47	55.36	-32.89	L1	ON	9.6
0.162000	38.51	---	65.36	-26.85	L1	ON	9.6
0.204000	---	21.43	53.45	-32.02	L1	ON	9.7
0.204000	36.18	---	63.45	-27.27	L1	ON	9.7
0.496000	---	12.28	46.07	-33.79	L1	ON	9.7
0.496000	27.56	---	56.07	-28.51	L1	ON	9.7
0.832000	---	8.86	46.00	-37.14	L1	ON	9.7
0.832000	19.97	---	56.00	-36.03	L1	ON	9.7
16.312000	---	26.63	50.00	-23.37	L1	ON	9.9
16.312000	39.35	---	60.00	-20.65	L1	ON	9.9
19.576000	---	25.24	50.00	-24.76	L1	ON	9.9
19.576000	38.40	---	60.00	-21.60	L1	ON	9.9

- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
 2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
 3. The emission levels of other frequencies were very low against the limit.
 4. Margin value = Emission level - Limit value
 5. Correction factor = Insertion loss + Cable loss
 6. Emission Level = Correction Factor + Reading Value.

Full Spectrum




TEST VOLTAGE	DC 5/9V From Adapter Input 120 Vac, 60 Hz	Detector Function & Resolution Bandwidth	Quasi-Peak (QP) / Average (AV), 9 kHz
ENVIRONMENTAL CONDITIONS	23deg. C, 52RH	TESTED BY	Jocan Guo

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Filter	Corr. (dB)
0.158000	---	29.65	55.57	-25.92	N	ON	10.1
0.158000	45.03	---	65.57	-20.54	N	ON	10.1
0.180000	---	26.13	54.49	-28.36	N	ON	10.2
0.180000	42.21	---	64.49	-22.28	N	ON	10.2
0.484000	---	18.21	46.27	-28.06	N	ON	10.1
0.484000	32.06	---	56.27	-24.21	N	ON	10.1
4.560000	---	20.52	46.00	-25.48	N	ON	9.8
4.560000	29.62	---	56.00	-26.38	N	ON	9.8
16.360000	---	36.85	50.00	-13.15	N	ON	10.0
16.360000	45.80	---	60.00	-14.20	N	ON	10.0
19.448000	---	35.55	50.00	-14.45	N	ON	10.0
19.448000	45.15	---	60.00	-14.85	N	ON	10.0

- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
 2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
 3. The emission levels of other frequencies were very low against the limit.
 4. Margin value = Emission level - Limit value
 5. Correction factor = Insertion loss + Cable loss
 6. Emission Level = Correction Factor + Reading Value.

Full Spectrum



2.2 RADIATED EMISSION MEASUREMENT

2.2.1 LIMITS OF RADIATED EMISSION MEASUREMENT

TEST STANDARD: FCC Part 15, Subpart B (Section: 15.109)

Emissions radiated outside of the specified bands, shall be according to the general radiated limits as following:

Radiated Emissions Limits at 10 meters (dBμV/m)				
Frequencies (MHz)	FCC 15B/ ICES-003, Class A	FCC 15B / ICES-003, Class B	CISPR 22, Class A	CISPR 22, Class B
30-88	39	29.5	40	30
88-216	43.5	33.1		
216-230	46.4	35.6		
230-960			47	37
960-1000	49.5	43.5		
1000-3000	Avg: 49.5	Avg: 43.5	Not defined	Not defined
3000+	Peak: 69.5	Peak: 63.5	Not defined	Not defined

Radiated Emissions Limits at 3 meters (dBμV/m)				
Frequencies (MHz)	FCC 15B / ICES-003, Class A	FCC 15B / ICES-003, Class B	CISPR 22, Class A	CISPR 22, Class B
30-88	49.5	40	50.5	40.5
88-216	54	43.5		
216-230	56.9	46		
230-960			57.5	47.5
960-1000	60	54		
1000-3000	Avg: 60 Peak: 80	Avg: 54 Peak: 74	Avg: 56 Peak: 76	Avg: 50 Peak: 70
3000+			Avg: 60 Peak: 80	Avg: 54 Peak: 74

Frequency Range (For unintentional radiators)

Highest frequency generated or used in the device or on which the device operates or tunes (MHz)	Upper frequency of measurement range (MHz)
Below 1.705	30
1.705-108	1000
108-500	2000
500-1000	5000
Above 1000	5 th harmonic of the highest frequency or 40GHz, whichever is lower

- NOTE:**
1. The lower limit shall apply at the transition frequencies.
 2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
 3. As shown in 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.
 4. QP detector shall be applied if not specified.

2.2.2 TEST INSTRUMENTS

Frequency range below 1GHz

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
3m Semi-anechoic Chamber	ETS-LINDGREN	9m*6m*6m	Euroshieldpn-CT0001143-1216	May 06,17	May 05,18
Bilog Antenna	ETS-LINDGREN	3143B	00161965	Nov. 26,16	Nov. 25,18
MXE EMI Receiver	KEYSIGHT	N9038A-544	MY54450026	Mar. 10,17	Mar. 09,18
Signal Pre-Amplifier	EMSI	EMC 9135	980249	Jul. 24,17	Jul. 23,18

Frequency range above 1GHz

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
3m Semi-anechoic Chamber	ETS-LINDGREN	9m*6m*6m	Euroshieldpn-CT0001143-1216	May 06,17	May 05,18
Horn Antenna	ETS-LINDGREN	3117	00168728	Nov. 26,16	Nov. 25,18
MXE EMI Receiver	KEYSIGHT	N9038A-544	MY54450026	Mar. 10,17	Mar. 09,18
Signal Pre-Amplifier	EMSI	EMC 012645B	980257	Jul. 24,17	Jul. 23,18

- NOTE:**
1. The test was performed in 3m chamber.
 2. The calibration interval of the above test instruments is 12 months or 24 months and the calibrations are traceable to CEPREI/CHINA, GRGT/CHINA and NIM/CHINA.
 3. The FCC Site Registration No. is 525120.

2.2.3 TEST PROCEDURE

<Frequency Range below 1GHz>

The basic test procedure was in accordance with ANSI C63.4:2014 (section 12).

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber room. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The height of antenna is varied from 1 meter to 4 meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1GHz.

NOTE:

1. The resolution bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection (QP) at frequency below 1GHz.
2. $\text{Emission level(dBuV/m)} = \text{Raw Value(dBuV)} + \text{Correction Factor(dB/m)}$
3. $\text{Correction Factor(dB/m)} = \text{Antenna Factor (dB/m)} + \text{Cable Factor (dB)}$ (if the raw value not contains the amplifier);
4. $\text{Correction Factor(dB/m)} = \text{Antenna Factor (dB/m)} + \text{Cable Factor (dB)} - \text{Amplifier Gain(dB)}$ (if the raw value contains the amplifier).
5. $\text{Margin value} = \text{Emission level} - \text{Limit value}$.

<Frequency Range above 1GHz>

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter fully-anechoic chamber room. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. The bore sight should be used during the test above 1GHz.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to peak and average detect function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz

NOTE:


1. The resolution bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection (QP) at frequency below 1GHz.
2. The resolution bandwidth is 1MHz and video bandwidth of test receiver/spectrum analyzer is 3MHz for Peak detection at frequency above 1GHz. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and video bandwidth of test receiver/spectrum analyzer is 10Hz for Average detection (AV) at frequency above 1GHz.
3. For measurement of frequency above 1000 MHz, the EUT was set 3 meters away from the receiver antenna.
4. $\text{Emission level(dBuV/m)} = \text{Raw Value(dBuV)} + \text{Correction Factor(dB/m)}$
5. $\text{Correction Factor(dB/m)} = \text{Antenna Factor (dB/m)} + \text{Cable Factor (dB)}$ (if the raw value not contains the amplifier);
6. $\text{Correction Factor(dB/m)} = \text{Antenna Factor (dB/m)} + \text{Cable Factor (dB)} - \text{Amplifier Gain(dB)}$ (if the raw value contains the amplifier)
7. $\text{Margin value} = \text{Emission level} - \text{Limit value.}$

2.2.4 DEVIATION FROM TEST STANDARD


No deviation.

2.2.5 TEST SETUP

<Frequency Range below 1GHz>



<Frequency Range above 1GHz>



* : depends on the EUT height and the antenna 3dB beamwidth both, refer to section 7.3 of CISPR 16-2-3.

2.2.6 EUT OPERATING CONDITIONS


Same as item 2.1.6.

2.2.7 TEST RESULTS

TEST VOLTAGE	DC 5/9V From Adapter Input 120 Vac, 60 Hz	FREQUENCY RANGE	30-1000 MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70 %RH	DETECTOR FUNCTION & RESOLUTION BANDWIDTH	Quasi-Peak, 120 kHz
TESTED BY	Simon Yang		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
63.95	34.4	63.88	40	-5.6	6.6	1.22	37.3	100	39	QP
97.9	30.04	57.75	43.5	-13.46	7.77	1.52	37	100	163	QP
144.46	32.09	58.52	43.5	-11.41	8.54	1.85	36.82	100	244	QP
242.43	41.76	63.82	46	-4.24	12.05	2.41	36.52	100	85	QP
399.57	35.68	52.07	46	-10.32	17.18	3.15	36.72	100	112	QP
825.4	40.26	50.13	46	-5.74	23	4.75	37.62	100	300	QP


- REMARKS:**
1. Peak detector quick scan is showed on the graph and final quasi-peak detector data is measured corresponding to relevant limit and recorded in the data table.
 2. Negative sign (-) in the margin column signify levels below the limit.
 3. Frequency range scanned: 30MHz to 1000MHz.
 4. Only emissions significantly above equipment noise floor are reported.



TEST VOLTAGE	DC 5/9V From Adapter Input 120 Vac, 60 Hz	FREQUENCY RANGE	30-1000 MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70 %RH	DETECTOR FUNCTION & RESOLUTION BANDWIDTH	Quasi-Peak, 120 kHz
TESTED BY	Simon Yang		

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
63.95	38.8	68.28	40	-1.2	6.6	1.22	37.3	223	237	QP
97.9	35.12	62.83	43.5	-8.38	7.77	1.52	37	200	55	QP
144.46	30.68	57.11	43.5	-12.82	8.54	1.85	36.82	200	157	QP
177.44	31.71	56.43	43.5	-11.79	9.94	2.04	36.7	200	306	QP
242.43	36.73	58.79	46	-9.27	12.05	2.41	36.52	200	247	QP
673.11	39.69	50.46	46	-6.31	22.35	4.21	37.33	200	98	QP

- REMARKS:**
1. Peak detector quick scan is showed on the graph and final quasi-peak detector data is measured corresponding to relevant limit and recorded in the data table.
 2. Negative sign (-) in the margin column signify levels below the limit.
 3. Frequency range scanned: 30MHz to 1000MHz.
 4. Only emissions significantly above equipment noise floor are reported.




TEST VOLTAGE	DC 5/9V From Adapter Input 120 Vac, 60 Hz	FREQUENCY RANGE	1-18 GHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70 %RH	DETECTOR FUNCTION & RESOLUTION BANDWIDTH	Peak/Average, 1 MHz
TESTED BY	Simon Yang		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
1755	35.86	46.98	54	-18.14	30.33	6.9	48.35	100	36	Average
1755	44.27	55.39	74	-29.73	30.33	6.9	48.35	100	36	Peak
2585	37.29	44.61	54	-16.71	32.49	8.5	48.31	100	95	Average
2585	44.94	52.26	74	-29.06	32.49	8.5	48.31	100	95	Peak
3585	39.56	44.76	54	-14.44	33.14	10.1	48.44	100	172	Average
3585	50.27	55.47	74	-23.73	33.14	10.1	48.44	100	172	Peak

REMARKS:

1. Peak detector quick scan is showed on the graph and final quasi-peak detector data is measured corresponding to relevant limit and recorded in the data table.
2. Negative sign (-) in the margin column signify levels below the limit.
3. Frequency range scanned: 1GHz to 18GHz.
4. Only emissions significantly above equipment noise floor are reported.




TEST VOLTAGE	DC 5/9V From Adapter Input 120 Vac, 60 Hz	FREQUENCY RANGE	1-18 GHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70 %RH	DETECTOR FUNCTION & RESOLUTION BANDWIDTH	Peak/Average, 1 MHz
TESTED BY	Simon Yang		

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
1755	36.24	47.36	54	-17.76	30.33	6.9	48.35	100	40	Average
1755	46.36	57.48	74	-27.64	30.33	6.9	48.35	100	40	Peak
2770	37.83	44.67	54	-16.17	32.67	8.81	48.32	100	86	Average
2770	46.61	53.45	74	-27.39	32.67	8.81	48.32	100	86	Peak
3555	39.21	44.51	54	-14.79	33.09	10.04	48.43	100	156	Average
3555	47.8	53.1	74	-26.2	33.09	10.04	48.43	100	156	Peak

REMARKS:

1. Peak detector quick scan is showed on the graph and final quasi-peak detector data is measured corresponding to relevant limit and recorded in the data table.
2. Negative sign (-) in the margin column signify levels below the limit.
3. Frequency range scanned: 1GHz to 18GHz.
4. Only emissions significantly above equipment noise floor are reported.





Test Report No.: FV170730W002

3 APPENDIX A – MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB

No any modifications were made to the EUT by the lab during the test.

---END---