

Test report No:
NIE: 69157RAN.002

Assessment report RF EXPOSURE REPORT ACCORDING TO FCC 47 CFR Part 2.1093

(*) Identification of item under evaluation	Rechargeable wireless hearing instrument
(*) Trademark	ReSound, Beltone
(*) Model and /or type reference	CABR70
(*) Other identification of the product	HW version: PCBA,CAM BTE70 RHI,V1.A,C6.0 SW Version: Dooku2 FCC ID: XC26CABR70 IC ID: 6941C-CABR70
(*) Features	BT 1/2Mbit, proximity & MI radio, rechargeable battery, IP68 enclosure
(*) Manufacturer	GN HEARING A/S Lautrupbjerg 7, 2750 Ballerup, Denmark
Test method requested, standard	FCC 47 CFR Part 2.1093. Radiofrequency radiation exposure evaluation: portable devices
Summary	IN COMPLIANCE
Approved by (name / position & signature)	Miguel Lacave Antennas Lab Manager
Date of issue	2022-02-08
Report template No	FAN24_02 (* "Data provided by the client")

Index

Competences and guarantees	3
General conditions	3
Data provided by the client.....	3
Identification of the client.....	3
Document history	3
Appendix A: FCC RF Exposure assessment result	4
General description of the device under evaluation	5
Evaluation Results.....	6
Appendix B: FCC RF Exposure information	7
FCC SAR test exclusion considerations for portable devices	8

Competences and guarantees

In order to assure the traceability to other national and international laboratories, DEKRA Testing and Certification, S.A.U. has a calibration and maintenance program for its measurement equipment.

DEKRA Testing and Certification, S.A.U. guarantees the reliability of the data presented in this report, which is the result of the measurements and the tests performed to the item under test on the date and under the conditions stated on the report and, it is based on the knowledge and technical facilities available at DEKRA Testing and Certification, S.A.U. at the time of performance of the test.

DEKRA Testing and Certification, S.A.U. is liable to the client for the maintenance of the confidentiality of all information related to the item under test and the results of the test.

The results presented in this Assessment Report apply only to the particular item under test established in this document.

IMPORTANT: No parts of this report may be reproduced or quoted out of context, in any form or by any means, except in full, without the previous written permission of DEKRA Testing and Certification, S.A.U.

General conditions

1. This report is only referred to the item that has undergone the assessment.
2. This report does not constitute or imply on its own an approval of the product by the Certification Bodies or competent Authorities.
3. This document is only valid if complete; no partial reproduction can be made without previous written permission of DEKRA Testing and Certification, S.A.U.
4. This test report cannot be used partially or in full for publicity and/or promotional purposes without previous written permission of DEKRA Testing and Certification, S.A.U. and the Accreditation Bodies

Data provided by the client

The following data has been provided by the client:

1. Information relating to the description of the sample ("Identification of the item tested", "Trademark", "Model and/or type reference tested", "Other identification of the product", "Features", "Manufacturer" and "General description of the device").
2. Maximum output power, maximum antenna gain and use distance information.

DEKRA Testing and Certification, S.A.U. declines any responsibility with respect to the information provided by the client and that may affect the validity of results.

Identification of the client

Company name: GN HEARING A/S

Postal address: Lautrupbjerg 7, 2750 Ballerup, Denmark

Contact person: Søren Carlsen

Telephone / e-mail: +45 28110360 / scarlsen@gnhearing.com

Document history

Report number	Date	Description
69157RAN.002	2022-02-08	First release

Appendix A: FCC RF Exposure assessment result

General description of the device under evaluation

The device under evaluation consists of a rechargeable wireless hearing aid.

According to the manufacturer, during its normal use, the separation distance between the radiating structures of the device and nearby users will be greater than 0 cm. In order to perform the assessment a conservative evaluation distance of 0 cm has been used.

The equipment specifications for each supported technology are shown in Table 1. Values corresponding to Proximity and Bluetooth Radios have been measured and stated into DEKRA Testing and Certification, S.A.U. test reports num. 69157RRF.005 and 69157RRF.006.

Values corresponding to Mi Radio technology have been declared by the manufacturer into page 87 of the “CABR70 Operational_description” document.

Technology / Mode	Band	Frequency (MHz)	Maximum Conducted Output Power (dBm)	Duty Cycle (%)	Time Averaged Conducted Power (dBm)	Antenna peak gain (dBi)	Maximum Averaged E.I.R.P. (dBm)	Maximum Averaged E.I.R.P. (mW)
Property Proximity	2.4 GHz	2402 - 2480	10.10	6.20	-1.98	-7.40	-9.38	0.12
BTLE	2.4 GHz	2402 - 2480	10.10	7.40	-1.21	-7.40	-8.61	0.14
Mi Radio	LF	10.667	-6.00	50.00	-9.01	N/A	-9.01	0.13

Table 1: Equipment specifications

Evaluation Results

The evaluation according to the minimum intended use distance of 0 mm (5mm applied for the evaluation according to KDB 447498 D01 General RF Exposure Guidance, see Appendix B for additional information) will be as follow:

Technology / Mode	Band	Frequency (MHz)	Distance (cm)	Maximum Conducted output power (mW)	Limit (mW)	Verdict
BTLE	2.4 GHz	2400 - 2483.5	0.50	0.76	1.00	Pass
Property Proximity	2.4 GHz	2402 - 2480	0.50	0.63	1.00	Pass
Mi Radio	LF	10.667	0.50	0.13	1.00	Pass

Table 2: FCC Evaluation Result

The computed value(s) are below the limit(s), so according to KDB 447498 D01 General RF Exposure Guidance DR04-44307, these modes qualify for 1-mW Test Exemption.

Simultaneous transmission assessment:

The device under evaluation is able to transmit simultaneously using several transmitters, therefore the most conservative approach for the evaluation of the simultaneous transmission will be:

Simultaneous technologies and modes	Result (\sum of Pout/Pmax ratios)	Verdict ($\sum \leq 1$)
BTLE 2.4 GHz + Mi Radio LF	0.88	Pass
Property Proximity 2.4 GHz + Mi Radio LF	0.76	Pass

Table 3: Simultaneous Result

Appendix B: FCC RF Exposure information

FCC SAR test exclusion considerations for portable devices

Blanket 1 mW Blanket Exemption

The 1 mW Blanket Exemption of §1.1307(b)(3)(i)(A) applies for single fixed, mobile, and portable RF sources with available maximum time-averaged power of no more than 1 mW, regardless of separation distance.

The 1-mW blanket exemption applies at separation distances less than 0.5 cm, including where there is no separation. This exemption shall not be used in conjunction with other exemption criteria other than those for multiple RF sources in paragraph §1.1307(b)(3)(ii)(A).

The 1-mW exemption is independent of service type and covers the full range of 100 kHz to 100 GHz, but it shall not be used in conjunction with other exemption criteria or in devices with higher-power transmitters operating in the same time-averaging period. Exposure from such higher-power transmitters would invalidate the underlying assumption that exposure from the lower-power transmitter is the only contributor to SAR in the relevant volume of tissue.

Simultaneous transmission assessment:

When multiple sources are introduced into an environment, it becomes necessary to address the sources interdependently, since each source will contribute some percentage of the maximum exposure towards the total exposure at a fixed location. The sum of the ratios of the exposure from each source to the corresponding maximum exposure for the frequency of each source must be evaluated.

The exposure complies with the maximum permissible exposure if the sum of the ratios is less than unity:

$$\sum_{i=1}^n \frac{S_i}{P_{\max_i}} < 1$$

Where

S_i is the calculated SAR tests exclusion value of each source.

P_{\max_i} is the SAR test exclusion threshold.

1-mW Test Exemption for Multiple Sources

As discussed in § 1.1307(b)(3)(ii)(A), the 1-mW exemption intended for single transmitters may be also applied to simultaneous transmission conditions, within the same host device, according one of the following criteria:

- a) When maximum available power each individual transmitting antenna within the same time averaging period is ≤ 1 mW, and the nearest parts of the antenna structures of the simultaneously operating transmitters are separated by at least 2 cm.
- b) When the aggregate maximum available power of all transmitting antennas is ≤ 1 mW in the same time averaging period.

This exemption may not be combined with any other exemption.