



Test report No:
NIE: 60210RRF.004

Partial Test report

USA FCC Part 15.249, 15.209

CANADA RSS-210, RSS-Gen

Radio Frequency Devices. Operation within the bands 902 - 928 MHz, 2400 -2483.5 MHz, and 5725 - 5850 MHz.

(*) Identification of item tested	Wireless hearing instrument
(*) Trademark	ReSound, Beltone, Interton, GN Hearing
(*) Model and /or type reference tested	CSI13
Other identification of the product	FCC ID: X26CSI13 IC: 6941C-CSI13
(*) Features	Audio amplification, proprietary 2.4 GHz wireless functionality (Proximity) and Bluetooth 5.0
Applicant	GN HEARING A/S Lautrupbjerg 7, 2750 Ballerup, Denmark
Test method requested, standard	USA FCC Part 15.249 10-1-18 Edition: Operation within the bands 902 - 928 MHz, 2400 -2483.5 MHz, 5725 - 5875 MHz, and 24.0 – 24.25 GHz. USA FCC Part 15.209 10-1-18 Edition: Radiated emission limits; general requirements. CANADA RSS-210 Issue 9 (August 2016). CANADA RSS-Gen Issue 5 (April 2018). ANSI C63.10-2013: American National Standard for Testing Unlicensed Wireless Devices. - Section 15.249 Subclause (a) / RSS-210 B.10 (a). Field strength of Fundamental and harmonic emissions. - Section 15.249 Subclause (a) and (d) / RSS-210 B.10 (b). Emissions radiated outside of the specific frequency bands (Transmitter).
Approved by (name / position & signature)	A. Llamas RF Lab. Manager
Date of issue	2019-07-17
Report template No	FDT08_22 (*) "Data provided by the client"

Index

Competences and guarantees3

General conditions3

Uncertainty3

Data provided by the client.....3

Usage of samples4

Test sample description4

Identification of the client.....5

Testing period and place.....5

Document history5

Environmental conditions5

Remarks and comments6

Testing verdicts.....6

Summary7

Appendix A: Test results. Bluetooth Low Energy 5.0 2M8

Appendix B: Test results. Bluetooth Low Energy 5.0 1M27

Appendix C: Test results. Proprietary protocol 2.4 GHz46

Competences and guarantees

DEKRA Testing and Certification S.A.U. is a testing laboratory accredited by the National Accreditation Body (ENAC -Entidad Nacional de Acreditación), to perform the tests indicated in the Certificate No. 51/LE 147.

DEKRA Testing and Certification is a FCC-recognized accredited testing laboratory with appropriate scope of accreditation that include testing performed in this test report.

DEKRA Testing and Certification is an ISED-recognized accredited testing laboratory with appropriate scope of accreditation that include testing performed in this test report.

In order to assure the traceability to other national and international laboratories, DEKRA Testing and Certification S.A.U. has a calibration and maintenance program for its measurement equipment.

DEKRA Testing and Certification S.A.U. guarantees the reliability of the data presented in this report, which is the result of the measurements and the tests performed to the item under test on the date and under the conditions stated on the report and, it is based on the knowledge and technical facilities available at DEKRA Testing and Certification S.A.U. at the time of performance of the test.

DEKRA Testing and Certification S.A.U. is liable to the client for the maintenance of the confidentiality of all information related to the item under test and the results of the test.

The results presented in this Test Report apply only to the particular item under test established in this document.

IMPORTANT: No parts of this report may be reproduced or quoted out of context, in any form or by any means, except in full, without the previous written permission of DEKRA Testing and Certification S.A.U.

General conditions

1. This report is only referred to the item that has undergone the test.
2. This report does not constitute or imply on its own an approval of the product by the Certification Bodies or competent Authorities.
3. This document is only valid if complete; no partial reproduction can be made without previous written permission of DEKRA Testing and Certification S.A.U.
4. This test report cannot be used partially or in full for publicity and/or promotional purposes without previous written permission of DEKRA Testing and Certification S.A.U. and the Accreditation Bodies.

Uncertainty

Uncertainty (factor $k=2$) was calculated according to the DEKRA Testing and Certification S.A.U. internal document PODT000.

Data provided by the client

The samples consists of a wireless hearing aid.

DEKRA Testing and Certification S.A.U. declines any responsibility with respect to the information provided by the client and that may affect the validity of results.

Usage of samples

Samples undergoing test have been selected by: The client.

- Sample S/01 is composed of the following elements:

Control N°	Description	Model	Serial N°	Reception
60210C/040	Wireless hearing instrument	CSI13	1900805930	2019/04/10

Sample S/01 has undergone the following test(s): All tests indicated in Appendixes A, B, C.

Test sample description

Ports..... :	Port name and description	Cable				
		Specified max length [m]	Attached during test	Shielded	Coupled to patient ⁽³⁾	
			☐	☐	☐	
Supplementary information to the ports..... :						
Rated power supply	Voltage and Frequency		Reference poles			
			L1	L2	L3	N
	☐	AC:	☐	☐	☐	☐
☒	DC: 1.45 Vdc (battery)					
Rated Power						
Clock frequencies						
Other parameters..... :						
Software version	Dooku1					
Hardware version..... :	PCBA, DALLAS, MFI, V1.B, C5.0					
Dimensions in cm (W x H x D)..... :						
Mounting position..... :	☐	Table top equipment				
	☐	Wall/Ceiling mounted equipment				
	☐	Floor standing equipment				
	☐	Hand-held equipment				
	☒	Other: Hearing aid				

Modules/parts	Module/parts of test item	Type	Manufacturer
Accessories (not part of the test item)	Description	Type	Manufacturer
Documents as provided by the applicant.....	Description	File name	Issue date

(3): Only for Medical Equipment.

Identification of the client

GN HEARING A/S
Lautrupbjerg 7, 2750 Ballerup, Denmark

Testing period and place

Test Location	DEKRA Testing and Certification S.A.U.
Date (start)	2019-04-11
Date (finish)	2019-04-23

Document history

Report number	Date	Description
60210RRF.004	2019-07-17	First release

Environmental conditions

In the control chamber, the following limits were not exceeded during the test:

Temperature	Min. = 15 °C Max. = 35 °C
Relative humidity	Min. = 20 % Max. = 75 %

In the semianechoic chamber, the following limits were not exceeded during the test.

Temperature	Min. = 15 °C Max. = 35 °C
Relative humidity	Min. = 20 % Max. = 75 %
Air pressure	Min. = 860 mbar Max. = 1060 mbar

Remarks and comments

Manufacturer states that conducted measurements for this model would be identical to the measurements performed on hearing aid platform "CSI12". Report ref.: 60210RRF.002.

The tests have been performed by the technical personnel: José Gabriel Pendón, Miguel Ángel Torres.

Used instrumentation:

Radiated Measurements:

		Last Calibration	Due Calibration
1.	Semianechoic Absorber Lined Chamber ETS LINDGREN FACT 3 200 STP	N.A.	N.A.
2.	RF Pre-amplifier 40 dB, 10 MHz - 6 GHz BONN ELEKTRONIK BLNA 0160-01N	2019/02	2020/08
3.	RF Pre-amplifier, 48 dB, 18 GHz - 40 GHz NARDA JS44-18004000-33-8P	2018/02	2020/02
4.	Biconical/Log Antenna ETS LINDGREN 3142E	2017/04	2020/04
5.	Signal and Spectrum Analyzer ROHDE AND SCHWARZ FSV40	2018/02	2020/02
6.	RF Pre-amplifier, 30 dB ,1-18 GHz BONN ELEKTRONIK BLMA 0118-3A	2019/04	2020/04
7.	Broadband Horn antenna 1-18 GHz SCHWARZBECK BBHA 9120 D	2018/01	2021/01
8.	Broadband Horn antenna 18-40 GHz SCHWARZBECK BBHA 9170	2018/07	2021/07
9.	EMI Test Receiver 7 GHz ROHDE AND SCHWARZ ESR7	2018/10	2020/10

Testing verdicts

Not applicable:	N/A
Pass:	P
Fail:	F
Not measured:	N/M

Summary

1. Bluetooth Low Energy 5.0 2M, 1M.

FCC PART 15.249 PARAGRAPH / RSS-210			
Requirement – Test case		Verdict	Remark
Section 15.249 Subclause (a) / RSS-210 B.10. (a)	Field strength of fundamental and harmonics emissions	P	
Section 15.249 Subclause (d) / RSS-210 B.10. (b)	Emissions radiated outside of the specific frequency bands	P	
<u>Supplementary information and remarks:</u> None.			

2. Proprietary protocol 2.4 GHz.

FCC PART 15.249 PARAGRAPH / RSS-210			
Requirement – Test case		Verdict	Remark
Section 15.249 Subclause (a) / RSS-210 B.10. (a)	Field strength of fundamental and harmonics emissions	P	
Section 15.249 Subclause (d) / RSS-210 B.10. (b)	Emissions radiated outside of the specific frequency bands	P	
<u>Supplementary information and remarks:</u> None.			

Appendix A: Test results. Bluetooth Low Energy 5.0 2M

Index

TEST CONDITIONS10

Section 15.249 Subclause (a) / RSS-210 B.10 (a). Field strength of Fundamental and harmonic emissions.....12

Section 15.249 Subclause (a) and (d) / RSS-210 B.10 (b). Emissions radiated outside of the specific frequency bands (Transmitter)15

TEST CONDITIONS

POWER SUPPLY (V):

Vnominal: 1.45 Vdc
Type of power supply: Battery
Type of antenna: Integral antenna
Declared antenna gain: -1.09 dBi

TEST FREQUENCIES:

Low Channel: 2402 MHz
Middle Channel: 2440 MHz
High Channel: 2480 MHz

RADIATED MEASUREMENTS


All radiated tests were performed in a semi-anechoic chamber. The measurement antenna is situated at a distance of 3 m for the frequency range 30 MHz-1000 MHz (30 MHz-1000 MHz Bilog antenna) and at a distance of 1m for the frequency range 1 GHz-26 GHz (1 GHz-18 GHz Double ridge horn antenna and 18 GHz-40 GHz horn antenna).

For radiated emissions in the range 1 GHz-26 GHz that is performed at a distance closer than the specified distance, an inverse proportionality factor of 20 dB per decade is used to normalize the measured data for determining compliance.


The equipment under test was set up on a non-conductive platform above the ground plane and the situation and orientation was varied to find the maximum radiated emission. It was also rotated 360° and the antenna height was varied from 1 to 4 meters to find the maximum radiated emission.

Measurements were made in both horizontal and vertical planes of polarization.

Radiated measurements setup $f < 1$ GHz:



Radiated measurements setup $f > 1$ GHz:



Section 15.249 Subclause (a) / RSS-210 B.10 (a). Field strength of Fundamental and harmonic emissions

SPECIFICATION:

The field strength of emissions from intentional radiators shall comply with the following

Fundamental frequency (MHz)	Field strength of fundamental (mV/m)	Field strength (dBµV/m)	Measurement distance (m)
902 - 928	50	93.98	3
2400 – 2483.5	50	93.98	3
5725 - 5875	50	93.98	3
24000-24250	250	107.96	3


For frequencies above 1000 MHz, the above field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.

RESULTS:


	Low Channel 2402 MHz	Middle Channel 2440 MHz	High Channel 2480 MHz
Average Field Strength (dBµV/m)	78.25	79.15	78.17
Peak Field Strength (dBµV/m)	92.83	93.75	92.59
Measurement Uncertainty (dB)	<±3.70		

Verdict: PASS


- Low Channel:



- Middle Channel:



- High Channel:



Section 15.249 Subclause (a) and (d) / RSS-210 B.10 (b). Emissions radiated outside of the specific frequency bands (Transmitter)

SPECIFICATION:

The field strength of harmonics from intentional radiators shall comply with the following

Fundamental frequency (MHz)	Field strength of harmonics ($\mu\text{V/m}$)	Field strength of harmonics ($\text{dB}\mu\text{V/m}$)	Measurement distance (m)
902 - 928	500	54	3
2400 – 2483.5	500	54	3
5725 - 5875	500	54	3
24000-24250	2500	67.96	3

Emissions radiated outside of the specific frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of fundamental or to the general radiated emission limits specified in section 15.209:

Frequency Range (MHz)	Field strength ($\mu\text{V/m}$)	Field strength ($\text{dB}\mu\text{V/m}$)	Measurement distance (m)
0.009-0.490	$2400/F(\text{kHz})$	-	300
0.490-1.705	$24000/F(\text{kHz})$	-	30
1.705 - 30.0	30	-	30
30 - 88	100	40	3
88 - 216	150	43.5	3
216 - 960	200	46	3
960 - 25000	500	54	3

Whichever is the lesser attenuation.

RESULTS:

The situation and orientation was varied to find the maximum radiated emission. It was also rotated 360° and the antenna height was varied from 1 to 4 meters to find the maximum radiated emission.

Measurements were made in both horizontal and vertical planes of polarization.

All tests were performed in a semi-anechoic chamber at a distance of 3 m for the frequency range 30 MHz-1000 MHz and at distance of 1m for the frequency range 1 GHz-26 GHz.

The field strength is calculated by adding correction factor to the measured level from the spectrum analyzer. This correction factor includes antenna factor, cable loss and pre-amplifiers gain.

Frequency range 30 MHz - 1 GHz.

The spurious signals detected do not depend on the operating channel.

No spurious frequencies detected at less than 20 dB below the limit.

Frequency range 1 - 26 GHz.

The results in the next tables show the maximum measured levels in the 1-26 GHz range including the restricted bands 2.31-2.39 GHz and 2.4835-2.5 GHz (see next plots).

Spurious signals with peak levels above the average limit (54 dB μ V/m at 3 m) are measured with average detector for checking compliance with the average limit.

- Low Channel (2402 MHz):

Spurious frequency (GHz)	Detector	Emission Level (dB μ V/m)	Polarization	Measurement Uncertainty (dB)
2.38929	Peak	58.37	H	< $\pm$ 3.70
	Average	40.91		
4.80297	Peak	51.41	V	< $\pm$ 3.70
9.60683	Peak	49.71	H	< $\pm$ 3.70

- Middle Channel (2440 MHz):


Spurious frequency (GHz)	Detector	Emission Level (dB μ V/m)	Polarization	Measurement Uncertainty (dB)
4.87903	Peak	53.30	H	< $\pm$ 3.70
9.75850	Peak	48.96	V	< $\pm$ 3.70

- High Channel (2480 MHz):

Spurious frequency (GHz)	Detector	Emission Level (dB μ V/m)	Polarization	Measurement Uncertainty (dB)
2.48350	Peak	68.96	H	< $\pm$ 3.70
	Average	44.30		
4.96117	Peak	51.30	H	< $\pm$ 3.70
9.92090	Peak	51.69	H	< $\pm$ 3.70

Verdict: PASS


FREQUENCY RANGE 30 MHz - 1 GHz



Note: This plot is valid for all three channels.


FREQUENCY RANGE 1 - 3 GHz

- Low Channel:




The peak shown in the plot above the limit is the carrier frequency.

- Middle Channel:



The peak shown in the plot above the limit is the carrier frequency.


- High Channel:




The peak shown in the plot above the limit is the carrier frequency.

FREQUENCY RANGE 3 - 17 GHz


- Low Channel:




- Middle Channel:



- High Channel:




FREQUENCY RANGE 17 - 26 GHz




Note: This plot is valid for all three channels.

FREQUENCY RANGE 2.31 - 2.39 GHz. (RESTRICTED BAND 1)


- Low Channel:



- Middle Channel:




- High Channel:




FREQUENCY RANGE 2.4835 - 2.5 GHz. (RESTRICTED BAND 2)


- Low Channel:



- Middle Channel:



- High Channel:



Appendix B: Test results. Bluetooth Low Energy 5.0 1M

Index

TEST CONDITIONS	29
Section 15.249 Subclause (a) / RSS-210 B.10 (a). Field strength of Fundamental and harmonic emissions.....	31
Section 15.249 Subclause (a) and (d) / RSS-210 B.10 (b). Emissions radiated outside of the specific frequency bands (Transmitter)	34

TEST CONDITIONS

POWER SUPPLY (V):

Vnominal: 1.45 Vdc
Type of power supply: Battery
Type of antenna: Integral antenna
Declared antenna gain: -1.09 dBi

TEST FREQUENCIES:

Low Channel: 2402 MHz
Middle Channel: 2440 MHz
High Channel: 2480 MHz

RADIATED MEASUREMENTS


All radiated tests were performed in a semi-anechoic chamber. The measurement antenna is situated at a distance of 3 m for the frequency range 30 MHz-1000 MHz (30 MHz-1000 MHz Bilog antenna) and at a distance of 1m for the frequency range 1 GHz-26 GHz (1 GHz-18 GHz Double ridge horn antenna and 18 GHz-40 GHz horn antenna).

For radiated emissions in the range 1 GHz-26 GHz that is performed at a distance closer than the specified distance, an inverse proportionality factor of 20 dB per decade is used to normalize the measured data for determining compliance.


The equipment under test was set up on a non-conductive platform above the ground plane and the situation and orientation was varied to find the maximum radiated emission. It was also rotated 360° and the antenna height was varied from 1 to 4 meters to find the maximum radiated emission.

Measurements were made in both horizontal and vertical planes of polarization.

Radiated measurements setup $f < 1$ GHz:



Radiated measurements setup $f > 1$ GHz:



Section 15.249 Subclause (a) / RSS-210 B.10 (a). Field strength of Fundamental and harmonic emissions

SPECIFICATION:

The field strength of emissions from intentional radiators shall comply with the following

Fundamental frequency (MHz)	Field strength of fundamental (mV/m)	Field strength (dB μ V/m)	Measurement distance (m)
902 - 928	50	93.98	3
2400 – 2483.5	50	93.98	3
5725 - 5875	50	93.98	3
24000-24250	250	107.96	3


For frequencies above 1000 MHz, the above field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.

RESULTS:


	Low Channel 2402 MHz	Middle Channel 2440 MHz	High Channel 2480 MHz
Average Field Strength (dB μ V/m)	83.39	84.23	83.44
Peak Field Strength (dB μ V/m)	92.66	93.51	92.58
Measurement Uncertainty (dB)	< $\pm$ 3.70		

Verdict: PASS


- Low Channel:



- Middle Channel:



- High Channel:



Section 15.249 Subclause (a) and (d) / RSS-210 B.10 (b). Emissions radiated outside of the specific frequency bands (Transmitter)

SPECIFICATION:

The field strength of harmonics from intentional radiators shall comply with the following:

Fundamental frequency (MHz)	Field strength of harmonics ($\mu\text{V/m}$)	Field strength of harmonics ($\text{dB}\mu\text{V/m}$)	Measurement distance (m)
902 - 928	500	54	3
2400 – 2483.5	500	54	3
5725 - 5875	500	54	3
24000-24250	2500	67.96	3

Emissions radiated outside of the specific frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of fundamental or to the general radiated emission limits specified in section 15.209:

Frequency Range (MHz)	Field strength ($\mu\text{V/m}$)	Field strength ($\text{dB}\mu\text{V/m}$)	Measurement distance (m)
0.009-0.490	$2400/F(\text{kHz})$	-	300
0.490-1.705	$24000/F(\text{kHz})$	-	30
1.705 - 30.0	30	-	30
30 - 88	100	40	3
88 - 216	150	43.5	3
216 - 960	200	46	3
960 - 25000	500	54	3

Whichever is the lesser attenuation.

RESULTS:

The situation and orientation was varied to find the maximum radiated emission. It was also rotated 360° and the antenna height was varied from 1 to 4 meters to find the maximum radiated emission.

Measurements were made in both horizontal and vertical planes of polarization.

All tests were performed in a semi-anechoic chamber at a distance of 3 m for the frequency range 30 MHz-1000 MHz and at distance of 1m for the frequency range 1 GHz-26 GHz.

The field strength is calculated by adding correction factor to the measured level from the spectrum analyzer. This correction factor includes antenna factor, cable loss and pre-amplifiers gain.

Frequency range 30 MHz - 1 GHz.

The spurious signals detected do not depend on the operating channel.

No spurious frequencies detected at less than 20 dB below the limit.

Frequency range 1 - 26 GHz.

The results in the next tables show the maximum measured levels in the 1-26 GHz range including the restricted bands 2.31-2.39 GHz and 2.4835-2.5 GHz (see next plots).

Spurious signals with peak levels above the average limit (54 dB μ V/m at 3 m) are measured with average detector for checking compliance with the average limit.

- Low Channel (2402 MHz):

Spurious frequency (GHz)	Detector	Emission Level (dB μ V/m)	Polarization	Measurement Uncertainty (dB)
2.38995	Peak	58.53	H	< $\pm$ 3.70
	Average	40.97		
4.80437	Peak	52.48	H	< $\pm$ 3.70
9.60870	Peak	50.59	H	< $\pm$ 3.70

- Middle Channel (2440 MHz):


Spurious frequency (GHz)	Detector	Emission Level (dB μ V/m)	Polarization	Measurement Uncertainty (dB)
4.87950	Peak	52.57	V	< $\pm$ 3.70
9.75850	Peak	49.48	H	< $\pm$ 3.70

- High Channel (2480 MHz):

Spurious frequency (GHz)	Detector	Emission Level (dB μ V/m)	Polarization	Measurement Uncertainty (dB)
2.48351	Peak	69.01	H	< $\pm$ 3.70
	Average	44.75		
4.96023	Peak	52.22	H	< $\pm$ 3.70
9.91900	Peak	50.34	H	< $\pm$ 3.70

Verdict: PASS


FREQUENCY RANGE 30 MHz - 1 GHz



Note: This plot is valid for all three channels.


FREQUENCY RANGE 1 - 3 GHz

- Low Channel:




The peak shown in the plot above the limit is the carrier frequency.

- Middle Channel:



The peak shown in the plot above the limit is the carrier frequency.


- High Channel:




The peak shown in the plot above the limit is the carrier frequency.

FREQUENCY RANGE 3 - 17 GHz


- Low Channel:




- Middle Channel:



- High Channel:




FREQUENCY RANGE 17 - 26 GHz




Note: This plot is valid for all three channels.

FREQUENCY RANGE 2.31 - 2.39 GHz. (RESTRICTED BAND 1)


- Low Channel:



- Middle Channel:




- High Channel:




FREQUENCY RANGE 2.4835 - 2.5 GHz. (RESTRICTED BAND 2)


- Low Channel:



- Middle Channel:



- High Channel:



Appendix C: Test results. Proprietary protocol 2.4 GHz

Index

TEST CONDITIONS	48
Section 15.249 Subclause (a) / RSS-210 B.10 (a). Field strength of Fundamental and harmonic emissions.....	50
Section 15.249 Subclause (a) and (d) / RSS-210 B.10 (b). Emissions radiated outside of the specific frequency bands (Transmitter)	53

TEST CONDITIONS

POWER SUPPLY (V):

Vnominal: 1.45 Vdc
Type of power supply: Battery
Type of antenna: Integral antenna.
Declared antenna gain: -1.09 dBi

TEST FREQUENCIES:

Low Channel: 2402 MHz
Middle Channel: 2440 MHz
High Channel: 2480 MHz

RADIATED MEASUREMENTS


All radiated tests were performed in a semi-anechoic chamber. The measurement antenna is situated at a distance of 3 m for the frequency range 30 MHz-1000 MHz (30 MHz-1000 MHz Bilog antenna) and at a distance of 1m for the frequency range 1 GHz-26 GHz (1 GHz-18 GHz Double ridge horn antenna and 18 GHz-40 GHz horn antenna).

For radiated emissions in the range 1 GHz-26 GHz that is performed at a distance closer than the specified distance, an inverse proportionality factor of 20 dB per decade is used to normalize the measured data for determining compliance.


The equipment under test was set up on a non-conductive platform above the ground plane and the situation and orientation was varied to find the maximum radiated emission. It was also rotated 360° and the antenna height was varied from 1 to 4 meters to find the maximum radiated emission.

Measurements were made in both horizontal and vertical planes of polarization.

Radiated measurements setup $f < 1$ GHz:



Radiated measurements setup $f > 1$ GHz:



Section 15.249 Subclause (a) / RSS-210 B.10 (a). Field strength of Fundamental and harmonic emissions

SPECIFICATION:

The field strength of emissions from intentional radiators shall comply with the following

Fundamental frequency (MHz)	Field strength of fundamental (mV/m)	Field strength (dBμV/m)	Measurement distance (m)
902 - 928	50	93.98	3
2400 – 2483.5	50	93.98	3
5725 - 5875	50	93.98	3
24000-24250	250	107.96	3


For frequencies above 1000 MHz, the above field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.

RESULTS:


	Low Channel 2402 MHz	Middle Channel 2440 MHz	High Channel 2480 MHz
Average Field Strength (dBμV/m)	77.56	79.73	79.32
Peak Field Strength (dBμV/m)	93.55	95.73	95.23
Measurement Uncertainty (dB)	<±3.70		

Verdict: PASS


- Low Channel:



- Middle Channel:



- High Channel:



Section 15.249 Subclause (a) and (d) / RSS-210 B.10 (b). Emissions radiated outside of the specific frequency bands (Transmitter)

SPECIFICATION:

The field strength of harmonics from intentional radiators shall comply with the following

Fundamental frequency (MHz)	Field strength of harmonics ($\mu\text{V/m}$)	Field strength of harmonics ($\text{dB}\mu\text{V/m}$)	Measurement distance (m)
902 - 928	500	54	3
2400 – 2483.5	500	54	3
5725 - 5875	500	54	3
24000-24250	2500	67.96	3

Emissions radiated outside of the specific frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of fundamental or to the general radiated emission limits specified in section 15.209:

Frequency Range (MHz)	Field strength ($\mu\text{V/m}$)	Field strength ($\text{dB}\mu\text{V/m}$)	Measurement distance (m)
0.009-0.490	$2400/F(\text{kHz})$	-	300
0.490-1.705	$24000/F(\text{kHz})$	-	30
1.705 - 30.0	30	-	30
30 - 88	100	40	3
88 - 216	150	43.5	3
216 - 960	200	46	3
960 - 25000	500	54	3

Whichever is the lesser attenuation.

RESULTS:

The situation and orientation was varied to find the maximum radiated emission. It was also rotated 360° and the antenna height was varied from 1 to 4 meters to find the maximum radiated emission.

Measurements were made in both horizontal and vertical planes of polarization.

All tests were performed in a semi-anechoic chamber at a distance of 3 m for the frequency range 30 MHz-1000 MHz and at distance of 1m for the frequency range 1 GHz-26 GHz.

The field strength is calculated by adding correction factor to the measured level from the spectrum analyzer. This correction factor includes antenna factor, cable loss and pre-amplifiers gain.

Frequency range 30 MHz - 1 GHz.

The spurious signals detected do not depend on the operating channel.

No spurious frequencies detected at less than 20 dB below the limit.

Frequency range 1 - 26 GHz.

The results in the next tables show the maximum measured levels in the 1-26 GHz range including the restricted bands 2.31-2.39 GHz and 2.4835-2.5 GHz (see next plots).

Spurious signals with peak levels above the average limit (54 dB μ V/m at 3 m) are measured with average detector for checking compliance with the average limit.

- Low Channel (2402 MHz):

Spurious frequency (GHz)	Detector	Emission Level (dB μ V/m)	Polarization	Measurement Uncertainty (dB)
2.38981	Peak	62.28	H	< $\pm$ 3.70
	Average	41.21		
4.80437	Peak	51.28	V	< $\pm$ 3.70
9.60823	Peak	47.61	H	< $\pm$ 3.70

- Middle Channel (2440 MHz):


Spurious frequency (GHz)	Detector	Emission Level (dB μ V/m)	Polarization	Measurement Uncertainty (dB)
4.88043	Peak	50.93	H	< $\pm$ 3.70
9.76130	Peak	50.70	H	< $\pm$ 3.70

- High Channel (2480 MHz):

Spurious frequency (GHz)	Detector	Emission Level (dB μ V/m)	Polarization	Measurement Uncertainty (dB)
2.48356	Peak	65.08	H	< $\pm$ 3.70
	Average	42.83		
4.95650	Peak	54.01	H	< $\pm$ 3.70
	Average	50.32		
9.91203	Peak	50.24	H	< $\pm$ 3.70

Verdict: PASS


FREQUENCY RANGE 30 MHz - 1 GHz



Note: This plot is valid for all three channels


FREQUENCY RANGE 1 - 3 GHz

- Low Channel:




The peak shown in the plot above the limit is the carrier frequency.

- Middle Channel:



The peak shown in the plot above the limit is the carrier frequency.


- High Channel:




The peak shown in the plot above the limit is the carrier frequency.

FREQUENCY RANGE 3 - 17 GHz


- Low Channel:




- Middle Channel:



- High Channel:




FREQUENCY RANGE 17 - 26 GHz




Note: This plot is valid for all three channels.

FREQUENCY RANGE 2.31 - 2.39 GHz. (RESTRICTED BAND 1)


- Low Channel:



- Middle Channel:




- High Channel:




FREQUENCY RANGE 2.4835 - 2.5 GHz. (RESTRICTED BAND 2)

- Low Channel:



- Middle Channel:



- High Channel:

