

FDSSL-G000

User manual
2019/05/28

Remote Layout



Five Function Buttons

1. Remote Start
2. Lock
3. Unlock
4. Trunk
5. Panic

Operation

Make sure you are within range of the vehicle before using the remote.

- Press Lock to lock all doors.
- Press Unlock to unlock the driver's door. Press Unlock again within 5 seconds to unlock all doors.
- Press the Trunk button twice to open the trunk.
- Press and Hold the Panic button for longer than 0.5 seconds to sound the vehicle's Panic Alarm.
- Press any button to stop the Panic Alarm

Note: The exact behavior in response to each button press may vary depending on the vehicle. Consult the vehicle manual for more information.

Pairing Instructions

This Smart key requires industry standard equipment to program and pair to your vehicle. Please contact a licensed locksmith to pair this key to your vehicle. For help or assistance, please contact technical support at: 1-844-KEY-USA with any questions related to the remote functions of this key.

Battery Replacement

If the battery needs to be replaced:

1. Slide the switch on the back of the remote to remove the emergency key.
2. Use the emergency key to pry the two halves of the remote apart at the space next to where they key was removed from.
3. Replace the battery with a CR2032 cell with the "+" side facing down into the plastic.
4. Press the two shell halves back together and replace the emergency key.

FCC Regulatory Statement

Model: FDSSL-G000
FCC ID: X32-FDSSG000

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

NOTE: This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to Part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses, and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio/TV technician for help.

Consult the dealer or an experienced radio/TV technician for help.

Warning: Changes or modifications to this device not expressly approved by iKeyless, LLC could void the user's authority to operate the equipment.

IC Regulatory Statement

Model: FDSSL-G000
IC: 8797A-FDSSG000
CAN ICES-3 (B)/NMB-3(B)

This device complies with Industry Canada's licence-exempt RSSs. Operation is subject to the following two conditions:

- (1) This device may not cause interference; and
- (2) This device must accept any interference, including interference that may cause undesired operation of the device.

Le présent appareil est conforme aux CNR d'Industrie Canada applicables aux appareils radio exempts de licence. L'exploitation est autorisée aux deux conditions suivantes :

- 1) l'appareil ne doit pas produire de brouillage;
- 2) l'appareil doit accepter tout brouillage radioélectrique subi, même si le brouillage est susceptible d'en compromettre le fonctionnement.