



**中认信通**  
CHINA CERTIFICATION ICT CO., LTD (DONGGUAN)



## TEST REPORT

**Applicant: Shanghai Smarfid Security Equipment Co., Ltd.**

Address: No. 88, Lane 600, XinLi Road, Minhang District, Shanghai China

**FCC ID: X3A-MW322**

**Product Name: Card Reader**

**Standard(s): 47 CFR Part 15, Subpart C(15.225)  
ANSI C63.10-2013**

The above equipment has been tested and found compliant with the requirement of the relative standards by China Certification ICT Co., Ltd (Dongguan)

**Report Number: CR221260863-00A**

**Date Of Issue: 2023/4/21**

**Reviewed By: Sun Zhong**

*Sun Zhong*

Title: Manager

**Test Laboratory: China Certification ICT Co., Ltd (Dongguan)**

No. 113, Pingkang Road, Dalang Town, Dongguan,  
Guangdong, China  
Tel: +86-769-82016888

### **Test Facility**

The Test site used by China Certification ICT Co., Ltd (Dongguan) to collect test data is located on the No. 113, Pingkang Road, Dalang Town, Dongguan, Guangdong, China.

The lab has been recognized as the FCC accredited lab under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No. : 442868, the FCC Designation No. : CN1314.

The lab has been recognized by Innovation, Science and Economic Development Canada to test to Canadian radio equipment requirements, the CAB identifier: CN0123.

### **Declarations**

China Certification ICT Co., Ltd (Dongguan) is not responsible for the authenticity of any test data provided by the applicant. Data included from the applicant that may affect test results are marked with a triangle symbol “▲”. Customer model name, addresses, names, trademarks etc. are not considered data.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested.

This report cannot be reproduced except in full, without prior written approval of the Company.

This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

This report may contain data that are not covered by the accreditation scope and shall be marked with an asterisk “★”.

---

## DOCUMENT REVISION HISTORY

---

Revision Number	Report Number	Description of Revision	Date of Revision
1.0	CR221260863-00A	Original Report	2023/4/21

## CONTENTS

<b>TEST FACILITY .....</b>	<b>2</b>
<b>DECLARATIONS.....</b>	<b>2</b>
<b>DOCUMENT REVISION HISTORY .....</b>	<b>3</b>
<b>1. GENERAL INFORMATION.....</b>	<b>6</b>
<b>1.1 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT) .....</b>	<b>6</b>
<b>1.2 DESCRIPTION OF TEST CONFIGURATION.....</b>	<b>7</b>
1.2.1 EUT Operation Condition:.....	7
1.2.2 Support Equipment List and Details .....	7
1.2.3 Support Cable List and Details .....	7
1.2.4 Block Diagram of Test Setup.....	8
<b>1.3 MEASUREMENT UNCERTAINTY .....</b>	<b>9</b>
<b>2. SUMMARY OF TEST RESULTS .....</b>	<b>10</b>
<b>3. REQUIREMENTS AND TEST PROCEDURES .....</b>	<b>11</b>
<b>3.1 AC LINE CONDUCTED EMISSIONS.....</b>	<b>11</b>
3.1.1 Applicable Standard.....	11
3.1.2 EUT Setup.....	12
3.1.3 EMI Test Receiver Setup .....	12
3.1.4 Test Procedure .....	13
3.1.5 Corrected Amplitude & Margin Calculation.....	13
<b>3.2 RADIATED EMISSIONS .....</b>	<b>14</b>
3.2.1 Applicable Standard.....	14
3.2.2 EUT Setup.....	14
3.2.3 EMI Test Receiver & Spectrum Analyzer Setup .....	15
3.2.4 Corrected Amplitude & Margin Calculation.....	15
<b>3.3 20 dB EMISSION BANDWIDTH:.....</b>	<b>16</b>
3.3.1 Applicable Standard.....	16
3.3.2 EUT Setup.....	16
3.3.3 Test Procedure .....	16
<b>3.4 FREQUENCY STABILITY.....</b>	<b>17</b>
3.4.1 Applicable Standard.....	17
3.4.2 EUT Setup.....	17
3.4.3 Test Procedure .....	17
<b>3.5 ANTENNA REQUIREMENT.....</b>	<b>18</b>
3.5.1 Applicable Standard.....	18
3.5.2 Judgment.....	18
<b>4. TEST DATA AND RESULTS .....</b>	<b>19</b>
<b>4.1 AC LINE CONDUCTED EMISSIONS.....</b>	<b>19</b>
<b>4.2 RADIATION SPURIOUS EMISSIONS .....</b>	<b>22</b>
<b>4.3 20 dB EMISSION BANDWIDTH .....</b>	<b>34</b>

**4.4 FREQUENCY STABILITY.....36**

**5. RF EXPOSURE EVALUATION ..... 37**

**5.1 APPLICABLE STANDARD.....37**

**5.2 PROCEDURE.....37**

**5.3 MEASUREMENT RESULT .....37**

## 1. GENERAL INFORMATION

### 1.1 Product Description for Equipment under Test (EUT)

<b>EUT Name:</b>	Card Reader
<b>EUT Model:</b>	MW-322
<b>Multiple Models:</b>	MW-322-7N, MW-322-8N, MW-322-7K, MW-322-8K
<b>Operation Frequency:</b>	13.56 MHz
<b>Modulation Type:</b>	ASK
<b>Rated Input Voltage:</b>	12Vdc
<b>Serial Number:</b>	1V3Q-1
<b>EUT Received Date:</b>	2022/12/14
<b>EUT Received Status:</b>	Good

Note: The Multiple models are electrically identical with the test model. Please refer to the declaration letter for more detail, which was provided by manufacturer. MW-322 have most complete function, so test only perform at MW-322 model.

#### Antenna Information Detail▲:

Antenna Type	input impedance (Ohm)	Frequency Range	Antenna Gain
Loop	50	13.56MHz	Unknown

The Method of §15.203 Compliance:

- Antenna must be permanently attached to the unit.
- Antenna must use a unique type of connector to attach to the EUT.
- Unit must be professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.

#### Accessory Information:

No.

## 1.2 Description of Test Configuration

### 1.2.1 EUT Operation Condition:

<b>EUT Operation Mode:</b>	The system was configured for testing in Engineering Mode, which was provided by the manufacturer.
<b>Equipment Modifications:</b>	No
<b>EUT Exercise Software:</b>	No
Engineering Mode was provided by manufacturer ▲. The maximum power was configured default setting.	

### 1.2.2 Support Equipment List and Details


Manufacturer	Description	Model	Serial Number
ORIENTAL HERO ELE.FTY	POWER ADAPTER	OH-101511201000U3-UL	E230964
NA	NFC Card	EINOLDA	EMZBNC21103001
Lenovo	Laptop	T460S	60PDTEK8
Unknown	Door Bell	Unknown	Unknown
ZKAT	Wiegand Card Reader	Q-K201D	N/A

### 1.2.3 Support Cable List and Details


Cable Description	Shielding Type	Ferrite Core	Length (m)	From Port	To
Adapter cable	Yes	No	0.8	EUT	Adapter
Cable*2	No	No	3	EUT(RS485)	Laptop
Cable*2	No	No	3	EUT()	Wiegand Card Reader
Cable*1	No	No	3	EUT	Door Bell

### 1.2.4 Block Diagram of Test Setup

Conducted emissions



Radiated emissions





### 1.3 Measurement Uncertainty

Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty. The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor K with the 95% confidence interval.

Parameter	Measurement Uncertainty
Occupied Channel Bandwidth	±5 %
Unwanted Emissions, radiated	9kHz~30MHz: 4.12dB 30M~200MHz: 4.15 dB,200M~1GHz: 5.61 dB,1G~6GHz: 5.14 dB, 6G~18GHz: 5.93 dB,18G~26.5G:5.47 dB,26.5G~40G:5.63 dB
Temperature	±1 °C
Humidity	±5%
DC and low frequency voltages	±0.4%
Duty Cycle	1%
AC Power Lines Conducted Emission	2.8 dB (150 kHz to 30 MHz)

## 2. SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
FCC§15.203	Antenna Requirement	Compliant
FCC§15.207 (a)	Conducted Emissions	Compliant
§15.225 §15.209 §15.205	Radiated Emission Test	Compliant
§15.225(e)	Frequency Stability	Compliant
§15.215(c)	20 dB Bandwidth	Compliant
§1.1307	RF Exposure Evaluation	Compliant

### 3. REQUIREMENTS AND TEST PROCEDURES

#### 3.1 AC Line Conducted Emissions

##### 3.1.1 Applicable Standard

FCC§15.207(a).

(a) Except as shown in paragraphs (b) and (c) of this section, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table, as measured using a 50  $\mu$ H/50 ohms line impedance stabilization network (LISN). Compliance with the provisions of this paragraph shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower limit applies at the boundary between the frequency ranges.

Frequency of emission (MHz)	Conducted limit (dB $\mu$ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

\*Decreases with the logarithm of the frequency.

(b) The limit shown in paragraph (a) of this section shall not apply to carrier current systems operating as intentional radiators on frequencies below 30 MHz. In lieu thereof, these carrier current systems shall be subject to the following standards:

(1) For carrier current system containing their fundamental emission within the frequency band 535-1705 kHz and intended to be received using a standard AM broadcast receiver: no limit on conducted emissions.

(2) For all other carrier current systems: 1000  $\mu$ V within the frequency band 535-1705 kHz, as measured using a 50  $\mu$ H/50 ohms LISN.

(3) Carrier current systems operating below 30 MHz are also subject to the radiated emission limits in §15.205, §15.209, §15.221, §15.223, or §15.227, as appropriate.

(c) Measurements to demonstrate compliance with the conducted limits are not required for devices which only employ battery power for operation and which do not operate from the AC power lines or contain provisions for operation while connected to the AC power lines. Devices that include, or make provisions for, the use of battery chargers which permit operating while charging, AC adapters or battery eliminators or that connect to the AC power lines indirectly, obtaining their power through another device which is connected to the AC power lines, shall be tested to demonstrate compliance with the conducted limits.

### 3.1.2 EUT Setup



- Note: 1. Support units were connected to second LISN.  
 2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.207 limits.

The spacing between the peripherals was 10 cm.

The adapter or EUT was connected to the main LISN with a 120 V/60 Hz AC power source.

### 3.1.3 EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

### 3.1.4 Test Procedure

During the conducted emission test, the adapter was connected to the outlet of the LISN.

The frequency and amplitude of the six highest ac power-line conducted emissions relative to the limit, measured over all the current-carrying conductors of the EUT power cords, and the operating frequency or frequency to which the EUT is tuned (if appropriate), should be reported, unless such emissions are more than 20 dB below the limit. AC power-line conducted emissions measurements are to be separately carried out only on each of the phase (“hot”) line(s) and (if used) on the neutral line(s), but not on the ground [protective earth] line(s). If less than six emission frequencies are within 20 dB of the limit, then the noise level of the measuring instrument at representative frequencies should be reported. The specific conductor of the power-line cord for each of the reported emissions should be identified. Measure the six highest emissions with respect to the limit on each current-carrying conductor of each power cord associated with the EUT (but not the power cords of associated or peripheral equipment that are part of the test configuration). Then, report the six highest emissions with respect to the limit from among all the measurements identifying the frequency and specific current-carrying conductor identified with the emission. The six highest emissions should be reported for each of the current-carrying conductors, or the six highest emissions may be reported over all the current-carrying conductors.

According FCC publication number 174176, for a device with a permanent antenna operating at or below 30 MHz, the measurements done with a suitable dummy load, in lieu of the permanent antenna under the following conditions: (1) perform the AC line conducted tests with the permanent antenna to determine compliance with the Section 15.207 limits outside the transmitter's fundamental emission band; (2) retest with a dummy load in lieu of the permanent antenna to determine compliance with the Section 15.207 limits within the transmitter's fundamental emission band.

### 3.1.5 Corrected Amplitude & Margin Calculation

The basic equation is as follows:

Result = Reading + Factor

Factor = attenuation caused by cable loss + voltage division factor of AMN

The “**Margin**” column of the following data tables indicates the degree of compliance within the applicable limit. The equation for margin calculation is as follows:

Margin = Limit – Result

## 3.2 Radiated Emissions


### 3.2.1 Applicable Standard

As per FCC Part 15.225


- The field strength of any emissions within the band 13.553–13.567 MHz shall not exceed 15,848 microvolts/meter at 30 meters.
- Within the bands 13.410–13.553 MHz and 13.567–13.710 MHz, the field strength of any emissions shall not exceed 334 microvolts/meter at 30 meters.
- Within the bands 13.110–13.410 MHz and 13.710–14.010 MHz the field strength of any emissions shall not exceed 106 microvolts/meter at 30 meters.
- The field strength of any emissions appearing outside of the 13.110–14.010 MHz band shall not exceed the general radiated emission limits in §15.209.

### 3.2.2 EUT Setup

9kHz-30MHz:



30MHz-1GHz:



The radiated emission tests were performed in the 3-meter chamber test site, using the setup accordance with the ANSI C63.10-2013.

The spacing between the peripherals was 10 cm.

For 9kHz-30MHz test, the lowest height of the magnetic antenna shall be 1 m above the ground and three antenna orientations (parallel, perpendicular, and ground-parallel) shall be measured.

### 3.2.3 EMI Test Receiver & Spectrum Analyzer Setup

The system was investigated from 9 kHz to 1 GHz.

During the radiated emission test, the EMI test Receiver was set with the following configurations:

Frequency Range	RBW	Video B/W	Detector
9 kHz – 150 kHz	200 Hz	1 kHz	QP
150 kHz – 30 MHz	9 kHz	30 kHz	QP
30 MHz – 1000 MHz	120 kHz	300 kHz	QP

If the maximized peak measured value complies with under the QP limit more than 6dB, then it is unnecessary to perform an QP measurement

### 3.2.4 Corrected Amplitude & Margin Calculation

The basic equation is as follows:

Result = Reading + Factor

Factor = Antenna Factor + Cable Loss- Amplifier Gain

The “**Margin**” column of the following data tables indicates the degree of compliance within the applicable limit. The equation for margin calculation is as follows:

Margin = Limit – Result


### 3.3 20 dB Emission Bandwidth:

#### 3.3.1 Applicable Standard

FCC §15.215

Intentional radiators operating under the alternative provisions to the general emission limits, as contained in §15.217 through § 15.257 and in Subpart E of this part, must be designed to ensure that the 20 dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated. The requirement to contain the designated bandwidth of the emission within the specified frequency band includes the effects from frequency sweeping, frequency hopping and other modulation techniques that may be employed as well as the frequency stability of the transmitter over expected variations in temperature and supply voltage. If a frequency stability is not specified in the regulations, it is recommended that the fundamental emission be kept within at least the central 80% of the permitted band in order to minimize the possibility of out-of band operation.

#### 3.3.2 EUT Setup



#### 3.3.3 Test Procedure

1. Position the EUT on the test table without connection to measurement instrument. Turn on the EUT. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
2. Measure the frequency difference of two frequencies that were attenuated 20 dB from the reference level. Record the frequency difference as the emission bandwidth.




### 3.4 Frequency Stability

#### 3.4.1 Applicable Standard

As per FCC Part 15.225:

The frequency tolerance of the carrier signal shall be maintained within  $\pm 0.01\%$  of the operating frequency over a temperature variation of  $-20$  degrees to  $+50$  degrees C at normal supply voltage, and for a variation in the primary supply voltage from 85% to 115% of the rated supply voltage at a temperature of 20 degrees C. For battery operated equipment, the equipment tests shall be performed using a new battery.

#### 3.4.2 EUT Setup



#### 3.4.3 Test Procedure

Frequency Stability vs. Temperature: The equipment under test was connected to an external DC power.

The EUT was placed inside the temperature chamber.

After the temperature stabilized for approximately 20 minutes, the frequency output was recorded from the Spectrum Analyzer.

Frequency Stability vs. Voltage: An external variable DC power supply Source. The voltage was set to the end point of the battery. The output frequency was recorded for each voltage.

## **3.5 Antenna Requirement**

### **3.5.1 Applicable Standard**

FCC §15.203

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the user of a standard antenna jack or electrical connector is prohibited. The structure and application of the EUT were analyzed to determine compliance with section §15.203 of the rules. §15.203 state that the subject device must meet the following criteria:

- a. Antenna must be permanently attached to the unit.
- b. Antenna must use a unique type of connector to attach to the EUT.
- c. Unit must be professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.

### **3.5.2 Judgment**

**Compliant.** Please refer to the Antenna Information detail in Section 1.

## 4. TEST DATA AND RESULTS

### 4.1 AC Line Conducted Emissions

Serial Number:	1V3Q-1	Test Date:	2022/12/16
Test Site:	CE	Test Mode:	Transmitting
Tester:	Vic Du	Test Result:	Pass

#### Environmental Conditions:

Temperature: (°C)	20.1	Relative Humidity: (%)	50	ATM Pressure: (kPa)	101.7
----------------------	------	------------------------------	----	------------------------	-------


#### Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	LISN	ENV216	101134	2022/04/01	2023/03/31
R&S	EMI Test Receiver	ESR3	102726	2022/07/15	2023/07/14
MICRO-COAX	Coaxial Cable	UTIFLEX	C-0200-01	2022/08/07	2023/08/06
Audix	Test Software	E3	190306 (V9)	N/A	N/A

\* Statement of Traceability: China Certification ICT Co., Ltd (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Mode: Transmitting  
 Port: Line  
 Note:


Date: 2022-12-16



No.	Frequency (MHz)	Reading (dBμV)	Factor (dB)	Result (dBμV)	Limit (dBμV)	Margin (dB)	Detector
1	0.305	23.84	9.61	33.45	50.09	16.64	Average
2	0.305	32.83	9.61	42.44	60.09	17.65	QP
3	0.538	10.63	9.61	20.24	46.00	25.76	Average
4	0.538	17.48	9.61	27.09	56.00	28.91	QP
5	1.188	13.00	9.62	22.62	46.00	23.38	Average
6	1.188	20.73	9.62	30.35	56.00	25.65	QP
7	3.902	3.72	9.65	13.37	46.00	32.63	Average
8	3.902	15.36	9.65	25.01	56.00	30.99	QP
9	13.560	37.25	9.68	46.93	50.00	3.07	Average
10	13.560	44.98	9.68	54.66	60.00	5.34	QP
11	27.121	38.92	9.83	48.75	50.00	1.25	Average
12	27.121	43.40	9.83	53.23	60.00	6.77	QP

Test Mode: Transmitting  
 Port: neutral  
 Note:

Date: 2022-12-16



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1	0.310	24.24	9.61	33.85	49.97	16.12	Average
2	0.310	32.68	9.61	42.29	59.97	17.68	QP
3	0.537	13.97	9.61	23.58	46.00	22.42	Average
4	0.537	19.88	9.61	29.49	56.00	26.51	QP
5	1.179	17.85	9.62	27.47	46.00	18.53	Average
6	1.179	24.52	9.62	34.14	56.00	21.86	QP
7	13.559	36.90	9.68	46.58	50.00	3.42	Average
8	13.559	43.88	9.68	53.56	60.00	6.44	QP
9	24.814	10.45	9.76	20.21	50.00	29.79	Average
10	24.814	18.14	9.76	27.90	60.00	32.10	QP
11	27.119	38.94	9.80	48.74	50.00	1.26	Average
12	27.119	46.44	9.80	56.24	60.00	3.76	QP

**4.2 Radiation Spurious Emissions**

Serial Number:	1V3Q-1	Test Date:	2023/04/18
Test Site:	966-2	Test Mode:	Transmitting
Tester:	Carl Xue	Test Result:	Pass

**Environmental Conditions:**

Temperature: (°C)	27.4	Relative Humidity: (%)	54	ATM Pressure: (kPa)	100.5
----------------------	------	---------------------------	----	---------------------------	-------

**Test Equipment List and Details:**


Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
EMCO	Passive Loop Antenna	6512	9706-1209	2023/2/15	2026/2/14
Sunol Sciences	Antenna	JB6	A082520-5	2020/10/19	2023/10/18
R&S	EMI Test Receiver	ESR3	102724	2022/07/15	2023/07/14
TIMES MICROWAVE	Coaxial Cable	LMR-600-UltraFlex	C-0470-02	2022/07/17	2023/07/16
TIMES MICROWAVE	Coaxial Cable	LMR-600-UltraFlex	C-0780-01	2022/07/17	2023/07/16
Sonoma	Amplifier	310N	186165	2022/07/17	2023/07/16
Audix	Test Software	E3	201021 (V9)	N/A	N/A

\* Statement of Traceability: China Certification ICT Co., Ltd (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

**Test Data:**


1) 9 kHz~30MHz:

**Parallel:**



Test Mode: Transmitting  
 Polarization: Parallel  
 Note:

Date: 2023-04-18




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	0.672	33.56	20.01	53.57	71.00	17.43	Peak
2	0.890	37.96	17.82	55.78	68.51	12.73	Peak
3	1.065	39.79	16.49	56.28	66.91	10.63	Peak
4	2.594	34.56	9.50	44.06	69.54	25.48	Peak
5	10.019	27.77	4.39	32.16	69.54	37.38	Peak
6	13.551	74.90	-6.36	68.54	69.54	1.00	Peak



Test Mode: Transmitting  
 Polarization: Parallel  
 Note:


Date: 2023-04-18



No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	13.348	36.39	-5.75	30.64	80.51	49.87	Peak
2	13.422	37.28	-5.98	31.30	90.47	59.17	Peak
3	13.484	39.70	-6.17	33.53	90.47	56.94	Peak
4	13.560	75.05	-6.38	68.67	124.00	55.33	Peak
5	13.629	39.47	-6.59	32.88	90.47	57.59	Peak
6	13.704	37.15	-6.82	30.33	90.47	60.14	Peak


**Perpendicular:**

Test Mode: Transmitting  
 Polarization: Perpendicular  
 Note:




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	0.010	7.33	58.10	65.43	127.66	62.23	Peak
2	0.012	7.31	56.22	63.53	125.98	62.45	Peak
3	0.015	6.52	53.64	60.16	124.07	63.91	Peak
4	0.024	6.34	47.78	54.12	119.97	65.85	Peak
5	0.050	4.66	42.26	46.92	113.61	66.69	Peak
6	0.060	2.16	40.07	42.23	112.05	69.82	Peak

Test Mode: Transmitting  
 Polarization: Perpendicular  
 Note:



No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	0.576	32.37	21.24	53.61	72.36	18.75	Peak
2	0.876	39.67	17.91	57.58	68.65	11.07	Peak
3	1.071	43.09	16.46	59.55	66.86	7.31	Peak
4	2.622	41.88	9.42	51.30	69.54	18.24	Peak
5	10.072	39.97	4.23	44.20	69.54	25.34	Peak
6	13.551	73.79	-6.36	67.43	69.54	2.11	Peak


Test Mode: Transmitting  
 Polarization: Perpendicular  
 Note:



No.	Frequency (MHz)	Reading (dB $\mu$ V)	Factor (dB/m)	Result (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)	Detector
1	13.386	43.11	-5.87	37.24	80.51	43.27	Peak
2	13.418	43.50	-5.97	37.53	90.47	52.94	Peak
3	13.481	44.56	-6.16	38.40	90.47	52.07	Peak
4	13.559	74.14	-6.38	67.76	124.00	56.24	Peak
5	13.634	42.74	-6.61	36.13	90.47	54.34	Peak
6	13.774	38.92	-7.04	31.88	80.51	48.63	Peak

**Ground-parallel:**


Test Mode: Transmitting  
 Polarization: Ground-parallel  
 Note:



Date: 2023-04-18

No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	0.010	7.74	57.91	65.65	127.49	61.84	Peak
2	0.024	9.08	47.82	56.90	120.02	63.12	Peak
3	0.030	3.51	45.56	49.07	117.99	68.92	Peak
4	0.050	8.35	42.29	50.64	113.64	63.00	Peak
5	0.060	4.58	40.04	44.62	112.02	67.40	Peak
6	0.070	6.04	38.25	44.29	110.70	66.41	Peak


Test Mode: Transmitting  
 Polarization: Ground-parallel  
 Note:



No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	0.694	33.59	19.72	53.31	70.72	17.41	Peak
2	0.890	40.28	17.82	58.10	68.51	10.41	Peak
3	1.077	40.47	16.42	56.89	66.82	9.93	Peak
4	2.297	33.45	10.36	43.81	69.54	25.73	Peak
5	9.861	28.09	4.46	32.55	69.54	36.99	Peak
6	13.551	73.86	-6.36	67.50	69.54	2.04	Peak

Test Mode: Transmitting  
 Polarization: Ground-parallel  
 Note:


Date: 2023-04-18



No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	13.348	35.05	-5.75	29.30	80.51	51.21	Peak
2	13.420	36.28	-5.98	30.30	90.47	60.17	Peak
3	13.484	36.35	-6.17	30.18	90.47	60.29	Peak
4	13.560	73.40	-6.38	67.02	124.00	56.98	Peak
5	13.666	35.99	-6.71	29.28	90.47	61.19	Peak
6	13.772	32.45	-7.03	25.42	80.51	55.09	Peak

2) 30MHz-1GHz:

Test Mode: Transmitting  
 Polarization: horizontal  
 Note:




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	54.261	46.33	-17.27	29.06	40.00	10.94	Peak
2	162.611	49.72	-12.31	37.41	43.50	6.09	Peak
3	189.837	55.28	-13.47	41.81	43.50	1.69	QP
4	205.905	51.56	-12.38	39.18	43.50	4.32	QP
5	216.965	52.79	-12.70	40.09	46.00	5.91	QP
6	298.268	47.10	-10.68	36.42	46.00	9.58	Peak



Test Mode: Transmitting  
 Polarization: vertical  
 Note:

Date: 2023-04-18



No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	40.679	45.97	-11.72	34.25	40.00	5.75	QP
2	54.237	49.81	-17.27	32.54	40.00	7.46	QP
3	162.611	48.90	-12.31	36.59	43.50	6.91	Peak
4	189.830	53.15	-13.47	39.68	43.50	3.82	QP
5	210.048	49.86	-12.47	37.39	43.50	6.11	Peak
6	298.268	41.72	-10.68	31.04	46.00	14.96	Peak

**4.3 20 dB Emission Bandwidth**

Serial Number:	1V3Q-1	Test Date:	2023/04/18
Test Site:	966-2	Test Mode:	Transmitting
Tester:	Carl Xue	Test Result:	Pass

**Environmental Conditions:**

Temperature: (°C)	27.4	Relative Humidity: (%)	54	ATM Pressure: (kPa)	100.5
----------------------	------	---------------------------	----	---------------------------	-------

**Test Equipment List and Details:**


Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
EMCO	Passive Loop Antenna	6512	9706-1209	2023/2/15	2026/2/14
R&S	EMI Test Receiver	ESR3	102724	2022/07/15	2023/07/14
TIMES MICROWAVE	Coaxial Cable	LMR-600-UltraFlex	C-0470-02	2022/07/17	2023/07/16
TIMES MICROWAVE	Coaxial Cable	LMR-600-UltraFlex	C-0780-01	2022/07/17	2023/07/16
Sonoma	Amplifier	310N	186165	2022/07/17	2023/07/16
Audix	Test Software	E3	201021 (V9)	N/A	N/A

*\* Statement of Traceability: China Certification ICT Co., Ltd (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).*

**Test Data:**

Test Frequency (MHz)	20 dB Bandwidth (Hz)
13.56	799

### 20dB Emission Bandwidth



**4.4 Frequency Stability**

Serial Number:	1V3Q-1	Test Date:	2023/04/18
Test Site:	RF	Test Mode:	Transmitting
Tester:	Carl Xue	Test Result:	Pass

**Environmental Conditions:**

Temperature: (°C)	27.1	Relative Humidity: (%)	58	ATM Pressure: (kPa)	100.5
----------------------	------	---------------------------	----	---------------------------	-------

**Test Equipment List and Details:**

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
EMCO	Passive Loop Antenna	6512	9706-1209	2023/2/15	2026/2/14
R&S	EMI Test Receiver	ESR3	102724	2022/07/15	2023/07/14
BACL	TEMP&HUMI Test Chamber	BTH-150-40	30174	2023/04/06	2024/04/05
YINSAIGE	Coaxial Cable	SS402	SJ0300001	Each time	N/A
UNI-T	Multimeter	UT39A+	C210582554	2022/09/29	2023/09/28
ZHAOXIN	DC Power Supply	RXN-6010D	21R6010D0912386	N/A	N/A

\* **Statement of Traceability:** China Certification ICT Co., Ltd (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

**Test Data:**

<b><math>f_0 = 13.56</math> MHz</b>					
Temperature	Voltage	Measured frequency	Frequency Error	Limit	
°C	V <sub>DC</sub>	MHz	Hz	Hz	
-20	12	13.5599482	-51.8	±1356	
-10		13.5599527	-47.3	±1356	
0		13.5599613	-38.7	±1356	
10		13.5599446	-55.4	±1356	
20		13.5599200	-80.0	±1356	
25		13.5599378	-62.2	±1356	
30		13.5599295	-70.5	±1356	
40		13.5599217	-78.3	±1356	
50		13.5599553	-44.7	±1356	
20		10	13.5599330	-67.0	±1356
20		24	13.5599572	-42.8	±1356

## 5. RF EXPOSURE EVALUATION

### 5.1 Applicable Standard

FCC §1.1307(b)(3)(i)(A)

a single RF source is exempt RF device (from the requirement to show data demonstrating compliance to RF exposure limits, as previously mentioned) if the available maximum time-averaged power is no more than 1 mW, regardless of separation distance.

### 5.2 Procedure

According to 447498 D04 Interim General RF Exposure Guidance v01, clause 2.1.2- 1-mW Test Exemption:

Per §1.1307(b)(3)(i)(A), a single RF source is *exempt RF device* (from the requirement to show data demonstrating compliance to RF exposure limits, as previously mentioned) if the available maximum time-averaged power is no more than 1 mW, regardless of separation distance.

This exemption applies to all operating configurations and exposure conditions, for the frequency range 100 kHz to 100 GHz, regardless of fixed, mobile, or portable device exposure conditions. This is a standalone exemption, and it cannot be applied in conjunction with any other test exemption.

### 5.3 Measurement Result

Frequency (MHz)	Maximum ERP Power		1-mW Test Exemption
	dBm	mW	
13.56	-28.68	0.001	Compliant

Note:

1. Chose the maximum power to do MPE analysis.
2. This device maximum E-Field level is 68.67 dB $\mu$ V/m at 3m, so the EIRP power is -26.53dBm.
3. EIRP(dBm)=Field Strength of Fundamental(dBuV/m)-95.2
4. ERP(dBm)= EIRP(dBm)-2.15dB

**Result: Compliant.** RF Exposure is exemption.

===== END OF REPORT =====