

Ampt, LLC

RF Exposure Exhibit

SCOPE OF WORK

EMC TESTING – Communication Unit, Model Tested: 31570025

REPORT NUMBER

105434881MPK-005

ISSUE DATE

June 29, 2023

REVISED DATE

N/A

PAGES

10

DOCUMENT CONTROL NUMBER

Non-Specific Radio Report Shell Rev. December 2017 MPK
© 2017 INTERTEK



RF Exposure Exhibit (Mobile Devices)

Report Number: 105434881MPK-005

Project Number: G105434881

Report Issue Date: June 29, 2023

Product Designation: Communication Unit

Model Tested: 31570025

to

47CFR 2.1091
RSS-102 Issue 5

for

Ampt, LLC

Tested by:

Intertek
1365 Adams Court
Menlo Park, CA 94025 USA

Client:

Ampt, LLC
4850 Innovation Drive
Fort Collins, CO 80525 USA

Report prepared by:



Kenneth Roque / EMC Project Engineer

Report reviewed by:



Anderson Soungpanya / EMC Team Leader

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

Report No. 105434881MPK-005	
Equipment Under Test:	Communication Unit
Model(s) Tested:	31570025
Applicant:	Ampt, LLC
Contact:	Robin Richardson
Address:	Ampt, LLC 4850 Innovation Drive Fort Collins, CO 80525
Country:	USA
Tel. Number:	1 (970) 372-6960
Email:	robin.richardson@ampt.com
Applicable Regulation:	47CFR 2.1091 RSS-102 Issue 5

TABLE OF CONTENTS

<i>Ampt, LLC</i>	1
1.0 RF Exposure Summary	5
2.0 RF Exposure Limits	5
3.0 Test Results (Mobile Configuration)	7
Appendix A: Power Density Calculation	9
4.0 Document History	10

1.0 RF Exposure Summary

Test	Reference FCC	Reference Industry Canada	Result
Radio frequency Radiation Exposure Evaluation	47 CFR§2.1091	RSS-102 Issue 5	Complies

2.0 RF Exposure Limits

In this document, we evaluate the RF Exposure to human body due the intentional transmission from the transmitter (EUT). The limits for Maximum Permissible Exposure (MPE) specified in FCC 1.1310 and RSS-102 are followed.

2.1 FCC Limits

According to FCC 1.1310 table 1: The criteria listed in the following table shall be used to evaluate the environmental impact of human exposure to radio-frequency (RF) radiation as specified in 1.1307(b)

LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (minutes)
(A)Limits For Occupational / Control Exposures				
0.3 – 3.0	614	1.63	*100	6
3.0 – 30	1842/f	4.89/f	*900/f ²	6
30-300	61.4	0.163	1.0	6
300 - 1500	F/300	6
1500 - 100,000	5	6
(B)Limits For General Population / Uncontrolled Exposure				
0.3 – 1.34	614	1.63	*100	30
1.34 – 30	824/f	2.19/f	*180/f ²	30
30 – 300	27.5	0.073	0.2	30
300 - 1500	F/1500	30
1500 - 100,000	1.0	30

F = Frequency in MHz

* = plane wave equivalent density

2.2 Industry Canada Limits

According to RSS-102, Industry Canada has adopted the SAR and RF field strength limits established in Health Canada's RF exposure guideline, Safety Code 6.

Table 4: RF Field Strength Limits for Devices Used by the General Public (Uncontrolled Environment)				
Frequency Range	Electric Field	Magnetic Field	Power Density	Reference Period
(MHz)	(V/m rms)	(A/m rms)	(W/m ²)	(minutes)
0.003-10	83	90	-	Instantaneous*
0.1-10	-	0.73/ f	-	6**
1.1-10	87/ f ^{0.5}	-	-	6**
10-20	27.46	0.0728	2	6
20-48	58.07/ f ^{0.25}	0.1540/ f ^{0.25}	8.944/ f ^{0.5}	6
48-300	22.06	0.05852	1.291	6
300-6000	3.142 f ^{0.3417}	0.008335 f ^{0.3417}	0.02619 f ^{0.6834}	6
6000-15000	61.4	0.163	10	6
15000-150000	61.4	0.163	10	616000/ f ^{1.2}
150000-300000	0.158 f ^{0.5}	4.21 x 10 ⁻⁴ f ^{0.5}	6.67 x 10 ⁻⁵ f	616000/ f ^{1.2}

Note: f is frequency in MHz.
 * Based on nerve stimulation (NS).
 ** Based on specific absorption rate (SAR).

3.0 Test Results (Mobile Configuration)

3.1 Classification

Radio is installed inside a mobile host device. The antenna of the product, under normal use condition, is at least 20 cm away from the body of the user and accessible to the end user. Warning statement to the user for keeping at least 20 cm or more separation distance with the antenna should be included in user's manual.

3.2 EIRP calculations

The Communication Unit, Model: 31570025 consists of one 2.4 GHz radio. For RF exposure compliance refer report # 105434881MPK-002.

3.3 Maximum RF Power

Frequency Range (MHz)	RF Output (dBm)	Antenna Gain ¹ (dBi)	Note
2410-2474.5	12.77	2.3	Conducted power measurements were taken from report # 105434881MPK-002.

¹As provided by the client. Intertek takes no responsibility for the accuracy of this information.

3.4 RF Exposure Calculation

3.4.1 RF Exposure Calculation for 2.4 GHz:

Frequency (MHz)	Power (dBm)	Antenna Gain (dBi)	EIRP (dBm)	EIRP (mW)	PD (mW/cm ²)	FCC PD Limits (mW/cm ²)	MPE Ratio FCC
2410-2474.5	12.77	2.3	15.07	32.14	0.0064	1	0.0064

Note: Antenna gains below 0 are considered as 0dBi.

Frequency (MHz)	Power (dBm)	Antenna Gain (dBi)	EIRP (dBm)	EIRP (mW)	PD (W/m ²)	ISED PD Limits (W/m ²)	MPE Ratio ISED
2410-2474.5	12.77	2.3	15.07	32.1366	0.0640	5.36	0.0119

Note: Antenna gains below 0 are considered as 0dBi.

Appendix A: Power Density Calculation

The Power Density can be calculated using the formula

$$S = \text{EIRP} / 4\pi D^2$$

Where: S is Power Density in mW/cm²

D is the distance from the antenna in cm.

4.0 Document History

Revision/ Job Number	Writer Initials	Reviewers Initials	Date	Change
1.0/ G105434881	KRQ	AS	June 29, 2023	Original document