

# RADIO PERFORMANCE TEST REPORT

**Test Report No.** : OT-245-RWD-018

**Reception No.** : 2312004386

**Applicant** : Amp'ed RF Technology

**Address** : 1879 Lundy Ave #138, San Jose, California, 95131, United States

**Manufacturer** : Amp'ed RF Technology

**Address** : 1879 Lundy Ave #138, San Jose, California, 95131, United States

**Type of Equipment** : Bluetooth Module

**FCC ID.** : X3ZBTMOD4

**Model Name** : BT33LT

**Serial number** : N/A

**Total page of Report** : 36 pages (including this page)

**Date of Incoming** : March 20, 2024

**Date of issue** : May 17, 2024

## SUMMARY

The equipment complies with the regulation; *FCC PART 15 SUBPART C Section 15.247*

This test report only contains the result of a single test of the sample supplied for the examination.

It is not a generally valid assessment of the features of the respective products of the mass-production.

**This report is not correlated with the "KS Q ISO/IEC 17025 and KOLAS accreditation" of Korean Laboratory Accreditation Scheme.**



Tested by  
Si-eon Lee / Sr. Engineer  
ONETECH Corp.



Reviewed by  
Tae-Ho, Kim / Chief Engineer  
ONETECH Corp.



Approved by  
Jae-Ho, Lee / Chief Engineer  
ONETECH Corp.

## CONTENTS

	Page
<b>1. VERIFICATION OF COMPLIANCE .....</b>	<b>6</b>
<b>2. TEST SUMMARY.....</b>	<b>7</b>
2.1 Test items and results .....	7
2.2 Additions, deviations, exclusions from standards .....	7
2.3 Related Submittal(s) / Grant(s).....	7
2.4 Purpose of the test.....	7
2.5 Test Methodology .....	7
2.6 Test Facility .....	7
<b>3. GENERAL INFORMATION.....</b>	<b>8</b>
3.1 Product Description.....	8
3.2 Alternative type(s)/model(s); also covered by this test report.....	8
<b>4. EUT MODIFICATIONS.....</b>	<b>8</b>
<b>5. SYSTEM TEST CONFIGURATION .....</b>	<b>9</b>
5.1 Justification .....	9
5.2 Peripheral equipment .....	9
5.3 Mode of operation during the test.....	10
5.4 Configuration of Test System .....	13
5.5 Antenna Requirement .....	13
<b>6. PRELIMINARY TEST .....</b>	<b>13</b>
6.1 AC Power line Conducted Emissions Tests .....	13
6.2 General Radiated Emissions Tests .....	13
<b>7. MINIMUM 20 dB BANDWIDTH.....</b>	<b>14</b>
7.1 Operating environment .....	14
7.2 Test set-up .....	14
7.3 Test Date.....	14
7.4 Test data for 1 Mbps .....	14
7.5 Test data for 2 Mbps .....	14
7.6 Test data for 3 Mbps .....	14
<b>8. HOPPING FREQUENCY SEPARATION.....</b>	<b>15</b>
8.1 Operating environment .....	15
8.2 Test set-up .....	15
8.3 Test Date.....	15

8.4 Test data for 1 Mbps .....	15
8.5 Test data for 2 Mbps .....	15
8.6 Test data for 3 Mbps .....	15
<b>9. NUMBER OF HOPPING CHANNELS .....</b>	<b>16</b>
9.1 Operating environment .....	16
9.2 Test set-up .....	16
9.3 Test Date .....	16
9.4 Test data for 1 Mbps .....	16
9.5 Test data for 2 Mbps .....	16
9.6 Test data for 3 Mbps .....	16
<b>10. TIME OF OCCUPANCY .....</b>	<b>17</b>
10.1 Operating environment .....	17
10.2 Test set-up .....	17
10.3 Test Date .....	17
10.4 Test data for 1 Mbps .....	18
10.5 Test data for 2 Mbps .....	18
10.6 Test data for 3 Mbps .....	19
<b>11. MAXIMUM PEAK OUTPUT POWER .....</b>	<b>20</b>
11.1 Operating environment .....	20
11.2 Test set-up .....	20
11.3 Test Date .....	20
11.4 Test data for 1 Mbps .....	21
11.5 Test data for 2 Mbps .....	21
11.6 Test data for 3 Mbps .....	21
<b>12. 100 kHz BANDWIDTH OUTSIDE THE FREQUENCY BAND .....</b>	<b>22</b>
12.1 Operating environment .....	22
12.2 Test set-up for conducted measurement .....	22
12.3 Test set-up for radiated measurement .....	22
12.4 Test Date .....	22
12.5 Test data for conducted emission .....	22
12.6 Test data for Transmitting mode radiated emission .....	23
12.6.1 Radiated Emission which fall in the Restricted Band.....	23
12.6.2 Spurious & Harmonic Radiated Emission above 1 GHz.....	26
<b>13. RADIATED EMISSION TEST .....</b>	<b>29</b>
13.1 Operating environment .....	29
13.2 Test set-up .....	29

13.3 Test Date .....30

13.4 Test data for 30 MHz ~ 1 000 MHz .....31

13.5 Test data for Below 30 MHz .....32

13.6 Test data for above 1 GHz .....32

**14. CONDUCTED EMISSION TEST .....33**

14.1 Operating environment .....33

14.2 Test set-up .....33

14.3 Measurement uncertainty .....33

14.4 Test date.....33

14.5 Test data .....34

**15. LIST OF TEST EQUIPMENT .....36**

※ Please refer to the Annex section for All test plots

**Revision History**

Rev. No.	Issue Report No.	Issued Date	Revisions	Section Affected
0	OT-245-RWD-018	May 17, 2024	Initial Release	All

## 1. VERIFICATION OF COMPLIANCE

Applicant : Amp'ed RF Technology  
 Address : 1879 Lundy Ave #138, San Jose, California, 95131, United States  
 Contact Person : Annie, Cai / Operations Manager  
 Telephone No. : +82-70-4991-9718  
 FCC ID : X3ZBTMOD4  
 Model Name : BT33LT  
 Brand Name : -  
 Serial Number : N/A  
 Date : May 17, 2024

EQUIPMENT CLASS	DSS – PART 15 SPREAD SPECTRUM TRANSMITTER
E.U.T. DESCRIPTION	Bluetooth Module
THIS REPORT CONCERNS	Original Grant
MEASUREMENT PROCEDURES	ANSI C63.10: 2013
TYPE OF EQUIPMENT TESTED	Pre-Production
KIND OF EQUIPMENT AUTHORIZATION REQUESTED	Certification
EQUIPMENT WILL BE OPERATED UNDER FCC RULES PART(S)	FCC PART 15 SUBPART C Section 15.247 KDB 558074 D01 15.247 Meas Guidance v05r02
Modifications on the Equipment to Achieve Compliance	None
Final Test was Conducted On	3 m, Semi Anechoic Chamber

-. The above equipment was tested by ONETECH Corp. for compliance with the requirement set forth in the FCC Rules and Regulations. This said equipment in the configuration described in this report, shows the maximum emission levels emanating from equipment are within the compliance requirements.

## 2. TEST SUMMARY

### 2.1 Test items and results

SECTION	TEST ITEMS	RESULTS
15.247 (a) (1)	Carrier Frequency Separation	Met the Limit / PASS
15.247 (a) (1) (iii)	Minimum Number of Hopping Channels	Met the Limit / PASS
15.247 (a) (1) (iii)	Average Time of Occupancy	Met the Limit / PASS
15.247 (b) (1)	Maximum Peak Conducted Output Power	Met the Limit / PASS
15.247 (d)	100 kHz Bandwidth Outside the Frequency Band	Met the Limit / PASS
15.247 (d)	Radiated Emission which fall in the Restricted Band	Met the Limit / PASS
15.209	Radiated Emission Limits, General Requirement	Met the Limit / PASS
15.207	Conducted Limits	Met the Limit / PASS
15.203	Antenna Requirement	Met requirement / PASS

Note: This test is not performed because the EUT is operated by only using DC Power.

### 2.2 Additions, deviations, exclusions from standards

No additions, deviations or exclusions have been made from standard.

### 2.3 Related Submittal(s) / Grant(s)

Original submittal only

### 2.4 Purpose of the test

To determine whether the equipment under test fulfills the requirements of the regulation stated in FCC PART 15 SUBPART C Section 15.247.

### 2.5 Test Methodology

Both conducted and radiated testing was performed according to the procedures in ANSI C63.10: 2013. Radiated testing was performed at a distance of 3 m from EUT to the antenna.

### 2.6 Test Facility

The Onetech Corp. has been designated to perform equipment testing in compliance with ISO/IEC 17025.

The Electromagnetic compatibility measurement facilities are located at 43-14, Jinsaegol-gil, Chowol-eup, Gwangju-si, Gyeonggi-do, 12735, Korea.

-. Site Filing:

VCCI (Voluntary Control Council for Interference) – Registration No. R-20122/ C-14617/ G-10666/ T-11842

ISED (Innovation, Science and Economic Development Canada) – Registration No. Site# 3736A-3

KOLAS (Korea Laboratory Accreditation Scheme) - Accreditation NO. KT085

FCC (Federal Communications Commission) - Accreditation No. KR0013

RRA (Radio Research Agency) – Designation No. KR0013

### 3. GENERAL INFORMATION

#### 3.1 Product Description

The Amp'ed RF Technology, Model BT33LT (referred to as the EUT in this report) is a Bluetooth Module. The product specification described herein was obtained from product data sheet or user's manual.

DEVICE TYPE	Bluetooth Module
OPERATING FREQUENCY	2 402 MHz ~ 2 480 MHz
MODULATION TYPE	GFSK for 1 Mbps, $\pi/4$ -DQPSK for 2 Mbps, 8-DPSK for 3 Mbps
RF OUTPUT POWER	3.04 dBm (1 Mbps), 0.76 dBm (2 Mbps), 0.95 dBm (3 Mbps)
ANTENNA TYPE	Chip Antenna
ANTENNA GAIN	-0.97 dBi
List of each Osc. or crystal Freq.(Freq. $\geq$ 1 MHz)	38.4 MHz
RATED SUPPLY VOLTAGE	DC 3.70 V

#### 3.2 Alternative type(s)/model(s); also covered by this test report.

-. None

### 4. EUT MODIFICATIONS

-. None



## 5. SYSTEM TEST CONFIGURATION

### 5.1 Justification

This device was configured for testing in a typical way as a normal customer is supposed to be used. During the test, the following components were installed inside of the EUT.

DEVICE TYPE	MANUFACTURER	MODEL/PART NUMBER	FCC ID
Main Board	Amp'ed RF Technology	N/A	X3ZBTMOD4

### 5.2 Peripheral equipment

Defined as equipment needed for correct operation of the EUT, but not considered as tested:

Model	Manufacturer	Description	Connected to
BT33LT	Amp'ed RF Technology	Bluetooth Module (EUT)	-
NT300V5A-S55S	SAMSUNG	Notebook PC	EUT

### 5.3 Mode of operation during the test

For the testing, software used to control the EUT for staying in continuous transmitting is programmed.

For final testing, the EUT was set at 2 402 MHz, 2 441 MHz, and 2 480 MHz to get a maximum emission levels from the EUT. The EUT was moved throughout the XY, XZ, and YZ planes and the worst case is “XY” axis, but the worst data was recorded in this report.

#### - Channel List (Bluetooth)

Channel	Frequency[MHz]	Channel	Frequency[MHz]	Channel	Frequency[MHz]
0	2 402.00	27	2 429.00	54	2 456.00
1	2 403.00	28	2 430.00	55	2 457.00
2	2 404.00	29	2 431.00	56	2 458.00
3	2 405.00	30	2 432.00	57	2 459.00
4	2 406.00	31	2 433.00	58	2 460.00
5	2 407.00	32	2 434.00	59	2 461.00
6	2 408.00	33	2 435.00	60	2 462.00
7	2 409.00	34	2 436.00	61	2 463.00
8	2 410.00	35	2 437.00	62	2 464.00
9	2 411.00	36	2 438.00	63	2 465.00
10	2 412.00	37	2 439.00	64	2 466.00
11	2 413.00	38	2 440.00	65	2 467.00
12	2 414.00	39	2 441.00	66	2 468.00
13	2 415.00	40	2 442.00	67	2 469.00
14	2 416.00	41	2 443.00	68	2 470.00
15	2 417.00	42	2 444.00	69	2 471.00
16	2 418.00	43	2 445.00	70	2 472.00
17	2 419.00	44	2 446.00	71	2 473.00
18	2 420.00	45	2 447.00	72	2 474.00
19	2 421.00	46	2 448.00	73	2 475.00
20	2 422.00	47	2 449.00	74	2 476.00
21	2 423.00	48	2 450.00	75	2 477.00
22	2 424.00	49	2 451.00	76	2 478.00
23	2 425.00	50	2 452.00	77	2 479.00
24	2 426.00	51	2 453.00	78	2 480.00
25	2 427.00	52	2 454.00		
26	2 428.00	53	2 455.00		


- Duty Cycle


Mode	Tx On Time [ ms ]	Tx Off Time [ ms ]	Duty Cycle [ % ]	Correction Factor [ dB ]
Bluetooth [ 1 Mbps ]	2.903	0.848	77.40	1.11
Bluetooth [ 2 Mbps ]	2.905	0.845	77.47	1.11
Bluetooth [ 3 Mbps ]	2.907	0.844	77.51	1.11

Note – Duty Cycle : (Tx On Time / (Tx On Time + Tx Off Time)) \* 100

Correction Factor : 10 \* Log(1 / (Duty Cycle / 100))


- Test Plot





Date: 20.MAR.2024 14:58:28

2 Mbps



Date: 20.MAR.2024 15:20:48

3 Mbps

**5.4 Configuration of Test System**

**Line Conducted Test:** It is not need to test this requirement, because the EUT shall be operated by only using DC Battery.

**Radiated Emission Test:** Preliminary radiated emissions test were conducted using the procedure in ANSI C63.10: 2013 to determine the worse operating conditions. Final radiated emission tests were conducted at 3 meter Semi Anechoic Chamber.

The turntable was rotated through 360 degrees and the EUT was tested by positioned three orthogonal planes to obtain the highest reading on the field strength meter. Once maximum reading was determined, the search antenna was raised and lowered in both vertical and horizontal polarization.

**5.5 Antenna Requirement**

For intentional device, according to section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

**Antenna Construction:**

The antenna of the EUT is a Chip Antenna on the main board in the EUT, so no consideration of replacement by the user.

**6. PRELIMINARY TEST**

**6.1 AC Power line Conducted Emissions Tests**

During Preliminary Test, the following operating mode was investigated.

Operation Mode	The Worse operating condition (Please check one only)
Charging Mode	X

**6.2 General Radiated Emissions Tests**

During Preliminary Test, the following operating mode was investigated.

Operation Mode	The Worse operating condition (Please check one only)
Transmitting Mode	X


## 7. MINIMUM 20 dB BANDWIDTH

### 7.1 Operating environment

Temperature : 24 °C  
 Relative humidity : 52 % R.H.

### 7.2 Test set-up

The antenna output of the EUT was connected to the spectrum analyzer. The resolution bandwidth is set to 1 % to 5 % of the OBW, and peak detection was used. The 20 dB bandwidth is defined as the total spectrum over which the power is higher than the peak power minus 20 dB.



### 7.3 Test Date

March 20, 2024 ~ March 22, 2024

### 7.4 Test data for 1 Mbps

CHANNEL	FREQUENCY (MHz)	20 dB Bandwidth (kHz)
Low	2 402.00	944.13
Middle	2 441.00	933.89
High	2 480.00	948.99

### 7.5 Test data for 2 Mbps

CHANNEL	FREQUENCY (MHz)	20 dB Bandwidth (kHz)
Low	2 402.00	1 313.79
Middle	2 441.00	1 313.79
High	2 480.00	1 338.62

### 7.6 Test data for 3 Mbps

CHANNEL	FREQUENCY (MHz)	20 dB Bandwidth (kHz)
Low	2 402.00	1 328.64
Middle	2 441.00	1 283.84
High	2 480.00	1 313.79


## 8. HOPPING FREQUENCY SEPARATION

### 8.1 Operating environment

Temperature : 24 °C  
 Relative humidity : 52 % R.H.

### 8.2 Test set-up

The antenna output of the EUT was connected to the spectrum analyzer. The frequency span is set to 5 MHz. The analyzer is set to peak hold then a pseudo-random hopping sequence of the transmitter is captured. The mark delta function was used to measure the frequency separation between two adjacent hopping channels.



### 8.3 Test Date

March 20, 2024 ~ March 22, 2024

### 8.4 Test data for 1 Mbps

-. Test Result : Pass

MEASURED VALUE (kHz)	Two-third of 20 dB Bandwidth (kHz)	LIMIT
974.00	622.59	Separated by a minimum of 622.59 kHz

### 8.5 Test data for 2 Mbps

-. Test Result : Pass

MEASURED VALUE (kHz)	Two-third of 20 dB Bandwidth (kHz)	LIMIT
999.00	875.86	Separated by a minimum of 875.86 kHz

### 8.6 Test data for 3 Mbps

-. Test Result : Pass

MEASURED VALUE (kHz)	Two-third of 20 dB Bandwidth (kHz)	LIMIT
999.00	855.89	Separated by a minimum of 855.89 kHz


## 9. NUMBER OF HOPPING CHANNELS

### 9.1 Operating environment

Temperature : 24 °C  
 Relative humidity : 52 % R.H.

### 9.2 Test set-up

The antenna output of the EUT was connected to the spectrum analyzer. The frequency span is set to 100 kHz and the resolution bandwidth is set to 300 kHz. The analyzer is set to peak hold and then complete pseudo-random hopping sequence of the transmitter is captured.



### 9.3 Test Date

March 20, 2024 ~ March 22, 2024

### 9.4 Test data for 1 Mbps

-. Test Result : Pass

Data Transfer Rate	Measured value (Number)	Limit (Number)	Margin (Number)
1 Mbps	79	Minimum of 15	64

### 9.5 Test data for 2 Mbps

-. Test Result : Pass

Data Transfer Rate	Measured value (Number)	Limit (Number)	Margin (Number)
2 Mbps	79	Minimum of 15	64

### 9.6 Test data for 3 Mbps

-. Test Result : Pass

Data Transfer Rate	Measured value (Number)	Limit (Number)	Margin (Number)
3 Mbps	79	Minimum of 15	64



## 10. TIME OF OCCUPANCY


### 10.1 Operating environment

Temperature : 24 °C

Relative humidity : 52 % R.H.

### 10.2 Test set-up

The antenna output of the EUT was connected to the spectrum analyzer. The transmitter is set to operate in its normal frequency hopping mode. The center frequency of the spectrum analyzer is set to one of hopping channels near the center of the operating band and span is set to zero Hz. The sweep time is set to display one complete pulse. The mark delta function is used to measure the duration of the pulses.



### 10.3 Test Date

March 20, 2024 ~ March 22, 2024

### 10.4 Test data for 1 Mbps

The system makes worst case 1 600 hops per second or 1 time slot has a length of 625 μs with 79 channels.

For DH1 packet type, the EUT needs 1 time slot for transmitting and 1 time slot for receiving and for DH3 packet type, the EUT needs 3 times slots for transmitting and 1 time slot for receiving, and DH5 packet needs 5 times slots for transmitting and 1 time slot for receiving. So The EUT has each channel for 10.13 times per second (= 1 600/2/79) for DH1, and 5.06 times (= 1 600/4/79) for DH3, and 3.38 times (= 1 600/6/79) for DH5.

Packet Type	Pulse Time (ms)	Hops per second with channels	Period Time (ms)	Total Dwell Time (ms)	Limit (ms)	Test Result
DH1	0.40	10.13	31.60	127.69	400.00	PASS
DH3	1.65	5.06	31.60	264.50	400.00	
DH5	2.90	3.38	31.60	310.01	400.00	

Total dwell time is calculated as following.

Total Dwell Time = Pulse time \* Hops per second with channels \* period time

Remark: See next page for an overview sweep performed with peak detector.

### 10.5 Test data for 2 Mbps

The system makes worst case 1 600 hops per second or 1 time slot has a length of 625 μs with 79 channels.

For DH1 packet type, the EUT needs 1 time slot for transmitting and 1 time slot for receiving and for DH3 packet type, the EUT needs 3 times slots for transmitting and 1 time slot for receiving, and DH5 packet needs 5 times slots for transmitting and 1 time slot for receiving. So The EUT has each channel for 10.13 times per second (= 1 600/2/79) for DH1, and 5.06 times (= 1 600/4/79) for DH3, and 3.38 times (= 1 600/6/79) for DH5.

Packet Type	Pulse Time (ms)	Hops per second with channels	Period Time (ms)	Total Dwell Time (ms)	Limit (ms)	Test Result
DH1	0.41	10.13	31.60	129.79	400.00	PASS
DH3	1.66	5.06	31.60	265.03	400.00	
DH5	2.91	3.38	31.60	310.36	400.00	

Total dwell time is calculated as following.

Total Dwell Time = Pulse time \* Hops per second with channels \* period time

Remark: See next page for an overview sweep performed with peak detector.

### 10.6 Test data for 3 Mbps

The system makes worst case 1 600 hops per second or 1 time slot has a length of 625 μs with 79 channels.

For DH1 packet type, the EUT needs 1 time slot for transmitting and 1 time slot for receiving and for DH3 packet type, the EUT needs 3 times slots for transmitting and 1 time slot for receiving, and DH5 packet needs 5 times slots for transmitting and 1 time slot for receiving. So The EUT has each channel for 10.13 times per second (= 1 600/2/79) for DH1, and 5.06 times (= 1 600/4/79) for DH3, and 3.38 times (= 1 600/6/79) for DH5.

Packet Type	Pulse Time (ms)	Hops per second with channels	Period Time (ms)	Total Dwell Time (ms)	Limit (ms)	Test Result
DH1	0.41	10.13	31.60	129.79	400.00	PASS
DH3	1.66	5.06	31.60	264.80	400.00	
DH5	2.91	3.38	31.60	310.51	400.00	

Total dwell time is calculated as following.

Total Dwell Time = Pulse time \* Hops per second with channels \* period time

Remark: See next page for an overview sweep performed with peak detector.

## 11. MAXIMUM PEAK OUTPUT POWER

### 11.1 Operating environment


Temperature : 24 °C

Relative humidity : 52 % R.H.

### 11.2 Test set-up

The antenna output of the EUT was connected to the spectrum analyzer.

The resolution bandwidth is set to  $\geq$  DTS Bandwidth, the video bandwidth is set to 3 times the resolution bandwidth.



### 11.3 Test Date

March 20, 2024 ~ March 22, 2024

**11.4 Test data for 1 Mbps**

-. Test Result : Pass

CHANNEL	FREQUENCY (MHz)	MEASURED VALUE (dBm)	LIMIT (dBm)	MARGIN (dB)
LOW	2 402.00	2.80	21.00	18.20
MIDDLE	2 441.00	3.04	21.00	17.96
HIGH	2 480.00	2.94	21.00	18.06

Remark. Margin = Limit – Measured Value (=Receiver Reading + Cable Loss)

**11.5 Test data for 2 Mbps**

-. Test Result : Pass

CHANNEL	FREQUENCY (MHz)	MEASURED VALUE (dBm)	LIMIT (dBm)	MARGIN (dB)
LOW	2 402.00	0.59	21.00	20.41
MIDDLE	2 441.00	0.76	21.00	20.24
HIGH	2 480.00	0.71	21.00	20.29

Remark. Margin = Limit – Measured Value (=Receiver Reading + Cable Loss)

**11.6 Test data for 3 Mbps**

-. Test Result : Pass

CHANNEL	FREQUENCY (MHz)	MEASURED VALUE (dBm)	LIMIT (dBm)	MARGIN (dB)
LOW	2 402.00	0.62	21.00	20.38
MIDDLE	2 441.00	0.95	21.00	20.05
HIGH	2 480.00	0.94	21.00	20.06

Remark. Margin = Limit – Measured Value (=Receiver Reading + Cable Loss)

## 12. 100 kHz BANDWIDTH OUTSIDE THE FREQUENCY BAND


### 12.1 Operating environment

Temperature : 24 °C

Relative humidity : 52 % R.H.

### 12.2 Test set-up for conducted measurement

The antenna output of the EUT was connected to the spectrum analyzer. The resolution bandwidth is set to 100 kHz and video bandwidth is set to 300 kHz, and peak detection was used.



### 12.3 Test set-up for radiated measurement

The radiated emissions measurements were performed on the 3 m semi anechoic chamber. The EUT was placed on turntable approximately 1.5 m above the ground plane.

The frequency spectrum from 30 MHz to 26.5 GHz was scanned and maximum emission levels at each frequency recorded. The system was rotated 360°, and the antenna was varied in the height between 1.0 m and 4.0 m in order to determine the maximum emission levels. This procedure was performed for horizontal and vertical polarization of the receiving antenna.

### 12.4 Test Date

March 20, 2024 ~ March 22, 2024

### 12.5 Test data for conducted emission

Please refer to the Annex

**12.6 Test data for Transmitting mode radiated emission**

**12.6.1 Radiated Emission which fall in the Restricted Band**

**12.6.1.1 Test data for 1 Mbps**

- Resolution bandwidth : 1 MHz and Peak Detector for Peak Mode  
1 MHz and RMS Detector for Average Mode
- Video bandwidth : 3 MHz for Peak and Average Mode
- Measurement distance : 3 m
- Duty Cycle : 77.40 %
- Result : PASSED

Frequency (MHz)	Reading (dBμV)	Detector Mode	Ant. Pol. (H/V)	Ant. Factor	Cable Loss	AMP Factor	ATT (dB)	Duty Factor (dB)	Total (dBμV/m)	Limits (dBμV/m)	Margin (dB)
<b>Test Data for Low Channel</b>											
2 366.29	53.66	Peak	H	27.50	2.46	42.80	-	-	40.82	74.00	33.18
2 389.17	42.46	Average	H	27.50	2.46	42.80	-	1.11	30.73	54.00	23.27
2 388.81	53.76	Peak	V	27.50	2.46	42.80	-	-	40.92	74.00	33.08
2 388.99	42.46	Average	V	27.50	2.46	42.80	-	1.11	30.73	54.00	23.27
<b>Test Data for High Channel</b>											
2 483.50	66.68	Peak	H	27.50	2.53	42.80	-	-	53.91	74.00	20.09
2 483.58	44.33	Average	H	27.50	2.53	42.80	-	1.11	32.67	54.00	21.33
2 483.56	65.89	Peak	V	27.50	2.53	42.80	-	-	53.12	74.00	20.88
2 483.78	43.78	Average	V	27.50	2.53	42.80	-	1.11	32.12	54.00	21.88

Remark: "H": Horizontal, "V": Vertical

$$\text{Margin (dB)} = \text{Limits (dB}\mu\text{V/m)} - \text{Total Level (dB}\mu\text{V/m)}$$

$$\text{Total Level} = \text{Reading} + \text{Antenna Factor} + \text{Cable Loss} + \text{ATT} + \text{Duty Factor} - \text{Amp Factor}$$

**12.6.1.2 Test data for 2 Mbps**

- Resolution bandwidth : 1 MHz and Peak Detector for Peak Mode  
1 MHz and RMS Detector for Average Mode
- Video bandwidth : 3 MHz for Peak and Average Mode
- Measurement distance : 3 m
- Duty Cycle : 77.47 %
- Result : PASSED

Frequency (MHz)	Reading (dBμV)	Detector Mode	Ant. Pol. (H/V)	Ant. Factor	Cable Loss	AMP Factor	ATT (dB)	Duty Factor (dB)	Total (dBμV/m)	Limits (dBμV/m)	Margin (dB)
<b>Test Data for Low Channel</b>											
2 389.08	53.16	Peak	H	27.50	2.46	42.80	-	-	40.32	74.00	33.68
2 389.45	43.54	Average	H	27.50	2.46	42.80	-	1.11	31.81	54.00	22.19
2 389.27	53.58	Peak	V	27.50	2.46	42.80	-	-	40.74	74.00	33.26
2 389.36	43.43	Average	V	27.50	2.46	42.80	-	1.11	31.70	54.00	22.30
<b>Test Data for High Channel</b>											
2 484.28	57.53	Peak	H	27.50	2.53	42.80	-	-	44.76	74.00	29.24
2 493.05	44.44	Average	H	27.50	2.53	42.80	-	1.11	32.78	54.00	21.22
2 484.06	58.37	Peak	V	27.50	2.53	42.80	-	-	45.60	74.00	28.40
2 492.77	44.56	Average	V	27.50	2.53	42.80	-	1.11	32.90	54.00	21.10

Remark: "H": Horizontal, "V": Vertical

$$\text{Margin (dB)} = \text{Limits (dB}\mu\text{V/m)} - \text{Total Level (dB}\mu\text{V/m)}$$

$$\text{Total Level} = \text{Reading} + \text{Antenna Factor} + \text{Cable Loss} + \text{ATT} + \text{Duty Factor} - \text{Amp Factor}$$



**12.6.1.3 Test data for 3 Mbps**

- Resolution bandwidth : 1 MHz and Peak Detector for Peak Mode  
1 MHz and RMS Detector for Average Mode
- Video bandwidth : 3 MHz for Peak and Average Mode
- Measurement distance : 3 m
- Duty Cycle : 77.51 %
- Result : PASSED

Frequency (MHz)	Reading (dBμV)	Detector Mode	Ant. Pol. (H/V)	Ant. Factor	Cable Loss	AMP Factor	ATT (dB)	Duty Factor (dB)	Total (dBμV/m)	Limits (dBμV/m)	Margin (dB)
<b>Test Data for Low Channel</b>											
2 388.44	53.94	Peak	H	27.50	2.46	42.80	-	-	41.10	74.00	32.90
2 389.17	43.79	Average	H	27.50	2.46	42.80	-	1.11	32.06	54.00	21.94
2 389.54	53.66	Peak	V	27.50	2.46	42.80	-	-	40.82	74.00	33.18
2 388.90	43.44	Average	V	27.50	2.46	42.80	-	1.11	31.71	54.00	22.29
<b>Test Data for High Channel</b>											
2 484.30	58.07	Peak	H	27.50	2.53	42.80	-	-	45.30	74.00	28.70
2 492.81	44.52	Average	H	27.50	2.53	42.80	-	1.11	32.86	54.00	21.14
2 484.32	58.23	Peak	V	27.50	2.53	42.80	-	-	45.46	74.00	28.54
2 493.01	44.29	Average	V	27.50	2.53	42.80	-	1.11	32.63	54.00	21.37

Remark: "H": Horizontal, "V": Vertical

$$\text{Margin (dB)} = \text{Limits (dB}\mu\text{V/m)} - \text{Total Level (dB}\mu\text{V/m)}$$

$$\text{Total Level} = \text{Reading} + \text{Antenna Factor} + \text{Cable Loss} + \text{ATT} + \text{Duty Factor} - \text{Amp Factor}$$

### 12.6.2 Spurious & Harmonic Radiated Emission above 1 GHz

#### 12.6.2.1 Test data for 1 Mbps

- Resolution bandwidth : 1 MHz and Peak Detector for Peak Mode for the emissions fall in restricted band,  
1 MHz and RMS Detector for Average Mode for the emissions fall in restricted band  
100 kHz for Peak Mode for the emissions outside restricted band
- Video bandwidth : 3 MHz for Peak and Average Mode
- Frequency range : 1 GHz ~ 26.5 GHz
- Measurement distance : 3 m
- Duty Cycle : 77.40 %
- Result : PASSED

Frequency (MHz)	Reading (dBμV)	Detector Mode	Ant. Pol. (H/V)	Ant. Factor	Cable Loss	AMP Factor	Duty Factor (dB)	Total (dBμV/m)	Limits (dBμV/m)	Margin (dB)
<b>Test Data for Low Channel</b>										
4 804.12	49.79	Peak	H	31.40	3.30	44.10	-	40.39	74.00	33.61
4 804.01	38.82	Average	H	31.40	3.30	44.10	1.11	30.53	54.00	23.47
4 804.27	49.60	Peak	V	31.40	3.30	44.10	-	40.20	74.00	33.80
4 803.87	38.86	Average	V	31.40	3.30	44.10	1.11	30.57	54.00	23.43
<b>Test Data for Middle Channel</b>										
4 882.25	50.68	Peak	H	31.40	3.40	44.10	-	41.38	74.00	32.62
4 882.02	40.75	Average	H	31.40	3.40	44.10	1.11	32.56	54.00	21.44
4 882.58	50.77	Peak	V	31.40	3.40	44.10	-	41.47	74.00	32.53
4 882.09	41.26	Average	V	31.40	3.40	44.10	1.11	33.07	54.00	20.93
<b>Test Data for High Channel</b>										
4 960.68	51.53	Peak	H	31.40	3.50	44.10	-	42.33	74.00	31.67
4 960.06	42.10	Average	H	31.40	3.50	44.10	1.11	34.01	54.00	19.99
4 959.77	52.11	Peak	V	31.40	3.50	44.10	-	42.91	74.00	31.09
4 960.00	42.32	Average	V	31.40	3.50	44.10	1.11	34.23	54.00	19.77

Remark: "H": Horizontal, "V": Vertical

$$\text{Margin (dB)} = \text{Limits (dB}\mu\text{V/m)} - \text{Total Level (dB}\mu\text{V/m)}$$

$$\text{Total Level} = \text{Reading} + \text{Antenna Factor} + \text{Cable Loss} + \text{Duty Factor} - \text{Amp Factor}$$

**12.6.2.2 Test data for 2 Mbps**

- Resolution bandwidth : 1 MHz and Peak Detector for Peak Mode for the emissions fall in restricted band,  
1 MHz and RMS Detector for Average Mode for the emissions fall in restricted band  
100 kHz for Peak Mode for the emissions outside restricted band
- Video bandwidth : 3 MHz for Peak and Average Mode
- Frequency range : 1 GHz ~ 26.5 GHz
- Measurement distance : 3 m
- Duty Cycle : 77.47 %
- Result : PASSED

Frequency (MHz)	Reading (dBμV)	Detector Mode	Ant. Pol. (H/V)	Ant. Factor	Cable Loss	AMP Factor	Duty Factor (dB)	Total (dBμV/m)	Limits (dBμV/m)	Margin (dB)
<b>Test Data for Low Channel</b>										
4 803.72	49.52	Peak	H	31.40	3.30	44.10	-	40.12	74.00	33.88
4 804.07	38.25	Average	H	31.40	3.30	44.10	1.11	29.96	54.00	24.04
4 804.12	49.32	Peak	V	31.40	3.30	44.10	-	39.92	74.00	34.08
4 803.98	38.34	Average	V	31.40	3.30	44.10	1.11	30.05	54.00	23.95
<b>Test Data for Middle Channel</b>										
4 882.18	50.09	Peak	H	31.40	3.40	44.10	-	40.79	74.00	33.21
4 882.03	38.49	Average	H	31.40	3.40	44.10	1.11	30.30	54.00	23.70
4 881.57	49.25	Peak	V	31.40	3.40	44.10	-	39.95	74.00	34.05
4 881.95	38.81	Average	V	31.40	3.40	44.10	1.11	30.62	54.00	23.38
<b>Test Data for High Channel</b>										
4 959.81	49.41	Peak	H	31.40	3.50	44.10	-	40.21	74.00	33.79
4 959.99	38.64	Average	H	31.40	3.50	44.10	1.11	30.55	54.00	23.45
4 960.06	49.69	Peak	V	31.40	3.50	44.10	-	40.49	74.00	33.51
4 960.08	38.92	Average	V	31.40	3.50	44.10	1.11	30.83	54.00	23.17

Remark: "H": Horizontal, "V": Vertical

$$\text{Margin (dB)} = \text{Limits (dB}\mu\text{V/m)} - \text{Total Level (dB}\mu\text{V/m)}$$

$$\text{Total Level} = \text{Reading} + \text{Antenna Factor} + \text{Cable Loss} + \text{Duty Factor} - \text{Amp Factor}$$

**12.6.2.3 Test data for 3 Mbps**

- Resolution bandwidth : 1 MHz and Peak Detector for Peak Mode for the emissions fall in restricted band,  
1 MHz and RMS Detector for Average Mode for the emissions fall in restricted band  
100 kHz for Peak Mode for the emissions outside restricted band
- Video bandwidth : 3 MHz for Peak and Average Mode
- Frequency range : 1 GHz ~ 26.5 GHz
- Measurement distance : 3 m
- Duty Cycle : 77.51 %
- Result : PASSED

Frequency (MHz)	Reading (dBμV)	Detector Mode	Ant. Pol. (H/V)	Ant. Factor	Cable Loss	AMP Factor	Duty Factor (dB)	Total (dBμV/m)	Limits (dBμV/m)	Margin (dB)
<b>Test Data for Low Channel</b>										
4 804.38	49.14	Peak	H	31.40	3.30	44.10	-	39.74	74.00	34.26
4 803.99	38.56	Average	H	31.40	3.30	44.10	1.11	30.27	54.00	23.73
4 803.96	49.45	Peak	V	31.40	3.30	44.10	-	40.05	74.00	33.95
4 804.05	38.36	Average	V	31.40	3.30	44.10	1.11	30.07	54.00	23.93
<b>Test Data for Middle Channel</b>										
4 882.09	49.52	Peak	H	31.40	3.40	44.10	-	40.22	74.00	33.78
4 882.04	38.45	Average	H	31.40	3.40	44.10	1.11	30.26	54.00	23.74
4 882.44	49.63	Peak	V	31.40	3.40	44.10	-	40.33	74.00	33.67
4 882.03	38.74	Average	V	31.40	3.40	44.10	1.11	30.55	54.00	23.45
<b>Test Data for High Channel</b>										
4 959.93	49.63	Peak	H	31.40	3.50	44.10	-	40.43	74.00	33.57
4 960.19	38.42	Average	H	31.40	3.50	44.10	1.11	30.33	54.00	23.67
4 960.13	49.42	Peak	V	31.40	3.50	44.10	-	40.22	74.00	33.78
4 960.17	38.31	Average	V	31.40	3.50	44.10	1.11	30.22	54.00	23.78

Remark: "H": Horizontal, "V": Vertical

$$\text{Margin (dB)} = \text{Limits (dB}\mu\text{V/m)} - \text{Total Level (dB}\mu\text{V/m)}$$

$$\text{Total Level} = \text{Reading} + \text{Antenna Factor} + \text{Cable Loss} + \text{Duty Factor} - \text{Amp Factor}$$

**13. RADIATED EMISSION TEST**

**13.1 Operating environment**

Temperature : 24 °C  
 Relative humidity : 52 % R.H.


**13.2 Test set-up**

The radiated emissions measurements were on the 3 m semi anechoic chamber. The EUT and other support equipment were placed on a non-conductive turntable above the ground plane. The interconnecting cables from outside test site were inserted into ferrite clamps at the point where the cables reach the turntable.


The frequency spectrum from 30 MHz to 26.5 GHz was scanned and emission levels maximized at each frequency recorded. The system was rotated 360°, and the antenna was varied in height between 1.0 m and 4.0 m in order to determine the maximum emission levels. This procedure was performed for both horizontal and vertical polarization of the receiving antenna.

**- Test Configuration**


1. Below 30 MHz



2. 30 MHz - 1 GHz



3. Above 1 GHz



**13.3 Test Date**

March 20, 2024 ~ March 22, 2024


**13.4 Test data for 30 MHz ~ 1 000 MHz**

Limits apply to : FCC CFR 47, PART 15, SUBPART C, SECTION 15.247

Result : PASSED

EUT : Bluetooth Module

Detector : CISPR Quasi-Peak (6 dB Bandwidth: 120 kHz)



No.	FREQ [MHz]	READING QP [dBuV]	ANT FACTOR [dB]	LOSS [dB]	GAIN [dB]	RESULT [dBuV/m]	LIMIT [dBuV/m]	MARGIN [dB]	ANTENNA [cm]	TABLE [DEG]
----- Horizontal -----										
1	201.690	41.1	15.7	1.8	32.1	26.5	43.5	17.0	200	359
2	241.460	37.2	17.4	2.0	32.1	24.5	46.0	21.5	200	359
3	389.870	36.2	20.7	2.5	32.1	27.3	46.0	18.7	400	171
----- Vertical -----										
4	562.529	34.0	23.8	3.1	32.3	28.6	46.0	17.4	100	183
5	687.655	32.1	25.4	3.4	32.4	28.5	46.0	17.5	100	183
6	832.181	29.1	27.3	3.8	32.2	28.0	46.0	18.0	111	0

**13.5 Test data for Below 30 MHz**

- Resolution bandwidth : 200 Hz (from 9 kHz to 0.15 MHz), 9 kHz (from 0.15 MHz to 30 MHz)
- Frequency range : 9 kHz ~ 30 MHz
- Measurement distance : 3 m

Frequency (MHz)	Reading (dB $\mu$ V)	Ant. Pol. (H/V)	Ant. Factor (dB/m)	Cable Loss	Amp Gain	Emission Level(dB $\mu$ V/m)	Limits (dB $\mu$ V/m)	Margin (dB)
Emission from the EUT more than 20 dB below the limit in each frequency range.								

**13.6 Test data for above 1 GHz**

- Resolution bandwidth : 1 MHz and Peak Detector for Peak Mode  
1 MHz and RMS Detector for Average Mode
- Video bandwidth : 3 MHz for Peak and Average Mode
- Frequency range : 1 GHz ~ 26.5 GHz
- Measurement distance : 3 m

Frequency (MHz)	Reading (dB $\mu$ V)	Ant. Pol. (H/V)	Ant. Factor (dB/m)	Cable Loss	Amp Gain	Emission Level(dB $\mu$ V/m)	Limits (dB $\mu$ V/m)	Margin (dB)
Emission from the EUT more than 20 dB below the limit in each frequency range.								



## 14. CONDUCTED EMISSION TEST

### 14.1 Operating environment

Temperature : 24 °C

Relative humidity : 52 % R.H.

### 14.2 Test set-up

The EUT was placed on a wooden table, 0.8 m height above the floor. Power was fed to the EUT through a 50  $\Omega$  / 50  $\mu$ H + 5  $\Omega$  Artificial Mains Network (AMN). The ground plane was electrically bonded to the reference ground system and all power lines were filtered from ambient.

### 14.3 Measurement uncertainty


The uncertainty for Conducted emission test is  $\pm 1.6$  dB

### 14.4 Test date

March 20, 2024 ~ March 22, 2024

### 14.5 Test data


- Resolution bandwidth : 9 kHz
- Frequency range : 0.15 MHz ~ 30 MHz
- Tested Line : HOT LINE



### Final Result

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Bandwidth (kHz)	Line	Corr. (dB)
0.154	---	13.94	55.81	41.86	9.0	L1	10.17
0.162	25.22	---	65.39	40.16	9.0	L1	10.17
0.389	---	18.76	48.07	29.32	9.0	L1	10.18
0.393	27.72	---	57.99	30.27	9.0	L1	10.18
0.838	20.60	---	56.00	35.40	9.0	L1	10.20
0.867	---	11.60	46.00	34.40	9.0	L1	10.21
2.018	19.74	---	56.00	36.26	9.0	L1	10.25
2.054	---	10.63	46.00	35.37	9.0	L1	10.25
3.178	---	9.18	46.00	36.82	9.0	L1	10.29
3.238	17.21	---	56.00	38.79	9.0	L1	10.29
11.246	---	13.92	50.00	36.08	9.0	L1	10.70
11.333	22.06	---	60.00	37.94	9.0	L1	10.70

- Tested Line : NEUTRAL LINE



### Final Result

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Bandwidth (kHz)	Line	Corr. (dB)
0.154	28.69	---	65.81	37.12	9.0	N	10.20
0.158	---	16.14	55.60	39.45	9.0	N	10.20
0.390	---	27.60	48.07	20.47	9.0	N	10.19
0.390	37.23	---	58.07	20.84	9.0	N	10.19
0.861	---	20.77	46.00	25.23	9.0	N	10.22
0.877	30.59	---	56.00	25.41	9.0	N	10.22
1.420	29.59	---	56.00	26.41	9.0	N	10.24
1.428	---	19.86	46.00	26.14	9.0	N	10.24
2.652	---	17.66	46.00	28.34	9.0	N	10.28
2.659	27.44	---	56.00	28.56	9.0	N	10.28
11.207	31.79	---	60.00	28.21	9.0	N	10.73
11.278	---	20.15	50.00	29.85	9.0	N	10.74

Remark: Margin (dB) = Limit – Level (Result)

The emission level in above table is included the transducer factor that means insertion loss (LISN), cable loss and attenuator.

**15. LIST OF TEST EQUIPMENT**

Model Number	Manufacturer	Description	Serial Number	Last Cal.(Interval)
FSVA40	Rohde & Schwarz	Signal Analyzer	101598	Jan. 15, 2024 (1Y)
ESU	Rohde & Schwarz	EMI Test Receiver	100261	Mar. 05, 2024 (1Y)
310N	Sonoma Instrument	Pre-Amplifier	392756	Oct. 16, 2023 (1Y)
SCU18	Rohde & Schwarz	Signal Conditioning unit	102266	Jul. 11, 2023 (1Y)
HPF 3GHz	Rohde & Schwarz	High Pass Filter	N/A	Jan. 17, 2024 (1Y)
FMZB 1513	Schwarzbeck	Loop Antenna	1513-235	Mar. 24, 2022 (2Y)
HLP-2008	TDK	Hybrid Antenna	131316	Mar. 07, 2024 (2Y)
BBHA9120D	Schwarzbeck	Horn Antenna	9120D-1366	Jun. 22, 2023 (1Y)
BBHA9170	Schwarzbeck	Horn Antenna	BBHA9170179	Jan. 25, 2024 (1Y)
TC-3000C	TESCOM	Bluetooth Tester	3000C000634	Jan. 16, 2024 (1Y)
AAMCS-UDC	AA-MCS	Directional Coupler	400	Jul. 11, 2023 (1Y)
ESR3	Rohde & Schwarz	EMI Test Receiver	102602	Mar. 11, 2024 (1Y)
ESH3-Z2	Rohde & Schwarz	Pulse Limiter	100655	Mar. 12, 2024 (1Y)
NSLK8126	Schwarzbeck	LISN	8126404	Mar. 12, 2024 (1Y)
DT2000-2t	Innco System	Turn Table	N/A	N/A
MA-4640-XPET	Innco System	Antenna Master	MA4640/652/43100318/P	N/A
CO3000	Innco System	Controller	1026/40960617/P	N/A