

RF Test Report

Applicant : ADLINK TECHNOLOGY INC.

Product Name : Arm-based IoT Gateway

Trade Name : ADLINK

Model Number : EMU-200-W, EMU-200L-W

Applicable Standard : FCC 47 CFR PART 15 SUBPART E
ANSI C63.10:2013

Received Date : Jul. 03, 2023

Test Period : Jul. 27 ~ Aug. 14, 2023

Issued Date : Oct. 06, 2023

Issued by

Eurofins E&E Wireless Taiwan Co., Ltd.
No. 140-1, Changan Street, Bade District,
Taoyuan City 334025, Taiwan (R.O.C.)
Tel : +886-3-2710188 / Fax : +886-3-2710190



Taiwan Accreditation Foundation accreditation number: 1330
Frequency Range : 9 kHz to 40 GHz
Test Firm Registration Number: 226252 (Bade test site)
Test Firm Registration Number: 191812 (Wugu test site)

Note:

1. The test results are valid only for samples provided by customers and under the test conditions described in this report.
2. This report shall not be reproduced except in full, without the written approval of Eurofins E&E Wireless Taiwan Co., Ltd.
3. The relevant information is provided by customers in this test report. According to the correctness, appropriateness or completeness of the information provided by the customer, if there is any doubt or error in the information which affects the validity of the test results, the laboratory does not take the responsibility.

Revision History

Version	Issued Date	Revisions	Revised By
00	Sep. 26, 2023	Initial Issue	Emma Chao
01	Oct. 06, 2023	Update chapter 2 (P.7) Update chapter 4 (P.26)	Emma Chao

Verification of Compliance

Applicant : ADLINK TECHNOLOGY INC.

Product Name : Arm-based IoT Gateway

Trade Name : ADLINK

Model Number : EMU-200-W, EMU-200L-W

FCC ID : X4D-EMU-200

Applicable Standard : FCC 47 CFR PART 15 SUBPART E
ANSI C63.10:2013

Test Result : Complied

Performing Lab. : Eurofins E&E Wireless Taiwan Co., Ltd.
No. 140-1, Changan Street, Bade District,
Taoyuan City 334025, Taiwan (R.O.C.)
Tel : +886-3-2710188 / Fax : +886-3-2710190
Taiwan Accreditation Foundation accreditation number: 1330



Eurofins E&E Wireless Taiwan Co., Ltd. tested the above equipment in accordance with the requirements set forth in the above standards. All indications of Pass/Fail in this report are opinions expressed by Eurofins E&E Wireless Taiwan Co., Ltd. based on interpretations and/or observations of test results. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.

Approved By : _____

TABLE OF CONTENTS

1	General Information.....	5
1.1.	Summary of Test Result.....	5
1.2.	Testing Location.....	6
1.3.	Measurement Uncertainty.....	6
1.4.	Test Site Environment.....	6
2	EUT Description.....	7
3	Test Methodology	9
3.1.	Mode of Operation.....	9
3.2.	EUT Test Step.....	10
3.3.	Configuration of Test System Details	10
3.4.	Test Instruments	11
4	Measurement Procedure	14
4.1.	AC Power Conducted Emission Measurement	14
4.2.	Transmitter Radiated Emissions Measurement.....	16
4.3.	Maximum Conducted Output Power Measurement.....	21
4.4.	26 dB RF Bandwidth Measurement	22
4.5.	6 dB RF Bandwidth Measurement	23
4.6.	Maximum Power Spectral Density Measurement.....	24
4.7.	Automatically discontinue transmission.....	25
4.8.	Antenna Requirement.....	26
5	Test Results	27
5.1.	Conducted Emission.....	27
5.2.	Radiated Emission Measurement	29
5.3.	Conducted Test Results	101

Appendix A. Test Data

Appendix B. Test Plots

Appendix C. Test Setup Photographs

1 General Information

1.1. Summary of Test Result

Standard	Item	Result	Remark
15.407(b)(9) 15.207	AC Power Conducted Emission	PASS	---
15.407(b) 15.205 / 15.209	Transmitter Radiated Emissions	PASS	---
15.407(a)	Maximum Conducted Output Power	PASS	---
15.407(a)	26 dB RF Bandwidth	Reference	---
15.407(e)	6 dB RF Bandwidth	PASS	---
15.407(a)	Maximum Power Spectral Density	PASS	---
15.407(c)	Automatically discontinue transmission	PASS	---
15.407(a) 15.203	Antenna Requirement	PASS	---

Decision Rule

- ☒ Uncertainty is not included.
☐ Uncertainty is included.

Standard	Description
CFR47, Part 15, Subpart C	Intentional Radiators
CFR47, Part 15, Subpart E	Unlicensed National Information Infrastructure Devices
ANSI C63. 10: 2013	American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices
KDB789033: D02	Guidelines for Compliance Testing of Unlicensed National Information Infrastructure (U-NII) Devices Part 15, Subpart E
KDB 662911 D01 v02r01	Emissions Testing of Transmitters with Multiple Outputs in the Same Band (e.g., MIMO, Smart Antenna, etc)

1.2. Testing Location

Lab Name: Eurofins E&E Wireless Taiwan Co., Ltd.
 Site Address: ☒ No. 140-1, Changan Street, Bade District, Taoyuan City 334025, Taiwan (R.O.C.)
 Site Address: ☐ No. 2, Wuquan 5th Rd. Wugu Dist., New Taipei City, Taiwan (R.O.C.)

1.3. Measurement Uncertainty

Test Item	Frequency	Uncertainty			
		BD		WG	
Conducted Emission	150 kHz ~ 30 MHz	2.7 dB		2.6 dB	
Conducted Output Power		1.1 dB		1.1 dB	
RF Bandwidth		4.5 %		4.5 %	
Power Spectral Density		1.1 dB		1.1 dB	
Duty Cycle		1.1 %		1.0 %	
Time Occupancy		1.5 %		1.2 %	
Test Item	Frequency	Uncertainty			
		96601-BD	96603-BD	96602-WG	96603-WG
Radiated Emission	9 kHz ~ 30 MHz	1.9 dB	1.9 dB	1.6 dB	1.6 dB
	30 MHz ~ 1000 MHz	4.9 dB	4.9 dB	4.8 dB	4.8 dB
	1000 MHz ~ 18000 MHz	4.9 dB	5.0 dB	5.0 dB	5.2 dB
	18000 MHz ~ 26500 MHz	4.3 dB	4.4 dB	4.4 dB	4.5 dB
	26500 MHz ~ 40000 MHz	4.5 dB	4.5 dB	4.6 dB	4.5 dB

1.4. Test Site Environment

Items	Required (IEC 60068-1)	Interval(*)
Temperature (°C)	15-35	20-30
Humidity (%RH)	25-75	45-75

(*)The measurement ambient temperature is within this range.

2 EUT Description

The product specifications of the EUT presented in the report are declared by the manufacturer who shall take full responsibility for the authenticity(except Max. RF Output Power).

Applicant	ADLINK TECHNOLOGY INC. No 66 Huaya 1st Rd Guishan District Taoyuan City, 333 Taiwan				
Product Name	Arm-based IoT Gateway				
Trade Name	ADLINK				
Model Number	EMU-200-W, EMU-200L-W				
Models different description	EMU-200-W: w/ Web Console; w/ WIFI EMU-200L-W: w/o Web Console; w/ WIFI				
FCC ID	X4D-EMU-200				
Operate Frequency	Frequency Band			Frequency Range (MHz)	
	802.11a	U-NII Band 1		5180 – 5240	
		U-NII Band 3		5745 – 5825	
	802.11n HT20	U-NII Band 1		5180 – 5240	
		U-NII Band 3		5745 – 5825	
	802.11n HT40	U-NII Band 1		5190 – 5230	
		U-NII Band 3		5755 – 5795	
Modulation Type	OFDM				
Antenna information	Antenna	Model	Type	Max. Gain (dBi)	
	ANT-0 / ANT-1	JR2Q00498-X0	Dipole Antenna	5150~5350 MHz	2.14
				5725~5850 MHz	2.33
Antenna Delivery	Reference section 3.1				
Operate Temp. Range	-40 ~ +50 °C				
EUT Power Rating	DC 9~30 V, 1.68 A-0.51 A, DC 24 V, 0.63 A				

Frequency Band		Max. RF Output Power (W)
802.11a	U-NII Band 1	0.038
	U-NII Band 3	0.017
802.11n HT20	U-NII Band 1	0.035
	U-NII Band 3	0.016
802.11n HT40	U-NII Band 1	0.021
	U-NII Band 3	0.011

Equipment Type		
Outdoor access point	point-to-point	---
	point-to-multipoint	---
Indoor access point		V
Fixed point-to-point access points		---
Client devices		---

5150 MHz ~5250 MHz(U-NII Band 1):

BW 20M	CH	36	40	44	48
	Freq. (MHz)	5180	5200	5220	5240
BW 40M	CH	38		46	
	Freq. (MHz)	5190		5230	

5725 MHz ~5850 MHz(U-NII Band 3):

BW 20M	CH	149	153	157	161	165
	Freq. (MHz)	5745	5765	5785	5805	5825
BW 40M	CH	151		159		NA
	Freq. (MHz)	5755		5795		

3 Test Methodology

3.1. Mode of Operation

Decision of Test Eurofins has verified the construction and function in typical operation. All the test modes were carried out with the EUT in normal operation, which was shown in this test report and defined as:

Pre-Test Mode	Final-Test Mode
Transmit Mode	V
802.11a	V
802.11n HT20	V
802.11n HT40	V

Note : ANT-1 is the worst case in 802.11a 、802.11n HT20 、802.11n HT40.

Software used to control the EUT for staying in continuous transmitting mode was programmed.

After verification, all tests were carried out with the worst case test modes.

By preliminary testing and verifying three axis (X, Y and Z) position of EUT transmitted status, it was found that “Y axis” position was the worst, then the final test was executed the worst condition and test data were recorded in this report.

Test Mode	ANT-0	ANT-1	ANT-0+1
802.11a	V	V	---
802.11n HT20	V	V	---
802.11n HT40	V	V	---

Test Mode	Antenna Delivery	Data Rate (Mbps)	Band	Test Channel
802.11a	1TX / 1RX (Diversity)	6	U-NII Band 1	36, 40, 48
			U-NII Band 3	149, 157, 165
802.11n HT20	1TX / 1RX (Diversity)	6.5	U-NII Band 1	36, 40, 48
			U-NII Band 3	149, 157, 165
802.11n HT40	1TX / 1RX (Diversity)	13.5	U-NII Band 1	38, 46
			U-NII Band 3	151,159


3.2. EUT Test Step

The EUT is operated in the engineering mode to fix the TX frequency for the purposes of measurement. According to its specifications, the EUT must comply with the requirements of Section 15.407 under the FCC Rules Part 15 Subpart E.

1.	Setup the EUT shown on "Configuration of Test System Details".
2.	Turn on the power of all equipment.
3.	Turn on TX function.
4.	EUT run test program.

3.3. Configuration of Test System Details

Conduction Emission & Radiated Emission



Devices Description				
	Product	Manufacturer	Model Number	Remark
(1)	NB	ASUS	P1448U	-
(2)	LAN Cable	TATUNG	CAT5E	-
(3)	SD Card	Transcend	9153BA 8G 07DS1	-
(4)	Switching Power Adapter	MEANWELL	GST40A24	-

3.4. Test Instruments

For Conducted Emission

Test Period: Aug. 10, 2023

Testing Engineer: Jayson Hsieh

Test Site		Conduction01-BD				
Use	Equipment	Manufacturer	Model Number	Serial Number	Cal. Date	Cal. Period
☒	Test Receiver	R&S	ESCI	100367	May 22, 2023	1 year
☐	Test Receiver	R&S	ESCI	100722	Nov. 02, 2022	1 year
☒	LISN	R&S	ENV216	101040	Mar. 21, 2023	1 year
☒	LISN	R&S	ENV216	101140	Jan. 12, 2023	1 year
☒	RF Cable	Woken	00100D1380194M	TE-02-03	Jun. 01, 2023	1 year
☒	Software	EZ EMC	1.1.4.3	N/A	N.C.R.	---

For Conducted

Test Period: Jul. 27 ~ Aug. 11, 2023

Testing Engineer: Andy Lu

Test Site		RF01-BD				
Use	Equipment	Manufacturer	Model Number	Serial Number	Cal. Date	Cal. Period
☒	Power Sensor	Agilent	N1921A	MY45241957	Nov. 30, 2022	1 year
☒	Power Meter	Agilent	N1911A	MY45101619	Nov. 30, 2022	1 year
☒	Spectrum Analyzer (10 Hz~26.5 GHz)	Keysight	N9010B	MY59071418	Mar. 20, 2023	1 year
☐	Spectrum Analyzer (20 Hz~26.5 GHz)	Agilent	N9020A	US47520902	Sep. 01, 2022	1 year
☐	Spectrum Analyzer (3 Hz~50 GHz)	Agilent	N9030A	MY53120541	Dec. 29, 2022	1 year
☐	Temperature & Humidity Chamber	TAICHY	MHU-225LA	980729	Mar. 29, 2023	1 year
☐	Signal Generator	Keysight	N5182B	MY53052569	Apr. 17, 2023	1 year
☐	Bluetooth Tester	R&S	CBT	100350	Mar. 20, 2023	2 years
☐	Wireless Connectivity Tester	R&S	CMW270	102208	Jun. 05, 2023	1 year
☐	Power Supply	KEITHLEY	2303	4045290	Jan. 06, 2023	1 year

Note: N.C.R. = No Calibration Request.

For Radiated Emissions

Test Period: Aug. 11 ~ Aug. 14, 2023

Testing Engineer: Kerry Xu, Marc Yeh

Test Site		96603-BD				
Radiation test sites		Semi Anechoic Room				
Use	Equipment	Manufacturer	Model Number	Serial Number	Cal. Date	Cal. Period
☐	Spectrum Analyzer (10 Hz~44 GHz)	Keysight	N9010A	MY52221312	Jan. 07, 2023	1 year
☐	Spectrum Analyzer (3 Hz~50 GHz)	Agilent	N9030A	MY53120541	Dec. 29, 2022	1 year
☒	Spectrum Analyzer (10 Hz~44 GHz)	Keysight	N9020B	MY60112363	Jan. 13, 2023	1 year
☒	Amplifier (100 kHz~1.3 GHz)	Agilent	8447D	2944A11119	Jan. 07, 2023	1 year
☐	Broadband Amplifier (100 kHz~1 GHz)	Titan	T0910E00014330 A1F	001	Jul. 24, 2023	1 year
☐	Amplifier (1 GHz~26.5 GHz)	Agilent	8449B	3008A02237	Oct. 19, 2022	1 year
☒	Broadband Amplifier (1 GHz~26.5 GHz)	Titan	T0912E01263025 A1F	002	Jul. 24, 2023	1 year
☒	Preamplifier (26.5 GHz~40 GHz)	EMCI	EMC2654045	980028	Sep. 02, 2022	1 year
☒	Loop Antenna (9 kHz~30 MHz)	COM-POWER CORPORATION	AL-130	121014	Mar. 23, 2023	1 year
☐	Active Loop Antenna (9 kHz~30 MHz)	Schwarzbeck Mess-Elektronik	FMZB 1513-60	1513-60-031	Feb. 21, 2023	1 year
☒	Trilog Broadband Antenna (30 kHz~1 GHz)	Schwarzbeck Mess-Elektronik	VULB9168	01146	Jun. 26, 2023	1 year
☐	Trilog Broadband Antenna (30 kHz~1 GHz)	Schwarzbeck Mess-Elektronik	VULB9168	416	Jun.13, 2023	1 year
☒	Broadband Horn Antenna (1 GHz~18 GHz)	Schwarzbeck Mess-Elektronik	9120D	02207	Jul. 07, 2023	1 year
☐	Broadband Horn Antenna (1 GHz~18 GHz)	Schwarzbeck Mess-Elektronik	9120D	9120D-550	Aug. 25, 2022	1 year
☒	Broadband Horn Antenna (18 GHz~40 GHz)	Schwarzbeck Mess-Elektronik	9170	9170-320	Aug. 25, 2022	1 year
☐	Horn Antenna (18 GHz~40 GHz)	ETS	3116	00086467	Dec. 05, 2022	1 year

Note: N.C.R. = No Calibration Request.

For Radiated Emissions

Test Period: Aug. 11 ~ Aug. 14, 2023

Testing Engineer: Kerry Xu, Marc Yeh

Test Site		96603-BD				
Radiation test sites		Semi Anechoic Room				
Use	Equipment	Manufacturer	Model Number	Serial Number	Cal. Date	Cal. Period
☒	Coaxial Cable	Titan	T0710AT327A10A 100	J11005	Aug. 10, 2023	1 year
☒	Coaxial Cable	Titan	T0710AT327A10A 900	J11004	Aug. 10, 2023	1 year
☒	Coaxial Cable	Titan	CFD400NL-LW	001	Aug. 10, 2023	1 year
☐	Bluetooth Tester	R&S	CBT	100350	Mar. 20, 2023	2 years
☐	Power Supply	KEITHLEY	2303	4045290	Jan. 06, 2023	1 year
☒	Software	EZ EMC	1.1.4.4	N/A	N.C.R.	---

Note: N.C.R. = No Calibration Request.


4 Measurement Procedure

4.1. AC Power Conducted Emission Measurement

■ Limit

Frequency (MHz)	Quasi-peak	Average
0.15 - 0.5	66 to 56	56 to 46
0.50 - 5.0	56	46
5.0 - 30.0	60	50

■ Test Setup



■ Test Procedure

The EUT and simulators are connected to the main power through a line impedance stabilization network (L.I.S.N.). This provides a $50\ \Omega // 50\ \mu\text{H}$ coupling impedance for the measuring equipment. The peripheral devices are also connected to the main power through a LISN that provides a $50\ \Omega // 50\ \mu\text{H}$ coupling impedance with 50 ohm termination.

Tabletop device shall be placed on a non-conducting platform, of nominal size 1 m by 1.5 m, raised 80 cm above the reference ground plane. The wall of screened room shall be located 40 cm to the rear of the EUT. Other surfaces of tabletop or floor standing EUT shall be at least 80 cm from any other ground conducting surface including one or more LISNs. For floor-standing device shall be placed under the EUT with a 12 mm insulating material.

Conducted emissions were investigated over the frequency range from 0.15 MHz to 30 MHz using a resolution bandwidth of 9 kHz. The equipment under test (EUT) shall be meet the limits in section 4.1, as applicable, including the average limit and the quasi-peak limit when using respectively, an average detector and quasi-peak detector measured in accordance with the methods described of related standard. When all of peak value were complied with quasi-peak and average limit from 150 kHz to 30 MHz then quasi-peak and average measurement was unnecessary.

The AMN shall be placed 0.8 m from the boundary of the unit under test and bonded to a ground reference plane for AMNs mounted on top of the ground reference plane. This distance is between the closest points of the AMN and the EUT. All other units of the EUT and associated equipment shall be at least 0.8 m from the AMN. If the mains power cable is longer than 1 m then the cable shall be folded back and forth at the centre of the lead to form a bundle no longer than 0.4 m. All of interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 cm to 40 cm long. All of EUT and AE shall be separate place more than 0.1 m. All 50 Ω ports of the LISN shall be resistively terminated into 50 Ω loads when not connected to the measuring instrument.

If the reading of the measuring receiver shows fluctuations close to the limit, the reading shall be observed for at least 15 s at each measurement frequency; the higher reading shall be recorded with the exception of any brief isolated high reading which shall be ignored

4.2. Transmitter Radiated Emissions Measurement

■ Limit

(1) Undesirable emission limits. Except as shown in paragraph (b)(9) of this section, the maximum emissions outside of the frequency bands of operation shall be attenuated in accordance with the following limits:

(a) For transmitters operating in the 5.15-5.25 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.

(b) For transmitters operating in the 5.25-5.35 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.

(c) For transmitters operating in the 5.47-5.725 GHz band: All emissions outside of the 5.47-5.725 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.

(d) For transmitters operating in the 5.725-5.85 GHz band:

(i) All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.

EIRP (dBm)	Field Strength at 3 m (dBuV/m)
-27	68.3

(2) Limits of Radiated Emission Measurement


Emissions radiated outside of the specified bands, shall be according to the general radiated limits in 15.209 as following:

Frequency Range (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	10	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3


Note: 1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. As shown in 15.35(b), for frequencies above 1000 MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20 dB under any condition of modulation.

■ Setup


9 kHz ~ 30 MHz



30 MHz ~ 1 GHz



Above 1 GHz



■ Test Procedure

Final radiation measurements were made on a three-meter, Semi Anechoic Chamber. The EUT system was placed on a nonconductive turntable which is 0.8 or 1.5 meters height (below 1 GHz use 0.8 m turntable / above 1 GHz use 1.5 m turntable), top surface 1.0 x 1.5 meter. The spectrum was examined from 250 MHz to 2.5 GHz in order to cover the whole spectrum below 10th harmonic which could generate from the EUT. During the test, EUT was set to transmit continuously & Measurements spectrum range from 9 kHz to 40 GHz is investigated.

For measurements below 30 MHz the resolution bandwidth is set to 10 kHz for peak detection measurements or 9 kHz for quasi-peak detection measurements. The video bandwidth is 3 times of the resolution bandwidth.

For measurements below 1 GHz the resolution bandwidth is set to 100 kHz for peak detection measurements or 120 kHz for quasi-peak detection measurements. Peak detection is used unless otherwise noted as quasi-peak.

For restricted measurements above 1 GHz the resolution bandwidth is set to 1 MHz, and then the video bandwidth is set to 3 MHz for peak measurements and 10 Hz for average measurements when Duty cycle > 0.98 / 1/T for average measurements when Duty cycle < 0.98.

For out of band measurements above 1 GHz the resolution bandwidth is set to 1 MHz, and then the video bandwidth is set to 3 MHz for peak measurements.

A nonconductive material surrounded the EUT to supporting the EUT for standing on three orthogonal planes. At each condition, the EUT was rotated 360 degrees, and the antenna was raised and lowered from one to four meters to find the maximum emission levels. Measurements were taken using both horizontal and vertical antenna polarization.

SCHWARZBECK MESS-ELEKTRONIK Trilog-Broadband Antenna at 3 Meter and the ETS-Lindgren Double-Ridged Waveguide Horn antenna Schwarzbeck Mess-Elektronik Broadband Horn Antenna was used in frequencies 1 – 40 GHz at a distance of 3 meter. The antenna at an angle toward the source of the emission. All test results were extrapolated to equivalent signal at 3 meters utilizing an inverse linear distance extrapolation Factor (20 dB/decade).

For testing above 1 GHz, the emission level of the EUT in peak mode was 20 dB lower than average limit (that means the emission level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.

Appropriate preamplifiers were used for improving sensitivity and precautions were taken to avoid overloading or desensitizing the spectrum analyzer. No post – detector video filters were used in the test.

The spectrum analyzer's 6 dB bandwidth was set to 1 MHz, and the analyzer was operated in the peak detection mode, for frequencies both below and up 1 GHz. The average levels were obtained by subtracting the duty cycle correction factor from the peak readings.

The following procedures were used to convert the emission levels measured in decibels referenced to 1 microvolt (dBuV) into field intensity in micro volts pre meter (uV/m).

The actual field intensity in decibels referenced to 1 microvolt in to field intensity in micro volts per meter (dBuV/m).

Data of measurement within this frequency range without mark in the table above means the reading of emissions are attenuated more than 20 dB below the permissible limits or the field strength is too small to be measured.

The actual field intensity in referenced to 1 microvolt per meter (dBuV/m) is determined by algebraically adding the measured reading in dBuV, the antenna factor (dB), and cable loss (dB) and Subtracting the gain of preamplifier (dB) is auto calculate in spectrum analyzer.

$$(1) \text{ Amplitude (dBuV/m) = FI (dBuV) + AF (dBuV) + CL (dBuV) - Gain (dB)}$$

FI= Reading of the field intensity.

AF= Antenna factor.

CL= Cable loss.

P.S Amplitude is auto calculate in spectrum analyzer.

$$(2) \text{ Actual Amplitude (dBuV/m) = Amplitude (dBuV) - Dis(dB)}$$

The FCC specified emission limits were calculated according the EUT operating frequency and by following linear interpolation equations:

(a) For fundamental frequency : Transmitter Output < +30 dBm

(b) For spurious frequency : Spurious emission limits = fundamental emission limit /10

Measuring Instruments and setting

The following table is the setting of spectrum analyzer and receiver.

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	40 GHz
RBW/VBW(Emission in restricted band)	1 MHz / 3 MHz for Peak 1 MHz / (1/T) for Average
RBW/VBW(Emission in non-restricted band)	1 MHz / 3 MHz for Peak


4.3. Maximum Conducted Output Power Measurement

■ Limit

Frequency Range (MHz)	FCC Maximum Conducted Output Power Limit
	Master
5.150 ~ 5.250 GHz	The lesser of 1 W (30 dBm)
5.250 ~ 5.350 GHz	The lesser of 250 mW (24 dBm) or 11 dBm + 10 log (B)
5.470 ~ 5.725 GHz	The lesser of 250 mW (24 dBm) or 11 dBm + 10 log (B)
5.725 ~ 5.850 GHz	The lesser of 1 W (30 dBm)

According FCC KDB 662911 D01 v02r01 – for power measurements on IEEE802.11 devices,

■ Test Setup



■ Test Procedure

The test is performed in accordance with ANSI C63.10:2013 section 12.3.3.2, Guidelines for Compliance Testing of Unlicensed National Information Infrastructure (U-NII) Devices

Section (E) Maximum Conducted Output Power

3. Measurement using a Power Meter (PM)


b) Method PM-G (Measurement using a gated RF average power meter)

4.4. 26 dB RF Bandwidth Measurement

■ **Limit**

N/A

■ **Test Setup**



■ **Test Procedure**

The test is performed in accordance with ANSI C63.10:2013 section 12.4.1, Guidelines for Compliance Testing of Unlicensed National Information Infrastructure (U-NII) Devices - Part 15, Subpart E.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	>26 dB Bandwidth
RBW	Approximately 1 % of the emission bandwidth
VBW	VBW > RBW
Detector	Peak
Trace	Max Hold
Sweep Time	Auto


4.5. 6 dB RF Bandwidth Measurement

■ Limit

6 dB RF Bandwidth

Systems using digital modulation techniques may operate in the 5725~5825 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

■ Test Setup



■ Test Procedure

6 dB RF Bandwidth

The EUT tested to UNII test procedure of ANSI C63.10:2013 section 6.9.2 for compliance to FCC 47CFR 15.407 requirements.

The antenna port of the EUT was connected to the input of a spectrum analyzer. Analyzer RES BW was set to 100 kHz. For each RF output channel investigated, the spectrum analyzer center frequency was set to the channel carrier.

A peak output reading was taken, a DISPLAY line was drawn 6 dB lower than peak level. The 6 dB bandwidth was determined from where the channel output spectrum intersected the display line.

The test was performed at 3 channels.


4.6. Maximum Power Spectral Density Measurement

■ Limit

Frequency Range (MHz)	FCC Limit
	Master
5.150 ~ 5.250 GHz	17 dBm/MHz
5.250 ~ 5.350 GHz	11 dBm/MHz
5.470 ~ 5.725 GHz	11 dBm/MHz
5.725 ~ 5.850 GHz	30 dBm/500 kHz

According FCC KDB 662911 D01 v02r01 – for power spectral density measurements on IEEE802.11 devices,

■ Test Setup



■ Test Procedure

The test is performed in accordance with ANSI C63.10:2013 section 12.5, Guidelines for Compliance Testing of Unlicensed National Information Infrastructure (U-NII) Devices - Part 15, Subpart E.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	Encompass the entire emissions bandwidth (EBW) of the signal
RBW	1 MHz (5725 ~ 5850 MHz use 100 kHz)
VBW	3 MHz (5725 ~ 5850 MHz use 300 kHz)
Detector	RMS
Trace	AVERAGE
Sweep Time	Auto
Trace Average	100 times
Note: If measurement bandwidth of Maximum PSD is specified in 500 kHz, add $10 \log(500 \text{ kHz}/100 \text{ kHz})$ to the measured result.	

4.7. Automatically discontinue transmission

The device shall automatically discontinue transmission in case of either absence of information to transmit or operational failure. These provisions are not intended to preclude the transmission of control or signalling information or the use of repetitive codes used by certain digital technologies to complete frame or burst intervals. Applicants shall include in their application for equipment authorization a description of how this requirement is met.

■ **Declare**

While the EUT is not transmitting any information, the EUT can automatically discontinue transmission and become standby mode for power saving.

The EUT can detect the controlling signal of ACK message transmitting from remote device and verify whether it shall resend or discontinue transmission.

4.8. Antenna Requirement

■ Requirement

For intentional device, according to 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

And According to 15.407 (a), if transmitting antennas of directional gain greater than 6 dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

■ Antenna Connector Construction

See section 2 – antenna information.

■ Directional Gain Calculated

Test mode	Band	Transmission Type	Antenna		Directional Gain For Power (dBi)	Directional Gain For PSD (dBi)	Power Limit Reduction (dB)	PSD Limit Reduction (dB)
			ANT-0 (dBi)	ANT-1 (dBi)				
802.11a	Band 1	ANT-1	2.14	2.14	2.14	2.14	0.00	0.00
	Band 3		2.33	2.33	2.33	2.33	0.00	0.00
802.11n HT20/ 802.11n HT40	Band 1	ANT-1	2.14	2.14	2.14	2.14	0.00	0.00
	Band 3		2.33	2.33	2.33	2.33	0.00	0.00


If transmit signals are correlated, then Directional gain = $10 \log[(10^{G1/20} + 10^{G2/20} + \dots + 10^{GN/20})^2 / NANT]$

If all transmit signals are completely uncorrelated, then Directional gain = $10 \log[(10^{G1/10} + 10^{G2/10} + \dots + 10^{GN/10}) / NANT]$

5 Test Results

5.1. Conducted Emission

Standard:	Part 15.407	Line:	L1
Test item:	Conducted Emission	Power:	AC 120 V/60 Hz
Test Mode:	Transmit mode		
Description:			




No.	Frequency (MHz)	QP reading (dBuV)	AVG reading (dBuV)	Correction factor (dB)	QP result (dBuV)	AVG result (dBuV)	QP limit (dBuV)	AVG limit (dBuV)	QP margin (dB)	AVG margin (dB)	Remark
1	0.1700	31.48	20.54	9.61	41.09	30.15	64.96	54.96	-23.87	-24.81	Pass
2	0.2220	26.86	13.39	9.61	36.47	23.00	62.74	52.74	-26.27	-29.74	Pass
3	0.2820	29.74	20.14	9.61	39.35	29.75	60.76	50.76	-21.41	-21.01	Pass
4	0.8380	22.76	14.77	9.65	32.41	24.42	56.00	46.00	-23.59	-21.58	Pass
5	1.4500	23.21	10.04	9.67	32.88	19.71	56.00	46.00	-23.12	-26.29	Pass
6	12.5740	30.62	20.64	9.92	40.54	30.56	60.00	50.00	-19.46	-19.44	Pass

Note: 1. Result (dBuV) = Correction factor (dB) + Reading(dBuV).

2. Correction factor (dB) = Cable loss (dB) + L.I.S.N. factor (dB).

Standard:	Part 15.407	Line:	N
Test item:	Conducted Emission	Power:	AC 120 V/60 Hz
Test Mode:	Transmit mode		
Description:			



No.	Frequency (MHz)	QP reading (dBuV)	AVG reading (dBuV)	Correction factor (dB)	QP result (dBuV)	AVG result (dBuV)	QP limit (dBuV)	AVG limit (dBuV)	QP margin (dB)	AVG margin (dB)	Remark
1	0.1540	29.77	15.99	9.60	39.37	25.59	65.78	55.78	-26.41	-30.19	Pass
2	0.2900	29.10	20.11	9.61	38.71	29.72	60.52	50.52	-21.81	-20.80	Pass
3	0.8340	24.60	14.89	9.64	34.24	24.53	56.00	46.00	-21.76	-21.47	Pass
4	1.4460	24.02	10.78	9.66	33.68	20.44	56.00	46.00	-22.32	-25.56	Pass
5	1.6700	22.25	12.31	9.68	31.93	21.99	56.00	46.00	-24.07	-24.01	Pass
6	12.0380	30.97	20.43	9.96	40.93	30.39	60.00	50.00	-19.07	-19.61	Pass


Note: 1. Result (dBuV) = Correction factor (dB) + Reading(dBuV).

2. Correction factor (dB) = Cable loss (dB) + L.I.S.N. factor (dB).

5.2. Radiated Emission Measurement

Below 1 GHz

Standard:	Part 15.407	Test Distance:	3 m
Test item:	Radiated Emission		
Test Mode:	Transmit mode		
Ant.Polar.:	Horizontal		




No.	Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	187.1400	34.78	-8.87	25.91	43.50	-17.59	QP
2	285.1100	31.16	-6.30	24.86	46.00	-21.14	QP
3	383.0800	31.89	-4.30	27.59	46.00	-18.41	QP
4	483.9600	29.77	-2.42	27.35	46.00	-18.65	QP
5	585.8100	29.67	-0.30	29.37	46.00	-16.63	QP
6*	749.7400	27.38	2.71	30.09	46.00	-15.91	QP

Note: 1. Result (dBuV/m) = Correct Factor (dB/m) + Reading (dBuV).

2. Correction factor (dB/m) = Antenna Factor (dB/m) + Cable loss (dB) – Pre-Amplifier gain (dB).

3. When the peak results are less than average limit, so not need to evaluate the average.

Standard:	Part 15.407	Test Distance:	3 m
Test item:	Radiated Emission		
Test Mode:	Transmit mode		
Ant.Polar.:	Vertical		



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	185.2000	30.80	-8.71	22.09	43.50	-21.41	QP
2	315.1800	28.87	-5.69	23.18	46.00	-22.82	QP
3	407.3300	30.48	-3.79	26.69	46.00	-19.31	QP
4	468.4400	30.58	-2.58	28.00	46.00	-18.00	QP
5	612.0000	28.31	0.08	28.39	46.00	-17.61	QP
6*	725.4900	28.48	2.18	30.66	46.00	-15.34	QP

Note:1.Result (dBuV/m) = Correct Factor (dB/m) + Reading(dBuV).


2.Correction factor (dB/m) = Antenna Factor (dB/m) + Cable loss (dB) – Pre-Amplifier gain (dB).

3.When the peak results are less than average limit, so not need to evaluate the average.

Harmonic


Above 1 GHz

Standard:	Part 15.407	Test Site:	966 Chamber
Polarization:	Horizontal		
Test Mode:	802.11a 5180 MHz		
Remark:			




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1*	10360.000	35.09	14.04	49.13	68.20	-19.07	peak
2	15540.000	33.25	16.69	49.94	74.00	-24.06	peak

Standard:	Part 15.407	Test Site:	966 Chamber
Polarization:	Vertical		
Test Mode:	802.11a 5180 MHz		
Remark:			




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1*	10360.000	36.06	14.04	50.10	68.20	-18.10	peak
2	15540.000	34.44	16.69	51.13	74.00	-22.87	peak

Standard:	Part 15.407	Test Site:	966 Chamber
Polarization:	Horizontal		
Test Mode:	802.11a 5200 MHz		
Remark:			




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1*	10400.000	35.57	14.27	49.84	68.20	-18.36	peak
2	15600.000	33.05	16.46	49.51	74.00	-24.49	peak

Standard:	Part 15.407	Test Site:	966 Chamber
Polarization:	Vertical		
Test Mode:	802.11a 5200 MHz		
Remark:			




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1*	10400.000	35.82	14.27	50.09	68.20	-18.11	peak
2	15600.000	34.02	16.46	50.48	74.00	-23.52	peak

Standard:	Part 15.407	Test Site:	966 Chamber
Polarization:	Horizontal		
Test Mode:	802.11a 5240 MHz		
Remark:			




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1*	10480.000	34.99	14.47	49.46	68.20	-18.74	peak
2	15720.000	33.67	16.43	50.10	74.00	-23.90	peak

Standard:	Part 15.407	Test Site:	966 Chamber
Polarization:	Vertical		
Test Mode:	802.11a 5240 MHz		
Remark:			




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1*	10480.000	35.80	14.47	50.27	68.20	-17.93	peak
2	15720.000	33.83	16.43	50.26	74.00	-23.74	peak

Standard:	Part 15.407	Test Site:	966 Chamber
Polarization:	Horizontal		
Test Mode:	802.11a 5745 MHz		
Remark:			




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	11490.000	34.89	15.44	50.33	74.00	-23.67	peak
2*	17235.000	32.22	21.19	53.41	68.20	-14.79	peak

Standard:	Part 15.407	Test Site:	966 Chamber
Polarization:	Vertical		
Test Mode:	802.11a 5745 MHz		
Remark:			




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	11490.000	35.33	15.44	50.77	74.00	-23.23	peak
2*	17235.000	32.77	21.19	53.96	68.20	-14.24	peak

Standard:	Part 15.407	Test Site:	966 Chamber
Polarization:	Horizontal		
Test Mode:	802.11a 5785 MHz		
Remark:			




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	11570.000	35.28	15.14	50.42	74.00	-23.58	peak
2*	17355.000	32.19	22.20	54.39	68.20	-13.81	peak

Standard:	Part 15.407	Test Site:	966 Chamber
Polarization:	Vertical		
Test Mode:	802.11a 5785 MHz		
Remark:			




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	11570.000	34.76	15.14	49.90	74.00	-24.10	peak
2*	17355.000	32.64	22.20	54.84	68.20	-13.36	peak

Standard:	Part 15.407	Test Site:	966 Chamber
Polarization:	Horizontal		
Test Mode:	802.11a 5825 MHz		
Remark:			




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	11650.000	35.71	14.96	50.67	74.00	-23.33	peak
2*	17475.000	33.23	23.54	56.77	68.20	-11.43	peak

Standard:	Part 15.407	Test Site:	966 Chamber
Polarization:	Vertical		
Test Mode:	802.11a 5825 MHz		
Remark:			




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	11650.000	34.95	14.96	49.91	74.00	-24.09	peak
2*	17475.000	33.41	23.54	56.95	68.20	-11.25	peak

Standard:	Part 15.407	Test Site:	966 Chamber
Polarization:	Horizontal		
Test Mode:	802.11n HT20 5180 MHz		
Remark:			




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1*	10360.000	35.90	14.04	49.94	68.20	-18.26	peak
2	15540.000	33.72	16.69	50.41	74.00	-23.59	peak

Standard:	Part 15.407	Test Site:	966 Chamber
Polarization:	Vertical		
Test Mode:	802.11n HT20 5180 MHz		
Remark:			




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1*	10360.000	34.85	14.04	48.89	68.20	-19.31	peak
2	15540.000	34.53	16.69	51.22	74.00	-22.78	peak

Standard:	Part 15.407	Test Site:	966 Chamber
Polarization:	Horizontal		
Test Mode:	802.11n HT20 5200 MHz		
Remark:			




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1*	10400.000	36.43	14.27	50.70	68.20	-17.50	peak
2	15600.000	34.23	16.46	50.69	74.00	-23.31	peak

Standard:	Part 15.407	Test Site:	966 Chamber
Polarization:	Vertical		
Test Mode:	802.11n HT20 5200 MHz		
Remark:			




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1*	10400.000	35.96	14.27	50.23	68.20	-17.97	peak
2	15600.000	33.94	16.46	50.40	74.00	-23.60	peak

Standard:	Part 15.407	Test Site:	966 Chamber
Polarization:	Horizontal		
Test Mode:	802.11n HT20 5240 MHz		
Remark:			




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1*	10480.000	35.85	14.47	50.32	68.20	-17.88	peak
2	15720.000	33.59	16.43	50.02	74.00	-23.98	peak

Standard:	Part 15.407	Test Site:	966 Chamber
Polarization:	Vertical		
Test Mode:	802.11n HT20 5240 MHz		
Remark:			




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1*	10480.000	37.51	14.47	51.98	68.20	-16.22	peak
2	15720.000	33.60	16.43	50.03	74.00	-23.97	peak

Standard:	Part 15.407	Test Site:	966 Chamber
Polarization:	Horizontal		
Test Mode:	802.11n HT20 5745 MHz		
Remark:			




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	11490.000	34.30	15.44	49.74	74.00	-24.26	peak
2*	17235.000	32.17	21.19	53.36	68.20	-14.84	peak

Standard:	Part 15.407	Test Site:	966 Chamber
Polarization:	Vertical		
Test Mode:	802.11n HT20 5745 MHz		
Remark:			




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	11490.000	35.77	15.44	51.21	74.00	-22.79	peak
2*	17235.000	31.65	21.19	52.84	68.20	-15.36	peak

Standard:	Part 15.407	Test Site:	966 Chamber
Polarization:	Horizontal		
Test Mode:	802.11n HT20 5785 MHz		
Remark:			




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	11570.000	35.59	15.14	50.73	74.00	-23.27	peak
2*	17355.000	32.93	22.20	55.13	68.20	-13.07	peak

Standard:	Part 15.407	Test Site:	966 Chamber
Polarization:	Vertical		
Test Mode:	802.11n HT20 5785 MHz		
Remark:			




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	11570.000	34.83	15.14	49.97	74.00	-24.03	peak
2*	17355.000	33.34	22.20	55.54	68.20	-12.66	peak

Standard:	Part 15.407	Test Site:	966 Chamber
Polarization:	Horizontal		
Test Mode:	802.11n HT20 5825 MHz		
Remark:			




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	11650.000	36.14	14.96	51.10	74.00	-22.90	peak
2*	17475.000	32.98	23.54	56.52	68.20	-11.68	peak

Standard:	Part 15.407	Test Site:	966 Chamber
Polarization:	Vertical		
Test Mode:	802.11n HT20 5825 MHz		
Remark:			




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	11650.000	35.11	14.96	50.07	74.00	-23.93	peak
2*	17475.000	33.69	23.54	57.23	68.20	-10.97	peak

Standard:	Part 15.407	Test Site:	966 Chamber
Polarization:	Horizontal		
Test Mode:	802.11n HT40 5190 MHz		
Remark:			




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1*	10380.000	35.54	14.15	49.69	68.20	-18.51	peak
2	15570.000	33.54	16.58	50.12	74.00	-23.88	peak

Standard:	Part 15.407	Test Site:	966 Chamber
Polarization:	Vertical		
Test Mode:	802.11n HT40 5190 MHz		
Remark:			




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1*	10380.000	35.42	14.15	49.57	68.20	-18.63	peak
2	15570.000	33.04	16.58	49.62	74.00	-24.38	peak

Standard:	Part 15.407	Test Site:	966 Chamber
Polarization:	Horizontal		
Test Mode:	802.11n HT40 5230 MHz		
Remark:			




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1*	10460.000	35.22	14.42	49.64	68.20	-18.56	peak
2	15690.000	34.57	16.46	51.03	74.00	-22.97	peak

Standard:	Part 15.407	Test Site:	966 Chamber
Polarization:	Vertical		
Test Mode:	802.11n HT40 5230 MHz		
Remark:			




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1*	10460.000	36.48	14.42	50.90	68.20	-17.30	peak
2	15690.000	33.80	16.46	50.26	74.00	-23.74	peak

Standard:	Part 15.407	Test Site:	966 Chamber
Polarization:	Horizontal		
Test Mode:	802.11n HT40 5755 MHz		
Remark:			




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	11510.000	34.70	15.47	50.17	74.00	-23.83	peak
2*	17265.000	32.94	21.50	54.44	68.20	-13.76	peak

Standard:	Part 15.407	Test Site:	966 Chamber
Polarization:	Vertical		
Test Mode:	802.11n HT40 5755 MHz		
Remark:			




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	11510.000	34.99	15.47	50.46	74.00	-23.54	peak
2*	17265.000	32.01	21.50	53.51	68.20	-14.69	peak

Standard:	Part 15.407	Test Site:	966 Chamber
Polarization:	Horizontal		
Test Mode:	802.11n HT40 5795 MHz		
Remark:			




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	11590.000	34.74	15.03	49.77	74.00	-24.23	peak
2*	17385.000	31.74	22.38	54.12	68.20	-14.08	peak

Standard:	Part 15.407	Test Site:	966 Chamber
Polarization:	Vertical		
Test Mode:	802.11n HT40 5795 MHz		
Remark:			




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	11590.000	34.92	15.03	49.95	74.00	-24.05	peak
2*	17385.000	33.04	22.38	55.42	68.20	-12.78	peak

Standard:	Part 15.407	Test Site:	966 Chamber
Polarization:	Horizontal		
Test Mode:	Simultaneous Transmitting WLAN 2.4 GHz + 5 GHz		
Remark:			



No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2751.000	42.90	-5.56	37.34	74.00	-36.66	peak
2	3839.000	42.63	-2.95	39.68	74.00	-34.32	peak
3*	4961.000	39.86	0.45	40.31	74.00	-33.69	peak

Standard:	Part 15.407	Test Site:	966 Chamber
Polarization:	Vertical		
Test Mode:	Simultaneous Transmitting WLAN 2.4 GHz + 5 GHz		
Remark:			




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2802.000	42.43	-5.51	36.92	74.00	-37.08	peak
2	3907.000	41.06	-2.71	38.35	74.00	-35.65	peak
3*	4791.000	39.25	-0.02	39.23	74.00	-34.77	peak

Band Edge


Peak

Standard:	Part 15.407	Test Site:	966 Chamber
Polarization:	Horizontal		
Test Mode:	802.11a 5180 MHz		
Remark:			




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5146.000	58.44	1.28	59.72	74.00	-14.28	peak
2	5150.000	56.84	1.28	58.12	74.00	-15.88	peak
3*	5178.680	107.39	1.09	108.48	68.20	40.28	peak

Standard:	Part 15.407	Test Site:	966 Chamber
Polarization:	Vertical		
Test Mode:	802.11a 5180 MHz		
Remark:			




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5066.200	55.06	1.13	56.19	74.00	-17.81	peak
2	5150.000	52.42	1.28	53.70	74.00	-20.30	peak
3*	5177.920	99.18	1.10	100.28	68.20	32.08	peak

Standard:	Part 15.407	Test Site:	966 Chamber
Polarization:	Horizontal		
Test Mode:	802.11a 5240 MHz		
Remark:			




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5116.320	53.27	1.30	54.57	74.00	-19.43	peak
2	5150.000	51.75	1.28	53.03	74.00	-20.97	peak
3*	5238.240	106.95	0.91	107.86	68.20	39.66	peak
4	5350.000	49.41	0.94	50.35	74.00	-23.65	peak
5	5452.320	52.76	1.77	54.53	74.00	-19.47	peak

Standard:	Part 15.407	Test Site:	966 Chamber
Polarization:	Vertical		
Test Mode:	802.11a 5240 MHz		
Remark:			




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5085.600	53.17	1.23	54.40	74.00	-19.60	peak
2	5150.000	51.39	1.28	52.67	74.00	-21.33	peak
3*	5240.160	100.46	0.91	101.37	68.20	33.17	peak
4	5350.000	49.11	0.94	50.05	74.00	-23.95	peak
5	5414.880	51.16	1.44	52.60	74.00	-21.40	peak

Standard:	Part 15.407	Test Site:	966 Chamber
Polarization:	Horizontal		
Test Mode:	802.11a 5745 MHz		
Remark:			




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1*	5644.250	51.90	1.74	53.64	68.20	-14.56	peak
2	5650.000	49.51	1.75	51.26	68.20	-16.94	peak
3	5700.000	52.01	1.72	53.73	105.20	-51.47	peak
4	5720.000	61.13	1.99	63.12	110.80	-47.68	peak
5	5725.000	69.61	2.05	71.66	122.20	-50.54	peak
6	5742.500	102.73	2.29	105.02	131.20	-26.18	peak

Standard:	Part 15.407	Test Site:	966 Chamber
Polarization:	Vertical		
Test Mode:	802.11a 5745 MHz		
Remark:			




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1*	5644.625	51.81	1.74	53.55	68.20	-14.65	peak
2	5650.000	49.99	1.75	51.74	68.20	-16.46	peak
3	5700.000	50.55	1.72	52.27	105.20	-52.93	peak
4	5720.000	54.29	1.99	56.28	110.80	-54.52	peak
5	5725.000	61.83	2.05	63.88	122.20	-58.32	peak
6	5747.375	95.20	2.36	97.56	131.20	-33.64	peak

Standard:	Part 15.407	Test Site:	966 Chamber
Polarization:	Horizontal		
Test Mode:	802.11a 5825 MHz		
Remark:			




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5823.125	100.81	2.79	103.60	131.20	-27.60	peak
2	5850.000	59.37	2.83	62.20	122.20	-60.00	peak
3	5855.000	60.17	2.86	63.03	110.80	-47.77	peak
4	5875.000	51.29	2.92	54.21	105.20	-50.99	peak
5	5925.000	49.54	2.90	52.44	68.20	-15.76	peak
6*	5930.000	50.99	2.87	53.86	68.20	-14.34	peak

Standard:	Part 15.407	Test Site:	966 Chamber
Polarization:	Vertical		
Test Mode:	802.11a 5825 MHz		
Remark:			




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5827.250	94.46	2.81	97.27	131.20	-33.93	peak
2	5850.000	55.02	2.83	57.85	122.20	-64.35	peak
3	5855.000	54.42	2.86	57.28	110.80	-53.52	peak
4	5875.000	49.41	2.92	52.33	105.20	-52.87	peak
5	5925.000	49.27	2.90	52.17	68.20	-16.03	peak
6*	5951.375	51.72	2.78	54.50	68.20	-13.70	peak

Standard:	Part 15.407	Test Site:	966 Chamber
Polarization:	Horizontal		
Test Mode:	802.11n HT20 5180 MHz		
Remark:			




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5146.760	54.78	1.28	56.06	74.00	-17.94	peak
2	5150.000	57.20	1.28	58.48	74.00	-15.52	peak
3*	5181.720	106.40	1.07	107.47	68.20	39.27	peak

Standard:	Part 15.407	Test Site:	966 Chamber
Polarization:	Vertical		
Test Mode:	802.11n HT20 5180 MHz		
Remark:			




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5146.760	52.97	1.28	54.25	74.00	-19.75	peak
2	5150.000	50.56	1.28	51.84	74.00	-22.16	peak
3*	5177.920	98.30	1.10	99.40	68.20	31.20	peak

Standard:	Part 15.407	Test Site:	966 Chamber
Polarization:	Horizontal		
Test Mode:	802.11n HT20 5240 MHz		
Remark:			




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5028.960	53.17	0.89	54.06	74.00	-19.94	peak
2	5150.000	52.62	1.28	53.90	74.00	-20.10	peak
3*	5237.280	105.96	0.92	106.88	68.20	38.68	peak
4	5350.000	49.24	0.94	50.18	74.00	-23.82	peak
5	5455.200	50.73	1.77	52.50	74.00	-21.50	peak

Standard:	Part 15.407	Test Site:	966 Chamber
Polarization:	Vertical		
Test Mode:	802.11n HT20 5240 MHz		
Remark:			




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5066.400	53.30	1.14	54.44	74.00	-19.56	peak
2	5150.000	51.09	1.28	52.37	74.00	-21.63	peak
3*	5241.120	98.75	0.91	99.66	68.20	31.46	peak
4	5350.000	50.09	0.94	51.03	74.00	-22.97	peak
5	5460.000	51.04	1.79	52.83	74.00	-21.17	peak

Standard:	Part 15.407	Test Site:	966 Chamber
Polarization:	Horizontal		
Test Mode:	802.11n HT20 5745 MHz		
Remark:			




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1*	5643.875	51.68	1.74	53.42	68.20	-14.78	peak
2	5650.000	49.77	1.75	51.52	68.20	-16.68	peak
3	5700.000	51.35	1.72	53.07	105.20	-52.13	peak
4	5720.000	56.54	1.99	58.53	110.80	-52.27	peak
5	5725.000	66.89	2.05	68.94	122.20	-53.26	peak
6	5742.500	102.20	2.29	104.49	131.20	-26.71	peak

Standard:	Part 15.407	Test Site:	966 Chamber
Polarization:	Vertical		
Test Mode:	802.11n HT20 5745 MHz		
Remark:			




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1*	5630.375	51.41	1.72	53.13	68.20	-15.07	peak
2	5650.000	49.23	1.75	50.98	68.20	-17.22	peak
3	5700.000	49.63	1.72	51.35	105.20	-53.85	peak
4	5720.000	56.85	1.99	58.84	110.80	-51.96	peak
5	5725.000	61.10	2.05	63.15	122.20	-59.05	peak
6	5743.625	96.46	2.31	98.77	131.20	-32.43	peak

Standard:	Part 15.407	Test Site:	966 Chamber
Polarization:	Horizontal		
Test Mode:	802.11n HT20 5825 MHz		
Remark:			




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5826.500	100.40	2.81	103.21	131.20	-27.99	peak
2	5850.000	60.45	2.83	63.28	122.20	-58.92	peak
3	5855.000	57.49	2.86	60.35	110.80	-50.45	peak
4	5875.000	50.70	2.92	53.62	105.20	-51.58	peak
5	5925.000	49.77	2.90	52.67	68.20	-15.53	peak
6*	5927.375	50.82	2.89	53.71	68.20	-14.49	peak

Standard:	Part 15.407	Test Site:	966 Chamber
Polarization:	Vertical		
Test Mode:	802.11n HT20 5825 MHz		
Remark:			




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5829.500	93.85	2.81	96.66	131.20	-34.54	peak
2	5850.000	56.89	2.83	59.72	122.20	-62.48	peak
3	5855.000	52.73	2.86	55.59	110.80	-55.21	peak
4	5875.000	50.52	2.92	53.44	105.20	-51.76	peak
5	5925.000	48.86	2.90	51.76	68.20	-16.44	peak
6*	5948.750	51.78	2.78	54.56	68.20	-13.64	peak

Standard:	Part 15.407	Test Site:	966 Chamber
Polarization:	Horizontal		
Test Mode:	802.11n HT40 5190 MHz		
Remark:			




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5142.960	55.11	1.28	56.39	74.00	-17.61	peak
2	5150.000	55.23	1.28	56.51	74.00	-17.49	peak
3*	5191.600	99.80	1.00	100.80	68.20	32.60	peak

Standard:	Part 15.407	Test Site:	966 Chamber
Polarization:	Vertical		
Test Mode:	802.11n HT40 5190 MHz		
Remark:			




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5101.920	53.01	1.31	54.32	74.00	-19.68	peak
2	5150.000	55.36	1.28	56.64	74.00	-17.36	peak
3*	5187.800	91.34	1.02	92.36	68.20	24.16	peak

Standard:	Part 15.407	Test Site:	966 Chamber
Polarization:	Horizontal		
Test Mode:	802.11n HT40 5230 MHz		
Remark:			




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5114.400	53.07	1.30	54.37	74.00	-19.63	peak
2	5150.000	53.43	1.28	54.71	74.00	-19.29	peak
3*	5224.800	102.69	0.92	103.61	68.20	35.41	peak
4	5350.000	49.42	0.94	50.36	74.00	-23.64	peak
5	5453.280	50.87	1.77	52.64	74.00	-21.36	peak

Standard:	Part 15.407	Test Site:	966 Chamber
Polarization:	Vertical		
Test Mode:	802.11n HT40 5230 MHz		
Remark:			




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5058.720	53.14	1.09	54.23	74.00	-19.77	peak
2	5150.000	50.53	1.28	51.81	74.00	-22.19	peak
3*	5231.520	97.01	0.92	97.93	68.20	29.73	peak
4	5350.000	49.44	0.94	50.38	74.00	-23.62	peak
5	5430.240	52.38	1.59	53.97	74.00	-20.03	peak

Standard:	Part 15.407	Test Site:	966 Chamber
Polarization:	Horizontal		
Test Mode:	802.11n HT40 5755 MHz		
Remark:			




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1*	5625.500	52.45	1.71	54.16	68.20	-14.04	peak
2	5650.000	49.25	1.75	51.00	68.20	-17.20	peak
3	5700.000	54.95	1.72	56.67	105.20	-48.53	peak
4	5720.000	67.97	1.99	69.96	110.80	-40.84	peak
5	5725.000	69.08	2.05	71.13	122.20	-51.07	peak
6	5751.875	97.43	2.40	99.83	131.20	-31.37	peak

Standard:	Part 15.407	Test Site:	966 Chamber
Polarization:	Vertical		
Test Mode:	802.11n HT40 5755 MHz		
Remark:			




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1*	5601.125	51.46	1.68	53.14	68.20	-15.06	peak
2	5650.000	49.73	1.75	51.48	68.20	-16.72	peak
3	5700.000	51.62	1.72	53.34	105.20	-51.86	peak
4	5720.000	61.46	1.99	63.45	110.80	-47.35	peak
5	5725.000	62.68	2.05	64.73	122.20	-57.47	peak
6	5750.375	90.75	2.39	93.14	131.20	-38.06	peak

Standard:	Part 15.407	Test Site:	966 Chamber
Polarization:	Horizontal		
Test Mode:	802.11n HT40 5795 MHz		
Remark:			



No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5790.500	96.96	2.69	99.65	131.20	-31.55	peak
2	5850.000	50.53	2.83	53.36	122.20	-68.84	peak
3	5855.000	49.52	2.86	52.38	110.80	-58.42	peak
4	5875.000	49.35	2.92	52.27	105.20	-52.93	peak
5	5925.000	49.66	2.90	52.56	68.20	-15.64	peak
6*	5964.500	51.75	2.82	54.57	68.20	-13.63	peak


Standard:	Part 15.407	Test Site:	966 Chamber
Polarization:	Vertical		
Test Mode:	802.11n HT40 5795 MHz		
Remark:			



No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5790.125	90.93	2.69	93.62	131.20	-37.58	peak
2	5850.000	49.85	2.83	52.68	122.20	-69.52	peak
3	5855.000	50.17	2.86	53.03	110.80	-57.77	peak
4	5875.000	51.71	2.92	54.63	105.20	-50.57	peak
5	5925.000	49.11	2.90	52.01	68.20	-16.19	peak
6*	5938.625	51.32	2.84	54.16	68.20	-14.04	peak


AVG

Standard:	Part 15.407	Test Site:	966 Chamber
Polarization:	Horizontal		
Test Mode:	802.11a 5180 MHz		
Remark:			




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5148.280	46.81	1.28	48.09	54.00	-5.91	AVG
2*	5150.000	48.40	1.28	49.68	54.00	-4.32	AVG

Standard:	Part 15.407	Test Site:	966 Chamber
Polarization:	Vertical		
Test Mode:	802.11a 5180 MHz		
Remark:			




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5146.000	42.40	1.28	43.68	54.00	-10.32	AVG
2*	5150.000	43.38	1.28	44.66	54.00	-9.34	AVG

Standard:	Part 15.407	Test Site:	966 Chamber
Polarization:	Horizontal		
Test Mode:	802.11a 5240 MHz		
Remark:			




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1*	5133.600	43.38	1.28	44.66	54.00	-9.34	AVG
2	5150.000	41.37	1.28	42.65	54.00	-11.35	AVG
3	5350.000	39.82	0.94	40.76	54.00	-13.24	AVG
4	5448.480	39.54	1.76	41.30	54.00	-12.70	AVG

Standard:	Part 15.407	Test Site:	966 Chamber
Polarization:	Vertical		
Test Mode:	802.11a 5240 MHz		
Remark:			




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1*	5138.400	41.72	1.28	43.00	54.00	-11.00	AVG
2	5150.000	41.36	1.28	42.64	54.00	-11.36	AVG
3	5350.000	39.44	0.94	40.38	54.00	-13.62	AVG
4	5455.200	39.49	1.77	41.26	54.00	-12.74	AVG

Standard:	Part 15.407	Test Site:	966 Chamber
Polarization:	Horizontal		
Test Mode:	802.11n HT20 5180 MHz		
Remark:			




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5148.280	46.41	1.28	47.69	54.00	-6.31	AVG
2*	5150.000	47.85	1.28	49.13	54.00	-4.87	AVG

Standard:	Part 15.407	Test Site:	966 Chamber
Polarization:	Vertical		
Test Mode:	802.11n HT20 5180 MHz		
Remark:			




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5145.240	42.14	1.28	43.42	54.00	-10.58	AVG
2*	5150.000	42.88	1.28	44.16	54.00	-9.84	AVG

Standard:	Part 15.407	Test Site:	966 Chamber
Polarization:	Horizontal		
Test Mode:	802.11n HT20 5240 MHz		
Remark:			




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1*	5134.560	42.84	1.29	44.13	54.00	-9.87	AVG
2	5150.000	41.34	1.28	42.62	54.00	-11.38	AVG
3	5350.000	39.77	0.94	40.71	54.00	-13.29	AVG
4	5455.200	39.80	1.77	41.57	54.00	-12.43	AVG

Standard:	Part 15.407	Test Site:	966 Chamber
Polarization:	Vertical		
Test Mode:	802.11n HT20 5240 MHz		
Remark:			




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1*	5073.120	41.62	1.16	42.78	54.00	-11.22	AVG
2	5150.000	41.05	1.28	42.33	54.00	-11.67	AVG
3	5350.000	39.58	0.94	40.52	54.00	-13.48	AVG
4	5460.000	39.37	1.79	41.16	54.00	-12.84	AVG

Standard:	Part 15.407	Test Site:	966 Chamber
Polarization:	Horizontal		
Test Mode:	802.11n HT40 5190 MHz		
Remark:			




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5148.280	45.85	1.28	47.13	54.00	-6.87	AVG
2*	5150.000	47.42	1.28	48.70	54.00	-5.30	AVG

Standard:	Part 15.407	Test Site:	966 Chamber
Polarization:	Vertical		
Test Mode:	802.11n HT40 5190 MHz		
Remark:			




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5146.760	41.93	1.28	43.21	54.00	-10.79	AVG
2*	5150.000	42.82	1.28	44.10	54.00	-9.90	AVG

Standard:	Part 15.407	Test Site:	966 Chamber
Polarization:	Horizontal		
Test Mode:	802.11n HT40 5230 MHz		
Remark:			



No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5140.320	42.25	1.28	43.53	54.00	-10.47	AVG
2*	5150.000	43.20	1.28	44.48	54.00	-9.52	AVG
3	5350.000	39.52	0.94	40.46	54.00	-13.54	AVG
4	5452.320	39.85	1.77	41.62	54.00	-12.38	AVG

Standard:	Part 15.407	Test Site:	966 Chamber
Polarization:	Vertical		
Test Mode:	802.11n HT40 5230 MHz		
Remark:			



No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1*	5111.520	41.78	1.31	43.09	54.00	-10.91	AVG
2	5150.000	41.54	1.28	42.82	54.00	-11.18	AVG
3	5350.000	39.47	0.94	40.41	54.00	-13.59	AVG
4	5458.080	39.65	1.78	41.43	54.00	-12.57	AVG

5.3. Conducted Test Results

Duty cycle

Reference Appendix A / Appendix B

Maximum Conducted Output Power Measurement

Reference Appendix A

26 dB RF Bandwidth Measurement

Reference Appendix A / Appendix B

6 dB RF Bandwidth Measurement

Reference Appendix A / Appendix B

Maximum Power Spectral Density Measurement

Reference Appendix A / Appendix B

---END---