

FCC ID: X4D-SC-1
Report No.: T200205D04-RP4

Page: 1 / 244
Rev.: 01

RADIO TEST REPORT

FCC 47 CFR PART 15 SUBPART E

Test Standard	FCC Part 15.407
Product name	SYSTEM TABLET CONTROLLER
Brand Name	OLYMPUS
Model No.	SC-1
Test Result	Pass
Statements of Conformity	Determination of compliance is based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.

The test Result was tested by Compliance Certification Services Inc. The test data, data evaluation, test procedures, and equipment configurations shown in this report were given in ANSI C63.10: 2013 and compliance standards.

The test results of this report relate only to the tested sample (EUT) identified in this report.

The test Report of full or partial shall not copy. Without written approval of Compliance Certification Services Inc.(Wugu Laboratory)

Approved by:



Kevin Tsai
Deputy Manager

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com.tw/Terms-and-Conditions> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com.tw/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of client's instruction, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced, except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.



Report No.: T200205D04-RP4

Page: 2 / 244

Rev.: 01

Revision History

Rev.	Issue Date	Revisions	Effect Page	Revised By
00	July 14, 2020	Initial Issue	ALL	Allison Chen
01	July 27, 2020	See the following note Rev.(01)	P.A-1	Allison Chen

Rev.(01)

1. Modify test setup photo for above 1GHz.



Report No.: T200205D04-RP4

Page: 3 / 244

Rev.: 01

Table of contents

1. GENERAL INFORMATION	4
1.1 EUT INFORMATION	4
1.2 EUT CHANNEL INFORMATION	5
1.3 ANTENNA INFORMATION	6
1.4 MEASUREMENT UNCERTAINTY	6
1.5 FACILITIES AND TEST LOCATION	7
1.6 INSTRUMENT CALIBRATION.....	7
1.7 SUPPORT AND EUT ACCESSORIES EQUIPMENT.....	8
1.8 TEST METHODOLOGY AND APPLIED STANDARDS	8
2. TEST SUMMERY	9
3. DESCRIPTION OF TEST MODES	10
3.1 THE EUT CHANNEL NUMBER OF OPERATING CONDITION.....	10
3.2 THE WORST MODE OF MEASUREMENT	11
3.3 EUT DUTY CYCLE	12
4. TEST RESULT	13
4.1 AC POWER LINE CONDUCTED EMISSION	13
4.2 26DB BANDWIDTH, 6DB BANDWIDTH AND OCCUPIED BANDWIDTH(99%)	16
4.3 OUTPUT POWER MEASUREMENT.....	74
4.4 POWER SPECTRAL DENSITY	84
4.5 RADIATION BANDEDGE AND SPURIOUS EMISSION	116
4.6 FREQUENCY STABILITY.....	242
APPENDIX-A TEST PHOTO	A-1
APPENDIX 1 - PHOTOGRAPHS OF EUT	



Report No.: T200205D04-RP4

Page: 4 / 244

Rev.: 01

1. GENERAL INFORMATION

1.1 EUT INFORMATION

Applicant	ADLINK TECHNOLOGY INC. 9F, No.166, Jian Yi Rd., Zhonghe Dist., New Taipei City, 235 Taiwan
Manufacturer	ADLINK TECHNOLOGY INC. 9F, No.166, Jian Yi Rd., Zhonghe Dist., New Taipei City, 235 Taiwan
Equipment	SYSTEM TABLET CONTROLLER
Model No.	SC-1
Model Discrepancy	N/A
Trade Name	OLYMPUS
Received Date	February 5, 2020
Date of Test	February 17 ~ May 12, 2020
Power Operation	1. EUT Power from Adapter. FSP GROUP INC. / FSP065M-DBA I/P: 100-240Vac, 2.0-1.0A, 50-60Hz O/P: 19.0Vdc, 3.43A Max 2. Power from Rechargeable Lithium Polymer Battery. Rating: 11.1Vdc, 2300mAh
HW Version	A2
SW Version	7.2

1.2 EUT CHANNEL INFORMATION

Frequency Range	<table border="1"> <thead> <tr> <th colspan="2">UNII-1</th></tr> </thead> <tbody> <tr> <td>IEEE 802.11a</td><td>5180 ~ 5240 MHz</td></tr> <tr> <td>IEEE 802.11n HT 20 MHz</td><td>5180 ~ 5240 MHz</td></tr> <tr> <td>IEEE 802.11n HT 40 MHz</td><td>5190 ~ 5230 MHz</td></tr> <tr> <td>IEEE 802.11ac VHT 80 MHz</td><td>5210 MHz</td></tr> </tbody> </table> <table border="1"> <thead> <tr> <th colspan="2">UNII-2a</th></tr> </thead> <tbody> <tr> <td>IEEE 802.11a</td><td>5260 ~ 5320 MHz</td></tr> <tr> <td>IEEE 802.11n HT 20 MHz</td><td>5260 ~ 5320 MHz</td></tr> <tr> <td>IEEE 802.11n HT 40 MHz</td><td>5270 ~ 5310 MHz</td></tr> <tr> <td>IEEE 802.11ac VHT 80 MHz</td><td>5290 MHz</td></tr> </tbody> </table> <table border="1"> <thead> <tr> <th colspan="2">UNII-2c</th></tr> </thead> <tbody> <tr> <td>IEEE 802.11a</td><td>5500 ~ 5700 MHz</td></tr> <tr> <td>IEEE 802.11n HT 20 MHz</td><td>5500 ~ 5700 MHz</td></tr> <tr> <td>IEEE 802.11n HT 40 MHz</td><td>5510 ~ 5670 MHz</td></tr> <tr> <td>IEEE 802.11ac VHT 80 MHz</td><td>5530 MHz</td></tr> </tbody> </table> <table border="1"> <thead> <tr> <th colspan="2">UNII-3</th></tr> </thead> <tbody> <tr> <td>IEEE 802.11a</td><td>5745 ~ 5825 MHz</td></tr> <tr> <td>IEEE 802.11n HT 20 MHz</td><td>5745 ~ 5825 MHz</td></tr> <tr> <td>IEEE 802.11n HT 40 MHz</td><td>5755 ~ 5795 MHz</td></tr> <tr> <td>IEEE 802.11ac VHT 80 MHz</td><td>5775 MHz</td></tr> </tbody> </table>	UNII-1		IEEE 802.11a	5180 ~ 5240 MHz	IEEE 802.11n HT 20 MHz	5180 ~ 5240 MHz	IEEE 802.11n HT 40 MHz	5190 ~ 5230 MHz	IEEE 802.11ac VHT 80 MHz	5210 MHz	UNII-2a		IEEE 802.11a	5260 ~ 5320 MHz	IEEE 802.11n HT 20 MHz	5260 ~ 5320 MHz	IEEE 802.11n HT 40 MHz	5270 ~ 5310 MHz	IEEE 802.11ac VHT 80 MHz	5290 MHz	UNII-2c		IEEE 802.11a	5500 ~ 5700 MHz	IEEE 802.11n HT 20 MHz	5500 ~ 5700 MHz	IEEE 802.11n HT 40 MHz	5510 ~ 5670 MHz	IEEE 802.11ac VHT 80 MHz	5530 MHz	UNII-3		IEEE 802.11a	5745 ~ 5825 MHz	IEEE 802.11n HT 20 MHz	5745 ~ 5825 MHz	IEEE 802.11n HT 40 MHz	5755 ~ 5795 MHz	IEEE 802.11ac VHT 80 MHz	5775 MHz
UNII-1																																									
IEEE 802.11a	5180 ~ 5240 MHz																																								
IEEE 802.11n HT 20 MHz	5180 ~ 5240 MHz																																								
IEEE 802.11n HT 40 MHz	5190 ~ 5230 MHz																																								
IEEE 802.11ac VHT 80 MHz	5210 MHz																																								
UNII-2a																																									
IEEE 802.11a	5260 ~ 5320 MHz																																								
IEEE 802.11n HT 20 MHz	5260 ~ 5320 MHz																																								
IEEE 802.11n HT 40 MHz	5270 ~ 5310 MHz																																								
IEEE 802.11ac VHT 80 MHz	5290 MHz																																								
UNII-2c																																									
IEEE 802.11a	5500 ~ 5700 MHz																																								
IEEE 802.11n HT 20 MHz	5500 ~ 5700 MHz																																								
IEEE 802.11n HT 40 MHz	5510 ~ 5670 MHz																																								
IEEE 802.11ac VHT 80 MHz	5530 MHz																																								
UNII-3																																									
IEEE 802.11a	5745 ~ 5825 MHz																																								
IEEE 802.11n HT 20 MHz	5745 ~ 5825 MHz																																								
IEEE 802.11n HT 40 MHz	5755 ~ 5795 MHz																																								
IEEE 802.11ac VHT 80 MHz	5775 MHz																																								
Modulation Type	1. IEEE 802.11a mode: OFDM 2. IEEE 802.11n HT 20 MHz mode: OFDM 3. IEEE 802.11n HT 40 MHz mode: OFDM 4. IEEE 802.11ac VHT 80 MHz mode: OFDM																																								

Remark:

Refer as ANSI C63.10: 2013 clause 5.6.1 Table 4 for test channels

Number of frequencies to be tested		
Frequency range in which device operates	Number of frequencies	Location in frequency range of operation
☐ 1 MHz or less	1	Middle
☐ 1 MHz to 10 MHz	2	1 near top and 1 near bottom
☒ More than 10 MHz	3	1 near top, 1 near middle, and 1 near bottom

1.3 ANTENNA INFORMATION

Antenna Specification	PCB Antenna			
Antenna Gain	1. IEEE 802.11 a mode: Chain 0: 2.22 dBi Chain 1: 3.37 dBi			
	2. IEEE 802.11n HT20 / HT40 / ac VHT 80 MHz mode:			
	Band	Chain0 (dBi)	Chain1 (dBi)	Power Directional Gain: (dBi)
	5G_U-NII 1	1.11	2.21	1.69
	5G_U-NII 2	1.11	2.21	1.69
	5G_U-NII 2a	2.22	3.37	2.83
	5G_U-NII 3	0.62	2.44	1.62
Antenna connector	IPEX			

Notes:

1. Power Directional Gain = $10 \cdot \text{LOG}(((10^{(\text{Ant1}/10)} + 10^{(\text{Ant2}/10)})/2))$

1.4 MEASUREMENT UNCERTAINTY

PARAMETER	UNCERTAINTY
AC Powerline Conducted Emission	+/- 1.2575
Emission bandwidth, 20dB bandwidth	+/- 0.0014
RF output power, conducted	+/- 1.14
Power density, conducted	+/- 1.40
3M Semi Anechoic Chamber / 30M~200M	+/- 4.12
3M Semi Anechoic Chamber / 200M~1000M	+/- 4.68
3M Semi Anechoic Chamber / 1G~8G	+/- 5.18
3M Semi Anechoic Chamber / 8G~18G	+/- 5.47
3M Semi Anechoic Chamber / 18G~26G	+/- 3.81
3M Semi Anechoic Chamber / 26G~40G	+/- 3.87

Remark:

1. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=2$

2. ISO/IEC 17025 requires that an estimate of the measurement uncertainties associated with the emissions test results be included in the report.

1.5 FACILITIES AND TEST LOCATION

All measurement facilities used to collect the measurement data are located at

No.11, Wugong 6th Rd., Wugu Dist., New Taipei City, Taiwan. (R.O.C.)

Test site	Test Engineer	Remark
AC Conduction Room	Dally Hong	-
Radiation	Jerry Chang	-
RF Conducted	Dally Hong	-

Remark: The sites are constructed in conformance with the requirements of ANSI C63.7, ANSI C63.4 and CISPR Publication 22.

1.6 INSTRUMENT CALIBRATION

3M 966 Chamber Test Site					
Name of Equipment	Manufacturer	Model	Serial Number	Calibration Date	Calibration Due
Bilog Antenna	Sunol Sciences	JB3	A030105	07/26/2019	07/25/2020
Coaxial Cable	HUBER SUHNER	SUCOFLEX 104PEA	20995	02/25/2020	02/24/2021
Coaxial Cable	EMCI	EMC105	190914+25111	09/20/2019	09/19/2020
Digital Thermo-Hygro Meter	WISEWIND	1206	D07	01/15/2020	01/14/2021
double Ridged Guide Horn Antenna	ETC	MCTD 1209	DRH13M02003	10/04/2019	10/03/2020
High Pass Filters	MICRO TRONICS	HPM13195	003	02/25/2020	02/24/2021
Horn Antenna	ETS LINDGREN	3116	00026370	12/18/2019	12/17/2020
Pre-Amplifier	EMEC	EM330	060609	02/25/2020	02/24/2021
Pre-Amplifier	HP	8449B	3008A00965	02/25/2020	02/24/2021
Pre-Amplifier	MITEQ	AMF-6F-1800 4000-37-8P	985646	06/18/2019	06/17/2020
PSA Series Spectrum Analyzer	Agilent	E4446A	MY46180323	05/29/2019	05/28/2020
Antenna Tower	CCS	CC-A-1F	N/A	N.C.R	N.C.R
Controller	CCS	CC-C-1F	N/A	N.C.R	N.C.R
Turn Table	CCS	CC-T-1F	N/A	N.C.R	N.C.R
Software	e3 6.11-20180413				

RF Conducted Test Site					
Name of Equipment	Manufacturer	Model	Serial Number	Calibration Date	Calibration Due
Coaxial Cable	Woken	WC12	CC001	06/28/2019	06/27/2020
Coaxial Cable	Woken	WC12	CC003	06/28/2019	06/27/2020
Signal Analyzer	R&S	FSV 40	101073	09/25/2019	09/24/2020
Power Meter	Anritsu	ML2495A	1149001	N.C.R	N.C.R
Power Seneor	Anritsu	MA2491A	030982	N.C.R	N.C.R
Software	N/A				

AC line Conduction Test Room					
Name of Equipment	Manufacturer	Model	Serial Number	Calibration Date	Calibration Due
CABLE	EMCI	CFD300-NL	CERF	06/27/2019	06/26/2020
EMI Test Receiver	R&S	ESCI	100064	07/26/2019	07/25/2020
LISN	SCHAFFNER	NNB 41	03/10013	02/13/2020	02/12/2021
Software	EZ-EMC(CCS-3A1-CE)				

Remark:

- Each piece of equipment is scheduled for calibration once a year.
- N.C.R. = No Calibration Required.

1.7 SUPPORT AND EUT ACCESSORIES EQUIPMENT

EUT Accessories Equipment					
No.	Equipment	Brand	Model	Series No.	FCC ID
	N/A				

Support Equipment					
No.	Equipment	Brand	Model	Series No.	FCC ID
	N/A				

1.8 TEST METHODOLOGY AND APPLIED STANDARDS

The test methodology, setups and results comply with all requirements in accordance with ANSI C63.10:2013, FCC Part 2, FCC Part 15.407, KDB 789033 D02, KDB 905462 D02.



Report No.: T200205D04-RP4

Page: 9 / 244

Rev.: 01

2. TEST SUMMERY

FCC Standard Sec.	Chapter	Test Item	Result
15.203	1.3	Antenna Requirement	Pass
15.207	4.1	AC Conducted Emission	Pass
15.403(i)	4.2	26dB Bandwidth	Pass
15.407(e)	4.2	6dB Bandwidth	Pass
2.1049	4.2	Occupied Bandwidth (99%)	Pass
15.407(a)	4.3	Output Power Measurement	Pass
15.407(a)	4.4	Power Spectral Density	Pass
15.407(b)	4.5	Radiation Band Edge	Pass
15.407(b)	4.5	Radiation Spurious Emission	Pass
15.407(g)	4.6	Frequency Stability	Pass
15.407(h)	4.7	Dynamic Frequency Selection	Pass

3. DESCRIPTION OF TEST MODES

3.1 THE EUT CHANNEL NUMBER OF OPERATING CONDITION

Operation mode	1. IEEE 802.11a mode: 6Mbps 2. IEEE 802.11n HT 20 MHz mode: MCS8 3. IEEE 802.11n HT 40 MHz mode: MCS8 4. IEEE 802.11ac VHT 80 MHz mode: MCS8				
Operating Frequency			Mode	Frequency Range (MHz)	
		U-NII-1	IEEE 802.11a	5180, 5220, 5240	
			IEEE 802.11n HT 20 MHz	5180, 5220, 5240	
			IEEE 802.11n HT 40 MHz	5190, 5230	
			IEEE 802.11ac VHT 80 MHz	5210	
		U-NII-2a	IEEE 802.11a	5260, 5280, 5320	
			IEEE 802.11n HT 20 MHz	5260, 5280, 5320	
			IEEE 802.11n HT 40 MHz	5270, 5310	
			IEEE 802.11ac VHT 80 MHz	5290	
		U-NII-2c	IEEE 802.11a	5500, 5580, 5700	
			IEEE 802.11n HT 20 MHz	5500, 5580, 5700	
			IEEE 802.11n HT 40 MHz	5510, 5550, 5670	
			IEEE 802.11ac VHT 80 MHz	5530	
		U-NII-3	IEEE 802.11a	5745, 5785, 5825	
			IEEE 802.11n HT 20 MHz	5745, 5785, 5825	
			IEEE 802.11n HT 40 MHz	5755, 5795	
IEEE 802.11ac VHT 80 MHz	5775				

Remark:

1. EUT pre-scanned data rate of output power for each mode, the worst data rate were recorded in this report.
2. The mode IEEE 802.11ac VHT20 and VHT40 are only different in control messages with IEEE 802.11n 20 MHz and HT40, and have same power setting. Therefore, the highest power(IEEE 802.11n 20 MHz and HT40) were test conducted and radiated measurement and recorded in this report.

3.2 THE WORST MODE OF MEASUREMENT

Radiated Emission Measurement Above 1G	
Test Condition	Radiated Emission Above 1G
Power supply Mode	Mode 1: EUT power by Adapter
Worst Mode	☒ Mode 1 ☐ Mode 2 ☐ Mode 3 ☐ Mode 4
Worst Position	☐ Placed in fixed position. ☐ Placed in fixed position at X-Plane (E2-Plane) ☒ Placed in fixed position at Y-Plane (E1-Plane) ☐ Placed in fixed position at Z-Plane (H-Plane)

Radiated Emission Measurement Below 1G	
Test Condition	Radiated Emission Below 1G
Power supply Mode	Mode 1: EUT power by Adapter
Worst Mode	☒ Mode 1 ☐ Mode 2 ☐ Mode 3 ☐ Mode 4


Remark:

1. The worst mode was record in this test report.
2. EUT pre-scanned in three axis ,X,Y, Z and two polarity, for radiated measurement. The worst case(Y-Plane) were recorded in this report

Report No.: T200205D04-RP4

3.3 EUT DUTY CYCLE

Duty Cycle				
Configuration	Duty Cycle (%)	Duty Factor (dB) $=10 \cdot \log(1/\text{Duty Cycle})$	1/T (kHz)	VBW setting (kHz)
802.11a	95.30%	0.21	0.49	1.00
802.11n HT20	94.22%	0.26	0.26	1.00
802.11n HT40	88.89%	0.51	0.54	1.00
802.11ac VHT80	92.78%	0.33	0.38	1.00



4. TEST RESULT

4.1 AC POWER LINE CONDUCTED EMISSION

4.1.1 Test Limit

According to §15.207(a),

Frequency Range (MHz)	Limits(dBμV)	
	Quasi-peak	Average
0.15 to 0.50	66 to 56*	56 to 46*
0.50 to 5	56	46
5 to 30	60	50


* Decreases with the logarithm of the frequency.

4.1.2 Test Procedure

Test method Refer as ANSI C63.10: 2013 clause 6.2,

1. The EUT was placed on a non-conducted table, which is 0.8m above horizontal ground plane and 0.4m above vertical ground plane.
2. EUT connected to the line impedance stabilization network (LISN)
3. Receiver set RBW of 9kHz and Detector Peak, and note as quasi-peak and average.
4. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
5. Recorded Line for Neutral and Line.

4.1.3 Test Setup




4.1.4 Test Result

Pass.


Test Data

Test Mode:	Mode 1	Temp/Hum	24(°C)/ 50%RH
Phase:	Line	Test Date	February 17, 2020
Test Voltage:	120Vac, 60Hz	Test Engineer	Dally Hong



Frequency (MHz)	Quasi Peak reading (dBuV)	Average reading (dBuV)	Correction factor (dB)	Quasi Peak result (dBuV)	Average result (dBuV)	Quasi Peak limit (dBuV)	Average limit (dBuV)	Quasi Peak margin (dB)	Average margin (dB)	Remark
0.1940	21.28	14.61	10.21	31.49	24.82	63.86	53.86	-32.37	-29.04	Pass
0.3067	19.54	11.56	10.22	29.76	21.78	60.06	50.06	-30.30	-28.28	Pass
0.3780	18.57	10.45	10.22	28.79	20.67	58.32	48.32	-29.53	-27.65	Pass
0.4500	20.53	11.02	10.22	30.75	21.24	56.88	46.88	-26.13	-25.64	Pass
0.6060	16.30	13.23	10.22	26.52	23.45	56.00	46.00	-29.48	-22.55	Pass
0.9260	22.11	9.49	10.24	32.35	19.73	56.00	46.00	-23.65	-26.27	Pass

Test Mode:	Mode 1	Temp/Hum	24(°C)/ 50%RH
Phase:	Line	Test Date	February 17, 2020
Test Voltage:	120Vac, 60Hz	Test Engineer	Dally Hong



Frequency (MHz)	Quasi Peak reading (dBuV)	Average reading (dBuV)	Correction factor (dB)	Quasi Peak result (dBuV)	Average result (dBuV)	Quasi Peak limit (dBuV)	Average limit (dBuV)	Quasi Peak margin (dB)	Average margin (dB)	Remark
0.2140	21.34	15.77	10.19	31.53	25.96	63.05	53.05	-31.52	-27.09	Pass
0.3140	35.58	26.03	10.19	45.77	36.22	59.86	49.86	-14.09	-13.64	Pass
0.4180	18.82	9.13	10.19	29.01	19.32	57.49	47.49	-28.48	-28.17	Pass
0.4940	11.63	5.14	10.19	21.82	15.33	56.10	46.10	-34.28	-30.77	Pass
0.6100	15.44	12.03	10.19	25.63	22.22	56.00	46.00	-30.37	-23.78	Pass
0.9260	23.68	9.14	10.21	33.89	19.35	56.00	46.00	-22.11	-26.65	Pass

4.2 26dB BANDWIDTH, 6dB BANDWIDTH AND OCCUPIED BANDWIDTH(99%)

4.2.1 Test Limit

26 dB Bandwidth : For reporting purposes only.

6 dB Bandwidth : Least 500kHz.

Occupied Bandwidth(99%) : For reporting purposes only.

4.2.2 Test Procedure

26dB


1. This measurement setting are specified in section D of KDB 789033 D02 General UNII Test Procedures New Rules v02r01.
2. Set RBW: approximately 1% of the emission bandwidth.
3. Set the VBW>RBW.
4. Detoctor = Peak.
5. Trace mode = max hold.
6. Measure the maximum width of the emission that is 26dB down from the peak of the emission. Compare this with the RBW setting of the analyser. Readjust RBW and repeat measurement as needed until the RBW/EBW ratio is approximately 1%.

6dB

1. This measurement setting are specified in section D of KDB 789033 D02 General UNII Test Procedures New Rules v02r01.
2. Set RBW = 100 kHz.
3. Set the video bandwidth (VBW) $\geq 3 \times$ RBW.
4. Detoctor = Peak.
5. Trace mode = max hold.
6. Sweep = auto couple.
7. Allow the trace to stabilize.
8. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

99%

1. This measurement setting are specified in section D of KDB 789033 D02 General UNII Test Procedures New Rules v02r01.
2. Set center frequency to the nominal EUT channel center frequency.
3. Set span = 1.5 times to 5.0 times the OBW.
4. Set RBW = 1 % to 5% of the OBW.
5. Set VBW $\geq 3 \times \text{RBW}$

4.2.3 Test Setup

4.2.4 Test Result

UNII-1 5150-5250 MHz					
Test mode: IEEE 802.11a mode					
Channel	Frequency (MHz)	Chain 0 OBW (99%) (MHz)	Chain 1 OBW (99%) (MHz)	Chain 0 26dB BW (MHz)	Chain 1 26dB BW (MHz)
Low	5180	16.2807	16.2807	19.9275	19.7101
Mid	5220	16.2807	16.2807	19.8551	20.0
High	5240	16.2807	16.2807	19.7826	20.2174
Test mode: IEEE 802.11n HT20 mode					
Channel	Frequency (MHz)	Chain 0 OBW (99%) (MHz)	Chain 1 OBW (99%) (MHz)	Chain 0 26dB BW (MHz)	Chain 1 26dB BW (MHz)
Low	5180	17.4384	17.3661	20.942	20.5797
Mid	5220	17.3661	17.3661	20.5072	20.6522
High	5240	17.3661	17.3661	20.3623	20.7971
Test mode: IEEE 802.11n HT40 mode					
Channel	Frequency (MHz)	Chain 0 OBW (99%) (MHz)	Chain 1 OBW (99%) (MHz)	Chain 0 26dB BW (MHz)	Chain 1 26dB BW (MHz)
Low	5190	36.0057	36.0057	42.435	41.971
High	5230	35.8900	35.8900	42.435	41.855
Test mode: IEEE 802.11ac VHT80 mode					
Channel	Frequency (MHz)	Chain 0 OBW (99%) (MHz)	Chain 1 OBW (99%) (MHz)	Chain 0 26dB BW (MHz)	Chain 1 26dB BW (MHz)
Mid	5210	75.2532	75.0217	83.478	83.478


UNII-2a 5250-5350 MHz					
Test mode: IEEE 802.11a mode					
Channel	Frequency (MHz)	Chain 0 OBW (99%) (MHz)	Chain 1 OBW (99%) (MHz)	Chain 0 26dB BW (MHz)	Chain 1 26dB BW (MHz)
Low	5260	16.2807	16.2807	20.0	19.8551
Mid	5280	16.2807	16.2807	20.0725	19.9275
High	5320	16.2807	16.2807	19.8551	20.0725
Test mode: IEEE 802.11n HT20 mode					
Channel	Frequency (MHz)	Chain 0 OBW (99%) (MHz)	Chain 1 OBW (99%) (MHz)	Chain 0 26dB BW (MHz)	Chain 1 26dB BW (MHz)
Low	5260	17.3661	17.3661	20.5797	20.5072
Mid	5280	17.4384	17.3661	20.6522	20.5797
High	5320	17.3661	17.4384	20.5072	20.2899
Test mode: IEEE 802.11n HT40 mode					
Channel	Frequency (MHz)	Chain 0 OBW (99%) (MHz)	Chain 1 OBW (99%) (MHz)	Chain 0 26dB BW (MHz)	Chain 1 26dB BW (MHz)
Low	5270	35.8900	36.0057	43.478	42.087
High	5310	35.8900	36.0057	44.638	42.551
Test mode: IEEE 802.11ac VHT80 mode					
Channel	Frequency (MHz)	Chain 0 OBW (99%) (MHz)	Chain 1 OBW (99%) (MHz)	Chain 0 26dB BW (MHz)	Chain 1 26dB BW (MHz)
Mid	5290	75.0217	75.0217	84.87	83.246

UNII-2c 5475-5725 MHz					
Test mode: IEEE 802.11a mode					
Channel	Frequency (MHz)	Chain 0 OBW (99%) (MHz)	Chain 1 OBW (99%) (MHz)	Chain 0 26dB BW (MHz)	Chain 1 26dB BW (MHz)
Low	5500	16.2807	16.2083	19.7826	20.0
Mid	5580	16.2807	16.2807	19.8551	19.5652
High	5700	16.2807	16.2807	20.0	19.8551
Test mode: IEEE 802.11n HT20 mode					
Channel	Frequency (MHz)	Chain 0 OBW (99%) (MHz)	Chain 1 OBW (99%) (MHz)	Chain 0 26dB BW (MHz)	Chain 1 26dB BW (MHz)
Low	5500	17.4384	17.4384	20.8696	20.7246
Mid	5580	17.4384	17.4384	20.4348	20.7246
High	5700	17.4384	17.4384	20.4348	20.2899
Test mode: IEEE 802.11n HT40 mode					
Channel	Frequency (MHz)	Chain 0 OBW (99%) (MHz)	Chain 1 OBW(99%) (MHz)	Chain 0 26dB BW (MHz)	Chain 1 26dB BW (MHz)
Low	5510	36.0057	36.0057	41.623	42.087
Mid	5550	36.0057	36.0057	42.203	42.319
High	5670	36.0057	36.0057	43.478	41.391
Test mode: IEEE 802.11ac VHT80 mode					
Channel	Frequency (MHz)	Chain 0 OBW(99%) (MHz)	Chain 1 OBW(99%) (MHz)	Chain 0 26dB BW (MHz)	Chain 1 26dB BW (MHz)
Low	5530	75.2532	75.2532	84.174	83.014

UNII-3 5725-5825MHz					
Test mode: IEEE 802.11a mode					
Channel	Frequency (MHz)	Chain 0 OBW(99%) (MHz)	Chain 1 OBW(99%) (MHz)	Chain 0 6dB BW (MHz)	Chain 1 6dB BW (MHz)
Low	5745	16.2807	16.2807	15.5217	15.2609
Mid	5785	16.2807	16.2807	15.3478	15.3043
High	5825	16.2807	16.2807	15.5217	15.3478
Test mode: IEEE 802.11n HT20 mode					
Channel	Frequency (MHz)	Chain 0 OBW(99%) (MHz)	Chain 1 OBW(99%) (MHz)	Chain 0 6dB BW (MHz)	Chain 1 6dB BW (MHz)
Low	5745	17.4384	17.4384	15.087	15.087
Mid	5785	17.3661	17.4384	15.1304	14.9565
High	5825	17.4384	17.4384	15.087	15.1739
Test mode: IEEE 802.11n HT40 mode					
Channel	Frequency (MHz)	Chain 0 OBW(99%) (MHz)	Chain 1 OBW(99%) (MHz)	Chain 0 6dB BW (MHz)	Chain 1 6dB BW (MHz)
Low	5755	36.0057	36.0057	35.014	35.13
High	5795	36.0057	36.0057	35.13	35.014
Test mode: IEEE 802.11ac VHT80 mode					
Channel	Frequency (MHz)	Chain 0 OBW(99%) (MHz)	Chain 1 OBW(99%) (MHz)	Chain 0 6dB BW (MHz)	Chain 1 6dB BW (MHz)
Mid	5775	75.2532	75.0217	75.13	75.13


Report No.: T200205D04-RP4

Test Data (26dB BANDWIDTH)




UNII-1 IEEE 802.11n HT20 mode- chain 0


Low CH



Mid CH




High CH




UNII-1 IEEE 802.11n HT40 mode- chain 0

Low CH




High CH




UNII-1 IEEE 802.11ac VHT80 mode- chain 0

Mid CH




Test Data (26dB BANDWIDTH)




UNII-2a IEEE 802.11n HT20 mode- chain 0


Low CH



Mid CH



High CH






Report No.: T200205D04-RP4


Page: 27 / 244

Rev.: 01




Report No.: T200205D04-RP4

Test Data (26dB BANDWIDTH)




UNII-2c IEEE 802.11n HT20 mode- chain 0


Low CH



Mid CH




High CH




UNII-2c IEEE 802.11n HT40 mode- chain 0


Low CH



Mid CH




High CH






Report No.: T200205D04-RP4

Page: 31 / 244
Rev.: 01



Report No.: T200205D04-RP4

Test Data (6dB BANDWIDTH)






Report No.: T200205D04-RP4

Page: 33 / 244


Rev.: 01

UNII-3 IEEE 802.11n HT20 mode- chain 0


Low CH




Mid CH



High CH




Report No.: T200205D04-RP4




Report No.: T200205D04-RP4

Test Data (26dB BANDWIDTH)




UNII-1 IEEE 802.11n HT20 mode- chain 1


Low CH




Mid CH




High CH






Report No.: T200205D04-RP4

Test Data (26dB BANDWIDTH)




UNII-2a IEEE 802.11n HT20 mode- chain 1


Low CH



Mid CH




High CH




UNII-2a IEEE 802.11n HT40 mode- chain 1

Low CH




High CH




UNII-2a IEEE 802.11ac VHT80 mode- chain 1

Mid CH




Report No.: T200205D04-RP4

Test Data (26dB BANDWIDTH)




UNII-2c IEEE 802.11n HT20 mode- chain 1


Low CH



Mid CH




High CH




UNII-2c IEEE 802.11n HT40 mode- chain 1


Low CH



Mid CH



High CH






Report No.: T200205D04-RP4


Page: 44 / 244

Rev.: 01




Report No.: T200205D04-RP4

Test Data (6dB BANDWIDTH)




UNII-3 IEEE 802.11n HT20 mode- chain 1


Low CH




Mid CH




High CH







Report No.: T200205D04-RP4


Test Data (BANDWIDTH 99%)









Test Data (BANDWIDTH 99%)










Report No.: T200205D04-RP4

Test Data (BANDWIDTH 99%)









Report No.: T200205D04-RP4

Page: 57 / 244
Rev.: 01

