

Test Report of FCC Part 15 C for FCC Certificate

On Behalf of

Astera LED-Technology GmbH

Product description: Radio remote control

Model No.: RC2

FCC ID: X55-RC2

Prepared for: Astera LED-Technology GmbH

Goetzeroth 6, Kleinich, 54483, Germany

Prepared by: Bontek Compliance Testing Laboratory Ltd

1/F, Block East H-3, OCT Eastern Ind. Zone, Qiaocheng East Road, Nanshan, Shenzhen, China

Tel: 86-755-86337020

Fax: 86-755-86337028


Report No.: BCT09KR-1120E

Issue Date: February 10, 2010

Test Date: November 25, 2009 ~ February 10, 2010

Test by:

Reviewed By:


Kendy Wang





Tony Wu

TABLE OF CONTENTS

1. GENERAL INFORMATION.....	3
1.1 Product Description for Equipment Under Test (EUT)	3
1.2 Related Submittal(s) / Grant (s)	3
1.3 Test Methodology	3
1.4 Test Facility	4
2. SYSTEM TEST CONFIGURATION	5
2.1 EUT Configuration	5
2.2 EUT Exercise	5
2.3 General Test Procedures.....	5
2.4 List of Measuring Equipments.....	6
3. SUMMARY OF TEST RESULTS	8
4. TEST OF CONDUCTED EMISSION	9
4.1 Applicable Standard.....	9
4.2 Test Setup Diagram	9
5. BAND EDGES MEASUREMENT.....	10
5.1 Limit of Band Edges Measurement.....	10
5.2 EUT Setup	10
5.3 Test Procedure	11
5.4 Test Result.....	11
6.SPURIOUS EMISSIONS.....	13
6.1 Limit of Spurious Emissions.....	13
6.2 EUT Setup	14
6.3 Test Procedure	15
6.4 Spurious Emissions Test Result	15
7. ANTENNA REQUIREMENT.....	20
7.1 Standard Applicable.....	20
7.2 Antenna Connected Construction	20

1. GENERAL INFORMATION

1.1 Product Description for Equipment Under Test (EUT)

Applicant:	Astera LED-Technology GmbH
Address of applicant:	Goetzeroth 6, Kleinich, 54483, Germany
Manufacturer:	Astera LED-Technology GmbH
Address of manufacturer:	Goetzeroth 6, Kleinich, 54483, Germany
EUT Description:	Radio remote control
Model No.:	RC2
Rated Voltage	DC 3V from battery
Frequency range	920MHz
Number of channels	1
Channel Separation	None
Product Class:	Low Power Communication Device Transmitter
Measurement Procedure	ANSI C63.4-2009

Remark: * The test data gathered are from the production sample provided by the manufacturer.

1.2 Related Submittal(s) / Grant (s)

This submittal(s) is a test report based on the Electromagnetic Interference (EMI) tests performed on the EUT. The EMI measurements were performed according to the measurement procedure described in ANSI C63.4 - 2009.

The tests were performed in order to determine compliance with Section 15.107 and 15.109 under the FCC Rules Part 15 Subpart B and Section 15.207, 15.209, 15.249 under the FCC Rules Part 15 Subpart C.

1.3 Test Methodology

Both conducted and radiated testing were performed according to the procedures in ANSI C63.4 - 2009, American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the range of 9 kHz to 40 GHz. Radiated testing was performed at an antenna to EUT distance 3 meters.

1.4 Test Facility

All measurement required was performed at laboratory of Bontek Compliance Testing Laboratory Ltd at 1/F, Block East H-3, OCT Eastern Ind. Zone, Qiaocheng East Road, Nanshan, Shenzhen, China.

The test facility is recognized, certified, or accredited by the following organizations:

FCC – Registration No.: 338263

Bontek Compliance Testing Laboratory Ltd. EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration 338263, March, 2008.

IC Registration No.: 7631A

The 3m alternate test site of Bontek Compliance Testing Laboratory Ltd. EMC Laboratory has been registered by Certification and Engineer Bureau of Industry Canada for the performance of with Registration NO.: 7631A on August 2009.

The facility also complies with the radiated and AC line conducted test site criteria set forth in ANSI C63.4-2009.

CNAS - Registration No.: L3923

Bontek Compliance Testing Laboratory Ltd. to ISO/IEC 17025:25 General Requirements for the Competence of Testing and Calibration Laboratories(CNAS-CL01 Accreditation Criteria for the Competence of Testing and Calibration Laboratories) for the competence in the field of testing. The acceptance letter from the CNAS is maintained in our files: Registration:L3923,February,2009.

TUV - Registration No.: UA 50145371-0001

Bontek Compliance Testing Laboratory Ltd. An assessment of the laboratory was conducted according to the"Procedures and Conditions for EMC Test Laboratories"with reference to EN ISO/IEC 17025 by a TUV Rheinland auditor. Audit Report NO. 17010783-001

2. SYSTEM TEST CONFIGURATION

The tests documented in this report were performed in accordance with ANSI C63.4-2009 and FCC CFR 47 Part 15 Subpart C.

2.1 EUT Configuration

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner that intends to maximize its emission characteristics in a continuous normal application.

2.2 EUT Exercise

The calibrated antennas used to sample the radiated field strength are mounted on a non-conductive, motorized antenna mast 3 or 10 meters from the leading edge of the turntable.

2.3 General Test Procedures

Conducted Emissions The EUT is placed on the turntable, which is 0.8 m above ground plane. According to the requirements in Section 7.1 of ANSI C63.4-2009. Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30MHz using CISPR Quasi-Peak detector mode. But the EUT is powered by DC 3V of battery, this test is not applicable.

Radiated Emissions The EUT is placed on a turntable, which is 0.8 m above ground plane. The turntable shall rotate 360 degrees to determine the position of maximum emission level. EUT is set 3m away from the receiving antenna, which varied from 1m to 4m to find out the highest emission. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical. In order to find out the maximum emissions, exploratory radiated emission measurements were made according to the requirements in Section 13.1.4.1 of ANSI C63.4-2009.

2.4 List of Measuring Equipments

No.	Instrument no.	Equipment	Manufacturer	Model No.	S/N	Calculator date	Calculator due date
1	BCT-EMC001	EMI Test Receiver	R&S	ESCI	100687	2009-4-14	2010-4-13
2	BCT-EMC002	EMI Test Receiver	R&S	ESPI	100097	2009-4-14	2010-4-13
3	BCT-EMC003	Amplifier	HP	8447D	1937A02492	2009-4-14	2010-4-13
4	BCT-EMC004	Single Power Conductor Module	FCC	FCC-LISN-5-50-1-01-CISPR25	07101	2009-4-14	2010-4-13
5	BCT-EMC005	Single Power Conductor Module	FCC	FCC-LISN-5-50-1-01-CISPR25	07102	2009-4-14	2010-4-13
6	BCT-EMC006	Power Clamp	SCHWARZBECK	MDS-21	3812	2009-4-14	2010-4-13
7	BCT-EMC007	Positioning Controller	C&C	CC-C-1F	MF7802113	N/A	N/A
8	BCT-EMC008	Electrostatic Discharge Simulator	TESEQ	NSG437	125	2009-4-14	2010-4-13
9	BCT-EMC009	Fast Transient Burst Generator	SCHAFFNER	MODULA6150	34572	2009-4-14	2010-4-13
10	BCT-EMC010	Fast Transient Noise Simulator	Noiseken	FNS-105AX	31485	2009-4-14	2010-4-13
11	BCT-EMC011	Color TV Pattern Generator	PHILIPS	PM5418	TM209947	N/A	N/A
12	BCT-EMC012	Power Frequency Magnetic Field Generator	EVERFINE	EMS61000-8K	608002	2009-4-14	2010-4-13
13	BCT-EMC013	N/A	N/A	N/A	N/A	N/A	N/A
14	BCT-EMC014	Capacitive Coupling Clamp	TESEQ	CDN8014	25096	2009-4-14	2010-4-13
15	BCT-EMC015	High Field Biconical Antenna	ELECTRO-METRICS	EM-6913	166	2009-4-14	2010-4-13

16	BCT-EMC016	Log Periodic Antenna	ELECTRO-METRICS	EM-6950	811	2009-4-14	2010-4-13
17	BCT-EMC017	Remote Active Vertical Antenna	ELECTRO-METRICS	EM-6892	304	2009-4-14	2010-4-13
18	BCT-EMC018	TRILOG Broadband Test-Antenna	SCHWARZBECK	VULB9163	9163-324	2009-4-14	2010-4-13
19	BCT-EMC019	Horn Antenna	SCHWARZBECK	BBHA9120A	B08000991-0001	2009-4-14	2010-4-13
20	BCT-EMC020	Teo Line Single Phase Module	SCHWARZBECK	NSLK8128	D-69250	2009-4-14	2010-4-13
21	BCT-EMC021	10dB attenuator	SCHWARZBECK	MTAIMP-136	R65.90.0001#06	2009-4-14	2010-4-13
22	BCT-EMC022	Electric bridge	Zentech	100 LCR METER	803024	N/A	N/A
23	BCT-EMC023	RF Current Probe	FCC	F-33-4	80	2009-4-14	2010-4-13
24	BCT-EMC024	SIGNAL GENERATOR	HP	8647A	3349A02296	2009-4-14	2010-4-13
25	BCT-EMC025	MICROWAVE AMPLIFIER	HP	8349B	2627A00994	2009-4-14	2010-4-13
26	BCT-EMC026	Triple-Loop Antenna	EVERFINE	LLA-2	607004	2009-4-14	2010-4-13
27	BCT-EMC027	CDN	FRANKONIA	M2+M3	A3027019	2009-10-20	2010-10-19
28	BCT-EMC028	6dB Attenuator	FRANKONIA	75-A-FFN-06	1001698	2009-10-20	2010-10-19
29	BCT-EMC029	EMV-Mess-Systeme GMBH	FRANKONIA	FLL-75	1020A1109	2009-10-20	2010-10-19
30	BCT-EMC030	EM Injection Clamp	FCC	F-203I-13mm	091536	2009-10-20	2010-10-19
31	BCT-EMC031	9KHz-2.4GHz Signal generator	MARCONI INSTRUMENTS	2024	112260/042	2009-10-20	2010-10-19

3. SUMMARY OF TEST RESULTS

EUT Fundamental Frequency	FCC Rules	Description of Test	Result
920MHz	15.207	Disturbance Voltage at The Mains Terminals	N/A NO AC power supply
	15.249	Band Edges Measurement	Pass
	15.249	Spurious Emission	Pass
	15.203	Antenna Requirement	Pass


4. TEST OF CONDUCTED EMISSION

4.1 Applicable Standard

Section 15.207: For a Low-power Radio-frequency Device is designed to be connected to the AC power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed below limits table.

Frequency Range (MHz)	Limits (dBuV)	
	Quasi-Peak	Average
0.150~0.500	66~56	56~46
0.500~5.000	56	46
5.000~30.00	60	50

4.2 Test Setup Diagram



Note: The EUT is powered by DC 3V of battery, this test is not applicable.

5. BAND EDGES MEASUREMENT

5.1 Limit of Band Edges Measurement

1. In the above emission table, the tighter limit applies at the band edges.
2. As shown in Section 15.35(b), for frequencies above 1000 MHz, the above field strength limits in paragraphs (a) and (b) of this section are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For point-to-point operation under paragraph (b) of this section, the peak field strength shall not exceed 2500 millivolts/meter at 3 meters along the antenna azimuth.

Frequency (MHz)	Field Strength ($\mu\text{V/m}$ at 3-meter)	Field Strength ($\text{dB}\mu\text{V/m}$ at 3-meter)
30-88	100	40
88-216	150	43.5
216-960	200	46
Above 960	500	54

Note: (1) The tighter limit shall apply at the edge between two frequency bands.

- (2) The emission limits shown in the above table are based on measurement employing a CISPR quasi-peak detector and above 1000MHz are based on measurements employing an average detector.

5.2 EUT Setup




Figure 2 : Frequencies measured above 1 GHz configuration

5.3 Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

- 1). Configure the EUT according to ANSI C63.4:2009.
- 2). The EUT was placed on the top of the turntable 0.8 meter above ground.
- 3). The receiving antenna was placed 3 meters far away from the turntable.
- 4). The turntable was rotated by 360 degrees to determine the position of the highest radiation.
- 5). The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emission field strength of both horizontal and vertical polarization. For each suspected emission, the antenna tower was scanned (from 1 M to 4 M) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.

5.4 Test Result

Temperature (°C) : 22~23	EUT: Radio remote control
Humidity (%RH) : 50~54	M/N: RC2
Barometric Pressure (mbar) : 950~1000	Operation Condition: Continuous Transmitting




*RBW 1 MHz Marker 1 [T1]
VBW 3 MHz 78.51 dBμV
SWT 2.5 ms 920.096000000 MHz

Ref 117 dBμV

*Att 30 dB

1 PK
VIEW



6.SPURIOUS EMISSIONS

6.1 Limit of Spurious Emissions

1. In the section 15.249(a): Except as provided in paragraph (b) of this section, the field strength of emissions from intentional radiators operated within these frequency bands shall comply with the following:
2. Except as provided elsewhere in this Subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Fundamental Frequency (MHz)	Field Strength of Fundamental Field Strength (mV/m)	Field Strength of Harmonics (µV/m)
902-928 MHz	50	500
2400 - 2483.5 MHz	50	500
5725 - 5875 MHz	50	500
24.0 - 24.25 GHz	250	2500

Frequency (MHz)	Field Strength (µV/m)	Measurement Distance (m)
30-88	100*	3
88-216	150*	3
216-960	200*	3
Above 960	500	3

Remark: Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this Section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this Part, e.g., Sections 15.231 and 15.241.

3. In the above emission table, the tighter limit applies at the band edges.

Frequency (MHz)	Field Strength (µV/m at 3-meter)	Field Strength (dBµV/m at 3-meter)
30-88	100	40
88-216	150	43.5
216-960	200	46
Above 960	500	54

6.2 EUT Setup




Figure 1 : Frequencies measured below 1 GHz configuration




Figure 2 : Frequencies measured above 1 GHz configuration

6.3 Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

- 1). Configure the EUT according to ANSI C63.4:2009.
- 2). The EUT was placed on the top of the turntable 0.8 meter above ground.
- 3). The receiving antenna was placed 3 meters far away from the turntable.
- 4). The turntable was rotated by 360 degrees to determine the position of the highest radiation.
- 5). The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emission field strength of both horizontal and vertical polarization. For each suspected emission, the antenna tower was scanned (from 1 M to 4 M) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.

6.4 Spurious Emissions Test Result


Temperature (°C) : 22~23	EUT: Radio remote control
Humidity (%RH) : 50~54	M/N: RC2
Barometric Pressure (mbar) : 950~1000	Operation Condition: continuous transmit

Spurious Emissions Below 1GHz:

EUT: Radio remote control M/N: RC2
Operating Condition: continuous transmit
Test Site: 3m CHAMBER
Operator: Chen
Test Specification: AC 120V/60Hz
Comment: Polarization: Horizontal
Tem:25°C Hum:50%

SWEEP TABLE: "test (30M-1G)"

Short Description:	Field Strength
Start Stop Detector Meas. IF Transducer	
Frequency Frequency	Time Bandw.
30.0 MHz 1.0 GHz	MaxPeak Coupled 100 kHz VULB9163 NEW



MEASUREMENT RESULT: "BCT09KP11202_red"

11/27/2009 10:00

Frequency MHz	Level dBμV/m	Transd dB	Limit dBμV/m	Margin dB	Det.	Height cm	Azimuth deg	Polarization
47.460000	26.70	15.8	40.0	13.3	QP	100.0	0.00	HORIZONTAL
59.100000	21.50	14.6	40.0	18.5	QP	100.0	0.00	HORIZONTAL
101.780000	24.60	17.4	43.5	18.9	QP	100.0	0.00	HORIZONTAL
289.960000	25.60	18.4	46.0	20.4	QP	100.0	0.00	HORIZONTAL
549.920000	31.90	25.2	46.0	14.1	QP	100.0	0.00	HORIZONTAL
920.060000	82.10	31.7	94.0	11.9	QP	100.0	0.00	HORIZONTAL


Note: The 920MHz is EUT transmit fundamental wave and it's limit is 50mV/m(94 dBμV/m).

Spurious Emissions Below 1GHz:

EUT: Radio remote control M/N: RC2
Operating Condition: continuous transmit
Test Site: 3m CHAMBER
Operator: Chen
Test Specification: AC 120V/60Hz
Comment: Polarization: Vertical
Tem:25°C Hum:50%

SWEEP TABLE: "test (30M-1G)"

Short Description:	Field Strength
Start Stop Detector Meas. IF Transducer	
Frequency Frequency Time Bandw.	
30.0 MHz 1.0 GHz MaxPeak Coupled 100 kHz VULB9163 NEW	



MEASUREMENT RESULT: "BCT09KP11201_red"


11/27/2009 09:55

Frequency MHz	Level dBμV/m	Transd dB	Limit dBμV/m	Margin dB	Det.	Height cm	Azimuth deg	Polarization
47.460000	25.90	15.8	40.0	14.1	QP	100.0	0.00	VERTICAL
55.220000	22.40	15.6	40.0	17.6	QP	100.0	0.00	VERTICAL
97.900000	24.20	17.4	43.5	19.3	QP	100.0	0.00	VERTICAL
284.140000	25.20	18.3	46.0	20.8	QP	100.0	0.00	VERTICAL
553.800000	31.20	25.3	46.0	14.8	QP	100.0	0.00	VERTICAL
920.060000	86.20	31.6	94.0	7.8	QP	100.0	0.00	VERTICAL

Note: The 920MHz is EUT transmit fundamental wave and it's limit is 50mV/m(94 dBμV/m).

Spurious Emissions above 1GHz

EUT: Radio remote control M/N: RC2
 Operating Condition: continuous transmit
 Test Site: 3m CHAMBER
 Operator: Chen
 Test Specification: AC 120V/60Hz
 Comment: Polarization: Horizontal
 Tem:25°C Hum:50%




MEASUREMENT RESULT

Frequency MHz	Level dBμV/m	Transd dB	Limit dBμV/m	Margin dB	Det.	Height cm	Azimuth deg	Polarization
1840.00000	32.10	14.3	44.0	11.9	AV	100.0	0.00	HORIZONTAL

Spurious Emissions above 1GHz

EUT:	Radio remote control	M/N: RC2
Operating Condition:	continuous transmit	
Test Site:	3m CHAMBER	
Operator:	Chen	
Test Specification:	AC 120V/60Hz	
Comment:	Polarization: Vertical	
	Tem:25°C Hum:50%	



MEASUREMENT RESULT

Frequency MHz	Level dB μ V/m	Transd dB	Limit dB μ V/m	Margin dB	Det.	Height cm	Azimuth deg	Polarization
1840.00000	35.90	14.3	44.0	8.1	AV	100.0	0.00	VERTICAL

7. ANTENNA REQUIREMENT

7.1 Standard Applicable

Section 15.203:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

7.2 Antenna Connected Construction

Please see to document "X55_Antenna Specification.pdf" ,The antenna connector is designed with permanent attachment and no consideration of replacement.