## FCC §15.247 (i) & §2.1091- MAXIMUM PERMISSIBLE EXPOSURE (MPE)

## **Applicable Standard**

According to subpart 15.247 (i) and subpart 2.1091 systems operating under the provisions of this section shall be operated in a manner that ensures the public is not exposed to RF energy level in excess of the communication guidelines.

Limits for General Population/Uncontrolled Exposure										
Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm <sup>2</sup> )	Averaging Time (Minutes)						
0.3-1.34	614	1.63	*(100)	30						
1.34-30	824/f	2.19/f	$*(180/f^2)$	30						
30-300	27.5	0.073	0.2	30						
300-1500	/	/	f/1500	30						
1500-100,000	/	/	1.0	30						

Limits for General Population/Uncontrolled Exposure

f = frequency in MHz

\* = Plane-wave equivalent power density

## Result

## **Calculated Formulary:**

Predication of MPE limit at a given distance

$$S = \frac{PG}{4\pi R^2}$$

S = power density (in appropriate units, e.g. mW/cm<sup>2</sup>)

P = power input to the antenna (in appropriate units, e.g., mW).

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor, is normally numeric gain.

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm)

For simultaneously transmit system, the calculated power density should comply with:

$$\sum_{i} \frac{S_i}{S_{Limit,i}} \leq 1$$

Shenzhen Accurate Technology Co., Ltd.

Mode	Frequency (MHz)	Antenna Gain		Tune up conducted power		Evaluation Distance	Power Density	MPE Limit
		(dBi)	(numeric)	(dBm)	(mW)	(cm)	$(mW/cm^2)$	$(\mathrm{mW/cm}^2)$
BT	2402-2480	7.35	5.43	7.0	5.01	20	0.005	1
BLE	2402-2480	7.35	5.43	4.5	2.82	20	0.003	1
Wi-Fi	2412-2462	7.35	5.43	21.0	125.89	20	0.136	1
UHF	917-922.2	2.0	1.58	9.5	8.91	20	0.003	0.611

Note: 1. The tune up conducted power and antenna gain was declared by the applicant.2. The BT/BLE/Wi-Fi can transmit at the same time with the UHF, and the BT, BLE and Wi-Fi can not transmitting simultaneously.

Simultaneous transmitting consideration (worst case):

The ratio=MPE <sub>Wi-Fi</sub>/limit+MPE<sub>UHF</sub>/limit=0.136/1+0.003/0.611=0.141<1.0

To maintain compliance with the FCC's RF exposure guidelines, place the equipment at least 20cm from nearby persons.

Result: Compliant.