

## RF EXPOSURE EVALUATION METHOD

## FCC ID: X5B-500137

## SAR Test Exclusion Thresholds for 100 MHz $\,$ - $\,$ 6 GHz and $\leq$ 50 mm

Approximate SAR Test Exclusion Power Thresholds at Selected Frequencies and Test Separation Distances are illustrated in the following Table.

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances  $\leq$  50 mm are determined by:

[(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)] •  $[\sqrt{f(GHz)}] \le 3.0$  for 1-g SAR and  $\le 7.5$  for 10-g extremity SAR,where f(GHz) is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum test separation distance is  $\leq 50$  mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

Maximum measured transmitter power.

ΒT

GFSK						
Test Channel	Frequency	Peak Output Power	Peak Output Power			
	(MHz)	(dBm)	(mW)			
CH00	2402	-0.846	0.823			
CH39	2441	-0.762	0.839			
CH78	2480	-1.874	0.650			
π /4-DQPSK						
Test Channel	Frequency	Peak Output Power	Peak Output Power			
	(MHz)	(dBm)	(mW)			
CH00	2402	-0.833	0.825			
CH39	2441	-0.743	0.843			
CH78	2480	-1.827	0.657			
8DPSK						
Test Channel	Frequency	Peak Output Power	Peak Output Power			
	(MHz)	(dBm)	(mW)			
CH00	2402	-0.847	0.823			
CH39	2441	-0.727	0.846			
CH78	2480	-1.893	0.647			

Remark: The best case gain of the antenna is 0dBi.

0 dBi logarithmic terms convert to numeric result is nearly 1.00

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances  $\leq$  50 mm are determined by:

[(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance,mm)] • [ $\checkmark$  f(GHz)]

ΒT

Test Channel	[(max. power of channel, mW)	(min. test separation distance,mm)]	[f(GHz)]	Result	Limit				
GFSK									
CH00	0.823	5	2.402	0.255	3				
CH39	0.839	5	2.441	0.262	3				
CH78	0.650	5	2.480	0.205	3				
	π /4-DQPSK								
CH00	0.825	5	2.402	0.256	3				
CH39	0.843	5	2.441	0.263	3				
CH78	0.657	5	2.480	0.207	3				
	8DPSK								
CH00	0.823	5	2.402	0.255	3				
CH39	0.846	5	2.441	0.264	3				
CH78	0.647	5	2.480	0.204	3				

The test Result is less than 3.0 for 1-g SAR and  $\leqslant$  7.5 for 10-g extremity SAR.

Conclusion: No SAR is required.