

# FCC Test Report

Product Name	Afterglow Nur PS4/PS3 Wireless Stand
Model No	PL-051-003T
FCC ID.	X5B-PL051003T

Applicant	Performance Designed Products, LLC
Address	14144 Ventura Blvd., Suite 200 Sherman Oaks, CA91423 USA

Date of Receipt	Aug. 25, 2014
Issue Date	Sep. 15, 2014
Report No.	1480541R-RFUSP25V00
Report Version	V1.0



The test results relate only to the samples tested.

The test results shown in the test report are traceable to the national/international standard through the calibration of the equipment and evaluated measurement uncertainty herein.

This report must not be used to claim product endorsement by TAF or any agency of the government.

The test report shall not be reproduced without the written approval of Quietek Corporation.

# Test Report

Issue Date: Sep. 15, 2014

Report No.: 1480541R-RFUSP25V00



Product Name	Afterglow Nur PS4/PS3 Wireless Stand
Applicant	Performance Designed Products, LLC
Address	14144 Ventura Blvd., Suite 200 Sherman Oaks, CA91423 USA
Manufacturer	Performance Designed Products, LLC
Model No.	PL-051-003T
EUT Rated Voltage	DC 5V (Power by USB)
EUT Test Voltage	AC 120V/60Hz
Trade Name	pdp, Afterglow
Applicable Standard	FCC CFR Title 47 Part 15 Subpart C: 2013 ANSI C63.10: 2009, KDB 558074
Test Result	Complied

Documented By : Rita Huang  
( Senior Adm. Specialist / Rita Huang )

Tested By : Benjamin Pan  
( Engineer / Benjamin Pan )

Approved By : Vincent Lin  
( Director / Vincent Lin )

# TABLE OF CONTENTS

Description	Page
<b>1. GENERAL INFORMATION .....</b>	<b>5</b>
1.1. EUT Description .....	5
1.2. Operational Description .....	7
1.3. Tested System Details .....	8
1.4. Configuration of Tested System .....	8
1.5. EUT Exercise Software .....	8
1.6. Test Facility .....	9
<b>2. Conducted Emission.....</b>	<b>10</b>
2.1. Test Equipment .....	10
2.2. Test Setup .....	10
2.3. Limits .....	11
2.4. Test Procedure .....	11
2.5. Uncertainty .....	11
2.6. Test Result of Conducted Emission.....	12
<b>3. Peak Power Output .....</b>	<b>14</b>
3.1. Test Equipment .....	14
3.2. Test Setup .....	14
3.3. Limit .....	14
3.4. Test Procedure .....	14
3.5. Test Result of Peak Power Output .....	15
<b>4. Radiated Emission.....</b>	<b>16</b>
4.1. Test Equipment .....	16
4.2. Test Setup .....	17
4.3. Limits .....	18
4.4. Test Procedure .....	18
4.5. Uncertainty .....	18
4.6. Test Result of Radiated Emission.....	19
<b>5. RF antenna conducted test.....</b>	<b>23</b>
5.1. Test Equipment .....	23
5.2. Test Setup .....	23
5.3. Limits .....	23
5.4. Test Procedure .....	24
5.5. Uncertainty .....	24
5.6. Test Result of RF antenna conducted test.....	25
<b>6. Band Edge .....</b>	<b>28</b>
6.1. Test Equipment .....	28
6.2. Test Setup .....	28
6.3. Limits .....	29
6.4. Test Procedure .....	29
6.5. Uncertainty .....	29
6.6. Test Result of Band Edge .....	30
<b>7. Occupied Bandwidth.....</b>	<b>34</b>

---

7.1.	Test Equipment.....	34
7.2.	Test Setup .....	34
7.3.	Limits .....	34
7.4.	Test Procedure .....	34
7.5.	Uncertainty .....	34
7.6.	Test Result of Occupied Bandwidth .....	35
<b>8.</b>	<b>Power Density .....</b>	<b>38</b>
8.1.	Test Equipment.....	38
8.2.	Test Setup .....	38
8.3.	Limits .....	38
8.4.	Test Procedure .....	38
8.5.	Uncertainty .....	38
8.6.	Test Result of Power Density .....	39
<b>9.</b>	<b>EMI Reduction Method During Compliance Testing .....</b>	<b>42</b>
Attachment 1:	EUT Test Photographs	
Attachment 2:	EUT Detailed Photographs	

## 1. GENERAL INFORMATION

### 1.1. EUT Description

Product Name	Afterglow Nur PS4/PS3 Wireless Stand
Trade Name	pdp, Afterglow
Model No.	PL-051-003T
FCC ID.	X5B-PL051003T
Frequency Range	2403.35 – 2479.35MHz
Channel Control	Auto
Channel Separation	2MHz
Antenna Gain	Refer to the table “Antenna List”
Channel Number	39
Type of Modulation	Pi/4 DQPSK
Antenna Type	Printed on PCB
USB Cable	Shielded, 1.8m
Audio Cable	Shielded, 1.2m
Optical Fiber Cable	Shielded, 1.7m

#### Antenna List

No.	Manufacturer	Part No.	Peak Gain
1	TATUNG	N/A (TX0) N/A (TX1)	6.05 dBi for 2.4 GHz

Note: The antenna of EUT is conform to FCC 15.203

## Center Frequency of Each Channel:

Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
Channel 1:	2403.35 MHz	Channel 11:	2423.35 MHz	Channel 21:	2443.35 MHz	Channel 31:	2463.35 MHz
Channel 2:	2405.35 MHz	Channel 12:	2425.35 MHz	Channel 22:	2445.35 MHz	Channel 32:	2465.35 MHz
Channel 3:	2407.35 MHz	Channel 13:	2427.35 MHz	Channel 23:	2447.35 MHz	Channel 33:	2467.35 MHz
Channel 4:	2409.35 MHz	Channel 14:	2429.35 MHz	Channel 24:	2449.35 MHz	Channel 34:	2469.35 MHz
Channel 5:	2411.35 MHz	Channel 15:	2431.35 MHz	Channel 25:	2451.35 MHz	Channel 35:	2471.35 MHz
Channel 6:	2413.35 MHz	Channel 16:	2433.35 MHz	Channel 26:	2453.35 MHz	Channel 36:	2473.35 MHz
Channel 7:	2415.35 MHz	Channel 17:	2435.35 MHz	Channel 27:	2455.35 MHz	Channel 37:	2475.35 MHz
Channel 8:	2417.35 MHz	Channel 18:	2437.35 MHz	Channel 28:	2457.35 MHz	Channel 38:	2477.35 MHz
Channel 9:	2419.35 MHz	Channel 19:	2439.35 MHz	Channel 29:	2459.35 MHz	Channel 39:	2479.35 MHz
Channel 10:	2421.35 MHz	Channel 20:	2441.35 MHz	Channel 30:	2461.35 MHz		

## Note:

1. The EUT is an Afterglow Nur PS4/PS3 Wireless Stand with a built-in 2.4GHz transceiver.
2. Regarding to the operation frequency, the lowest, middle and highest frequency are selected to perform the test.
3. Device contains a diversity function, only worst case is shown in the report.
4. These tests are conducted on a sample for the purpose of demonstrating compliance of 2.4GHz transmitter with Part 15 Subpart C Paragraph 15.247 of spread spectrum devices

Test Mode:	Mode 1: Transmit
------------	------------------


### 1.3. Tested System Details

The types for all equipment, plus descriptions of all cables used in the tested system (including inserted cards) are:

	Product	Manufacturer	Model No.	Serial No.	Power Cord
1	Notebook PC	DELL	PP18L	36119001664	Non-Shielded, 0.8m
2	Cambridge SoundWorks	Creative	S80130	AM01303200000941	Non-Shielded, 1.9m

Signal Cable Type	Signal cable Description
A	USB Cable Shielded, 2.0m, with two ferrite cores bonded.
B	Audio Cable Shielded, 1.2m
C	Optical Fiber Cable Shielded, 1.8m

### 1.4. Configuration of Tested System



### 1.5. EUT Exercise Software

- (1) Setup the EUT as shown in Section 1.4.
- (2) Execute “VMI dedbug.exe (v1.1.6.47)” on the Notebook PC.
- (3) Configure the test mode, the test channel, and the data rate.
- (4) Press “OK” to start the continuous Transmit.
- (5) Verify that the EUT works properly.

## 1.6. Test Facility

Ambient conditions in the laboratory:

Items	Required (IEC 68-1)	Actual
Temperature (°C)	15-35	20-35
Humidity (%RH)	25-75	50-65
Barometric pressure (mbar)	860-1060	950-1000

The related certificate for our laboratories about the test site and management system can be downloaded from

Quietek Corporation's Web Site: <http://www.quietek.com/tw/ctg/cts/accreditations.htm>

The address and introduction of Quietek Corporation's laboratories can be founded in our Web site:

<http://www.quietek.com/>

Site Description: File on  
Federal Communications Commission  
FCC Engineering Laboratory  
7435 Oakland Mills Road  
Columbia, MD 21046  
Registration Number: 92195

Site Name: Quietek Corporation  
Site Address: No.5-22, Ruishukeng,  
Linkou Dist. New Taipei City 24451,  
Taiwan, R.O.C.  
TEL: 886-2-8601-3788 / FAX : 886-2-8601-3789  
E-Mail : [service@quietek.com](mailto:service@quietek.com)

FCC Accreditation Number: TW1014



## 2. Conducted Emission


### 2.1. Test Equipment

The following test equipment are used during the conducted emission test:

Item	Instrument	Manufacturer	Type No./Serial No	Last Cal.	Remark
1	Test Receiver	R & S	ESCS 30/825442/17	May, 2014	
2	L.I.S.N.	R & S	ESH3-Z5/825016/6	May, 2014	EUT
3	L.I.S.N.	Kyoritsu	KNW-407/8-1420-3	May, 2014	Peripherals
4	Pulse Limiter	R & S	ESH3-Z2	May, 2014	
5	No.1 Shielded Room			N/A	

Note: All instruments are calibrated every one year.

### 2.2. Test Setup



**2.3. Limits**

<b>FCC Part 15 Subpart C Paragraph 15.207 (dBuV) Limit</b>		
Frequency MHz	Limits	
	QP	AVG
0.15 - 0.50	66-56	56-46
0.50-5.0	56	46
5.0 - 30	60	50

**2.4. Test Procedure**

The EUT and simulators are connected to the main power through a line impedance stabilization network (L.I.S.N.). This provides a 50 ohm /50uH coupling impedance for the measuring equipment. The peripheral devices are also connected to the main power through a LISN that provides a 50ohm /50uH coupling impedance with 50ohm termination. (Please refers to the block diagram of the test setup and photographs.)

Both sides of A.C. line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10: 2009 on conducted measurement.

Conducted emissions were invested over the frequency range from 0.15MHz to 30MHz using a receiver bandwidth of 9kHz.

**2.5. Uncertainty**

± 2.26 dB

## 2.6. Test Result of Conducted Emission

Product : Afterglow Nur PS4/PS3 Wireless Stand  
 Test Item : Conducted Emission Test  
 Power Line : Line 1  
 Test Mode : Mode 1: Transmit (2441.35MHz)

Frequency MHz	Correct Factor dB	Reading Level dBuV	Measurement Level dBuV	Margin dB	Limit dBuV
<b>Line 1</b>					
<b>Quasi-Peak</b>					
0.162	9.657	42.950	52.607	-13.050	65.657
0.189	9.650	40.080	49.730	-15.156	64.886
0.298	9.656	34.730	44.386	-17.385	61.771
0.384	9.660	25.860	35.520	-23.794	59.314
0.666	9.676	23.730	33.406	-22.594	56.000
4.384	9.839	21.980	31.819	-24.181	56.000
<b>Average</b>					
0.162	9.657	24.930	34.587	-21.070	55.657
0.189	9.650	19.510	29.160	-25.726	54.886
0.298	9.656	23.650	33.306	-18.465	51.771
0.384	9.660	7.680	17.340	-31.974	49.314
0.666	9.676	11.460	21.136	-24.864	46.000
4.384	9.839	15.950	25.789	-20.211	46.000

Note:

1. All Reading Levels are Quasi-Peak and average value.
2. "■" means the worst emission level.
3. Measurement Level = Reading Level + Correct Factor

Product : Afterglow Nur PS4/PS3 Wireless Stand  
 Test Item : Conducted Emission Test  
 Power Line : Line 2  
 Test Mode : Mode 1: Transmit (2441.35MHz)

Frequency MHz	Correct Factor dB	Reading Level dBuV	Measurement Level dBuV	Margin dB	Limit dBuV
<b>Line 2</b>					
<b>Quasi-Peak</b>					
0.158	9.658	42.730	52.388	-13.383	65.771
0.189	9.660	40.140	49.800	-15.086	64.886
0.298	9.659	35.120	44.779	-16.992	61.771
0.666	9.676	22.540	32.216	-23.784	56.000
3.884	9.828	23.690	33.518	-22.482	56.000
20.404	10.213	24.770	34.983	-25.017	60.000
<b>Average</b>					
0.158	9.658	26.120	35.778	-19.993	55.771
0.189	9.660	19.430	29.090	-25.796	54.886
0.298	9.659	24.140	33.799	-17.972	51.771
0.666	9.676	10.710	20.386	-25.614	46.000
3.884	9.828	16.970	26.798	-19.202	46.000
20.404	10.213	17.310	27.523	-22.477	50.000

Note:

1. All Reading Levels are Quasi-Peak and average value.
2. "■" means the worst emission level.
3. Measurement Level = Reading Level + Correct Factor


### 3. Peak Power Output

#### 3.1. Test Equipment

	Equipment	Manufacturer	Model No./Serial No.	Last Cal.
X	Power Meter	Anritsu	ML2495A/6K00003357	May, 2014
X	Power Sensor	Anritsu	MA2411B/0738448	Jun, 2014

Note: 1. All equipments are calibrated every one year.  
 2. The test instruments marked by “X” are used to measure the final test results.

#### 3.2. Test Setup



#### 3.3. Limit

The maximum peak power shall be less 1Watt.

#### 3.4. Test Procedure

The EUT was tested according to DTS test procedure of KDB 558074 for compliance to FCC 47CFR 15.247 requirements. The maximum peak conducted output power using KDB 558074 section 9.1.3 PKPM1 Peak power meter method.

### 3.5. Test Result of Peak Power Output

Product : Afterglow Nur PS4/PS3 Wireless Stand  
 Test Item : Peak Power Output Data  
 Test Site : No.3 OATS  
 Test Mode : Mode 1: Transmit

#### Signal Path A

Channel No.	Frequency (MHz)	Measurement Level (dBm)	Required Limit (dBm)	Result
01	2403.35	3.42	<29.5dBm	Pass
20	2441.35	2.60	<29.5dBm	Pass
39	2479.35	0.57	<29.5dBm	Pass

#### Signal Path B

Channel No.	Frequency (MHz)	Measurement Level (dBm)	Required Limit (dBm)	Result
01	2403.35	3.93	<29.5dBm	Pass
20	2441.35	3.31	<29.5dBm	Pass
39	2479.35	1.24	<29.5dBm	Pass

## 4. Radiated Emission

### 4.1. Test Equipment


The following test equipment are used during the radiated emission test:

Test Site		Equipment	Manufacturer	Model No./Serial No.	Last Cal.
☒ Site # 3	X	Loop Antenna	Teseq	HLA6120 / 26739	Jul., 2014
	X	Bilog Antenna	Schaffner Chase	CBL6112B/2673	Sep., 2014
	X	Horn Antenna	Schwarzbeck	BBHA9120D/D305	Sep., 2014
	X	Horn Antenna	Schwarzbeck	BBHA9170/208	Jul., 2014
	X	Pre-Amplifier	QTK	QTK-AMP-03 / 0003	May, 2014
	X	Pre-Amplifier	QTK	AP-180C / CHM_0906076	Sep., 2014
	X	Pre-Amplifier	MITEQ	AMF-4D-180400-45-6P/ 925975	Mar, 2014
	X	Spectrum Analyzer	Agilent	E4407B / US39440758	May, 2014
	X	Test Receiver	R & S	ESCS 30/ 825442/018	Sep., 2014
	X	Coaxial Cable	QuieTek	QTK-CABLE/ CAB5	Feb., 2014
	X	Controller	QuieTek	QTK-CONTROLLER/ CTRL3	N/A
	X	Coaxial Switch	Anritsu	MP59B/6200265729	N/A


- Note:
1. All equipments are calibrated with traceable calibrations. Each calibration is traceable to the national or international standards.
  2. The test instruments marked with “X” are used to measure the final test results.

## 4.2. Test Setup

### Radiated Emission Below 1GHz



### Radiated Emission Above 1GHz





### 4.3. Limits

Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 20dB below the level of the fundamental or to the general radiated emission limits in paragraph 15.209, whichever is the lesser attenuation.

FCC Part 15 Subpart C Paragraph 15.209(a) Limits		
Frequency MHz	Field strength (microvolts/meter)	Measurement distance (meter)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

Remarks: E field strength (dBuV/m) = 20 log E field strength (uV/m)

### 4.4. Test Procedure

The EUT was setup according to ANSI C63.10, 2009 and tested according to DTS test procedure of KDB558074 for compliance to FCC 47CFR 15.247 requirements.

The EUT is placed on a turn table which is 0.8 meter above ground. The turn table is rotated 360 degrees to determine the position of the maximum emission level. The EUT was positioned such that the distance from antenna to the EUT was 3 meters.

The antenna is scanned between 1 meter and 4 meters to find out the maximum emission level.

This is repeated for both horizontal and vertical polarization of the antenna. In order to find the maximum emission, all of the interface cables were manipulated according to ANSI C63.10:2009 on radiated measurement.

The resolution bandwidth below 30MHz setting on the field strength meter is 9kHz and 30MHz~1GHz is 120kHz and above 1GHz is 1MHz.

Radiated emission measurements below 30MHz are made using Loop Antenna and 30MHz~1GHz are made using broadband Bilog antenna and above 1GHz are made using Horn Antennas.

The measurement is divided into the Preliminary Measurement and the Final Measurement.

The suspected frequencies are searched for in Preliminary Measurement with the measurement antenna kept pointed at the source of the emission both in azimuth and elevation, with the polarization of the antenna oriented for maximum response. The antenna is pointed at an angle towards the source of the emission, and the EUT is rotated in both height and polarization to maximize the measured emission. The emission is kept within the illumination area of the 3 dB bandwidth of the antenna.

The worst radiated emission is measured in the Open Area Test Site on the Final Measurement.

The measurement frequency range from 9KHz - 10th Harmonic of fundamental was investigated.

### 4.5. Uncertainty

± 3.9 dB above 1GHz

± 3.8 dB below 1GHz

#### 4.6. Test Result of Radiated Emission

Product : Afterglow Nur PS4/PS3 Wireless Stand  
 Test Item : Harmonic Radiated Emission Data  
 Test Site : No.3 OATS  
 Test Mode : Mode 1: Transmit (2403.35MHz)

Frequency MHz	Correct Factor dB	Reading Level dBuV	Measurement Level dBuV/m	Margin dB	Limit dBuV/m
<b>Horizontal</b>					
<b>Peak Detector:</b>					
4806.700	2.534	41.690	44.224	-29.776	74.000
7210.050	9.466	40.534	50.000	-24.000	74.000
9613.400	10.343	43.929	54.273	-19.727	74.000
<b>Average</b>					
<b>Detector:</b>					
9613.400	10.343	34.219	44.563	-9.437	54.000
<b>Vertical</b>					
<b>Peak Detector:</b>					
4806.700	2.934	42.524	45.458	-28.542	74.000
7210.050	9.946	42.460	52.407	-21.593	74.000
9613.400	10.808	43.855	54.663	-19.337	74.000
<b>Average</b>					
<b>Detector:</b>					
9613.400	10.808	33.377	44.185	-9.815	54.000

Note:

1. All Readings below 1GHz are Quasi-Peak, above 1GHz are performed with peak and/or average measurements as necessary.
2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.
4. Measurement Level = Reading Level + Correct Factor.
5. Correct Factor = Antenna factor + Cable loss – Amplifier gain.
6. The average measurement was not performed when the peak measured data under the limit of average detection.
7. The emission levels of other frequencies are very lower than the limit and not show in test report.

Product : Afterglow Nur PS4/PS3 Wireless Stand  
 Test Item : Harmonic Radiated Emission Data  
 Test Site : No.3 OATS  
 Test Mode : Mode 1: Transmit (2441.35MHz)

Frequency MHz	Correct Factor dB	Reading Level dBuV	Measurement Level dBuV/m	Margin dB	Limit dBuV/m
<b>Horizontal</b>					
<b>Peak Detector:</b>					
4882.700	2.021	43.402	45.423	-28.577	74.000
7324.050	9.783	42.125	51.908	-22.092	74.000
9765.400	9.687	43.617	53.304	-20.696	74.000
<b>Average</b>					
<b>Detector:</b>					
<b>Vertical</b>					
<b>Peak Detector:</b>					
4882.700	2.484	44.695	47.179	-26.821	74.000
7324.050	10.399	45.822	56.221	-17.779	74.000
9765.400	10.320	43.170	53.490	-20.510	74.000
<b>Average</b>					
<b>Detector:</b>					
7324.050	10.399	38.496	48.895	-5.105	54.000

Note:

1. All Readings below 1GHz are Quasi-Peak, above 1GHz are performed with peak and/or average measurements as necessary.
2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.
4. Measurement Level = Reading Level + Correct Factor.
5. Correct Factor = Antenna factor + Cable loss – Amplifier gain.
6. The average measurement was not performed when the peak measured data under the limit of average detection.
7. The emission levels of other frequencies are very lower than the limit and not show in test report.

Product : Afterglow Nur PS4/PS3 Wireless Stand  
 Test Item : Harmonic Radiated Emission Data  
 Test Site : No.3 OATS  
 Test Mode : Mode 1: Transmit (2479.35MHz)

Frequency MHz	Correct Factor dB	Reading Level dBuV	Measurement Level dBuV/m	Margin dB	Limit dBuV/m
<b>Horizontal</b>					
<b>Peak Detector:</b>					
4958.700	2.569	41.332	43.901	-30.099	74.000
7438.050	10.548	42.932	53.480	-20.520	74.000
9917.400	10.202	37.335	47.537	-26.463	74.000
<b>Average</b>					
<b>Detector:</b>					
--					
<b>Vertical</b>					
<b>Peak Detector:</b>					
4958.700	3.378	43.068	46.447	-27.553	74.000
7438.050	11.216	47.128	58.344	-15.656	74.000
9917.400	11.244	37.275	48.519	-25.481	74.000
<b>Average</b>					
<b>Detector:</b>					
7438.050	11.216	40.194	51.410	-2.590	54.000

Note:

1. All Readings below 1GHz are Quasi-Peak, above 1GHz are performed with peak and/or average measurements as necessary.
2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.
4. Measurement Level = Reading Level + Correct Factor.
5. Correct Factor = Antenna factor + Cable loss – Amplifier gain.
6. The average measurement was not performed when the peak measured data under the limit of average detection.
7. The emission levels of other frequencies are very lower than the limit and not show in test report.

Product : Afterglow Nur PS4/PS3 Wireless Stand  
 Test Item : General Radiated Emission Data  
 Test Site : No.3 OATS  
 Test Mode : Mode 1: Transmit (2441.35MHz)

Frequency MHz	Correct Factor dB	Reading Level dBuV	Measurement Level dBuV/m	Margin dB	Limit dBuV/m
<b>Horizontal</b>					
130.880	-7.407	32.310	24.902	-18.598	43.500
305.480	-3.836	28.108	24.272	-21.728	46.000
468.440	3.544	29.081	32.625	-13.375	46.000
606.180	4.196	25.312	29.508	-16.492	46.000
724.520	3.835	26.049	29.884	-16.116	46.000
908.820	6.330	24.859	31.189	-14.811	46.000
<b>Vertical</b>					
119.240	-3.571	29.840	26.270	-17.230	43.500
249.220	-5.096	27.337	22.241	-23.759	46.000
371.440	-0.310	25.629	25.319	-20.681	46.000
536.340	1.609	25.343	26.952	-19.048	46.000
689.600	2.302	25.054	27.356	-18.644	46.000
833.160	1.716	28.923	30.639	-15.361	46.000

Note:

1. All Readings below 1GHz are Quasi-Peak, above 1GHz are performed with peak and/or average measurements as necessary.
2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.
4. Measurement Level = Reading Level + Correct Factor.
5. Correct Factor = Antenna factor + Cable loss – Amplifier gain.
6. The average measurement was not performed when the peak measured data under the limit of average detection.
7. The emission levels of other frequencies are very lower than the limit and not show in test report.
8. No emission found between lowest internal used/generated frequency to 30MHz.

**5. RF antenna conducted test**


**5.1. Test Equipment**

	Equipment	Manufacturer	Model No./Serial No.	Last Cal.
	Spectrum Analyzer	R&S	FSP40 / 100170	Jun, 2014
	Spectrum Analyzer	Agilent	E4407B / US39440758	Jun, 2014
X	Spectrum Analyzer	Agilent	N9010A / MY48030495	Apr., 2014

- Note:
1. All equipments are calibrated with traceable calibrations. Each calibration is traceable to the national or international standards.
  2. The test instruments marked with “X” are used to measure the final test results.

**5.2. Test Setup**

**RF antenna Conducted Measurement:**



**5.3. Limits**

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 15.205(c)).

#### **5.4. Test Procedure**

The EUT was tested according to DTS test procedure of KDB558074 for compliance to FCC 47CFR 15.247 requirements.

Set RBW = 100 kHz, Set VBW > RBW, scan up through 10th harmonic.

#### **5.5. Uncertainty**


The measurement uncertainty

Conducted is defined as  $\pm 1.27\text{dB}$

5.6. Test Result of RF antenna conducted test

Product : Afterglow Nur PS4/PS3 Wireless Stand  
Test Item : RF antenna conducted test  
Test Site : No.3 OATS  
Test Mode : Mode 1: Transmit

Channel 01 (2403.35MHz) 30M-25GHz




Note: The above test pattern is synthesized by multiple of the frequency range.



Product : Afterglow Nur PS4/PS3 Wireless Stand  
Test Item : RF antenna conducted test  
Test Site : No.3 OATS  
Test Mode : Mode 1: Transmit


**Channel 20 (2441.35MHz) 30M-25GHz**



Note: The above test pattern is synthesized by multiple of the frequency range.

Product : Afterglow Nur PS4/PS3 Wireless Stand  
Test Item : RF antenna conducted test  
Test Site : No.3 OATS  
Test Mode : Mode 1: Transmit

**Channel 39 (2479.35MHz) 30M-25GHz**



Note: The above test pattern is synthesized by multiple of the frequency range.

## 6. Band Edge

### 6.1. Test Equipment

#### RF Radiated Measurement:


The following test equipments are used during the band edge tests:

Test Site	Equipment	Manufacturer	Model No./Serial No.	Last Cal.	
☒ Site # 3		Bilog Antenna	Schaffner Chase	CBL6112B/2673	Sep., 2014
	X	Horn Antenna	Schwarzbeck	BBHA9120D/D305	Sep., 2014
		Horn Antenna	Schwarzbeck	BBHA9170/208	Jul., 2014
		Pre-Amplifier	QTK	QTK-AMP-03 / 0003	May, 2014
	X	Pre-Amplifier	QTK	AP-180C / CHM_0906076	Sep., 2014
		Pre-Amplifier	MITEQ	AMF-4D-180400-45-6P/ 925975	Mar, 2014
	X	Spectrum Analyzer	Agilent	E4407B / US39440758	May, 2014
		Test Receiver	R & S	ESCS 30/ 825442/018	Sep., 2014
	X	Coaxial Cable	Quietek	QTK-CABLE/ CAB5	Feb., 2014
	X	Controller	Quietek	QTK-CONTROLLER/ CTRL3	N/A
	X	Coaxial Switch	Anritsu	MP59B/6200265729	N/A

- Note:
1. All instruments are calibrated every one year.
  2. The test instruments marked by "X" are used to measure the final test results.

### 6.2. Test Setup

#### RF Radiated Measurement:



### **6.3. Limits**

Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 20dB below the level of the fundamental or to the general radiated emission limits in paragraph 15.209, whichever is the lesser attenuation.

### **6.4. Test Procedure**

The EUT was setup according to ANSI C63.10, 2009 and tested according to DTS test procedure of KDB558074 for compliance to FCC 47CFR 15.247 requirements.

The EUT is placed on a turn table which is 0.8 meter above ground. The turn table is rotated 360 degrees to determine the position of the maximum emission level. The EUT was positioned such that the distance from antenna to the EUT was 3 meters.

The antenna is scanned from 1 meter to 4 meters to find out the maximum emission level. This is repeated for both horizontal and vertical polarization of the antenna. In order to find the maximum emission, all of the interface cables were manipulated according to ANSI C63.10:2009 on radiated measurement.

### **6.5. Uncertainty**

± 3.9 dB above 1GHz

± 3.8 dB below 1GHz


**6.6. Test Result of Band Edge**

Product : Afterglow Nur PS4/PS3 Wireless Stand  
 Test Item : Band Edge Data  
 Test Site : No.3 OATS  
 Test Mode : Mode 1: Transmit-


**RF Radiated Measurement (Horizontal):**

Channel No.	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBuV)	Emission Level (dBuV/m)	Peak Limit (dBuV/m)	Average Limit (dBuV/m)	Result
01 (Peak)	2390.000	-1.131	50.948	49.817	74.00	54.00	Pass
01 (Peak)	2400.000	-1.084	72.715	71.632	--	--	--
01 (Peak)	2403.600	-1.064	97.693	96.629	--	--	--
01 (Average)	2390.000	-1.131	36.247	35.116	74.00	54.00	Pass
01 (Average)	2400.000	-1.084	61.037	59.954	--	--	--
01 (Average)	2403.400	-1.065	94.407	93.342	--	--	--

**Figure Channel 01: Horizontal (Peak)**



**Figure Channel 01: Horizontal (Average)**




- Note: 1. All readings above 1GHz are performed with peak and/or average measurements as necessary.  
 2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.  
 3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.  
 4. “ \* ”, means this data is the worst emission level.  
 5. Measurement Level = Reading Level + Correct Factor.  
 6. The average measurement was not performed when the peak measured data under the limit of average detection.

Product : Afterglow Nur PS4/PS3 Wireless Stand  
 Test Item : Band Edge Data  
 Test Site : No.3 OATS  
 Test Mode : Mode 1: Transmit-


**RF Radiated Measurement (Vertical):**

Channel No.	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBuV)	Emission Level (dBuV/m)	Peak Limit (dBuV/m)	Average Limit (dBuV/m)	Result
01 (Peak)	2390.000	-1.725	53.007	51.282	74.00	54.00	Pass
01 (Peak)	2400.000	-1.733	74.910	73.178	--	--	--
01 (Peak)	2403.600	-1.726	100.585	98.860	--	--	--
01 (Average)	2390.000	-1.725	38.020	36.295	74.00	54.00	Pass
01 (Average)	2400.000	-1.733	64.207	62.475	--	--	--
01 (Average)	2403.400	-1.726	97.667	95.941	--	--	--

**Figure Channel 01: Vertical (Peak)**



**Figure Channel 01: Vertical (Average)**



Note:


1. All readings above 1GHz are performed with peak and/or average measurements as necessary.
2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.
4. “ \* ”, means this data is the worst emission level.
5. Measurement Level = Reading Level + Correct Factor.
6. The average measurement was not performed when the peak measured data under the limit of average detection.

Product : Afterglow Nur PS4/PS3 Wireless Stand  
 Test Item : Band Edge Data  
 Test Site : No.3 OATS  
 Test Mode : Mode 1: Transmit-


**RF Radiated Measurement (Horizontal):**

Channel No.	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBuV)	Emission Level (dBuV/m)	Peak Limit (dBuV/m)	Average Limit (dBuV/m)	Result
39 (Peak)	2479.700	-0.581	91.979	91.397	--	--	--
39 (Peak)	2483.500	-0.558	53.882	53.324	74.00	54.00	Pass
39 (Average)	2479.300	-0.585	88.828	88.243	--	--	--
39 (Average)	2483.500	-0.558	47.928	47.370	74.00	54.00	Pass

**Figure Channel 38: Horizontal (Peak)**



**Figure Channel 38: Horizontal (Average)**




- Note: 1. All readings above 1GHz are performed with peak and/or average measurements as necessary.  
 2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.  
 3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.  
 4. “ \* ”, means this data is the worst emission level.  
 5. Measurement Level = Reading Level + Correct Factor.  
 6. The average measurement was not performed when the peak measured data under the limit of average detection.

Product : Afterglow Nur PS4/PS3 Wireless Stand  
 Test Item : Band Edge Data  
 Test Site : No.3 OATS  
 Test Mode : Mode 1: Transmit-


**RF Radiated Measurement (Vertical):**

Channel No.	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBuV)	Emission Level (dBuV/m)	Peak Limit (dBuV/m)	Average Limit (dBuV/m)	Result
39 (Peak)	2479.700	-1.325	97.890	96.564	--	--	--
39 (Peak)	2483.500	-1.305	59.578	58.273	74.00	54.00	Pass
39 (Average)	2479.300	-1.328	94.724	93.396	--	--	--
39 (Average)	2483.500	-1.305	53.669	52.364	74.00	54.00	Pass

**Figure Channel 38: Vertical (Peak)**



**Figure Channel 38: Vertical (Average)**



Note:

1. All readings above 1GHz are performed with peak and/or average measurements as necessary.
2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.
4. “ \* ”, means this data is the worst emission level.
5. Measurement Level = Reading Level + Correct Factor.
6. The average measurement was not performed when the peak measured data under the limit of average detection.




**7. Occupied Bandwidth**

**7.1. Test Equipment**

Equipment	Manufacturer	Model No./Serial No.	Last Cal.
Spectrum Analyzer	R&S	FSP40 / 100170	Jun, 2014
Spectrum Analyzer	Agilent	E4407B / US39440758	Jun, 2014
X Spectrum Analyzer	Agilent	N9010A / MY48030495	Apr., 2014

Note: 1. All instruments are calibrated every one year.  
 2. The test instruments marked by “X” are used to measure the final test results.

**7.2. Test Setup**



**7.3. Limits**

The minimum bandwidth shall be at least 500 kHz.

**7.4. Test Procedure**

The EUT was setup according to ANSI C63.10, 2009; tested according to DTS test procedure of KDB558074 for compliance to FCC 47CFR 15.247 requirements.

Set RBW = 1-5% of the emission bandwidth, VBW ≥ 3\*RBW

**7.5. Uncertainty**


± 150Hz

**7.6. Test Result of Occupied Bandwidth**

Product : Afterglow Nur PS4/PS3 Wireless Stand  
 Test Item : Occupied Bandwidth Data  
 Test Site : No.3 OATS  
 Test Mode : Mode 1: Transmit (2403.35MHz)

Channel No.	Frequency (MHz)	Measurement Level (kHz)	Required Limit (kHz)	Result
01	2403.35	1700	>500	Pass


**Figure Channel 01:**



Product : Afterglow Nur PS4/PS3 Wireless Stand  
 Test Item : Occupied Bandwidth Data  
 Test Site : No.3 OATS  
 Test Mode : Mode 1: Transmit (2441.35MHz)

Channel No.	Frequency (MHz)	Measurement Level (kHz)	Required Limit (kHz)	Result
20	2441.35	1660	>500	Pass


**Figure Channel 20:**



Product : Afterglow Nur PS4/PS3 Wireless Stand  
 Test Item : Occupied Bandwidth Data  
 Test Site : No.3 OATS  
 Test Mode : Mode 1: Transmit (2479.35MHz)

Channel No.	Frequency (MHz)	Measurement Level (kHz)	Required Limit (kHz)	Result
39	2479.35	1690	>500	Pass

**Figure Channel 38:**



**8. Power Density**


**8.1. Test Equipment**

Equipment	Manufacturer	Model No./Serial No.	Last Cal.
Spectrum Analyzer	R&S	FSP40 / 100170	Jun, 2014
Spectrum Analyzer	Agilent	E4407B / US39440758	Jun, 2014
X Spectrum Analyzer	Agilent	N9010A / MY48030495	Apr., 2014

Note: 1. All equipments are calibrated every one year.

1. The test instruments marked by “X” are used to measure the final test results.

**8.2. Test Setup**



**8.3. Limits**

The transmitted power density averaged over any 1 second interval shall not be greater +8dBm in any 3kHz bandwidth.

**8.4. Test Procedure**

The EUT was setup according to ANSI C63.10, 2009; tested according to DTS test procedure of KDB 558074 for compliance to FCC 47CFR 15.247 requirements.

The maximum power spectral density using KDB 558074 section 10.2 PKPSD (peak PSD) method.

**8.5. Uncertainty**


± 1.27 dB

**8.6. Test Result of Power Density**

Product : Afterglow Nur PS4/PS3 Wireless Stand  
 Test Item : Power Density Data  
 Test Site : No.3 OATS  
 Test Mode : Mode 1: Transmit(2403.35MHz)

Channel No.	Frequency (MHz)	Measure Level (dBm)	Limit (dBm)	Result
01	2403.35	-0.06	< 7.5dBm	Pass


**Figure Channel 01:**



Product : Afterglow Nur PS4/PS3 Wireless Stand  
 Test Item : Power Density Data  
 Test Site : No.3OATS  
 Test Mode : Mode 1: Transmit (2441.35MHz)

Channel No.	Frequency (MHz)	Measurement Level (dBm)	Required Limit (dBm)	Result
20	2441.35	-1.60	< 7.5dBm	Pass


**Figure Channel 20:**



Product : Afterglow Nur PS4/PS3 Wireless Stand  
 Test Item : Power Density Data  
 Test Site : No.3 OATS  
 Test Mode : Mode 1: Transmit (2479.35MHz)

Channel No.	Frequency (MHz)	Measurement Level (dBm)	Required Limit (dBm)	Result
39	2479.35	-3.01	< 7.5dBm	Pass

**Figure Channel 39:**





## 9. EMI Reduction Method During Compliance Testing

No modification was made during testing.

## Attachment 1: EUT Test Photographs

## Attachment 2: EUT Detailed Photographs