

# FC

## Test Report

Product Name	Afterglow Universal/ XBOX360/ PS3 Wireless Dongle
Model No	PL-9929T, PL3771T, PL6471T
FCC ID.	X5B-PL9929T

Applicant	Performance Designed Products, LLC
Address	14144 Ventura Blvd., Suite 200 Sherman Oaks, CA 91423 USA

Date of Receipt	June 22, 2012
Issue Date	July 31, 2012
Report No.	126402R-RFUSP42V01
Report Version	V1.0



The test results relate only to the samples tested.  
The test report shall not be reproduced except in full without the written approval of Quietek Corporation.  
This report must not be used to claim product endorsement by NVLAP any agency of the U.S. Government

# Test Report Certification

Issue Date: July 31, 2012

Report No.: 126402R-RFUSP42V01


**Accredited by NIST (NVLAP)**

NVLAP Lab Code: 200533-0

Product Name	Afterglow Universal/ XBOX360/ PS3 Wireless Dongle
Applicant	Performance Designed Products, LLC
Address	14144 Ventura Blvd., Suite 200 Sherman Oaks, CA 91423 USA
Manufacturer	Performance Designed Products, LLC
Model No.	PL-9929T, PL3771T, PL6471T
EUT Rated Voltage	DC 5V (Power by USB)
EUT Test Voltage	AC 120V/60Hz
Trade Name	pdp
Applicable Standard	FCC CFR Title 47 Part 15 Subpart C: 2010 ANSI C63.4: 2003
Test Result	Complied

The test results relate only to the samples tested.

The test report shall not be reproduced except in full without the written approval of Quietek Corporation.

This report must not be used to claim product endorsement by NVLAP any agency of the U.S. Government

Documented By : Genie Chang  
( Senior Adm. Specialist / Genie Chang )

Tested By : Henk Huang  
( Engineer / Henk Huang )

Approved By : Vincent Lin  
( Manager / Vincent Lin )

# TABLE OF CONTENTS

Description	Page
<b>1. GENERAL INFORMATION</b>	<b>5</b>
1.1. EUT Description	5
1.2. Operational Description	7
1.3. Tested System Details	8
1.4. Configuration of Tested System	8
1.5. EUT Exercise Software	9
1.6. Test Facility	10
<b>2. Conducted Emission</b>	<b>11</b>
2.1. Test Equipment	11
2.2. Test Setup	11
2.3. Limits	12
2.4. Test Procedure	12
2.5. Uncertainty	12
2.6. Test Result of Conducted Emission	13
<b>3. Peak Power Output</b>	<b>15</b>
3.1. Test Equipment	15
3.2. Test Setup	15
3.3. Limit	15
3.4. Test Procedure	15
3.5. Test Result of Peak Power Output	16
<b>4. Radiated Emission</b>	<b>17</b>
4.1. Test Equipment	17
4.2. Test Setup	18
4.3. Limits	19
4.4. Test Procedure	19
4.5. Uncertainty	19
4.6. Test Result of Radiated Emission	20
<b>5. RF antenna conducted test</b>	<b>24</b>
5.1. Test Equipment	24
5.2. Test Setup	24
5.3. Limits	24
5.4. Test Procedure	25
5.5. Uncertainty	25
5.6. Test Result of RF antenna conducted test	26
<b>6. Band Edge</b>	<b>32</b>
6.1. Test Equipment	32
6.2. Test Setup	33
6.3. Limits	33
6.4. Test Procedure	34
6.5. Uncertainty	34
6.6. Test Result of Band Edge	35
<b>7. Occupied Bandwidth</b>	<b>39</b>

---

7.1.	Test Equipment.....	39
7.2.	Test Setup .....	39
7.3.	Limits .....	39
7.4.	Test Procedure .....	39
7.5.	Uncertainty .....	39
7.6.	Test Result of Occupied Bandwidth.....	40
<b>8.</b>	<b>Power Density.....</b>	<b>43</b>
8.1.	Test Equipment.....	43
8.2.	Test Setup .....	43
8.3.	Limits .....	43
8.4.	Test Procedure .....	43
8.5.	Uncertainty .....	43
8.6.	Test Result of Power Density .....	44
<b>9.</b>	<b>EMI Reduction Method During Compliance Testing .....</b>	<b>47</b>

Attachment 1: EUT Test Photographs

Attachment 2: EUT Detailed Photographs

## 1. GENERAL INFORMATION

### 1.1. EUT Description

Product Name	Afterglow Universal/ XBOX360/ PS3 Wireless Dongle
Trade Name	pdp
Model No.	PL-9929T, PL3771T, PL6471T
FCC ID.	X5B-PL9929T
Frequency Range	2403.35 – 2479.35MHz
Channel Control	Auto
Channel Separation	2MHz
Antenna Gain	Refer to the table “Antenna List”
Channel Number	39
Type of Modulation	Pi/4 DQPSK
Antenna Type	Printed on PCB

#### Antenna List

No.	Manufacturer	Part No.	Peak Gain
1	TATUNG(TX0)	N/A	2.29 dBi for 2.4 GHz
	TATUNG(TX1)	N/A	2.97 dBi for 2.4 GHz

Note: The antenna of EUT is conform to FCC 15.203

Center Frequency of Each Channel:

Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
Channel 1:	2403.35 MHz	Channel 11:	2423.35 MHz	Channel 21:	2443.35 MHz	Channel 31:	2463.35 MHz
Channel 2:	2405.35 MHz	Channel 12:	2425.35 MHz	Channel 22:	2445.35 MHz	Channel 32:	2465.35 MHz
Channel 3:	2407.35 MHz	Channel 13:	2427.35 MHz	Channel 23:	2447.35 MHz	Channel 33:	2467.35 MHz
Channel 4:	2409.35 MHz	Channel 14:	2429.35 MHz	Channel 24:	2449.35 MHz	Channel 34:	2469.35 MHz
Channel 5:	2411.35 MHz	Channel 15:	2431.35 MHz	Channel 25:	2451.35 MHz	Channel 35:	2471.35 MHz
Channel 6:	2413.35 MHz	Channel 16:	2433.35 MHz	Channel 26:	2453.35 MHz	Channel 36:	2473.35 MHz
Channel 7:	2415.35 MHz	Channel 17:	2435.35 MHz	Channel 27:	2455.35 MHz	Channel 37:	2475.35 MHz
Channel 8:	2417.35 MHz	Channel 18:	2437.35 MHz	Channel 28:	2457.35 MHz	Channel 38:	2477.35 MHz
Channel 9:	2419.35 MHz	Channel 19:	2439.35 MHz	Channel 29:	2459.35 MHz	Channel 39:	2479.35 MHz
Channel 10:	2421.35 MHz	Channel 20:	2441.35 MHz	Channel 30:	2461.35 MHz		

Note:

1. The EUT is an Afterglow Universal/ XBOX360/ PS3 Wireless Dongle.
2. Regarding to the operation frequency, the lowest, middle and highest frequency are selected to perform the test.
3. The different of each model is shown as below:

Product Name	Model Number
Afterglow Universal Wireless Dongle	PL-9929T
Afterglow XBOX360 Wireless Dongle	PL3771T
Afterglow PS3 Wireless Dongle	PL6471T

4. These tests are conducted on a sample for the purpose of demonstrating compliance of 2.4GHz transmitter with Part 15 Subpart C Paragraph 15.247 of spread spectrum devices
5. The radiation measurements are performed in X, Y, Z axis positioning. Only the worst case is shown in the report.

Test Mode:	Mode 1: Transmit
------------	------------------


### 1.3. Tested System Details

The types for all equipment, plus descriptions of all cables used in the tested system (including inserted cards) are:

	Product	Manufacturer	Model No.	Serial No.	Power Cord
1	Notebook PC	DELL	PPT	N/A	Non-Shielded, 0.8m
2	Modem	ACEEX	DM-1414	0102027547	Non-Shielded, 1.8m
3	DVD ROM	DELL	PD01S	P0690-A01	N/A
4	Microphone & Earphone	PCHOME	N/A	N/A	N/A
5	iPod nano	Apple	A1199	5U7047U8VQ5	N/A
6	Monitor	LG	W2261VT	907YHZK07373	Non-Shielded, 1.8m

Signal Cable Type	Signal cable Description
A	VGA Cable Non-Shielded, 1.8m, with two ferrite cores bonded.
B	USB extension Cable Shielded, 1.8m
C	Modem Cable Non-Shielded, 1.5m
D	DVD Cable Non-Shielded, 0.3m
E	Microphone & Earphone Cable Non-Shielded, 2.0m
F	Audio Cable Non-Shielded, 1.2m

### 1.4. Configuration of Tested System



## 1.5. EUT Exercise Software

- (1) Setup the EUT as shown in Section 1.4.
- (2) Execute “Vmidev.exe (v1.1.6.38)” on the Notebook.
- (3) Configure the test mode, the test channel, and the data rate.
- (4) Press “OK” to start the continuous Transmit.
- (5) Verify that the EUT works properly.



## 1.6. Test Facility

Ambient conditions in the laboratory:

Items	Required (IEC 68-1)	Actual
Temperature (°C)	15-35	20-35
Humidity (%RH)	25-75	50-65
Barometric pressure (mbar)	860-1060	950-1000

The related certificate for our laboratories about the test site and management system can be downloaded from Quietek Corporation's Web Site : <http://tw.quietek.com/tw/emc/accreditations/accreditations.htm>  
The address and introduction of Quietek Corporation's laboratories can be founded in our Web site : <http://www.quietek.com/>

Site Description: File on  
Federal Communications Commission  
FCC Engineering Laboratory  
7435 Oakland Mills Road  
Columbia, MD 21046  
Registration Number: 92195

Accreditation on NVLAP  
NVLAP Lab Code: 200533-0

Site Name: Quietek Corporation  
Site Address: No. 5-22, Ruei-Shu Valley, Ruei-Ping Tsuen,  
Lin-Kou Shiang, Taipei,  
Taiwan, R.O.C.  
TEL: 886-2-8601-3788 / FAX : 886-2-8601-3789  
E-Mail : [service@quietek.com](mailto:service@quietek.com)

FCC Accreditation Number: TW1014

## 2. Conducted Emission


### 2.1. Test Equipment

The following test equipment are used during the conducted emission test:

Item	Instrument	Manufacturer	Type No./Serial No	Last Cal.	Remark
1	Test Receiver	R & S	ESCS 30/825442/17	May, 2012	
2	L.I.S.N.	R & S	ESH3-Z5/825016/6	May, 2012	EUT
3	L.I.S.N.	Kyoritsu	KNW-407/8-1420-3	May, 2012	Peripherals
4	Pulse Limiter	R & S	ESH3-Z2	May, 2012	
5	No.1 Shielded Room			N/A	

Note: All instruments are calibrated every one year.

### 2.2. Test Setup



**2.3. Limits**

<b>FCC Part 15 Subpart C Paragraph 15.207 (dBuV) Limit</b>		
Frequency MHz	Limits	
	QP	AVG
0.15 - 0.50	66-56	56-46
0.50-5.0	56	46
5.0 - 30	60	50

**2.4. Test Procedure**

The EUT and simulators are connected to the main power through a line impedance stabilization network (L.I.S.N.). This provides a 50 ohm /50uH coupling impedance for the measuring equipment. The peripheral devices are also connected to the main power through a LISN that provides a 50ohm /50uH coupling impedance with 50ohm termination. (Please refers to the block diagram of the test setup and photographs.) Both sides of A.C. line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.4: 2003 on conducted measurement. Conducted emissions were invested over the frequency range from 0.15MHz to 30MHz using a receiver bandwidth of 9kHz.

**2.5. Uncertainty**

± 2.26 dB

## 2.6. Test Result of Conducted Emission

Product : Afterglow Universal/ XBOX360/ PS3 Wireless Dongle  
 Test Item : Conducted Emission Test  
 Power Line : Line 1  
 Test Mode : Mode 1: Transmit (2441.35MHz) -Ant1

Frequency MHz	Correct Factor dB	Reading Level dBuV	Measurement Level dBuV	Margin dB	Limit dBuV
<b>Line 1</b>					
<b>Quasi-Peak</b>					
0.224	9.670	20.090	29.760	-34.126	63.886
0.416	9.640	15.580	25.220	-33.180	58.400
0.584	9.640	15.990	25.630	-30.370	56.000
1.916	9.680	14.880	24.560	-31.440	56.000
4.752	9.690	12.990	22.680	-33.320	56.000
17.736	9.890	21.070	30.960	-29.040	60.000
<b>Average</b>					
0.224	9.670	20.080	29.750	-24.136	53.886
0.416	9.640	14.900	24.540	-23.860	48.400
0.584	9.640	15.050	24.690	-21.310	46.000
1.916	9.680	13.200	22.880	-23.120	46.000
4.752	9.690	6.190	15.880	-30.120	46.000
17.736	9.890	10.050	19.940	-30.060	50.000

Note:

1. All Reading Levels are Quasi-Peak and average value.
2. "■" means the worst emission level.
3. Measurement Level = Reading Level + Correct Factor

Product : Afterglow Universal/ XBOX360/ PS3 Wireless Dongle  
 Test Item : Conducted Emission Test  
 Power Line : Line 2  
 Test Mode : Mode 1: Transmit (2441.35MHz) -Ant1

Frequency MHz	Correct Factor dB	Reading Level dBuV	Measurement Level dBuV	Margin dB	Limit dBuV
<b>Line 2</b>					
<b>Quasi-Peak</b>					
0.166	9.718	24.580	34.298	-31.245	65.543
0.502	9.650	23.480	33.130	-22.870	56.000
0.666	9.650	19.250	28.900	-27.100	56.000
2.416	9.700	17.430	27.130	-28.870	56.000
4.920	9.710	13.450	23.160	-32.840	56.000
22.252	10.130	21.480	31.610	-28.390	60.000
<b>Average</b>					
0.166	9.718	24.260	33.978	-21.565	55.543
0.502	9.650	22.540	32.190	-13.810	46.000
0.666	9.650	18.500	28.150	-17.850	46.000
2.416	9.700	15.790	25.490	-20.510	46.000
4.920	9.710	7.130	16.840	-29.160	46.000
22.252	10.130	10.350	20.480	-29.520	50.000

Note:

1. All Reading Levels are Quasi-Peak and average value.
2. "█" means the worst emission level.
3. Measurement Level = Reading Level + Correct Factor


### 3. Peak Power Output

#### 3.1. Test Equipment

	Equipment	Manufacturer	Model No./Serial No.	Last Cal.
X	Power Meter	Anritsu	ML2495A/6K00003357	May, 2012
X	Power Sensor	Anritsu	MA2411B/0738448	Jun, 2012

- Note:
1. All equipments are calibrated every one year.
  2. The test instruments marked by “X” are used to measure the final test results.

#### 3.2. Test Setup



#### 3.3. Limit

The maximum peak power shall be less 1Watt.

#### 3.4. Test Procedure

The EUT was setup to ANSI C63.4, 2003; tested to FHSS test procedure of FCC Public Notice DA 00-705 for compliance to FCC 47CFR 15.247 requirements.

### 3.5. Test Result of Peak Power Output

Product : Afterglow Universal/ XBOX360/ PS3 Wireless Dongle  
 Test Item : Peak Power Output Data  
 Test Site : No.3 OATS  
 Test Mode : Mode 1: Transmit

#### Ant 0

Channel No.	Frequency (MHz)	Measurement Level (dBm)	Required Limit (dBm)	Result
01	2403.35	4.09	<30dBm	Pass
20	2441.35	3.31	<30dBm	Pass
39	2479.35	2.68	<30dBm	Pass

#### Ant 1

Channel No.	Frequency (MHz)	Measurement Level (dBm)	Required Limit (dBm)	Result
01	2403.35	4.24	<30dBm	Pass
20	2441.35	3.74	<30dBm	Pass
39	2479.35	2.86	<30dBm	Pass

#### 4. Radiated Emission

##### 4.1. Test Equipment

The following test equipment are used during the radiated emission test:


Test Site		Equipment	Manufacturer	Model No./Serial No.	Last Cal.
☒ Site # 3	X	Bilog Antenna	Schaffner Chase	CBL6112B/2673	Sep., 2011
	X	Horn Antenna	Schwarzbeck	BBHA9120D/D305	Sep., 2011
	X	Horn Antenna	Schwarzbeck	BBHA9170/208	Jul., 2012
	X	Pre-Amplifier	QTK	QTK-AMP-03 / 0003	May, 2012
	X	Pre-Amplifier	QTK	AP-180C / CHM_0906076	Sep., 2011
	X	Pre-Amplifier	MITEQ	AMF-4D-180400-45-6P/ 925975	Mar, 2012
	X	Spectrum Analyzer	Agilent	E4407B / US39440758	May, 2012
	X	Test Receiver	R & S	ESCS 30/ 825442/018	Sep., 2011
	X	Coaxial Cable	Quietek	QTK-CABLE/ CAB5	Feb., 2012
	X	Controller	Quietek	QTK-CONTROLLER/ CTRL3	N/A
	X	Coaxial Switch	Anritsu	MP59B/6200265729	N/A

- Note:
1. All equipments are calibrated with traceable calibrations. Each calibration is traceable to the national or international standards.
  2. The test instruments marked with "X" are used to measure the final test results.




## 4.2. Test Setup

### Radiated Emission Below 1GHz



### Radiated Emission Above 1GHz



### 4.3. Limits

Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 20dB below the level of the fundamental or to the general radiated emission limits in paragraph 15.209, whichever is the lesser attenuation.

<b>FCC Part 15 Subpart C Paragraph 15.209(a) Limits</b>		
Frequency MHz	uV/m @3m	dBuV/m@3m
30-88	100	40
88-216	150	43.5
216-960	200	46
Above 960	500	54

Remarks: E field strength (dBuV/m) = 20 log E field strength (uV/m)

### 4.4. Test Procedure

The EUT was setup according to ANSI C63.4, 2003 and tested according to DTS test procedure of Jan. 2012 KDB558074 for compliance to FCC 47CFR 15.247 requirements. The EUT is placed on a turn table which is 0.8 meter above ground. The turn table is rotated 360 degrees to determine the position of the maximum emission level. The EUT was positioned such that the distance from antenna to the EUT was 3 meters.

The antenna is scanned between 1 meter and 4 meters to find out the maximum emission level. This is repeated for both horizontal and vertical polarization of the antenna. In order to find the maximum emission, all of the interface cables were manipulated according to ANSI C63.4:2003 on radiated measurement.

The resolution bandwidth below 1GHz setting on the field strength meter is 120 kHz and above 1GHz is 1MHz.

Radiated emission measurements below 1GHz are made using broadband Bilog antenna and above 1GHz are made using Horn Antennas.

The measurement is divided into the Preliminary Measurement and the Final Measurement.

The suspected frequencies are searched for in Preliminary Measurement with the measurement antenna kept pointed at the source of the emission both in azimuth and elevation, with the polarization of the antenna oriented for maximum response. The antenna is pointed at an angle towards the source of the emission, and the EUT is rotated in both height and polarization to maximize the measured emission. The emission is kept within the illumination area of the 3 dB bandwidth of the antenna.

The worst radiated emission is measured in the Open Area Test Site on the Final Measurement.

The measurement frequency range from 30MHz - 10th Harmonic of fundamental was investigated.

### 4.5. Uncertainty

± 3.9 dB above 1GHz

± 3.8 dB below 1GHz

#### 4.6. Test Result of Radiated Emission

Product : Afterglow Universal/ XBOX360/ PS3 Wireless Dongle  
 Test Item : Harmonic Radiated Emission Data  
 Test Site : No.3 OATS  
 Test Mode : Mode 1: Transmit (2403.35MHz)-Ant1

Frequency MHz	Correct Factor dB	Reading Level dBuV	Measurement Level dBuV/m	Margin dB	Limit dBuV/m
<b>Horizontal</b>					
<b>Peak Detector:</b>					
4804.700	-8.362	31.770	23.408	-50.592	74.000
7207.050	1.805	32.600	34.404	-39.596	74.000
9609.400	4.992	33.090	38.082	-35.918	74.000
<b>Vertical</b>					
<b>Peak Detector:</b>					
4804.700	-6.944	31.910	24.966	-49.034	74.000
7207.050	1.763	33.790	35.553	-38.447	74.000
9609.400	4.066	33.690	37.756	-36.244	74.000

**Note:**

- All Readings below 1GHz are Quasi-Peak, above 1GHz are performed with peak and/or average measurements as necessary.
- Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
- Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.
- Measurement Level = Reading Level + Correct Factor.
- Correct Factor = Antenna factor + Cable loss - Amplifier gain.
- The average measurement was not performed when the peak measured data under the limit of average detection.
- The emission levels of other frequencies are very lower than the limit and not show in test report.

Product : Afterglow Universal/ XBOX360/ PS3 Wireless Dongle  
 Test Item : Harmonic Radiated Emission Data  
 Test Site : No.3 OATS  
 Test Mode : Mode 1: Transmit (2441.35MHz) -Ant1

Frequency MHz	Correct Factor dB	Reading Level dBuV	Measurement Level dBuV/m	Margin dB	Limit dBuV/m
<b>Horizontal</b>					
<b>Peak Detector:</b>					
4882.700	-7.419	31.720	24.301	-49.699	74.000
7324.050	3.984	32.590	36.575	-37.425	74.000
9765.400	4.552	34.390	38.942	-35.058	74.000
<b>Vertical</b>					
<b>Peak Detector:</b>					
4882.700	-6.185	31.440	25.255	-48.745	74.000
7324.050	3.774	32.640	36.414	-37.586	74.000
9765.400	3.872	34.470	38.342	-35.658	74.000

**Note:**

1. All Readings below 1GHz are Quasi-Peak, above 1GHz are performed with peak and/or average measurements as necessary.
2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.
4. Measurement Level = Reading Level + Correct Factor.
5. Correct Factor = Antenna factor + Cable loss – Amplifier gain.
6. The average measurement was not performed when the peak measured data under the limit of average detection.
7. The emission levels of other frequencies are very lower than the limit and not show in test report.

Product : Afterglow Universal/ XBOX360/ PS3 Wireless Dongle  
 Test Item : Harmonic Radiated Emission Data  
 Test Site : No.3 OATS  
 Test Mode : Mode 1: Transmit (2479.35MHz) -Ant1

Frequency MHz	Correct Factor dB	Reading Level dBuV	Measurement Level dBuV/m	Margin dB	Limit dBuV/m
<b>Horizontal</b>					
<b>Peak Detector:</b>					
4960.700	-6.533	32.010	25.477	-48.523	74.000
7441.050	4.605	31.780	36.385	-37.615	74.000
9921.400	5.500	34.550	40.050	-33.950	74.000
<b>Vertical</b>					
<b>Peak Detector:</b>					
4960.700	-5.751	31.970	26.219	-47.781	74.000
7441.050	4.032	31.810	35.842	-38.158	74.000
9921.400	4.869	34.510	39.378	-34.622	74.000

Note:

1. All Readings below 1GHz are Quasi-Peak, above 1GHz are performed with peak and/or average measurements as necessary.
2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.
4. Measurement Level = Reading Level + Correct Factor.
5. Correct Factor = Antenna factor + Cable loss – Amplifier gain.
6. The average measurement was not performed when the peak measured data under the limit of average detection.
7. The emission levels of other frequencies are very lower than the limit and not show in test report.

Product : Afterglow Universal/ XBOX360/ PS3 Wireless Dongle  
 Test Item : General Radiated Emission Data  
 Test Site : No.3 OATS  
 Test Mode : Mode 1: Transmit (2441.35MHz) -Ant1

Frequency MHz	Correct Factor dB	Reading Level dBuV	Measurement Level dBuV/m	Margin dB	Limit dBuV/m
<b>Horizontal</b>					
132.820	-10.230	45.015	34.785	-8.715	43.500
363.680	-1.433	37.739	36.306	-9.694	46.000
431.580	-2.099	29.537	27.438	-18.562	46.000
536.340	2.195	36.853	39.048	-6.952	46.000
749.740	3.320	28.920	32.240	-13.760	46.000
887.480	6.204	28.788	34.992	-11.008	46.000
<b>Vertical</b>					
94.020	-8.189	39.684	31.494	-12.006	43.500
249.220	-6.014	42.340	36.326	-9.674	46.000
396.660	-2.296	39.803	37.507	-8.493	46.000
532.460	1.957	33.093	35.050	-10.950	46.000
666.320	2.031	31.189	33.221	-12.779	46.000
796.300	5.161	31.127	36.288	-9.712	46.000

**Note:**

1. All Readings below 1GHz are Quasi-Peak, above 1GHz are performed with peak and/or average measurements as necessary.
2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.
4. Measurement Level = Reading Level + Correct Factor.
5. Correct Factor = Antenna factor + Cable loss – Amplifier gain.
6. The average measurement was not performed when the peak measured data under the limit of average detection.
7. The emission levels of other frequencies are very lower than the limit and not show in test report.

**5. RF antenna conducted test**


**5.1. Test Equipment**

	Equipment	Manufacturer	Model No./Serial No.	Last Cal.
	Spectrum Analyzer	R&S	FSP40 / 100170	Jun, 2012
	Spectrum Analyzer	Agilent	E4407B / US39440758	Jun, 2012
X	Spectrum Analyzer	Agilent	N9010A / MY48030495	Apr., 2012

- Note:
1. All equipments are calibrated with traceable calibrations. Each calibration is traceable to the national or international standards.
  2. The test instruments marked with "X" are used to measure the final test results.

**5.2. Test Setup**

**RF antenna Conducted Measurement:**



**5.3. Limits**

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 15.205(c)).

#### **5.4. Test Procedure**

The EUT was tested according to DTS test procedure of Jan. 2012 KDB558074 for compliance to FCC 47CFR 15.247 requirements.

Set RBW = 100 kHz, Set VBW > RBW, scan up through 10th harmonic.

#### **5.5. Uncertainty**

The measurement uncertainty


Conducted is defined as  $\pm 1.27\text{dB}$




**5.6. Test Result of RF antenna conducted test**

Product : Afterglow Universal/ XBOX360/ PS3 Wireless Dongle  
 Test Item : RF antenna conducted test  
 Test Site : No.3 OATS  
 Test Mode : Mode 1: Transmit -Ant1


**Channel 01 (2403.35MHz) 30M-1GHz**



Channel 01 (2403.35MHz) 1GHz-12GHz




Channel 01 (2403.35MHz) 12GHz-25GHz




Product : Afterglow Universal/ XBOX360/ PS3 Wireless Dongle  
 Test Item : RF antenna conducted test  
 Test Site : No.3 OATS  
 Test Mode : Mode 1: Transmit -Ant1


**Channel 20 (2441.35MHz) 30M-1GHz**



Channel 20 (2441.35MHz) 1G-12GHz




Channel 20 (2441.35MHz) 12G-25GHz




Product : Afterglow Universal/ XBOX360/ PS3 Wireless Dongle  
 Test Item : RF antenna conducted test  
 Test Site : No.3 OATS  
 Test Mode : Mode 1: Transmit -Ant1


**Channel 39 (2479.35MHz) 30M-1GHz**



### Channel 39 (2479.35MHz) 1G-12GHz



### Channel 39 (2479.35MHz) 12G-25GHz



## 6. Band Edge

### 6.1. Test Equipment

#### RF Conducted Measurement

The following test equipments are used during the band edge tests:

	Equipment	Manufacturer	Model No./Serial No.	Last Cal.
	Spectrum Analyzer	R&S	FSP40 / 100170	Jun, 2012
	Spectrum Analyzer	Agilent	E4407B / US39440758	Jun, 2012
X	Spectrum Analyzer	Agilent	N9010A / MY48030495	Apr., 2012

Note:

1. All equipments are calibrated with traceable calibrations. Each calibration is traceable to the national or international standards.
2. The test instruments marked with "X" are used to measure the final test results.

#### RF Radiated Measurement:


The following test equipments are used during the band edge tests:

Test Site	Equipment	Manufacturer	Model No./Serial No.	Last Cal.
☒ Site # 3	Bilog Antenna	Schaffner Chase	CBL6112B/2673	Sep., 2011
	X Horn Antenna	Schwarzbeck	BBHA9120D/D305	Sep., 2011
	Horn Antenna	Schwarzbeck	BBHA9170/208	Jul., 2012
	Pre-Amplifier	QTK	QTK-AMP-03 / 0003	May, 2012
	X Pre-Amplifier	QTK	AP-180C / CHM_0906076	Sep., 2012
	Pre-Amplifier	MITEQ	AMF-4D-180400-45-6P/ 925975	Mar, 2012
	X Spectrum Analyzer	Agilent	E4407B / US39440758	May, 2012
	Test Receiver	R & S	ESCS 30/ 825442/018	Sep., 2011
	X Coaxial Cable	Quietek	QTK-CABLE/ CAB5	Feb., 2012
	X Controller	Quietek	QTK-CONTROLLER/ CTRL3	N/A
X Coaxial Switch	Anritsu	MP59B/6200265729	N/A	


- Note:
1. All instruments are calibrated every one year.
  2. The test instruments marked by "X" are used to measure the final test results.

## 6.2. Test Setup

### RF Conducted Measurement



### RF Radiated Measurement:



## 6.3. Limits

Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 20dB below the level of the fundamental or to the general radiated emission limits in paragraph 15.209, whichever is the lesser attenuation.



#### **6.4. Test Procedure**

The EUT was setup according to ANSI C63.4, 2003 and tested according to DTS test procedure of Jan. 2012 KDB558074 for compliance to FCC 47CFR 15.247 requirements. The EUT is placed on a turn table which is 0.8 meter above ground. The turn table is rotated 360 degrees to determine the position of the maximum emission level. The EUT was positioned such that the distance from antenna to the EUT was 3 meters. The antenna is scanned from 1 meter to 4 meters to find out the maximum emission level. This is repeated for both horizontal and vertical polarization of the antenna. In order to find the maximum emission, all of the interface cables were manipulated according to ANSI C63.4:2003 on radiated measurement.

#### **6.5. Uncertainty**

± 3.9 dB above 1GHz

± 3.8 dB below 1GHz

## 6.6. Test Result of Band Edge

Product : Afterglow Universal/ XBOX360/ PS3 Wireless Dongle  
 Test Item : Band Edge Data  
 Test Site : No.3 OATS  
 Test Mode : Mode 1: Transmit

### Fundamental Filed Strength

Antenna Pole	Frequency [MHz]	Correction Factor [dB/m]	Reading Level [dBuV]	Emission Level [dBuV/m]	Detector
Horizontal	2403.35	31.583	63.74	95.322	Peak
Horizontal	2403.35	31.583	60.35	91.932	Average
Vertical	2403.35	30.922	61.38	92.301	Peak
Vertical	2403.35	30.922	57.61	88.531	Average

Note: 1:Spectrum Analyzer setting:

Peak detector: RBW=1MHz, VBW=1MHz

Average detector: RBW=1MHz, VBW=10Hz

### Band Edge Test Data

Antenna Pole	Test Frequency (MHz)	Fundamental (dBuV/m)	$\Delta$ (dB)	Band Edge Field Strength (dBuV/m)	Detector
Horizontal	2390	95.322	49.754	45.568	Peak
Horizontal	2390	91.932	63.685	28.247	Average
Vertical	2390	92.301	49.754	42.547	Peak
Vertical	2390	88.531	63.685	24.846	Average

Note:


The Band Edge Field Strength was calculated using the Fundamental and Conducted Band Edge measurements per the Marker-Delta Method with the following formula:

Band Edge field Strength = F -  $\Delta$


F = Fundamental field Strength (Peak or Average)

$\Delta$  = Conducted Band Edge Delta (Peak or Average)

### Peak Detector of conducted Band Edge Delta



### Average Detector of conducted Band Edge Delta



Product : Afterglow Universal/ XBOX360/ PS3 Wireless Dongle  
 Test Item : Band Edge Data  
 Test Site : No.3 OATS  
 Test Mode : Mode 1: Transmit

### Fundamental Filed Strength

Antenna Pole	Frequency [MHz]	Correction Factor [dB/m]	Reading Level [dBuV]	Emission Level [dBuV/m]	Detector
Horizontal	2479.35	32.15	61.3	93.451	Peak
Horizontal	2479.35	32.15	57.89	90.041	Average
Vertical	2479.35	31.407	61	92.407	Peak
Vertical	2479.355	31.407	57.34	88.748	Average

Note: 1:Spectrum Analyzer setting:

Peak detector: RBW=1MHz, VBW=1MHz

Average detector: RBW=1MHz, VBW=10Hz

### Band Edge Test Data

Antenna Pole	Test Frequency (MHz)	Fundamental (dBuV/m)	$\Delta$ (dB)	Band Edge Field Strength (dBuV/m)	Detector
Horizontal	2483.5	93.451	40.365	53.086	Peak
Horizontal	2483.5	90.041	50.929	39.112	Average
Vertical	2483.5	92.407	40.365	52.042	Peak
Vertical	2483.5	88.748	50.929	37.819	Average

Note:


The Band Edge Field Strength was calculated using the Fundamental and Conducted Band Edge measurements per the Marker-Delta Method with the following formula:

Band Edge field Strength = F -  $\Delta$


F = Fundamental field Strength (Peak or Average)

$\Delta$  = Conducted Band Edge Delta (Peak or Average)

### Peak Detector of conducted Band Edge Delta



### Average Detector of conducted Band Edge Delta




**7. Occupied Bandwidth**

**7.1. Test Equipment**

	Equipment	Manufacturer	Model No./Serial No.	Last Cal.
	Spectrum Analyzer	R&S	FSP40 / 100170	Jun, 2012
	Spectrum Analyzer	Agilent	E4407B / US39440758	Jun, 2012
X	Spectrum Analyzer	Agilent	N9010A / MY48030495	Apr., 2012

Note: 1. All instruments are calibrated every one year.  
 2. The test instruments marked by "X" are used to measure the final test results.

**7.2. Test Setup**



**7.3. Limits**

The minimum bandwidth shall be at least 500 kHz.

**7.4. Test Procedure**

The EUT was setup according to ANSI C63.4, 2003; tested according to DTS test procedure of Jan. 2012 KDB558074 for compliance to FCC 47CFR 15.247 requirements.

Set RBW = 1-5% of the emission bandwidth, VBW≥3\*RBW

**7.5. Uncertainty**


± 150Hz

### 7.6. Test Result of Occupied Bandwidth

Product : Afterglow Universal/ XBOX360/ PS3 Wireless Dongle  
 Test Item : Occupied Bandwidth Data  
 Test Site : No.3 OATS  
 Test Mode : Mode 1: Transmit (2403.35MHz)

Channel No.	Frequency (MHz)	Measurement Level (kHz)	Required Limit (kHz)	Result
01	2403.35	1749	>500	Pass


Figure Channel 01:



Product : Afterglow Universal/ XBOX360/ PS3 Wireless Dongle  
 Test Item : Occupied Bandwidth Data  
 Test Site : No.3 OATS  
 Test Mode : Mode 1: Transmit (2441.35MHz)

Channel No.	Frequency (MHz)	Measurement Level (kHz)	Required Limit (kHz)	Result
20	2441.35	1748	>500	Pass

**Figure Channel 20:**






Product : Afterglow Universal/ XBOX360/ PS3 Wireless Dongle  
 Test Item : Occupied Bandwidth Data  
 Test Site : No.3 OATS  
 Test Mode : Mode 1: Transmit (2479.35MHz)

Channel No.	Frequency (MHz)	Measurement Level (kHz)	Required Limit (kHz)	Result
39	2479.35	1743	>500	Pass

**Figure Channel 39:**




## 8. Power Density

### 8.1. Test Equipment

	Equipment	Manufacturer	Model No./Serial No.	Last Cal.
	Spectrum Analyzer	R&S	FSP40 / 100170	Jun, 2012
	Spectrum Analyzer	Agilent	E4407B / US39440758	Jun, 2012
X	Spectrum Analyzer	Agilent	N9010A / MY48030495	Apr., 2012

Note: 1. All equipments are calibrated every one year.  
 2. The test instruments marked by "X" are used to measure the final test results.

### 8.2. Test Setup



### 8.3. Limits

The transmitted power density averaged over any 1 second interval shall not be greater +8dBm in any 3kHz bandwidth.

### 8.4. Test Procedure

The EUT was setup according to ANSI C63.4, 2003; tested according to DTS test procedure of Jan. 2012 KDB558074 for compliance to FCC 47CFR 15.247 requirements.  
 Set RBW= 100 kHz, VBW≥300KHz, SPAN to 5-30 % greater than the EBW,  
 Scale the observed power level to an equivalent value in 3 kHz by adjusting (reducing) the measured power by a bandwidth correction factor (BWCF) where BWCF = 10log (3 kHz/100 kHz = -15.2 dB).

### 8.5. Uncertainty


± 1.27 dB

### 8.6. Test Result of Power Density

Product : Afterglow Universal/ XBOX360/ PS3 Wireless Dongle  
 Test Item : Power Density Data  
 Test Site : No.3 OATS  
 Test Mode : Mode 1: Transmit(2403.35MHz)

Channel No.	Frequency (MHz)	Measure Level (dBm)	Limit (dBm)	Result
01	2403.35	-15.385	< 8dBm	Pass


Figure Channel 01:



Product : Afterglow Universal/ XBOX360/ PS3 Wireless Dongle  
 Test Item : Power Density Data  
 Test Site : No.3OATS  
 Test Mode : Mode 1: Transmit (2441.35MHz)

Channel No.	Frequency (MHz)	Measurement Level (dBm)	Required Limit (dBm)	Result
20	2441.35	-16.301	< 8dBm	Pass


Figure Channel 20:



Product : Afterglow Universal/ XBOX360/ PS3 Wireless Dongle  
 Test Item : Power Density Data  
 Test Site : No.3 OATS  
 Test Mode : Mode 1: Transmit (2479.35MHz)

Channel No.	Frequency (MHz)	Measurement Level (dBm)	Required Limit (dBm)	Result
39	2479.35	-17.381	< 8dBm	Pass

**Figure Channel 39:**



## 9. EMI Reduction Method During Compliance Testing

No modification was made during testing.