



Product Service

Choose certainty.
Add value.

Report On

RF Exposure Assessment of the
VECTRONIC Aerospace GmbH
60105 Survey VERTEX PLUS

FCC ID: XZ5VERTEXPLUS
IC: 8020A-13604SURVEY

Document 75934743 Report 02 Issue 2

August 2016



Product Service

TÜV SÜD Product Service, Octagon House, Concorde Way, Segensworth North,
Fareham, Hampshire, United Kingdom, PO15 5RL
Tel: +44 (0) 1489 558100. Website: www.tuv-sud.co.uk

REPORT ON

RF Exposure Assessment of the
VECTRONIC Aerospace GmbH
60105 Survey VERTEX PLUS

Document 75934743 Report 02 Issue 2

August 2016

PREPARED FOR

VECTRONIC Aerospace GmbH
Carl-Scheele-Str. 12
Berlin
12489
Germany

PREPARED BY


Ryan Henley
Project Manager

APPROVED BY


Simon Bennett
Authorised Signatory

DATED

31 August 2016

This report has been up-issued to Issue 2 to include the FCC and Industry Canada ID's.



Product Service

CONTENTS

| Section | Page No |
|---|-----------|
| 1 REPORT SUMMARY | 3 |
| 1.1 Introduction | 4 |
| 1.2 Regional Requirements | 5 |
| 1.3 Product Information | 6 |
| 1.3.1 Technical Description | 6 |
| 1.3.2 Supported Features | 6 |
| 1.3.3 Antennas..... | 6 |
| 1.4 Brief Summary of Results | 7 |
| 2 TEST DETAILS | 9 |
| 2.1 Rationale for Assessment of the RF Exposure | 10 |
| 2.2 Test Result Details..... | 11 |
| 3 DISCLAIMERS AND COPYRIGHT..... | 12 |
| 3.1 Disclaimers and Copyright..... | 13 |



Product Service

SECTION 1

REPORT SUMMARY

RF Exposure Assessment of the
VECTRONIC Aerospace GmbH
60105 Survey VERTEX PLUS



Product Service

1.1 INTRODUCTION

The information contained in this report is intended to show verification of the RF Exposure Assessment of the VECTRONIC Aerospace GmbH 60105 Survey VERTEX PLUS to the requirements of the applied test specifications.

| | |
|-------------------------------|--|
| Objective | To perform RF Exposure Assessment to determine the Equipment Under Test's (EUT's) compliance of the applied rules. |
| Applicant | VECTRONIC Aerospace GmbH |
| Manufacturer | VECTRONIC Aerospace GmbH |
| Manufacturing Description | Survey VERTEX PLUS |
| Model Number(s) | 60105 |
| Test Specification/Issue/Date | CFR 47 Pt1.1310 Health Canada Safety Code 6 |



Product Service

1.2 REGIONAL REQUIREMENTS

The table below shows the regional requirements that are referenced in this test report. A full list of the requirements is shown in Annex A.

| Report Reference | Regional Requirement |
|------------------|-----------------------------|
| FCC | CFR 47 Pt1.1310 |
| IC | Health Canada Safety Code 6 |



Product Service

1.3 PRODUCT INFORMATION

1.3.1 Technical Description

The Equipment under test was a VECTRONIC Aerospace GmbH 60105 Survey VERTEX PLUS. A full technical description can be found in the manufacturer's documentation.

All reported calculations were carried out on the relevant information supplied for the 60105 Survey VERTEX PLUS to demonstrate compliance with the applied test specification(s). The sample assessed was found to comply with the requirements of the applied rules.

1.3.2 Supported Features

The following radio access technologies and frequency bands are supported by the equipment under test.

| | |
|-------------------------|----------------------------|
| Radio Access Technology | Satellite |
| Frequency Band | 1611.25 MHz to 1618.75 MHz |

1.3.3 Antennas

The following antennas are supported by the equipment under test.

| No. | Model | Gain (dBi) |
|-----|---------------|------------|
| 1 | Ceramic Patch | 3.51 |



Product Service

1.4 BRIEF SUMMARY OF RESULTS

The wireless device described within this report has been shown to be capable of compliance with the basic restrictions related to human exposure to electromagnetic fields for both General Public and Occupational. The calculations shown in this report were made in accordance the procedures specified in the applied test specification(s).

| Required Compliance Boundary (m) | |
|----------------------------------|--------------------|
| Occupational | General Population |
| 0.01 | 0.01 |

Table 1 – Compliance Boundary Results



Product Service

| Regional Requirement | Calculated RF exposure level at compliance boundary of 0.01 m | | | | | |
|----------------------|---|---------|---------------|---------|---------------|--------|
| | S Field (W/m ²) | | E Field (V/m) | | H Field (A/m) | |
| | Result | Limit | Result | Limit | Result | Limit |
| FCC* | 0.0893 | 5.0000 | N/A | N/A | N/A | N/A |
| IC | 0.8928 | 25.9106 | 18.3462 | 98.8360 | 0.0487 | 0.2622 |

* Requirement and Result in mW/cm²

Table 2 – Occupational Results

The calculations show that the EUT complies with the occupational exposure levels described in CFR 47 Pt1.1310 and Health Canada Safety Code 6 at the point of investigation, 0.01 m.

| Regional Requirement | Calculated RF exposure level at compliance boundary of 0.01 m | | | | | |
|----------------------|---|--------|---------------|---------|---------------|--------|
| | S Field (W/m ²) | | E Field (V/m) | | H Field (A/m) | |
| | Result | Limit | Result | Limit | Result | Limit |
| FCC* | 0.0893 | 1.0000 | N/A | N/A | N/A | N/A |
| IC | 0.8928 | 4.0730 | 18.3462 | 39.1826 | 0.0487 | 0.1039 |

* Requirement and Result in mW/cm²

Table 3 – General Population Results

The calculations show that the EUT complies with the occupational exposure levels described in CFR 47 Pt1.1310 and Health Canada Safety Code 6 at the point of investigation, 0.01 m.



Product Service

SECTION 2

TEST DETAILS



Product Service

2.1 RATIONALE FOR ASSESSMENT OF THE RF EXPOSURE

The aim of the assessment report is to evaluate the compliance boundary for a set of given input power(s) according to the basic restrictions (directly or indirectly via compliance with reference levels) related to human exposure to radio frequency electromagnetic fields.

The chosen assessment method to establish the compliance boundary in the far-field region is the reference method as defined in the relevant specifications.

The RF exposure assessment is based upon the following criteria:

The 60105 Survey VERTEX PLUS operates with the following transmitters active on the antenna ports shown in Section 1.3.3. For each transmitter, the Radio Access Technology (RAT), EIRP inclusive of antenna gain and duty cycle, gain of the antenna and lowest frequency of operation are shown as they contribute to the calculation of S Field, E field and H field values according to the following formulas.

The power flux (S Field):

$$S = \frac{PG_{(\theta, \phi)}}{4\pi r^2}$$

The electric field strength (E Field):

$$E = \frac{\sqrt{30PG_{(\theta, \phi)}}}{r}$$

The magnetic field strength (H Field):

$$H = \frac{E}{\eta_o}$$

Where:

P = Average Power (W)

G = Antenna Gain (dBi)

r = Distance (cm) or (m)

$\eta_o = 377$



Product Service

2.2 TEST RESULT DETAILS

The frequencies shown in the tables below have been chosen based on the lowest possible frequency that the EUT can transmit.

| Antenna Port | Tx No. | Ant No. | RAT | EIRP (W) | Duty Cycle (%) | Gain (dBi) | Frequency (MHz) | RF Exposure Level at compliance boundary of 0.01 m | | |
|--------------|--------|---------|-----------|----------|----------------|------------|-----------------|--|---------------|---------------|
| | | | | | | | | S Field (W/m ²) | E Field (V/m) | H Field (A/m) |
| 1 | 1 | 1 | Satellite | 0.001 | 0.5 | 3.51 | 1611.25 | 0.8928 | 18.3462 | 0.0487 |

Table 4 – Occupational Transmitter Summary

| Antenna Port | Tx No. | Ant No. | RAT | EIRP (W) | Duty Cycle (%) | Gain (dBi) | Frequency (MHz) | RF Exposure Level at compliance boundary of 0.01 m | | |
|--------------|--------|---------|-----------|----------|----------------|------------|-----------------|--|---------------|---------------|
| | | | | | | | | S Field (W/m ²) | E Field (V/m) | H Field (A/m) |
| 1 | 1 | 1 | Satellite | 0.001 | 0.5 | 3.51 | 1611.25 | 0.8928 | 18.3462 | 0.0487 |

Table 5 – General Population Transmitter Summary



Product Service

SECTION 3

DISCLAIMERS AND COPYRIGHT



Product Service

3.1 DISCLAIMERS AND COPYRIGHT

This report relates only to the actual item/items tested.

This report must not be reproduced, except in its entirety, without the written permission of
TÜV SÜD Product Service

© 2016 TÜV SÜD Product Service



Product Service

ANNEX A

REGIONAL REQUIREMENTS



Product Service

| Frequency Range (MHz) | S Field (mW/cm ²) | Electric Field Strength (V/m) | Magnetic Field Strength (A/m) |
|-----------------------|-------------------------------|-------------------------------|-------------------------------|
| 0 - 0.3 | - | - | - |
| 0.3 - 3 | 100 | 614 | 1.63 |
| 3 - 30 | 900/f ² | 1842/f | 4.89/f |
| 30 - 300 | 1 | 61.4 | 0.163 |
| 300 - 1500 | f/300 | - | - |
| 1500 - 100000 | 5 | - | - |

Table A.1 – CFR 47 Pt1.1310 Occupational Limits

| Frequency Range (MHz) | S Field (mW/cm ²) | Electric Field Strength (V/m) | Magnetic Field Strength (A/m) |
|-----------------------|-------------------------------|-------------------------------|-------------------------------|
| 0 - 0.3 | - | - | - |
| 0.3 - 3 | 100 | 614 | 1.63 |
| 3 - 30 | 180/f ² | 824/f | 2.19/f |
| 30 - 300 | 0.2 | 27.5 | 0.073 |
| 300 - 1500 | f/1500 | - | - |
| 1500 - 100000 | 1 | - | - |

Table A.2 – CFR 47 Pt1.1310 General Population Limits

| Frequency Range (MHz) | Power Density (W/m ²) | Electric Field Strength (V/m) | Magnetic Field Strength (A/m) |
|-----------------------|-----------------------------------|-------------------------------|-------------------------------|
| 10 - 20 | 10 | 61.4 | 0.163 |
| 20 - 48 | 44.72/f ^{0.5} | 129.8/f ^{0.25} | 0.3444/f ^{0.25} |
| 48 - 100 | 6.455 | 49.33 | 0.1309 |
| 100 - 6000 | 0.6455*f ^{0.5} | 15.60*f ^{0.25} | 0.04138*f ^{0.25} |
| 6000 - 150000 | 50 | 137 | 0.364 |

Table A.3 – Health Canada Safety Code 6 Occupational Limits

| Frequency Range (MHz) | Power Density (W/m ²) | Electric Field Strength (V/m) | Magnetic Field Strength (A/m) |
|-----------------------|-----------------------------------|-------------------------------|-------------------------------|
| 10 - 20 | 2 | 27.46 | 0.0728 |
| 20 - 48 | 8.944/f ^{0.5} | 58.07/f ^{0.25} | 0.1540/f ^{0.25} |
| 48 - 300 | 1.291 | 22.06 | 0.05852 |
| 300 - 6000 | 0.02619*f ^{0.6834} | 3.142*f ^{0.3417} | 0.008335*f ^{0.3417} |
| 6000 - 15000 | 10 | 61.4 | 0.163 |

Table A.4 – Health Canada Safety Code 6 General Population Limits