



Shenzhen Asia Test Technology Co., Ltd.

7 / F, Xinwei Building, Gushu Village, Xixiang Town, Baoan
District, Shenzhen, China
Tel: +86)-0755-23284990
Email: att@att-lab.com
Http: www.att-lab.cn

Report No. ATT-2015SZ0127013F
- Page 1 of 50 -

FCC RADIO TEST REPORT

FCC ID: X6HBS057RQ

Product : BLUETOOTH HEADSET

Trade Name : N/A

Model Name : BS057RQ

Serial Model : MAGsmart Metallic, BS058F

Prepared for

Alpha Comm Enterprises, Inc.

1500 Lakes Parkway, Suite B Lawrenceville Georgia USA.

Prepared by

Shenzhen Asia Test Technology Co.,Ltd.

7 / F, Xinwei Building, Gushu Village, Xixiang Town, Baoan District,
Shenzhen, China

Tel: +(86)-0755-23284990 Fax: +(86)-0755-23284990
Http: www.att-lab.cn

This document cannot be reproduced except in full, without prior written approval of ATT. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.



Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2015SZ0127013F
- Page 2 of 50 -

TEST RESULT CERTIFICATION

Applicant's name Alpha Comm Enterprises, Inc.

Address 1500 Lakes Parkway, Suite B Lawrenceville Georgia USA.

Manufacture's Name GuangZhou U&I Electronic Technology Co.,Ltd

Address 3rd Floor, Building G, FengSheng Industrial Zone, ShiBei Industrial Road, HuiJiang, Da Shi Street, PanYu District, Guangzhou, China

Product description

Product name BLUETOOTH HEADSET

Model and/or type reference BS057RQ

Additional Model MAGsmart Metallic, BS058F

Standards FCC Part15.247

Test procedure ANSI C63.10

This device described above has been tested by ATT, and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.

This report shall not be reproduced except in full, without the written approval of ATT, this document may be altered or revised by ATT, personal only, and shall be noted in the revision of the document.

Date of Test

Date (s) of performance of tests Jan. 22 2015 ~Jan. 30 2015

Date of Issue Jan. 30 2015

Test Result **Pass**

Tested by: Eric Wang
Eric Wang
Project Leader

Reviewed by: Jerry You
Jerry You
Laboratory Supervisor

Approved by: Jack Yu
Jack Yu
Technical Director



Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2015SZ0127013F
- Page 3 of 50 -

Table of Contents

| | Page |
|---|-----------|
| 1 . SUMMARY OF TEST RESULTS | 6 |
| 1.1 TEST FACILITY | 7 |
| 1.2 MEASUREMENT UNCERTAINTY | 7 |
| 1.3 TEST ENVIRONMENT CONDITION | 7 |
| 2 . GENERAL INFORMATION | 8 |
| 2.1 GENERAL DESCRIPTION OF EUT | 8 |
| 3 EUT CONFIGURATIONS | 9 |
| 3.1 GENERAL CONFIGURATIONS | 9 |
| 3.2 CUSTOMIZED CONFIGURATIONS | 9 |
| 3.3 TEST ENVIRONMENTS | 9 |
| 3.4 TEST SETUPS | 9 |
| 3.5 TEST CONDITIONS | 12 |
| 3.6 EQUIPMENTS LIST FOR ALL TEST ITEMS | 14 |
| 4 . EMC EMISSION TEST | 15 |
| 4.1 CONDUCTED EMISSION MEASUREMENT | 15 |
| 4.1.1 TEST RESULTS | 16 |
| 4.2 RADIATED EMISSION MEASUREMENT | 18 |
| 4.2.1 RADIATED EMISSION LIMITS | 18 |
| 4.2.2 TEST PROCEDURE | 19 |
| 4.2.3 DEVIATION FROM TEST STANDARD | 19 |
| 4.2.4 TEST SETUP | 20 |
| 4.2.5 EUT OPERATING CONDITIONS | 21 |
| 4.2.6 TEST RESULTS (BELOW 30 MHZ) | 22 |
| 4.2.7 TEST RESULTS (BETWEEN 30M – 1000 MHZ) | 23 |
| 4.2.8 TEST RESULTS (ABOVE 1000 MHZ) | 24 |
| 5 . NUMBER OF HOPPING CHANNEL | 30 |
| 5.1 APPLIED PROCEDURES / LIMIT | 30 |
| 5.1.1 TEST PROCEDURE | 30 |
| 5.1.2 DEVIATION FROM STANDARD | 30 |



Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2015SZ0127013F
- Page 4 of 50 -

Table of Contents

| | Page |
|--|-----------|
| 5.1.3 TEST SETUP | 30 |
| 5.1.4 EUT OPERATION CONDITIONS | 30 |
| 5.1.5 TEST RESULTS | 31 |
| 6 . AVERAGE TIME OF OCCUPANCY | 32 |
| 6.1 APPLIED PROCEDURES / LIMIT | 32 |
| 6.1.1 TEST PROCEDURE | 32 |
| 6.1.2 TEST SETUP | 32 |
| 6.1.3 TEST RESULTS | 33 |
| 7 . HOPPING CHANNEL SEPARATION MEASUREMENT | 34 |
| 7.1 APPLIED PROCEDURES / LIMIT | 34 |
| 7.1.1 TEST PROCEDURE | 34 |
| 7.1.2 DEVIATION FROM STANDARD | 34 |
| 7.1.3 TEST SETUP | 34 |
| 7.1.4 EUT OPERATION CONDITIONS | 34 |
| 7.1.5 TEST RESULTS | 35 |
| 8 . BANDWIDTH TEST | 37 |
| 8.1 APPLIED PROCEDURES / LIMIT | 37 |
| 8.1.1 TEST PROCEDURE | 37 |
| 8.1.2 DEVIATION FROM STANDARD | 37 |
| 8.1.3 TEST SETUP | 37 |
| 8.1.4 EUT OPERATION CONDITIONS | 37 |
| 8.1.5 TEST RESULTS | 38 |
| 9 . PEAK OUTPUT POWER TEST | 40 |
| 9.1 APPLIED PROCEDURES / LIMIT | 40 |
| 9.1.1 TEST PROCEDURE | 40 |
| 9.1.2 DEVIATION FROM STANDARD | 40 |
| 9.1.3 TEST SETUP | 40 |
| 9.1.4 EUT OPERATION CONDITIONS | 40 |
| 9.1.5 TEST RESULTS | 41 |
| 10 . 100 KHZ BANDWIDTH OF FREQUENCY BAND EDGE | 43 |
| 10.1 DEVIATION FROM STANDARD | 43 |
| 10.2 TEST SETUP | 44 |



Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2015SZ0127013F
- Page 5 of 50 -

Table of Contents

| | Page |
|---|-----------|
| 10.3 EUT OPERATION CONDITIONS | 44 |
| 10.4 TEST RESULTS | 45 |
| 11 . ANTENNA REQUIREMENT | 48 |
| 11.1 STANDARD REQUIREMENT | 48 |
| 11.2 EUT ANTENNA | 48 |
| 12 . EUT TEST PHOTO | 49 |
| APPENDIX-PHOTOGRAPHS OF EUT CONSTRUCTIONAL DETAILS | |



Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2015SZ0127013F
- Page 6 of 50 -

1. SUMMARY OF TEST RESULTS

Test procedures according to the technical standards:

| Test Item | FCC Part No. | Requirements | Verdict |
|--|---------------------|--|---------|
| 20dB Emission Bandwidth (EBW) | 15.247(a)(1) | No limit. | PASS |
| Carrier Frequency Separation | 15.247(a)(1) | $\geq \text{MAX}\{25\text{kHz}, \text{IF}\{\text{output power} \leq 125\text{mW}, 2/3 \times 20\text{dB EBW}, 20\text{dB EBW}\}\}$. | PASS |
| Number of Hopping Channel | 15.247(a)(1)(iii) | ≥ 15 channels. | PASS |
| Time of Occupancy (Dwell Time) | 15.247(a)(1)(iii) | $< 0.4\text{s}$ within a period of $(0.4\text{s} \times \text{hopping number})$. | PASS |
| Maximum Peak Conducted Output Power | 15.247(b)(1) | $< 1\text{W}$ if using ≥ 75 Non-overlapping channels. | PASS |
| Band edge spurious emission | 15.247(d) | $< -20 \text{ dBc}/100\text{kHz}$ if total peak power \leq power limit. | PASS |
| Conducted RF Spurious Emission | 15.247(d) | $< -20 \text{ dBc}/100\text{kHz}$ if total peak power \leq power limit. | PASS |
| Radiated Emissions in the Restricted Bands | 15.247(d) 15.209 | FCC Part 15.209 field strength limit; | PASS |
| AC Power Line Conducted Emissions | 15.207 | FCC Part 15.207 conducted limit; | PASS |



Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2015SZ0127013F
- Page 7 of 50 -

1.1 TEST FACILITY

Shenzhen Asia Test Technology Co.,Ltd.

7 / F, Xinwei Building, Gushu Village, Xixiang Town, Baoan District, Shenzhen, China

FCC Registration No.: 348715; IC Registration No.: 12198A

1.2 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement $y \pm U$, where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95 % .

| No. | Item | Uncertainty |
|-----|------------------------------|-------------------------|
| 1 | Conducted Emission Test | $\pm 1.38\text{dB}$ |
| 2 | RF power,conducted | $\pm 0.16\text{dB}$ |
| 3 | Spurious emissions,conducted | $\pm 0.21\text{dB}$ |
| 4 | All emissions,radiated(<1G) | $\pm 4.68\text{dB}$ |
| 5 | All emissions,radiated(>1G) | $\pm 4.89\text{dB}$ |
| 6 | Temperature | $\pm 0.5^\circ\text{C}$ |
| 7 | Humidity | $\pm 2\%$ |

1.3 TEST ENVIRONMENT CONDITION

Ambient Temperature: 19.5to 25°C

Ambient Relative Humidity: 40 to 55 %

Atmospheric Pressure: Not applicable



Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2015SZ0127013F
- Page 8 of 50 -

2. GENERAL INFORMATION

2.1 GENERAL DESCRIPTION OF EUT

| | |
|------------------|--|
| Equipment | BLUETOOTH HEADSET |
| Model Name | BS057RQ |
| Serial Model | MAGsmart Metallic, BS058F |
| Model Difference | All models are identical except model name. |
| Frequency Range | 2402 ~ 2480 MHz |
| BT versions | V3.0 |
| Modulation Type | GFSK |
| Antenna Type | Internal |
| Antenna Gain | 2 dBi |
| Ratings | 5.0Vdc (for charge) 3.7Vdc (Li-ion battery) |
| Adapter | N/A |
| Battery | DC 3.7V |

| Channel List | | | | | |
|--------------|-----------------|---------|-----------------|---------|-----------------|
| Channel | Frequency (MHz) | Channel | Frequency (MHz) | Channel | Frequency (MHz) |
| 00 | 2402 | 27 | 2429 | 54 | 2456 |
| 01 | 2403 | 28 | 2430 | 55 | 2457 |
| 02 | 2404 | 29 | 2431 | 56 | 2458 |
| 03 | 2405 | 30 | 2432 | 57 | 2459 |
| 04 | 2406 | 31 | 2433 | 58 | 2460 |
| 05 | 2407 | 32 | 2434 | 59 | 2461 |
| 06 | 2408 | 33 | 2435 | 60 | 2462 |
| 07 | 2409 | 34 | 2436 | 61 | 2463 |
| 08 | 2410 | 35 | 2437 | 62 | 2464 |
| 09 | 2411 | 36 | 2438 | 63 | 2465 |
| 10 | 2412 | 37 | 2439 | 64 | 2466 |
| 11 | 2413 | 38 | 2440 | 65 | 2467 |
| 12 | 2414 | 39 | 2441 | 66 | 2468 |
| 13 | 2415 | 40 | 2442 | 67 | 2469 |
| 14 | 2416 | 41 | 2443 | 68 | 2470 |
| 15 | 2417 | 42 | 2444 | 69 | 2471 |
| 16 | 2418 | 43 | 2445 | 70 | 2472 |
| 17 | 2419 | 44 | 2446 | 71 | 2473 |
| 18 | 2420 | 45 | 2447 | 72 | 2474 |
| 19 | 2421 | 46 | 2448 | 73 | 2475 |
| 20 | 2422 | 47 | 2449 | 74 | 2476 |
| 21 | 2423 | 48 | 2450 | 75 | 2477 |
| 22 | 2424 | 49 | 2451 | 76 | 2478 |
| 23 | 2425 | 50 | 2452 | 77 | 2479 |
| 24 | 2426 | 51 | 2453 | 78 | 2480 |
| 25 | 2427 | 52 | 2454 | | |
| 26 | 2428 | 53 | 2455 | | |



Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2015SZ0127013F
- Page 9 of 50 -

3 EUT CONFIGURATIONS

3.1 GENERAL CONFIGURATIONS

| Configuration | Description |
|---------------------|---|
| Test Antenna Ports | Until otherwise specified, All TX tests are performed at all TX antenna ports of the EUT. |
| Multiple RF Sources | Other than the tested RF source of the EUT, other RF source(s) are disabled or shutdown during measurements. |

Note: The EUT was programmed to be in continuously transmitting mode and the transmit duty cycle is not less than 98%. Measurements are performed according to the Public Notice-DA 00-705.

3.2 CUSTOMIZED CONFIGURATIONS

| #EUT Conf. | Signal Description | Operating Frequency |
|--------------|---|---------------------|
| TM1_DH5_Hop | GFSK modulation, package type DH5, hopping on. | --- |
| TM1_DH5_Ch0 | GFSK modulation, package type DH5, hopping off. | Ch No. 00 /2402MHz |
| TM1_DH5_Ch39 | GFSK modulation, package type DH5, hopping off. | Ch No. 39/ 2441MHz |
| TM1_DH5_Ch78 | GFSK modulation, package type DH5, hopping off. | Ch No. 78/ 2480MHz |

3.3 TEST ENVIRONMENTS


NOTE: The values used in the test report maybe stringent than the declared.

| Environment Parameter | Selected Values During Tests | | |
|-----------------------|------------------------------|-------------------|------------------------------|
| NTNV | Temperature Ambient | Voltage 3.7VDC | Relative Humidity Ambient |

3.4 TEST SETUPS

3.4.1 POWER LINE CONDUCTED EMISSION LIMITS

The EUT is controlled by PC/software to emit the specified signals for the purpose of measurements.



This document cannot be reproduced except in full, without prior written approval of ATT. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.




Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2015SZ0127013F
- Page 10 of 50 -

3.4.2 Test Setup 2

The test sites anechoic chamber has met the requirement of NSA tolerance 4dB according to the standards: ANSIC63.4. The test distance is 3m. The setup is according to ANSI C63.4 and CAN/CSA-CEI/IEC CISPR 22.


The maximal emission value is acquired by adjusting the antenna height, polarization and turntable azimuth. Normally, the height range of antenna is 1m to 4m, the azimuth range of turntable is 0° to 360°, and the receive antenna has two polarizations Vertical (V) and Horizontal (H).





Shenzhen Asia Test Technology Co., Ltd.


Report No. ATT-2015SZ0127013F
- Page 11 of 50 -



3.4.3 Test Setup 3

The mains cable of the EUT (maybe per AC/DC Adapter) must be connected to LISN. The LISN shall be placed 0.8 m from the boundary of EUT and bonded to a ground reference plane for LISN mounted on top of the ground reference plane. This distance is between the closest points of the LISN and the EUT. All other units of the EUT and associated equipment shall be least 0.8m from the LISN.

Ground connections, where required for safety purposes, shall be connected to the reference ground point of the LISN and, where not otherwise provided or specified by the manufacturer, shall be of same length as the mains cable and run parallel to the mains connection at a separation distance of not more than 0.1 m.





Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2015SZ0127013F
- Page 12 of 50 -

3.5 TEST CONDITIONS

| Test Case | Test Conditions | |
|--|------------------|--|
| | Configuration | Description |
| 20dB Emission Bandwidth (EBW) | Meas. Method | ANSI C63.10:2009 |
| | Test Environment | NTNV |
| | Test Setup | Test Setup1 |
| | EUT Conf. | TM1_DH5_Ch00, TM1_DH5_Ch39, TM1_DH5_Ch78 TM4_DH5_Ch00, TM4_DH5_Ch19, TM4_DH5_Ch39. |
| Carrier Frequency Separation | Meas. Method | ANSI C63.10:2009 |
| | Test Environment | NTNV |
| | Test Setup | Test Setup1 |
| | EUT Conf. | TM1_DH5_Hop |
| Number of Hopping Channel | Meas. Method | ANSI C63.10:2009 |
| | Test Environment | NTNV |
| | Test Setup | Test Setup1 |
| | EUT Conf. | TM1_DH5_Hop |
| Time of Occupancy (Dwell Time) | Meas. Method | ANSI C63.10:2009 |
| | Test Environment | NTNV |
| | Test Setup | Test Setup1 |
| | EUT Conf. | TM1_DH5_Ch39 |
| Maximum Peak Conducted Output Power | Meas. Method | ANSI C63.10:2009 |
| | Test Environment | NTNV |
| | Test Setup | Test Setup1 |
| | EUT Conf. | TM1_DH3_Ch00, TM1_DH3_Ch39, TM1_DH3_Ch78 TM4_DH3_Ch00, TM4_DH3_Ch19, TM4_DH3_Ch39. |
| Bandedge spurious emission (Conducted) | Meas. Method | ANSI C63.10:2009 |
| | Test Environment | NTNV |
| | Test Setup | Test Setup1 |
| | EUT Conf. | TM1_DH3_Ch00, TM1_DH3_Ch78 TM4_DH3_Ch00, TM4_DH3_Ch39. |
| Conducted RF Spurious Emission | Meas. Method | ANSI C63.10:2009 |
| | Test Environment | NTNV |
| | Test Setup | Test Setup1 |
| | EUT Conf. | TM1_DH5_Ch00, TM1_DH5_Ch39, TM1_DH5_Ch78, TM2_2DH5_Ch00, TM4_DH5_Ch00, TM4_DH5_Ch19, TM4_DH5_Ch39. |
| Radiated Emissions in the Restricted Bands | Meas. Method | ANSI C63.10:2009 30 MHz to 1 GHz: Pre: RBW=100kHz; VBW=300kHz; Det. = |

This document cannot be reproduced except in full, without prior written approval of ATT. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.



Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2015SZ0127013F
- Page 13 of 50 -

| | | |
|--|------------------|---|
| | | Peak. Final: RBW=120kHz; Det. = CISPR Quasi-Peak. 1 GHz to 26.5GHz: Average: RBW=1 MHz; VBW= 10Hz; Det. = Peak; Sweep-time= Auto; Trace = Single. Peak: RBW=1 MHz; VBW= 3 MHz; Det. = Peak; Sweep-time= Auto; Trace≥ MaxHold * 100. |
| | Test Environment | NTNV |
| | Test Setup | Test Setup2 |
| | EUT Conf. | 30 MHz-1GHz TM1_DH5_Ch00 (Worst Conf.). 1-18 GHz: TM1_DH5_Ch00, TM1_DH5_Ch39, TM1_DH5_Ch78, (Worst Conf.). |

| Test Case | Test Conditions | |
|-----------------------------------|--------------------|------------------------------|
| | Configuration | Description |
| AC Power Line Conducted Emissions | Measurement Method | AC mains conducted. |
| | Test Environment | NTNV |
| | Test Setup | TestSetup3 |
| | EUT Configuration | TM1_DH5_Ch39. (Worst Conf.). |

Note: For Radiated Emissions, By preliminary testing and verifying three axis (X, Y and Z) position of EUT transmitted status, it was found that "Z axis" position was the worst, then the final test was executed the worst condition and test data were recorded in this report.



Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2015SZ0127013F
- Page 14 of 50 -

3.6 EQUIPMENTS LIST FOR ALL TEST ITEMS

Radiation Test equipment

| Item | Kind of Equipment | Manufacturer | Type No. | Serial No. | Last calibration | Calibrated until | Calibration period |
|------|--------------------|--------------|-------------|--------------|------------------|------------------|--------------------|
| 1 | Spectrum Analyzer | Agilent | E4407B | MY45108040 | 2014.07.06 | 2015.07.05 | 1 year |
| 2 | Test Receiver | R&S | ESPI | 101318 | 2014.06.07 | 2015.06.06 | 1 year |
| 3 | Bilog Antenna | TESEQ | CBL6111D | 31216 | 2014.07.06 | 2015.07.05 | 1 year |
| 4 | 50Ω Coaxial Switch | Anritsu | MP59B | 6200264416 | 2014.06.07 | 2015.06.06 | 1 year |
| 5 | Spectrum Analyzer | ADVANTEST | R3132 | 150900201 | 2014.06.07 | 2015.06.06 | 1 year |
| 6 | Horn Antenna | EM | EM-AH-10180 | 2011071402 | 2014.07.06 | 2015.07.05 | 1 year |
| 7 | Horn Ant | Schwarzbeck | BBHA 9170 | 9170-181 | 2014.07.06 | 2015.07.05 | 1 year |
| 8 | Amplifier | EM | EM-30180 | 060538 | 2014.12.22 | 2015.12.21 | 1 year |
| 9 | Loop Antenna | ARA | PLA-1030/B | 1029 | 2014.06.08 | 2015.06.07 | 1 year |
| 10 | Power Meter | R&S | NRVS | 100696 | 2014.07.06 | 2015.07.05 | 1 year |
| 11 | Power Sensor | R&S | URV5-Z4 | 0395.1619.05 | 2014.07.06 | 2015.07.05 | 1 year |
| 12 | Test Receiver | R&S | FSU | 550062 | 2014.06.07 | 2015.06.06 | 1 year |
| 13 | Cable 30-1000MHz | R&S | ATT-R01 | 201309R001 | 2014.06.08 | 2015.06.07 | 1 year |
| 14 | Cable 1-26.5GHz | R&S | ATT-R02 | 201309R048 | 2014.06.08 | 2015.06.07 | 1 year |

Conduction Test equipment

| Item | Kind of Equipment | Manufacturer | Type No. | Serial No. | Last calibration | Calibrated until | Calibration period |
|------|-----------------------|--------------|----------|------------|------------------|------------------|--------------------|
| 1 | Test Receiver | R&S | ESCI | 101160 | 2014.06.06 | 2015.06.05 | 1 year |
| 2 | LISN | R&S | ENV216 | 101313 | 2014.08.24 | 2015.08.23 | 1 year |
| 3 | LISN | EMCO | 3816/2 | 00042990 | 2014.08.24 | 2015.08.23 | 1 year |
| 4 | 50Ω Coaxial Switch | Anritsu | MP59B | 6200264417 | 2014.06.07 | 2015.06.06 | 1 year |
| 5 | Passive Voltage Probe | R&S | ESH2-Z3 | 100196 | 2014.06.07 | 2015.06.06 | 1 year |
| 6 | Absorbing clamp | R&S | MOS-21 | 100423 | 2014.06.08 | 2015.06.07 | 1 year |
| 7 | Cable 0.009-30MHz | R&S | ATT-C01 | 201309C006 | 2014.06.08 | 2015.06.07 | 1 year |



Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2015SZ0127013F
- Page 15 of 50 -

4. EMC EMISSION TEST

4.1 CONDUCTED EMISSION MEASUREMENT

TEST PROCEDURE

1. The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. The EUT is a tabletop system; a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per ANSI C63.10-2009.
2. Support equipment, if needed, was placed as per ANSI C63.10-2009
3. All I/O cables were positioned to simulate typical actual usage as per ANSI C63.10-2009
4. The EUT received DC5V power from the adapter, the adapter received AC120V/60Hz power through a Line Impedance Stabilization Network (LISN) which supplied power source and was grounded to the ground plane.
5. All support equipments received AC power from a second LISN, if any.
6. The EUT test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum Analyzer / Receiver connected to the LISN powering the EUT. The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side). Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50 ohm load; the second scan had Line 1 connected to a 50 ohm load and Line 2 connected to the Analyzer / Receiver.
7. Analyzer / Receiver scanned from 150 KHz to 30MHz for emissions in each of the test modes.
8. During the above scans, the emissions were maximized by cable manipulation.

AC Power Conducted Emission Limit

For intentional device, according to § 15.207(a) AC Power Conducted Emission Limits is as following :

| Frequency (MHz) | Maximum RF Line Voltage (dB μ V) | | | |
|--------------------|--------------------------------------|------|---------|--------|
| | CLASS A | | CLASS B | |
| | Q.P. | Ave. | Q.P. | Ave. |
| 0.15 - 0.50 | 79 | 66 | 66-56* | 56-46* |
| 0.50 - 5.00 | 73 | 60 | 56 | 46 |
| 5.00 - 30.0 | 73 | 60 | 60 | 50 |

* Decreasing linearly with the logarithm of the frequency

TEST RESULTS

Note: We tested Conducted Emission of GFSK mode from 0.15 KHz to 30MHz (DH1, DH3 and DH5) and all channels (low, middle and high), recorded the worst case data at GFSK DH5 middle channel.



Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2015SZ0127013F
- Page 16 of 50 -


4.1.1 TEST RESULTS

| | | | |
|----------------|------------------------------------|---------------------|---------|
| EUT : | BLUETOOTH HEADSET | Model Name : | BS057RQ |
| Temperature : | 26 °C | Relative Humidity : | 54% |
| Pressure : | 1010hPa | Phase : | L |
| Test Voltage : | DC 5V from adapter AC 120V/60Hz | Test Mode : | BT LINK |

| Frequency (MHz) | Meter Reading (dB μ V) | Factor (dB) | Emission Level (dB μ V) | Limits (dB μ V) | Margin (dB) | Detector Type |
|--------------------|-------------------------------|----------------|--------------------------------|------------------------|----------------|---------------|
| 0.4299 | 30.01 | 10.41 | 40.42 | 47.25 | -6.83 | AVG |
| 0.798 | 38.24 | 10.41 | 48.65 | 56 | -7.35 | QP |
| 1.2259 | 30.86 | 10.41 | 41.27 | 46 | -4.73 | AVG |
| *1.234 | 41.49 | 10.41 | 51.9 | 56 | -4.1 | QP |
| 1.9739 | 24.33 | 10.42 | 34.75 | 46 | -11.25 | AVG |
| 2.042 | 37.43 | 10.42 | 47.85 | 56 | -8.15 | QP |

Remark:

1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.
3. '*' means the worst case





Shenzhen Asia Test Technology Co., Ltd.


Report No. ATT-2015SZ0127013F
- Page 17 of 50 -

| | | | |
|----------------|------------------------------------|---------------------|---------|
| EUT : | BLUETOOTH HEADSET | Model Name : | BS057RQ |
| Temperature : | 26 °C | Relative Humidity : | 54% |
| Pressure : | 1010hPa | Phase : | N |
| Test Voltage : | DC 5V from adapter AC 120V/60Hz | Test Mode : | BT LINK |

| Frequency (MHz) | Meter Reading (dB μ V) | Factor (dB) | Emission Level (dB μ V) | Limits (dB μ V) | Margin (dB) | Detector Type |
|--------------------|-------------------------------|----------------|--------------------------------|------------------------|----------------|---------------|
| | | | | | | |
| 0.562 | 37.66 | 10.4 | 48.06 | 56 | -7.94 | QP |
| 0.622 | 26.18 | 10.41 | 36.59 | 46 | -9.41 | AVG |
| *1.186 | 41.16 | 10.41 | 51.57 | 56 | -4.43 | QP |
| 1.242 | 29.86 | 10.41 | 40.27 | 46 | -5.73 | AVG |
| 1.97 | 37.73 | 10.42 | 48.15 | 56 | -7.85 | QP |
| 1.986 | 23.04 | 10.42 | 33.46 | 46 | -12.54 | AVG |

Remark:

1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.
3. ** means the worst case





Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2015SZ0127013F
- Page 18 of 50 -

4.2 RADIATED EMISSION MEASUREMENT

4.2.1 RADIATED EMISSION LIMITS (Frequency Range 9kHz-1000MHz)

20dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

| Frequencies (MHz) | Field Strength (micorvolts/meter) | Measurement Distance (meters) |
|-------------------|-----------------------------------|-------------------------------|
| 0.009~0.490 | 2400/F(KHz) | 300 |
| 0.490~1.705 | 24000/F(KHz) | 30 |
| 1.705~30.0 | 30 | 30 |
| 30~88 | 100 | 3 |
| 88~216 | 150 | 3 |
| 216~960 | 200 | 3 |
| Above 960 | 500 | 3 |

Notes:

- (1) The limit for radiated test was performed according to FCC PART 15C.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).

| Spectrum Parameter | Setting |
|---------------------------------------|--|
| Attenuation | Auto |
| Start Frequency | 1000 MHz |
| Stop Frequency | 10 th carrier harmonic |
| RB / VB (emission in restricted band) | 1 MHz / 1 MHz for Peak, 1 MHz / 10Hz for Average |

| Receiver Parameter | Setting |
|------------------------|----------------------------------|
| Attenuation | Auto |
| Start ~ Stop Frequency | 9kHz~150kHz / RB 200Hz for QP |
| Start ~ Stop Frequency | 150kHz~30MHz / RB 9kHz for QP |
| Start ~ Stop Frequency | 30MHz~1000MHz / RB 120kHz for QP |



Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2015SZ0127013F
- Page 19 of 50 -

4.2.2 TEST PROCEDURE

- a. The measuring distance of at 3 m shall be used for measurements at frequency up to 1GHz. For frequencies above 1GHz, any suitable measuring distance may be used.
- b. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter open area test site. The table was rotated 360 degrees to determine the position of the highest radiation.
- c. The height of the equipment or of the substitution antenna shall be 0.8 m; the height of the test antenna shall vary between 1 m to 4 m. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- e. If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed.
- f. For the actual test configuration, please refer to the related Item –EUT Test Photos.

Note:

Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported

4.2.3 DEVIATION FROM TEST STANDARD

No deviation




Shenzhen Asia Test Technology Co., Ltd.


Report No. ATT-2015SZ0127013F
- Page 20 of 50 -

4.2.4 TEST SETUP

(A) Radiated Emission Test-Up Frequency Below 30MHz



(B) Radiated Emission Test-Up Frequency 30MHz~1GHz






Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2015SZ0127013F
- Page 21 of 50 -

(C) Radiated Emission Test-Up Frequency Above 1GHz



4.2.5 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.



Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2015SZ0127013F
- Page 22 of 50 -

4.2.6 TEST RESULTS (BELOW 30 MHZ)

| | | | |
|---------------|-------------------|---------------------|---------|
| EUT : | BLUETOOTH HEADSET | Model Name : | BS057RQ |
| Temperature : | 20 °C | Relative Humidity : | 48% |
| Pressure : | 1010 hPa | Test Voltage : | DC 3.7V |
| Test Mode : | TX | Polarization : | --- |

| Freq. (MHz) | Reading (dBuV/m) | Limit (dBuV/m) | Margin (dB) | State |
|----------------|---------------------|-------------------|----------------|-------|
| -- | -- | -- | -- | P |
| -- | -- | -- | -- | P |

NOTE:

The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

Distance extrapolation factor = $20 \log(\text{specific distance}/\text{test distance})$ (dB);
Limit line = specific limits(dBuV) + distance extrapolation factor.



Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2015SZ0127013F
- Page 23 of 50 -

4.2.7 TEST RESULTS (BETWEEN 30M – 1000 MHZ)

| | | | |
|----------------|-------------------|---------------------|---------|
| EUT : | BLUETOOTH HEADSET | Model Name : | BS057RQ |
| Temperature : | 24 °C | Relative Humidity : | 54% |
| Pressure : | 1010hPa | Test Mode : | TX 2402 |
| Test Voltage : | DC 3.7V | | |

| Polar (H/V) | Frequency | Meter Reading | Factor | Emission Level | Limits | Margin | Detector Type |
|----------------|-----------|------------------|--------|-------------------|----------|--------|------------------|
| | (MHz) | (dBuV) | (dB) | (dBuV/m) | (dBuV/m) | (dB) | |
| V | 57.48 | 21.65 | 10.22 | 31.87 | 40 | -8.13 | QP |
| V | 133.39 | 24.56 | 10.73 | 35.29 | 40 | -4.71 | QP |
| V | 241.39 | 17.68 | 12.55 | 30.23 | 47 | -16.77 | QP |
| V | 337.25 | 16.55 | 15.73 | 32.28 | 47 | -14.72 | QP |
| V | 421.37 | 15.36 | 16.14 | 31.5 | 46 | -14.5 | QP |
| V | 488.63 | 17.94 | 16.75 | 34.69 | 46 | -11.31 | QP |
| H | 66.73 | 20.33 | 9.35 | 29.68 | 40 | -10.32 | QP |
| H | 157.37 | 22.19 | 9.76 | 31.95 | 40 | -8.05 | QP |
| H | 198.36 | 21.27 | 10.62 | 31.89 | 46 | -14.11 | QP |
| H | 400.26 | 20.65 | 11.73 | 32.38 | 46 | -13.62 | QP |
| H | 478.81 | 22.18 | 12.84 | 35.02 | 46 | -10.98 | QP |
| H | 553.27 | 20.33 | 14.94 | 35.27 | 47 | -11.73 | QP |

Remark:

Absolute Level= ReadingLevel+ Factor, Margin= Absolute Level - Limit



Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2015SZ0127013F
- Page 24 of 50 -

4.2.8 TEST RESULTS (ABOVE 1000 MHZ)

Remark:

1. The radiated measurement are performed the each channel (low/mid/high) at all Packet type (DH1, DH3 and DH5) also for GFSK modulation type , recorded worst case at GFSK_DH5_Low channel (Channel 00), GFSK_DH5_Middle channel (Channel 39), GFSK_DH5_High channel (Channel 78).
2. ULTRA-BROADBAND ANTENNA for the radiation emission test below 1G.
3. HORN ANTENNA for the radiation emission test above 1G.
4. We tested both battery powered and powered by adapter charging mode at three orientate ones, recorded worst case at powered by adapter charging mode.
5. “---” means not recorded as emission levels lower than limit.

| Low Channel (2402 MHz)-Above 1G | | | | | | | |
|----------------------------------|----------------------------|----------------|-------------------------------|--------------------|----------------|------------------|----------------|
| Frequency (MHz) | Meter Reading (dBuV) | Factor (dB) | Emission Level (dBuV/m) | Limits (dBuV/m) | Margin (dB) | Detector Type | Polar (H/V) |
| 4803.98 | 53.63 | -3.26 | 50.37 | 74 | -23.63 | Pk | Vertical |
| 4803.98 | 40.84 | -3.26 | 37.58 | 54 | -16.42 | Av | Vertical |
| 7206.14 | 51.37 | -2.31 | 49.06 | 74 | -24.94 | Pk | Vertical |
| 7206.14 | 38.39 | -2.31 | 36.08 | 54 | -17.92 | Av | Vertical |
| 4804.33 | 51.29 | -3.18 | 48.11 | 74 | -25.89 | Pk | Horizontal |
| 4804.33 | 42.92 | -3.18 | 39.74 | 54 | -14.26 | Av | Horizontal |
| 7206.19 | 46.82 | -2.28 | 44.54 | 74 | -29.46 | Pk | Horizontal |
| 7206.19 | 35.53 | -2.28 | 33.25 | 54 | -20.75 | Av | Horizontal |
| Mid Channel (2441 MHz)-Above 1G | | | | | | | |
| 4882.43 | 52.56 | -3.55 | 49.01 | 74 | -24.99 | Pk | Vertical |
| 4882.43 | 41.36 | -3.55 | 37.81 | 54 | -16.19 | Av | Vertical |
| 7324.15 | 50.36 | -0.76 | 49.6 | 74 | -24.4 | Pk | Vertical |
| 7324.15 | 39.28 | -0.76 | 38.52 | 54 | -15.48 | Av | Vertical |
| 4882.76 | 49.74 | -3.82 | 45.92 | 74 | -28.08 | Pk | Horizontal |
| 4882.76 | 36.83 | -3.82 | 33.01 | 54 | -20.99 | Av | Horizontal |
| 7324.23 | 47.66 | -0.91 | 46.75 | 74 | -27.25 | Pk | Horizontal |
| 7324.23 | 34.28 | -0.91 | 33.37 | 54 | -20.63 | Av | Horizontal |
| High Channel (2480MHz)- Above 1G | | | | | | | |
| 4960.25 | 53.73 | -3.67 | 50.06 | 74 | -23.94 | Pk | Vertical |
| 4960.25 | 40.47 | -3.67 | 36.8 | 54 | -17.2 | Av | Vertical |
| 7440.16 | 51.37 | -0.73 | 50.64 | 74 | -23.36 | Pk | Vertical |
| 7440.16 | 37.84 | -0.73 | 37.11 | 54 | -16.89 | Av | Vertical |
| 4960.44 | 49.68 | -3.47 | 46.21 | 74 | -27.79 | Pk | Horizontal |
| 4960.44 | 35.66 | -3.47 | 32.19 | 54 | -21.81 | Av | Horizontal |
| 7440.78 | 47.86 | -0.54 | 47.32 | 74 | -26.68 | Pk | Horizontal |
| 7440.78 | 33.74 | -0.54 | 33.2 | 54 | -20.8 | Av | Horizontal |





Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2015SZ0127013F
- Page 25 of 50 -

Conducted Spurious Emissions at Antenna Port:

1Mbps




This document cannot be reproduced except in full, without prior written approval of ATT. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.




Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2015SZ0127013F
- Page 26 of 50 -



CH39







Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2015SZ0127013F
- Page 27 of 50 -

RS



RS







Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2015SZ0127013F
- Page 28 of 50 -


CH78





Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2015SZ0127013F
- Page 29 of 50 -





Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2015SZ0127013F
- Page 30 of 50 -

5. NUMBER OF HOPPING CHANNEL

5.1 APPLIED PROCEDURES / LIMIT

| FCC Part15 (15.247) , Subpart C | | | | |
|---------------------------------|---------------------------|-------|-----------------------|--------|
| Section | Test Item | Limit | Frequency Range (MHz) | Result |
| 15.247 (a)(1)(iii) | Number of Hopping Channel | ≥15 | 2400-2483.5 | PASS |

| Spectrum Parameters | Setting |
|---------------------|-----------------------------------|
| Attenuation | Auto |
| Span Frequency | = the frequency band of operation |
| RB | RBW =100kHz |
| VB | VBW ≥ RBW |
| Detector | Peak |
| Trace | Max Hold |
| Sweep Time | Auto |


5.1.1 TEST PROCEDURE

- The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below,
- Spectrum Setting : RBW= 100kHz, VBW=300kHz, Sweep time = Auto.

5.1.2 DEVIATION FROM STANDARD

No deviation.

5.1.3 TEST SETUP



5.1.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.




Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2015SZ0127013F
- Page 31 of 50 -

5.1.5 TEST RESULTS

| | | | |
|---------------|-------------------|---------------------|---------|
| EUT : | BLUETOOTH HEADSET | Model Name : | BS057RQ |
| Temperature : | 25 °C | Relative Humidity : | 60% |
| Pressure : | 1015 hPa | Test Voltage : | DC 3.7V |
| Test Mode : | Hopping Mode | | |

| | |
|---------------------------|----|
| Number of Hopping Channel | 79 |
|---------------------------|----|





Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2015SZ0127013F
- Page 32 of 50 -

6. AVERAGE TIME OF OCCUPANCY


6.1 APPLIED PROCEDURES / LIMIT

The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.

6.1.1 TEST PROCEDURE

The transmitter output was connected to the spectrum analyzer through an attenuator. Set center frequency of spectrum analyzer=operating frequency with RBW=1MHz and VBW=3MHz, Span=0Hz.

6.1.2 TEST SETUP





Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2015SZ0127013F
- Page 33 of 50 -

6.1.3 TEST RESULTS

The Dwell Time=Burst Width*Total Hops. The detailed calculations are showed as follows:

The duration for dwell time calculation: $0.4[\text{s}]*\text{hopping number}=0.4[\text{s}]*79[\text{ch}]=31.6[\text{s}*\text{ch}]$;

The burst width [ms/hop/ch], which is directly measured, refers to the duration on one channel hop.

The hops per second for all channels: The selected EUT Conf uses a slot type of 5-Tx&1-Rx and a hopping rate of 1600 [ch*hop/s] for all channels. So the final hopping rate for all channels is $1600/6=266.67$ [ch*hop/s];

The hops per second on one channel: 266.67 [ch*hop/s]/79 [ch]=3.38 [hop/s];


The total hops for all channels within the dwell time calculation duration: 3.38

[hop/s]*31.6[s*ch]=106.67 [hop*ch];

The dwell time for all channels hopping: 106.67 [hop*ch]*Burst Width [ms/hop/ch].

Remark: 1. We test Frequency Separation at all test channels, recorded worst case at middle channel.

| GFSK Test Mode | | | | | |
|---|-----------------|------------------|----------------|-----------|---------|
| Mode | Frequency (MHz) | Pulse Width (ms) | Dwell Time (S) | Limit (S) | Verdict |
| DH5 | 2441 | 2.995 | 0.319 | 0.4 | PASS |
| Note: Dwell time=Pulse Time (ms) \times (1600 \div 6 \div 79) \times 31.6 Second | | | | | |





7. HOPPING CHANNEL SEPARATION MEASUREMENT

7.1 APPLIED PROCEDURES / LIMIT

Frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater.

| Spectrum Parameter | Setting |
|--------------------|---|
| Attenuation | Auto |
| Span Frequency | > Measurement Bandwidth or Channel Separation |
| RB | 100kHz |
| RB | 300kHz |
| Detector | Peak |
| Trace | Max Hold |
| Sweep Time | Auto |


7.1.1 TEST PROCEDURE

- The transmitter output (antenna port) was connected to the spectrum analyser in peak hold mode.
- The resolution bandwidth of 100 kHz and the video bandwidth of 300 kHz were utilised for channel separation measurement.

7.1.2 DEVIATION FROM STANDARD

No deviation.

7.1.3 TEST SETUP



7.1.4 EUT OPERATION CONDITIONS

The EUT was programmed to be in continuously transmitting mode.




Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2015SZ0127013F
- Page 35 of 50 -

7.1.5 TEST RESULTS

| GFSK Test Mode | | |
|----------------|----------------------|----------|
| Frequency | Ch. Separation (MHz) | Result |
| 2402 MHz | 1.000 | Complies |
| 2441 MHz | 1.000 | Complies |
| 2480 MHz | 1.000 | Complies |

CH00 -1Mbps







Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2015SZ0127013F
- Page 36 of 50 -

CH39 -1Mbps



CH78 -1Mbps





Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2015SZ0127013F
- Page 37 of 50 -

8. BANDWIDTH TEST

8.1 APPLIED PROCEDURES / LIMIT

| FCC Part15 (15.247) , Subpart C | | | | |
|---------------------------------|-----------|------------------|-----------------------|--------|
| Section | Test Item | Limit | Frequency Range (MHz) | Result |
| 15.247 (a)(1) | Bandwidth | (20dB bandwidth) | 2400-2483.5 | PASS |

| Spectrum Parameter | Setting |
|--------------------|---|
| Attenuation | Auto |
| Span Frequency | > Measurement Bandwidth or Channel Separation |
| RB | 30 kHz |
| VB | 100 kHz |
| Detector | Peak |
| Trace | Max Hold |
| Sweep Time | Auto |


8.1.1 TEST PROCEDURE

- The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below,
- Spectrum Setting : RBW= 30KHz, VBW=100KHz, Sweep time = Auto.

8.1.2 DEVIATION FROM STANDARD

No deviation.

8.1.3 TEST SETUP



8.1.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.




Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2015SZ0127013F
- Page 38 of 50 -

8.1.5 TEST RESULTS

| | | | |
|---------------|-------------------------|---------------------|---------|
| EUT : | BLUETOOTH HEADSET | Model Name : | BS057RQ |
| Temperature : | 25 °C | Relative Humidity : | 60% |
| Pressure : | 1012 hPa | Test Voltage : | DC 3.7V |
| Test Mode : | CH00 / CH39 /C78(1Mbps) | | |



| Frequency | 20dB Bandwidth (MHz) | Result |
|-----------|----------------------|--------|
| 2402 MHz | 0.783 | PASS |
| 2441 MHz | 0.817 | PASS |
| 2480 MHz | 0.813 | PASS |





Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2015SZ0127013F
- Page 39 of 50 -





Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2015SZ0127013F
- Page 40 of 50 -

9. PEAK OUTPUT POWER TEST

9.1 APPLIED PROCEDURES / LIMIT

| FCC Part15 (15.247) , Subpart C | | | | |
|---------------------------------|-------------------|---------------|-----------------------|--------|
| Section | Test Item | Limit | Frequency Range (MHz) | Result |
| 15.247 (b)(i) | Peak Output Power | 0.125 w or 1w | 2400-2483.5 | PASS |

9.1.1 TEST PROCEDURE

- The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below,
- Spectrum Setting : RBW > the 20 dB bandwidth of the emission being measured

Span = approximately 5 times the 20 dB bandwidth, centered on a hopping channel
 $VBW \geq RBW$

Sweep = auto


Detector function = peak

Trace = max hold

9.1.2 DEVIATION FROM STANDARD

No deviation.

9.1.3 TEST SETUP



9.1.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.



Shenzhen Asia Test Technology Co., Ltd.


Report No. ATT-2015SZ0127013F
- Page 41 of 50 -

9.1.5 TEST RESULTS

Remark: We test maximum peak output power at difference Packet Type (DH1, DH3 and DH5), recorded worst case at DH3

| 1Mbps | | | |
|--------------|-----------------|-------------------------|-------------|
| Test Channel | Frequency (MHz) | Peak Output Power (dBm) | LIMIT (dBm) |
| CH00 | 2402 | -0.98 | 30 |
| CH39 | 2441 | -0.78 | 30 |
| CH78 | 2480 | -0.86 | 30 |



Note: The relevant measured result has the offset with cable loss already.





Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2015SZ0127013F
- Page 42 of 50 -





Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2015SZ0127013F
- Page 43 of 50 -

10. 100 KHZ BANDWIDTH OF FREQUENCY BAND EDGE

APPLICABLE STANDARD

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

TEST PROCEDURE

- a) Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- b) Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
- c) Set RBW to 100 kHz and VBW of spectrum analyzer to 300 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
- d) Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
- e) Repeat above procedures until all measured frequencies were complete.

10.1 DEVIATION FROM STANDARD


No deviation.



Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2015SZ0127013F
- Page 44 of 50 -

10.2 TEST SETUP



10.3 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.



Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2015SZ0127013F
- Page 45 of 50 -

10.4 TEST RESULTS

| | | | |
|---------------|-------------------|---------------------|---------|
| EUT : | BLUETOOTH HEADSET | Model Name : | BS057RQ |
| Temperature : | 24 °C | Relative Humidity : | 60% |
| Pressure : | 1012 hPa | Test Voltage : | DC 3.7V |

| Frequency Band | Delta Peak to band emission (dBc) | > Limit (dBc) | Result |
|-------------------|-----------------------------------|---------------|--------|
| 1Mbps Non-hopping | | | |
| Left-band | 46.42 | 20 | Pass |
| Right-band | 46.60 | 20 | Pass |
| 1Mbps hopping | | | |
| Left-band | 43.91 | 20 | Pass |
| Right-band | 46.98 | 20 | Pass |

| Frequency (MHz) | Meter Reading (dB μ V) | Factor (dB) | Emission Level (dB μ V/m) | Limits (dB μ V/m) | Margin (dB) | Detector Type | Comment | | |
|-------------------|----------------------------|-------------|-------------------------------|-----------------------|-------------|---------------|------------|--|--|
| | | | | | | | | | |
| 1Mbps Non-hopping | | | | | | | | | |
| 2390 | 55.74 | -13.06 | 42.68 | 54 | -11.32 | peak | Vertical | | |
| 2390 | 52.16 | -13.06 | 39.1 | 54 | -14.9 | peak | Horizontal | | |
| 2483.5 | 50.84 | -12.78 | 38.06 | 54 | -15.94 | peak | Vertical | | |
| 2483.5 | 51.48 | -12.78 | 38.7 | 54 | -15.3 | peak | Horizontal | | |



Note: Test method to see chapter 3.2 . When PK value is lower than the Average value limit, average didn't record.



Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2015SZ0127013F
- Page 46 of 50 -

DH5: Band Edge, Left Side







Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2015SZ0127013F
- Page 47 of 50 -

DH5: Band Edge, Right Side





Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2015SZ0127013F
- Page 48 of 50 -

11. ANTENNA REQUIREMENT

11.1 STANDARD REQUIREMENT

15.203 requirement: For intentional device, according to 15.203: an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

11.2 EUT ANTENNA

The EUT antenna is PCB antenna. It comply with the standard requirement.