



RF-EXPOSURE ASSESSMENT REPORT FCC 47 CFR Part 2.1091 ISED RSS-102 RF-Exposure evaluation of mobile equipment	
Report Reference No.	G0M-1611-6036-TFC091ME-V01
Testing Laboratory	Eurofins Product Service GmbH
Address.....	Storkower Str. 38c 15526 Reichenwalde Germany
Accreditation	<div style="display: flex; justify-content: center; align-items: center;">   </div> <p style="text-align: center; margin-top: 5px;"> A2LA Accredited Testing Laboratory, Certificate No.: 1983.01 FCC Filed Test Laboratory, Reg.-No.: 96970 IC OATS Filing assigned code: 3470A </p>
Applicant's name	Dräger Safety AG & Co. KGaA
Address.....	Revalstraße 1 23560 Lübeck GERMANY
Test specification:	
Standard	47 CFR 2.1091 KDB 447498 D01 v06:2015-10-23 RSS-102, Issue 5:2015-03
Equipment under test (EUT):	
Product description	Portable Alarm Amplifier
Model No.	AAC 00xx
Additional Model(s)	None
Brand Name(s)	Dräger X-zone 5500
Hardware version	8324825 // X-zone 5500 Japan with 8324181 ASM PCB Main
Firmware / Software version	2.25
	FCC-ID: X6O-AAC00XX IC: 5895F-AAC00XX
Test result	Passed

Test Report No.: G0M-1611-6036-TFC091ME-V01

Eurofins Product Service GmbH
Storkower Str. 38c, D-15526 Reichenwalde, Germany

Possible test case verdicts:

- neither assessed nor tested: N/N
- required by standard but not appl. to test object.....: N/A
- required by standard but not tested.....: N/T
- not required by standard for the test object: N/R
- test object does meet the requirement.....: P (Pass)
- test object does not meet the requirement.....: F (Fail)

Testing:

Test Lab Temperature: 20 – 23 °C

Test Lab Humidity: 32 – 38 %

Date of receipt of test item: 2016-11-23

Date (s) of assessment: 2017-01-30

Compiled by: Christian Weber

Assessed by (+ signature): Matthias Handrik
(Responsible for Assessment)

Approved by (+ signature): Christian Weber

Date of issue: 2017-01-30

Total number of pages: 12

Handrik

.....

C. Weber

.....

General remarks:

The test results presented in this report relate only to the object tested.

The results contained in this report reflect the results for this particular model and serial number. It is the responsibility of the manufacturer to ensure that all production models meet the intent of the requirements detailed within this report.

This report shall not be reproduced, except in full, without the written approval of the Issuing testing laboratory.

Additional comments:

Version History

Version	Issue Date	Remarks	Revised by
01	2017-01-30	Initial Release	

REPORT INDEX

1	EQUIPMENT (TEST ITEM) DESCRIPTION	5
1.1	Reference Documents	6
1.2	Radiation Sources	7
2	RESULT SUMMARY	8
3	RF-EXPOSURE CLASSIFICATIONS	9
4	ASSESSMENT	10
4.1	MPE Assessment – 47 CFR 2.1091 / RSS-102	10

1 Equipment (Test item) Description

Description	Portable Alarm Amplifier
Model	AAC 00xx
Additional Model(s)	None
Brand Name(s)	Dräger X-zone 5500
Serial number	None
Hardware version	8324825 // X-zone 5500 Japan with 8324181 ASM PCB Main
Software / Firmware version	2.25
FCC-ID	X6O-AAC00XX
IC	5895F-AAC00XX
Equipment type	End product

1.1 Reference Documents

Document type	Document No.	Issued by	Date
FCC 15.247 Test Report	G0M20910-2625-P-15	Eurofins Product Service GmbH	2010-02-17
FCC 15.247 Test Report	G0M-1407-3996-TFC247DT-V01	Eurofins Product Service GmbH	2012-09-01
FCC 15.247 Test Report	G0M-1611-6036-TFC247DT-V01	Eurofins Product Service GmbH	2016-11-29

1.2 Radiation Sources

Mode #	Description	
920 MHz	Frequency range [MHz]	917 -926
	Modulations	FSK
	Maximum radiated power [dBm]	15.98
	Maximum transmission duty cycle [%]	1 %
	Antenna gain [dBi]	1.0
	Antenna diameter [cm]	unspecified

2 Result Summary

FCC 47 CFR Part 2.1091, ISED RSS-102			
Product Specific Standard Section	Requirement	Result	Remarks
47 CFR 2.1091	Maximum permissible exposure @ 20cm below limit	PASS	
RSS-102 2.5.2	Maximum permissible exposure @ 20cm below limit	PASS	
Remarks:			

3 RF-Exposure Classifications

Device Types	
Fixed	A fixed device is defined as a device physically secured at one fixed location and cannot be easily re-located.
Mobile	A mobile device is defined as a transmitting device designed to be used in other than fixed locations and to generally be used in such a way that a separation distance of at least 20 centimeters is normally maintained between the transmitter's radiating structure(s) and the body of the user or nearby persons. (47 CFR 2.1091)
Portable	A portable device is defined as a transmitting device designed to be used so that the radiating structure(s) of the device is/are within 20 centimeters of the body of the user. (47 CFR 2.1093)

Exposure Categories	
Occupational / Controlled	Limits apply in situations in which persons are exposed as a consequence of their employment provided those persons are fully aware of the potential for exposure and can exercise control over their exposure. Limits for occupational/controlled exposure also apply in situations when an individual is transient through a location where occupational/controlled limits apply provided he or she is made aware of the potential for exposure.
General population / uncontrolled	Exposures apply in situations in which the general public may be exposed, or in which persons that are exposed as a consequence of their employment may not be fully aware of the potential for exposure or cannot exercise control over their exposure.

4 Assessment

4.1 MPE Assessment – 47 CFR 2.1091 / RSS-102

MPE Assessment acc. to 47 CFR 2.1091 / ISED RSS-102				Verdict: PASS
Assessment according to reference	Reference Method			
	FCC OET Bulletin 65 / RSS-102 & Safety Code 6			
Device type	mobile			
Exposure category	General public			
IC Limits – Occupational / Controlled Exposure				
Frequency range [MHz]	Electric field strength [V/M]	Magnetic field strength [A/M]	Power density [W/m ²]	Averaging time [min]
0.003-10*	170	180	-	Instantaneous*
0.1-10	-	1.6 / f	-	6**
1.29-10	193 / $f^{0.5}$	-	-	6**
10-20	61.4	0.163	-10	6
20-48	129.8 / $f^{0.25}$	0.3444 / $f^{0.25}$	44.72 / $f^{0.5}$	6
48-100	49.33	0.1309	6.455	6
100-6000	15.60 $f^{0.25}$	0.04138 $f^{0.25}$	0.6455 $f^{0.5}$	6
6000-15000	137	0.364	50	6
15000-150000	137	0.364	50	616000 / $f^{1.2}$
150000-300000	0.354 $f^{0.5}$	9.40 x 10 ⁻⁴ $f^{0.5}$	3.33 x 10 ⁻⁴ f	616000 / $f^{1.2}$
IC Limits – General Population / Uncontrolled Exposure				
Frequency range [MHz]	Electric field strength [V/M]	Magnetic field strength [A/M]	Power density [W/m ²]	Averaging time [min]
0.003-10*	83	90	-	Instantaneous*
0.1-10	-	0.73 / f	-	6**
1.1-10	87 / $f^{0.5}$	-	-	6**
10-20	27.46	0.0728	2	6
20-48	58.07 / $f^{0.25}$	0.1540 / $f^{0.25}$	8.944 / $f^{0.5}$	6
48-300	22.06	0.05852	1.291	6
300-6000	3.142 $f^{0.3417}$	0.008335 $f^{0.3417}$	0.02619 $f^{0.6834}$	6
6000-15000	61.4	0.163	10	6
15000-150000	61.4	0.163	10	616000 / $f^{1.2}$
150000-300000	0.158 $f^{0.5}$	4.21 x 10 ⁻⁴ $f^{0.5}$	6.67 x 10 ⁻⁵ f	616000 / $f^{1.2}$
* = Based on nerve stimulation				
** = Bases on specific absorption rate				

FCC Limits – Occupational / Controlled Exposure				
Frequency range [MHz]	Electric field strength [V/M]	Magnetic field strength [A/M]	Power density [mW/cm ²]	Averaging time [min]
0.3 – 3.0	614	1.63	(100)*	6
3.0 - 30	1842/f	4.89/f	(900/f ²)*	6
30 - 300	61.4	0.163	1.0	6
300 - 1500	N/A	N/A	f/300	6
1500 - 100000	N/A	N/A	5.0	6
FCC Limits – General Population / Uncontrolled Exposure				
Frequency range [MHz]	Electric field strength [V/M]	Magnetic field strength [A/M]	Power density [mW/cm ²]	Averaging time [min]
0.3 – 1.34	614	1.63	(100)*	30
1.34 - 30	842/f	2.19/f	(180/f ²)*	30
30 - 300	27.5	0.073	0.2	30
300 - 1500	N/A	N/A	f/1500	30
1500 - 100000	N/A	N/A	1.0	30
* = Plane wave equivalent power density; f in MHz				
Assessment Relations				
$\lambda[m] = \frac{c \left[\frac{m}{s} \right]}{f[Hz]} ; R_{FF}[m] \geq \frac{2 \cdot D[m]^2}{\lambda[m]}$ $S[mW/cm^2] = \frac{P_{E.I.R.P.}[mW]}{4\pi R[cm]^2} ; R[cm] = \sqrt{\frac{P_{E.I.R.P.}[mW]}{4\pi S[mW/cm^2]}}$ $P_R[mW] = P_C[mW] \cdot G ; P_R[dBm] = P_C[dBm] + G[dBi]$ $DCC [dB] = 10 \cdot \text{Log}_{10} \left(\frac{DC[\%]}{100} \right)$				
Assessment procedure				
<p>For each radio and frequency band the worst case transmission mode with the highest peak conducted or radiated power is evaluated at the frequency that results in the most restrictive rf-exposure limit. From the peak power values, antenna gains and duty cycles taken from the reference documents, the source average radiated power values are calculated. From the average radiated power the power densities at antenna far-field distance, at 20cm separation distance from the radiation source is calculated. Compliance with the RF-Exposure limit is determined at 20cm separation distance.</p>				

Assessment results		
Transmission mode		
Operating mode frequency range [MHz]	917 – 926	
Assessment frequency (f) [MHz]	917	
Transmission duty cycle (DC) [%]	1	
Peak conducted power (P _C) [dBm]	14.98	
Peak radiated power (P _R) [dBm e.i.r.p.]	15.98	
Peak Antenna gain (G) [dBi]	1.00	
Maximum Antenna Diameter D [cm]	N/A	
Antenna far-field distance		
Transmission frequency wavelength (λ)	0.327 m	32.72 cm
Antenna far-field distance (R _{FF})	N/A	N/A
Power evaluation		
Peak conducted power (P _C)	31.48 mW	14.98 dBm
Peak Antenna Gain (G)	1.26	1.00 dBi
Calculated peak radiated power (P _{R-Calc})	39.63 mW	15.98 dBm
Measured peak radiated power (P _R)	39.63 mW	15.98 dBm
Source average Power		
Maximum transmission duty cycle (DC)	1.0 %	
Duty cycle correction (DCC)	0.01	-20.00 dB
Measured peak radiated power (P _R)	39.63 mW	15.98 dBm
Averaged peak radiated power (P _{RAVG})	0.40 mW	-4.02 dBm
Power density		
Compliance power density limit	0.611 mW/cm ²	6.11 W/m ²
Power density @ Antenna far-field distance	N/A	N/A
Power density @ 20cm	0.000 mW/cm ²	0.001 W/m ²
Distance for compliance power density	0.002 m	0.23 cm
Verdict		
The power density of the EUT at 20cm is below the FCC/ISED MPE limit!		
Comments:		