



HCT CO., LTD.

Product Compliance Division

TEL : +82 31 639 8518 FAX : +82 31 639 8525

CERTIFICATE OF COMPLIANCE

FCC PART 15.247 Certification

Applicant Name:
MAXFOR Technology Inc.

Address:
#E 809, Bundang, Techno-Park, 151, Yatap-Dong,
Bundang-Gu, Seongnam-City, Gyeonggi-Do, 463-760,
Korea

Date of Issue:
March 19, 2010
Test Site/Location:
HCT.CO., LTD., San 136-1 Ami-ri, Bubal-eup, Icheon-si,
Kyungki-do, Korea
Test Report No.: HCTR1003FR16
HCT FRN: 0005866421
IC Recognition No.: 5944A-1

FCC ID: X6VMTMCM4000MSP

APPLICANT: MAXFOR Technology Inc.

FCC Rule Part(s): Part 15.247

Application Type: Certification

EUT Type: network module

Model(s): MTM-CM4000MSP

Frequency Range: 2405-2480 MHz (DSSS)

FCC Classification: Digital Transmission System (DTS)

Max. RF Output Power: 2.60 dBm(1.82 mW)

Engineering Statement:

The measurements shown in this report were made in accordance with the procedures indicated, and the emissions from this equipment were found to be within the limits applicable. I assume full responsibility for the accuracy and completeness of these measurements, and for the qualifications of all persons taking them.

HCT.CO., LTD. Certifies that no party to this application has been denied FCC benefits pursuant to section 5301 of the Anti-Drug Abuse Act of 1998, 21 U.S. C.862

Hyo Sun Kwak

Report prepared by

: Hyo Sun Kwak

Test engineer of RF Team

Sang Jun Lee

Approved by

: Sang Jun Lee

Manager of RF Team

HCT PT.15.247 TEST REPORT		FCC CERTIFICATION REPORT			www.hct.co.kr
Test Report No.	Date of Issue:	EUT Type:	FCC ID:		
HCTR1003FR16	March 19, 2010	network module	X6VMTMCM4000MSP		Page 1 of 32



Table of Contents

1. GENERAL INFORMATION.....	3
2. EUT DESCRIPTION.....	3
3. TEST METHODOLOGY	4
3.1 EUT CONFIGURATION.....	4
3.2 EUT EXERCISE.....	4
3.3 GENERAL TEST PROCEDURES.....	4
3.4 DESCRIPTION OF TEST MODES.....	4
4. INSTRUMENT CALIBRATION.....	5
5. FACILITIES AND ACCREDITATIONS	5
5.1 FACILITIES.....	5
5.2 EQUIPMENT	5
6. ANTENNA REQUIREMENTS	6
7. TEST RESULT	7
7.1 6dB Bandwidth Measurement.....	7
7.2 Output Power Measurement	10
7.3 Power Spectral Density	13
7.4 Out of Band Emissions at the Band Edge/ Conducted Spurious Emissions	16
7.5 MAXIMUM PERMISSIBLE EXPOSURE.....	21
7.6 Radiated Measurement.....	23
7.6.1 Radiated Spurious Emissions.....	23
7.6.2 Radiated Restricted Band Edge Measurements	31
8. LIST OF TEST EQUIPMENT	32

HCT PT.15.247 TEST REPORT		FCC CERTIFICATION REPORT			www.hct.co.kr
Test Report No. HCTR1003FR16	Date of Issue: March 19, 2010	EUT Type: network module		FCC ID: X6VMTMCM4000MSP	Page 2 of 32



1. GENERAL INFORMATION

Applicant: MAXFOR Technology Inc.

Address: #E 809, Bundang, Techno-Park, 151, Yatap-Dong, Bundang-Gu, Seongnam-City, Gyeonggi-Do, 463-760, Korea

FCC ID: X6VMTMCM4000MSP

EUT: network module

Model: MTM-CM4000MSP

Date of Test: January 25, 2010

Contact person: Name: Joong Deok Choi
Phone #: TEL :+82-31-601-3533 / FAX : +82-31-705-4653

2. EUT DESCRIPTION

Product	network module
Model Name	MTM-CM4000MSP
Power Supply	DC 3.3 V
Frequency Range	2405 ~ 2480 MHz (DSSS)
Max. RF Output Power	2.60 dBm(1.82 mW)
Modulation Type	DSSS
Antenna Specification	Manufacturer: MAXFOR Technology Inc. Antenna type: PCB Antenna Peak Gain : -2.31 dBi

HCT PT.15.247 TEST REPORT	FCC CERTIFICATION REPORT			www.hct.co.kr
Test Report No. HCTR1003FR16	Date of Issue: March 19, 2010	EUT Type: network module	FCC ID: X6VMTMCM4000MSP	Page 3 of 32



3. TEST METHODOLOGY

The measurement procedure described in the American National Standard for Methods of Measurement of Radio-Noise Emission from Low-Voltage Electrical and Electronic Equipment in the Range of 9kHz to 40GHz(ANSI C63.4-2003)

3.1 EUT CONFIGURATION

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner that intends to maximize its emission characteristics in a continuous normal application.

3.2 EUT EXERCISE

The EUT was operated in the engineering mode to fix the Tx frequency that was for the purpose of the measurements. According to its specifications, the EUT must comply with the requirements of the Section 15.207, 15.209 and 15.247 under the FCC Rules Part 15 Subpart C.

3.3 GENERAL TEST PROCEDURES

Conducted Emissions

The EUT is placed on the turntable, which is 0.8 m above ground plane. According to the requirements in Section 13.1.4.1 of ANSI C63.4. (Version :2003) Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30MHz using CISPR Quasi-peak and average detector modes.

Radiated Emissions

The EUT is placed on a turn table, which is 0.8 m above ground plane. The turntable shall rotate 360 degrees to determine the position of maximum emission level. EUT is set 3 m away from the receiving antenna, which varied from 1 m to 4 m to find out the highest emission. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical. In order to find out the max. emission, the relative positions of this hand-held transmitter (EUT) was rotated through three orthogonal axes according to the requirements in Section 13.1.4.1 of ANSI C63.4. (Version: 2003)

3.4 DESCRIPTION OF TEST MODES

The EUT has been tested under operating condition. Test program used to control the EUT for staying in continuous transmitting and receiving mode is programmed.

Channel low, mid and high with highest data rate (worst case) is chosen for full testing.

HCT PT.15.247 TEST REPORT		FCC CERTIFICATION REPORT			www.hct.co.kr
Test Report No. HCTR1003FR16	Date of Issue: March 19, 2010	EUT Type: network module	FCC ID: X6VMTMCM4000MSP		Page 4 of 32



4. INSTRUMENT CALIBRATION

The measuring equipment, which was utilized in performing the tests documented herein, has been calibrated in accordance with the manufacturer's recommendations for utilizing calibration equipments, which is traceable to recognized national standards.

5. FACILITIES AND ACCREDITATIONS

5.1 FACILITIES

The open area test site and conducted measurement facility used to collect the radiated data are located at the 254-1,Maekok-Ri, Hobup-Myun, Ichon-Si, Kyoungki-Do, 467-701, KOREA. The site is constructed in conformance with the requirements of ANSI C63.4. (Version :2003) and CISPR Publication 22. Detailed description of test facility was submitted to the Commission and accepted dated June 10, 2009 (Registration Number: 90661)

5.2 EQUIPMENT

Radiated emissions are measured with one or more of the following types of Linearly polarized antennas: tuned dipole, bi-conical, log periodic, bi-log, and/or ridged waveguide, horn. Spectrum analyzers with pre-selectors and quasi-peak detectors are used to perform radiated measurements. Conducted emissions are measured with Line Impedance Stabilization Networks and EMI Test Receivers. Calibrated wideband preamplifiers, coaxial cables, and coaxial attenuators are also used for making measurements.

All receiving equipment conforms to CISPR Publication 16-1, "Radio Interference Measuring Apparatus and Measurement Methods."

HCT PT.15.247 TEST REPORT		FCC CERTIFICATION REPORT			www.hct.co.kr
Test Report No. HCTR1003FR16	Date of Issue: March 19, 2010	EUT Type: network module		FCC ID: X6VMTMCM4000MSP	Page 5 of 32



6. ANTENNA REQUIREMENTS

According to FCC 47 CFR §15.203:

“An intentional radiator antenna shall be designed to ensure that no antenna other than that furnished by the responsible party can be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.”

* The antennas of this E.U.T are permanently attached.

*The E.U.T Complies with the requirement of §15.203

HCT PT.15.247 TEST REPORT		FCC CERTIFICATION REPORT			www.hct.co.kr
Test Report No. HCTR1003FR16	Date of Issue: March 19, 2010	EUT Type: network module	FCC ID: X6VMTMCM4000MSP	Page 6 of 32	

7. TEST RESULT


7.1 6dB Bandwidth Measurement

Test Requirements and limit, §15.247(a)(2)

The bandwidth at 6dB down from the highest in-band spectral density is measured with a spectrum analyzer connected to the receive antenna while the EUT is operating in transmission mode at the appropriate frequencies.

The minimum permissible 6dB bandwidth is 500 kHz.

TEST CONFIGURATION



TEST PROCEDURE

The transmitter output is connected to the Spectrum Analyzer.

The Spectrum Analyzer is set to

RBW: 100 kHz

VBW: 100 kHz

SPAN: 10 MHz

TEST RESULTS


Conducted 6dB Bandwidth Measurements

Frequency [MHz]	Channel No.	Measured Bandwidth [MHz]	Minimum Bandwidth [MHz]	Pass / Fail
2405	11	1.68	0.500	Pass
2445	19	1.67	0.500	Pass
2480	26	1.68	0.500	Pass


HCT PT.15.247 TEST REPORT	FCC CERTIFICATION REPORT			www.hct.co.kr
Test Report No. HCTR1003FR16	Date of Issue: March 19, 2010	EUT Type: network module	FCC ID: X6VMTMCM4000MSP	Page 7 of 32

□ RESULT PLOTS

6dB Bandwidth plot (CH 11)




6dB Bandwidth plot (CH 19)



HCT PT.15.247 TEST REPORT		FCC CERTIFICATION REPORT			www.hct.co.kr	
Test Report No. HCTR1003FR16	Date of Issue: March 19, 2010	EUT Type: network module		FCC ID: X6VMTMCM4000MSP	Page 8	of 32

6dB Bandwidth plot (802.11b-CH 26)



HCT PT.15.247 TEST REPORT		FCC CERTIFICATION REPORT			www.hct.co.kr
Test Report No. HCTR1003FR16	Date of Issue: March 19, 2010	EUT Type: network module		FCC ID: X6VMTMCM4000MSP	Page 9 of 32


7.2 Output Power Measurement

Test Requirements and limit, §15.247(b)(3)

A transmitter antenna terminal of EUT is connected to the input of a Spectrum Analyzer. Measurement is made while the EUT is operating in transmission mode at the appropriate frequencies.

The maximum permissible conducted output power is 1 Watt.

TEST CONFIGURATION



TEST PROCEDURE

The transmitter output is connected to the Spectrum Analyzer.

The Spectrum Analyzer is set to

RBW: 1 MHz

VBW: 1 MHz

SPAN: 5 MHz

Detector Mode = Peak

TEST RESULTS


Conducted Output Power Measurements

Frequency[MHz]	Channel No.	Measured Peak Power(dBm)	Limit (dBm)
2405	11	-0.63	30
2445	19	1.12	30
2480	26	2.60	30


HCT PT.15.247 TEST REPORT	FCC CERTIFICATION REPORT			www.hct.co.kr
Test Report No. HCTR1003FR16	Date of Issue: March 19, 2010	EUT Type: network module	FCC ID: X6VMTMCM4000MSP	Page 10 of 32

□ RESULT PLOTS

Conducted Output Power (CH 11)




Conducted Output Power (CH 19)



HCT PT.15.247 TEST REPORT	FCC CERTIFICATION REPORT			www.hct.co.kr
Test Report No. HCTR1003FR16	Date of Issue: March 19, 2010	EUT Type: network module	FCC ID: X6VMTMCM4000MSP	Page 1 1 of 32

Conducted Output Power (CH 26)



HCT PT.15.247 TEST REPORT		FCC CERTIFICATION REPORT			www.hct.co.kr
Test Report No. HCTR1003FR16	Date of Issue: March 19, 2010	EUT Type: network module	FCC ID: X6VMTMCM4000MSP	Page 1 2	of 32


7.3 Power Spectral Density

Test Requirements and limit, §15.247(e)

The peak power density is measured with a spectrum analyzer connected to the antenna terminal while the EUT is operating in transmission mode at the appropriate frequencies.

The maximum permissible power spectral density is 8 dBm in any 3 KHz band.

■ TEST CONFIGURATION



■ TEST PROCEDURE

The spectrum analyzer is set to :

1. Span = 300 kHz
2. RBW = 3 kHz
3. VBW = 3 kHz
4. Sweep = 100 sec
5. Detector Mode = Peak

■ TEST RESULTS


Conducted Power Density Measurements

Frequency (MHz)	Channel No.	Measured Power Spectral Density [dBm]	Maximum Permissible Power Density [dBm / 3 KHz]	Pass/Fail
2405	11	-18.02	8.0	Pass
2445	19	-15.78	8.0	Pass
2480	26	-14.47	8.0	Pass


HCT PT.15.247 TEST REPORT	FCC CERTIFICATION REPORT			www.hct.co.kr
Test Report No. HCTR1003FR16	Date of Issue: March 19, 2010	EUT Type: network module	FCC ID: X6VMTMCM4000MSP	Page 1 3 of 32

RESULT PLOTS

Power Spectral Density (CH 11)




Power Spectral Density (CH 19)



HCT PT.15.247 TEST REPORT		FCC CERTIFICATION REPORT			www.hct.co.kr
Test Report No. HCTR1003FR16	Date of Issue: March 19, 2010	EUT Type: network module		FCC ID: X6VMTMCM4000MSP	Page 1 4 of 32

Power Spectral Density (CH 26)




HCT PT.15.247 TEST REPORT		FCC CERTIFICATION REPORT			www.hct.co.kr
Test Report No. HCTR1003FR16	Date of Issue: March 19, 2010	EUT Type: network module		FCC ID: X6VMTMCM4000MSP	Page 15 of 32

7.4 Out of Band Emissions at the Band Edge/ Conducted Spurious Emissions

Test Requirements and limit, §15.247(d)

§15.247 (c) In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

█ TEST CONFIGURATION



█ TEST PROCEDURE

The transmitter output is connected to the spectrum analyzer. The resolution bandwidth is set to 100 kHz. The video bandwidth is set to 300 kHz.


Detector Mode is set to a peak detector Mode.

Measurements are made over the 30 MHz to 26 GHz range with the transmitter set to the lowest, middle, and highest channels.


HCT PT.15.247 TEST REPORT		FCC CERTIFICATION REPORT			www.hct.co.kr
Test Report No. HCTR1003FR16	Date of Issue: March 19, 2010	EUT Type: network module		FCC ID: X6VMTMCM4000MSP	Page 16 of 32

□ RESULT PLOTS

BandEdge (CH 11)




BandEdge (CH 26)




HCT PT.15.247 TEST REPORT		FCC CERTIFICATION REPORT			www.hct.co.kr
Test Report No. HCTR1003FR16	Date of Issue: March 19, 2010	EUT Type: network module		FCC ID: X6VMTMCM4000MSP	Page 17 of 32

30 MHz ~ 1 GHz

Conducted Spurious Emission (CH11)




Conducted Spurious Emission (CH19)




HCT PT.15.247 TEST REPORT		FCC CERTIFICATION REPORT			www.hct.co.kr
Test Report No. HCTR1003FR16	Date of Issue: March 19, 2010	EUT Type: network module		FCC ID: X6VMTMCM4000MSP	Page 18 of 32

Conducted Spurious Emission (CH26)




1 GHz ~ 26 GHz

Conducted Spurious Emission (CH11)




HCT PT.15.247 TEST REPORT		FCC CERTIFICATION REPORT			www.hct.co.kr
Test Report No. HCTR1003FR16	Date of Issue: March 19, 2010	EUT Type: network module		FCC ID: X6VMTMCM4000MSP	Page 19 of 32

Conducted Spurious Emission (CH19)



Conducted Spurious Emission (CH26)



HCT PT.15.247 TEST REPORT		FCC CERTIFICATION REPORT			www.hct.co.kr	
Test Report No. HCTR1003FR16	Date of Issue: March 19, 2010	EUT Type: network module		FCC ID: X6VMTMCM4000MSP	Page 20	of 32



7.5 MAXIMUM PERMISSIBLE EXPOSURE

1. LIMITS

According to §1.1310 and §2.1091 RF exposure is calculated.

(B) Limits for General Population/Uncontrolled Exposures

Frequency range (MHz)	Electric field Strength (V/m)	Magnetic field Strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
0.3 - 1.34.....	614	1.63	*(100)	30
1.34 - 30.....	824/f	2.19/f	*(180/ f ²)	30
30 - 300.....	27.5	0.073	0.2	30
300 - 1500.....	f/1500	30
1500 - 100.000.....	1.0	30

F = frequency in MHz

* = Plane-wave equivalent power density

2. MAXIMUM PERMISSIBLE EXPOSURE Prediction

Prediction of MPE limit at a given distance

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S = PG/4\pi R^2$$

S = Power density

P = power input to antenna

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna

HCT PT.15.247 TEST REPORT	FCC CERTIFICATION REPORT			www.hct.co.kr
Test Report No. HCTR1003FR16	Date of Issue: March 19, 2010	EUT Type: network module	FCC ID: X6VMTMCM4000MSP	Page 21 of 32



Max Peak output Power at antenna input terminal	2.60000	dBm
Max Peak output Power at antenna input terminal	1.81970	mW
Prediction distance	20.00000	cm
Prediction frequency	2480.00000	MHz
Antenna Gain(typical)	-2.31000	dBi
Antenna Gain(numeric)	0.58749	-
Power density at prediction frequency (S)	0.00021	mW/cm ²
MPE limit for uncontrolled exposure at prediction frequency	1.00000	mW/cm ²

3. RESULTS

The power density level at 20 cm is 0.00021 mW/cm², which is below the uncontrolled exposure limit of 1.0 mW/cm² at 2480 MHz

HCT PT.15.247 TEST REPORT		FCC CERTIFICATION REPORT			www.hct.co.kr
Test Report No. HCTR1003FR16	Date of Issue: March 19, 2010	EUT Type: network module	FCC ID: X6VMTMCM4000MSP	Page 22 of 32	



7.6 Radiated Measurement.

7.6.1 Radiated Spurious Emissions.

Test Requirements and limit, §15.247(d)


1. 20dBc in any 100kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed

Frequency (MHz)	Field Strength (uV/m)	Measurement Distance (m)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3


HCT PT.15.247 TEST REPORT	FCC CERTIFICATION REPORT			www.hct.co.kr
Test Report No. HCTR1003FR16	Date of Issue: March 19, 2010	EUT Type: network module	FCC ID: X6VMTMCM4000MSP	Page 23 of 32

Test Configuration

Below 30 MHz




30 MHz - 1 GHz



HCT PT.15.247 TEST REPORT		FCC CERTIFICATION REPORT			www.hct.co.kr
Test Report No. HCTR1003FR16	Date of Issue: March 19, 2010	EUT Type: network module		FCC ID: X6VMTMCM4000MSP	Page 24 of 32

Above 1 GHz



TEST PROCEDURE

1. The EUT is placed on a turntable, which is 0.8 m above ground plane.
2. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
3. EUT is set 3 m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emissions.
4. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
5. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
6. Repeat above procedures until the measurements for all frequencies are complete.

HCT PT.15.247 TEST REPORT		FCC CERTIFICATION REPORT			www.hct.co.kr
Test Report No. HCTR1003FR16	Date of Issue: March 19, 2010	EUT Type: network module		FCC ID: X6VMTMCM4000MSP	Page 25 of 32



TEST RESULTS

9 kHz – 30MHz

Operation Mode: Normal Link

Frequency	Reading	Ant. factor	Cable loss	Ant. POL	Total	Limit	Margin
MHz	dB μ V	dB /m	dB	(H/V)	dB μ V/m	dB μ V/m	dB
No Critical peaks found							

Notes:

1. Measuring frequencies from 9 kHz to the 30MHz.
2. The reading of emissions are attenuated more than 20 dB below the permissible limits or the field strength is too small to be measured.
3. Distance extrapolation factor = $40 \log (\text{specific distance} / \text{test distance})$ (dB)
4. Limit line = specific Limits (dB μ V) + Distance extrapolation factor
5. Detector : Qusi-peak

HCT PT.15.247 TEST REPORT	FCC CERTIFICATION REPORT			www.hct.co.kr
Test Report No. HCTR1003FR16	Date of Issue: March 19, 2010	EUT Type: network module	FCC ID: X6VMTMCM4000MSP	Page 26 of 32



TEST RESULTS

Below 1 GHz

Operation Mode: Normal Link

Frequency MHz	Reading dBuV	Ant. Factor dB/m	Cable Loss dB	ANT POL (H/V)	Total dBuV/m	Limit dBuV/m	Margin dB
959.26	11.4	23.9	3.7	H	39.00	46.0	7.0
974.78	6.8	24.1	3.8	V	34.65	54.0	19.4

Notes:

1. Measuring frequencies from 30 MHz to the 1 GHz.
2. Radiated emissions measured in frequency range from 30 MHz to 1000 MHz were made with an instrument using Quasi peak detector mode.
3. RBW: 120 kHz, VBW: 300 kHz

HCT PT.15.247 TEST REPORT	FCC CERTIFICATION REPORT				www.hct.co.kr
Test Report No. HCTR1003FR16	Date of Issue: March 19, 2010	EUT Type: network module		FCC ID: X6VMTMCM4000MSP	Page 27 of 32



Above 1 GHz

Operation Mode : CH Low

Frequency [MHz]	Reading dBuV	AN.+CL-AMP G [dB]	ANT. POL [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Detect
4810	58.41	-4.78	V	53.63	74	20.37	PK
4810	50.50	-4.78	V	45.72	54	8.28	AV
7215	49.31	1.24	V	50.55	74	23.45	PK
7215	37.95	1.24	V	39.19	54	14.81	AV
4810	57.16	-4.78	H	52.38	74	21.62	PK
4810	49.76	-4.78	H	44.98	54	9.02	AV
7215	47.48	1.24	H	48.72	74	25.28	PK
7215	38.41	1.24	H	39.65	54	14.35	AV

* A·F: ANTENNA FACTOR

C·L: CABLE LOSS

AMP GAIN: AMPLIFIER GAIN

Notes:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Measurements above show only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin > 20 dB from the applicable limit) and considered that's already beyond the background noise floor.
3. Radiated emissions measured in frequency above 1000MHz were made with an instrument using Peak detector mode and average detector mode of the emission shown in Actual FS column.
4. Spectrum setting:
 - a. Peak Setting 1 GHz – 26 GHz, RBW = 1 MHz, VBW = 1 MHz.
 - b. AV Setting 1 GHz – 26 GHz, RBW = 1 MHz, VBW = 10 Hz.

HCT PT.15.247 TEST REPORT		FCC CERTIFICATION REPORT			www.hct.co.kr
Test Report No.	Date of Issue:	EUT Type:	FCC ID:		Page 28 of 32
HCTR1003FR16	March 19, 2010	network module	X6VMTMCM4000MSP		



Operation Mode : CH Mid

Frequency [MHz]	Reading dBuV	AN.+CL-AMP G [dB]	ANT. POL [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Detect
4890	54.68	-4.59	V	50.09	74	23.91	PK
4890	47.33	-4.59	V	42.74	54	11.26	AV
7335	49.17	1.66	V	50.83	74	23.17	PK
7335	36.53	1.66	V	38.19	54	15.81	AV
4890	55.98	-4.59	H	51.39	74	22.61	PK
4890	46.97	-4.59	H	42.38	54	11.62	AV
7335	49.28	1.66	H	50.94	74	23.06	PK
7335	36.45	1.66	H	38.11	54	15.89	AV

* A·F: ANTENNA FACTOR

C·L: CABLE LOSS

AMP GAIN: AMPLIFIER GAIN

Notes:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Measurements above show only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin > 20 dB from the applicable limit) and considered that's already beyond the background noise floor.
3. Radiated emissions measured in frequency above 1000MHz were made with an instrument using Peak detector mode and average detector mode of the emission shown in Actual FS column.
4. Spectrum setting:
 - a. Peak Setting 1 GHz – 26 GHz, RBW = 1 MHz, VBW = 1 MHz.
 - b. AV Setting 1 GHz – 26 GHz, RBW = 1 MHz, VBW = 10 Hz.

HCT PT.15.247 TEST REPORT		FCC CERTIFICATION REPORT			www.hct.co.kr
Test Report No. HCTR1003FR16	Date of Issue: March 19, 2010	EUT Type: network module	FCC ID: X6VMTMCM4000MSP	Page 29 of 32	



Operation Mode : CH High

Frequency [MHz]	Reading dBuV	AN.+CL-AMP G [dB]	ANT. POL [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Detect
4960	53.92	-4.42	V	49.50	74	24.50	PK
4960	43.39	-4.42	V	38.97	54	15.03	AV
7440	48.24	2.04	V	50.28	74	23.72	PK
7440	34.81	2.04	V	36.85	54	17.15	AV
4960	51.34	-4.42	H	46.92	74	27.08	PK
4960	41.73	-4.42	H	37.31	54	16.69	AV
7440	47.63	2.04	H	49.67	74	24.33	PK
7440	34.81	2.04	H	36.85	54	17.15	AV

* A·F: ANTENNA FACTOR

C·L: CABLE LOSS

AMP GAIN: AMPLIFIER GAIN

Notes:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Measurements above show only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin > 20 dB from the applicable limit) and considered that's already beyond the background noise floor.
3. Radiated emissions measured in frequency above 1000MHz were made with an instrument using Peak detector mode and average detector mode of the emission shown in Actual FS column.
4. Spectrum setting:
 - a. Peak Setting 1 GHz – 26 GHz, RBW = 1 MHz, VBW = 1 MHz.
 - b. AV Setting 1 GHz – 26 GHz, RBW = 1 MHz, VBW = 10 Hz.

HCT PT.15.247 TEST REPORT		FCC CERTIFICATION REPORT			www.hct.co.kr
Test Report No. HCTR1003FR16	Date of Issue: March 19, 2010	EUT Type: network module	FCC ID: X6VMTMCM4000MSP	Page 30 of 32	



7.6.2 Radiated Restricted Band Edge Measurements

Test Requirements and limit, §15.247(d)

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in section 15.209(a) (See section 15.205(c)).

Operating Frequency	2405 MHz, 2480 MHz		
Channel No.	11 Ch, 26 Ch		

Frequency [MHz]	Reading dBuV	AN.+CL-AMP G [dB]	ANT. POL [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Detect
2376.08	54.43	-10.22	H	44.21	74	29.79	PK
2376.08	43.86	-10.22	H	33.64	54	20.36	AV
2361.36	51.45	-10.28	V	41.17	74	32.83	PK
2361.36	38.47	-10.28	V	28.19	54	25.81	AV
2490.75	50.35	-9.73	H	40.62	74	33.38	PK
2490.75	38.23	-9.73	H	28.50	54	25.50	AV
2483.83	50.04	-9.76	V	40.28	74	33.72	PK
2483.83	37.70	-9.76	V	27.94	54	26.06	AV

Notes:

1. Spectrum setting:
 - a. Peak Setting 1 GHz – 26 GHz, RBW = 1 MHz, VBW = 1 MHz.
 - b. AV Setting 1 GHz – 26 GHz, RBW = 1 MHz, VBW = 10 Hz.

HCT PT.15.247 TEST REPORT	FCC CERTIFICATION REPORT			www.hct.co.kr
Test Report No. HCTR1003FR16	Date of Issue: March 19, 2010	EUT Type: network module	FCC ID: X6VMTMCM4000MSP	Page 31 of 32



8. LIST OF TEST EQUIPMENT

Manufacturer	Model / Equipment	Cal Interval	Calibration Date	Serial No.
Rohde & Schwarz	ESH2-Z5/ LISN	Annual	04/10/2009	861741/013
Rohde & Schwarz	ESH3-Z6/ LISN	Annual	06/13/2009	100329
Schwarzbeck	VULB 9160/ TRILOG Antenna	Biennial	12/18/2008	9160-3150
HD	MA240/ Antenna Position Tower	N/A	N/A	556
EMCO	1050/ Turn Table	N/A	N/A	114
HD GmbH	HD 100/ Controller	N/A	N/A	13
HD GmbH	KMS 560/ SlideBar	N/A	N/A	12
Rohde & Schwarz	ESH3-Z2/ PULSE LIMITER	Annual	10/30/2009	375.8810.352
MITEQ	AMF-60-0010 1800-35-20P/AMP	Annual	05/20/2009	1200937
Schwarzbeck	BBHA 9120D/ Horn Antenna	Biennial	03/26/2008	147
Rohde & Schwarz	FSP30 / Spectrum Analyzer	Annual	07/31/2009	839117/011
Agilent	E4440A / Spectrum Analyzer	Annual	12/23/2009	US45303008
Agilent	E4416A /Power Meter	Annual	01/14/2010	GB41291412
Wainwright Instrument	WHF3.3/18G-10EF / High Pass Filter	Annual	06/29/2009	1
Hewlett Packard	11636B/Power Divider	Annual	12/24/2009	11377
DIGITAL	EP-3010 /DC POWER SUPPLY	Annual	01/08/2010	3110117
ITECH	IT6720 / DC POWER SUPPLY	Annual	12/01/2009	010002156287001199
TESCOM	TC-3000A / BLUETOOTH TESTER	Annual	01/11/2010	3000A490112
Rohde & Schwarz	CBT / BLUETOOTH TESTER	Annual	06/22/2009	100422
EMCO	6502.LOOP ANTENNA	Biennial	01/13/2010	9009-2536

HCT PT.15.247 TEST REPORT	FCC CERTIFICATION REPORT			www.hct.co.kr
Test Report No. HCTR1003FR16	Date of Issue: March 19, 2010	EUT Type: network module	FCC ID: X6VMTMCM4000MSP	Page 32 of 32