

## Maximum Permissible Exposure Report

### Product Information

FCC ID:	X7IBL10
Product name	Smart Bike-sharing GPS Lock
Model number	BL10
Power supply	DC 3.70V, 10000mAh Charging parameter: Input: DC5V, 1A(max) from solar power
Modulation Type	GFSK, $\pi/4$ -DQPSK, 8-DPSK for Bluetooth(V3.0) GFSK for Bluetooth(V4.0) GMSK for GPRS
Antenna Type	PIFA Antenna
Antenna Gain	-1dBi(max) for bluetooth, 0 dBi (max) for GPRS
Exposure category	General population/uncontrolled environment
EUT Type	Production Unit
Device Type	Mobile Device

### 2. Evaluation Method

Systems operating under the provisions of FCC 47 CFR section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines. In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as mobile device whereby a distance of 0.2m normally can be maintained between the user and the device, and below RF Permissible Exposure limit shall comply with.

In accordance with KDB447498D01 for Simultaneous transmission MPE test exclusion applies when the sum of the MPE ratios for all simultaneous transmitting antennas incorporated in a host device, based on the calculated/estimated, numerically modelled or measured field strengths or power density, is  $\leq 1.0$ . The MPE ratio of each antenna is determined at the minimum test separation distance required by the operating configurations and exposure conditions of the host device, according to the ratio of field strengths or power density to MPE limit, at the test frequency. Either the maximum peak or spatially averaged results from measurements or numerical simulations may be used to determine the MPE ratios. Spatial averaging does not apply when MPE is estimated using simple calculations based on far-field plane-wave equivalent conditions. The antenna installation and operating requirements for the host device must meet the minimum test separation distances required by all antennas, in both standalone and simultaneous transmission operations, to satisfy compliance.

### 3. Limit

#### 3.1 Refer evaluation method

[ANSI C95.1-1999](#): IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz.

[FCC KDB publication 447498 D01 General 1 RF Exposure Guidance v06](#): Mobile and Portable Devices RF Exposure Procedures and Equipment Authorization Policies.

[FCC CFR 47 part1 1.1310](#): Radiofrequency radiation exposure limits.

[FCC CFR 47 part2 2.1091](#): Radiofrequency radiation exposure evaluation: mobile devices

### 3.2 Limit

#### Limits for Maximum Permissible Exposure (MPE)/Controlled Exposure

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density (mW/cm <sup>2</sup> )	Averaging Time (minute)
Limits for Occupational/Controlled Exposure				
0.3 – 3.0	614	1.63	(100) *	6
3.0 – 30	1842/f	4.89/f	(900/f <sup>2</sup> )*	6
30 – 300	61.4	0.163	1.0	6
300 – 1500	/	/	f/300	6
1500 – 100,000	/	/	5	6

#### Limits for Maximum Permissible Exposure (MPE)/Uncontrolled Exposure

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density (mW/cm <sup>2</sup> )	Averaging Time (minute)
Limits for Occupational/Controlled Exposure				
0.3 – 3.0	614	1.63	(100) *	30
3.0 – 30	824/f	2.19/f	(180/f <sup>2</sup> )*	30
30 – 300	27.5	0.073	0.2	30
300 – 1500	/	/	f/1500	30
1500 – 100,000	/	/	1.0	30

F=frequency in MHz

\*=Plane-wave equivalent power density

### 4. MPE Calculation Method

Predication of MPE limit at a given distance  
Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S=PG/4\pi R^2$$

Where: S=power density

P=power input to antenna

G=power gain of the antenna in the direction of interest relative to an isotropic radiator

R=distance to the center of radiation of the antenna

### 5. Antenna Information

X7IBL10 only use antennas certificated as follows provided by manufacturer;

Internal Identification	Antenna type and antenna number	Operate frequency band	Maximum antenna gain
Antenna 1	PIFA Antenna	2402 MHz – 2480 MHz	-1 dBi
Antenna 2	PIFA Antenna	824 MHz – 850 MHz 1850 MHz – 1910 MHz	0 dBi

### 6. Conducted Power

Test Mode	Channel	Frequency (MHz)	Measured Peak Output Power (dBm)		
			Ant 1	Ant 2	Sum
GFSK	0	2402	5.622	/	/
	39	2441	5.836	/	/
	79	2480	5.811	/	/
π/4DQPSK	0	2402	5.406	/	/
	39	2441	5.594	/	/
	79	2480	5.606	/	/
8-DPSK	0	2402	5.559	/	/
	39	2441	5.776	/	/
	79	2480	5.724	/	/
GFSK	0	2402	0.920	/	/
	19	2440	0.765	/	/
	39	2480	0.783	/	/

GSM 850		Burst Average Conducted power (dBm)		
		Channel/Frequency(MHz)		
		128/824.2	190/836.6	251/848.8
GPRS (GMSK)	1TX slot	32.27	32.30	32.27
	2TX slot	30.97	31.01	31.00
	3TX slot	29.51	29.50	29.48
	4TX slot	27.97	28.03	27.98

GSM 1900		Burst Average Conducted power (dBm)		
		Channel/Frequency(MHz)		
		512/1850.2	661/1880	810/1909.8
GPRS (GMSK)	1TX slot	29.41	29.38	29.39
	2TX slot	27.99	28.01	28.03
	3TX slot	26.51	26.47	26.52
	4TX slot	25.00	25.01	25.00

## 7. Manufacturing Tolerance

GFSK (Peak)			
Channel	Channel 0	Channel 39	Channel 79
Target (dBm)	5.0	5.0	5.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
$\pi$ /4DQPSK (Peak)			
Channel	Channel 0	Channel 39	Channel 79
Target (dBm)	5.0	5.0	5.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
8-DPSK (Peak)			
Channel	Channel 0	Channel 39	Channel 79
Target (dBm)	5.0	5.0	5.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
GFSK (Peak)			
Channel	Channel 0	Channel 19	Channel 39
Target (dBm)	0.0	0.0	0.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0

GMSK (Avg)-GPRS 850			
Channel	Channel 128	Channel 190	Channel 251
Target (dBm)	32.0	32.0	32.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
GMSK (Avg)-GPRS 1900			
Channel	Channel 512	Channel 660	Channel 810
Target (dBm)	29.0	29.0	29.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0

## 8. Measurement Results

### 8.1 Standalone MPE

As declared by the Applicant, the EUT is a wireless device used in a fix application, at least 20 cm from any body part of the user or nearby persons; from the maximum EUT RF output power, the minimum separation distance,  $r = 20\text{cm}$ , as well as the gain of the used antenna refer to antenna information, the RF power density can be obtained.

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	MPE (mW/cm <sup>2</sup> )	MPE Limits (mW/cm <sup>2</sup> )
	dBm	mW				
GFSK	6.00	3.9811	-1	0.7943	0.0006	1.0000
$\pi/4$ DQPSK	6.00	3.9811	-1	0.7943	0.0006	1.0000
8-DPSK	6.00	3.9811	-1	0.7943	0.0006	1.0000
GFSK	1.00	1.2589	-1	0.7943	0.0002	1.0000

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	MPE (mW/cm <sup>2</sup> )	MPE Limits (mW/cm <sup>2</sup> )
	dBm	mW				
GMSK-GPRS 850	33.00	1995.2623	0	1.0000	0.3971	1.0000
GMSK-GPRS 1900	30.00	1000.0000	0	1.0000	0.1990	1.0000

Remark:

1. Output power including tune-up tolerance;
2. MPE evaluate distance is 20cm from user manual provide by manufacturer;

### 8.2 Simultaneous Transmission MPE

The sample only supports one BT modular with one antenna, one GPRS module with one antenna, it support simultaneous transmission for BT and GRPS, therefor, simultaneous transmission is required for accessment:

Operation Mode	MPE (mW/cm <sup>2</sup> ) GPRS850	MPE (mW/cm <sup>2</sup> ) BT	MPE (mW/cm <sup>2</sup> )	MPE Limits (mW/cm <sup>2</sup> )
GPRS 850 + BT(worst case)	0.3971	0.0006	0.3977	1.0000

## 9. Conclusion

The measurement results comply with the FCC Limit per 47 CFR 2.1091 for the uncontrolled RF Exposure of mobile device.

-----THE END OF REPORT-----