

Modular Approval Request FCC (KDB 996369 D01 & Part 15.212)

FCC ID: X8WBT840XEE

<i>Items to be covered by Single modular transmitters.</i>	<i>Answer from applicant</i>
1. The radio elements must have the radio frequency circuitry shielded. Physical components and tuning capacitor(s) may be located external to the shield, but must be on the module assembly.	The module has a metal shielded. Refer to the external photo of EUT
2. The module must have buffered modulation/data inputs to ensure that the device will comply with Part 15 requirements with any type of input signal.	Data to the modulation circuit is buffered as described in the circuit/block diagram - nRF52840 provided with the application.
3. The module must contain power supply regulation on the module	The module contains its own power supply regulation. Please refer to schematic as nRF52840 contain power regulation supplied to sub-functionality of the radio
4. The module must contain a permanently attached antenna, or contain a unique antenna connector, and be marketed and operated only with specific antenna(s), per §§ 15.203, 15.204(b), 15.204(c), 15.212(a), 2.929(b).	Device is equipped with External Antenna with unique non standard antenna port, u.fl and PCB and MCX Antenna. Refer to the photo of EUT.
5.The module must demonstrate compliance in a stand-alone configuration.	The module was tested standalone as shown in test report setup photographs filed with this application.
6.The module must be labeled with its permanently affixed FCC ID label, or use an electronic display (see KDB Publication 784748).	The modular has a permanent fixed label, and below statement was listed in the User Manual; The host device must be labeled to display the FCC ID of the module “Contains FCC ID:X8WBT840XEE”
7.The module must comply with all specific rules applicable to the transmitter, including all the conditions provided in the integration instructions by the grantee.	The module comply with all specific rules applicable to the transmitter including all the conditions provided in the integration instructions by the grantee, Refer to test report and user manual
8.The module must comply with RF exposure requirements.	The transmitter meets MPE calculation of 47CFR§ 2.1091 & 47 CFR §1.1307. Refer to MPE Reports and Refer to modular installation manual.

Items to be covered by <i>Split modular transmitters.</i>	Answer from applicant
1. The modular transmitter must comply with all requirements of a single modular transmitter except for items (1) & (5) of the above single modular approval requirements.	
2. Only the radio front end must be shielded. The physical crystal and tuning capacitors may be located external to the shielded radio elements. The interface between the split sections of the modular system must be digital with a minimum signalling amplitude of 150 mV peak-to-peak.	
3. Control information and other data may be exchanged between the transmitter control elements and radio front end.	
4. The sections of a split modular transmitter must be tested installed in a host device(s) similar to that which is representative of the platform(s) intended for use.	
5. Manufacturers must ensure that only transmitter control elements and radio front end components that have been approved together are capable of operating together. The transmitter module must not operate unless it has verified that the installed transmitter control elements and radio front end have been authorized together. Manufacturers may use means including, but not limited to, coding in hardware and electronic signatures in software to meet these requirements, and must describe the methods in their application for equipment authorization.	

Note: A limited modular approval (LMA) may be granted for *single* or *split* modular transmitters that comply partially with the requirements above.

Name and surname of applicant (or authorized representative): Paudy Tung / Engineer

Date: 2022/11/21

Signature:

