

Modular Approval Request FCC (KDB 996369 D01 & Part 15.212)

FCC ID: <u>X8WLR62E1</u>

Items to be covered by Single modular transmitters.	Answer from applicant
 The radio elements must have the radio frequen Physical components and tuning capacitor(s) may to the shield, but must be on the module assembly 	y be located external shielded. Refer to the external
2. The module must have buffered modulation/data the device will comply with Part 15 requirements v signal.	
3. The module must contain power supply regulation	
4. The module must contain a permanently attached a unique antenna connector, and be marketed ar specific antenna(s), per §§ 15.203, 15.204(b), 15.204(c), 1	d antenna, or contain nd operated only with 15.212(a), 2.929(b). Device is equipped with External Antenna with unique non standard antenna port, PCB, Chip and Dipole Antenna. Refer to the photo of EUT.
5.The module must demonstrate compliance in a stand configuration.	
6.The module must be labeled with its permanently aff use an electronic display (see KDB Publication 78	ixed FCC ID label, or The modular has a permanent
7.The module must comply with all specific rules transmitter, including all the conditions provide instructions by the grantee.	The module comply with all specific rules applicable to
8.The module must comply with RF exposure requiren	



Ite	ms to be covered by Split modular transmitters.	Answer from applicant
1.	The modular transmitter must comply with all requirements of a single modular transmitter except for items (1) & (5) of the above single modular approval requirements.	
2.	Only the radio front end must be shielded. The physical crystal and tuning capacitors may be located external to the shielded radio elements. The interface between the split sections of the modular system must be digital with a minimum signalling amplitude of 150 mV peak-to-peak.	
3.	Control information and other data may be exchanged between the transmitter control elements and radio front end.	
4.	The sections of a split modular transmitter must be tested installed in a host device(s) similar to that which is representative of the platform(s) intended for use.	
5.	Manufacturers must ensure that only transmitter control elements and radio front end components that have been approved together are capable of operating together. The transmitter module must not operate unless it has verified that the installed transmitter control elements and radio front end have been authorized together. Manufacturers may use means including, but not limited to, coding in hardware and electronic signatures in software to meet these requirements, and must describe the methods in their application for equipment authorization.	

Note: A limited modular approval (LMA) may be granted for *single* or *split* modular transmitters that comply partially with the requirements above.

Name	and surname of applic	ant (or <u>authorized</u> representative):	Paudy Tung I
Engir	nner		
Date: _	2024/1/18	Signature: 244d	Tung



Revision Record Sheet:

Revision	Section number	Page number	Date	Remark(s)	issued by
5		1	18-01-2024	History sheet added	WJJ

Issued/modified by : Willem Jan Jong Function : Team Lead

Revision : 5

Date : 18-01-2024

Verified by : Axel Gase
Function : Quality Manager
Date : 18-01-2024

Released by : Axel Gase

Function : Manager Quality Assurance

Date of release: : 18-01-2024