



FCC ID TEST REPORT

for

BLUETOOTH KEYBOARD

MODEL: BL-BKB80B

Trade Mark: R&Y

FCC ID: X9PBKB80

Test Report Number: WSCT12090665E

Issued Date: September 20, 2012

Issued for

Shenzhen Paoluy Silicone Technology Co., Ltd.

**No.31, Furong Road, Gushu Village Xixiang Town, Baoan Distric,
Shenzhen, China**

Issued By:

WORLD STANDARDIZATION CERTIFICATION & TESTING CO., LTD.

**Building A, Baoshi Science & Technology Park, Baoshi Road,
Bao'an District, Shenzhen, Guangdong, China**

TEL: +86-755-26996192

FAX: +86-755-26996253

Note: This report shall not be reproduced except in full, without the written approval of World Standardization Certification & Testing CO., LTD. This document may be altered or revised by World Standardization Certification & Testing CO., LTD. personnel only, and shall be noted in the revision section of the document. The test results in the report only apply to the tested sample.





Report No.: WSCT12090665E
FCC ID: X9PBKB80

Issued: September 20, 2012

Revised: None
ACC. NO. L3732
www.cnas.org.cn

Revision History Of Report

Rev.	Issue No.	Revisions	Effect Page	Revised By
00	WSCT12090665E	Initial Issue	ALL	Kallen Wang





Report No.: WSCT12090665E
FCC ID: X9PBKB80

Issued: September 20, 2012

Revised: None
ACC. NO. L3732
www.cnas.org.cn

TABLE OF CONTENTS

1	TEST CERTIFICATION.....	4
2	TEST RESULT SUMMARY	5
3	EUT DESCRIPTION.....	6
4	TEST METHODOLOGY	7
	4.1. DECISION OF FINAL TEST MODE.....	7
	4.2. EUT SYSTEM OPERATION.....	7
5	SETUP OF EQUIPMENT UNDER TEST.....	8
	5.1. DESCRIPTION OF SUPPORT UNITS	8
	5.2. CONFIGURATION OF SYSTEM UNDER TEST	8
6	FACILITIES AND ACCREDITATIONS	9
	6.1. FACILITIES	9
	6.2. ACCREDITATIONS	9
	6.3. MEASUREMENT UNCERTAINTY.....	9
7	TEST REQUIREMENTS.....	9
	7.1. CONDUCTED EMISSION MEASUREMENT.....	9
	7.2. Radiation Emission Test	9
	7.3. Band edge test.....	9
8.	ANTENNA REQUIREMENT	9
9	PHOTOGRAPHS OF THE TEST CONFIGURATION	9
10	PHOTOGRAPHS OF EUT	9





Report No.: WSCT12090665E
FCC ID: X9PBKB80

Issued: September 20, 2012

Revised: None
ACC. NO. L3732
www.cnas.org.cn

1 TEST CERTIFICATION

Product:	BLUETOOTH KEYBOARD
Model:	BL-BKB80B
Trade Mark	R&Y
Applicant:	Shenzhen Paoluy Silicone Technology Co., Ltd. No.31, Furong Road, Gushu Village Xixiang Town, Baoan Distric, Shenzhen, China
Factory:	Shenzhen Paoluy Silicone Technology Co., Ltd. No.31, Furong Road, Gushu Village Xixiang Town, Baoan Distric, Shenzhen, China
Tested:	September 14, 2012~ September 20, 2012
Test Voltage:	AC 120V/60Hz
Applicable Standards:	FCC Part 15 Subpart C: 2011 ANSI C63.4:2003

The above equipment has been tested by World Standardization Certification & Testing Co., Ltd., and found compliance with the requirements set forth in the technical standards mentioned above. The results of testing in this report apply only to the product/system, which was tested. Other similar equipment will not necessarily produce the same results due to production tolerance and measurement uncertainties.

Jack Ma

Tested By: _____

(Jack Ma)

Date: September 20, 2012

Kallen Wang

Approved By: _____

(Kallen Wang)

Date: September 20, 2012





Report No.: WSCT12090665E
FCC ID: X9PBKB80

Issued: September 20, 2012

Revised: None
ACC. NO. L3732
www.cnas.org.cn

2 TEST RESULT SUMMARY

Standard	Item	Result
FCC Part 15 Subpart C: Clause 15.249	Conducted emission Test	PASS
	Radiation Emission Test	PASS
	Band Edge Test	PASS

Note: 1. The test result judgment is decided by the limit of test standard
2. The information of measurement uncertainty is available upon the customer's request.





Report No.: WSCT12090665E
FCC ID: X9PBKB80

Issued: September 20, 2012

Revised: None
ACC. NO. L3732
www.cnas.org.cn

3 EUT DESCRIPTION

Product	BLUETOOTH KEYBOARD
Trade Mark	R&Y
Model	BL-BKB80B
Applicant	Shenzhen Paoluy Silicone Technology Co., Ltd.
Serial Number	N/A
Antenna Type	SMD ANTENNA
EUT Power Rating	DC 5V
Battery Power Rating	DC3.7V
Adapter Power Rating	AC100-240V 50/60Hz
Test Voltage	AC120V/60Hz
Temperature Range(Operating)	-20 ~ +55℃
Operating Frequency (Bluetooth)	2402MHz ~ 2480MHz
Number of Channels	79 Channels
USB Line	Unshielded: 1m

Note: N/A stand for no applicable.

Models difference

N/A



ADD: Building A, Baoshi Science & technology Park, Baoshi Road, Bao'an District, Shenzhen, Guangdong, China
TEL: 86-755-26996143/26996144/26996145/26996192 FAX: 86-755-26996253 E-mail: market@wsct.org.cn Http: www.wsct-cert.org

Member of the WSCT INC.



4 TEST METHODOLOGY

4.1. DECISION OF FINAL TEST MODE

The EUT was tested together with the below additional components, and configuration, which produced the worst emission levels, was selected and recorded in this report.

The measurement was performed at 3 axis for lie orientation, side orientation and stand orientation. The lie orientation is the worst mode, so only the worst mode test data was reported.

The following test mode was recorder in this report.

Test item	Test mode
Conducted Emission Test	Charging & Transmitting
Radiation Emission Test	CH1, CH40, CH79
Band Edge Test	CH1, CH79,

4.2. EUT SYSTEM OPERATION

1. Set up EUT with the support equipments.
2. Make sure the EUT transmitting continuously during the test.

4.3. Configuration of Test Setup

Evaluation for “xyz” 3 directions.





Report No.: WSCT12090665E
FCC ID: X9PBKB80

Issued: September 20, 2012

Revised: None
ACC. NO. L3732
www.cnas.org.cn

5 SETUP OF EQUIPMENT UNDER TEST

5.1. DESCRIPTION OF SUPPORT UNITS


The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Manufacturer	Description	Model	Serial Number	FCC
MLF	Adapter	IMU13	N/A	--

Note:

- 1) All the equipment/cables were placed in the worst-case configuration to maximize the emission during the test.
- 2) Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.

5.2. CONFIGURATION OF SYSTEM UNDER TEST



(BLUETOOTH KEYBOARD)



Report No.: WSCT12090665E
FCC ID: X9PBKB80

Issued: September 20, 2012

Revised: None
ACC. NO. L3732
www.cnas.org.cn

6 FACILITIES AND ACCREDITATIONS

6.1. FACILITIES

All measurement facilities used to collect the measurement data are located at

World Standardization Certification & Testing CO., LTD.

Building A, Baoshi Road, Baoshi Science & Technology Park, Bao'an District, Shenzhen, Guangdong, China

The sites are constructed in conformance with the requirements of ANSI C63.4 and CISPR Publication 22. All receiving equipment conforms to CISPR Publication 16-1, "Radio Interference Measuring Apparatus and Measurement Methods."

6.2. ACCREDITATIONS

Our laboratories are accredited and approved by the following approval agencies according to ISO/IEC 17025.

USA	FCC (The certificate registration number is 131628)
	TIMCO (The certificate registration number is Q2012033001)
Japan	VCCI (The certificate registration number is C-4128, R-2662)
Canada	INDUSTRY CANADA (The certificated registration number is 7700A-1)
Germany	TUV (The certificate registration number is UA50138086-0001,UA50138086-0002)
	EMCC (The certificated registration number is #080380)
	PHOENIX (The certificated registration number is 702777a)
China	CNAS (The certificated registration number is L3732)

Copies of granted accreditation certificates are available for downloading from our web site, <http://www.wsct-cert.org>

6.3. MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

Measurement	Frequency		Uncertainty
Conducted emissions	150kHz~30MHz		+/- 3.59dB
Radiated emissions	Horizontal	30MHz ~ 200MHz	+/- 4.77dB
		200MHz ~1000MHz	+/- 4.93dB
		1000MHz~25000 MHz	+/- 5.01dB
	Vertical	30MHz ~ 200MHz	+/- 5.04dB
		200MHz ~1000MHz	+/- 4.93dB
		1000MHz~25000 MHz	+/- 5.01dB

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.



Report No.: WSCT12090665E
FCC ID: X9PBKB80

Issued: September 20, 2012

Revised: None
ACC. NO. L3732
www.cnas.org.cn

7 TEST REQUIREMENTS

7.1. CONDUCTED EMISSION MEASUREMENT

7.1.1. LIMITS

FREQUENCY (MHz)	Class B (dBuV)	
	Quasi-peak	Average
0.15 - 0.5	66 - 56	56 - 46
0.50 - 5.0	56	46
5.0 - 30.0	60	50

NOTE:

- (1) The lower limit shall apply at the transition frequencies.
- (2) The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50 MHz.
- (3) All emanations from a class A/B digital device or system, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strengths specified above.

7.1.2. TEST INSTRUMENTS

Conducted Emission Test Site				
Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
EMI Test Receiver	R&S	ESCI	100005	12/16/2012
LISN	LS	LS16	16010222119	12/16/2012
LISN(EUT)	Mestec	AN3016	04/10040	12/22/2012

- NOTE:** 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to international system unit (SI).
2. N.C.R = No Calibration Request.

7.1.3. TEST PROCEDURES

The EUT was put on a wooden table which was 0.8metre high above the ground and connected to the AC mains through a Artificial Mains Network (A.M.N). The mains lead in excess of 1 m separating the EUT from the AMN was folded back and forth parallel to the lead so as to form a bundle with a length of 0.3m to 0.4m. The EUT was kept 0.4m from any other earthed conducting surface. Both sides of AC line were checked to find out the maximum conducted emission levels according to the test procedure during conducted emission test.

The bandwidth of the test receiver (ESCI) was set at 9KHz.

The frequency range from 150 KHz to 30 MHz was investigated.

The test data of the worst-case condition(s) was recorded.




Report No.: WSCT12090665E
FCC ID: X9PBKB80

Issued: September 20, 2012

Revised: None
ACC. NO. L3732
www.cnas.org.cn

7.1.4. TEST SETUP



For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.

7.1.5. Test Result

Model No.	BL-BKB80B	6dB Bandwidth	120 KHz
Environmental Conditions	26°C, 60% RH	Test Mode	Charging & Transmitting
Detector Function	Peak / Quasi-peak/AV	Test Result	Pass
Test By	Jack Ma		

NOTE: 1. L1 = Line One (Live Line) / L2 = Line Two (Neutral Line).

2. “---” denotes the emission level was or more than 2dB below the Average limit, so no re-check anymore.

Freq. = Emission frequency in MHz

Reading level(dBuV) = Receiver reading

Corr. Factor (dB) = Attenuator Factor+ Cable loss

Level (dBuV) = Reading level(dBuV) + Corr. Factor (dB)

Limit (dBuV) = Limit stated in standard

Margin (dB) = Level (dBuV) – Limits (dBuV)

Q.P.=Quasi-Peak






Report No.: WSCT12090665E
FCC ID: X9PBKB80

Issued: September 20, 2012

Revised: None
ACC. NO. L3732
www.cnas.org.cn

Please refer to following diagram for individual





Report No.: WSCT12090665E
FCC ID: X9PBKB80

Issued: September 20, 2012

Revised: None
ACC. NO. L3732
www.cnas.org.cn

Conducted Emission Measurement


File : PAOLUY

Data : #4

Date: 2012-9-19

Time: 13:56:47

80.0 dBuV



Site: 843 Shielded Room

Phase: N

Temperature: 26

Limit: FCC Part15 B Conduction(QP)

Power: AC 120V/60Hz

Humidity: 60 %

EUT: BLUETOOTH KEYBOARD

M/N: BL-BKB80B

Mode: Charging & Transmitting

Note:

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector	Comment
1		0.1516	30.92	10.44	41.36	65.91	-24.55	QP	
2		0.1516	13.37	10.44	23.81	55.91	-32.10	AVG	
3		0.1806	28.35	10.36	38.71	64.45	-25.74	QP	
4		0.1806	16.00	10.36	26.36	54.45	-28.09	AVG	
5		0.4420	33.28	10.46	43.74	57.02	-13.28	QP	
6		0.4420	22.76	10.46	33.22	47.02	-13.80	AVG	
7	*	2.5300	34.26	10.54	44.80	56.00	-11.20	QP	
8		2.5300	22.60	10.54	33.14	46.00	-12.86	AVG	
9		6.8500	28.23	10.53	38.76	60.00	-21.24	QP	
10		6.8500	16.37	10.53	26.90	50.00	-23.10	AVG	
11		19.7500	31.22	10.50	41.72	60.00	-18.28	QP	
12		19.7500	14.79	10.50	25.29	50.00	-24.71	AVG	

*:Maximum data x:Over limit l:over margin

(Reference Only)



ADD: Building A, Baoshi Science & Technology Park, Baoshi Road, Bao'an District, Shenzhen, Guangdong, China
TEL: 86-755-26996143/26996144/26996145/26996192 FAX: 86-755-26996253 E-mail: market@wsct.org.cn Http: www.wsct-cert.org

Member of the WSCT INC.



7.2. Radiation Emission Test

7.2.1. Limits

According to 15.249 the field strength of emissions from intentional radiators operated under these frequencies bands shall not exceed the following:

Fundamental Frequency	Field Strength of Fundamental		Field Strength of Spurious	
	mV/meter	dBuV/meter	uV/meter	dBuV/meter
902-928MHz	50	94	500	54
2400-2483.5MHz	50	94	500	54
5725-5875MHz	50	94	500	54
24.0-24.25GHz	250	108	2500	68

The above field strength limits are specified at a distance of 3 meters. Emissions radiated outside of the specified bands, shall be according to the general radiated limits in 15.209 as following:

Frequencies (MHz)	Field strength uV/meter	Measurement distance (meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

As shown in 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.

Frequency Range of Radiated Measurement

According to 15.33(a), the intentional radiator operates below 10GHz,must be measured up to the tenth harmonic of the highest fundamental frequency or 40GHz,whichever is lower



Report No.: WSCT12090665E
FCC ID: X9PBKB80

Issued: September 20, 2012

Revised: None
ACC. NO. L3732
www.cnas.org.cn

7.2.2. TEST INSTRUMENT

966 Chamber				
Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
EMI Test Receiver	R&S	ESCI	100005	12/16/2012
Spectrum Analyzer	R&S	FSU	100114	12/14/2012
Pre Amplifier	H.P.	HP8447E	2945A02715	12/16/2012
Pre-Amplifier	Compliance	PAM0118	1360976	12/16/2012
Bilog Antenna	SUNOL Sciences	JB3	A021907	12/10/2012
Horn Antenna	Compliance	CE18000	001	12/10/2012
Loop Antenna	Schwarzbeck	FESP5132	RS101	12/23/2012
Cable	TIME MICROWAVE	LMR-400	N-TYPE04	12/09/2012
Cable	TIME MICROWAVE	--	--	12/09/2012
System-Controller	CCS	N/A	N/A	N.C.R
Turn Table	CCS	N/A	N/A	N.C.R
Antenna Tower	CCS	N/A	N/A	N.C.R

Note: 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to international system unit (SI).
2. N.C.R = No Calibration Request.

Report No.: WSCT12090665E
FCC ID: X9PBKB80

Issued: September 20, 2012

Revised: None

7.2.3. Test procedure

The EUT was placed on a turn table which was 0.8 meter above ground. The turn table can rotate 360 degrees to determine the position of the maximum emission level. The EUT was set 3 meters away from the receiving antenna which was mounted on a antenna tower. At the frequency band of 30MHz to 1GHz, The measuring antenna moved up and down to find out the maximum emission level. It moved from 1 to 4 m for horizontal and vertical polarizations. The broadband antenna (calibrated by dipole antenna) was used as a receiving antenna. At the frequency band of 1GHz to 25GHz, The measuring antenna moved from 1 to 4 m for horizontal and vertical polarization. The horn antenna was used as a receiving antenna.

The resolution bandwidth and video bandwidth of the test receiver was 120 KHz and 300KHz for Quasi-peak detection at frequency below 1GHz.

The resolution bandwidth and video bandwidth of the test receiver was 1MHz and 3MHz for Peak emission measurement above 1GHz.

For Average emission above 1GHz, the resolution bandwidth and video bandwidth of the test receiver was 1MHz and 10Hz.

The EUT was tested in Chamber Site.

The test data of the worst case condition(s) was reported on the following pages.






Report No.: WSCT12090665E
FCC ID: X9PBKB80

Issued: September 20, 2012


Revised: None
ACC. NO. L3732
www.cnas.org.cn

7.2.4 Test setup diagram

Below 1GHz



Above 1GHz





Report No.: WSCT12090665E
FCC ID: X9PBKB80

Issued: September 20, 2012

Revised: None
ACC. NO. L3732
www.cnas.org.cn

7.2.5. Test Result

A. Fundamental Radiated Emission Data

Product:	BLUETOOTH KEYBOARD	Test mode:	CH Low~CH High
Test Item:	Fundamental Radiated Emission Data	Temperature:	25°C
Test Voltage:	AC 120V	Humidity:	56%RH
Test Result:	PASS		

CH Low

Freq. (MHz)	Emission(dBμV/m) Peak Detector/ AV	HORIZ/ VERT	Limits(dBμV/m) Peak/Average	Margin (dB)
2402.00	91.5/ 73.3	HORIZ	114/94	22.5/20.7
2402.00	94.5 / 76.4	VERT	114/94	19.5/17.6

CH Middle

Freq. (MHz)	Emission(dBμV/m) Peak Detector/ AV	HORIZ/ VERT	Limits(dBμV/m) Peak/ Average	Margin (dB)
2441.00	92.7/73.8	HORIZ	114/94	21.3/20.2
2441.00	93.6/74.1	VERT	114/94	20.4/19.9

CH High

Freq. (MHz)	Emission(dBμV/m) Peak Detector/ AV	HORIZ/ VERT	Limits(dBμV/m) Peak/ Average	Margin (dB)
2480.0	92.9/75.4	HORIZ	114/94	21.1/18.6
2480.0	94.3/77.2	VERT	114/94	19.7/16.8



Report No.: WSCT12090665E
FCC ID: X9PBKB80

Issued: September 20, 2012

Revised: None
ACC. NO. L3732
www.cnas.org.cn

B. Harmonics Radiated Emission Data

Product:	BLUETOOTH KEYBOARD	Test mode:	CH Low~CH High
Test Item:	Radiated Emission Data	Temperature:	25°C
Test Voltage:	AC 120V	Humidity:	56%RH
Test Result:	PASS		

CH Low

Freq. (MHz)	Emission(dBuV/m) Peak Detector	HORIZ/ VERT	Limits(dBuV/m) Peak/ Average	Margin (dB)
4804.12	49.2/33.2	H/V	74.0/54.0	24.8/20.8
7206.18	49.2/33.9	H/V	74.0/54.0	24.8/20.1
9608.24	48.7/33.2	H/V	74.0/54.0	25.3/20.8
12010.3	48.3/32.8	H/V	74.0/54.0	25.7/21.2
14412.36	48.5/33.2	H/V	74.0/54.0	25.5/20.8
16814.42	49.6/33.5	H/V	74.0/54.0	24.4/20.5
19216.48	48.6/32.7	H/V	74.0/54.0	25.4/21.3
21618.54	48.0/32.8	H/V	74.0/54.0	26.0/21.2
24020.6	47.9/32.9	H/V	74.0/54.0	26.1/22.1

CH Middle

Freq. (MHz)	Emission(dBuV/m) Peak Detector	HORIZ/ VERT	Limits(dBuV/m) Peak/ Average	Margin (dB)
4882.18	49.2/33.8	H/V	74.0/54.0	24.8/20.2
7323.27	49.6/33.7	H/V	74.0/54.0	24.4/20.3
9764.36	49.7/33.4	H/V	74.0/54.0	24.3/20.6
12205.45	48.3/32.8	H/V	74.0/54.0	25.7/21.2
14646.54	48.5/33.3	H/V	74.0/54.0	25.5/20.7
17087.63	48.4/32.2	H/V	74.0/54.0	25.6/21.8
19528.72	48.6/32.7	H/V	74.0/54.0	25.4/21.3
21969.81	48.0/32.2	H/V	74.0/54.0	26.0/21.8
24410.9	48.9/32.6	H/V	74.0/54.0	25.1/21.4





Report No.: WSCT12090665E
FCC ID: X9PBKB80

Issued: September 20, 2012

Revised: None
ACC. NO. L3732
www.cnas.org.cn

CH High

Freq. (MHz)	Emission(dBμV/m) Peak Detector	HORIZ/ VERT	Limits(dBμV/m) Peak/ Average	Margin (dB)
4960.26	49.1/33.9	H/V	74.0/54.0	24.9/20.1
7440.39	48.9/33.2	H/V	74.0/54.0	25.1/20.8
9920.52	48.7/33.5	H/V	74.0/54.0	25.3/20.5
12400.65	48.3/32.8	H/V	74.0/54.0	25.7/21.2
14880.78	49.5/32.7	H/V	74.0/54.0	24.5/21.3
17360.91	48.4/32.5	H/V	74.0/54.0	25.6/21.5
19841.04	47.6/32.7	H/V	74.0/54.0	26.4/21.3
22321.17	48.0/32.2	H/V	74.0/54.0	26.0/21.8
24801.3	48.9/33.7	H/V	74.0/54.0	25.1/20.4

Note: - means the emission is too low at least 20dB to the limit.

C. General Radiated Emission Data

Product: BLUETOOTH KEYBOARD Test mode: transmitting
Test Item: Radiated Emission Data Temperature: 25°C
Test Voltage: AC 120V Humidity: 56%RH
Test Result: PASS

Freq. (MHz)	Emission(dBμV/m) Peak Detector	HORIZ/ VERT	Limits(dBμV/m) Peak/ Average	Margin (dB)
96.82	30.2	HORIZ	43.5	13.3
96.82	32.7	VERT	43.5	10.8
195.53	27.5	HORIZ	43.5	16.0
195.53	30.7	VERT	43.5	12.8
432.43	29.7	HORIZ	46	16.3
432.43	32.5	VERT	46	13.5

NOTE: 9KHz-30MHz the measurements were greater than 20dB below the limit.



Report No.: WSCT12090665E
FCC ID: X9PBKB80

Issued: September 20, 2012

Revised: None

7.3. Band edge test

7.3.1. Limits

According 15.249(d), Emission radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50dB below the level of the fundamental or to the general radiated emission limits in section 15.209, whichever is the lesser attenuation.

7.3.2. TEST INSTRUMENT

Same as 7.2.2

7.3.3. Test procedure

1. The EUT was placed on a turntable which is 0.8m above ground plane.
2. Set EUT as continuous transmitting mode.
3. Set the EUT work on the CH1, CH79 individually.
4. Set SPA Frequency = Operation frequency, for PK: RBW =1MHz, VBW=3MHz
5. Set SPA trace max hold, then view.

7.3.4. Test setup diagram

Same as 7.2.4



Report No.: WSCT12090665E
FCC ID: X9PBKB80


Issued: September 20, 2012

Revised: None
ACC. NO. L3732
www.cnas.org.cn

7.3.5. Test result

Product: BLUETOOTH KEYBOARD
Test Item: Band edge
Test Voltage: AC 120V
Test Result: PASS

Test mode: CH Low, CH High
Temperature: 25°C
Humidity: 56%RH



Emission in the Restricted Bands

Frequency [MHz]	dBc [dB]	PK [dBμV/m]	Polarity (H/V)	AV limit [dBμV/m]
2310	-	34.6	V	54
2385	-	34.7	V	54
2390	-	34.8	V	54

The above field strength levels were measured in Vertical polarity which is the worst case.


The PK value is already under the AV limit, then AV value is not required.



Report No.: WSCT12090665E
FCC ID: X9PBKB80

Issued: September 20, 2012

Revised: None
ACC. NO. L3732
www.cnas.org.cn



Emission in the Restricted Bands

Frequency [MHz]	dBc [dB]	PK [dBμV/m]	Polarity (H/V)	AV limit [dBμV/m]
2483.5	-	32.87	V	54
2493.4	-	33.08	V	54
2500	-	33.83	V	54

The above field strength levels were measured in Vertical polarity which is the worst case.
The PK value is already under the AV limit, then AV value is not required.



Report No.: WSCT12090665E
FCC ID: X9PBKB80

Issued: September 20, 2012

Revised: None
ACC. NO. L3732
www.cnas.org.cn

8. ANTENNA REQUIREMENT

8.1. Standard applicable

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

8.2. Antenna connected construction

The antenna used in this product is PCB ANTENNA and no consideration of replacement.





Report No.: WSCT12090665E
FCC ID: X9PBKB80

Issued: September 20, 2012

Revised: None
ACC. NO. L3732
www.cnas.org.cn

9 PHOTOGRAPHS OF THE TEST CONFIGURATION

CONDUCTED EMISSION TEST



RADIATED EMISSION TEST BELOW 1GHz






Report No.: WSCT12090665E
FCC ID: X9PBKB80

Issued: September 20, 2012

Revised: None
ACC. NO. L3732
www.cnas.org.cn



RADIATED EMISSION TEST ABOVE 1GHz






Report No.: WSCT12090665E
FCC ID: X9PBKB80

Issued: September 20, 2012

Revised: None
ACC. NO. L3732
www.cnas.org.cn

10 PHOTOGRAPHS OF EUT

Appearance photograph of EUT



Appearance photograph of EUT





Report No.: WSCT12090665E
FCC ID: X9PBKB80

Issued: September 20, 2012

Revised: None
ACC. NO. L3732
www.cnas.org.cn

Appearance photograph of EUT



Appearance photograph of EUT





Report No.: WSCT12090665E
FCC ID: X9PBKB80

Issued: September 20, 2012


Revised: None

ACC. NO. L3732
www.cnas.org.cn

Internal photograph of EUT



PCB photograph of EUT





Report No.: WSCT12090665E
FCC ID: X9PBKB80

Issued: September 20, 2012

Revised: None
ACC. NO. L3732
www.cnas.org.cn

PCB photograph of EUT



PCB photograph of EUT

