



849 NW State Road 45  
Newberry, FL 32669 USA  
Ph: 888.472.2424 or 352.472.5500  
Fax: 352.472.2030  
Email: [info@timcoengr.com](mailto:info@timcoengr.com)  
Website: [www.timcoengr.com](http://www.timcoengr.com)

**FCC PART 15.247 AND IC RSS-210**  
**TEST REPORT**  
**DIGITAL SPREAD SPECTRUM**

Applicant	PROXENSE, LLC.	
Address	1013 N. State Road 7	
	Royal Palm Beach, Fl. 33411 USA	
FCC ID	X9S-BE1000	
IC	9282A-BE1000	
Model Number	BE1000	
Product Description	Beacon with 5.12dBi dipole antenna	
Date Sample Received	7/20/2010	
Date Tested	7/21/2010	
Tested By	Richard Block	
Approved By	Mario R. de Aranzeta	
Report Number	1677AT10TestReport_Ant 1.doc	
Test Results	<input checked="" type="checkbox"/> PASS	<input type="checkbox"/> FAIL

**THE ATTACHED REPORT SHALL NOT BE REPRODUCED EXCEPT IN FULL  
WITHOUT THE WRITTEN APPROVAL OF TIMCO ENGINEERING, INC.**



Testing Certificate # 0955-01



## TABLE OF CONTENT

GENERAL REMARKS .....	3
GENERAL INFORMATION .....	4
EMC EQUIPMENT LIST .....	5
TEST PROCEDURES .....	6
CALCULATION OF DUTY CYCLE .....	7
RADIATION INTERFERENCE .....	10
POWER LINE CONDUCTED INTERFERENCE .....	15
OCCUPIED BANDWIDTH .....	16
POWER OUTPUT .....	18
SPURIOUS EMISSIONS AT ANTENNA TERMINALS .....	19
RADIATED SPURIOUS EMISSIONS INTO ADJACENT RESTRICTED BAND .....	21
POWER SPECTRAL DENSITY .....	28
RADIATED EMISSIONS TEST SETUP PHOTO .....	29

APPLICANT: PROXENSE, LLC.

FCC ID: X9S-BE1000

IC: 9282A-BE1000

REPORT: Y:\P\PROXENSE\1677AT10\1677AT10TestReport\_Ant 1.doc

## **GENERAL REMARKS**

The attached report shall not be reproduced except in full without the written permission of Timco Engineering Inc.

The test results relate only to the items tested.

## **Summary**

The device under test does:

- fulfill the general approval requirements as identified in this test report
- not fulfill the general approval requirements as identified in this test report

## **Attestations**

This equipment has been tested in accordance with the standards identified in this test report. To the best of my knowledge and belief, these tests were performed using the measurement procedures described in this report.

All instrumentation and accessories used to test products for compliance to the indicated standards are calibrated regularly in accordance with ISO 17025 requirements.



Testing Certificate # 0955-01

I attest that the necessary measurements were made, under my supervision, at:

Timco Engineering Inc.  
849 NW State Road 45  
Newberry, FL 32669



## **Authorized Signatory Name:**

Mario de Aranzeta C.E.T.  
Compliance Engineer/ Lab. Supervisor

**Date:** 7/28/2010

APPLICANT: PROXENSE, LLC.

FCC ID: X9S-BE1000

IC: 9282A-BE1000

REPORT: Y:\P\PROXENSE\1677AT10\1677AT10TestReport\_Ant 1.doc

## GENERAL INFORMATION

### DUT Specification

Applicable Standard	FCC Part 15.247, IC RSS-210 and RSS-GEN		
DUT Description	Beacon with 5.12dBi dipole antenna		
FCC ID	X9S-BE1000		
IC	9282A-BE1000		
Model	BE1000		
Operating Frequency	TX: 2405-2480 MHz		
DUT Power Source	<input type="checkbox"/> 110-120Vac/50- 60Hz		
	<input checked="" type="checkbox"/> DC Power PoE (Power over Ethernet)		
	<input type="checkbox"/> Battery Operated Exclusively		
Test Item	<input type="checkbox"/> Prototype	<input checked="" type="checkbox"/> Pre-Production	<input type="checkbox"/> Production
Type of Equipment	<input checked="" type="checkbox"/> Fixed	<input type="checkbox"/> Mobile	<input type="checkbox"/> Portable
Antenna Connector	SMA		
Antenna	5.12 dBi dipole		
Test Facility	Timco Engineering Inc. located at 849 NW State Road 45 Newberry, FL 32669 USA.		
Test Conditions	Temperature: 26°C Relative humidity: 50%		
Test Exercise	The DUT was placed in continuous transmit mode of operation.		

### Test Supporting Equipment

Supporting Device	Manufacturer	Model / FCC ID	Serial Number
N/A			

APPLICANT: PROXENSE, LLC.

FCC ID: X9S-BE1000

IC: 9282A-BE1000

REPORT: Y:\P\PROXENSE\1677AT10\1677AT10TestReport\_Ant 1.doc

**EMC EQUIPMENT LIST**

<b>Device</b>	<b>Manufacturer</b>	<b>Model</b>	<b>Serial Number</b>	<b>Cal/Char Date</b>	<b>Due Date</b>
3-Meter Semi-Anechoic Chamber	Panashield	N/A	N/A	Listed 3/10/10	3/10/12
AC Voltmeter	HP	400FL	2213A14499	CAL 3/23/09	3/23/11
Antenna: Dipole Kit	Electro-Metrics	TDA-30/1-4	153	CHAR 6/10/09	6/10/11
Frequency Counter	HP	5385A	3242A07460	CAL 5/26/09	5/26/11
Hygro-Thermometer	Extech	445703	0602	CAL 1/30/09	1/30/11
Modulation Analyzer	HP	8901A	3435A06868	CAL 5/26/09	5/26/11
Digital Multimeter	Fluke	FLUKE-77-3	79510405	CAL 5/18/09	5/18/11
Analyzer Tan Tower Preamplifier	HP	8449B-H02	3008A00372	CAL 11/21/09	11/21/11
Analyzer Tan Tower Quasi-Peak Adapter	HP	85650A	3303A01690	CAL 11/22/09	11/22/11
Analyzer Tan Tower RF Preselector	HP	85685A	3221A01400	CAL 11/21/09	11/21/11
Analyzer Tan Tower Spectrum Analyzer	HP	8566B Opt 462	3138A07786 3144A20661	CAL 11/24/09	11/24/11
Temperature Chamber	Tenney Engineering	TTRC	11717-7	CHAR 4/25/10	4/25/12

APPLICANT: PROXENSE, LLC.

FCC ID: X9S-BE1000

IC: 9282A-BE1000

REPORT: Y:\P\PROXENSE\1677AT10\1677AT10TestReport\_Ant 1.doc

## TEST PROCEDURES

**Radiation Interference:** ANSI C63.4-2003 using a spectrum analyzer, a preselector, a quasi-peak adapter, and an appropriate antenna. The analyzer was calibrated in dB above a microvolt at the output of the antenna. The resolution bandwidth was 100 kHz with an appropriate sweep speed and the video bandwidth was 300 kHz up to 1 GHz and 1 MHz with a video BW of 3 MHz above 1 GHz. When an emission was found, the table was rotated to produce the maximum signal strength. The antenna was placed in both the horizontal and vertical planes and the worse case emissions were reported. The spectrum was searched to at least the tenth (10) harmonic of the fundamental.

**Formula Of Conversion Factors:** The field strength at 3m was established by adding the meter reading of the spectrum analyzer (which is set to read in units of dBuV) to the antenna correction factor supplied by the antenna manufacturer plus the coax loss. The antenna correction factors are stated in terms of dB. The gain of the preselector was accounted for in the spectrum analyzer meter reading.

Example:

$$\begin{array}{llll}
 \text{Freq (MHz)} & \text{Meter Reading} & + \text{ACF} & + \text{CL} = \text{FS} \\
 33 & 20 \text{ dBuV} & + 10.36 \text{ dB} & + 0.5 = 30.86 \text{ dBuV/m @ 3m}
 \end{array}$$

**Power Line Conducted Interference:** The procedure used was ANSI C63.4-2003 using a 50uH LISN. Both lines were observed. The bandwidth of the spectrum analyzer was 10 kHz with an appropriate sweep speed. The spectrum was scanned from 0.15 to 30 MHz.

**Occupied Bandwidth:** A small sample of the transmitter output was fed into the spectrum analyzer and the attached plot was printed. The vertical scale is set to -10 dBm per division.

**Bandwidth 6.0dB:** The measurements were made with the spectrum analyzer's resolution bandwidth (RBW)=1 MHz and the video bandwidth (VBW) =3 MHz and the span set as shown on plot.

**Power Output:** The RF power output was measured at the antenna feed point using a peak power meter.

**Antenna Conducted Emissions:** The RBW=100 kHz, VBW=300 kHz and the span set to 10 MHz and the spectrum was scanned from 30 MHz to the 10<sup>th</sup> Harmonic of the fundamental. Above 1 GHz the resolution bandwidth was 1 MHz and the VBW = 3 MHz and the span to 50 MHz.

**ANSI C63.4-2003 10.1 Measurement Procedures:** The DUT was placed on a table 80 cm high and with dimensions of 1m by 1.5m. The DUT was placed in the center of the table (1.5m side). The table used for radiated measurements is capable of continuous rotation.

When an emission was found, the table was rotated to produce the maximum signal strength. At this point, the antenna was raised and lowered from 1m to 4m. The antenna was placed in both the horizontal and vertical planes. Emissions attenuated more than 20 dB below the permissible value are not reported.

APPLICANT: PROXENSE, LLC.

FCC ID: X9S-BE1000

IC: 9282A-BE1000

REPORT: Y:\P\PROXENSE\1677AT10\1677AT10TestReport\_Ant 1.doc

## CALCULATION OF DUTY CYCLE


The period of the pulse train is determined by observing it on an oscilloscope or a spectrum analyzer with zero (0) frequency span. A plot is then made of the pulse train with a sweep time of 100 milliseconds. This sweep determines the duration of the pulse train. This sweep allows the determination of the number of and type of pulses, i.e. long & short. Plots are then made showing the duration of each type of pulse and its duration. From the 100-millisecond plot, the number of a given type of pulse is then multiplied by the duration of that type pulse. This allows the calculation of the amount of time the DUT is on within 100 ms.

Long Pulse	0
Short Pulse	6(4.260 ms)
On Time	25.560 ms
Length of Pulse Train	100 ms
Total	0.2556

$$\begin{aligned}
 \text{dB} &= 20 \cdot \log(\text{ON TIME}) / \text{PERIOD} \\
 \text{dB} &= 20 \cdot \log(25.56 / 100) \\
 \text{dB} &= 20 \cdot \log(0.2556) \\
 \text{dB} &= -11.9
 \end{aligned}$$

See the following plots.

APPLICANT: PROXENSE, LLC.  
 FCC ID: X9S-BE1000  
 IC: 9282A-BE1000  
 REPORT: Y:\P\PROXENSE\1677AT10\1677AT10TestReport\_Ant 1.doc




APPLICANT: PROXENSE, LLC.

FCC ID: X9S-BE1000

IC: 9282A-BE1000

REPORT: Y:\P\PROXENSE\1677AT10\1677AT10TestReport\_Ant 1.doc



APPLICANT: PROXENSE, LLC.

FCC ID: X9S-BE1000

IC: 9282A-BE1000

REPORT: Y:\P\PROXENSE\1677AT10\1677AT10TestReport\_Ant 1.doc

## RADIATION INTERFERENCE

**Rules Part No.:** 15.247, 15.209, RSS-210, RSS-GEN

### Requirements:

Frequency	Limits
Part 15.209	
9 to 490 kHz	2400/F (kHz) $\mu$ V/m @ 300 meters
490 to 1705 kHz	24000/F (kHz) $\mu$ V/m @ 30 meters
1705 kHz to 30 MHz	29.54 dB $\mu$ V/m @ 30 meters
30 – 88	40.0 dB $\mu$ V/m @ 3 meters
80 – 216	43.5 dB $\mu$ V/m @ 3 meters
216 – 960	46.0 dB $\mu$ V/m @ 3 meters
Above 960	54.0 dB $\mu$ V/m @ 3 meters
Part 15.247	
Fundamental 902 – 928 MHz	127.37 dB $\mu$ V/m @ 3 meters
Fundamental 2.4 – 2.4835 MHz	127.37 dB $\mu$ V/m @ 3 meters
Harmonics	54.0 dB $\mu$ V/m @ 3 meters

Any emissions that fall in the restricted bands (15.205) must be less than or equal to 54 dB $\mu$ V/m. Spurious emissions not in a restricted band must be 20 dBc. Harmonics were checked through the 10<sup>th</sup> harmonic.

**Test Data:** All values are peak unless noted.

### Maximum conducted output power 21.8 dBm

Tuned Frequency MHz	Emission Frequency MHz	Meter Reading dB $\mu$ V	Ant. Polarity	Coax Loss dB	Correction Factor dB/m	Duty Cycle dB	Field Strength dB $\mu$ V/m	Margin dB	Peak or Average
2,405.00	2,405.00	75.8	H	3.18	32.25	11.90	99.33	28.05	
2,405.00	2,405.00	90.7	V	3.18	32.25	11.90	114.23	13.15	
2,405.00	4,810.00	21.0	H	4.91	34.10	11.90	48.11	5.89	Average
2,405.00	4,810.00	25.1	V	4.91	34.10	11.90	52.21	1.79	Average
2,405.00	4,810.00	31.5	H	4.91	34.10	11.90	58.61	15.39	Peak
2,405.00	4,810.00	34.7	V	4.91	34.10	11.90	61.81	12.19	Peak
2,405.00	7,215.00	17.0	H	5.73	36.04	11.90	46.87	7.13	Average
2,405.00	7,215.00	17.3	V	5.73	36.04	11.90	47.17	6.83	Average
2,405.00	7,215.00	26.6	H	5.73	36.04	11.90	56.47	17.53	Peak
2,405.00	7,215.00	27.4	V	5.73	36.04	11.90	57.27	16.73	Peak

APPLICANT: PROXENSE, LLC.

FCC ID: X9S-BE1000

IC: 9282A-BE1000

REPORT: Y:\P\PROXENSE\1677AT10\1677AT10TestReport\_Ant 1.doc

## TEST DATA CONTD.

Tuned Frequency MHz	Emission Frequency MHz	Meter Reading dBuV	Ant. Polarity	Coax Loss dB	Correction Factor dB/m	Duty Cycle dB	Field Strength dBuV/m	Margin dB	Peak or Average
2,405.00	9,620.00	8.2	H	6.79	36.72	11.90	39.81	14.19	Average
2,405.00	9,620.00	8.7	V	6.79	36.72	11.90	40.31	13.69	Average
2,405.00	9,620.00	18.8	V	6.79	36.72	11.90	50.41	23.59	Peak
2,405.00	9,620.00	19.6	H	6.79	36.72	11.90	51.21	22.79	Peak
2,405.00	12,025.00	5.5	H	7.82	38.72	11.90	40.14	13.86	
2,405.00	12,025.00	5.5	V	7.82	38.72	11.90	40.14	13.86	
2,440.00	2,440.00	72.3	H	3.21	32.34	11.90	95.95	31.43	
2,440.00	2,440.00	86.5	V	3.21	32.34	11.90	110.15	17.23	
2,440.00	4,880.00	21.4	H	4.94	34.10	11.90	48.54	5.46	Average
2,440.00	4,880.00	24.2	V	4.94	34.10	11.90	51.34	2.66	Average
2,440.00	4,880.00	31.4	H	4.94	34.10	11.90	58.54	15.46	Peak
2,440.00	4,880.00	34.5	V	4.94	34.10	11.90	61.64	12.36	Peak
2,440.00	7,320.00	17.4	V	5.79	36.06	11.90	47.35	6.65	Average
2,440.00	7,320.00	17.5	H	5.79	36.06	11.90	47.45	6.55	Average
2,440.00	7,320.00	26.4	V	5.79	36.06	11.90	56.35	17.65	Peak
2,440.00	7,320.00	27.5	H	5.79	36.06	11.90	57.45	16.55	Peak
2,440.00	9,760.00	5.9	H	6.83	36.86	11.90	37.69	16.31	Average
2,440.00	9,760.00	9.1	V	6.83	36.86	11.90	40.89	13.11	Average
2,440.00	9,760.00	16.3	H	6.83	36.86	11.90	48.09	25.91	Peak
2,440.00	9,760.00	18.7	V	6.83	36.86	11.90	50.49	23.51	Peak
2,440.00	12,200.00	6.0	H	7.94	38.86	11.90	40.90	13.10	
2,440.00	12,200.00	6.9	V	7.94	38.86	11.90	41.80	12.20	
2,475.00	2,475.00	72.7	H	3.23	32.44	11.90	96.47	30.91	
2,475.00	2,475.00	85.5	V	3.23	32.44	11.90	109.27	18.11	
2,475.00	4,950.00	19.7	H	4.98	34.10	11.90	46.88	7.12	Average
2,475.00	4,950.00	20.9	V	4.98	34.10	11.90	48.08	5.92	Average
2,475.00	4,950.00	34.9	V	4.98	34.10	11.90	62.08	11.92	Peak
2,475.00	4,950.00	29.2	H	4.98	34.10	11.90	56.38	17.62	Peak

APPLICANT: PROXENSE, LLC.

FCC ID: X9S-BE1000

IC: 9282A-BE1000

REPORT: Y:\P\PROXENSE\1677AT10\1677AT10TestReport\_Ant 1.doc

**TEST DATA CONTD.**

Tuned Frequency MHz	Emission Frequency MHz	Meter Reading dBuV	Ant. Polarity	Coax Loss dB	Correction Factor dB/m	Duty Cycle dB	Field Strength dBuV/m	Margin dB	Peak or Average
2,475.00	7,425.00	20.0	V	5.86	36.09	11.90	50.05	23.95	Peak
2,475.00	7,425.00	23.7	V	5.86	36.09	11.90	53.75	20.25	Peak
2,475.00	7,425.00	19.7	H	5.86	36.09	11.90	49.75	4.25	Average
2,475.00	7,425.00	29.3	H	5.86	36.09	11.90	59.35	14.65	Peak
2,475.00	9,900.00	5.3	H	6.87	37.00	11.90	37.27	16.73	Average
2,475.00	9,900.00	6.7	V	6.87	37.00	11.90	38.67	15.33	Average
2,475.00	9,900.00	14.2	H	6.87	37.00	11.90	46.17	27.83	Peak
2,475.00	9,900.00	16.7	V	6.87	37.00	11.90	48.67	25.33	Peak
2,475.00	12,375.00	-0.9	V	8.06	39.00	11.90	34.26	19.74	Average
2,475.00	12,375.00	6.5	H	8.06	39.00	11.90	41.66	12.34	
2,475.00	12,375.00	8.6	V	8.06	39.00	11.90	43.76	30.24	Peak

APPLICANT: PROXENSE, LLC.

FCC ID: X9S-BE1000

IC: 9282A-BE1000

REPORT: Y:\P\PROXENSE\1677AT10\1677AT10TestReport\_Ant 1.doc

**Maximum conducted output power 2.2 dBm**

Tuned Frequency MHz	Emission Frequency MHz	Meter Reading dBuV	Ant. Polarity	Coax Loss dB	Correction Factor dB/m	Duty Cycle dB	Field Strength dBuV/m	Margin dB	Peak or Average
2,480.00	2,480.00	56.3	H	3.24	32.45	11.90	80.09	47.29	
2,480.00	2,480.00	66.3	V	3.24	32.45	11.90	90.09	37.29	
2,480.00	4,960.00	9.0	H	4.98	34.10	11.90	36.18	17.82	
2,480.00	4,960.00	10.8	V	4.98	34.10	11.90	37.98	16.02	
2,480.00	7,440.00	9.4	H	5.86	36.09	11.90	39.45	14.55	
2,480.00	7,440.00	9.7	V	5.86	36.09	11.90	39.75	14.25	
2,480.00	9,920.00	5.7	H	6.88	37.02	11.90	37.70	16.30	
2,480.00	9,920.00	5.9	V	6.88	37.02	11.90	37.90	16.10	
2,480.00	12,400.00	4.7	V	8.08	39.02	11.90	39.90	14.10	
2,480.00	12,400.00	4.8	H	8.08	39.02	11.90	40.00	14.00	


APPLICANT: PROXENSE, LLC.

FCC ID: X9S-BE1000

IC: 9282A-BE1000

REPORT: Y:\P\PROXENSE\1677AT10\1677AT10TestReport\_Ant 1.doc

### **Method of Measuring Radiated Spurious Emissions**



**METHOD OF MEASUREMENT:** The procedure used was ANSI standard C63.4-2003 & the FCC/OET Guidance on Measurements for Spread Spectrum Systems – Public Notice DA 00-705 dated March 30<sup>th</sup>, 2000.

APPLICANT: PROXENSE, LLC.

FCC ID: X9S-BE1000

IC: 9282A-BE1000

REPORT: Y:\P\PROXENSE\1677AT10\1677AT10TestReport\_Ant 1.doc

## POWER LINE CONDUCTED INTERFERENCE

**Rules Part No.:** Part 15.207, RSS-210, RSS-GEN

### Requirements:

Frequency (MHz)	Quasi Peak Limits (dBuv)	Average Limits (dBuV)
0.15 – 0.5	66 – 56 *	56 – 46 *
0.5 – 5.0	56	46
5.0 – 30	60	50

\* Decrease with logarithm of frequency

**Test Data:** N/A: Device is powered by PoE (Power over Ethernet)

APPLICANT: PROXENSE, LLC.  
FCC ID: X9S-BE1000  
IC: 9282A-BE1000  
REPORT: Y:\P\PROXENSE\1677AT10\1677AT10TestReport\_Ant 1.doc

## OCCUPIED BANDWIDTH


**Rules Part No.:** 15.247(a)(2), RSS-210, RSS-GEN

**Requirements:** The 6 dB bandwidth must be greater than 500 kHz.

### Test Data:

Three places in the band were measured and the worst case reported.

#### 6 dB Bandwidth




APPLICANT: PROXENSE, LLC.

FCC ID: X9S-BE1000

IC: 9282A-BE1000

REPORT: Y:\P\PROXENSE\1677AT10\1677AT10TestReport\_Ant 1.doc

**20 dB Bandwidth**


APPLICANT: PROXENSE, LLC.

FCC ID: X9S-BE1000


IC: 9282A-BE1000

REPORT: Y:\P\PROXENSE\1677AT10\1677AT10TestReport\_Ant 1.doc

## POWER OUTPUT

**Rules Part #:** 15.247(b) 1 Watt conducted, 4W ERP

TEST SET UP:



\*Harmonics were checked through the 10<sup>th</sup> harmonic\*

### Test Results:


Frequency MHz	Po dBm	Po Watts
2405	22.2	0.166
2440	21.8	0.151
2475	21.6	0.145
2480	2.2	0.002

APPLICANT: PROXENSE, LLC.  
 FCC ID: X9S-BE1000  
 IC: 9282A-BE1000  
 REPORT: Y:\P\PROXENSE\1677AT10\1677AT10TestReport\_Ant 1.doc

## SPURIOUS EMISSIONS AT ANTENNA TERMINALS

**Requirements:** Emissions must be at least 20dB down from the highest emission level within the authorized band as measured with a 100 kHz RBW.

15.247(c) Method of Measuring RF Conducted Spurious Emissions



### Test Data:

Tuned Frequency MHz	Emission Frequency MHz	Meter Reading dBuV	Emission dBc
2405	2405	124.9	0.0
2405	4810	52.2	72.7
2405	7215	54.0	70.9
2405	9620	52.5	72.4
2405	12025	53.1	71.8
2405	14430	57.3	67.6
2405	16835	59.5	65.4
2405	19240	62.0	62.9
2405	21645	63.3	61.6
2440	2440	123.9	0.0
2440	4880	52.2	71.7
2440	7320	54.0	69.9
2440	9760	52.5	71.4
2440	12200	53.1	70.8
2440	14640	57.3	66.6
2440	17080	59.5	64.4
2440	19520	62.0	61.9
2440	21960	63.3	60.6

APPLICANT: PROXENSE, LLC.

FCC ID: X9S-BE1000

IC: 9282A-BE1000

REPORT: Y:\P\PROXENSE\1677AT10\1677AT10TestReport\_Ant 1.doc

**TEST DATA CONTD.**

<b>Tuned Frequency MHz</b>	<b>Emission Frequency MHz</b>	<b>Meter Reading dBuV</b>	<b>Emission dBc</b>
2475	2475	123.7	0.0
2475	4950	53.5	70.2
2475	7425	53.2	70.5
2475	9900	53.6	70.1
2475	12375	52.4	71.3
2475	14850	57.2	66.5
2475	17325	58.2	65.5
2475	19800	62.9	60.8
2475	22275	62.6	61.1
2480	2480	103.4	20.3
2480	4960	50.3	73.4
2480	7440	52.0	71.7
2480	9920	52.4	71.3
2480	12400	52.3	71.4
2480	14880	57.4	66.3
2480	17360	57.8	65.9
2480	19840	63.1	60.6
2480	22320	62.9	60.8

APPLICANT: PROXENSE, LLC.

FCC ID: X9S-BE1000

IC: 9282A-BE1000


REPORT: Y:\P\PROXENSE\1677AT10\1677AT10TestReport\_Ant 1.doc

## RADIATED SPURIOUS EMISSIONS INTO ADJACENT RESTRICTED BAND

**Requirements:** Emissions that fall in the restricted bands (15.205). These emissions must be less than or equal to 500 uV/m (54 dBuV/m).

**Test Procedure:** An in band field strength measurement of the fundamental Emission using the RBW and detector function required by C63.4-2000 and FCC Rules. The procedure was repeated with an average detector and a plot made. The calculated field strength in the adjacent restricted band is presented below.

Lower adjacent restricted band – Peak



Tuned Frequency MHz	Emission Frequency MHz	Meter Reading dBuV	Ant. Pol	Coax Loss dB	Correction Factor dB/m	Duty Cycle dB	Field Strength dBuV/m	Margin dB
2,405.00	2,375.00	25.5	V	3.16	32.18	11.90	48.94	25.06


APPLICANT: PROXENSE, LLC.

FCC ID: X9S-BE1000

IC: 9282A-BE1000

REPORT: Y:\P\PROXENSE\1677AT10\1677AT10TestReport\_Ant 1.doc

## Lower adjacent restricted band – Average



Tuned Frequency MHz	Emission Frequency MHz	Meter Reading dB $\mu$ V	Ant. Pol	Coax Loss dB	Correction Factor dB/m	Duty Cycle dB	Field Strength dB $\mu$ V/m	Margin dB
2,405.00	2,389.80	13.9	V	3.17	32.21	11.90	37.38	16.62


APPLICANT: PROXENSE, LLC.

FCC ID: X9S-BE1000

IC: 9282A-BE1000


REPORT: Y:\P\PROXENSE\1677AT10\1677AT10TestReport\_Ant 1.doc

## Lower Band edge



APPLICANT: PROXENSE, LLC.  
 FCC ID: X9S-BE1000  
 IC: 9282A-BE1000  
 REPORT: Y:\P\PROXENSE\1677AT10\1677AT10TestReport\_Ant 1.doc

## Upper Bandedge 2475 MHz Peak



Tuned Frequency MHz	Emission Frequency MHz	Meter Reading dB $\mu\text{V}$	Ant. Pol	Coax Loss dB	Correction Factor dB/m	Duty Cycle dB	Field Strength dB $\mu\text{V/m}$	Margin dB
2,475.00	2,483.50	39.9	V	3.24	32.46	11.90	63.70	10.30


APPLICANT: PROXENSE, LLC.

FCC ID: X9S-BE1000

IC: 9282A-BE1000

REPORT: Y:\P\PROXENSE\1677AT10\1677AT10TestReport\_Ant 1.doc

## Upper Bandedge 2475 MHz Average



Tuned Frequency MHz	Emission Frequency MHz	Meter Reading dB $\mu$ V	Ant. Pol	Coax Loss dB	Correction Factor dB/m	Duty Cycle dB	Field Strength dB $\mu$ V/m	Margin dB
2,475.00	2,483.50	29.6	V	3.24	32.46	11.90	53.40	0.60


APPLICANT: PROXENSE, LLC.

FCC ID: X9S-BE1000

IC: 9282A-BE1000

REPORT: Y:\P\PROXENSE\1677AT10\1677AT10TestReport\_Ant 1.doc

## Upper Bandedge 2480 MHz Peak



Tuned Frequency MHz	Emission Frequency MHz	Meter Reading dB <sub>u</sub> V	Ant. Pol	Coax Loss dB	Correction Factor dB/m	Duty Cycle dB	Field Strength dB <sub>u</sub> V/m	Margin dB
2,480.00	2,483.50	35.4	V	3.24	32.46	11.90	59.20	14.80


APPLICANT: PROXENSE, LLC.

FCC ID: X9S-BE1000

IC: 9282A-BE1000

REPORT: Y:\P\PROXENSE\1677AT10\1677AT10TestReport\_Ant 1.doc

## Upper Bandedge 2480 MHz Average



Tuned Frequency MHz	Emission Frequency MHz	Meter Reading dBuV	Ant. Pol	Coax Loss dB	Correction Factor dB/m	Duty Cycle dB	Field Strength dBuV/m	Margin dB
2,480.00	2,483.50	26.2	V	3.24	32.46	11.90	50.00	4.00

APPLICANT: PROXENSE, LLC.

FCC ID: X9S-BE1000

IC: 9282A-BE1000


REPORT: Y:\P\PROXENSE\1677AT10\1677AT10TestReport\_Ant 1.doc

## POWER SPECTRAL DENSITY

**Rules Part No.:** 15.247(d), RSS-210, RSS-GEN

**Requirements:** The peak level measured must be less than +8.0 dBm.

**Test Data:** SEE THE FOLLOWING PLOT



Three places in the band were measured and the worst case reported.

64.8 dB<sub>μ</sub>V  
+35 dB CF for 1 Hz to 3 kHz RBW  
 99.8 dB<sub>μ</sub>V  
 -7.2 dBm

APPLICANT: PROXENSE, LLC.  
 FCC ID: X9S-BE1000  
 IC: 9282A-BE1000  
 REPORT: Y:\P\PROXENSE\1677AT10\1677AT10TestReport\_Ant 1.doc

**RADIATED EMISSIONS TEST SETUP PHOTO**



APPLICANT: PROXENSE, LLC.

FCC ID: X9S-BE1000

IC: 9282A-BE1000

REPORT: Y:\P\PROXENSE\1677AT10\1677AT10TestReport\_Ant 1.doc