



FCC PART 15.407

TEST REPORT

For

AudioCodes Ltd.

1 Hayarden Street, Airport City, Lod, Israel

FCC ID: XAK470HDB

Report Type: Original Report	Product Type: IP phone
Report Number: <u>RSZ201023001-00C</u>	
Report Date: <u>2020-12-29</u>	
Reviewed By: Jacob Kong <u>Jacob Kong</u>	
Prepared By: Bay Area Compliance Laboratories Corp. (Shenzhen) 6/F., West Wing, Third Phase of Wanli Industrial Building, Shihua Road, Futian Free Trade Zone, Shenzhen, Guangdong, China Tel: +86-755-33320018 Fax: +86-755-33320008 www.baclcorp.com.cn	

Note: This report may contain data that are not covered by the A2LA accreditation and are marked with an asterisk “★”.

BACL is not responsible for the authenticity of any test data provided by the applicant. Data included from the applicant that may affect test results are marked with an asterisk “*”. Customer model name, addresses, names, trademarks etc. are not considered data.

This report cannot be reproduced except in full, without prior written approval of the Company. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested. This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

TABLE OF CONTENTS

GENERAL INFORMATION.....	4
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT).....	4
OBJECTIVE	4
TEST METHODOLOGY	4
MEASUREMENT UNCERTAINTY	5
TEST FACILITY	5
SYSTEM TEST CONFIGURATION.....	6
DESCRIPTION OF TEST CONFIGURATION	6
EUT EXERCISE SOFTWARE	7
DUTY CYCLE	8
EQUIPMENT MODIFICATIONS	9
SUPPORT EQUIPMENT LIST AND DETAILS	9
EXTERNAL I/O CABLE.....	9
BLOCK DIAGRAM OF TEST SETUP	10
SUMMARY OF TEST RESULTS.....	11
TEST EQUIPMENT LIST	12
1.1307 (b) (1) & §2.1091- MAXIMUM PERMISSIBLE EXPOSURE (MPE).....	13
APPLICABLE STANDARD	13
RESULT	13
FCC §15.203 – ANTENNA REQUIREMENT.....	14
APPLICABLE STANDARD	14
ANTENNA CONNECTOR CONSTRUCTION	14
FCC §15.407 (b) (6) §15.207 (a) – CONDUCTED EMISSIONS	15
APPLICABLE STANDARD	15
EUT SETUP	15
EMI TEST RECEIVER SETUP.....	15
TEST PROCEDURE	15
TEST DATA	16
§15.205 & §15.209 & §15.407(B) (1), (2), (3), (4),(6),(7) – UNDESIRABLE EMISSION	19
APPLICABLE STANDARD	19
EUT SETUP	19
EMI TEST RECEIVER & SPECTRUM ANALYZER SETUP	20
TEST PROCEDURE	20
CORRECTED AMPLITUDE & MARGIN CALCULATION	21
TEST DATA	21
FCC §15.407(1), (5),(e) – 26 dB & 6dB EMISSION BANDWIDTH	46
APPLICABLE STANDARD	46
TEST PROCEDURE	46
TEST DATA	47
FCC §15.407(a)(1)(2)(3) – CONDUCTED TRANSMITTER OUTPUT POWER.....	48
APPLICABLE STANDARD	48
TEST PROCEDURE	48
TEST DATA	49

FCC §15.407(a) (1) (2) (3) - POWER SPECTRAL DENSITY	50
TEST PROCEDURE	50
TEST DATA	51
APPENDIX	52
APPENDIX A1:EMISSION BANDWIDTH	52
APPENDIX A2: OCCUPIED CHANNEL BANDWIDTH	68
APPENDIX A3: MIN EMISSION BANDWIDTH	90
APPENDIX B: MAXIMUM CONDUCTED OUTPUT POWER	96
APPENDIX C: MAXIMUM POWER SPECTRAL DENSITY	98
APPENDIX D: DUTY CYCLE.....	120

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

Product	IP phone
Tested Model	C470HD
Frequency Range	5G Wi-Fi: 5150-5250MHz; 5250-5350MHz; 5470-5725MHz; 5725-5850MHz
Maximum Conducted Average Output Power	5150-5250 MHz: 13.13dBm (802.11a), 13.78dBm(802.11n20), 12.56dBm(802.11n40) 11.93dBm (802.11ac20), 12.98dBm(802.11 ac40), 12.47dBm(802.11 ac80) 5250-5350MHz: 14.40dBm (802.11a), 13.82dBm(802.11n20), 11.78dBm(802.11n40) 12.48dBm (802.11ac20), 11.97dBm(802.11 ac40), 10.32dBm(802.11 ac80) 5470-5725MHz: 12.26dBm (802.11a), 11.07dBm(802.11n20), 9.99dBm(802.11n40) 10.35dBm (802.11ac20), 9.99dBm(802.11 ac40), 9.68dBm(802.11 ac80) 5725-5850 MHz: 12.80dBm (802.11a), 11.97dBm(802.11n20), 10.49 dBm(802.11n40) 10.75dBm (802.11ac20), 10.81dBm(802.11 ac40), 10.18dBm(802.11 ac80)
Modulation Technique	OFDM
Antenna Specification*	3.52 dBi(It is provided by the applicant)
Voltage Range	DC 12V from adapter
Date of Test	2020-11-13 to 2020-11-27
Sample serial number	RSZ201023001-RF-S1 (Assigned by BACL, Shenzhen)
Received date	2020-10-30
Sample/EUT Status	Good condition
Adapter information	Model: RD1202000-C55-29MG Input: AC 100-240V, 50/60Hz, 0.6A Output: DC 12V, 2.0A

Objective

This test report is in accordance with Part 2-Subpart J, Part 15-Subparts A and E of the Federal Communication Commissions rules.

The tests were performed in order to determine compliance with FCC Part 15, Subpart E, section 15.203, 15.205, 15.207, 15.209 and 15.407 rules.

Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices. And KDB789033 D02 General U-NII Test Procedures New Rules v02r01.

All emissions measurement was performed at Bay Area Compliance Laboratories Corp. (Shenzhen). The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

Measurement Uncertainty

Parameter	Uncertainty	
Occupied Channel Bandwidth	±5%	
RF Output Power with Power meter	±0.73dB	
RF conducted test with spectrum	±1.6dB	
AC Power Lines Conducted Emissions	±1.95dB	
Emissions, Radiated	Below 1GHz Above 1GHz	±4.75dB ±4.88dB
Temperature	±1°C	
Humidity	±6%	
Supply voltages	±0.4%	

Note: The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor K with the 95% confidence interval. Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty.

Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Shenzhen) to collect test data is located on the 6/F., West Wing, Third Phase of Wanli Industrial Building, Shihua Road, Futian Free Trade Zone, Shenzhen, Guangdong, China.

The test site has been approved by the FCC under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No.: 342867, the FCC Designation No.: CN1221.

The test site has been registered with ISED Canada under ISED Canada Registration Number 3062B.

SYSTEM TEST CONFIGURATION

Description of Test Configuration

The system was configured for testing in an engineering mode, which was provided by manufacturer.

The EUT can operate in 802.11a/n20/n40/ac20/ac40/ac80 modes.

For 5150-5250MHz Band, 7 channels are provided to testing:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
36	5180	44	5220
38	5190	46	5230
40	5200	48	5240
42	5210	/	/

For 5250-5350MHz Band, 7 channels are provided to testing:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
52	5260	60	5300
54	5270	62	5310
56	5280	64	5320
58	5290	/	/

For 5470-5725MHz Band, 18 channels are provided to testing:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
100	5500	124	5620
102	5510	126	5630
104	5520	128	5640
106	5530	132	5660
108	5540	134	5670
110	5550	136	5680
112	5560	140	5700
116	5580	/	/
118	5590	/	/
120	5600	/	/
122	5610	/	/

For 5725-5850MHz Band, 8 channels are provided to testing:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
149	5745	157	5785
151	5755	159	5795
153	5765	161	5805
155	5775	165	5825

EUT Exercise Software

“CRT”* was used. Test frequencies and power level were configured as below:

U-NII	Mode	Frequency (MHz)	Data Rate	Power Level*
5150 – 5250MHz	802.11 a	5180	6Mbps	14
		5200	6Mbps	14
		5240	6Mbps	14
	802.11 n20	5180	MCS0	15
		5200	MCS0	15
		5240	MCS0	14
	802.11 n40	5190	MCS0	13
		5230	MCS0	13
	802.11 ac20	5180	MCS0	14
		5200	MCS0	14
		5240	MCS0	14
	802.11 ac40	5190	MCS0	13
		5230	MCS0	13
	802.11 ac80	5210	MCS0	12
5250 – 5350MHz	802.11 a	5260	6Mbps	16
		5280	6Mbps	16
		5320	6Mbps	16
	802.11 n20	5260	MCS0	15
		5280	MCS0	15
		5320	MCS0	15
	802.11 n40	5270	MCS0	13
		5310	MCS0	13
	802.11 ac20	5260	MCS0	14
		5280	MCS0	14
		5320	MCS0	14
	802.11 ac40	5270	MCS0	13
		5310	MCS0	13
	802.11 ac80	5290	MCS0	12

U-NII	Mode	Frequency (MHz)	Data Rate set	Power Level*
5470 – 5725MHz	802.11 a	5500	6Mbps	16
		5580	6Mbps	16
		5700	6Mbps	16
	802.11 n20	5500	MCS0	15
		5580	MCS0	15
		5700	MCS0	15
	802.11 n40	5510	MCS0	13
		5550	MCS0	13
		5670	MCS0	13
	802.11 ac20	5500	MCS0	14
		5580	MCS0	14
		5700	MCS0	14
	802.11 ac40	5510	MCS0	13
		5550	MCS0	13
		5670	MCS8	13
	802.11 ac80	5530	MCS9	12
		5610	MCS9	12
5725 – 5850MHz	802.11 a	5745	6Mbps	16
		5785	6Mbps	16
		5825	6Mbps	16
	802.11 n20	5745	MCS0	15
		5785	MCS0	15
		5825	MCS0	15
	802.11 n40	5755	MCS0	13
		5795	MCS0	13
	802.11 ac20	5745	MCS0	14
		5785	MCS0	14
		5825	MCS0	14
	802.11 ac40	5755	MCS0	13
		5795	MCS0	13
	802.11 ac80	5775	MCS0	12

The worse-case data rates are determined to be as follows for each mode based upon investigations by measuring the average power and PSD across all data rated bandwidths, and modulations.

The software and power level was provided by the applicant.

Duty cycle

Test Result: Pass. Please refer to the Appendix.

Equipment Modifications


No modification was made to the EUT tested.

Support Equipment List and Details

Manufacturer	Description	Model	Serial Number
DELL	Laptop	Latitude E5430	11429208685
Kingston	USB Disk	DTSE9G2 64G	DTSE9G2
TPK Holdings	USB Disk	Unknown	USB Disk
HIKVISION	Router	DS-3WR03-E	10021642429

External I/O Cable

Cable Description	Length (m)	From Port	To
Un-shielding Un-Detachable AC Cable	1.0	Socket	LISN
Un-shielding Un-Detachable DC Cable	2.5	Adapter	EUT
Un-Shielding Detachable RJ45 Cable	10.0	EUT	Laptop
Un-Shielding Detachable RJ45 Cable	10.0	EUT	Router

Block Diagram of Test Setup

SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
§1.1307 (b) (1) & §2.1091	MaximuM Permissible exposure (MPE)	Compliance
§15.203	Antenna Requirement	Compliance
§15.407(b)(6)& §15.207(a)	Conducted Emissions	Compliance
§15.205& §15.209 &§15.407(b) (1), (2), (3), (4), (6) (7)	Undesirable Emission& Restricted Bands	Compliance
§15.407(a) (1), (5),(e)	26 dB Emission Bandwidth & 6dB Bandwidth	Compliance
§15.407(a)(1),(2), (3)	Conducted Transmitter Output Power	Compliance
§15.407 (a)(1), (2), (3)	Power Spectral Density	Compliance
§15.407 (h)	Transmit Power Control (TPC)	Not Applicable
§15.407 (h)	Dynamic Frequency Selection (DFS)	Compliance*

Not Applicable: the EUT has no TPC function which was declared by the applicant.

Compliance*: Please refer to the DFS report: RSZ201026003-00A.

TEST EQUIPMENT LIST

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
AC Line Conducted test					
Rohde & Schwarz	EMI Test Receiver	ESCI	101120	2020/08/04	2021/08/03
Rohde & Schwarz	LISN	ENV216	101613	2020/08/04	2021/08/03
Rohde & Schwarz	Transient Limitor	ESH3Z2	DE25985	2019/11/29	2020/11/28
Unknown	CE Cable	CE Cable	UF A210B-1-0720-504504	2019/11/29	2020/11/28
Rohde & Schwarz	CE Test software	EMC 32	V8.53.0	NCR	NCR
Radiated Emission Test					
R&S	EMI Test Receiver	ESR3	102455	2020/08/04	2021/08/03
Sonoma instrument	Pre-amplifier	310 N	186238	2020/08/04	2021/08/03
Sunol Sciences	Broadband Antenna	JB1	A040904-1	2017/12/22	2020/12/21
Unknown	Cable 2	RF Cable 2	F-03-EM197	2019/11/29	2020/11/28
Unknown	Cable	Chamber Cable 1	F-03-EM236	2019/11/29	2020/11/28
Rohde & Schwarz	Auto test software	EMC 32	V9.10	NCR	NCR
Rohde & Schwarz	Spectrum Analyzer	FSV40-N	102259	2020/08/04	2021/08/03
COM-POWER	Pre-amplifier	PA-122	181919	2019/11/29	2020/11/28
Quinstar	Amplifier	QLW-18405536-J0	15964001002	2019/11/29	2020/11/28
Sunol Sciences	Horn Antenna	DRH-118	A052604	2017/12/22	2020/12/21
Insulted Wire Inc.	RF Cable	SPS-2503-3150	02222010	2019/11/29	2020/11/28
Unknown	RF Cable	W1101-EQ1 OUT	F-19-EM005	2019/11/29	2020/11/28
Unknown	Signal Cable	RG-214	2	2019/11/29	2020/11/28
SNSD	Band Reject filter	BSF5150-5850MN-0899-004	5G filter	2020/04/20	2021/04/20
Ducommun Technologies	Horn antenna	ARH-4223-02	1007726-02 1304	2017/12/06	2020/12/05
Ducommun Technologies	Horn antenna	ARH-2823-02	1007726-02 1302	2017/12/06	2020/12/05
RF Conducted Test					
Tonscend Corporation	RF control Unit	JS0806-2	19D8060154	2020/08/04	2021/08/03
Rohde & Schwarz	Signal and Spectrum Analyzer	FSV40	101473	2020/08/04	2021/08/03
Unknown	RF Cable 2	Unknown	F-03-EM198	2019/11/12	2020/11/12
Unknown	RF Cable 2	Unknown	F-03-EM198	2020/11/12	2021/11/12

*** Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

1.1307 (b) (1) & §2.1091- MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Applicable Standard

According to subpart 1.1307 (b)(1), 2.1091 systems operating under the provisions of this section shall be operated in a manner that ensures the public is not exposed to RF energy level in excess of the communication guidelines.

Limits for General Population/Uncontrolled Exposure

Limits for General Population/Uncontrolled Exposure				
Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm²)	Averaging Time (Minutes)
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f ²)	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	f/1500	30
1500-100,000	/	/	1.0	30

f = frequency in MHz

* = Plane-wave equivalent power density

Result

Calculated Formulary:

Predication of MPE limit at a given distance

$$S = \frac{PG}{4\pi R^2}$$

S = power density (in appropriate units, e.g. mW/cm²)

P = power input to the antenna (in appropriate units, e.g., mW).

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor, is normally numeric gain.

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm)

Frequency (MHz)	Antenna Gain		Tune up conducted power		Evaluation Distance (cm)	Power Density (mW/cm²)	MPE Limit (mW/cm²)
	(dBi)	(numeric)	(dBm)	(mW)			
5150-5250	3.52	2.25	14.0	25.12	20	0.0112	1
5250-5350	3.52	2.25	14.5	28.18	20	0.0126	1
5470-5725	3.52	2.25	12.5	17.78	20	0.0080	1
5725-5850	3.52	2.25	13.0	19.95	20	0.0089	1

Note: The BT, 2.4G Wi-Fi and 5G Wi-Fi can't transmit at the same time.

To maintain compliance with the FCC's RF exposure guidelines, place the equipment at least 20cm from nearby persons.

Result: Pass

FCC §15.203 – ANTENNA REQUIREMENT

Applicable Standard

According to § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the user of a standard antenna jack or electrical connector is prohibited. The structure and application of the EUT were analyzed to determine compliance with section §15.203 of the rules. §15.203 state that the subject device must meet the following criteria:

- a. Antenna must be permanently attached to the unit.
- b. Antenna must use a unique type of connector to attach to the EUT.

Unit must be professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.

And according to FCC 47 CFR section 15.407 (a), if the transmitting antennas of directional gain greater than 6dBi are used, the transmit power and power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

Antenna Connector Construction

The EUT has one internal antenna arrangement for 5G Wi-Fi, which was permanently attached and the antenna gain is 3.52dBi, fulfill the requirement of this section. Please refer to the EUT photos.


Result: Compliance.

FCC §15.407 (b) (6) §15.207 (a) – CONDUCTED EMISSIONS

Applicable Standard

FCC §15.207, §15.407(b) (6)

EUT Setup



- Note:**
1. Support units were connected to second LISN.
 2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.207 limits.

The spacing between the peripherals was 10 cm.

EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

Test Procedure

During the conducted emission test, the adapter was connected to the LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All data was recorded in the Quasi-peak and average detection mode.


Test Data

Environmental Conditions

Temperature:	25 °C
Relative Humidity:	65 %
ATM Pressure:	101.0 kPa

The testing was performed by Haiguo Li on 2020-11-17.


EUT operation mode: Transmitting

AC 120V/60 Hz, Line:**Final Result 1**

Frequency (MHz)	QuasiPeak (dB μ V)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dB μ V)
0.253500	49.4	9.000	L1	19.8	12.2	61.6
0.278501	47.4	9.000	L1	19.8	13.5	60.9
0.301500	47.2	9.000	L1	19.7	13.0	60.2
0.313230	47.5	9.000	L1	19.8	12.4	59.9
1.038190	42.1	9.000	L1	19.9	13.9	56.0
1.136810	40.4	9.000	L1	19.8	15.6	56.0

Final Result 2

Frequency (MHz)	Average (dB μ V)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dB μ V)
0.253500	44.2	9.000	L1	19.8	7.4	51.6
0.278501	42.8	9.000	L1	19.8	8.1	50.9
0.301500	42.2	9.000	L1	19.7	8.0	50.2
0.313230	41.9	9.000	L1	19.8	8.0	49.9
1.038190	36.2	9.000	L1	19.9	9.8	46.0
1.136810	34.2	9.000	L1	19.8	11.8	46.0

AC 120V/60 Hz, Neutral:**Final Result 1**

Frequency (MHz)	QuasiPeak (dB μ V)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dB μ V)
0.257500	46.6	9.000	N	19.8	14.9	61.5
0.281500	47.2	9.000	N	19.7	13.6	60.8
0.305410	47.8	9.000	N	19.7	12.3	60.1
0.325050	47.1	9.000	N	19.8	12.5	59.6
1.058310	41.8	9.000	N	19.8	14.2	56.0
1.148990	40.1	9.000	N	19.8	15.9	56.0

Final Result 2

Frequency (MHz)	Average (dB μ V)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dB μ V)
0.222000	40.5	9.000	N	19.8	12.2	52.7
0.254000	43.7	9.000	N	19.8	7.9	51.6
0.270000	44.2	9.000	N	19.7	6.9	51.1
0.294000	43.1	9.000	N	19.7	7.3	50.4
0.322000	41.3	9.000	N	19.8	8.4	49.7
1.046000	37.4	9.000	N	19.8	8.6	46.0

§15.205 & §15.209 & §15.407(B) (1), (2), (3), (4),(6),(7) – UNDESIRABLE EMISSION

Applicable Standard

FCC §15.407 (b) (1), (2), (3), (4), (6), (7); §15.209; §15.205;


(b) Undesirable emission limits. Except as shown in paragraph (b)(7) of this section, the maximum emissions outside of the frequency bands of operation shall be attenuated in accordance with the following limits:


- (1) For transmitters operating in the 5.15-5.25 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.
- (2) For transmitters operating in the 5.25-5.35 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.
- (3) For transmitters operating in the 5.47-5.725 GHz band: All emissions outside of the 5.47-5.725 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.
- (4) For transmitters operating in the 5.725-5.85 GHz band:
 - (i) All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.

Unwanted emissions below 1 GHz must comply with the general field strength limits set forth in §15.209.

EUT Setup

Below 1 GHz:



Above 1 GHz:

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC 15.209 and FCC 15.407 limits.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

EMI Test Receiver & Spectrum Analyzer Setup

The system was investigated from 30 MHz to 40 GHz.

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

Frequency Range	RBW	Video B/W	IF B/W	Measurement
30 MHz – 1000 MHz	100 kHz	300 kHz	120 kHz	QP
Above 1 GHz	1 MHz	3 MHz	/	PK
	1MHz	10 Hz ^{Note 1}	/	Average
	1MHz	>1/T ^{Note 2}	/	Average

Note 1: when duty cycle is no less than 98%

Note 2: when duty cycle is less than 98%

Test Procedure**Radiated Spurious Emission**

During the radiated emission test, the adapter was connected to the AC floor outlet.

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all the installation combinations.

Data was recorded in Quasi-peak detection mode for frequency range of 30 MHz-1GHz, peak and Average detection modes for frequencies above 1GHz.

Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

$$\text{Corrected Amplitude} = \text{Meter Reading} + \text{Antenna Factor} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “Margin” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

Test Data


Environmental Conditions

Temperature:	28~32.1 °C
Relative Humidity:	52~58 %
ATM Pressure:	101.0 kPa

The testing was performed by Holland Yang on 2020-11-13 for below 1GHz and by Alen He from 2020-11-14 to 2020-11-17 for above 1GHz.

EUT operation mode: Transmitting

30 MHz – 1 GHz: (worst case is 802.11n20 mode 5260 MHz)



Final Result

Frequency (MHz)	QuasiPeak (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)
30.657250	22.24	40.00	17.76	273.0	V	343.0	-4.7
44.527000	19.55	40.00	20.45	169.0	V	0.0	-14.0
71.303875	20.15	40.00	19.85	145.0	V	124.0	-17.4
213.019875	33.93	43.50	9.57	202.0	V	104.0	-10.7
299.962250	30.36	46.00	15.64	401.0	H	184.0	-9.2
350.013000	31.45	46.00	14.55	109.0	H	134.0	-8.4

1 ~ 40 GHz:

Note: The test distance is 1m, so the correct factor from 3m to 1m is $20\log(3/1)=9.5\text{dB}$ which was added into the final limit.

5150-5250 MHz:

Frequency (MHz)	Receiver		Turtable Degree	Rx Antenna		Corrected Factor (dB/m)	Corrected Amplitude (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)					
	Reading (dB μ V)	PK/QP/Ave.		Height (m)	Polar (H / V)									
802.11a														
5180 MHz														
5146.06	34.42	PK	97	2.3	V	38.36	72.78	83.5	10.72					
5146.06	20.84	AV	97	2.3	V	38.36	59.20	63.5	4.30					
5394.81	31.54	PK	320	1.8	V	39.19	70.73	83.5	12.77					
5394.81	19.66	AV	320	1.8	V	39.19	58.85	63.5	4.65					
10360.00	44.84	PK	214	2.4	V	17.42	62.26	77.7	15.44					
15540.00	45.02	PK	246	1.6	V	17.54	62.56	83.5	20.94					
15540.00	32.25	Ave.	246	1.6	V	17.54	49.79	63.5	13.71					
5200 MHz														
10400.00	44.91	PK	161	1.0	V	17.52	62.43	77.7	15.27					
15600.00	44.57	PK	39	1.2	V	18.68	63.25	83.5	20.25					
15600.00	32.22	Ave.	39	1.2	V	18.68	50.90	63.5	12.60					
5240 MHz														
5146.06	32.09	PK	308	2.4	V	38.36	70.45	83.5	13.05					
5146.06	19.52	Ave.	308	2.4	V	38.36	57.88	63.5	5.62					
5404.52	31.98	PK	8	2.1	V	39.19	71.17	83.5	12.33					
5404.52	19.74	Ave.	8	2.1	V	39.19	58.93	63.5	4.57					
10480.00	44.20	PK	291	2.0	V	17.25	61.45	77.7	16.25					
15720.00	44.51	PK	265	1.1	V	17.86	62.37	83.5	21.13					
15720.00	32.18	Ave.	265	1.1	V	17.86	50.04	63.5	13.46					

Frequency (MHz)	Receiver		Turntable Degree	Rx Antenna		Corrected Factor (dB/m)	Corrected Amplitude (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)					
	Reading (dB μ V)	PK/QP/Ave.		Height (m)	Polar (H / V)									
802.11n20														
5180 MHz														
5148.16	38.53	PK	350	1.8	V	38.36	76.89	83.5	6.61					
5148.16	23.14	Ave.	350	1.8	V	38.36	61.50	63.5	2.00					
5427.92	31.96	PK	207	2.3	V	39.19	71.15	83.5	12.35					
5427.92	19.58	Ave.	207	2.3	V	39.19	58.77	63.5	4.73					
10360.00	44.23	PK	325	1.1	V	17.42	61.65	77.7	16.05					
15540.00	44.96	PK	73	2.2	V	17.54	62.50	83.5	21.00					
15540.00	31.56	Ave.	73	2.2	V	17.54	49.10	63.5	14.40					
5200 MHz														
10400.00	44.16	PK	47	1.2	V	17.52	61.68	77.7	16.02					
15600.00	44.74	PK	41	2.5	V	18.68	63.42	83.5	20.08					
15600.00	32.16	Ave.	41	2.5	V	18.68	50.84	63.5	12.66					
5240 MHz														
5121.45	31.63	PK	144	1.1	V	38.36	69.99	83.5	13.51					
5121.45	19.71	Ave.	144	1.1	V	38.36	58.07	63.5	5.43					
5392.11	32.94	PK	49	2.2	V	39.19	72.13	83.5	11.37					
5392.11	19.77	Ave.	49	2.2	V	39.19	58.96	63.5	4.54					
10480.00	44.18	PK	17	1.8	V	17.25	61.43	77.7	16.27					
15720.00	44.53	PK	17	2.5	V	17.86	62.39	83.5	21.11					
15720.00	32.09	Ave.	17	2.5	V	17.86	49.95	63.5	13.55					

Frequency (MHz)	Receiver		Turntable	Rx Antenna		Corrected Factor (dB/m)	Corrected Amplitude (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
	Reading (dB μ V)	PK/QP/Ave.	Degree	Height (m)	Polar (H / V)				
802.11n40									
5190 MHz									
5149.67	36.88	PK	218	1.7	V	38.36	75.24	83.5	8.26
5149.67	22.29	Ave.	218	1.7	V	38.36	60.65	63.5	2.85
5432.38	31.68	PK	159	1.3	V	39.29	70.97	83.5	12.53
5432.38	20.78	Ave.	159	1.3	V	39.29	60.07	63.5	3.43
10380.00	42.57	PK	209	1.7	V	17.42	59.99	77.7	17.71
15570.00	43.86	PK	122	1.5	V	18.58	62.44	83.5	21.06
15570.00	31.06	Ave.	122	1.5	V	18.58	49.64	63.5	13.86
5230 MHz									
5148.52	31.55	PK	19	1.5	V	38.36	69.91	83.5	13.59
5148.52	20.74	Ave.	19	1.5	V	38.36	59.10	63.5	4.40
5368.86	32.10	PK	96	1.4	V	39.09	71.19	83.5	12.31
5368.86	20.68	Ave.	96	1.4	V	39.09	59.77	63.5	3.73
10460.00	41.35	PK	35	1.7	V	17.15	58.50	77.7	19.20
15690.00	43.81	PK	115	1.5	V	17.76	61.57	83.5	21.93
15690.00	31.02	Ave.	115	1.5	V	17.76	48.78	63.5	14.72
802.11ac20									
5180 MHz									
5147.94	36.08	PK	241	1.9	V	38.36	74.44	83.5	9.06
5147.94	20.36	Ave.	241	1.9	V	38.36	58.72	63.5	4.78
5379.61	32.26	PK	37	1.4	V	39.09	71.35	83.5	12.15
5379.61	19.96	Ave.	37	1.4	V	39.09	59.05	63.5	4.45
10360.00	43.84	PK	57	1.5	V	17.42	61.26	77.7	16.44
5200 MHz									
10400.00	43.78	PK	283	1.7	V	17.52	61.30	77.7	16.40
5240 MHz									
5101.77	32.41	PK	194	2.3	V	38.26	70.67	83.5	12.83
5101.77	19.72	Ave.	194	2.3	V	38.26	57.98	63.5	5.52
5407.87	32.67	PK	268	2.4	V	39.19	71.86	83.5	11.64
5407.87	19.86	Ave.	268	2.4	V	39.19	59.05	63.5	4.45
10480.00	43.72	PK	5	2.4	V	17.25	60.97	77.7	16.73
802.11ac40									
5190 MHz									
5149.31	37.33	PK	36	1.3	V	38.36	75.69	83.5	7.81
5149.31	23.54	Ave.	36	1.3	V	38.36	61.90	63.5	1.60
5363.13	31.74	PK	29	1.5	V	39.09	70.83	83.5	12.67
5363.13	20.67	Ave.	29	1.5	V	39.09	59.76	63.5	3.74
10380.00	42.95	PK	146	1.1	V	17.42	60.37	77.7	17.33
5230 MHz									
5132.09	31.88	PK	133	1.7	V	38.36	70.24	83.5	13.26
5132.09	20.85	Ave.	133	1.7	V	38.36	59.21	63.5	4.29
5453.23	32.12	PK	211	1.3	V	39.37	71.49	83.5	12.01
5453.23	20.82	Ave.	211	1.3	V	39.37	60.19	63.5	3.31
10460.00	42.91	PK	329	2.3	V	17.15	60.06	77.7	17.64

Frequency (MHz)	Receiver		Turntable Degree	Rx Antenna		Corrected Factor (dB/m)	Corrected Amplitude (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
	Reading (dB μ V)	PK/QP/Ave.		Height (m)	Polar (H / V)				
802.11ac80									
5148.73	36.75	PK	312	2.0	V	38.36	75.11	83.5	8.39
5148.73	23.46	Ave.	312	2.0	V	38.36	61.82	63.5	1.68
5353.90	31.99	PK	307	1.5	V	39.09	71.08	83.5	12.42
5353.90	20.74	Ave.	307	1.5	V	39.09	59.83	63.5	3.67
10420.00	41.51	PK	324	1.3	V	17.52	59.03	77.7	18.67

5250-5350 MHz:

Frequency (MHz)	Receiver		Turntable Degree	Rx Antenna		Corrected Factor (dB/m)	Corrected Amplitude (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)					
	Reading (dB μ V)	PK/QP/Ave.		Height (m)	Polar (H/V)									
802.11a														
5260 MHz														
5106.55	32.20	PK	118	2.1	V	38.26	70.46	83.5	13.04					
5106.55	19.29	Ave.	118	2.1	V	38.26	57.55	63.5	5.95					
5450.37	32.18	PK	33	2.4	V	39.37	71.55	83.5	11.95					
5450.37	19.92	Ave.	33	2.4	V	39.37	59.29	63.5	4.21					
10520.00	45.05	PK	157	1.5	V	17.25	62.30	77.7	15.40					
15780.00	44.66	PK	283	1.1	V	17.36	62.02	83.5	21.48					
15780.00	31.55	Ave.	283	1.1	V	17.36	48.91	63.5	14.59					
5280 MHz														
10560.00	44.73	PK	10	2.4	V	17.91	62.64	77.7	15.06					
15840.00	44.85	PK	328	1.0	V	17.46	62.31	83.5	21.19					
15840.00	32.54	Ave.	328	1.0	V	17.46	50.00	63.5	13.50					
5320 MHz														
5121.38	31.78	PK	32	1.3	V	38.36	70.14	83.5	13.36					
5121.38	19.55	Ave.	32	1.3	V	38.36	57.91	63.5	5.59					
5350.24	35.37	PK	87	1.1	V	39.09	74.46	83.5	9.04					
5350.24	21.95	Ave.	87	1.1	V	39.09	61.04	63.5	2.46					
10640.00	45.56	PK	267	1.0	V	18.01	63.57	83.5	19.93					
10640.00	33.25	Ave.	267	1.0	V	18.01	51.26	63.5	12.24					
15960.00	44.74	PK	50	2.1	V	16.97	61.71	83.5	21.79					
15960.00	31.86	Ave.	50	2.1	V	16.97	48.83	63.5	14.67					

Frequency (MHz)	Receiver		Turntable Degree	Rx Antenna		Corrected Factor (dB/m)	Corrected Amplitude (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)					
	Reading (dB μ V)	PK/QP/Ave.		Height (m)	Polar (H/V)									
802.11n20														
5260 MHz														
5127.89	32.07	PK	132	1.4	V	38.36	70.43	83.5	13.07					
5127.89	19.58	Ave.	132	1.4	V	38.36	57.94	63.5	5.56					
5451.48	31.25	PK	120	1.6	V	39.37	70.62	83.5	12.88					
5451.48	19.65	Ave.	120	1.6	V	39.37	59.02	63.5	4.48					
10520.00	43.56	PK	102	1.9	V	17.25	60.81	77.7	16.89					
15780.00	44.40	PK	321	1.2	V	17.36	61.76	83.5	21.74					
15780.00	31.84	Ave.	321	1.2	V	17.36	49.20	63.5	14.30					
5280 MHz														
10560.00	44.49	PK	149	1.5	V	17.91	62.40	77.7	15.30					
15840.00	44.35	PK	249	2.0	V	17.46	61.81	83.5	21.69					
15840.00	31.81	Ave.	249	2.0	V	17.46	49.27	63.5	14.23					
5320 MHz														
5137.38	31.19	PK	109	1.3	V	38.36	69.55	83.5	13.95					
5137.38	19.56	Ave.	109	1.3	V	38.36	57.92	63.5	5.58					
5350.56	33.68	PK	232	1.4	V	39.09	72.77	83.5	10.73					
5350.56	20.97	Ave.	232	1.4	V	39.09	60.06	63.5	3.44					
10640.00	44.19	PK	24	2.1	V	18.01	62.20	83.5	21.30					
10640.00	31.41	Ave.	24	2.1	V	18.01	49.42	63.5	14.08					
15960.00	44.21	PK	287	1.5	V	16.97	61.18	83.5	22.32					
15960.00	31.75	Ave.	287	1.5	V	16.97	48.72	63.5	14.78					
802.11n40														
5270MHz														
5107.85	31.78	PK	228	2.5	V	38.26	70.04	83.5	13.46					
5107.85	20.18	Ave.	228	2.5	V	38.26	58.44	63.5	5.06					
5424.90	31.98	PK	346	2.3	V	39.19	71.17	83.5	12.33					
5424.90	20.81	Ave.	346	2.3	V	39.19	60.00	63.5	3.50					
10540.00	41.72	PK	66	1.3	V	17.25	58.97	77.7	18.73					
15810.00	44.68	PK	7	1.8	V	17.46	62.14	83.5	21.36					
15810.00	32.31	Ave.	7	1.8	V	17.46	49.77	63.5	13.73					
5310 MHz														
5121.38	32.35	PK	298	1.2	V	38.36	70.71	83.5	12.79					
5121.38	20.72	Ave.	298	1.2	V	38.36	59.08	63.5	4.42					
5353.90	37.40	PK	221	2.0	V	39.09	76.49	83.5	7.01					
5353.90	22.76	Ave.	221	2.0	V	39.09	61.85	63.5	1.65					
10620.00	41.98	PK	134	2.3	V	18.01	59.99	83.5	23.51					
10620.00	30.46	Ave.	134	2.3	V	18.01	48.47	63.5	15.03					
15930.00	44.47	PK	230	2.4	V	19.37	63.84	83.5	19.66					
15930.00	32.25	Ave.	230	2.4	V	19.37	51.62	63.5	11.88					

Frequency (MHz)	Receiver		Turntable Degree	Rx Antenna		Corrected Factor (dB/m)	Corrected Amplitude (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)					
	Reading (dB μ V)	PK/QP/Ave.		Height (m)	Polar (H/V)									
802.11ac20														
5260 MHz														
5136.22	33.34	PK	131	2.5	V	38.36	71.70	83.5	11.80					
5136.22	19.60	Ave.	131	2.5	V	38.36	57.96	63.5	5.54					
5391.79	32.29	PK	44	1.6	V	39.19	71.48	83.5	12.02					
5391.79	19.65	Ave.	44	1.6	V	39.19	58.84	63.5	4.66					
10520.00	42.73	PK	267	1.8	V	17.25	59.98	77.7	17.72					
15780.00	44.88	PK	110	1.5	V	17.36	62.24	83.5	21.26					
15780.00	31.82	Ave.	110	1.5	V	17.36	49.18	63.5	14.32					
5280 MHz														
10560.00	44.01	PK	349	2.5	V	17.91	61.92	77.7	15.78					
15840.00	44.69	PK	327	1.8	V	17.46	62.15	83.5	21.35					
15840.00	31.75	Ave.	327	1.8	V	17.46	49.21	63.5	14.29					
5320 MHz														
5109.88	31.66	PK	74	2.3	V	38.26	69.92	83.5	13.58					
5109.88	19.76	Ave.	74	2.3	V	38.26	58.02	63.5	5.48					
5351.35	32.55	PK	63	1.8	V	39.09	71.64	83.5	11.86					
5351.35	20.71	Ave.	63	1.8	V	39.09	59.80	63.5	3.70					
10640.00	44.12	PK	158	1.4	V	18.01	62.13	83.5	21.37					
10640.00	31.05	Ave.	158	1.4	V	18.01	49.06	63.5	14.44					
15960.00	44.65	PK	159	1.5	V	16.97	61.62	83.5	21.88					
15960.00	31.71	Ave.	159	1.5	V	16.97	48.68	63.5	14.82					

Frequency (MHz)	Receiver		Turntable Degree	Rx Antenna		Corrected Factor (dB/m)	Corrected Amplitude (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)					
	Reading (dB μ V)	PK/QP/Ave.		Height (m)	Polar (H/V)									
802.11ac40														
5270 MHz														
5115.38	32.08	PK	156	1.3	V	38.36	70.44	83.5	13.06					
5115.38	20.91	Ave.	156	1.3	V	38.36	59.27	63.5	4.23					
5375.87	32.30	PK	57	2.0	V	39.09	71.39	83.5	12.11					
5375.87	20.76	Ave.	57	2.0	V	39.09	59.85	63.5	3.65					
10540.00	42.05	PK	50	1.3	V	17.25	59.30	77.7	18.40					
15810.00	44.73	PK	332	1.4	V	17.46	62.19	83.5	21.31					
15810.00	32.47	Ave.	332	1.4	V	17.46	49.93	63.5	13.57					
5310 MHz														
5123.12	32.17	PK	76	1.4	V	38.36	70.53	83.5	12.97					
5123.12	20.31	Ave.	76	1.4	V	38.36	58.67	63.5	4.83					
5354.54	35.59	PK	315	2.5	V	39.09	74.68	83.5	8.82					
5354.54	22.53	Ave.	315	2.5	V	39.09	61.62	63.5	1.88					
10620.00	42.37	PK	188	1.6	V	18.01	60.38	83.5	23.12					
10620.00	30.52	Ave.	188	1.6	V	18.01	48.53	63.5	14.97					
15930.00	44.54	PK	69	1.3	V	19.37	63.91	83.5	19.59					
15930.00	32.41	Ave.	69	1.3	V	19.37	51.78	63.5	11.72					
802.11ac80														
5290 MHz														
5124.86	32.79	PK	130	2.5	V	38.36	71.15	83.5	12.35					
5124.86	20.66	Ave.	130	2.5	V	38.36	59.02	63.5	4.48					
5353.58	33.50	PK	165	2.2	V	39.09	72.59	83.5	10.91					
5353.58	21.80	Ave.	165	2.2	V	39.09	60.89	63.5	2.61					
10580.00	41.76	PK	178	1.3	V	17.91	59.67	77.7	18.03					
15870.00	44.94	PK	353	1.3	V	19.27	64.21	83.5	19.29					
15870.00	32.92	Ave.	353	1.3	V	19.27	52.19	63.5	11.31					

5470-5725MHz:

Frequency (MHz)	Receiver		Turntable Degree	Rx Antenna		Corrected Factor (dB/m)	Corrected Amplitude (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)					
	Reading (dB μ V)	PK/QP/Ave.		Height (m)	Polar (H/V)									
802.11a														
5500 MHz														
5469.66	36.89	PK	348	2.1	V	39.37	76.26	77.7	1.44					
5755.45	33.68	PK	348	2.1	V	39.61	73.29	77.7	4.41					
11000.00	42.92	PK	63	2.3	V	17.66	60.58	83.5	22.92					
11000.00	29.67	Ave.	63	2.3	V	17.66	47.33	63.5	16.17					
16500.00	49.82	PK	144	1.1	V	19.82	69.64	77.7	8.06					
5580MHz														
11160.00	42.73	PK	9	2.2	V	17.39	60.12	83.5	23.38					
11160.00	29.58	Ave.	9	2.2	V	17.39	46.97	63.5	16.53					
16740.00	47.42	PK	133	2.3	V	19.22	66.64	77.7	11.06					
5700 MHz														
5305.00	31.27	PK	33	2.1	V	38.72	69.99	77.7	7.71					
5725.99	34.14	PK	33	2.1	V	39.49	73.63	77.7	4.07					
11400.00	42.65	PK	126	2.3	V	17.73	60.38	83.5	23.12					
11400.00	29.54	Ave.	126	2.3	V	17.73	47.27	63.5	16.23					
17100.00	49.22	PK	212	2.2	V	20.72	69.94	77.7	7.76					
802.11n20														
5500 MHz														
5468.98	36.51	PK	206	2.4	V	39.37	75.88	77.7	1.82					
5729.61	33.48	PK	245	2.4	V	39.49	72.97	77.7	4.73					
11000.00	42.52	PK	165	2.4	V	17.66	60.18	83.5	23.32					
11000.00	29.64	Ave.	165	2.4	V	17.66	47.30	63.5	16.20					
16500.00	48.03	PK	88	1.0	V	19.82	67.85	77.7	9.85					
5580 MHz														
11160.00	42.46	PK	92	1.2	V	17.39	59.85	83.5	23.65					
11160.00	29.61	Ave.	92	1.2	V	17.39	47.00	63.5	16.50					
16740.00	48.45	PK	71	1.4	V	19.22	67.67	77.7	10.03					
5700MHz														
5460.82	31.72	PK	352	2.4	V	39.37	71.09	77.7	6.61					
5726.57	37.79	PK	358	1.1	V	39.49	77.28	77.7	0.42					
11400.00	44.28	PK	196	2.3	V	17.73	62.01	83.5	21.49					
11400.00	31.38	Ave.	196	2.3	V	17.73	49.11	63.5	14.39					
17100.00	50.38	PK	258	1.9	V	20.72	71.10	77.7	6.60					

Frequency (MHz)	Receiver		Turntable Degree	Rx Antenna		Corrected Factor (dB/m)	Corrected Amplitude (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)					
	Reading (dB μ V)	PK/QP/Ave.		Height (m)	Polar (H/V)									
802.11n40														
5510 MHz														
5466.94	37.04	PK	278	1.1	V	39.37	76.41	77.7	1.29					
5766.84	33.09	PK	278	1.1	V	39.61	72.70	77.7	5.00					
11020.00	42.67	PK	272	2.5	V	17.66	60.33	83.5	23.17					
11020.00	30.35	Ave.	272	2.5	V	17.66	48.01	63.5	15.49					
16530.00	45.34	PK	329	1.6	V	19.92	65.26	77.7	12.44					
5550 MHz														
11100.00	42.43	PK	14	2.4	V	16.72	59.15	83.5	24.35					
11100.00	30.31	Ave.	14	2.4	V	16.72	47.03	63.5	16.47					
16650.00	47.12	PK	194	2.1	V	18.82	65.94	77.7	11.76					
5670 MHz														
5452.66	31.91	PK	191	1.2	V	39.37	71.28	77.7	6.42					
5798.86	33.4	PK	191	1.2	V	39.61	73.01	77.7	4.69					
11340.00	42.17	PK	179	1.9	V	17.43	59.60	83.5	23.90					
11340.00	30.21	Ave.	179	1.9	V	17.43	47.64	63.5	15.86					
17010.00	44.03	PK	173	1.7	V	18.81	62.84	77.7	14.86					
802.11ac20														
5500 MHz														
5468.98	34.29	PK	29	1.7	V	39.37	73.66	77.7	4.04					
5796.26	33.54	PK	29	1.7	V	39.61	73.15	77.7	4.55					
11000.00	42.46	PK	280	1.4	V	17.66	60.12	83.5	23.38					
11000.00	29.65	Ave.	280	1.4	V	17.66	47.31	63.5	16.19					
16500.00	47.83	PK	65	1.5	V	19.82	67.65	77.7	10.05					
5580 MHz														
11160.00	42.24	PK	253	1.3	V	17.39	59.63	83.5	23.87					
11160.00	29.59	Ave.	253	1.3	V	17.39	46.98	63.5	16.52					
16740.00	47.20	PK	224	1.4	V	19.22	66.42	77.7	11.28					
5700 MHz														
5379.20	31.73	PK	321	2.0	V	39.09	70.82	77.7	6.88					
5727.66	36.56	PK	321	2.0	V	39.49	76.05	77.7	1.65					
11400.00	42.31	PK	337	2.1	V	17.73	60.04	83.5	23.46					
11400.00	29.62	Ave.	337	2.1	V	17.73	47.35	63.5	16.15					
17100.00	48.53	PK	103	1.4	V	20.72	69.25	77.7	8.45					

Frequency (MHz)	Receiver		Turntable Degree	Rx Antenna		Corrected Factor (dB/m)	Corrected Amplitude (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)					
	Reading (dB μ V)	PK/QP/Ave.		Height (m)	Polar (H/V)									
802.11ac40														
5510 MHz														
5469.66	36.52	PK	91	1.5	V	39.37	75.89	77.7	1.81					
5777.80	33.09	PK	91	1.5	V	39.61	72.70	77.7	5.00					
11020.00	42.38	PK	289	1.8	V	17.66	60.04	83.5	23.46					
11020.00	30.41	Ave.	289	1.8	V	17.66	48.07	63.5	15.43					
16530.00	44.75	PK	342	1.4	V	19.92	64.67	77.7	13.03					
5550 MHZ														
11100.00	42.35	PK	177	1.4	V	16.72	59.07	83.5	24.43					
11100.00	30.38	Ave.	177	1.4	V	16.72	47.10	63.5	16.40					
16650.00	46.23	PK	141	2.4	V	18.82	65.05	77.7	12.65					
5670 MHz														
5468.98	31.57	PK	249	1.9	V	39.37	70.94	77.7	6.76					
5727.23	33.66	PK	249	1.9	V	39.49	73.15	77.7	4.55					
11340.00	42.03	PK	1	1.9	V	17.43	59.46	83.5	24.04					
11340.00	30.30	Ave.	1	1.9	V	17.43	47.73	63.5	15.77					
17010.00	44.87	PK	178	1.7	V	18.81	63.68	77.7	14.02					
802.11ac80														
5530MHz														
5461.50	32.84	PK	127	1.4	V	39.37	72.21	77.7	5.49					
5743.29	33.68	PK	127	1.4	V	39.49	73.17	77.7	4.53					
11060.00	42.51	PK	257	1.1	V	16.72	59.23	83.5	24.27					
11060.00	30.63	Ave.	257	1.1	V	16.72	47.35	63.5	16.15					
16590.00	44.54	PK	149	1.5	V	17.58	62.12	77.7	15.58					
5610 MHz														
5466.34	31.95	PK	76	1.3	V	39.37	71.32	77.7	6.38					
5775.09	33.37	PK	76	1.3	V	39.61	72.98	77.7	4.72					
11220.00	42.78	PK	243	1.0	V	17.39	60.17	83.5	23.33					
11220.00	31.09	Ave.	243	1.0	V	17.39	48.48	63.5	15.02					
16830.00	43.85	PK	204	1.8	V	20.62	64.47	77.7	13.23					

5725-5850 MHz:

Frequency (MHz)	Receiver		Turtable Degree	Rx Antenna		Corrected Factor (dB/m)	Corrected Amplitude (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)					
	Reading (dB μ V)	PK/QP/Ave.		Height (m)	Polar (H/V)									
802.11a														
5745 MHz														
5629.63	32.98	PK	132	2.5	V	39.46	72.44	77.7	5.26					
5694.61	33.4	PK	115	1.7	V	39.49	72.89	110.71	37.82					
5719.99	43.02	PK	115	1.7	V	39.49	82.51	120.3	37.79					
5724.82	48.09	PK	264	1.2	V	39.49	87.58	131.29	43.71					
3830.00	56.64	PK	253	1.1	V	4.12	60.76	83.5	22.74					
3830.00	54.03	Ave.	253	1.1	V	4.12	58.15	63.5	5.35					
11490.00	42.95	PK	115	1.3	V	17.47	60.42	83.5	23.08					
11490.00	29.74	Ave.	115	1.3	V	17.47	47.21	63.5	16.29					
17235.00	49.93	PK	119	2.5	V	22.14	72.07	77.7	5.63					
5785 MHz														
3856.60	57.10	PK	281	2.0	V	3.36	60.46	83.5	23.04					
3856.60	54.26	Ave.	281	2.0	V	3.36	57.62	63.5	5.88					
11570.00	42.86	PK	177	2.4	V	17.51	60.37	83.5	23.13					
11570.00	29.71	Ave.	177	2.4	V	17.51	47.22	63.5	16.28					
17355.00	49.03	PK	161	1.8	V	21.92	70.95	77.7	6.75					
5825 MHz														
5850.47	40.9	PK	1	1.9	V	39.87	80.77	130.63	49.86					
5855.59	38.06	PK	1	1.9	V	39.87	77.93	120.13	42.20					
5879.16	34.06	PK	39	2.2	V	39.87	73.93	111.62	37.69					
5928.64	33.69	PK	304	1.3	V	39.97	73.66	77.7	4.04					
3883.30	57.22	PK	348	2.0	V	3.36	60.58	83.5	22.92					
3883.30	54.62	Ave.	348	2.0	V	3.36	57.98	63.5	5.52					
11650.00	42.51	PK	261	2.1	V	16.18	58.69	83.5	24.81					
11650.00	29.65	Ave.	261	2.1	V	16.18	45.83	63.5	17.67					
17475.00	45.37	PK	203	2.0	V	20.11	65.48	77.7	12.22					

Frequency (MHz)	Receiver		Turntable Degree	Rx Antenna		Corrected Factor (dB/m)	Corrected Amplitude (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)					
	Reading (dB μ V)	PK/QP/Ave.		Height (m)	Polar (H/V)									
802.11n20														
5745 MHz														
5646.85	32.83	PK	186	2.2	V	39.46	72.29	77.7	5.41					
5699.96	33.4	PK	249	1.2	V	39.49	72.89	114.67	41.78					
5718.68	43.75	PK	249	1.2	V	39.49	83.24	119.93	36.69					
5722.49	47.16	PK	186	2.2	V	39.49	86.65	125.98	39.33					
3830.00	57.55	PK	90	1.1	V	4.12	61.67	83.5	21.83					
3830.00	54.56	Ave.	90	1.1	V	4.12	58.68	63.5	4.82					
11490.00	42.67	PK	284	2.1	V	17.47	60.14	83.5	23.36					
11490.00	29.35	Ave.	284	2.1	V	17.47	46.82	63.5	16.68					
17235.00	50.07	PK	261	1.5	V	22.14	72.21	77.7	5.49					
5785 MHz														
3856.60	57.13	PK	28	1.3	V	3.36	60.49	83.5	23.01					
3856.60	54.56	Ave.	28	1.3	V	3.36	57.92	63.5	5.58					
11570.00	42.53	PK	104	2.4	V	17.51	60.04	83.5	23.46					
11570.00	29.31	Ave.	104	2.4	V	17.51	46.82	63.5	16.68					
17355.00	48.48	PK	166	1.6	V	21.92	70.40	77.7	7.30					
5825 MHz														
5850.03	41.94	PK	202	2.3	V	39.87	81.81	131.63	49.82					
5855.83	38.74	PK	202	2.3	V	39.87	78.61	120.07	41.46					
5882.27	34.27	PK	75	1.2	V	39.87	74.14	109.32	35.18					
5934.82	33.54	PK	75	1.2	V	39.97	73.51	77.7	4.19					
3883.30	57.71	PK	242	2.1	V	3.36	61.07	83.5	22.43					
3883.30	55.29	Ave.	242	2.1	V	3.36	58.65	63.5	4.85					
11650.00	42.34	PK	236	1.3	V	16.18	58.52	83.5	24.98					
11650.00	29.25	Ave.	236	1.3	V	16.18	45.43	63.5	18.07					
17475.00	44.41	PK	195	1.8	V	20.11	64.52	77.7	13.18					

Frequency (MHz)	Receiver		Turntable Degree	Rx Antenna		Corrected Factor (dB/m)	Corrected Amplitude (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)					
	Reading (dB μ V)	PK/QP/Ave.		Height (m)	Polar (H/V)									
802.11n40														
5755 MHz														
5640.49	32.61	PK	309	1.7	V	39.46	72.07	77.7	5.63					
5698.44	36.26	PK	46	2.4	V	39.49	75.75	113.55	37.80					
5719.52	41.09	PK	46	2.4	V	39.49	80.58	120.17	39.59					
5724.29	43.23	PK	309	1.7	V	39.49	82.72	130.08	47.36					
3836.70	57.63	PK	113	1.9	V	4.12	61.75	83.5	21.75					
3836.70	54.10	Ave.	113	1.9	V	4.12	58.22	63.5	5.28					
11510.00	42.46	PK	100	1.4	V	17.47	59.93	83.5	23.57					
11510.00	31.26	Ave.	100	1.4	V	17.47	48.73	63.5	14.77					
17265.00	45.83	PK	265	2.4	V	18.97	64.80	77.7	12.90					
5795 MHz														
5851.07	35.79	PK	19	1.3	V	39.87	75.66	129.26	53.60					
5864.05	35.32	PK	19	1.3	V	39.87	75.19	117.77	42.58					
5878.22	34.07	PK	123	1.7	V	39.87	73.94	112.32	38.38					
5934.82	33.54	PK	123	1.7	V	39.97	73.51	77.7	4.19					
3863.30	57.74	PK	73	2.2	V	3.36	61.10	83.5	22.40					
3863.30	55.44	Ave.	73	2.2	V	3.36	58.80	63.5	4.70					
11590.00	42.23	PK	62	1.5	V	17.51	59.74	83.5	23.76					
11590.00	31.19	Ave.	62	1.5	V	17.51	48.70	63.5	14.80					
17385.00	42.80	PK	329	1.1	V	21.92	64.72	77.7	12.98					

Frequency (MHz)	Receiver		Turntable Degree	Rx Antenna		Corrected Factor (dB/m)	Corrected Amplitude (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)					
	Reading (dB μ V)	PK/QP/Ave.		Height (m)	Polar (H/V)									
802.11ac20														
5745 MHz														
5698.23	33.03	PK	129	2.0	V	39.49	72.52	113.39	40.87					
5719.75	41.76	PK	129	2.0	V	39.49	81.25	120.23	38.98					
5724.62	45.34	PK	162	1.6	V	39.49	84.83	130.83	46.00					
5640.34	32.94	PK	162	1.6	V	39.46	72.40	77.7	5.30					
3830.00	56.35	PK	254	2.4	V	4.12	60.47	83.5	23.03					
3830.00	54.19	Ave.	254	2.4	V	4.12	58.31	63.5	5.19					
11490.00	42.37	PK	322	1.3	V	17.47	59.84	83.5	23.66					
11490.00	29.34	Ave.	322	1.3	V	17.47	46.81	63.5	16.69					
17235.00	48.99	PK	341	1.2	V	22.14	71.13	77.7	6.57					
5785 MHz														
3856.70	57.17	PK	194	2.1	V	3.36	60.53	83.5	22.97					
3856.70	54.70	Ave.	194	2.1	V	3.36	58.06	63.5	5.44					
11570.00	42.45	PK	307	1.7	V	17.51	59.96	83.5	23.54					
11570.00	29.38	Ave.	307	1.7	V	17.51	46.89	63.5	16.61					
17355.00	47.64	PK	166	1.4	V	21.92	69.56	77.7	8.14					
5825 MHz														
5850.15	40.46	PK	285	2.3	V	39.87	80.33	131.36	51.03					
5857.19	36.79	PK	285	2.3	V	39.87	76.66	119.69	43.03					
5913.39	33.81	PK	79	1.3	V	39.87	73.68	86.29	12.61					
5953.82	33.21	PK	79	1.3	V	39.84	73.05	77.7	4.65					
3883.30	57.57	PK	227	2.1	V	3.36	60.93	83.5	22.57					
3883.30	55.07	Ave.	227	2.1	V	3.36	58.43	63.5	5.07					
11650.00	42.18	PK	61	2.4	V	16.18	58.36	83.5	25.14					
11650.00	29.28	Ave.	61	2.4	V	16.18	45.46	63.5	18.04					
17475.00	43.83	PK	165	2.0	V	20.11	63.94	77.7	13.76					

Frequency (MHz)	Receiver		Turntable Degree	Rx Antenna		Corrected Factor (dB/m)	Corrected Amplitude (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)					
	Reading (dB μ V)	PK/QP/Ave.		Height (m)	Polar (H/V)									
802.11ac40														
5755 MHz														
5647.21	32.5	PK	303	2.0	V	39.46	71.96	77.7	5.74					
5697.50	34.7	PK	32	2.1	V	39.49	74.19	112.85	38.66					
5719.99	41.44	PK	32	2.1	V	39.49	80.93	120.3	39.37					
5723.54	43.87	PK	303	2.0	V	39.49	83.36	128.37	45.01					
3836.60	57.41	PK	96	2.2	V	4.12	61.53	83.5	21.97					
3836.60	54.55	Ave.	96	2.2	V	4.12	58.67	63.5	4.83					
11510.00	42.41	PK	261	2.4	V	17.47	59.88	83.5	23.62					
11510.00	30.98	Ave.	261	2.4	V	17.47	48.45	63.5	15.05					
17265.00	45.37	PK	33	2.4	V	18.97	64.34	77.7	13.36					
5795 MHz														
5854.82	34.7	PK	56	1.2	V	39.87	74.57	120.71	46.14					
5856.81	34.53	PK	56	1.2	V	39.87	74.40	119.79	45.39					
5923.08	34.59	PK	172	1.1	V	39.97	74.56	79.12	4.56					
5938.62	34.04	PK	172	1.1	V	39.97	74.01	77.7	3.69					
3863.30	57.35	PK	130	1.8	V	3.36	60.71	83.5	22.79					
3863.30	55.44	Ave.	130	1.8	V	3.36	58.80	63.5	4.70					
11590.00	42.23	PK	91	2.4	V	17.51	59.74	83.5	23.76					
11590.00	30.92	Ave.	91	2.4	V	17.51	48.43	63.5	15.07					
17385.00	42.75	PK	353	2.1	V	21.92	64.67	77.7	13.03					

Frequency (MHz)	Receiver		Turntable Degree	Rx Antenna		Corrected Factor (dB/m)	Corrected Amplitude (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)					
	Reading (dB μ V)	PK/QP/Ave.		Height (m)	Polar (H/V)									
802.11ac80														
5775 MHz														
5634.70	33.64	PK	295	1.7	V	39.46	73.10	77.7	4.60					
5686.94	37.98	PK	36	1.0	V	39.49	77.47	105.04	27.57					
5717.55	40.63	PK	36	1.0	V	39.49	80.12	119.61	39.49					
5723.40	40.47	PK	178	1.0	V	39.49	79.96	128.05	48.09					
5851.91	35.3	PK	268	1.1	V	39.87	75.17	127.35	52.18					
5860.54	34.74	PK	268	1.1	V	39.87	74.61	118.75	44.14					
5878.73	33.98	PK	116	1.0	V	39.87	73.85	111.94	38.09					
5927.33	32.95	PK	116	1.0	V	39.97	72.92	77.7	4.78					
3850.00	57.50	PK	142	1.8	V	3.36	60.86	83.5	22.64					
3850.00	55.06	Ave.	142	1.8	V	3.36	58.42	63.5	5.08					
11550.00	43.57	PK	218	1.8	V	17.51	61.08	83.5	22.42					
11550.00	31.30	Ave.	218	1.8	V	17.51	48.81	63.5	14.69					
17325.00	43.28	PK	347	2.5	V	18.97	62.25	77.7	15.45					


Note:

Corrected Amplitude = Corrected Factor + Reading


Corrected Factor=Antenna factor (RX) + Cable Loss – Amplifier Factor

Margin = Limit- Corr. Amplitude


All other spurious emissions are 20 dB below the limit or are on the system noise floor level.

Peak**Pre-scan with 802.11n40 5795MHz
Horizontal**


Date: 17.NOV.2020 13:16:14




Date: 17.NOV.2020 14:00:49




Vertical







Date: 17.NOV.2020 13:51:45




Date: 17.NOV.2020 14:11:02

**Average
Horizontal**

Date: 17.NOV.2020 13:20:49




Date: 17.NOV.2020 14:05:14




Date: 17.NOV.2020 14:25:58


Vertical



Date: 17.NOV.2020 13:11:06



Date: 17.NOV.2020 13:56:17



Date: 17.NOV.2020 14:15:34

FCC §15.407(1), (5),(e) – 26 dB & 6dB EMISSION BANDWIDTH

Applicable Standard

The maximum power spectral density is measured as a conducted emission by direct connection of a calibrated test instrument to the equipment under test. If the device cannot be connected directly, alternative techniques acceptable to the Commission may be used. Measurements in the 5.725-5.85 GHz band are made over a reference bandwidth of 500 kHz or the 26 dB emission bandwidth of the device, whichever is less. Measurements in the 5.15-5.25 GHz, 5.25-5.35 GHz, and the 5.47-5.725 GHz bands are made over a bandwidth of 1 MHz or the 26 dB emission bandwidth of the device, whichever is less. A narrower resolution bandwidth can be used, provided that the measured power is integrated over the full reference bandwidth.

Within the 5.725-5.85 GHz band, the minimum 6 dB bandwidth of U-NII devices shall be at least 500 kHz.

Test Procedure


1. Emission Bandwidth (EBW)

- a) Set RBW = approximately 1% of the emission bandwidth.
- b) Set the VBW \geq RBW.
- c) Detector = Peak.
- d) Trace mode = max hold.
- e) Measure the maximum width of the emission that is 26 dB down from the maximum of the emission. Compare this with the RBW setting of the analyzer. Readjust RBW and repeat measurement as needed until the RBW/EBW ratio is approximately 1%.

2. Minimum Emission Bandwidth for the band 5.725-5.85 GHz

Section 15.407(e) specifies the minimum 6 dB emission bandwidth of at least 500 kHz for the band 5.725-5.85 GHz. The following procedure shall be used for measuring this bandwidth:

- a) Set RBW = 100 kHz.
- b) Set the video bandwidth (VBW) $\geq 3 \times$ RBW.
- c) Detector = Peak.
- d) Trace mode = max hold.
- e) Sweep = auto couple.
- f) Allow the trace to stabilize.
- g) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.



Test Data**Environmental Conditions**

Temperature:	24 °C
Relative Humidity:	56 %
ATM Pressure:	101.0 kPa

The testing was performed by Bravos Zhao on 2020-11-27.

EUT operation mode: Transmitting

Test Result: Pass

Please refer to the Appendix.

FCC §15.407(a)(1)(2)(3) – CONDUCTED TRANSMITTER OUTPUT POWER

Applicable Standard

For an indoor access point operating in the band 5.15-5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.


For client devices in the 5.15-5.25 GHz band, the maximum conducted output power over the frequency band of operation shall not exceed 250 mW provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

For the 5.25-5.35 GHz and 5.47-5.725 GHz bands, the maximum conducted output power over the frequency bands of operation shall not exceed the lesser of 250 mW or $11 \text{ dBm} + 10 \log B$, where B is the 26 dB emission bandwidth in megahertz. In addition, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

For the band 5.725-5.85 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W. In addition, the maximum power spectral density shall not exceed 30 dBm in any 500-kHz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. However, fixed point-to-point U-NII devices operating in this band may employ transmitting antennas with directional gain greater than 6 dBi without any corresponding reduction in transmitter conducted power. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple collocated transmitters transmitting the same information. The operator of the U-NII device, or if the equipment is professionally installed, the installer, is responsible for ensuring that systems employing high gain directional antennas are used exclusively for fixed, point-to-point operations.

Test Procedure

1. Place the EUT on a bench and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to one test equipment.
3. Add a correction factor to the display.



Test Data

Environmental Conditions

Temperature:	24 °C
Relative Humidity:	56 %
ATM Pressure:	101.0 kPa

The testing was performed by Bravos Zhao on 2020-11-27.

EUT operation mode: Transmitting

Test Result: Pass

Please refer to the Appendix.

FCC §15.407(a) (1) (2) (3) - POWER SPECTRAL DENSITY

For client devices in the 5.15-5.25 GHz band, the maximum conducted output power over the frequency band of operation shall not exceed 250 mW provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

For the 5.25-5.35 GHz and 5.47-5.725 GHz bands, the maximum conducted output power over the frequency bands of operation shall not exceed the lesser of 250 mW or $11 \text{ dBm} + 10 \log B$, where B is the 26 dB emission bandwidth in megahertz. In addition, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

For the band 5.725-5.85 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W. In addition, the maximum power spectral density shall not exceed 30 dBm in any 500-kHz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. However, fixed point-to-point U-NII devices operating in this band may employ transmitting antennas with directional gain greater than 6 dBi without any corresponding reduction in transmitter conducted power. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple collocated transmitters transmitting the same information. The operator of the U-NII device, or if the equipment is professionally installed, the installer, is responsible for ensuring that systems employing high gain directional antennas are used exclusively for fixed, point-to-point operations.

Test Procedure

For devices operating in the bands 5.15-5.25 GHz, 5.25-5.35 GHz, and 5.47-5.725 GHz, the above procedures make use of 1 MHz RBW to satisfy directly the 1 MHz reference bandwidth specified in § 15.407(a)(5). For devices operating in the band 5.725-5.85 GHz, the rules specify a measurement bandwidth of 500 kHz. Many spectrum analyzers do not have 500 kHz RBW, thus a narrower RBW may need to be used. The rules permit the use of a RBWs less than 1 MHz, or 500 kHz, "provided that the measured power is integrated over the full reference bandwidth" to show the total power over the specified measurement bandwidth (i.e., 1 MHz, or 500 kHz). If measurements are performed using a reduced resolution bandwidth ($< 1 \text{ MHz}$, or $< 500 \text{ kHz}$) and integrated over 1 MHz, or 500 kHz bandwidth, the following adjustments to the procedures apply:

- a) Set RBW $\geq 1/T$, where T is defined in section II.B.1.a).
- b) Set VBW $\geq 3 \text{ RBW}$.
- c) If measurement bandwidth of Maximum PSD is specified in 500 kHz, add $10 \log (500 \text{ kHz}/\text{RBW})$ to the measured result, whereas RBW ($< 500 \text{ kHz}$) is the reduced resolution bandwidth of the spectrum analyzer set during measurement.
- d) If measurement bandwidth of Maximum PSD is specified in 1 MHz, add $10 \log (1\text{MHz}/\text{RBW})$ to the measured result, whereas RBW ($< 1 \text{ MHz}$) is the reduced resolution bandwidth of spectrum analyzer set during measurement.
- e) Care must be taken to ensure that the measurements are performed during a period of continuous transmission or are corrected upward for duty cycle.

Test Data

Environmental Conditions

Temperature:	24 °C
Relative Humidity:	56 %
ATM Pressure:	101.0 kPa

The testing was performed by Bravos Zhao on 2020-11-27.

EUT operation mode: Transmitting

Test Result: Pass


Please refer to the Appendix.


APPENDIX


Appendix A1:Emission Bandwidth Test Result


TestMode	Antenna	Channel	26db EBW [MHz]	Limit[MHz]	Verdict
11A	Ant1	5180	20.520	---	PASS
		5200	20.640	---	PASS
		5240	20.560	---	PASS
		5260	20.600	---	PASS
		5280	20.600	---	PASS
		5320	20.680	---	PASS
		5500	20.520	---	PASS
		5580	20.600	---	PASS
		5700	20.560	---	PASS
		5180	21.440	---	PASS
11N20SISO	Ant1	5200	21.080	---	PASS
		5240	21.000	---	PASS
		5260	21.080	---	PASS
		5280	21.280	---	PASS
		5320	21.240	---	PASS
		5500	21.440	---	PASS
		5580	21.080	---	PASS
		5700	21.320	---	PASS
		5190	40.000	---	PASS
		5230	39.760	---	PASS
11N40SISO	Ant1	5270	39.920	---	PASS
		5310	39.680	---	PASS
		5510	39.840	---	PASS
		5550	39.840	---	PASS
		5670	40.080	---	PASS
		5180	21.040	---	PASS
		5200	20.960	---	PASS
11AC20SISO	Ant1	5240	21.080	---	PASS
		5260	21.080	---	PASS
		5280	21.280	---	PASS
		5320	20.920	---	PASS
		5500	21.040	---	PASS
		5580	21.240	---	PASS
		5700	21.120	---	PASS
		5190	39.680	---	PASS
		5230	39.600	---	PASS
		5270	39.600	---	PASS
11AC40SISO	Ant1	5310	39.600	---	PASS
		5510	39.680	---	PASS
		5550	39.760	---	PASS
		5670	39.760	---	PASS
		5210	81.120	---	PASS
		5290	80.960	---	PASS
		5530	81.280	---	PASS
11AC80SISO	Ant1	5610	81.280	---	PASS


Test Graphs









































**Appendix A2: Occupied channel bandwidth
Test Result**

TestMode	Antenna	Channel	OCB [MHz]	Limit[MHz]	Verdict
11A	Ant1	5180	16.983	---	PASS
		5200	16.943	---	PASS
		5240	16.943	---	PASS
		5260	17.063	---	PASS
		5280	17.103	---	PASS
		5320	17.103	---	PASS
		5500	17.023	---	PASS
		5580	17.063	---	PASS
		5700	17.103	---	PASS
		5745	17.143	---	PASS
		5785	17.103	---	PASS
		5825	17.063	---	PASS
		5180	18.382	---	PASS
		5200	18.462	---	PASS
11N20SISO	Ant1	5240	18.382	---	PASS
		5260	18.462	---	PASS
		5280	18.342	---	PASS
		5320	18.422	---	PASS
		5500	18.422	---	PASS
		5580	18.382	---	PASS
		5700	18.422	---	PASS
		5745	18.462	---	PASS
		5785	18.462	---	PASS
		5825	18.382	---	PASS
		5190	36.603	---	PASS
		5230	36.603	---	PASS
		5270	36.603	---	PASS
		5310	36.683	---	PASS
11N40SISO	Ant1	5510	36.523	---	PASS
		5550	36.603	---	PASS
		5670	36.603	---	PASS
		5755	36.603	---	PASS
		5795	36.603	---	PASS
		5180	18.302	---	PASS
		5200	18.222	---	PASS
		5240	18.302	---	PASS
		5260	18.302	---	PASS
		5280	18.302	---	PASS
		5320	18.302	---	PASS
		5500	18.302	---	PASS
		5580	18.302	---	PASS
		5700	18.302	---	PASS
11AC20SISO	Ant1	5745	18.342	---	PASS
		5785	18.342	---	PASS
		5825	18.302	---	PASS
		5190	36.603	---	PASS
		5230	36.683	---	PASS
		5270	36.603	---	PASS
		5310	36.603	---	PASS
		5510	36.523	---	PASS
		5550	36.683	---	PASS
		5670	36.603	---	PASS
		5755	36.603	---	PASS
		5795	36.523	---	PASS
		5210	76.084	---	PASS
11AC80SISO	Ant1	5290	75.924	---	PASS

Bay Area Compliance Laboratories Corp. (Shenzhen)

Report No.: RSZ201023001-00C

		5530	75.924	---	PASS
		5610	76.084	---	PASS
		5775	76.084	---	PASS

Test Graphs

