



Product Service

## RF - TEST REPORT

Report Number : **68/760.9.131.01** Date of Issue: 25 June 2009

Model : **PC-91002, PC-912**

Product Type : Notebook

Applicant : Wanlida Group Co., Ltd.

Address : No. 618 Jiahe Road, Wanlida Industry Zone,  
Xiamen Fujian, China 361006

Production Facility : Wanlida Group Co., Ltd.

Address : Wanlida Industry Zone, Nanjing, Fujian, China 363601

Test Result : ☒ **Positive** ☐ **Negative**

Total pages including  
Appendices : 18

*Jiangsu TÜV Product Service Ltd. – Shenzhen Branch is a subcontractor to TÜV SÜD Product Service GmbH according to the principles outlined in ISO 17025.*

*Jiangsu TÜV Product Service Ltd. – Shenzhen Branch reports apply only to the specific samples tested under stated test conditions. Construction of the actual test samples has been documented. It is the manufacturer's responsibility to assure that additional production units of this model are manufactured with identical electrical and mechanical components. The manufacturer/importer is responsible to the Competent Authorities in Europe for any modifications made to the production units which result in non-compliance to the relevant regulations. Jiangsu TÜV Product Service Ltd. – Shenzhen Branch shall have no liability for any deductions, inferences or generalizations drawn by the client or others from Jiangsu TÜV Product Service Ltd. – Shenzhen Branch issued reports.*

*This report is the confidential property of the client. As a mutual protection to our clients, the public and ourselves, extracts from the test report shall not be reproduced except in full without our written approval*



## 1 Table of Contents

1	Table of Contents.....	2
2	Details about the Test Laboratory.....	3
3	Description of the Equipment Under Test.....	4
4	Summary of Test Standards.....	5
5	Summary of Test Results.....	6
6	General Remarks.....	7
7	Technical Requirements.....	8
7.1	Conducted Emission AC Power Port.....	8
7.2	Conducted Peak Power.....	12
7.3	Spurious Radiated Emissions.....	14
8	System Measurement Uncertainty.....	18

## 2 Details about the Test Laboratory

### Details about the Test Laboratory

Company name: Jiangsu TÜV Product Service Ltd. – Shenzhen Branch  
6th Floor, H Hall,  
Century Craftwork Culture Square,  
No. 4001, Fuqiang Road,  
Futian District 518048,  
Shenzhen, P.R.C.

Telephone: 86 755 8828 6998  
Fax: 86 755 8828 5299

Company name: China Shenzhen Academy of Metrology and Quality Inspection,  
Metrology and Quality Inspection building,  
Central Section of LongZhu Road,  
Nan Shan,  
Shenzhen,

Telephone: 86 755 2694 1599  
Fax: 86 755 2694 1545

Company name: Audix Technology (shenzhen) Co., Ltd  
Block Shenzhen, Science & Industry Park,  
Nantou, Shenzhen,  
Guangdong,  
China

Telephone: 86 755 2663 9496  
Fax: 86 755 2663 2877

### 3 Description of the Equipment Under Test

#### Description of the Equipment Under Test

Product:	Notebook
Model no.:	PC-91002
Serial number:	NIL
Options and accessories:	NIL
Rating:	DC 12V 3A, 36W AC Adaptor: Model: MPA-12030 Input: 100-240V ~ 50/60Hz 1A MAX Output: +12V DC 3A
Antenna:	Integral antenna inside the EUT, NOT accessible by end user
RF Transmission Frequency:	2400-2483.5MHz
Description of the EUT:	A certified Wi-Fi module was installed in this Notebook PC-91002, PC-912.  The information of Wi-Fi module: Product Type: 802.11 b/g Wireless Module Module No.: WT-mU-MTRa01 FCC ID: XB5-UMS5001-1 Applicant: Shenzhen Allwins Technology Corporation Address: Tsinghua Hi-Tech Park, Nanshan District, Shenzhen, Guangdong, 518057 China

#### Auxiliary Equipment and Cable Used during Test:

DESCRIPTION	MANUFACTURER	MODEL NO.(SHIELD)	S/N(LENGTH)
LCD monitor	Lenovo	9227-AE1	V1TDB38
Keyboard	Lenovo	SK-8825 (L)	02553778
Mouse	Lenovo	MO28UOL	4418011108
Headphone	Ouyun	OH601	----
USB flash drive	Kingston	Data Traveller	----
SD card	Kingston	SD4/4GBFE	----
VGA cable	Lenovo	Shield	140cm
AC Power cable	Lenovo	Unshield	180cm

#### 4 Summary of Test Standards

Test Standards	
FCC Part 15 Subpart C	PART 15 - RADIO FREQUENCY DEVICES Subpart C - Intentional Radiators
FCC Part 15 Subpart B	PART 15 - RADIO FREQUENCY DEVICES Subpart B - Unintentional Radiators

## 5 Summary of Test Results

Technical Requirements				
FCC Part 15 Subpart C				
Test Condition	Pages	Test Result		
		Pass	Fail	N/A
15.107 15.207 Conducted Emission AC Power Port	8	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
15.247 (b) (1) Conducted peak output power	12	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
15.247(d) 15.209 15.109 Spurious radiated emissions	14	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>

## 6 General Remarks

### Remarks

This submittal(s) (test report) is intended for the Class 2 permissive change of 802.11 b/g Wireless Module, Model No.: WT-mU-MTRa01, FCC ID: XB5-UMS5001-1.

Models PC-91002 and PC-912 are identical except the model name. So EMC full tests were applied on PC-91002, PC-912 is deemed to fulfill relevant EMC requirement without further testing.

### SUMMARY:

All tests according to the regulations cited on page 5 were

■ - Performed

□ - **Not** Performed

The Equipment Under Test

■ - **Fulfills** the general approval requirements.

□ - **Does not** fulfill the general approval requirements.

Sample Received Date: May 22 2009

Testing Start Date: May 22 2009

Testing End Date: Jun 10 2009

- Jiangsu TÜV Product Service Ltd. – Shenzhen Branch -

Reviewed by:

Prepared by:



Paul Yu  
EMC Project Manager



Ken Li  
EMC Test Engineer

## 7 Technical Requirement

### 7.1 Conducted Emission

#### Test Method

- 1 The EUT was placed on a table, which is 0.8m above ground plane
- 2 The power line of the EUT is connected to the AC mains through a Artificial Mains Network (A.M.N.).
- 3 Maximum procedure was performed to ensure EUT compliance
- 4 A EMI test receiver (R&S Test Receiver ESCS30) is used to test the emissions from both sides of AC line

#### Limit

Frequency MHz	QP Limit dB $\mu$ V	AV Limit dB $\mu$ V
0.150-0.500	66-56*	56-46*
0.500-5	56	46
5-30	60	50


Decreasing linearly with logarithm of the frequency



## Conducted Emission

### Conducted Disturbance

EUT: MN-PC-91002  
Op Cond: WIFI TRANSMITTING  
Test Spec: L  
Comment: AC 120V/60Hz



Frequency MHz	Cable Loss dB	Reading dBμV	QP Test result dBμV	QP Limit dBμV	Margin dB
0.202	9.8	34.6	44.4	63.5	19.1
0.266	9.8	26.7	36.5	61.2	24.7


Frequency MHz	Cable Loss dB	Reading dBμV	AV Test result dBμV	AV Limit dBμV	Margin dB
0.202	9.8	20.7	30.5	53.5	23
0.266	9.8	13.3	23.1	51.2	28.1

Remark: Test Result= Reading + Cable Loss

## Conducted Emission

### Conducted Disturbance

EUT: MN-PC-91002  
Op Cond: WIFI TRANSMITTING  
Test Spec: N  
Comment: AC 120V/60Hz



Frequency MHz	Cable Loss dB	Reading dBμV	QP Test result dBμV	QP Limit dBμV	Margin dB
0.206	9.8	33.1	42.9	63.3	20.4
0.258	9.8	29.0	38.8	61.5	22.7
Frequency MHz	Cable Loss dB	Reading dBμV	AV Test result dBμV	AV Limit dBμV	Margin dB
0.206	9.8	12.8	22.6	53.3	30.7
0.258	9.8	9.7	19.5	51.5	32

Remark: Test Result= Reading + Cable Loss

## Test Equipment List

### Conducted Emission Test

DESCRIPTION	MANUFACTURER	MODEL NO.	SERIAL NO.	CAL.DUE.DATE
ESPI Test Receiver	ROHDE&SCHWARZ	ESPI 3	100379	2009-12-05
TWO Line-V-NETW	ROHDE&SCHWARZ	EZH3-Z5	100253	2009-12-05

## 7.2 Conducted peak output power

### Test Method

The transmitter output is connected to the Spectrum analyzer. The Spectrum analyzer is set to the peak power detection.

### Limits for conducted peak output power measurements

Frequency Range MHz	Limit W	Limit dBm
2400-2483	≤1	≤30

## Conducted peak output power

### IEEE 802.11g Modulation Test Result

Frequency MHz	Conducted Peak Output Power dBm	Result
CH1 2412MHz	16.44	Pass
CH6 2437MHz	16.72	Pass
CH11 2462MHz	16.92	Pass

### IEEE 802.11b Modulation Test Result

Frequency MHz	Conducted Peak Output Power dBm	Result
CH1 2412MHz	18.71	Pass
CH6 2437MHz	18.74	Pass
CH11 2462MHz	17.29	Pass

## Test Equipment

### Maximum transmit power Test

DESCRIPTION	MANUFACTURER	MODEL NO.	SERIAL NO.	CAL.DUE.DATE
Spectrum Analyzer	Agilent	E4446A	US44300459	2010-05-10

## 7.3 Spurious radiated emissions

### Test Method

- 1 The EUT is placed on a turntable, which is 0.8m above ground plane.
- 2 The turntable shall be rotated for 360 degrees to determine the position of maximum emission level
- 3 EUT is set 3m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emissions.
- 4 Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
- 5 each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.

### Limit

Frequency MHz	Field Strength uV/m	Field Strength dBμV/m	Detector
30-88	100	40	QP
88-216	150	43.5	QP
216-960	200	46	QP
960-1000	500	54	QP
Above 1000	500	54	AV
Above 1000	5000	74	PK

## Spurious radiated emissions

### IEEE 802.11g Modulation test result-2402MHz

Frequency MHz	Cable Loss dB	Antenna Factor dB/m	Reading dBuV	Emission Level dBuV/m	Polarization	Limit dBuV/m	Detector	Result
348.470	3.2	15.4	18.6	37.2	Horizontal	46.0	QP	Pass
200.042	2.4	10.3	16.0	28.7	Vertical	43.5	QP	Pass
4804.000	3.8	33.3	18.3	55.4	Horizontal	74	PK	Pass
4804.000	3.8	33.3	9.5	46.6	Horizontal	54	AV	Pass
4804.000	3.8	33.3	18.5	55.6	Vertical	74	PK	Pass
4804.000	3.8	33.3	7.8	44.9	Vertical	54	AV	Pass

### Test Result-2437MHz

Frequency MHz	Cable Loss dB	Antenna Factor dB/m	Reading dBuV	Emission Level dBuV/m	Polarization	Limit dBuV/m	Detector	Result
4874.000	3.9	33.3	20.1	57.3	Horizontal	74	PK	Pass
4874.000	3.9	33.3	9.0	46.2	Horizontal	54	AV	Pass
4874.000	3.9	33.3	19.0	56.2	Vertical	74	PK	Pass
4874.000	3.9	33.3	7.1	44.3	Vertical	54	AV	Pass

### Test Result-2462MHz

Frequency MHz	Cable Loss dB	Antenna Factor dB/m	Reading dBuV	Emission Level dBuV/m	Polarization	Limit dBuV/m	Detector	Result
4924.000	3.9	33.3	20.6	57.8	Horizontal	74	PK	Pass
4924.000	3.9	33.3	11.8	50.0	Horizontal	54	AV	Pass
4924.000	3.9	33.3	18.3	55.5	Vertical	74	PK	Pass
4924.000	3.9	33.3	10.4	47.6	Vertical	54	AV	Pass

Remark: Emission Level= Cable Loss(include amplifier factor) + Antenna Factor + Reading

## Spurious radiated emissions

### IEEE 802.11b Modulation test result-2402MHz

Frequency MHz	Cable Loss dB	Antenna Factor dB/m	Reading dBuV	Emission Level dBuV/m	Polarization	Limit dBuV/m	Detector	Result
349.262	3.2	15.4	15.8	34.4	Horizontal	46.0	QP	Pass
183.743	2.2	9.8	16.9	28.9	Vertical	43.5	QP	Pass
4804.000	3.8	33.3	17.2	54.3	Horizontal	74	PK	Pass
4804.000	3.8	33.3	7.5	44.6	Horizontal	54	AV	Pass
4804.000	3.8	33.3	16.3	53.4	Vertical	74	PK	Pass
4804.000	3.8	33.3	8.4	45.5	Vertical	54	AV	Pass

### Test Result-2437MHz

Frequency MHz	Cable Loss dB	Antenna Factor dB/m	Reading dBuV	Emission Level dBuV/m	Polarization	Limit dBuV/m	Detector	Result
4874.000	3.9	33.3	20.0	57.2	Horizontal	74	PK	Pass
4874.000	3.9	33.3	9.3	46.5	Horizontal	54	AV	Pass
4874.000	3.9	33.3	19.1	56.3	Vertical	74	PK	Pass
4874.000	3.9	33.3	7.8	45.0	Vertical	54	AV	Pass

### Test Result-2462MHz

Frequency MHz	Cable Loss dB	Antenna Factor dB/m	Reading dBuV	Emission Level dBuV/m	Polarization	Limit dBuV/m	Detector	Result
4924.000	3.9	33.3	18.6	55.8	Horizontal	74	PK	Pass
4924.000	3.9	33.3	7.7	44.9	Horizontal	54	AV	Pass
4924.000	3.9	33.3	17.3	54.5	Vertical	74	PK	Pass
4924.000	3.9	33.3	7.4	44.6	Vertical	54	AV	Pass

Remark: Emission Level= Cable Loss(include amplifier factor) + Antenna Factor + Reading



## Test Equipment List

### Spurious radiated emissions Test

DESCRIPTION	MANUFACTURER	MODEL NO.	SERIAL NO.	CAL.DUE.DATE
Spectrum	Agilent	E4446A	US44300459	2010-05-10
SG	HP	83723B	US34490501	2010-05-10
Amp	HP	8449B	3008A02495	2010-05-24
Antenna	EMCO	3115	9607-4877	2010-05-27

## 8 System Measurement Uncertainty

For a 95% confidence level, the measurement expanded uncertainties for defined systems, in accordance with the recommendations of ISO 17025 were:

**System Measurement Uncertainty**

Items		Extended Uncertainty
RE	Field strength (dB $\mu$ V/m)	U=4.6dB; k=2(30MHz-1GHz)
CE	Disturbance Voltage (dB $\mu$ V)	U=3.3dB; k=2