



Most Technology Service Co., Ltd.
Tel:(86) 755-26825180 Fax:(86) 755-86170310
Http:// www. szmost.com Email: szmost@szmost.com

Test Report

Product Name: 802.11b/g Wireless Module

FCC ID: XB5-UMS5001

MODEL NO. : AWM50G-US, AWM503g-WT, WT-mU-MTRa01

Applicant:

Shenzhen Allwins Technology Corporation
902#, Block A, R&D Building, Tsinghua Hi-Tech Park,
Nanshan District, Shenzhen, Guangdong, China

Date Received: 05/27/009

Date Tested: 05/25-26/2009

APPLICANT: Shenzhen Allwins Technology Corporation
FCC ID: XB5-UMS5001

Cover Sheet



Most Technology Service Co., Ltd.
 Tel:(86) 755-26825180 Fax:(86) 755-86170310
 Http:// www. szmost.com Email: szmost@szmost.com

TABLE OF CONTENTS

APPLICANT: Shenzhen Allwins Technology Corporation

FCC ID: XB5-UMS5001

TEST REPORT CONTAINING:

PAGE 1.....TEST EQUIPMENT LIST
 PAGE 2.....TEST PROCEDURE
 PAGE 3-5.....POWER LINE CONDUCTED INTERFERENCE AND PLOTS
 PAGE 6-8.....RADIATION INTERFERENCE TEST DATA
 PANG 9.....6dB BANDWITH TEST
 PANG 10.....OUTPUT POWER TEST
 PANG 11-19.....BAND EDGE COMPLIANCE TEST
 PANG 20.....POWER SPECTRAL DENSITY TEST

EXHIBIT INCLUDED:

PAGE 1.....BLOCK DIAGRAM
 PAGE 2.....SCHEMATIC
 PAGE 3.....USERS MANUAL
 PAGE 4.....LABEL SAMPLE
 PAGE 5.....LABEL LOCATION
 PAGE 6.....EXTERNAL PHOTOGRAPHS
 PAGE 7.....INTERNAL PHOTOGRAPHS
 PAGE 8.....OPERATIONAL DESCRIPTION
 PAGE 9.....TEST SET UP PHOTOGRAPHS

APPLICANT: Shenzhen Allwins Technology Corporation
 FCC ID: XB5-UMS5001



Most Technology Service Co., Ltd.
 Tel:(86) 755-26825180 Fax:(86) 755-86170310
 Http:// www. szmost.com Email: szmost@szmost.com

EMC Equipment List

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
EMI Test Receiver	ROHDE&SCHWARZ	ESCI	100492	Mar 10,2009	1 Year
LISN	ROHDE&SCHWARZ	ENV216	100093	Mar 10,2009	1Year
EMI Test Receiver	ROHDE&SCHWARZ	ESCI	101202	Mar 10,2009	1 Year
Spectrum Analyzer	ANRITSU	MS2651B	6200238316	Mar 10,2009	1 Year
50 Coaxial Switch	ANRITSU CORP	MP59B	6200283933	Mar 10,2009	1 Year
Bilog Antenna	Sunol	JB3	A121206	Mar 10,2009	1 Year
Horn Antenna	EMCO	3115	640201028-06	Mar 10,2009	1 Year
50 Coaxial Switch	ANRITSU CORP	MP59B	6200283933	Mar 10,2009	1 Year
Cable	Resenberger	N/A	NO.1	Mar 10,2009	1 Year
Cable	SCHWARZBECK	N/A	NO.2	Mar 10,2009	1 Year
Cable	SCHWARZBECK	N/A	NO.3	Mar 10,2009	1 Year
Single Phase Power Line Filter	Kikusui	LIN40MA-PC R-L	LM002352	Mar 10,2009	1Year
AC Power Source	Kikusui	AC40MA	LM003232	Mar 10,2009	1Year
Test analyzer	Kikusui	KHA1000	LM003720	Mar 10,2009	1Year
ESD Tester	Kikusui	KES4021	LM003537	Mar 10,2009	1 Year
Signal Generator	IFR	2032	203002/100	Mar 10,2009	1 Year
Amplifier	A&R	150W1000	301584	NCR	NCR
Dual Directional Coupler	A&R	DC6080	301508	Mar 10,2009	1 Year
Power Head	A&R	PH2000	301193	Mar 10,2009	1 Year
Power Meter	A&R	PM2002	302799	Mar 10,2009	1 Year
Field Monitor	A&R	FM5004	300329	Mar 10,2009	1 Year
Field Probe	A&R	FP5000	300221	Mar 10,2009	1 Year
EMC PRO System	EM Test	UCS-500-M4	V0648102026	Mar 10,2009	1 Year
EMC PRO System	EM Test	UCS-500-M4	V0648102026	Mar 10,2009	1 Year
Spectrum Analyzer	Agilent	E4446A	US44300459	Mar 10,2009	1 Year
Attenuator	Agilent	8491B	MY39262165	Mar 10,2009	1 Year

Remark:

Test Firm Name: Most Technology Service Co., Ltd.
 Test Firm Address:

No. 5, 2nd Langshan Road, North District, Hi-tech Industrial Park, Nanshan, Shenzhen, Guangdong, China

FCC Registered Test Site Number: 490827

APPLICANT: Shenzhen Allwins Technology Corporation
 FCC ID: XB5-UMS5001



Most Technology Service Co., Ltd.
Tel:(86) 755-26825180 Fax:(86) 755-86170310
Http:// www. szmost.com Email: szmost@szmost.com

TEST PROCEDURE

GENERAL: This report shall NOT be reproduced except in full without the written approval of MOST TECHNOLOGY SERVICE CO., LTD. The EUT was transmitting a test signal during the testing.

POWER LINE CONDUCTED INTERFERENCE: The test procedure used was ANSI Standard C63.4-2003 using a 50 UH LISN. Both Lines were observed. The bandwidth of the receiver was 10kHz with an appropriate sweep speed. The ambient temperature of the EUT was 25 with a humidity of 58%.

RADIATION INTERFERENCE: The test procedure used was ANSI Standard C63.4-2003 using a ANRITSU spectrum analyzer with a pre-selector. The analyzer was calibrated in dB above a micro volt at the output of the antenna. The resolution bandwidth was 100 kHz and the video bandwidth was 300 kHz up to 1 GHz and 1 MHz with a video BW of 3 MHz above 1 GHz. The ambient temperature of the EUT was 25 with a humidity of 58%.

FORMULA OF CONVERSION FACTORS: The Field Strength at 3m was established by adding the meter reading of the spectrum analyzer (which is set to read in units of dBuV) to the antenna correction factor supplied by the antenna manufacturer and cable loss. The antenna correction factors and cable loss are stated in terms of dB. The gain of the Pre-selector was accounted for in the Spectrum Analyzer Meter Reading.

Example:

Freq (MHz) METER READING + ACF + CABLE = FS
33 20 dBuV + 10.36 dB + 0.9 dB= 31.26 dBuV/m @ 3m

ANSI STANDARD C63.4-2003 10.1.7 MEASUREMENT PROCEDURES: The EUT was placed on a table 80 cm high and with dimensions of 1m by 1.5m. The EUT was placed in the center of the table (1.5m side). The table used for radiated measurements is capable of continuous rotation. The spectrum was scanned from 30 MHz to 10th harmonic of the fundamental.

Peak readings were taken in three (3) orthogonal planes and the highest readings were converted to average readings based on the duration of "ON" time.

When an emission was found, the table was rotated to produce the maximum signal strength. At this point, the antenna was raised and lowered from 1m to 4m. The antenna was placed in both the horizontal and vertical planes.

The situation was similar for the conducted measurement except that the table did not rotate. The EUT was setup as described in ANSI Standard C63.4-2003 10.1.7 with the EUT 40 cm from the vertical ground wall.



Most Technology Service Co., Ltd.
 Tel:(86) 755-26825180 Fax:(86) 755-86170310
 Http:// www. szmost.com Email: szmost@szmost.com

APPLICANT: Shenzhen Allwins Technology Corporation

FCC ID: XB5-UMS5001

NAME OF TEST: POWER LINE CONDUCTED INTERFERENCE

RULES PART NUMBER: 15.207(a), 15.247

REQUIREMENTS:

Frequency of Emission (MHz)	Conducted Limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56 *	56 to 46 *
0.5-5	56	46
5-30	60	50

* Decreases with the logarithm of the frequency.

TEST PROCEDURE: ANSI STANDARD C63.4-2003


Conducted Emission Measurement

File : Allwins
 80.0 dBuV

Data : #1

Date: 2009-05-25

Time: 10/12/39



Site site #1

Phase: **L1**

Temperature: 26

Limit: FCC Part 15C Conduction (QP)

Power: DC 5V from PC Input AC 120V/60Hz

Humidity: 60 %

EUT: 802.11b/g Wireless Module

M/N: AWM50G-US

Mode: WIFI Mode

Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector	Comment
		MHz	dBuV	dB	dBuV	dBuV	dB		
1		0.1900	32.65	11.40	44.05	64.03	-19.98	QP	
2		0.3183	24.06	11.21	35.27	59.75	-24.48	QP	
3	*	1.1300	32.01	9.87	41.88	56.00	-14.12	QP	
4		2.3420	26.60	9.34	35.94	56.00	-20.06	QP	
5		7.5019	29.50	10.50	40.00	60.00	-20.00	QP	
6		10.9699	29.92	9.00	38.92	60.00	-21.08	QP	

*:Maximum data x:Over limit !:over margin


Conducted Emission Measurement

File : Allwins
 80.0 dBuV

Data : #2

Date: 2009-05-25

Time: 10/15/02



Site site #1

Phase: **N**

Temperature: 26

Limit: FCC Part 15C Conduction (QP)

Power: DC 5V from PC Input AC 120V/60Hz

Humidity: 60 %

EUT: 802.11b/g Wireless Module

M/N: AWM50G-US

Mode: WIFI Mode

Note:

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector	Comment
1		0.1900	32.16	11.40	43.56	64.03	-20.47	QP	
2		0.3140	24.81	11.24	36.05	59.86	-23.81	QP	
3		0.7219	22.42	10.00	32.42	56.00	-23.58	QP	
4	*	1.1298	31.24	9.87	41.11	56.00	-14.89	QP	
5		2.4260	27.85	9.43	37.28	56.00	-18.72	QP	
6		7.5019	29.30	10.50	39.80	60.00	-20.20	QP	

*:Maximum data x:Over limit !:over margin



Most Technology Service Co., Ltd.
 Tel:(86) 755-26825180 Fax:(86) 755-86170310
 Http:// www. szmost.com Email: szmost@szmost.com

APPLICANT: Shenzhen Allwins Technology Corporation

FCC ID: XB5-UMS5001

NAME OF TEST: RADIATION INTERFERENCE

RULES PART NUMBER: 15.247, 15.209(a)

REQUIREMENTS:

30-88 MHz 40 dBuV/m @3m
 88-216 MHz 43.5 dBuV/m @3m
 216-960 MHz 46 dBuV/m @3m
 960-1000 MHz 54 dBuV/m @3m
 Above 1000MHz 74 dBuV/m(Peak) @3m, 54 dBuV/m(AV) @3m

EMISSIONS RADIATED OUTSIDE OF THE SPECIFIED FREQUENCY BANDS, EXCEPT FOR HARMONICS, SHALL BE ATTENUATED BY AT LEAST 50 Db BELOW THE LEVEL OF THE FUNDAMENTAL OR TO THE GENERAL RADIATED EMISSION LIMITS IN 15.209, WHICHEVER IS THE LESSER ATTENUATION.

REMARK: Emissions attenuated more than 20 dB below the permissible value are not reported.

Frequency (MHz)	Antenna Polarization	Emission Level (dBuV/m)			FCC 15 Subpart C Limit(dBuV/m)
		Avg	QP	Peak	
11Mbps for IEEE 802.11b TX High frequency (2412.00MHz)					
214.01	Vertical	---	31.24	33.09	43.5
4824.00	Vertical	---	---	29.22	74.0
7236.10	Vertical	---	---	30.43	74.0
9648.20	Vertical	---	---	30.27	74.0
332.05	Horizontal	---	30.47	32.89	46.0
4824.00	Horizontal	---	---	32.24	74.0
7236.10	Horizontal	---	---	32.56	74.0
9648.20	Horizontal	---	---	30.32	74.0
54Mbps for IEEE 802.11g TX High frequency (2412.00MHz)					
213.90	Vertical	---	30.68	33.64	43.5
4824.09	Vertical	---	---	30.60	74.0
7236.10	Vertical	---	---	31.22	74.0
9648.01	Vertical	---	---	30.42	74.0
332.10	Horizontal	---	31.23	33.63	46.0
4824.01	Horizontal	---	---	32.04	74.0
7236.10	Horizontal	---	---	32.53	74.0
9648.21	Horizontal	---	---	30.15	74.0

Emissions attenuated more than 20 dB below the permissible value are not reported.

TEST PROCEDURE: ANSI Standard C63.4-2003 using a ANRITSU spectrum analyzer with a pre-selector and an appropriate antenna. The resolution bandwidth of spectrum analyzer was 100 kHz below 1 GHz and 1 MHz above 1 GHz. An appropriate sweep speed was used. When an emission was found, the table was rotated to produce the maximum signal strength. The antenna was placed in both the horizontal and vertical planes and the worse case emissions were reported. The spectrum was searched to at least the tenth (10) harmonic of the fundamental.

APPLICANT: Shenzhen Allwins Technology Corporation
 FCC ID: XB5-UMS5001



Most Technology Service Co., Ltd.
 Tel:(86) 755-26825180 Fax:(86) 755-86170310
 Http:// www. szmost.com Email: szmost@szmost.com

APPLICANT: Shenzhen Allwins Technology Corporation

FCC ID: XB5-UMS5001

NAME OF TEST: RADIATION INTERFERENCE

RULES PART NUMBER: 15.247, 15.209(a)

REQUIREMENTS:

30-88 MHz 40 dBuV/m @3m
 88-216 MHz 43.5 dBuV/m @3m
 216-960 MHz 46 dBuV/m @3m
 960-1000 MHz 54 dBuV/m @3m
 Above 1000MHz 74 dBuV/m(Peak) @3m, 54 dBuV/m(AV) @3m

EMISSIONS RADIATED OUTSIDE OF THE SPECIFIED FREQUENCY BANDS, EXCEPT FOR HARMONICS, SHALL BE ATTENUATED BY AT LEAST 50 Db BELOW THE LEVEL OF THE FUNDAMENTAL OR TO THE GENERAL RADIATED EMISSION LIMITS IN 15.209, WHICHEVER IS THE LESSER ATTENUATION.

REMARK: Emissions attenuated more than 20 dB below the permissible value are not reported. Continued:

Frequency (MHz)	Antenna Polarization	Emission Level (dBuV/m)			FCC 15 Subpart C Limit(dBuV/m)
		Avg	QP	Peak	
11Mbps for IEEE 802.11b TX High frequency (2442.00MHz)					
213.90	Vertical	---	32.09	34.02	43.5
4884.10	Vertical	---	---	31.27	74.0
7326.03	Vertical	---	---	30.82	74.0
9768.30	Vertical	---	---	32.56	74.0
332.10	Horizontal	---	31.75	33.67	46.0
4884.10	Horizontal	---	---	30.79	74.0
7326.20	Horizontal	---	---	31.37	74.0
9768.00	Horizontal	---	---	30.22	74.0
54Mbps for IEEE 802.11b TX High frequency (2442.00MHz)					
214.01	Vertical	---	31.30	33.45	43.5
4884.09	Vertical	---	---	30.21	74.0
7326.00	Vertical	---	---	32.45	74.0
9768.11	Vertical	---	---	32.20	74.0
332.08	Horizontal	---	31.52	34.18	46.0
4884.10	Horizontal	---	---	31.44	74.0
7324.13	Horizontal	---	---	32.03	74.0
9768.01	Horizontal	---	---	30.32	74.0

Emissions attenuated more than 20 dB below the permissible value are not reported.

TEST PROCEDURE: ANSI Standard C63.4-2003 using a ANRITSU spectrum analyzer with a pre-selector and an appropriate antenna. The resolution bandwidth of spectrum analyzer was 100 kHz below 1 GHz and 1 MHz above 1 GHz. An appropriate sweep speed was used. When an emission was found, the table was rotated to produce the maximum signal strength. The antenna was placed in both the horizontal and vertical planes and the worse case emissions were reported. The spectrum was searched to at least the tenth (10) harmonic of the fundamental.

APPLICANT: Shenzhen Allwins Technology Corporation
 FCC ID: XB5-UMS5001



Most Technology Service Co., Ltd.
 Tel:(86) 755-26825180 Fax:(86) 755-86170310
 Http:// www. szmost.com Email: szmost@szmost.com

APPLICANT: Shenzhen Allwins Technology Corporation

FCC ID: XB5-UMS5001

NAME OF TEST: RADIATION INTERFERENCE

RULES PART NUMBER: 15.247, 15.209(a)

REQUIREMENTS:

30-88 MHz 40 dBuV/m @3m
 88-216 MHz 43.5 dBuV/m @3m
 216-960 MHz 46 dBuV/m @3m
 960-1000 MHz 54 dBuV/m @3m
 Above 1000MHz 74 dBuV/m(Peak) @3m, 54 dBuV/m(AV) @3m

EMISSIONS RADIATED OUTSIDE OF THE SPECIFIED FREQUENCY BANDS, EXCEPT FOR HARMONICS, SHALL BE ATTENUATED BY AT LEAST 50 Db BELOW THE LEVEL OF THE FUNDAMENTAL OR TO THE GENERAL RADIATED EMISSION LIMITS IN 15.209, WHICHEVER IS THE LESSER ATTENUATION.

REMARK: Emissions attenuated more than 20 dB below the permissible value are not reported. Continued:

Frequency (MHz)	Antenna Polarization	Emission Level (dBuV/m)			FCC 15 Subpart C Limit(dBuV/m)
		Avg	QP	Peak	
11Mbps for IEEE 802.11b TX High frequency (2462.00MHz)					
214.09	Vertical	---	31.35	33.70	43.5
4924.09	Vertical	---	---	30.32	74.0
7386.11	Vertical	---	---	31.34	74.0
9848.10	Vertical	---	---	32.63	74.0
331.90	Horizontal	---	---	34.34	46.0
4924.08	Horizontal	---	32.11	33.17	74.0
7386.21	Horizontal	---	---	31.28	74.0
9848.01	Horizontal	---	---	30.39	74.0
54Mbps for IEEE 802.11b TX High frequency (2462.00MHz)					
214.10	Vertical	---	31.42	34.25	43.5
4924.09	Vertical	---	---	30.32	74.0
7386.11	Vertical	---	---	32.29	74.0
9848.10	Vertical	---	---	31.07	74.0
332.06	Horizontal	---	---	30.35	46.0
4924.05	Horizontal	---	32.06	34.23	74.0
7386.10	Horizontal	---	---	31.34	74.0
9848.09	Horizontal	---	---	32.62	74.0

Emissions attenuated more than 20 dB below the permissible value are not reported.

TEST PROCEDURE: ANSI Standard C63.4-2003 using a ANRITSU spectrum analyzer with a pre-selector and an appropriate antenna. The resolution bandwidth of spectrum analyzer was 100 kHz below 1 GHz and 1 MHz above 1 GHz. An appropriate sweep speed was used. When an emission was found, the table was rotated to produce the maximum signal strength. The antenna was placed in both the horizontal and vertical planes and the worse case emissions were reported. The spectrum was searched to at least the tenth (10) harmonic of the fundamental.

APPLICANT: Shenzhen Allwins Technology Corporation
 FCC ID: XB5-UMS5001



Most Technology Service Co., Ltd.
 Tel:(86) 755-26825180 Fax:(86) 755-86170310
 Http:// www. szmost.com Email: szmost@szmost.com

APPLICANT: Shenzhen Allwins Technology Corporation

FCC ID: XB5-UMS5001

NAME OF TEST: 6dB Bandwidth Test

RULES PART NUMBER: 15.247(a)(2)

REQUIREMENTS:The transmitter output was connected to a spectrum analyzer via a Attenuator.The bandwidth of the fundamental frequency was measured by spectrum analyzer with 100 KHz RBW and 100 KHz VBW.The 6dB Bandwidth is defined as the total spectrum the power of which is lower than peak power minus 6dB, The 6dB bandwidth shall be at least 500 KHz.

TEST RESULTS:

Test Mode: 11Mbps for IEEE 802.11b TX

Test Frequency (MHz)	6DB Bandwidth(MHz)	Limit	Conclusion
CH1:2412MHz	13.02	>500	PASS
CH7:2442MHz	13.42	>500	PASS
CH11:2462MHz	13.35	>500	PASS

Test Mode: 54Mbps for IEEE 802.11g TX

Test Frequency (MHz)	6DB Bandwidth(MHz)	Limit	Conclusion
CH1:2412MHz	14.25	>500	PASS
CH7:2442MHz	14.25	>500	PASS
CH11:2462MHz	14.25	>500	PASS



Most Technology Service Co., Ltd.
 Tel:(86) 755-26825180 Fax:(86) 755-86170310
 Http:// www. szmost.com Email: szmost@szmost.com

APPLICANT: Shenzhen Allwins Technology Corporation

FCC ID: XB5-UMS5001

NAME OF TEST: Output Power Test

RULES PART NUMBER: 15.247(b)(3)

REQUIREMENTS: The transmitter output was connected to a power meter via a Attenuator , use the power meter to read out the peak output power, the peak output power shall be not exceed 30dBm .

TEST RESULTS:

Test mode: 11Mbps for IEEE 802.11b TX

Test Frequency (MHz)	Read(PK) (dBm)	Cable loss (dB)	Atten loss (dB)	Result (dBm)	Limit (dBm)	Conclusion
CH1:2412MHz	-5.90	0.6	20	14.70	30	PASS
CH7:2442MHz	-6.52	0.6	20	14.08	30	PASS
CH11:2462MHz	-7.89	0.6	20	12.71	30	PASS

Test mode: 54Mbps for IEEE 802.11g TX

Test Frequency (MHz)	Read(PK) (dBm)	Cable loss (dB)	Atten loss (dB)	Result (dBm)	Limit (dBm)	Conclusion
CH1:2412MHz	-6.52	0.6	20	14.08	30	PASS
CH7:2442MHz	-6.33	0.6	20	14.27	30	PASS
CH11:2462MHz	-6.28	0.6	20	14.32	30	PASS



Most Technology Service Co., Ltd.
Tel:(86) 755-26825180 Fax:(86) 755-86170310
Http:// www. szmost.com Email: szmost@szmost.com

APPLICANT: Shenzhen Allwins Technology Corporation
FCC ID: XB5-UMS5001
NAME OF TEST: Band Edge Compliance Test
RULES PART NUMBER: 15.205(b), 15.247(d)
REQUIREMENTS:


APPLICANT: Shenzhen Allwins Technology Corporation
FCC ID: XB5-UMS5001




Most Technology Service Co., Ltd.
Tel: (86) 755-26825180 Fax: (86) 755-86170310
Http:// www.szmost.com Email: szmost@szmost.com

Test mode: 11Mbps for IEEE 802.11b TX (Low Channel)

Detector mode: Peak Polarity: Vertical



Detector mode: Average Polarity: Vertical




APPLICANT: Shenzhen Allwins Technology Corporation
FCC ID: XB5-UMS5001




Most Technology Service Co., Ltd.
Tel: (86) 755-26825180 Fax: (86) 755-86170310
Http:// www.szmost.com Email: szmost@szmost.com

Test mode: 11Mbps for IEEE 802.11b TX (Low Channel)

Detector mode: Peak Polarity: Horizontal



Detector mode: Average Polarity: Horizontal




APPLICANT: Shenzhen Allwins Technology Corporation
FCC ID: XB5-UMS5001




Most Technology Service Co., Ltd.
Tel: (86) 755-26825180 Fax: (86) 755-86170310
Http:// www.szmost.com Email: szmost@szmost.com

Test mode: 11Mbps for IEEE 802.11b TX (High Channel)

Detector mode: Peak Polarity: Vertical



Detector mode: Average Polarity: Vertical




APPLICANT: Shenzhen Allwins Technology Corporation
FCC ID: XB5-UMS5001




Most Technology Service Co., Ltd.
Tel: (86) 755-26825180 Fax: (86) 755-86170310
Http:// www.szmost.com Email: szmost@szmost.com

Test mode: 11Mbps for IEEE 802.11b TX (High Channel)

Detector mode: Peak Polarity: Horizontal



Detector mode: Average Polarity: Horizontal




APPLICANT: Shenzhen Allwins Technology Corporation
FCC ID: XB5-UMS5001



Most Technology Service Co., Ltd.
Tel: (86) 755-26825180 Fax: (86) 755-86170310
Http:// www.szmost.com Email: szmost@szmost.com

Test mode: 54Mbps for IEEE 802.11g TX (Low Channel)

Detector mode: Peak Polarity: Vertical



Detector mode: Average Polarity: Vertical




APPLICANT: Shenzhen Allwins Technology Corporation
FCC ID: XB5-UMS5001




Most Technology Service Co., Ltd.
Tel: (86) 755-26825180 Fax: (86) 755-86170310
Http:// www.szmost.com Email: szmost@szmost.com

Test mode: 54Mbps for IEEE 802.11g TX (Low Channel)

Detector mode: Peak Polarity: Horizontal



Detector mode: Average Polarity: Horizontal




APPLICANT: Shenzhen Allwins Technology Corporation
FCC ID: XB5-UMS5001




Most Technology Service Co., Ltd.
Tel: (86) 755-26825180 Fax: (86) 755-86170310
Http:// www.szmost.com Email: szmost@szmost.com

Test mode: 54Mbps for IEEE 802.11g TX (High Channel)

Detector mode: Peak Polarity: Vertical



Detector mode: Average Polarity: Vertical



APPLICANT: Shenzhen Allwins Technology Corporation
FCC ID: XB5-UMS5001




Most Technology Service Co., Ltd.
Tel: (86) 755-26825180 Fax: (86) 755-86170310
Http:// www.szmost.com Email: szmost@szmost.com

Test mode: 54Mbps for IEEE 802.11g TX (High Channel)


Detector mode: Peak

Polarity: Horizontal



Detector mode: Average

Polarity: Horizontal



APPLICANT: Shenzhen Allwins Technology Corporation
FCC ID: XB5-UMS5001



Most Technology Service Co., Ltd.
 Tel:(86) 755-26825180 Fax:(86) 755-86170310
 Http:// www. szmost.com Email: szmost@szmost.com

APPLICANT: Shenzhen Allwins Technology Corporation

FCC ID: XB5-UMS5001

NAME OF TEST: Power Spectral Density Test

RULES PART NUMBER: 15.247(e)

REQUIREMENTS:The transmitter output was connected to a spectrum analyzer via a Attenuator. The power density was measured by spectrum analyzer with 3 KHz RBW and 30 KHz VBW, sweep time=span/3KHz,the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3KHz band during any time interval of continuous transmission.

TEST RESULTS:

Test mode: 11Mbps for IEEE 802.11b TX

Test Frequency (MHz)	Read(PK) (dBm/3KHz)	Cable loss (dB)	Atten loss (dB)	Result (dBm/3KHz)	Limit (dBm/3KHz)	Conclusion
CH1:2412MHz	-23.19	0.6	20	-2.59	8	PASS
CH7:2442MHz	-22.40	0.6	20	-1.80	8	PASS
CH11:2462MHz	-23.04	0.6	20	-2.44	8	PASS

Test mode: 54Mbps for IEEE 802.11g TX

Test Frequency (MHz)	Read(PK) (dBm/3KHz)	Cable loss (dB)	Atten loss (dB)	Result (dBm/3KHz)	Limit (dBm/3KHz)	Conclusion
CH1:2412MHz	-25.30	0.6	20	-4.70	8	PASS
CH7:2442MHz	-24.69	0.6	20	-4.09	8	PASS
CH11:2462MHz	-25.28	0.6	20	-4.68	8	PASS

APPLICANT: Shenzhen Allwins Technology Corporation
 FCC ID: XB5-UMS5001