

FCC TEST REPORT
FOR
Aeon Labs LLC.

Aeon Minimote
Model No.: DS03202B-ZWUS, DS03202W-ZWUS

Prepared for : Aeon Labs LLC.
Address : 121 Buckingham drive, unit36 santa claras CA95051 USA
Tel: (1) 408-248 2013
Fax: (1) 408-248 2013

Prepared By : Anbotek Compliance Laboratory Limited
Address : 2F, Langfeng Building, Kefa Road North, Hi-tech Industrial Park,
Nanshan District, Shenzhen 518057, China
Tel: (86) 755-26014771
Fax: (86) 755-26014772

Report Number : 200907788F
Date of Test : Jul. 31~Aug. 11, 2009
Date of Report : Aug. 18, 2009

TABLE OF CONTENTS

Description

	Page
Test Report Verification	
1. GENERAL INFORMATION	4
1.1. Description of Device (EUT)	4
1.2. Description of Test Facility	5
1.3. Measurement Uncertainty	5
2. POWER LINE CONDUCTED MEASUREMENT	6
2.1. Test Equipment	6
2.2. Block Diagram of Test Setup	6
2.3. Power Line Conducted Emission Measurement Limits (FCC Part 15 Class B)	6
2.4. Configuration of EUT on Measurement.....	7
2.5. Operating Condition of EUT	7
2.6. Test Procedure.....	7
2.7. Power Line Conducted Emission Measurement Results.....	7
3. RADIATED EMISSION MEASUREMENT.....	10
3.1. Test Equipment	10
3.2. Block Diagram of Test Setup	10
3.3. Radiated Emission Limit (Subpart B Class B)	11
3.4. EUT Configuration on Measurement.....	11
3.5. Operating Condition of EUT.....	11
3.6. Test Procedure.....	11
3.7. Radiated Emission Measurement Results	12
4. PHOTOGRAPH.....	17
4.1. Photo of Power Line Conducted Emission Test.....	17
4.2. Photo of Radiated Emission Test	17

APPENDIX I (Photos of EUT) (4 Pages)

TEST REPORT

Applicant : Aeon Labs LLC.

Manufacturer : Aeon Labs LLC.

EUT : Aeon Minimote

(A) MODEL NO. : DS03202B-ZWUS, DS03202W-ZWUS

(B) SERIAL NO. : N/A

(C) POWER SUPPLY: DC 3.7V via Battery or DC 5V via PC

(D) TRADE MARK: N/A

Measurement Procedure Used:

FCC Rules and Regulations Part 15 Subpart B 15.107&15.109-2007 & ANSI C63.4-2003

The device described above is tested by Anbotek Compliance Laboratory Limited To determine the maximum emission levels emanating from the device. The maximum emission levels are compared to the FCC Part 15 Subpart B Class B limits both radiated and conducted emissions. The measurement results are contained in this test report and Anbotek Compliance Laboratory Limited Is assumed full responsibility for the accuracy and completeness of these measurements. Also, this report shows that the Equipment Under Test (EUT) is to be technically compliant with the FCC requirements.

This report applies to above tested sample only. This report shall not be reproduced in part without written approval of Anbtek Compliance Laboratory Limited

Date of Test :

Jul. 31~Aug. 11, 2009

Jacky

Prepared by :

(Engineer)

Coco

Reviewer:

(Project Manager)



Approved & Authorized Signer :

(Manager)

1. GENERAL INFORMATION

1.1. Description of Device (EUT)

Description : Aeon Minimote

Model Number : DS03202B-ZWUS, DS03202W-ZWUS
The above samples are same except the model number & shape of appliances, so we prepare "DS03202W-ZWUS" for EMC test only.)

Test Power Supply : DC 3.7V via Battery or DC 5V via PC

Notebook PC : Manufacturer: IBM
M/N: 2373
S/N: 99-OL5HH
CE , FCC: DOC

Applicant : Aeon Labs LLC.
Address : 121 Buckingham drive, unit36 santa claras CA95051 USA

Manufacturer : Aeon Labs LLC.
Address : 121 Buckingham drive, unit36 santa claras CA95051 USA

Date of Sample received : Jul. 16, 2009

Date of Test : Jul. 31~Aug. 11, 2009

1.2. Description of Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

CNAS - LAB Code: L3503

Anbotek Compliance Laboratory Limited., Laboratory has been assessed and in compliance with CNAS/CL01: 2006 accreditation criteria for testing laboratories (identical to ISO/IEC 17025:2005 General Requirements) for the Competence of Testing Laboratories.

FCC-Registration No.: 607248

Anbotek Compliance Laboratory Limited, EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration 607248, November 12, 2008.

IC-Registration No.: 8058A

Anbotek Compliance Laboratory Limited., EMC Laboratory has been registered and fully described in a report filed with the (IC) Industry Canada. The acceptance letter from the IC is maintained in our files. Registration 8058A, November 12, 2008.

Test Location

All Emissions tests were performed

Anbotek Compliance Laboratory Limited. at 2F, Langfeng Building, Kefa Road North, Hi-tech Industrial Park, Nanshan District, Shenzhen 518057, China

1.3. Measurement Uncertainty

Radiation Uncertainty : $Ur = \pm 4.26\text{dB}$

Conduction Uncertainty : $Uc = \pm 2.66\text{dB}$

2. POWER LINE CONDUCTED MEASUREMENT


2.1. Test Equipment

The following test equipments are used during the power line conducted measurement:

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	EMI Test Receiver	Rohde & Schwarz	ESPI	1101604	Jun. 21, 2009	1 Year
2.	Spectrum Analyzer	Agilent	E7405A	MY45114970	Jun. 21, 2009	1 Year
3.	Artificial Mains	Rohde & Schwarz	ENV216	100055	Jun. 21, 2009	1 Year
4.	CE Variac	QUANLI	TDGC2-5	N/A	N/A	N/A
5.	Coaxial cable	Anbotek	RG214-N-3	11066	Jun. 21, 2009	1 Year
6.	EMI Test Software	SHURPLE	N/A	N/A	N/A	N/A

2.2. Block Diagram of Test Setup

2.2.1. Block diagram of connection between the EUT and simulators



(EUT: Aeon Minimote)

2.3. Power Line Conducted Emission Measurement Limits (FCC Part 15

Class B)

Frequency MHz	Limits dB(μV)	
	Quasi-peak Level	Average Level
0.15 ~ 0.50	66 ~ 56*	56 ~ 46*
0.50 ~ 5.00	56	46
5.00 ~ 30.00	60	50

Notes: 1. *Decreasing linearly with logarithm of frequency.
2. The lower limit shall apply at the transition frequencies.

2.4. Configuration of EUT on Measurement

The following equipments are installed on Power Line Conducted Emission Measurement to meet the commission requirement and operating regulations in a manner which tends to maximize its emission characteristics in a normal application.

EUT : Aeon Minimote
Model Number : DS03202W-ZWUS
Applicant : Aeon Labs LLC.

2.5. Operating Condition of EUT

- 2.5.1. Setup the EUT and simulator as shown as Section 2.2.
- 2.5.2. Turn on the power of all equipment.
- 2.5.3. Let the EUT work in test mode (Connect to PC) and measure it.

2.6. Test Procedure

The EUT system is connected to the power mains through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm coupling impedance for the EUT system. Please refer the block diagram of the test setup and photographs. Both sides of AC line are checked to find out the maximum conducted emission. In order to find the maximum emission levels, the relative positions of equipment and all of the interface cables shall be changed according to FCC ANSI C63.4-2003 on Conducted Emission Measurement.

The bandwidth of test receiver (E7405A) set at 9KHz.

The frequency range from 150KHz to 30MHz is checked.

The test result are reported on Section 2.7.

2.7. Power Line Conducted Emission Measurement Results

PASS.


The frequency range from 150KHz to 30 MHz is investigated.

The test curves Please refer the following pages.

Conducted disturbance

EUT: Aeon Minimote
 Op Cond: Connect to PC
 Test Spec: L
 Comment: AC 120V/60Hz
 Data: 2009-08-07

M/N: DS03202W-ZWUS




Frequency (MHz)	Reading Level (dBµV)	Limit (dBµV)	Over limit (dB)	
0.189	49.1	64.06	-14.96	QP
0.189	43.5	54.06	-10.56	AV
0.315	45.4	59.84	-14.44	QP
0.315	41.3	49.84	-8.54	AV

Conducted disturbance

EUT: Aeon Minimote
 Op Cond: Connect to PC
 Test Spec: N
 Comment: AC 120V/60Hz
 Data: 2009-08-07

M/N: DS03202W-ZWUS



Frequency (MHz)	Reading Level (dBµV)	Limit (dBµV)	Over limit (dB)	
0.185	50.6	64.24	-13.64	QP
0.185	44.8	54.24	-9.44	AV
0.313	47.7	59.89	-12.19	QP
0.313	43.4	49.89	-6.49	AV

3. RADIATED EMISSION MEASUREMENT

3.1. Test Equipment

The following test equipments are used during the radiated emission measurement:


3.1.1. For Anechoic Chamber

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	Trilog Broadband Antenna	SCHWARZBECK	VULB9163	345	Mar. 21, 2009	1 Year
2.	Spectrum Analyzer	Agilent	E7405A	MY45114970	Jun. 21, 2009	1 Year
3.	EMI Test Receiver	Rohde & Schwarz	ESPI	1101604	Jun. 21, 2009	1 Year
4.	EMI Test Software	Shurples	N/A	N/A	N/A	N/A
5.	Coaxial cable	Anbotek	RG214-N-8	11065	Jun. 21, 2009	1 Year
6.	PC	N/A	486DX2	N/A	N/A	N/A

3.2. Block Diagram of Test Setup

3.2.1. Block diagram of connection between the EUT and simulators


- 3.2.1.1. For Standby Mode.
- 3.2.1.2. For Connect to PC Mode.



(EUT: Aeon Minimote)

3.2.2. Anechoic Chamber Test Setup Diagram

ANTENNA TOWER



3.3. Radiated Emission Limit (Subpart B Class B)

FREQUENCY MHz	DISTANCE Meters	FIELD STRENGTHS LIMIT	
		μV/m	dB(μV)/m
30~88	3	100	40.0
88~216	3	150	43.5
216~960	3	200	46.0
960~1000	3	500	54.0

Remark : (1) Emission level (dB) μ V = 20 log Emission level μ V/m
 (2) The smaller limit shall apply at the cross point between two frequency bands.
 (3) Distance is the distance in meters between the measuring instrument, antenna and the closest point of any part of the device or system.

3.4. EUT Configuration on Measurement

The following equipments are installed on Radiated Emission Measurement to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

EUT : Aeon Minimote
 Model Number : DS03202W-ZWUS
 Applicant : Aeon Labs LLC.

3.5. Operating Condition of EUT

3.5.1. Setup the EUT as shown in Section 3.2.
 3.5.2. Let the EUT work in test mode (Standby / Connect to PC) and measure it.

3.6. Test Procedure

EUT and its simulators are placed on a turn table, which is 0.8 meter high above ground. The turn table can rotate 360 degrees to determine the position of the maximum emission level. EUT is set 3.0 meters away from the receiving antenna, which is mounted on a antenna tower. The antenna can be moved up and down between 1.0 meter and 4 meters to find out the maximum emission level. Broadband antenna (Trilog Broadband Antenna) is used as receiving antenna. Both horizontal and vertical polarizations of the antenna are set on measurement. In order to find the maximum emission levels, all of the interface cables must be manipulated according to ANSI C63.4-2003 on radiated emission measurement.

The bandwidth of the EMI test receiver (E7405A) is set at 120kHz.

The frequency range from 30MHz to 1000MHz is checked.

The test mode (Standby / Connect to PC) is tested in chamber and all the test results are listed in Section 3.7.

3.7. Radiated Emission Measurement Results

PASS.


The test curves Please refer the following pages.

**Anbotek Compliance Laboratory Limited**

2/F, Langfeng Building, Kefa Road North, Hi-tech Industrial Park, Nanshan District, Shenzhen 518057, China

Tel (86)755- 26014755
Fax: (86)755-26014720
Http://www.anbotek.com

Job No.:	AT0907728F	Polarization:	Horizontal
Standard:	FCC Class B 3M Radiation	Power Source:	DC 3.7V via Battery
Test item:	Radiation Test	Date:	09/08/07/
Temp. (C)/Hum. (%RH):	25.5(C)/42%RH	Time:	9/33/56
EUT:	Aeon Minimote	Test By:	Jacky
Model:	DS03202W-ZWUS	Distance:	3m
Note:		Standby	




No.	Frequency	Reading	Correct	Result	Limit	Margin	Remark
	(MHz)	(dBuV/m)	Factor(dB)	(dBuV/m)	(dBuV/m)	(dB)	

**Anbotek Compliance Laboratory Limited**

2/F, Langfeng Building, Kefa Road North, Hi-tech Industrial Park, Nanshan District, Shenzhen 518057, China

Tel (86)755- 26014755
Fax: (86)755-26014720
Http://www.anbotek.com

Job No.:	AT0907728F	Polarization:	Vertical
Standard:	FCC Class B 3M Radiation	Power Source:	DC 3.7V via Battery
Test item:	Radiation Test	Date:	09/08/07/
Temp. (C)/Hum. (%RH):	25.5(C)/42%RH	Time:	9/33/30
EUT:	Aeon Minimote	Test By:	Jacky
Model:	DS03202W-ZWUS	Distance:	3m
Note:		Standby	




No.	Frequency	Reading	Correct	Result	Limit	Margin	Remark
	(MHz)	(dBuV/m)	Factor(dB)	(dBuV/m)	(dBuV/m)	(dB)	

**Anbotech Compliance Laboratory Limited**

2/F, Langfeng Building, Kefa Road North, Hi-tech Industrial Park, Nanshan District, Shenzhen 518057, China

Tel (86)755- 26014755
Fax: (86)755-26014720
Http://www.anbotech.com

Job No.:	AT0907728F	Polarization:	Horizontal
Standard:	FCC Class B 3M Radiation	Power Source:	AC 120V, 60Hz
Test item:	Radiation Test	Date:	09/08/07/
Temp.(C)/Hum.(%RH):	25.5(C)/42%RH	Time:	8/35/20
EUT:	Aeon Minimote	Test By:	Jacky
Model:	DS03202W-ZWUS	Distance:	3m
Note:	Connect to PC		




No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	86.6020	51.00	-29.60	21.40	40.00	-18.60	QP
2	192.4180	59.11	-29.42	29.69	43.50	-13.81	QP
3	332.4080	55.40	-26.06	29.34	46.00	-16.66	QP
4	798.9796	54.05	-16.57	37.48	46.00	-8.52	QP

**Anbotek Compliance Laboratory Limited**

2/F, Langfeng Building, Kefa Road North, Hi-tech Industrial Park, Nanshan District, Shenzhen 518057, China

Tel (86)755- 26014755
Fax: (86)755-26014720
Http://www.anbotek.com

Job No.:	AT0907728F	Polarization:	Vertical
Standard:	FCC Class B 3M Radiation	Power Source:	AC 120V, 60Hz
Test item:	Radiation Test	Date:	09/08/07/
Temp. (C)/Hum. (%RH):	25.5(C)/42%RH	Time:	8/37/30
EUT:	Aeon Minimote	Test By:	Jacky
Model:	DS03202W-ZWUS	Distance:	3m
Note:	Connect to PC		



No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	30.7454	60.32	-27.60	32.72	40.00	-7.28	QP
2	91.5100	59.15	-28.74	30.41	43.50	-13.09	QP
3	729.3582	57.60	-17.63	39.97	46.00	-6.03	QP