

TEST REPORT

Reference No...... : WTS15S1239484E
FCC ID..... : XBAZW069
Applicant..... : Aeon Labs LLC.
Address..... : 121 Buckingham Drive Unit 36 Santa Claras California United States
Manufacturer : Fantem Technologies (Shenzhen) Co., Ltd
Address..... : North,3/F, Yitao Technology Industrial Park, Baihua Yuan Rd., The
Second Industrial Area, Guangming Sub-district Office, Guangming
New District, Shenzhen, Guangdong, China
Product Name..... : Smart Strip Gen5,Strip Gen5
Model No..... : ZW069-A02,ZW072-A02
Brand..... : N/A
Standards..... : FCC CFR47 Part 15 Section 15.249: 2015
Date of Receipt sample.... : Dec.11, 2015
Date of Test..... : Dec.12, 2015 ~ Jan. 19, 2016
Date of Issue..... : Jan. 26, 2016
Test Result..... : Pass

Remarks:

The results shown in this test report refer only to the sample(s) tested, this test report cannot be reproduced, except in full, without prior written permission of the company. The report would be invalid without specific stamp of test institute and the signatures of compiler and approver.

Prepared By:

Waltek Services (Shenzhen) Co., Ltd.


Address: 1/F., Fukangtai Building, West Baima Road, Songgang Street, Baoan District, Shenzhen,
Guangdong, China

Tel :+86-755-83551033

Fax:+86-755-83552400

Compiled by:

Approved by:



Zero Zhou / Test Engineer

Philo Zhong / Manager

2 Test Summary

Test Items	Test Requirement	Result
Conducted Emissions	15.207	PASS
Radiated Emission	15.249(a) 15.209 15.205(a)	PASS
Periodic Operation	15.35(c)	PASS
Band Edge	15.249 15.205 15.209	PASS
20dB Bandwidth	15:215(c)	PASS
Antenna Requirement	15.203	PASS

3 Contents

	Page
1 COVER PAGE.....	1
2 TEST SUMMARY.....	2
3 CONTENTS.....	3
4 GENERAL INFORMATION.....	4
4.1 GENERAL DESCRIPTION OF E.U.T.....	4
4.2 DETAILS OF E.U.T.....	4
4.3 TEST FACILITY.....	4
5 EQUIPMENT USED DURING TEST.....	5
5.1 EQUIPMENTS LIST.....	5
5.2 DESCRIPTION OF SUPPORT UNITS.....	6
5.3 MEASUREMENT UNCERTAINTY.....	6
5.4 TEST EQUIPMENT CALIBRATION.....	6
6 CONDUCTED EMISSION.....	7
6.1 E.U.T. OPERATION.....	7
6.2 EUT SETUP.....	7
6.3 MEASUREMENT DESCRIPTION.....	7
6.4 TEST RESULT.....	8
7 RADIATION EMISSION TEST.....	10
7.1 EUT OPERATION.....	10
7.2 TEST SETUP.....	11
7.3 SPECTRUM ANALYZER SETUP.....	12
7.4 TEST PROCEDURE.....	13
7.5 TEST RESULT.....	14
8 PERIODIC OPERATION.....	16
9 BAND EDGE.....	17
9.1 TEST PROCEDURE.....	17
9.2 TEST RESULT.....	17
10 20 DB BANDWIDTH MEASUREMENT.....	18
10.1 TEST PROCEDURE.....	18
10.2 TEST RESULT.....	18
11 ANTENNA REQUIREMENT.....	19
12 PHOTOGRAPHS- MODEL ZW069-A02 TEST SETUP.....	20
12.1 PHOTOGRAPH – RADIATION EMISSION.....	20
12.2 PHOTOGRAPH – CONDUCTED EMISSION TEST SETUP AT TEST SITE 1#.....	21
13 PHOTOGRAPHS - CONSTRUCTIONAL DETAILS.....	22
13.1 MODEL ZW069-A02 - EXTERNAL PHOTOS.....	22
13.2 MODEL ZW069-A02 - INTERNAL PHOTOS.....	25

4 General Information

4.1 General Description of E.U.T.

Product Name:	Smart Strip Gen5,Strip Gen5
Model No.:	ZW069-A02,ZW072-A02
Model Differences:	ZW069-A02 comes with an power detector function more than ZW072-A02
Type of Modulation:	FSK
Frequency Range:	908.40MHz,908.42MHz
The Lowest Oscillator:	4.096MHz
Antenna installation:	Embedded Antenna
Remark:	Both model are tested, and the worst case is model ZW069-A02 and the test data recorded in report.

4.2 Details of E.U.T.

Technical Data:	AC 125V 60Hz Max: 15A
-----------------	-----------------------

4.3 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **IC – Registration No.:7760A-1**

Waltek Services(Shenzhen) Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the Industry Canada. The acceptance letter from the Industry Canada is maintained in our files. Registration number 7760A-1, October 15, 2015.

- **FCC Test Site 1#– Registration No.: 880581**

Waltek Services(Shenzhen) Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration 880581, April 29, 2014.

- **FCC Test Site 2#– Registration No.: 328995**

Waltek Services(Shenzhen) Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration 328995, December 3, 2014.

4.3.1 Test Mode

All test mode(s) and condition(s) mentioned were considered and evaluated respectively by performing full tests, the worst data were recorded and reported.

Test mode	Lower channel	Middle channel	Upper channel
Transmitting	908.40MHz	/	908.42MHz

5 Equipment Used during Test

5.1 Equipments List

Conducted Emissions Test Site 1#						
Item	Equipment	Manufacturer	Model No.	Serial No.	Last Calibration Date	Calibration Due Date
1.	EMI Test Receiver	R&S	ESCI	100947	Sep.15,2015	Sep.14,2016
2.	LISN	R&S	ENV216	101215	Sep.15,2015	Sep.14,2016
3.	Cable	Top	TYPE16(3.5M)	-	Sep.15,2015	Sep.14,2016
3m Semi-anechoic Chamber for Radiation Emissions Test site 1#						
Item	Equipment	Manufacturer	Model No.	Serial No.	Last Calibration Date	Calibration Due Date
1	EMC Analyzer	Agilent	E7405A	MY45114943	Sep.15,2015	Sep.14,2016
2	Active Loop Antenna	Beijing Dazhi	ZN30900A	-	Sep.15,2015	Sep.14,2016
3	Trilog Broadband Antenna	SCHWARZBECK	VULB9163	336	Apr.19,2015	Apr.18,2016
4	Coaxial Cable (below 1GHz)	Top	TYPE16(13M)	-	Sep.15,2015	Sep.14,2016
5	Broad-band Horn Antenna	SCHWARZBECK	BBHA 9120 D	667	Apr.19,2015	Apr.18,2016
6	Broad-band Horn Antenna	SCHWARZBECK	BBHA 9170	335	Apr.19,2015	Apr.18,2016
7	Broadband Preamplifier	COMPLIANCE DIRECTION	PAP-1G18	2004	Mar.17,2015	Mar.16,2016
8	Coaxial Cable (above 1GHz)	Top	1GHz-25GHz	EW02014-7	Apr.10,2015	Apr.09,2016
3m Semi-anechoic Chamber for Radiation Emissions Test site 2#						
Item	Equipment	Manufacturer	Model No.	Serial No	Last Calibration Date	Calibration Due Date
1	Test Receiver	R&S	ESCI	101296	Sep.15,2015	Sep.14,2016
2	Trilog Broadband Antenna	SCHWARZBECK	VULB9160	9160-3325	Sep.15,2015	Sep.14,2016
3	Amplifier	Compliance pirection systems inc	PAP-0203	22024	Sep.15,2015	Sep.14,2016
4	Cable	HUBER+SUHNER	CBL2	525178	Sep.15,2015	Sep.14,2016
RF Conducted Testing						
Item	Equipment	Manufacturer	Model No.	Serial No.	Last Calibration Date	Calibration Due Date
1.	EMC Analyzer (9k~26.5GHz)	Agilent	E7405A	MY45114943	Sep.15,2015	Sep.14,2016
2.	Spectrum Analyzer	R&S	FSL6	100959	Sep.15,2015	Sep.14,2016

	(9k-6GHz)					
3.	Signal Analyzer (9k~26.5GHz)	Agilent	N9010A	MY50520207	Sep.15,2015	Sep.14,2016

5.2 Description of Support Units

Equipment	permanent assets	Note
Light Load	Waltek	Max 1875W

5.3 Measurement Uncertainty

Parameter	Uncertainty
Radio Frequency	$\pm 1 \times 10^{-6}$
RF Power	± 1.0 dB
RF Power Density	± 2.2 dB
Radiated Spurious Emissions test	± 5.03 dB (Bilog antenna 30M~1000MHz)
	± 5.47 dB (Horn antenna 1000M~25000MHz)

5.4 Test Equipment Calibration

All the test equipments used are valid and calibrated by CEPREI Certification Body that address is No.110 Dongguan Zhuang RD. Guangzhou, P.R.China.

6 Conducted Emission

Test Requirement:	FCC CFR 47 Part 15 Section 15.207
Test Method:	ANSI C63.10:2013
Test Result:	PASS
Frequency Range:	150kHz to 30MHz
Class/Severity:	Class B
Limit:	66-56 dB μ V between 0.15MHz & 0.5MHz 56 dB μ V between 0.5MHz & 5MHz 60 dB μ V between 5MHz & 30MHz
Detector:	Peak for pre-scan (9kHz Resolution Bandwidth)

6.1 E.U.T. Operation

Operating Environment :


Temperature:	25.5 °C
Humidity:	51 % RH
Atmospheric Pressure:	101.2kPa

EUT Operation :

The test was performed in transmitting mode, the test data were shown in the report.

6.2 EUT Setup

The conducted emission tests were performed using the setup accordance with the ANSI C63.10:2013




6.3 Measurement Description


The maximised peak emissions from the EUT was scanned and measured for both the Live and Neutral Lines. Quasi-peak & average measurements were performed if peak emissions were within 6dB of the average limit line.

6.4 Test Result

Live line:



Neutral line:



No.	Freq. (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit dBuV	Margin (dB)	Detector	Remark
1	0.1539	39.72	10.13	49.85	65.78	-15.93	QP	
2	0.1539	28.73	10.13	38.86	55.78	-16.92	AVG	
3	0.1620	35.36	10.13	45.49	65.36	-19.87	QP	
4	0.1620	23.79	10.13	33.92	55.36	-21.44	AVG	
5	0.1740	36.28	10.14	46.42	64.76	-18.34	QP	
6	0.1740	26.74	10.14	36.88	54.76	-17.88	AVG	
7	0.1940	34.53	10.15	44.68	63.86	-19.18	QP	
8	0.1940	26.00	10.15	36.15	53.86	-17.71	AVG	
9	0.2180	31.05	10.15	41.20	62.89	-21.69	QP	
10	0.2180	24.50	10.15	34.65	52.89	-18.24	AVG	
11	1.0940	30.99	10.22	41.21	56.00	-14.79	QP	
12	1.0940	25.03	10.22	35.25	46.00	-10.75	AVG	

7 Radiation Emission Test

Test Requirement: FCC Part15 Paragraph 15.249&15.209&15.205

Test Method: ANSI 63.10: 2013

Measurement Distance: 3m

Test Result: PASS

15.249(a)Limit:

Fundamental frequency	Field strength of fundamental		Field strength of harmonics	
	mV/m	dBuV/m	uV/m	dBuV/m
902-928 MHz	50	94	500	54
2400-2483.5 MHz	50	94	500	54
5725-5875 MHz	50	94	500	54
24.0-24.25 GHz	250	108	2500	68

15.209 Limit:

Frequency (MHz)	Field Strength		Field Strength Limit at 3m Measurement Dist	
	uV/m	Distance (m)	uV/m	dBuV/m
0.009 ~ 0.490	2400/F(kHz)	300	10000 * 2400/F(kHz)	$20\log^{(2400/F(kHz))} + 80$
0.490 ~ 1.705	24000/F(kHz)	30	100 * 24000/F(kHz)	$20\log^{(24000/F(kHz))} + 40$
1.705 ~ 30	30	30	100 * 30	$20\log^{(30)} + 40$
30 ~ 88	100	3	100	$20\log^{(100)}$
88 ~ 216	150	3	150	$20\log^{(150)}$
216 ~ 960	200	3	200	$20\log^{(200)}$
Above 960	500	3	500	$20\log^{(500)}$

Note: RF Voltage(dBuV)=20 log₁₀ RF Voltage(uV)

7.1 EUT Operation

Operating Environment :

Temperature: 23.5 °C

Humidity: 51.1 % RH

Atmospheric Pressure: 101.2kPa


EUT Operation :

The test was performed in transmitting mode, the test data were shown in the report.


7.2 Test Setup

The radiated emission tests were performed in the 3m Semi- Anechoic Chamber test site, using the setup accordance with the ANSI C63.10: 2013.


The test setup for emission measurement below 30MHz.



The test setup for emission measurement from 30MHz to 1GHz.



The test setup for emission measurement above 1 GHz.



7.3 Spectrum Analyzer Setup

Below 30MHz

Sweep Speed..... Auto
 IF Bandwidth..... 10kHz
 Video Bandwidth..... 10kHz
 Resolution Bandwidth..... 10kHz

30MHz ~ 1GHz

Sweep Speed..... Auto
 Detector..... PK
 Resolution Bandwidth..... 100kHz
 Video Bandwidth..... 300kHz

Above 1GHz

Sweep Speed..... Auto
 DetectorPK
 Resolution Bandwidth..... 1MHz
 Video Bandwidth..... 3MHz
 DetectorAve.
 Resolution Bandwidth..... 1MHz
 Video Bandwidth..... 10Hz

Video Bandwidth..... 10Hz

7.4 Test Procedure

1. The EUT is placed on a turntable. For below 1GHz, the EUT is 0.8m above ground plane; For above 1GHz, the EUT is 1.5m above ground plane.
2. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
3. EUT is set 3m away from the receiving antenna, which is moved from 1m to 4m to find out the maximum emissions. The spectrum was investigated from the lowest radio frequency signal generated in the device, without going below 9 kHz, up to the tenth harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower.
4. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
5. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
6. Repeat above procedures until the measurements for all frequencies are complete.
7. The radiation measurements are tested under 3-axes(X,Y,Z) position(X denotes lying on the table, Y denotes side stand and Z denotes vertical stand), After pre-test, It was found that the worse radiation emission was get at the X position. So the data shown was the X position only.

7.5 Test Result

Test Frequency :4.096MHz ~ 30MHz

Frequency (MHz)	Measurement results	Detector	Correct factor	Extrapolation factor	Measurement results (calculated)	FCC Part 15.249/209/205	
	dBμV/m@3m	PK/QP	dB/m	dB	dBμV/m @30m	Limit	Margin
6.202	25.14	QP	21.76	40.00	6.90	29.54	-22.64
8.198	24.39	QP	21.04	40.00	5.43	29.54	-24.11
26.695	27.99	QP	20.31	40.00	8.30	29.54	-21.24

Test Frequency: 30MHz ~ 10GHz

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	FCC Part 15.249/209/205	
				Height	Polar			Limit	Margin
(MHz)	(dBμV)	(PK/QP)	Degree	(m)	(H/V)	(dB/m)	(dBμV/m)	(dBμV/m)	(dB)
342.52	39.21	QP	216	1.1	V	-11.40	27.81	46.00	-18.19
908.42	91.06	PK	123	1.2	H	0.97	92.03	114.00	-21.97
908.42	88.14	PK	298	1.5	V	0.97	89.11	114.00	-24.89
1816.84	64.21	PK	53	1.5	H	-13.21	51.00	74.00	-23.00
1816.84	68.05	PK	142	1.9	V	-13.21	54.84	74.00	-19.16
2725.26	69.30	PK	250	1.8	H	-13.08	56.22	74.00	-17.78
2725.26	64.82	PK	329	1.8	V	-13.08	51.74	74.00	-22.26
3633.68	65.33	PK	26	1.4	H	-9.08	56.25	74.00	-17.75
3633.68	64.07	PK	144	1.3	V	-9.08	54.99	74.00	-19.01

AV = Peak +20Log10(duty cycle) =PK+(-9.27) [refer to section 8 for more detail]

Frequency	PK	RX Antenna Polar	Duty cycle Factor	AV	FCC Part 15.249/209/205	
					Limit	Margin
(MHz)	(dBμV/m)	(H/V)	(dB)	(dBμV/m)	(dBμV/m)	(dB)
908.42	92.03	H	-9.27	82.76	94.00	-11.24
908.42	89.11	V	-9.27	79.84	94.00	-14.16
1816.84	51.00	H	-9.27	41.73	54.00	-12.27
1816.84	54.84	V	-9.27	45.57	54.00	-8.43
2725.26	56.22	H	-9.27	46.95	54.00	-7.05
2725.26	51.74	V	-9.27	42.47	54.00	-11.53
3633.68	56.25	H	-9.27	46.98	54.00	-7.02
3633.68	54.99	V	-9.27	45.72	54.00	-8.28

8 Periodic Operation

The duty cycle was determined by the following equation:


To calculate the actual field intensity, the duty cycle correction factor in decibel is needed for later use and can be obtained from following conversion

Duty Cycle(%)=Total On interval in a complete pulse train/ Length of a complete pulse train * %

Duty Cycle Correction Factor(dB)=20 * Log₁₀(Duty Cycle)

Total transmission time(ms)	34.40
Length of a complete transmission period(ms)	100
Duty Cycle(%)	34.40
Duty Cycle Correction Factor(dB)	-9.27

Refer to the duty cycle plot (as below)




9 Band Edge

Test Requirement:	15.249(d):Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in §15.209, whichever is the lesser attenuation.
Test Method:	ANSI C63.10:2013
Test Mode:	Transmitting

9.1 Test Procedure

1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum;
2. Set the spectrum analyzer: RBW = 100kHz, VBW = 300kHz, Sweep = auto
Detector function = peak, Trace = max hold

9.2 Test Result



10 20 dB Bandwidth Measurement

Test Requirement:

FCC CFR47 Part 15 Section 15.215(c)

Test Method:

ANSI C63.10:2013

Test Mode:


Transmitting

10.1 Test Procedure

1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum;
2. Set the spectrum analyzer: RBW = 30kHz, VBW = 100kHz

10.2 Test Result

Frequency (MHz)	Bandwidth Emission (kHz)
908.42	137.70




11 Antenna Requirement

According to the FCC Part 15 Paragraph 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. This product has a Embedded Antenna , fulfil the requirement of this section.


12 Photographs- Model ZW069-A02 Test Setup

12.1 Photograph – Radiation Emission

Test frequency 4.096MHz to 30MHz at test site 2#



Test frequency from 30MHz to 1GHz at test site 2#



Test frequency above 1GHz at test site 1#




12.2 Photograph – Conducted Emission Test Setup at Test Site 1#



13 Photographs - Constructional Details


13.1 Model ZW069-A02 - External Photos












13.2 Model ZW069-A02 - Internal Photos











=====End of Report=====