



## FCC CERTIFICATION TEST REPORT

<b>Applicant</b>	:	AAMP of Florida, Inc. dba AAMP Global
<b>Address of Applicant</b>	:	15500 Lightwave Drive, Suite 202 Clearwater, FL 33760
<b>Manufacturer</b>	:	Skypine Electronics (ShenZhen)Co.,Ltd
<b>Address of Manufacturer</b>	:	Third floor, Building B, Jingang Science Park, Qiaotou Community, Fuhai Street, Baoan District, Shenzhen City, Guangdong Province, China
<b>Equipment under Test</b>	:	NAVIGATION MULTIMEDIA RECEIVER
<b>Model No.</b>	:	iX210, iX210-C, iX210-SR, iX210-E, iX212, iX212-C, iX212-SR, iX212-E, iX215, iX215-C, iX215-SR, iX215-E
<b>FCC ID</b>	:	XBD-IX210
<b>Test Standard(s)</b>	:	FCC Rules and Regulations Part 15 Subpart C, ANSI C63.10:2013
<b>Report No.</b>	:	DDT-RE23101322-2E03
<b>Issue Date</b>	:	2023/11/25
<b>Issue By</b>	:	Guangdong Dongdian Testing Service Co., Ltd.
<b>Address of Laboratory</b>	:	Unit 2, Building 1, No. 17, Zongbu 2nd Road, Songshan Lake Park, Dongguan, Guangdong, China, 523808

# REPORT

## Table of Contents

	Test report declares.....	4
1.	Summary of Test Results.....	6
2.	General Test Information .....	7
2.1.	Description of EUT .....	7
2.2.	Accessories of EUT.....	8
2.3.	Assistant equipment used for test.....	8
2.4.	Block diagram of EUT configuration for test .....	8
2.5.	Deviations of test standard.....	9
2.6.	Test environment conditions .....	9
2.7.	Test laboratory .....	9
2.8.	Measurement uncertainty.....	10
3.	Equipment Used During Conductive Test.....	11
4.	6dB Bandwidth .....	12
4.1.	Block diagram of test setup.....	12
4.2.	Limits .....	12
4.3.	Test procedure .....	12
4.4.	Test result.....	13
4.5.	Test graphs .....	14
5.	99% Bandwidth .....	18
5.1.	Block diagram of test setup.....	18
5.2.	Limits .....	18
5.3.	Test procedure .....	18
5.4.	Test result.....	19
5.5.	Test graphs .....	20
6.	Conducted Output Power.....	24
6.1.	Block diagram of test setup.....	24
6.2.	Limits .....	24
6.3.	Test procedure .....	24
6.4.	Test result.....	25
7.	Power Spectral Density.....	26
7.1.	Block diagram of test setup.....	26
7.2.	Limits .....	26
7.3.	Test procedure .....	26
7.4.	Test result.....	27
7.5.	Test graphs .....	28
8.	Band Edge Compliance (Conducted Method) .....	32
8.1.	Block diagram of test setup.....	32
8.2.	Limits .....	32
8.3.	Test procedure .....	32

8.4.	Test result.....	33
8.5.	Test graphs .....	33
9.	RF Conducted Spurious Emissions .....	36
9.1.	Block diagram of test setup.....	36
9.2.	Limits .....	36
9.3.	Test procedure .....	36
9.4.	Test result.....	37
9.5.	Test graphs .....	38
10.	Duty Cycle .....	50
10.1.	Block diagram of test setup.....	50
10.2.	Limit.....	50
10.3.	Test procedure .....	50
10.4.	Test result.....	51
10.5.	Test graphs .....	52
11.	Radiated Spurious Emissions .....	56
11.1.	Test equipment.....	56
11.2.	Block diagram of test setup.....	56
11.3.	Limit .....	58
11.4.	Test procedure .....	60
11.5.	Test result.....	61
12.	Radiated Band Edge Compliance.....	70
12.1.	Test equipment.....	70
12.2.	Block diagram of test setup.....	70
12.3.	Limit .....	70
12.4.	Test procedure .....	71
12.5.	Test result.....	71
13.	Power Line Conducted Emission .....	88
13.1.	Test equipment.....	88
13.2.	Block diagram of test setup.....	88
13.3.	Power Line Conducted Emission Limits .....	88
13.4.	Test procedure .....	89
13.5.	Test result.....	89
14.	Antenna Requirements .....	90
14.1.	Limit.....	90
14.2.	Result .....	90
15.	Test Setup Photograph .....	91
16.	Photos of the EUT .....	93

## Test Report Declare

<b>Applicant</b>	:	AAMP of Florida, Inc. dba AAMP Global
<b>Address of Applicant</b>	:	15500 Lightwave Drive, Suite 202 Clearwater, FL 33760
<b>Equipment under Test</b>	:	NAVIGATION MULTIMEDIA RECEIVER
<b>Model No.</b>	:	iX210, iX210-C, iX210-SR, iX210-E, iX212, iX212-C, iX212-SR, iX212-E, iX215, iX215-C, iX215-SR, iX215-E
<b>Manufacturer</b>	:	Skypine Electronics (ShenZhen)Co.,Ltd
<b>Address of Manufacturer</b>	:	Third floor, Building B, Jingang Science Park, Qiaotou Community, Fuhai Street, Baoan District, Shenzhen City, Guangdong Province, China

### Test Standard Used:

FCC Rules and Regulations Part 15 Subpart C

### Test Procedure Used:

ANSI C63.10:2013,

### We Declare:

The equipment described above is tested by Guangdong Dongdian Testing Service Co., Ltd. and in the configuration tested the equipment complied with the standards specified above. The test results are contained in this test report and Guangdong Dongdian Testing Service Co., Ltd. is assumed of full responsibility for the accuracy and completeness of these tests.

**After test and evaluation, our opinion is that the equipment provided for test compliance with the requirement of the above standards.**

<b>Report No.:</b>	DDT-RE23101322-2E03		
<b>Date of Receipt:</b>	2023/10/18	<b>Date of Test:</b>	2023/10/18-2023/11/25

**Prepared By:**

*Jacky Huang*

**Jacky Huang/Engineer**

**Approved By:**



*Damon Hu*

**Damon Hu/EMC Manager**

Note: This report applies to above tested sample only. This report shall not be reproduced in parts without written approval of Guangdong Dongdian Testing Service Co., Ltd.

### Revision History

Rev.	Revisions	Issue Date	Revised By
---	Initial issue	2023/11/25	

## 1. Summary of Test Results

The EUT have been tested according to the applicable standards as referenced below.		
Description of Test Item	Standard	Results
6dB Bandwidth and 99% Bandwidth	FCC Part 15: 15.247(a)(2)	PASS
Conducted Output Power	FCC Part 15: 15.247(b)(3)	PASS
Power Spectral Density	FCC Part 15:15.247(e)	PASS
Band-edge and Spurious Emissions (Conducted)	FCC Part 15: 15.247(d)	PASS
Radiated Spurious Emissions	FCC Part 15: 15.205 FCC Part 15: 15.209 FCC Part 15: 15.247(d)	PASS
Radiated Band Edge Compliance	FCC Part 15: 15.205 FCC Part 15: 15.209 FCC Part 15: 15.247(d)	PASS
Power Line Conducted Emission	FCC Part 15: 15.207(a)	N/A
Antenna requirement	FCC Part 15: 15.203	PASS
Note: NA is not applicable.		

## 2. General Test Information

### 2.1. Description of EUT

EUT Name	: NAVGATION MULTIMEDIA RECEIVER
Model Number	: iX210, iX210-C, iX210-SR, iX210-E, iX212, iX212-C, iX212-SR, iX212-E, iX215, iX215-C, iX215-SR, iX215-E
Model Difference	: All models have same electrical circuit design, only the model's name, Software, LCD Screen size, mechanical and package are different for marketing requirements. The test model is iX210
EUT Function Description	: Please reference user manual of this device
Power Supply	: DC 12V
Radio Specification	: Bluetooth V4.2 (BR/EDR/LE), WLAN (2.4 GHz): IEEE 802.11b/g/n, WLAN (5 GHz): IEEE 802.11a/n/ac
Operation Frequency	: Bluetooth (BR/EDR/LE): 2402 MHz-2480 MHz IEEE 802.11b/g/n: 2412 MHz to 2462 MHz, IEEE 802.11a/n/ac: 5180 MHz to 5240 MHz, 5745 MHz to 5825 MHz
Modulation	: Bluetooth BR/EDR: GFSK, $\pi/4$ -DQPSK, 8DPSK Bluetooth LE: GFSK IEEE 802.11b: DSSS (CCK, DQPSK, DBPSK) IEEE 802.11g/a: OFDM (64QAM, 16QAM, QPSK, BPSK) IEEE 802.11n: OFDM (64QAM, 16QAM, QPSK, BPSK) IEEE 802.11ac: OFDM (256QAM, 64QAM, 16QAM, QPSK, BPSK)
Sample Number	: S23101322-02

Note 1: EUT is the abbreviation of equipment under test.

Note 2: “☑” means to be chosen or applicable; “☐” means don't to be chosen or not applicable; This note applies to entire report.

Note 3: This report only for WLAN (2.4 GHz): IEEE 802.11b/g/n.

Note 4: Simultaneously transmission condition: N/A.

Note 5: Antenna information:

WLAN (2.4 GHz) Antenna information	
Antenna Type	: FPC
Antenna Gain (dBi)	: 3.53

Note 6: Channel information:

Channel information					
CH	Frequency (MHz)	CH	Frequency (MHz)	CH	Frequency (MHz)
1	2412	5	2432	9	2452
2	2417	6	2437	10	2457
3	2422	7	2442	11	2462
4	2427	8	2447	/	/

Note 7: The above EUT information is declared by manufacturer and for more detailed features description please refer to the manufacturer's specifications or User's Manual. The above Antenna information is declared by manufacturer and for more detailed features description please refer to the manufacturer's specifications, the laboratory shall not be held responsible.


## 2.2. Accessories of EUT

Accessories	Manufacturer	Model number	Description
N/A	N/A	N/A	N/A

## 2.3. Assistant equipment used for test

Assistant equipment	Manufacturer	Model number	EMC Compliance	SN
N/A	N/A	N/A	N/A	N/A

## 2.4. Block diagram of EUT configuration for test



The Xshell.exe was used to control EUT work in Continuous Tx mode, and select test channel, wireless mode as below table.

The pathloss of external cable: 0.5 dB (According to the manufacturer's claims)



Tested mode, channel, and data rate information				
Mode	Setting Tx Power	data rate (Mbps) (see Note)	Channel	Frequency (MHz)
IEEE 802.11b	40	1	LCH: CH1	2412
	40	1	MCH: CH6	2437
	40	1	HCH: CH11	2462
IEEE 802.11g	40	6	LCH: CH1	2412
	40	6	MCH: CH6	2437
	40	6	HCH: CH11	2462
IEEE 802.11n HT20	40	MCS 0	LCH: CH1	2412
	40	MCS 0	MCH: CH6	2437
	40	MCS 0	HCH: CH11	2462
IEEE 802.11n HT40	40	MCS 0	LCH: CH3	2422
	40	MCS 0	MCH: CH6	2437
	40	MCS 0	HCH: CH9	2452

Note: According exploratory test, EUT will have maximum output power in those data rate, so those data rate were used for all test.

## 2.5. Deviations of test standard

No Deviation

## 2.6. Test environment conditions

Temperature range:	+15°C to +35 °C
Humidity range:	20% to 75%
Pressure range:	86 kPa to 106 kPa

## 2.7. Test laboratory

Guangdong Dongdian Testing Service Co., Ltd.

Unit 2, Building 1, No.17, Zongbu 2nd Road, Songshan Lake Park, Dongguan, Guangdong, China, 523808

Tel.: +86-0769-38826678, <http://www.dgddt.com>, Email: [ddt@dgddt.com](mailto:ddt@dgddt.com).

CNAS Accreditation No. L6451; A2LA Accreditation Number: 3870.01

FCC Designation Number: CN1182, Test Firm Registration Number: 540522

Innovation, Science and Economic Development Canada Site Registration Number: 10288A

Conformity Assessment Body identifier: CN0048

VCCI facility registration number: C-20087, T-20088, R-20123, R-20155, G-20118

## 2.8. Measurement uncertainty

Test Item	Uncertainty
Bandwidth	1.1%
Peak Output Power (Conducted) (Spectrum analyzer)	0.86 dB (10 MHz ≤ f < 3.6 GHz);
	1.38 dB (3.6 GHz ≤ f < 8 GHz)
Peak Output Power (Conducted) (Power Sensor)	0.74 dB
Power Spectral Density	0.74 dB (10 MHz ≤ f < 3.6 GHz);
	1.38 dB (3.6 GHz ≤ f < 8 GHz)
Frequencies Stability	6.7 × 10 <sup>-8</sup> (Antenna couple method)
	5.5 × 10 <sup>-8</sup> (Conducted method)
Conducted spurious emissions	0.86 dB (10 MHz ≤ f < 3.6 GHz);
	1.40 dB (3.6 GHz ≤ f < 8 GHz)
	1.66 dB (8 GHz ≤ f < 26.5 GHz)
Uncertainty for radio frequency (RBW < 20 kHz)	3×10 <sup>-8</sup>
Temperature	0.4 °C
Humidity	2 %
Uncertainty for Radiation Emission test (9 kHz – 30 MHz)	3.44 dB
Uncertainty for Radiation Emission test (30 MHz - 1 GHz)	4.70 dB (Antenna Polarize: V)
	4.84 dB (Antenna Polarize: H)
Uncertainty for Radiation Emission test (1 GHz - 40 GHz)	4.10 dB (1 - 6 GHz)
	4.40 dB (6 GHz - 18 GHz)
	3.54 dB (18 GHz - 26 GHz)
	4.30 dB (26 GHz - 40 GHz)
Uncertainty for Power line conduction emission test	3.34dB (150KHz-30MHz)
	3.72dB (9KHz-150KHz)


Note: This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

### 3. Equipment Used During Conductive Test

Equipment	Manufacturer	Model No.	Serial Number	Due Date	Cal. Interval
<input checked="" type="checkbox"/> RF Connected Test (RF Measurement System 3#)					
SIGNAL ANALYZER	R&S	FSV40	101407	2024/07/11	1 Year
Wideband Radio Communication Tester	R&S	CMW500	117491	2024/04/26	1 Year
EXG Analog Signal Generator	KEYSIGHT	N5173B	MY62153058	2024/07/11	1 Year
MXG Vector Signal Generator	Agilent	N5182A	MY48180912	2024/04/22	1 Year
RF Control Unit	Tonscend	JS0806-2	20C8060230	2024/04/26	1 Year
TEMP&HUMI Programmable Chamber	ZHIXIANG	ZXGDJS-150L	ZX170110-A	2024/05/14	1 Year
Test Software	Tonscend	JS1120-3	Ver.3.2.22	N/A	N/A

## 4. 6dB Bandwidth

### 4.1. Block diagram of test setup



### 4.2. Limits

For direct sequence systems, the minimum 6 dB bandwidth shall be at least 500 kHz

### 4.3. Test procedure

- (1) The test according to ANSI C63.10-2013 clause 11.8.
- (2) Connect EUT's antenna output to spectrum analyzer by RF cable, the path loss was compensated to the results
- (3) Set the EUT as maximum power setting and enable the EUT transmit continuously
- (4) Use the following spectrum analyzer settings for 6 dB Bandwidth:
 


RBW:	100 kHz
VBW:	$\geq [3 \times \text{RBW}]$
Detector Mode:	peak
Sweep time:	auto
Trace mode	max hold
- (5) Allow the trace to stabilize, measure the 6 dB bandwidth of signal, and record the results in the report.




## 4.4. Test result




Test Site:	RF Measurement System 3#	Test Date:	2023.10.26-2023.10.26
Ambient Condition:	25.3°C, 44.0 %RH	Test Engineer:	Zhongyao
Equipment under Test:	NAVIGATION MULTIMEDIA RECEIVER	Model No.:	iX210
Sample Number:	S23101322-02	Test Power Supply:	DC12V

Test Mode	Antenna	Frequency [MHz]	DTS BW [MHz]	FL [MHz]	FH [MHz]	Limit [MHz]	Verdict
11B	Ant1	2412	10.08	2406.96	2417.04	0.5	PASS
		2437	10.08	2431.96	2442.04	0.5	PASS
		2462	10.08	2456.96	2467.04	0.5	PASS
11G	Ant1	2412	16.32	2403.84	2420.16	0.5	PASS
		2437	16.32	2428.84	2445.16	0.5	PASS
		2462	16.32	2453.84	2470.16	0.5	PASS
11N20SISO	Ant1	2412	17.52	2403.24	2420.76	0.5	PASS
		2437	17.52	2428.24	2445.76	0.5	PASS
		2462	17.08	2453.44	2470.52	0.5	PASS
11N40SISO	Ant1	2422	35.76	2404.08	2439.84	0.5	PASS
		2437	35.84	2419.08	2454.92	0.5	PASS
		2452	35.52	2434.24	2469.76	0.5	PASS




4.5. Test graphs












## 5. 99% Bandwidth

### 5.1. Block diagram of test setup



### 5.2. Limits

Just for Report.

### 5.3. Test procedure

- (1) The test according to ANSI C63.10-2013 clause 6.9.3.
- (2) Connect EUT's antenna output to spectrum analyzer by RF cable, the path loss was compensated to the results
- (3) Set the EUT as maximum power setting and enable the EUT transmit continuously
- (4) Use the following spectrum analyzer settings for the 99% Bandwidth:
 


RBW:	1% to 5% of the OBW
VBW:	approximately three times RBW
Span:	between 1.5 times and 5.0 times the OBW
Detector Mode:	peak
Sweep time:	auto
Trace mode	max hold
- (5) Allow the trace to stabilize, measure the 99% bandwidth of signal, and record the results in the report.




#### 5.4. Test result




Test Site:	RF Measurement System 3#	Test Date:	2023.10.26-2023.10.26
Ambient Condition:	25.3°C, 44.0 %RH	Test Engineer:	Zhongyao
Equipment under Test:	NAVIGATION MULTIMEDIA RECEIVER	Model No.:	iX210
Sample Number:	S23101322-02	Test Power Supply:	DC12V




Test Mode	Antenna	Channel Frequency [MHz]	OCB [MHz]	FL [MHz]	FH [MHz]	Limit [MHz]	Verdict
11B	Ant1	2412	15.105	2404.4076	2419.5125	---	---
		2437	15.105	2429.4076	2444.5125	---	---
		2462	15.065	2454.4476	2469.5125	---	---
11G	Ant1	2412	17.343	2403.3686	2420.7113	---	---
		2437	17.662	2428.0490	2445.7113	---	---
		2462	17.542	2453.2088	2470.7512	---	---
11N20SISO	Ant1	2412	18.422	2402.8092	2421.2308	---	---
		2437	18.541	2427.6893	2446.2308	---	---
		2462	18.342	2452.7692	2471.1109	---	---
11N40SISO	Ant1	2422	36.843	2403.5385	2440.3816	---	---
		2437	37.003	2418.4585	2455.4615	---	---
		2452	36.763	2433.5385	2470.3017	---	---

5.5. Test graphs










## 6. Conducted Output Power

### 6.1. Block diagram of test setup



### 6.2. Limits

For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. If transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

### 6.3. Test procedure

- (1) The test according to ANSI C63.10-2013 clause 11.9.2.3.
- (2) Connect EUT's antenna output to RF power meter by RF cable, the path loss was compensated to the results.
- (3) Set the EUT as maximum power setting and enable the EUT transmit continuously, If the transmitter does not transmit continuously, measure the duty cycle, D, of the transmitter output signal.
- (4) Measure the average power of the transmitter. This measurement is an average over both the ON and OFF periods of the transmitter.
- (5) Adjust the measurement in dBm by adding  $[10 \log (1 / D)]$ , where D is the duty cycle.
- (6) Record the RF average power of each antenna port.



#### 6.4. Test result


Test Site:	RF Measurement System 3#	Test Date:	2023.10.26-2023.10.26
Ambient Condition:	25.3°C, 44.0 %RH	Test Engineer:	Zhongyao
Equipment under Test:	NAVIGATION MULTIMEDIA RECEIVER	Model No.:	iX210
Sample Number:	S23101322-02	Test Power Supply:	DC12V

Test Mode	Antenna	Frequency [MHz]	Average power [dBm]	Duty Cycle [%]	DC Factor [dBm]	Result [dBm]	Limit [dBm]	EIRP [dBm]	EIRP Limit [dBm]	Verdict
11B	Ant1	2412	15.66	99.68	0.01	15.67	≤30.00	19.20	≤36.00	PASS
		2437	15.53	99.60	0.02	15.55	≤30.00	19.08	≤36.00	PASS
		2462	15.43	99.68	0.01	15.44	≤30.00	18.97	≤36.00	PASS
11G	Ant1	2412	10.84	94.09	0.26	11.10	≤30.00	14.63	≤36.00	PASS
		2437	10.71	93.64	0.29	11.00	≤30.00	14.53	≤36.00	PASS
		2462	10.60	97.18	0.12	10.72	≤30.00	14.25	≤36.00	PASS
11N20SISO	Ant1	2412	10.82	93.24	0.30	11.12	≤30.00	14.65	≤36.00	PASS
		2437	10.65	91.87	0.37	11.02	≤30.00	14.55	≤36.00	PASS
		2462	10.55	92.75	0.33	10.88	≤30.00	14.41	≤36.00	PASS
11N40SISO	Ant1	2422	10.91	86.36	0.64	11.55	≤30.00	15.08	≤36.00	PASS
		2437	10.82	86.36	0.64	11.46	≤30.00	14.99	≤36.00	PASS
		2452	10.75	84.68	0.72	11.47	≤30.00	15.00	≤36.00	PASS

Note: EIRP (dBm)=Conducted Output Power (dBm)+ Antenna Gain (dBi)

## 7. Power Spectral Density

### 7.1. Block diagram of test setup



### 7.2. Limits

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

### 7.3. Test procedure

- (1) The test according to ANSI C63.10-2013 clause 11.10.5.
- (2) Connect EUT's antenna output to spectrum analyzer by RF cable, the path loss was compensated to the results.
- (3) Set the EUT as maximum power setting and enable the EUT transmit continuously.
- (4) Use the following spectrum analyzer settings for Power Spectral Density measurement:
 

Center frequency	DTS Channel center frequency
RBW:	$3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$
VBW:	$\geq 3\text{RBW}$
Span	1.5 times the DTS bandwidth
Detector Mode:	RMS
Sweep time:	auto
Trace mode:	max hold
Trace:	Employ trace averaging (rms) mode over a minimum of 100 traces.
- (5) Add  $[10 \log (1 / D)]$ , where D is the duty cycle measured in step a), to the measured PSD to compute the average PSD during the actual transmission time.  
If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.


#### 7.4. Test result




Test Site:	RF Measurement System 3#	Test Date:	2023.10.26-2023.10.26
Ambient Condition:	25.3°C, 44.0 %RH	Test Engineer:	Zhongyao
Equipment under Test:	NAVIGATION MULTIMEDIA RECEIVER	Model No.:	iX210
Sample Number:	S23101322-02	Test Power Supply:	DC12V




Test Mode	Antenna	Frequency [MHz]	Result [dBm/3-100kHz]	Limit [dBm/3kHz]	Verdict
11B	Ant1	2412	-16.98	≤8.00	PASS
		2437	-16.89	≤8.00	PASS
		2462	-16.90	≤8.00	PASS
11G	Ant1	2412	-20.96	≤8.00	PASS
		2437	-19.67	≤8.00	PASS
		2462	-21.59	≤8.00	PASS
11N20SISO	Ant1	2412	-21.00	≤8.00	PASS
		2437	-21.56	≤8.00	PASS
		2462	-21.27	≤8.00	PASS
11N40SISO	Ant1	2422	-21.33	≤8.00	PASS
		2437	-22.56	≤8.00	PASS
		2452	-22.25	≤8.00	PASS




Note: The Duty Cycle Factor is compensated in the graph.

7.5. Test graphs










## 8. Band Edge Compliance (Conducted Method)

### 8.1. Block diagram of test setup



### 8.2. Limits

In any 100 kHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 30 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power.

### 8.3. Test procedure

- (1) Connect EUT's antenna output to spectrum analyzer by RF cable.
- (2) Establish a reference level by using the following procedure:
 

RBW:	100 kHz
VBW:	300 kHz
Span	Encompass frequency range to be measured
Detector Mode:	Peak
Sweep time:	auto
Trace mode	Max hold
- (3) Allow the trace to stabilize, use the peak marker function to determine the maximum peak power level to establish the reference level.
- (4) Then mark the maximum amplitude of all unwanted emissions outside of the authorized frequency band.







8.4. Test result




Test Site:	RF Measurement System 3#	Test Date:	2023.10.26-2023.10.26
Ambient Condition:	25.3°C, 44.0 %RH	Test Engineer:	Zhongyao
Equipment under Test:	NAVIGATION MULTIMEDIA RECEIVER	Model No.:	iX210
Sample Number:	S23101322-02	Test Power Supply:	DC12V

EUT Set Mode	Channel or Frequency	Result (dBm)	EUT Set Mode	Channel or Frequency	Result (dBm)
11b	CH1	Pass	11g	CH1	Pass
	CH11	Pass		CH11	Pass
11n HT 20	CH1	Pass	11n HT 40	CH3	Pass
	CH11	Pass		CH9	Pass

8.5. Test graphs








## 9. RF Conducted Spurious Emissions

### 9.1. Block diagram of test setup



### 9.2. Limits

In any 100 kHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 30 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power.

### 9.3. Test procedure

(1) Connect EUT's antenna output to spectrum analyzer by RF cable.

(2) Establish a reference level by using the following procedure:

Center frequency	Test frequency
RBW:	100 kHz
VBW:	300 kHz
Span	Wide enough to capture the peak level of the in-band emission
Detector Mode:	Peak
Sweep time:	auto
Trace mode	Max hold

(3) Allow the trace to stabilize, use the peak marker function to determine the maximum peak power level to establish the reference level.

(4) Set the spectrum analyzer as follows:

RBW:	100 kHz
VBW:	300 kHz
Span	Encompass frequency range to be measured
Number of measurement points	$\geq \text{Span}/\text{RBW}$
Detector Mode:	Peak
Sweep time:	auto
Trace mode	Max hold




(5) Allow the trace to stabilize, use the peak marker function to determine the maximum amplitude of all unwanted emissions outside of the authorized frequency band




**9.4. Test result**

Test Site:	RF Measurement System 3#	Test Date:	2023.10.26-2023.10.26
Ambient Condition:	25.3°C, 44.0 %RH	Test Engineer:	Zhongyao
Equipment under Test:	NAVIGATION MULTIMEDIA RECEIVER	Model No.:	iX210
Sample Number:	S23101322-02	Test Power Supply:	DC12V




EUT Set Mode	Channel or Frequency	Result (dBm)	EUT Set Mode	Channel or Frequency	Result (dBm)
11b	CH1	Pass	11g	CH1	Pass
	CH11	Pass		CH11	Pass
11n HT 20	CH1	Pass	11n HT 40	CH3	Pass
	CH11	Pass		CH9	Pass

9.5. Test graphs





























































## 10. Duty Cycle

### 10.1. Block diagram of test setup



### 10.2. Limit

Just for Report.

### 10.3. Test procedure

(1) Connected the EUT's antenna port to the Spectrum Analyzer by suitable attenuator, The cable loss and attenuator loss have been put into spectrum analyzer as amplitude offset.

set the Spectrum Analyzer as below:

Centre Frequency: The centre frequency of the middle hopping channel.

Resolution BW: 10 MHz.

Video BW: 10 MHz.

Span: Zero span.

Detector: Peak.

Trace Mode: Clear Write.

Sweep: Video Trigger

(2) When the trace is complete, measure the sending time of 1 burst and the duty cycle of 1 burst cycle.

(3) Calculate dwell time follow below formula:

Duty cycle= Pulse's on time / Burst cycle