



Global Product Certification
EMC-EMF Safety Approvals

EMC Technologies Pty Ltd
ABN 82 057 105 549
176 Harrick Road
Keilor Park Victoria Australia 3042

Ph: + 613 9365 1000
Fax: + 613 9331 7455
email: melb@emctech.com.au

**EMI TEST REPORT for
CERTIFICATION to
FCC PART 15.209 & RSS-210 / RSS-Gen**

FCC ID: XBH-FFW
Industry Canada ID: 8425A-FFW

Test Sample: ISO FFW Series RFID Readers

Tested for: Aleis Pty Ltd

Report Number: M110315_Cert_ISO_FFW

Issue Date: 17th March 2011

EMC Technologies Pty Ltd reports apply only to the specific samples tested under stated test conditions. It is the manufacturer's responsibility to assure that additional production units of this model are manufactured with identical electrical and mechanical components. EMC Technologies Pty Ltd shall have no liability for any deductions, inferences or generalisations drawn by the client or others from EMC Technologies Pty Ltd issued reports. This report shall not be used to claim, constitute or imply product endorsement by EMC Technologies Pty Ltd.



This document is issued in accordance with NATA's accreditation requirements. The results of tests, calibration and/or measurements included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing and calibration reports.

This document shall not be reproduced except in full.

**EMI TEST REPORT FOR CERTIFICATION
to
FCC Part 15.209 & RSS-210 / RSS-Gen**

EMC Technologies Report No. M110315_Cert_ISO_FFW

Issue Date: 17th March 2011

CONTENTS

- 1.0 INTRODUCTION**
- 2.0 GENERAL INFORMATION**
- 3.0 CONDUCTED EMI MEASUREMENTS**
- 4.0 RADIATED EMI MEASUREMENTS**
- 5.0 ANTENNA REQUIREMENT**
- 6.0 COMPLIANCE STATEMENT**
- 7.0 UNCERTAINTIES**
- 8.0 TEST REPORT APPENDICES**

APPENDIX A: MEASUREMENT INSTRUMENT DETAILS

APPENDIX B: PHOTOGRAPHS

APPENDIX C: OPERATIONAL DESCRIPTION

APPENDIX D: BLOCK DIAGRAM

APPENDIX E: SCHEMATIC

APPENDIX F: FCC ID and IC ID LABELLING

APPENDIX G: USER MANUAL

APPENDIX H: GRAPHS of EMI MEASUREMENTS

Attachment 1: Model Comparisons



This document is issued in accordance with NATA's accreditation requirements. The results of tests, calibration and/or measurements included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing and calibration reports.

This document shall not be reproduced except in full.

**EMI TEST REPORT FOR CERTIFICATION
to
FCC PART 15.209 & RSS-210 / RSS-Gen**

Report No. M110315_Cert_ISO_FFW

Test Sample: ISO FFW Series RFID Readers
Manufacturer: Aleis Pty Ltd

FCC ID: XBH-FFW
IC ID: 8425A-FFW

Equipment Type: Intentional Radiator

Tested for: Aleis Pty Ltd
Address: PO Box 63
Jandowae QLD 4410

Contact: Brian Clayton
Responsible Party: John Finlayson

Test Standards: FCC Part 15 – Radio Frequency Devices (October 2009)
FCC Part 15.209: Radiated Emission Limits, General Requirements.
ANSI C63.4 – 2003

RSS-210 Issue 8 - Low Power Licence-Exempt RadioCommunication
Devices (All Frequency Bands): Category I Equipment
RSS-Gen Issue 3 - General Requirements and Information for the
Certification of RadioCommunication Equipment

Test Dates: 7th and 8th March 2011

Test Engineer: Chieu Huynh

Attestation: I hereby certify that the device(s) described herein were tested as
described in this report and that the data included is that which was
obtained during such testing.



Authorised Signatory: _____
Chieu Huynh
EMC Technologies Pty Ltd



This document is issued in accordance with NATA's accreditation requirements. The results of tests, calibration and/or measurements included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing and calibration reports.

This document shall not be reproduced except in full.

EMI TEST REPORT FOR CERTIFICATION
to
FCC PART 15.209 & RSS-210 / RSS-Gen

1.0 INTRODUCTION

EMI testing was performed on the ISO FFW Series RFID Readers.

The ISO FFW Series is available in different configurations (refer to below):

ISO-FFW6000	This unit is the most basic of the series. No Display or Keypad
ISO-FFW8030	The ISO-FFW8030 unit has all off the main components of the ISO-FFW9060-EXP-CLK tested with no Expansion or Clock boards fitted and the basic 8030/50 keypad
ISO-FFW8030-EXP	The ISO-FFW8030-EXP unit has all off the main components of the ISO-FFW9060-EXP-CLK tested with no Clock board fitted and the basic 8030/50 keypad
ISO-FFW8030-EXP-CLK	The ISO-FFW8030-EXP-CLK unit has all off the main components of the ISO-FFW9060-EXP-CLK tested with Expansion, Clock and the basic 8030/50 keypad
ISO-FFW9060	The ISO-FFW9060 unit has all off the main components of the ISO-FFW9060-EXP-CLK tested with no Expansion or Clock boards and the 9060 keypad
ISO-FFW9060-EXP	The ISO-FFW9060-EXP unit has all off the main components of the ISO-FFW9060-EXP-CLK tested with no Clock board fitted and the 9060 keypad
ISO-FFW9060-EXP-CLK	The ISO-FFW9060-EXP-CLK unit is the most complex of the ISO-FFW Series. This unit was used for the testing.

The intention of this application is to use one FCC ID: XBH-FFW (IC ID: 8425A-FFW) for all the models listed above. The configuration selected for testing was worst case to cover all the different possible parts/combinations which make up any of the other configurations.

Test results and procedures were performed in accordance with the following Federal Communications Commission (FCC) standards/regulations:

47 CFR, Part 15, Subpart C:	Rules for intentional radiators (particularly section 15.209)
Section 15.203:	Antenna requirements
Section 15.205:	Restricted bands of operation
Section 15.207:	Conducted Emission Limits
Section 15.209:	Radiated Emission Limits, General Requirements

The test sample **complied** with the requirements of 47 CFR, Part 15 Subpart C - Section 15.209: Radiated Emission Limits, General Requirements.

The test sample also **complied** with the Industry Canada RSS-210 Issue 8 & RSS-Gen Issue 3.



This document is issued in accordance with NATA's accreditation requirements. The results of tests, calibration and/or measurements included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing and calibration reports.

This document shall not be reproduced except in full.

1.1 Summary of Results

FCC Part 15, Subpart C Clauses	Industry Canada RSS-210 / RSS-Gen Clauses	Test Performed	Result
15.203	7.1.4	Antenna Requirement	Not Applicable
15.205	2.2	Operation in Restricted Band	Complies
15.207	7.2.2	Conducted Emissions	Not Applicable
15.209	2.6 (tables 2 & 3)	Radiated Emissions	Complies

The measurement procedure used was in accordance with ANSI C63.4-2003. The instrumentation conformed to the requirements of ANSI C63.2-1996.

1.2 EUT – Voltage Power Conditions

Testing was performed at a voltage of 12VDC

1.3 Modifications

No modifications were required.

2.0 GENERAL INFORMATION

(Information supplied by the Client)

2.1 Product Details

Test Sample:	ISO FFW Series RFID Readers
Part Number:	ISO-FFW9162-EXP-CLK
Transmit Frequency:	134 kHz
Microprocessor Type:	NXP LPC2103 and Renesas H8S/2643
Crystal Frequencies:	17.1776 MHz and 14.7456 MHz
Highest Operating Frequency:	17.1776 MHz and 14.7456 MHz
Real Time Clock:	32.768 kHz
Input Supply:	12 VDC, 1200mA Max

2.2 Operational Description

The ISO FFW Series RFID Readers are used for detecting and recording RFIDs in Livestock and domestic Animals (pets).

2.3 Test Configuration

The EUT is operating in both HDX and FDX modes. Unit is continuously transmitting for the testing. EUT has option EXP9000 board with 5M cable on the R-NET and a 20m RS232 serial cable. Refer to EMCT test report: M110315_FCC (FCC Declaration of Conformity).

2.4 Test Procedure

Emissions measurements were performed in accordance with the procedures of ANSI C63.4-2003. Radiated emissions tests were performed at a distance of 3 and 10 metres from the EUT.



Accreditation No. 5292

This document is issued in accordance with NATA's accreditation requirements. The results of tests, calibration and/or measurements included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing and calibration reports.

This document shall not be reproduced except in full.

2.5 Test Facility

2.5.1 General

EMC Technologies Pty Ltd is listed by the FCC as a test laboratory able to perform compliance testing for the public. EMC Technologies is listed as an FCC part 47CFR2.948 test lab and may perform the testing required under Parts 15 and 18 – **FCC Registration Number 90560**

EMC Technologies Pty Ltd has also been accredited as a Conformity Assessment Body (CAB) by Australian Communications and Media Authority (ACMA) under the APECTEL MRA and is designated to perform compliance testing on equipment subject to Declaration of Conformity (Doc) and Certification under Parts 15 & 18 of the FCC Commission's rules – **Registration Number 494713 & Designation number AU0001**.

EMC Technologies has also been accepted by Industry Canada for the performance of radiated measurements in accordance with RSS 212, Issue 1 (Provisional) - **Industry Canada number 3569B**.

Measurements were performed at EMC Technologies' laboratory in Keilor Park, Victoria Australia.

2.5.2 NATA Accreditation

EMC Technologies is accredited in Australia to test to the following standards by the National Association of Testing Authorities (NATA).

"FCC Part 15 unintentional and intentional emitters in the frequency range 9kHz to 18 GHz excluding TV receivers (15.117 and 15.119), TV interface devices (15.115), cable ready consumer electronic equipment (15.118) and cable locating equipment (15.213).

The current full scope of accreditation can be found on the NATA website: www.nata.asn.au It also includes a large number of emissions, immunity, SAR, EMR and Safety standards.

NATA is the Australian national laboratory accreditation body and has accredited EMC Technologies to operate to the IEC/ISO17025 requirements. A major requirement for accreditation is the assessment of the company and its personnel as being technically competent in testing to the standards. This requires fully documented test procedures, continued calibration of all equipment to the National Standard at the National Measurements Institute (NMI) and an internal quality system to ISO 9002. NATA has mutual recognition agreements with the National Voluntary Laboratory Accreditation Program (NVLAP) and the American Association for Laboratory Accreditation (A²LA).

2.6 Test Equipment Calibration

All measurement instrumentation and transducers were calibrated in accordance with the applicable standards by an independent NATA registered laboratory such as Agilent Technologies (Australia) Pty Ltd or the National Measurement Institute (NMI). All equipment calibration is traceable to Australia national standards at the National Measurements Institute. The reference antenna calibration was performed by NMI and the working antennas (active loop, biconical and log-periodic) calibrated by the EMC Technologies. The complete list of test equipment used for the measurements, including calibration dates and traceability is contained in Appendix A



Accreditation No. 5292

This document is issued in accordance with NATA's accreditation requirements. The results of tests, calibration and/or measurements included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing and calibration reports.

This document shall not be reproduced except in full.

3.0 CONDUCTED EMISSION MEASUREMENTS

Not applicable, as EUT is battery powered.

4.0 RADIATED EMISSION MEASUREMENTS

4.1 Test Procedure

Testing was performed in accordance with the requirements of FCC Part 15.209.

Radiated emission measurements were performed to the limits as per section 15.209.

The EUT was set up on the table top (placed on turntable) of total height 80 cm above the ground plane, and operated as described in section 2 of this report. The EMI Receiver was operated under software control via the PC Controller through the IEEE.488 Interface Bus Card Adaptor. The test frequency range was sub-divided into smaller bands with sufficient frequency resolution to permit reliable display and identification of possible EMI peaks while also permitting fast frequency scan times. A calibrated loop antenna was used for measurements between 0.009 MHz to 30 MHz. A calibrated Biconical antenna was used for measurements between 30 MHz to 200 MHz and a calibrated Logperiodic antenna used for measurements between 200 MHz to 1000 MHz.

The following bandwidth settings were used:

RBW = 200 Hz and VBW = 1 kHz for frequency band 9 kHz – 150 kHz

RBW = 9 kHz and VBW = 30 kHz for frequency band 150 kHz – 30 MHz

RBW = 120 kHz and VBW = 300 kHz for frequency band 30 MHz – 1000 MHz

RBW = 200 Hz and VBW = 10 Hz for frequency bands 9 kHz – 90 kHz and 110 kHz – 490 kHz

The receiver bandwidth was set to 6 dB.

The EUT was slowly rotated with the Peak Detector set to Max-Hold. This was performed for two antenna heights. When an emission was located, it was positively identified and its maximum level found by rotating the automated turntable, and by varying the antenna height. Each significant peak was investigated with the Peak/Average Detectors. The measurement data for each frequency range was corrected for cable losses, antenna factors and preamplifier gain. This process was performed for both horizontal and vertical antenna polarisations.

4.2 Plotting of Measurement Data for Radiated Emissions

The stored measurement data was combined to form a single graph which comprised of all the frequency sub-ranges over the range 0.009-30 MHz and 30-1000 MHz. The accumulated EMI (EUT ON) was plotted as the Red trace.

The highest recorded EMI signals are shown on the Peaks List on the bottom right side of the graph. For radiated EMI, each numbered peak is listed as a frequency, peak field strength, quasi-peak field strength and the margin relative to the limit in dB. A negative margin is the deviation of the recorded value below the limit.

At times, the quasi peak level may appear to be higher than the peak level. This happens because the individual peak is further maximised with the QP detector, after the peak trace is recorded. This will be apparent when the peaks list at the foot of the graphs shows the quasi peak level.



Accreditation No. 5292

This document is issued in accordance with NATA's accreditation requirements. The results of tests, calibration and/or measurements included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing and calibration reports.

This document shall not be reproduced except in full.

4.3 Calculation of field strength

The field strength was calculated automatically by the software using all the pre-stored calibration data. The method of calculation is shown below:

$$E = V + AF - G + L \text{ Where:}$$

E = Radiated Field Strength in dB μ V/m.

V = EMI Receiver Voltage in dB μ V. (measured value)

AF = Antenna Factor in dB(m⁻¹). (stored as a data array)

G = Preamplifier Gain in dB. (stored as a data array)

L = Cable loss in dB. (stored as a data array of Insertion Loss versus frequency)

- **Example Field Strength Calculation**

Assuming a receiver reading of 34.0 dB μ V is obtained at 90 MHz, the Antenna Factor at that frequency is 9.2 dB. The cable loss is 1.9 dB while the preamplifier gain is 20 dB. The resulting Field Strength is therefore as follows:

$$34.0 + 9.2 + 1.9 - 20 = 25.1 \text{ dB}\mu\text{V/m}$$

4.4 Results

Testing was performed in accordance with the requirements of FCC Part 15.209 and RSS-210.

4.4.1 Frequency Band: 0.009 - 30 MHz (Fundamental and Spurious)

Testing was performed at a distance of 10 metres and also investigated at 3 metres.

Average and Quasi-Peak detectors were used in the frequency bands 9-90 kHz & 110-490 kHz. No significant differences in the field strength levels were measured.

The fundamental limit at 134 kHz is 25.1 dB μ V at 300m. However, measurement was performed at a distance of 10m. Therefore, the calculated limit at 10m is 84.1 dB μ V.

Frequency MHz	Test Distance (m)	Measured Level dB μ V/m	LIMIT dB μ V/m	Δ \pm dB
0.134	10	84.0	84.1	-0.1
15.30	10	40.2	49.0	-8.8
0.268	10	57.4	78.1	-20.7

The field strength emission complied with FCC limits by a margin of 0.1 dB at 10 m distance. Refer to Appendix H, graph 1.

Harmonics and spurious emissions were found to comply with FCC limits by a margin of 8.8 dB. Refer to Appendix H, graph 1.



Accreditation No. 5292

This document is issued in accordance with NATA's accreditation requirements. The results of tests, calibration and/or measurements included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing and calibration reports.

This document shall not be reproduced except in full.

4.4.2 Frequency Band: 30 - 1000 MHz

Testing was performed at a distance of 3 metres.

Frequency MHz	Polarisation	Measured QP Level dB μ V/m	QP LIMIT dB μ V/m	Δ QP \pm dB
58.97	Vertical	32.3	40.0	-7.7
768.01	Vertical	37.0	46.0	-9.0
768.0	Horizontal	36.8	46.0	-9.2
88.44	Vertical	33.8	43.5	-9.7
88.44	Horizontal	33.4	43.5	-10.1
81.0	Vertical	26.5	40.0	-13.5

The worst case radiated EMI occurred at 58.97 MHz and complied with the FCC 15.209 Class B quasi peak limit by a margin of 7.7 dB. Refer to Appendix H, graphs 2 and 3.

5.0 ANTENNA REQUIREMENT

Testing to the requirements of FCC Part 15.203 was not applicable as this intentional radiator was designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

6.0 COMPLIANCE STATEMENT

The ISO FFW Series RFID Readers, tested on behalf of Aleis Pty Ltd, **complied** with the requirements of 47 CFR, Part 15 Subpart C - Rules for Radio Frequency Devices (intentional radiators), Section 15.209: Radiated Emission Limits, General Requirements.

The test sample also **complied** with the Industry Canada RSS-210 Issue 8 & RSS-Gen Issue 3.

Results were as follows:

FCC Part 15, Subpart C Clauses	Industry Canada RSS-210 / RSS-Gen Clauses	Test Performed	Result
15.203	7.1.4	Antenna Requirement	Not Applicable
15.205	2.2	Operation in Restricted Band	Complies
15.207	7.2.2	Conducted Emissions	Not Applicable
15.209	2.6 (tables 2 & 3)	Radiated Emissions	Complies



Accreditation No. 5292

This document is issued in accordance with NATA's accreditation requirements. The results of tests, calibration and/or measurements included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing and calibration reports.

This document shall not be reproduced except in full.

7.0 UNCERTAINTIES

EMC Technologies has evaluated the equipment and the methods used to perform the emissions testing. The estimated measurement uncertainties for emissions tests shown within this report are as follows:

Radiated Emissions:	9 kHz to 30 MHz	±4.1 dB
	30 MHz to 300 MHz	±5.1 dB
	300 MHz to 1000 MHz	±4.7 dB

The above expanded uncertainties are based on standard uncertainties multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95%.

8.0 TEST REPORT APPENDICES

- APPENDIX A: MEASUREMENT INSTRUMENT DETAILS**
- APPENDIX B: PHOTOGRAPHS**
- APPENDIX C: OPERATIONAL DESCRIPTION**
- APPENDIX D: BLOCK DIAGRAM**
- APPENDIX E: SCHEMATIC**
- APPENDIX F: FCC ID and IC ID LABELLING**
- APPENDIX G: USER MANUAL**
- APPENDIX H: GRAPHS of EMI MEASUREMENTS**

Attachment 1: Model Comparisons



This document is issued in accordance with NATA's accreditation requirements. The results of tests, calibration and/or measurements included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing and calibration reports.

This document shall not be reproduced except in full.