



Test Report

Product Name : Wireless Temperature Sensor
Model No. : WTS-110
FCC ID. : XBTWTS-110

Applicant : United Integrated Services Co., Ltd
Address : 5F, No.3, LANE 7 PAOKAO ROAD HSINTIEN 23144,
TAIPEI HSIEN, TAIWAN

Date of Receipt : Jan. 10, 2009
Issued Date : Mar. 20, 2009
Report No. : 091163R-RFUSP07V01
Version : V1.0

The Test Results relate only to the samples tested.
The test report shall not be reproduced except in full without the written approval of Quietek Corporation.
This report must not be used to claim product endorsement by NVLAP any agency of the U.S. Government

Test Report Certification

Issued Date: Mar. 20, 2009

Report No. : 091163R-RFUSP07V01



Product Name : Wireless Temperature Sensor

Applicant : United Integrated Services Co., Ltd

Address : 5F, No.3, LANE 7 PAOKAO ROAD HSINTIEN 23144, TAIPEI HSIEN,
TAIWAN

Manufacturer : United Integrated Services Co., Ltd

Model No. : WTS-110

FCC ID. : XBTWTS-110

Rated Voltage : DC 3V

Working Voltage : DC 3V

Trade Name : UIS

Applicable Standard : FCC CFR Title 47 Part 15 Subpart C: 2008
ANSI C63.4: 2003



Test Result : Complied

The Test Results relate only to the samples tested.

The test report shall not be reproduced except in full without the written approval of Quietek Corporation.

This report must not be used to claim product endorsement by NVLAP any agency of the U.S. Government

Documented By : Anita Chou
(Senior Engineering Adm. Specialist / Anita Chou)



Tested By : Dino Chen
(Engineer / Dino Chen)

Approved By : Vincent Lin
(Manager / Vincent Lin)



TABLE OF CONTENTS

Description	Page
1. GENERAL INFORMATION	4
1.1. EUT Description.....	4
1.2. Operation Description	6
1.3. Tested System Details	7
1.4. Configuration of Test System.....	7
1.5. EUT Exercise Software	7
1.6. Test Facility	8
2. Conducted Emission.....	9
2.1. Test Equipment.....	9
2.2. Test Setup	9
2.3. Limits.....	10
2.4. Test Procedure	10
2.5. Uncertainty	10
2.6. Test Result of Conducted Emission.....	11
3. Radiated Emission.....	12
3.1. Test Equipment.....	12
3.2. Test Setup	13
3.3. Limits.....	14
3.4. Test Procedure	15
3.5. Uncertainty	15
3.6. Test Result of Radiated Emission.....	16
4. Band Edge	21
4.1. Test Equipment.....	21
4.2. Test Setup	22
4.3. Limit	22
4.4. Test Procedure	23
4.5. Uncertainty	23
4.6. Test Result of Band Edge	24
5. Duty Cycle	28
5.1. Test Equipment.....	28
5.2. Test Setup	28
5.3. Uncertainty	28
5.4. Test Result of Duty Cycle	29
6. EMI Reduction Method During Compliance Testing.....	31

1. GENERAL INFORMATION

1.1. EUT Description

Product Name	Wireless Temperature Sensor
Trade Name	UIS
FCC ID.	XBTWTS-110
Model No.	WTS-110
Frequency Range	2401 – 2481MHz
Type of Modulation	GFSK
Number of Channels	81
Channel Control	Auto
Antenna Type	Printed on PCB
Antenna Gain	Refer to the table “Antenna List”

Antenna List

No.	Manufacturer	Part No.	Peak Gain
1	UIS	N/A	-5.12 dBi for 2.4 GHz

Center Frequency of Each Channel:

Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
Channel 1:	2401 MHz	Channel 22:	2422 MHz	Channel 43:	2443 MHz	Channel 64:	2464 MHz
Channel 2:	2402 MHz	Channel 23:	2423 MHz	Channel 44:	2444 MHz	Channel 65:	2465 MHz
Channel 3:	2403 MHz	Channel 24:	2424 MHz	Channel 45:	2445 MHz	Channel 66:	2466 MHz
Channel 4:	2404 MHz	Channel 25:	2425 MHz	Channel 46:	2446 MHz	Channel 67:	2467 MHz
Channel 5:	2405 MHz	Channel 26:	2426 MHz	Channel 47:	2447 MHz	Channel 68:	2468 MHz
Channel 6:	2406 MHz	Channel 27:	2427 MHz	Channel 48:	2448 MHz	Channel 69:	2469 MHz
Channel 7:	2407 MHz	Channel 28:	2428 MHz	Channel 49:	2449 MHz	Channel 70:	2470 MHz
Channel 8:	2408 MHz	Channel 29:	2429 MHz	Channel 50:	2450 MHz	Channel 71:	2471 MHz
Channel 9:	2409 MHz	Channel 30:	2430 MHz	Channel 51:	2451 MHz	Channel 72:	2472 MHz
Channel 10:	2410 MHz	Channel 31:	2431 MHz	Channel 52:	2452 MHz	Channel 73:	2473 MHz
Channel 11:	2411 MHz	Channel 32:	2432 MHz	Channel 53:	2453 MHz	Channel 74:	2474 MHz
Channel 12:	2412 MHz	Channel 33:	2433 MHz	Channel 54:	2454 MHz	Channel 75:	2475 MHz
Channel 13:	2413 MHz	Channel 34:	2434 MHz	Channel 55:	2455 MHz	Channel 76:	2476 MHz
Channel 14:	2414 MHz	Channel 35:	2435 MHz	Channel 56:	2456 MHz	Channel 77:	2477 MHz
Channel 15:	2415 MHz	Channel 36:	2436 MHz	Channel 57:	2457 MHz	Channel 78:	2478 MHz
Channel 16:	2416 MHz	Channel 37:	2437 MHz	Channel 58:	2458 MHz	Channel 79:	2479 MHz
Channel 17:	2417 MHz	Channel 38:	2438 MHz	Channel 59:	2459 MHz	Channel 80:	2480 MHz
Channel 18:	2418 MHz	Channel 39:	2439 MHz	Channel 60:	2460 MHz	Channel 81:	2481 MHz
Channel 19:	2419 MHz	Channel 40:	2440 MHz	Channel 61:	2461 MHz		
Channel 20:	2420 MHz	Channel 41:	2441 MHz	Channel 62:	2462 MHz		
Channel 21:	2421 MHz	Channel 42:	2442 MHz	Channel 63:	2463 MHz		

Note:

1. The EUT is a Wireless Temperature Sensor with a built-in 2.4GHz transceiver
2. These tests are conducted on a sample of the equipment for the purpose of demonstrating compliance with Part 15 Subpart C Paragraph 15.249.
3. Regarding to the operation frequency, the lowest, middle and highest frequency are selected to perform the test.
4. The radiation measurements are performed in X, Y, Z axis positioning. Only the worst case is shown in the report.

EMI Test Mode	Mode 1: Transmitter
---------------	---------------------

1.2. Operation Description

The EUT is a Wireless Temperature Sensor with a built-in 2.4GHz transceiver. The EUT operation frequency is 2.401GHz-2.481GHz. The signals modulated GFSK are transmitted from the Printed Antenna of the EUT.

1.3. Tested System Details

The types for all equipment, plus descriptions of all cables used in the tested system (including inserted cards) are:

Product	Manufacturer	Model No.	Serial No.	Power Cord
N/A	N/A	N/A	N/A	N/A

Signal Cable Type	Signal cable Description
N/A	N/A

1.4. Configuration of Test System



1.5. EUT Exercise Software

- (1) Setup the EUT as shown in section 1.4
- (2) Provides the power source, start continuous transmit
- (3) Verify that the EUT works correctly.

1.6. Test Facility

Ambient conditions in the laboratory:

Items	Required (IEC 68-1)	Actual
Temperature (°C)	15-35	20-35
Humidity (%RH)	25-75	50-65
Barometric pressure (mbar)	860-1060	950-1000

The related certificate for our laboratories about the test site and management system can be downloaded from Quietek Corporation’s Web Site : <http://tw.quietek.com/modules/myalbum/>
 The address and introduction of Quietek Corporation’s laboratories can be founded in our Web site : <http://www.quietek.com/>

Site Description: File on
 Federal Communications Commission
 FCC Engineering Laboratory
 7435 Oakland Mills Road
 Columbia, MD 21046
 Registration Number: 92195



Accreditation on NVLAP
 NVLAP Lab Code: 200533-0



Site Name: Quietek Corporation
 Site Address: No. 5-22, Ruei-Shu Valley, Ruei-Ping Tsuen,
 Lin-Kou Shiang, Taipei,
 Taiwan, R.O.C.
 TEL: 886-2-8601-3788 / FAX : 886-2-8601-3789
 E-Mail : service@quietek.com

FCC Accreditation Number: TW1014



2. Conducted Emission


2.1. Test Equipment

The following test equipment are used during the conducted emission test:

Item	Instrument	Manufacturer	Type No./Serial No	Last Cal.	Remark
1	Test Receiver	R & S	ESCS 30/825442/17	May, 2008	
2	L.I.S.N.	R & S	ESH3-Z5/825016/6	May, 2008	EUT
3	L.I.S.N.	Kyoritsu	KNW-407/8-1420-3	May, 2008	Peripherals
4	Pulse Limiter	R & S	ESH3-Z2	May, 2008	
5	No.1 Shielded Room			N/A	

Note: All instruments are calibrated every one year.

2.2. Test Setup



2.3. Limits

FCC Part 15 Subpart C Paragraph 15.207 (dBuV) Limit		
Frequency MHz	Limits	
	QP	AVG
0.15 - 0.50	66-56	56-46
0.50-5.0	56	46
5.0 - 30	60	50

2.4. Test Procedure

The EUT and simulators are connected to the main power through a line impedance stabilization network (L.I.S.N.). This provides a 50 ohm /50uH coupling impedance for the measuring equipment. The peripheral devices are also connected to the main power through a LISN that provides a 50ohm /50uH coupling impedance with 50ohm termination. (Please refers to the block diagram of the test setup and photographs.)

Both sides of A.C. line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.4: 2003 on conducted measurement.

Conducted emissions were invested over the frequency range from 0.15MHz to 30MHz using a receiver bandwidth of 9kHz.

2.5. Uncertainty

± 2.26 dB

2.6. Test Result of Conducted Emission

Owing to the DC operation of EUT, this test item is not performed

3. Radiated Emission

3.1. Test Equipment


The following test equipment are used during the radiated emission test:

Test Site		Equipment	Manufacturer	Model No./Serial No.	Last Cal.
<input type="checkbox"/> Site # 1		Test Receiver	R & S	ESVS 10 / 834468/003	May, 2008
		Spectrum Analyzer	Advantest	R3162/ 00803480	May, 2008
		Pre-Amplifier	Advantest	BB525C/ 3307A01812	May, 2008
		Bilog Antenna	SCHAFFNER	CBL6112B / 2697	Sep., 2008
<input type="checkbox"/> Site # 2		Test Receiver	R & S	ESCS 30 / 836858 / 022	May, 2008
		Spectrum Analyzer	Advantest	R3162 / 100803466	May, 2008
		Pre-Amplifier	Advantest	BB525C/3307A01814	May, 2008
		Bilog Antenna	SCHAFFNER	CBL6112B / 2705	May, 2008
		Horn Antenna	ETS	3115 / 0005-6160	Sep., 2008
		Pre-Amplifier	QTK	QTK-AMP-01/ 0001	May, 2008
<input checked="" type="checkbox"/> Site # 3	X	Test Receiver	R & S	ESI 26 / 838786/004	May, 2008
	X	Spectrum Analyzer	Agilent	E4407B / US39440758	May, 2008
	X	Bilog Antenna	SCHAFFNER	CBL6112B / 2697	May, 2008
	X	Horn Antenna	Schwarzbeck	BBHA9120D / 305, 306	July, 2008
	X	Horn Antenna	Schwarzbeck	BBHA9170 / 208, 209	July, 2008
	X	Pre-Amplifier	QTK	QTK-AMP-01 / 0001	July, 2008
	X	Pre-Amplifier	QTK	QTK-AMP-03 / 0003	May, 2008
	X	Pre-Amplifier	HP	8449B / 3008A01123	July, 2008


- Note:
1. All equipments are calibrated every one year.
 2. Test equipments marked by "X" are used to measure the final test results.

3.2. Test Setup

Below 1GHz



Above 1GHz



3.3. Limits

➤ Fundamental and Harmonics Emission Limits

FCC Part 15 Subpart C Paragraph 15.249 Limits				
Frequency MHz	Field Strength of Fundamental		Field Strength of Harmonics	
	(mV/m @3m)	(dBuV/m @3m)	(uV/m @3m)	(dBuV/m @3m)
902-928	50	94	500	54
2400-2483.5	50	94	500	54
5725-5875	50	94	500	54

- Remarks :
1. RF Voltage (dBuV/m) = 20 log RF Voltage (uV/m)
 2. Distance refers to the distance in meters between the measuring instrument antenna and the closed point of any part of the device or system.

➤ General Radiated Emission Limits

Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50dB below the level of the fundamental or to the general radiated emission limits in paragraph 15.209, whichever is the lesser attenuation.

FCC Part 15 Subpart C Paragraph 15.209 Limits		
Frequency MHz	uV/m @3m	dBuV/m@3m
30-88	100	40
88-216	150	43.5
216-960	200	46
Above 960	500	54

- Remarks :
1. RF Voltage (dBuV/m) = 20 log RF Voltage (uV/m)
 2. In the Above Table, the tighter limit applies at the band edges.
 3. Distance refers to the distance in meters between the measuring instrument antenna and the closed point of any part of the device or system.

3.4. Test Procedure

The EUT and its simulators are placed on a turn table which is 0.8 meter above ground. The turn table can rotate 360 degrees to determine the position of the maximum emission level. The EUT was positioned such that the distance from antenna to the EUT was 3 meters.

The antenna can move up and down between 1 meter and 4 meters to find out the maximum emission level.

Both horizontal and vertical polarization of the antenna are set on measurement. In order to find the maximum emission, all of the interface cables must be manipulated according to ANSI C63.4: 2003 on radiated measurement.

The resolution bandwidth below 1GHz setting on the field strength meter is 120 kHz and above 1GHz is 1MHz.

Radiated emission measurements below 1GHz are made using broadband Bilog antenna and above 1GHz are made using Horn Antennas.

The measurement is divided into the Preliminary Measurement and the Final Measurement.

The suspected frequencies are searched for in Preliminary Measurement with the measurement antenna kept pointed at the source of the emission both in azimuth and elevation, with the polarization of the antenna oriented for maximum response. The antenna is pointed at an angle towards the source of the emission, and the EUT is rotated in both height and polarization to maximize the measured emission. The emission is kept within the illumination area of the 3 dB bandwidth of the antenna.

The worst radiated emission is measured on the Final Measurement.

The measurement frequency range from 30MHz - 10th Harmonic of fundamental was investigated.

3.5. Uncertainty

± 3.9 dB above 1GHz

± 3.8 dB below 1GHz

3.6. Test Result of Radiated Emission

Product : Wireless Temperature Sensor
 Test Item : Fundamental Radiated Emission
 Test Site : No.3 OATS
 Test Mode : Mode 1: Transmitter (2401,2441,2481 MHz)

Peak Detector

Frequency MHz	Correct Factor dB	Reading Level dBuV	Measurement Level dBuV/m	Margin dB	Limit dBuV/m
Horizontal					
2401.000	-6.727	83.190	76.463	-37.537	114.000
2441.000	-6.584	82.160	75.576	-38.424	114.000
2481.000	-6.471	79.770	73.298	-40.702	114.000
Vertical					
2401.000	-6.727	82.250	75.523	-38.477	114.000
2441.000	-6.584	83.470	76.886	-37.114	114.000
2481.000	-6.471	83.310	76.838	-37.162	114.000

Note:

1. Measurement Level = Reading Level + Correct Factor.
Correct Factor = Antenna Factor + Cable Loss – PreAMP.

Average Detector:

Frequency MHz	Peak Measurement dBuV/m	Duty Cycle Factor dB	Measurement Level dBuV/m	Margin dB	Limit dBuV/m
Horizontal					
2401.000	--	--	--	--	94.000
2441.000	--	--	--	--	94.000
2481.000	--	--	--	--	94.000
Vertical					
2401.000	--	--	--	--	94.000
2441.000	--	--	--	--	94.000
2481.000	--	--	--	--	94.000

Note:

1. AVG Measurement=Peak Measurement + Duty Cycle
2. The Duty Cycle is refer to section 5.
3. If Duty Cycle is smaller than -20dB,based on FCC part15 the duty cycle correction factor is -20dB for calculating average emission.

Product : Wireless Temperature Sensor
 Test Item : Harmonic Radiated Emission Data
 Test Site : No.3 OATS
 Test Mode : Mode 1: Transmitter (2401 MHz)

Peak Detector:

Frequency MHz	Correct Factor dB	Reading Level dBuV	Measurement Level dBuV/m	Margin dB	Peak Limit dBuV/m
Horizontal					
4802.000	-0.202	56.480	56.278	-17.722	74.000
7203.000	3.318	42.850	46.168	-27.832	74.000
9604.000	5.689	41.630	47.319	-26.681	74.000
Vertical					
4802.000	-0.202	57.750	57.548	-16.452	74.000
7203.000	3.318	42.870	46.188	-27.812	74.000
9604.000	5.689	41.210	46.899	-27.101	74.000

Note:

1. All Readings below 1GHz are Quasi-Peak, above are performed with peak and/or average measurements as necessary.
2. Receiver setting (Peak Detector) : RBW:1MHz; VBW:1MHz; Span:100MHz °
3. Emission Level = Reading Level + Correct Factor.
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

Average Detector:

Frequency MHz	Peak Measurement dBuV/m	Duty Cycle Factor dB	Measurement Level dBuV/m	Margin dB	Limit dBuV/m
Horizontal					
4802.000	56.278	-20.000	36.278	-17.722	54.000
Vertical					
4802.000	57.548	-20.000	37.548	-16.452	54.000

Note:

1. AVG Measurement=Peak Measurement + Duty Cycle
2. The Duty Cycle is refer to section 5.
3. If Duty Cycle is smaller than -20dB,based on FCC part15 the duty cycle correction factor is -20dB for calculating average emission.
4. The average measurement was not performed when the peak measured data under the limit of average detection. If the readings given are average, peak measurement should also be supplied.

Product : Wireless Temperature Sensor
 Test Item : Harmonic Radiated Emission Data
 Test Site : No.3 OATS
 Test Mode : Mode 1: Transmitter (2441 MHz)

Peak Detector:

Frequency MHz	Correct Factor dB	Reading Level dBuV	Measurement Level dBuV/m	Margin dB	Peak Limit dBuV/m
Horizontal					
4882.000	-0.276	56.020	55.744	-18.256	74.000
7323.000	3.330	43.330	46.659	-27.341	74.000
9764.000	6.262	40.480	46.743	-27.257	74.000
Vertical					
4882.000	-0.276	58.190	57.914	-16.086	74.000
7323.000	3.330	41.770	45.099	-28.901	74.000
9764.000	6.262	41.080	47.343	-26.657	74.000

Note:

1. All Readings below 1GHz are Quasi-Peak, above are performed with peak and/or average measurements as necessary.
2. Receiver setting (Peak Detector) : RBW:1MHz; VBW:1MHz; Span:100MHz °
3. Emission Level = Reading Level + Correct Factor.
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

Average Detector:

Frequency MHz	Peak Measurement dBuV/m	Duty Cycle Factor dB	Measurement Level dBuV/m	Margin dB	Limit dBuV/m
Horizontal					
4882.000	55.744	-20.000	35.744	-18.256	54.000
Vertical					
4882.000	57.914	-20.000	37.914	-16.086	54.000

Note:

1. AVG Measurement=Peak Measurement + Duty Cycle
2. The Duty Cycle is refer to section 5.
3. If Duty Cycle is smaller than -20dB, based on FCC part15 the duty cycle correction factor is -20dB for calculating average emission.
4. The average measurement was not performed when the peak measured data under the limit of average detection. If the readings given are average, peak measurement should also be supplied.

Product : Wireless Temperature Sensor
 Test Item : Harmonic Radiated Emission Data
 Test Site : No.3 OATS
 Test Mode : Mode 1: Transmitter (2481MHz)

Peak Detector:

Frequency MHz	Correct Factor dB	Reading Level dBuV	Measurement Level dBuV/m	Margin dB	Peak Limit dBuV/m
Horizontal					
4962.000	0.618	55.630	56.248	-17.752	74.000
7443.000	3.939	43.120	47.060	-26.940	74.000
9924.000	6.461	40.050	46.510	-27.490	74.000
Vertical					
4962.000	0.618	59.020	59.638	-14.362	74.000
7443.000	3.939	42.770	46.710	-27.290	74.000
9924.000	6.461	40.130	46.590	-27.410	74.000

Note:

1. All Readings below 1GHz are Quasi-Peak, above are performed with peak and/or average measurements as necessary.
2. Receiver setting (Peak Detector) : RBW:1MHz; VBW:1MHz; Span:100MHz °
3. Emission Level = Reading Level + Correct Factor.
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

Average Detector:

Frequency MHz	Peak Measurement dBuV/m	Duty Cycle Factor dB	Measurement Level dBuV/m	Margin dB	Limit dBuV/m
Horizontal					
4962.000	56.248	-20.000	36.248	-17.752	54.000
Vertical					
4962.000	59.638	-20.000	39.638	-14.362	54.000

Note:

1. AVG Measurement=Peak Measurement + Duty Cycle
2. The Duty Cycle is refer to section 5.
3. If Duty Cycle is smaller than -20dB,based on FCC part15 the duty cycle correction factor is -20dB for calculating average emission.
4. The average measurement was not performed when the peak measured data under the limit of average detection. If the readings given are average, peak measurement should also be supplied.

Product : Wireless Temperature Sensor
 Test Item : General Radiated Emission Data
 Test Site : No.3 OATS
 Test Mode : Mode 1: Transmitter (2441 MHz)

Frequency	Correct	Reading	Measurement	Margin	Limit
	Factor	Level	Level		
MHz	dB	dBuV	dBuV/m	dB	dBuV/m
Horizontal					
363.680	-1.904	33.323	31.419	-14.581	46.000
544.100	2.992	22.811	25.803	-20.197	46.000
629.460	1.079	25.549	26.628	-19.372	46.000
718.700	3.052	21.535	24.587	-21.413	46.000
809.880	4.730	22.099	26.829	-19.171	46.000
974.780	6.141	21.499	27.640	-26.360	54.000
Vertical					
214.300	-8.494	28.991	20.497	-23.003	43.500
365.620	-2.667	32.357	29.690	-16.310	46.000
544.100	-1.208	22.201	20.993	-25.007	46.000
695.420	1.429	23.229	24.658	-21.342	46.000
840.920	2.570	20.957	23.527	-22.473	46.000
970.900	6.782	21.052	27.834	-26.166	54.000

Note:

1. All Readings below 1GHz are Quasi-Peak, above are performed with peak and/or average measurements as necessary.
2. "■" means the worst emission level.
3. Measurement Level = Reading Level + Correct Factor

4. Band Edge

4.1. Test Equipment

The following test equipments are used during the band edge tests:

	Equipment	Manufacturer	Model No./Serial No.	Last Cal.
X	Test Receiver	R & S	ESI 26 / 838786/004	May, 2008
X	Spectrum Analyzer	Agilent	E4407B / US39440758	May, 2008
X	Bilog Antenna	SCHAFFNER	CBL6112B / 2697	May, 2008
X	Horn Antenna	Schwarzbeck	BBHA9120D / 305, 306	July, 2008
X	Horn Antenna	Schwarzbeck	BBHA9170 / 208, 209	July, 2008
X	Pre-Amplifier	QTK	QTK-AMP-01 / 0001	July, 2008
X	Pre-Amplifier	QTK	QTK-AMP-03 / 0003	May, 2008
X	Pre-Amplifier	HP	8449B / 3008A01123	July, 2008


OATS No.3

- Note:
1. All equipments are calibrated every one year.
 2. The test equipments marked by “X” are used to measure the final test results.

4.2. Test Setup

RF Radiated Measurement:

Above 1GHz



4.3. Limit

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 50 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 15.205(c)).

4.4. Test Procedure

The EUT and its simulators are placed on a turn table which is 0.8 meter above ground. The turn table can rotate 360 degrees to determine the position of the maximum emission level. The EUT was positioned such that the distance from antenna to the EUT was 3 meters.

The antenna can move up and down between 1 meter and 4 meters to find out the maximum emission level.

Both horizontal and vertical polarization of the antenna are set on measurement. In order to find the maximum emission, all of the interface cables must be manipulated according to ANSI C63.4:2003 on radiated measurement.

The bandwidth below 1GHz setting on the field strength meter (R&S Test Receiver ESCS 30)is 120 kHz, above 1GHz are 1 MHz.

4.5. Uncertainty

Conducted is ± 1.27 dB

Radiated is ± 3.9 dB


4.6. Test Result of Band Edge

Product : Wireless Temperature Sensor
 Test Item : Band Edge Data
 Test Site : No.3 OATS
 Test Mode : Mode 1: Transmitter (2401 MHz)

RF Radiated Measurement (Horizontal):

Channel No.	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBuV)	Emission Level (dBuV/m)	Peak Limit (dBuV/m)	Result
01(Peak)	2390.000	-2.378	46.647	44.270	74.000	Pass

Figure Channel 01: Horizontal (Peak)



Note:

1. All readings above 1GHz are performed with peak and/or average measurements as necessary.
2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
3. “ * ”, means this data is the worst emission level.
4. Measurement Level = Reading Level + Correct Factor.

Average Detector:

Frequency	Peak Measurement	Duty Cycle Factor	Measurement Level	Margin	Limit	Result
MHz	dBuV/m	dB	dBuV/m	dB	dBuV/m	Pass

Horizontal

--	--	--	--	--	54.000	Pass
----	----	----	----	----	--------	------

Note:


1. AVG Measurement=Peak Measurement + Duty Cycle
2. The Duty Cycle is refer to section 5.
3. If Duty Cycle is smaller than -20dB,based on FCC part15 the duty cycle correction factor is -20dB for calculating average emission.
4. The average measurement was not performed when the peak measured data under the limit of average detection. If the readings given are average, peak measurement should also be supplied.

Product : Wireless Temperature Sensor
 Test Item : Band Edge Data
 Test Site : No.3 OATS
 Test Mode : Mode 1: Transmitter (2401 MHz)

RF Radiated Measurement (Vertical):

Channel No.	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBuV)	Emission Level (dBuV/m)	Peak Limit (dBuV/m)	Result
01(Peak)	2390.000	-2.378	41.433	39.056	74.000	Pass

Figure Channel 01: Vertical (Peak)



Note:

1. All readings above 1GHz are performed with peak and/or average measurements as necessary.
2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
3. “ * ”, means this data is the worst emission level.
4. Measurement Level = Reading Level + Correct Factor.

Average Detector:

Frequency	Peak Measurement	Duty Cycle Factor	Measurement Level	Margin	Limit	Result
MHz	dBuV/m	dB	dBuV/m	dB	dBuV/m	Pass
--	--	--	--	--	54.000	Pass

Note:


1. AVG Measurement=Peak Measurement + Duty Cycle
2. The Duty Cycle is refer to section 5.
3. If Duty Cycle is smaller than -20dB,based on FCC part15 the duty cycle correction factor is -20dB for calculating average emission.
4. The average measurement was not performed when the peak measured data under the limit of average detection. If the readings given are average, peak measurement should also be supplied.

Product : Wireless Temperature Sensor
 Test Item : Band Edge Data
 Test Site : No.3 OATS
 Test Mode : Mode 1: Transmitter (2481 MHz)

RF Radiated Measurement (Horizontal):

Channel No.	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBuV)	Emission Level (dBuV/m)	Peak Limit (dBuV/m)	Result
81(Peak)	2483.500	-1.937	64.847	62.910	74.000	Pass

Figure Channel 81: Horizontal(Peak)



Note:

1. All readings above 1GHz are performed with peak and/or average measurements as necessary.
2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
3. “ * ”, means this data is the worst emission level.
4. Measurement Level = Reading Level + Correct Factor.

Average Detector:

Frequency MHz	Peak Measurement dBuV/m	Duty Cycle Factor dB	Measurement Level dBuV/m	Margin dB	Limit dBuV/m	Result Pass
Vertical 2483.500	62.910	-20.000	42.910	-11.090	54.000	Pass

Note:


1. AVG Measurement=Peak Measurement + Duty Cycle
2. The Duty Cycle is refer to section 5.
3. If Duty Cycle is smaller than -20dB, based on FCC part15 the duty cycle correction factor is -20dB for calculating average emission.
4. The average measurement was not performed when the peak measured data under the limit of average detection. If the readings given are average, peak measurement should also be supplied.

Product : Wireless Temperature Sensor
 Test Item : Band Edge Data
 Test Site : No.3 OATS
 Test Mode : Mode 1: Transmitter (2481 MHz)

RF Radiated Measurement (Vertical):

Channel No.	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBUV)	Emission Level (dBUV/m)	Peak Limit (dBUV/m)	Result
81(Peak)	2483.500	-1.937	58.195	56.258	74.000	Pass

Figure Channel 81: Vertical(Peak)



Note:

1. All readings above 1GHz are performed with peak and/or average measurements as necessary.
2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
3. “ * ”, means this data is the worst emission level.
4. Measurement Level = Reading Level + Correct Factor.

Average Detector:

Frequency (MHz)	Peak Measurement (dBUV/m)	Duty Cycle Factor (dB)	Measurement Level (dBUV/m)	Margin (dB)	Limit (dBUV/m)	Result
Vertical						
2483.500	56.258	-20.000	36.258	-17.742	54.000	Pass

Note:

1. AVG Measurement=Peak Measurement + Duty Cycle
2. The Duty Cycle is refer to section 5.
3. If Duty Cycle is smaller than -20dB,based on FCC part15 the duty cycle correction factor is -20dB for calculating average emission.
4. The average measurement was not performed when the peak measured data under the limit of average detection. If the readings given are average, peak measurement should also be supplied.

5. Duty Cycle


5.1. Test Equipment

The following test equipments are used during the band edge tests:

Equipment	Manufacturer	Model No./Serial No.	Last Cal.
X Spectrum Analyzer	R&S	FSP40 / 100339	Jun, 2008

- Note:
1. All equipments are calibrated every one year.
 2. The test equipments marked by “X” are used to measure the final test results.

5.2. Test Setup




5.3. Uncertainty


± 150Hz

5.4. Test Result of Duty Cycle

Product : Wireless Temperature Sensor
 Test Item : Duty Cycle Data
 Test Site : No.3 OATS
 Test Mode : Mode 1: Transmitter



Date: 19.JAN.2009 17:41:59



Date: 19.JAN.2009 17:40:49

Time on of 100ms= 120us*11=1.1ms (1 cycle) *4 = 4.4ms

Duty Cycle= 4.4ms / 100ms= 0.044

Duty Cycle correction factor= 20 LOG 0.044 = -27.131 dB

Duty Cycle correction factor	-20.00	dB
-------------------------------------	---------------	-----------

Remark:

1. If Duty Cycle is smaller than -20dB, based on FCC part15 the duty cycle correction factor is -20dB for calculating average emission.

6. EMI Reduction Method During Compliance Testing

No modification was made during testing.