

FCC Test Report

Report No.: RF191105E04

FCC ID: XCNUBC1326

Test Model: UBC1326

Received Date: July 09, 2019

Test Date: Nov. 11, 2019 to Feb. 07, 2020

Issued Date: Mar. 06, 2020

Applicant: Ubee Interactive Corp.

Address: 10F-1, No. 5, Taiyuan 1st St. Zhubei City, Hsinchu County 302, Taiwan ,
R.O.C.

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch
Hsin Chu Laboratory

Lab Address: E-2, No.1, Li Hsin 1st Road, Hsinchu Science Park, Hsinchu City 300,
Taiwan.

Test Location: E-2, No.1, Li Hsin 1st Road, Hsinchu Science Park, Hsinchu City 300,
Taiwan.

**FCC Registration /
Designation Number:** 723255 / TW2022



This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification. The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any government agencies.

Table of Contents

Release Control Record	4
1 Certificate of Conformity	5
2 Summary of Test Results	6
2.1 Measurement Uncertainty	6
2.2 Modification Record	6
3 General Information	7
3.1 General Description of EUT	7
3.2 Description of Test Modes	9
3.2.1 Test Mode Applicability and Tested Channel Detail	10
3.3 Duty Cycle of Test Signal	12
3.4 Description of Support Units	13
3.4.1 Configuration of System under Test	14
3.5 General Description of Applied Standards and references	15
4 Test Types and Results	16
4.1 Radiated Emission and Bandedge Measurement	16
4.1.1 Limits of Radiated Emission and Bandedge Measurement	16
4.1.2 Test Instruments	17
4.1.3 Test Procedures	20
4.1.4 Deviation from Test Standard	20
4.1.5 Test Setup	21
4.1.6 EUT Operating Conditions	22
4.1.7 Test Results	23
4.2 Conducted Emission Measurement	37
4.2.1 Limits of Conducted Emission Measurement	37
4.2.2 Test Instruments	37
4.2.3 Test Procedures	38
4.2.4 Deviation from Test Standard	38
4.2.5 Test Setup	38
4.2.6 EUT Operating Conditions	38
4.2.7 Test Results	39
4.3 6dB Bandwidth Measurement	41
4.3.1 Limits of 6dB Bandwidth Measurement	41
4.3.2 Test Setup	41
4.3.3 Test Instruments	41
4.3.4 Test Procedure	41
4.3.5 Deviation from Test Standard	41
4.3.6 EUT Operating Conditions	41
4.3.7 Test Result	42
4.4 Conducted Output Power Measurement	44
4.4.1 Limits of Conducted Output Power Measurement	44
4.4.2 Test Setup	44
4.4.3 Test Instruments	44
4.4.4 Test Procedures	44
4.4.5 Deviation from Test Standard	44
4.4.6 EUT Operating Conditions	44
4.4.7 Test Results	45
4.5 Power Spectral Density Measurement	49
4.5.1 Limits of Power Spectral Density Measurement	49
4.5.2 Test Setup	49
4.5.3 Test Instruments	49
4.5.4 Test Procedure	49
4.5.5 Deviation from Test Standard	49
4.5.6 EUT Operating Condition	49

4.5.7 Test Results	50
4.6 Conducted Out of Band Emission Measurement	55
4.6.1 Limits of Conducted Out of Band Emission Measurement.....	55
4.6.2 Test Setup.....	55
4.6.3 Test Instruments	55
4.6.4 Test Procedure	55
4.6.5 Deviation from Test Standard	55
4.6.6 EUT Operating Condition	55
4.6.7 Test Results	55
5 Pictures of Test Arrangements.....	72
Appendix – Information of the Testing Laboratories	73

Release Control Record

Issue No.	Description	Date Issued
RF191105E04	Original release.	Mar. 06, 2020

1 Certificate of Conformity

Product: Wireless eMTA

Brand: Ubee


Test Model: UBC1326

Applicant: Ubee Interactive Corp.

Test Date: Nov. 11, 2019 to Feb. 07, 2020

Standards: 47 CFR FCC Part 15, Subpart C (Section 15.247)
ANSI C63.10: 2013

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

Prepared by :  , **Date:** Mar. 06, 2020
Claire Kuan / Specialist

Approved by :  , **Date:** Mar. 06, 2020
Clark Lin / Technical Manager

2 Summary of Test Results

47 CFR FCC Part 15, Subpart C (Section 15.247)			
FCC Clause	Test Item	Result	Remarks
15.207	AC Power Conducted Emission	PASS	Meet the requirement of limit. Minimum passing margin is -15.54dB at 0.15781 MHz.
15.205 / 15.209 / 15.247(d)	Radiated Emissions and Band Edge Measurement	PASS	Meet the requirement of limit. Minimum passing margin is -0.1dB at 2483.50MHz
15.247(d)	Antenna Port Emission	PASS	Meet the requirement of limit.
15.247(a)(2)	6dB bandwidth	PASS	Meet the requirement of limit.
15.247(b)	Conducted power	PASS	Meet the requirement of limit.
15.247(e)	Power Spectral Density	PASS	Meet the requirement of limit.
15.203	Antenna Requirement	PASS	Antenna connector is i-pex (MHF) not a standard connector.

Note:

Determining compliance based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.

2.1 Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

Measurement	Frequency	Expanded Uncertainty (k=2) (\pm)
Conducted Emissions at mains ports	150kHz ~ 30MHz	1.8 dB
Conducted Emissions	-	2.7 dB
Radiated Emissions up to 1 GHz	9kHz ~ 30MHz	3.0 dB
	30MHz ~ 1GHz	4.9 dB
Radiated Emissions above 1 GHz	1GHz ~ 6GHz	5.1 dB
	6GHz ~ 18GHz	4.9 dB
	18GHz ~ 40GHz	5.2 dB

2.2 Modification Record

There were no modifications required for compliance.

3 General Information

3.1 General Description of EUT

Product	Wireless eMTA
Brand	Ubee
Test Model	UBC1326
Power Supply Rating	12Vdc from power adapter
Modulation Type	CCK, DQPSK, DBPSK for DSSS 64QAM, 16QAM, QPSK, BPSK for OFDM 256QAM for OFDM in 11ac mode and VHT20/40 in 2.4GHz mode 1024QAM for OFDMA in 11ax HE mode
Modulation Technology	DSSS, OFDM, OFDMA
Transfer Rate	802.11b: up to 11Mbps 802.11a/g: up to 54Mbps 802.11n: up to 600Mbps 802.11ac: up to 1733.3Mbps 802.11ax: up to 2401.9Mbps
Operating Frequency	2.4GHz: 2.412 ~ 2.462GHz 5GHz: 5.18~ 5.24GHz, 5.745 ~ 5.825GHz
Number of Channel	2.4GHz: 802.11b, 802.11g, 802.11n (HT20), VHT20, 802.11ax (HE20): 11 802.11n (HT40), VHT40, 802.11ax (HE40): 7 5GHz: 802.11a, 802.11n (HT20), 802.11ac (VHT20), 802.11ax (HE20): 9 802.11n (HT40), 802.11ac (VHT40), 802.11ax (HE40): 4 802.11ac (VHT80), 802.11ax (HE80): 2
Output Power	Non-Beamforming Mode: 2.4GHz: 985.542mW 5.18 ~ 5.24GHz: 759.186mW 5.745 ~ 5.825GHz: 977.737mW Beamforming Mode: 2.4GHz: 403.108mW 5.18 ~ 5.24GHz: 373.518mW 5.745 ~ 5.825GHz: 382.095mW
Antenna Type	Refer to Note
Antenna Connector	Refer to Note
Accessory Device	NA
Data Cable Supplied	NA

Note:

1. Simultaneously transmission condition.

Condition	Technology	
	WLAN (2.4GHz)	WLAN (5GHz)
1		

Note: The emission of the simultaneous operation has been evaluated and no non-compliance was found.

2. The EUT power needs to be supplied from a power adapter, the information is as below table:

No.	Brand	Model No.	Spec.
1	APD	WA-36N12FU	Input: 100-240Vac, 0.9A, 50-60Hz Output: 12Vdc, 3A DC Output cable: Unshielded, 1.8m

3. The antennas provided to the EUT, please refer to the following table:

Antenna NO.	RF Chain NO.	Antenna Net Gain(dBi)	Frequency range	Antenna Type	Connector Type	Cable Length
WiFi 1	Chain1/2	3.9/4.14	2.4GHz/5GHz	PCB	i-pex(MHF)	155mm
WiFi 2	Chain2/1	3.97/4.84	2.4GHz/5GHz	PCB	i-pex(MHF)	87mm
WiFi 3	Chain0/3	3.9/3.85	2.4GHz/5GHz	PCB	i-pex(MHF)	75mm
WiFi 4	Chain3/0	3.08/3.59	2.4GHz/5GHz	PCB	i-pex(MHF)	100mm

4. The EUT incorporates a MIMO function.

2.4GHz Band		
MODULATION MODE	TX & RX CONFIGURATION	
802.11b	4TX	4RX
802.11g	4TX	4RX
802.11n (HT20)	4TX	4RX
802.11n (HT40)	4TX	4RX
VHT20	4TX	4RX
VHT40	4TX	4RX
802.11ax (HE20)	4TX	4RX
802.11ax (HE40)	4TX	4RX
5GHz Band		
MODULATION MODE	TX & RX CONFIGURATION	
802.11a	4TX	4RX
802.11n (HT20)	4TX	4RX
802.11n (HT40)	4TX	4RX
802.11ac (VHT20)	4TX	4RX
802.11ac (VHT40)	4TX	4RX
802.11ac (VHT80)	4TX	4RX
802.11ax (HE20)	4TX	4RX
802.11ax (HE40)	4TX	4RX
802.11ax (HE80)	4TX	4RX

Note:

1. All of modulation mode support beamforming function except 802.11 a/b/g modulation mode.
2. The EUT support Beamforming and non-beamforming mode, therefore both mode were investigated and the worst case scenario was identified. The worst case data were presented in test report.
3. The modulation and bandwidth are similar for 802.11n mode for 20MHz (40MHz), VHT mode for 20MHz (40MHz) and 802.11ax mode for 20MHz (40MHz), therefore the manufacturer will control the 802.11n/VHT mode power as same or lower than 802.11ax and investigated worst case to representative mode in test report. (Final test mode refer section 3.2.1)

5. The above EUT information is declared by manufacturer and for more detailed features description, please refers to the manufacturer's specifications or user's manual.

3.2 Description of Test Modes

11 channels are provided for 802.11b, 802.11g, 802.11n (HT20), VHT20 and 802.11ax (HE20):

Channel	Frequency	Channel	Frequency
1	2412MHz	7	2442MHz
2	2417MHz	8	2447MHz
3	2422MHz	9	2452MHz
4	2427MHz	10	2457MHz
5	2432MHz	11	2462MHz
6	2437MHz		

7 channels are provided for 802.11n (HT40), VHT40 and 802.11ax (HE40):

Channel	Frequency	Channel	Frequency
3	2422MHz	7	2442MHz
4	2427MHz	8	2447MHz
5	2432MHz	9	2452MHz
6	2437MHz		

3.2.1 Test Mode Applicability and Tested Channel Detail

EUT CONFIGURE MODE	APPLICABLE TO				DESCRIPTION
	RE \geq 1G	RE $<$ 1G	PLC	APCM	
-	√	√	√	√	-

Where **RE \geq 1G**: Radiated Emission above 1GHz & Bandedge Measurement
RE $<$ 1G: Radiated Emission below 1GHz
PLC: Power Line Conducted Emission
APCM: Antenna Port Conducted Measurement

Radiated Emission Test (Above 1GHz):

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

Non-Beamforming Mode					
MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	Data Rate Parameter
802.11b	1 to 11	1, 6, 11	DSSS	DBPSK	1Mb/s
802.11g	1 to 11	1, 6, 11	OFDM	BPSK	6Mb/s
802.11ax (HE20)	1 to 11	1, 6, 11	OFDMA	BPSK	MCS0
802.11ax (HE40)	3 to 9	3, 6, 9	OFDMA	BPSK	MCS0

Radiated Emission Test (Below 1GHz):

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

Non-Beamforming Mode					
MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	Data Rate Parameter
802.11b	1 to 11	6	DSSS	DBPSK	1Mb/s

Power Line Conducted Emission Test:

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

Non-Beamforming Mode					
MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	Data Rate Parameter
802.11b	1 to 11	6	DSSS	DBPSK	1Mb/s

Antenna Port Conducted Measurement:

- This item includes all test value of each mode, but only includes spectrum plot of worst value of each mode.
- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

Non-Beamforming Mode					
MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	Data Rate Parameter
802.11b	1 to 11	1, 6, 11	DSSS	DBPSK	1Mb/s
802.11g	1 to 11	1, 6, 11	OFDM	BPSK	6Mb/s
VHT20 (Output power only)	1 to 11	1, 6, 11	OFDM	BPSK	MCS0
VHT40 (Output power only)	3 to 9	3, 6, 9	OFDM	BPSK	MCS0
802.11ax (HE20)	1 to 11	1, 6, 11	OFDMA	BPSK	MCS0
802.11ax (HE40)	3 to 9	3, 6, 9	OFDMA	BPSK	MCS0
Beamforming Mode (output power only)					
MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	Data Rate Parameter
VHT20	1 to 11	1, 6, 11	OFDM	BPSK	MCS0
VHT40	3 to 9	3, 6, 9	OFDM	BPSK	MCS0
802.11ax (HE20)	1 to 11	1, 6, 11	OFDMA	BPSK	MCS0
802.11ax (HE40)	3 to 9	3, 6, 9	OFDMA	BPSK	MCS0

Test Condition:

Applicable To	Environmental Conditions	Input Power	Tested By
RE \geq 1G	25deg. C, 75%RH	120Vac, 60Hz	Gary Cheng
RE $<$ 1G	24deg. C, 66%RH	120Vac, 60Hz	Jeff Lee
PLC	25deg. C, 75%RH	120Vac, 60Hz	Kevin Ko
APCM	25deg. C, 60%RH	120Vac, 60Hz	Jyunchun Lin

3.3 Duty Cycle of Test Signal

If duty cycle of test signal is $\geq 98\%$, duty factor is not required.
 If duty cycle of test signal is $< 98\%$, duty factor shall be considered.

802.11b: Duty cycle = $12.457/12.513 = 0.996$


802.11g: Duty cycle = $2.064/2.096 = 0.985$

VHT20: Duty cycle = $1.486/1.52 = 0.978$, Duty factor = $10 * \log(1/\text{Duty cycle}) = 0.1$

VHT40: Duty cycle = $0.769/0.806 = 0.954$, Duty factor = $10 * \log(1/\text{Duty cycle}) = 0.2$

802.11ax (HE20): Duty cycle = $1.486/1.52 = 0.978$, Duty factor = $10 * \log(1/\text{Duty cycle}) = 0.1$

802.11ax (HE40): Duty cycle = $0.769/0.806 = 0.954$, Duty factor = $10 * \log(1/\text{Duty cycle}) = 0.2$



3.4 Description of Support Units

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.


ID	Product	Brand	Model No.	Serial No.	FCC ID	Remarks
A.	Telephone	WONDER	WD-303	7C17KA04011	N/A	Provided by Lab
B.	Laptop	DELL	E5430	HYV4VY1	FCC DoC	Provided by Lab
C.	Laptop	Lenovo	81A4	YD02YN22	PD93165NGU	Provided by Lab
D.	USB Dongle	Sandisk	64GB	NA	NA	Supplied by client

Note:

1. All power cords of the above support units are non-shielded (1.8m).

ID	Descriptions	Qty.	Length (m)	Shielding (Yes/No)	Cores (Qty.)	Remarks
1.	DC Cable	1	1.8	No	0	Supplied by client
2.	RJ-11 Cable	1	10	No	0	Provided by Lab
3.	RJ-45 Cable	1	10	No	0	Provided by Lab
4.	RJ-45 Cable	1	10	No	0	Provided by Lab
5.	Coaxial Cable	1	10	Yes	0	Provided by Lab
6.	Type C to Type A USB Cable	1	0.06	Yes	0	Provided by Lab

3.4.1 Configuration of System under Test



3.5 General Description of Applied Standards and references

The EUT is a RF Product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards and references:

Test standard:

FCC Part 15, Subpart C (15.247)
ANSI C63.10-2013

All test items have been performed and recorded as per the above standards.

References Test Guidance :

KDB 558074 D01 15.247 Meas Guidance v05r02
KDB 662911 D01 Multiple Transmitter Output v02r01

All test items have been performed as a reference to the above KDB test guidance.

4 Test Types and Results

4.1 Radiated Emission and Bandedge Measurement

4.1.1 Limits of Radiated Emission and Bandedge Measurement

Radiated emissions which fall in the restricted bands must comply with the radiated emission limits specified as below table. Other emissions shall be at least 30dB below the highest level of the desired power:

Frequencies (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

NOTE:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. For frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.

4.1.2 Test Instruments

For radiated emission (below 1GHz) test:

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
Test Receiver Keysight	N9038A	MY54450088	July 03, 2019	July 02, 2020
Pre-Amplifier EMCI	EMC001340	980142	May 30, 2019	May 29, 2020
Loop Antenna Electro-Metrics	EM-6879	269	Sep. 16, 2019	Sep. 15, 2020
RF Cable	NA	LOOPCAB-001	Jan. 14, 2019	Jan. 13, 2020
RF Cable	NA	LOOPCAB-002	Jan. 14, 2019	Jan. 13, 2020
Pre-Amplifier Mini-Circuits	ZFL-1000VH2B	AMP-ZFL-01	Oct. 23, 2019	Oct. 22, 2020
Trilog Broadband Antenna SCHWARZBECK	VULB 9168	9168-406	Nov. 11, 2019	Nov. 10, 2020
RF Cable	8D	966-4-1	Mar. 19, 2019	Mar. 18, 2020
RF Cable	8D	966-4-2	Mar. 19, 2019	Mar. 18, 2020
RF Cable	8D	966-4-3	Mar. 19, 2019	Mar. 18, 2020
Fixed attenuator Mini-Circuits	UNAT-5+	PAD-3m-4-01	Sep. 26, 2019	Sep. 25, 2020
Software	ADT_Radiated_V8.7.08	NA	NA	NA
Boresight Antenna Tower & Turn Table Max-Full	MF-7802BS	MF780208530	NA	NA

Note:

1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. The test was performed in 966 Chamber No. 4.
3. Loop antenna was used for all emissions below 30 MHz.
4. Tested Date: Nov. 11 to 16, 2019

For radiated emission (Above 1GHz) test:

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
Test Receiver Agilent	N9038A	MY51210202	Dec. 13, 2019	Dec. 12, 2020
Horn_Antenna SCHWARZBECK	BBHA 9120D	9120D-783	Nov. 24, 2019	Nov. 23, 2020
Pre-Amplifier EMCI	EMC12630SE	980385	Aug. 15, 2019	Aug. 14, 2020
RF Cable	EMC104-SM-SM-1200	160923	Jan. 15, 2020	Jan. 14, 2021
RF Cable	104 RF cable	131215	Jan. 09, 2020	Jan. 08, 2021
RF Cable	EMC104-SM-SM-6000	180418	May 03, 2019	May 02, 2020
Pre-Amplifier EMCI	EMC184045SE	980387	Jan. 15, 2020	Jan. 14, 2021
Horn_Antenna SCHWARZBECK	BBHA 9170	BBHA9170519	Nov. 24, 2019	Nov. 23, 2020
RF Cable	EMC102-KM-KM-1200	160924	Jan. 15, 2020	Jan. 14, 2021
RF Cable	EMC102-KM-KM-4500	181205	Aug. 26, 2019	Aug. 25, 2020
Software	ADT_Radiated_V8.7.08	NA	NA	NA
Boresight Antenna Tower & Turn Table Max-Full	MF-7802BS	MF780208530	NA	NA

Note:

1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. The test was performed in 966 Chamber No. 4.
3. Loop antenna was used for all emissions below 30 MHz.
4. Tested Date: Feb. 07, 2020

For other test items:

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
Spectrum Analyzer R&S	FSV40	100964	June 04, 2019	June 03, 2020
Power meter Anritsu	ML2495A	1014008	May 13, 2019	May 12, 2020
Power sensor Anritsu	MA2411B	0917122	May 13, 2019	May 12, 2020
Fixed Attenuator Mini-Circuits	MDCS18N-10	MDCS18N-10-01	Apr. 15, 2019	Apr. 14, 2020

Note:

1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. The test was performed in 966 Chamber No. 4.
3. Loop antenna was used for all emissions below 30 MHz.
4. Tested Date: Feb. 05, 2020

4.1.3 Test Procedures

For Radiated emission below 30MHz

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter chamber room. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. Parallel, perpendicular, and ground-parallel orientations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Quasi-Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.

NOTE:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 9kHz at frequency below 30MHz.

For Radiated emission above 30MHz

- a. The EUT was placed on the top of a rotating table 0.8 meters (for 30MHz ~ 1GHz) / 1.5 meters (for above 1GHz) above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.
- f. The test-receiver system was set to peak and average detects function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz. If the peak reading value also meets average limit, measurement with the average detector is unnecessary.

Note:


1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection (QP) at frequency below 1GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz for Peak detection (PK) at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is $\geq 1/T$ (Duty cycle < 98%) or 10Hz (Duty cycle $\geq 98\%$) for Average detection (AV) at frequency above 1GHz.
4. All modes of operation were investigated and the worst-case emissions are reported.

4.1.4 Deviation from Test Standard


No deviation.

4.1.5 Test Setup


For Radiated emission below 30MHz



For Radiated emission 30MHz to 1GHz



For Radiated emission above 1GHz



For the actual test configuration, please refer to the attached file (Test Setup Photo).

4.1.6 EUT Operating Conditions

- a. Connected the EUT with the Laptop which is placed on remote site.
- b. Controlling software (Mtool 3.1.0.1) has been activated to set the EUT under transmission condition continuously at specific channel frequency.

4.1.7 Test Results

Above 1GHz Data:

802.11b

CHANNEL	TX Channel 1	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	60.6 PK	74.0	-13.4	1.76 H	75	62.3	-1.7
2	2390.00	53.8 AV	54.0	-0.2	1.76 H	75	55.5	-1.7
3	*2412.00	118.6 PK			1.76 H	75	120.4	-1.8
4	*2412.00	115.9 AV			1.76 H	75	117.7	-1.8
5	4824.00	43.2 PK	74.0	-30.8	1.87 H	49	40.9	2.3
6	4824.00	39.4 AV	54.0	-14.6	1.87 H	49	37.1	2.3

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	53.2 PK	74.0	-20.8	1.81 V	34	54.9	-1.7
2	2390.00	46.5 AV	54.0	-7.5	1.81 V	34	48.2	-1.7
3	*2412.00	112.3 PK			1.81 V	34	114.1	-1.8
4	*2412.00	109.6 AV			1.81 V	34	111.4	-1.8
5	4824.00	41.5 PK	74.0	-32.5	1.48 V	77	39.2	2.3
6	4824.00	38.0 AV	54.0	-16.0	1.48 V	77	35.7	2.3

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.

CHANNEL		TX Channel 6			DETECTOR FUNCTION		Peak (PK) Average (AV)	
FREQUENCY RANGE		1GHz ~ 25GHz			DETECTOR FUNCTION		Peak (PK) Average (AV)	
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	56.6 PK	74.0	-17.4	1.65 H	83	58.3	-1.7
2	2390.00	50.2 AV	54.0	-3.8	1.65 H	83	51.9	-1.7
3	*2437.00	119.2 PK			1.65 H	83	120.9	-1.7
4	*2437.00	116.9 AV			1.65 H	83	118.6	-1.7
5	2483.50	57.4 PK	74.0	-16.6	1.65 H	83	59.1	-1.7
6	2483.50	51.3 AV	54.0	-2.7	1.65 H	83	53.0	-1.7
7	4874.00	44.6 PK	74.0	-29.4	1.87 H	36	42.4	2.2
8	4874.00	40.9 AV	54.0	-13.1	1.87 H	36	38.7	2.2
9	7311.00	49.2 PK	74.0	-24.8	1.62 H	89	40.1	9.1
10	7311.00	44.2 AV	54.0	-9.8	1.62 H	89	35.1	9.1
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	50.4 PK	74.0	-23.6	1.80 V	44	52.1	-1.7
2	2390.00	43.2 AV	54.0	-10.8	1.80 V	44	44.9	-1.7
3	*2437.00	112.3 PK			1.80 V	44	114.0	-1.7
4	*2437.00	109.8 AV			1.80 V	44	111.5	-1.7
5	2483.50	51.0 PK	74.0	-23.0	1.80 V	44	52.7	-1.7
6	2483.50	44.4 AV	54.0	-9.6	1.80 V	44	46.1	-1.7
7	4874.00	43.3 PK	74.0	-30.7	1.49 V	88	41.1	2.2
8	4874.00	39.5 AV	54.0	-14.5	1.49 V	88	37.3	2.2
9	7311.00	52.6 PK	74.0	-21.4	1.76 V	96	43.5	9.1
10	7311.00	48.1 AV	54.0	-5.9	1.76 V	96	39.0	9.1

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.

CHANNEL	TX Channel 11	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2462.00	119.0 PK			1.31 H	76	120.7	-1.7
2	*2462.00	116.5 AV			1.31 H	76	118.2	-1.7
3	2483.50	60.3 PK	74.0	-13.7	1.31 H	76	62.0	-1.7
4	2483.50	53.8 AV	54.0	-0.2	1.31 H	76	55.5	-1.7
5	4924.00	44.9 PK	74.0	-29.1	1.89 H	41	42.5	2.4
6	4924.00	40.9 AV	54.0	-13.1	1.89 H	41	38.5	2.4
7	7386.00	48.9 PK	74.0	-25.1	1.66 H	85	39.4	9.5
8	7386.00	43.7 AV	54.0	-10.3	1.66 H	85	34.2	9.5

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2462.00	111.7 PK			1.75 V	48	113.4	-1.7
2	*2462.00	109.1 AV			1.75 V	48	110.8	-1.7
3	2483.50	53.0 PK	74.0	-21.0	1.75 V	48	54.7	-1.7
4	2483.50	46.7 AV	54.0	-7.3	1.75 V	48	48.4	-1.7
5	4924.00	42.8 PK	74.0	-31.2	1.54 V	91	40.4	2.4
6	4924.00	39.0 AV	54.0	-15.0	1.54 V	91	36.6	2.4
7	7386.00	53.2 PK	74.0	-20.8	1.78 V	82	43.7	9.5
8	7386.00	48.5 AV	54.0	-5.5	1.78 V	82	39.0	9.5

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.

802.11g

CHANNEL	TX Channel 1	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	72.4 PK	74.0	-1.6	1.51 H	146	74.1	-1.7
2	2390.00	53.7 AV	54.0	-0.3	1.51 H	146	55.4	-1.7
3	*2412.00	117.1 PK			1.51 H	146	118.9	-1.8
4	*2412.00	107.0 AV			1.51 H	146	108.8	-1.8
5	4824.00	40.3 PK	74.0	-33.7	1.83 H	33	38.0	2.3
6	4824.00	36.2 AV	54.0	-17.8	1.83 H	33	33.9	2.3

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	65.8 PK	74.0	-8.2	1.84 V	48	67.5	-1.7
2	2390.00	46.6 AV	54.0	-7.4	1.84 V	48	48.3	-1.7
3	*2412.00	110.2 PK			1.84 V	48	112.0	-1.8
4	*2412.00	100.3 AV			1.84 V	48	102.1	-1.8
5	4824.00	39.2 PK	74.0	-34.8	1.43 V	72	36.9	2.3
6	4824.00	35.4 AV	54.0	-18.6	1.43 V	72	33.1	2.3

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.

CHANNEL	TX Channel 6	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	64.4 PK	74.0	-9.6	2.33 H	146	66.1	-1.7
2	2390.00	47.8 AV	54.0	-6.2	2.33 H	146	49.5	-1.7
3	*2437.00	122.9 PK			2.33 H	146	124.6	-1.7
4	*2437.00	111.8 AV			2.33 H	146	113.5	-1.7
5	2483.50	65.2 PK	74.0	-8.8	2.33 H	146	66.9	-1.7
6	2483.50	49.5 AV	54.0	-4.5	2.33 H	146	51.2	-1.7
7	4874.00	43.1 PK	74.0	-30.9	1.93 H	56	40.9	2.2
8	4874.00	39.4 AV	54.0	-14.6	1.93 H	56	37.2	2.2
9	7311.00	48.4 PK	74.0	-25.6	1.70 H	83	39.3	9.1
10	7311.00	43.1 AV	54.0	-10.9	1.70 H	83	34.0	9.1

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	57.4 PK	74.0	-16.6	1.78 V	62	59.1	-1.7
2	2390.00	40.3 AV	54.0	-13.7	1.78 V	62	42.0	-1.7
3	*2437.00	115.7 PK			1.78 V	62	117.4	-1.7
4	*2437.00	104.9 AV			1.78 V	62	106.6	-1.7
5	2483.50	58.3 PK	74.0	-15.7	1.78 V	62	60.0	-1.7
6	2483.50	42.3 AV	54.0	-11.7	1.78 V	62	44.0	-1.7
7	4874.00	42.1 PK	74.0	-31.9	1.56 V	80	39.9	2.2
8	4874.00	38.2 AV	54.0	-15.8	1.56 V	80	36.0	2.2
9	7311.00	52.3 PK	74.0	-21.7	1.78 V	90	43.2	9.1
10	7311.00	47.6 AV	54.0	-6.4	1.78 V	90	38.5	9.1

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.

CHANNEL	TX Channel 11	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2462.00	112.4 PK			1.46 H	149	114.1	-1.7
2	*2462.00	102.7 AV			1.46 H	149	104.4	-1.7
3	2483.50	73.9 PK	74.0	-0.1	1.46 H	149	75.6	-1.7
4	2483.50	50.2 AV	54.0	-3.8	1.46 H	149	51.9	-1.7
5	4924.00	39.0 PK	74.0	-35.0	1.80 H	17	36.6	2.4
6	4924.00	34.7 AV	54.0	-19.3	1.80 H	17	32.3	2.4
7	7386.00	46.5 PK	74.0	-27.5	1.70 H	77	37.0	9.5
8	7386.00	41.7 AV	54.0	-12.3	1.70 H	77	32.2	9.5

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2462.00	105.6 PK			1.86 V	45	107.3	-1.7
2	*2462.00	95.6 AV			1.86 V	45	97.3	-1.7
3	2483.50	67.0 PK	74.0	-7.0	1.86 V	45	68.7	-1.7
4	2483.50	43.4 AV	54.0	-10.6	1.86 V	45	45.1	-1.7
5	4924.00	38.2 PK	74.0	-35.8	1.52 V	90	35.8	2.4
6	4924.00	33.2 AV	54.0	-20.8	1.52 V	90	30.8	2.4
7	7386.00	50.8 PK	74.0	-23.2	1.73 V	98	41.3	9.5
8	7386.00	45.3 AV	54.0	-8.7	1.73 V	98	35.8	9.5

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.

802.11ax (HE20)

CHANNEL	TX Channel 1	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	73.6 PK	74.0	-0.4	1.36 H	74	75.3	-1.7
2	2390.00	53.8 AV	54.0	-0.2	1.36 H	74	55.5	-1.7
3	*2412.00	117.1 PK			1.36 H	74	118.9	-1.8
4	*2412.00	104.4 AV			1.36 H	74	106.2	-1.8
5	4824.00	38.6 PK	74.0	-35.4	1.83 H	30	36.3	2.3
6	4824.00	34.2 AV	54.0	-19.8	1.83 H	30	31.9	2.3

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	66.6 PK	74.0	-7.4	1.79 V	55	68.3	-1.7
2	2390.00	46.8 AV	54.0	-7.2	1.79 V	55	48.5	-1.7
3	*2412.00	110.2 PK			1.79 V	55	112.0	-1.8
4	*2412.00	97.4 AV			1.79 V	55	99.2	-1.8
5	4824.00	37.2 PK	74.0	-36.8	1.42 V	74	34.9	2.3
6	4824.00	33.2 AV	54.0	-20.8	1.42 V	74	30.9	2.3

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.

CHANNEL	TX Channel 6	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	68.4 PK	74.0	-5.6	1.32 H	74	70.1	-1.7
2	2390.00	51.2 AV	54.0	-2.8	1.32 H	74	52.9	-1.7
3	*2437.00	122.7 PK			1.32 H	74	124.4	-1.7
4	*2437.00	110.4 AV			1.32 H	74	112.1	-1.7
5	2483.50	70.2 PK	74.0	-3.8	1.32 H	74	71.9	-1.7
6	2483.50	51.8 AV	54.0	-2.2	1.32 H	74	53.5	-1.7
7	4874.00	42.8 PK	74.0	-31.2	1.98 H	65	40.6	2.2
8	4874.00	39.0 AV	54.0	-15.0	1.98 H	65	36.8	2.2
9	7311.00	48.3 PK	74.0	-25.7	1.72 H	80	39.2	9.1
10	7311.00	43.3 AV	54.0	-10.7	1.72 H	80	34.2	9.1

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	57.8 PK	74.0	-16.2	1.74 V	60	59.5	-1.7
2	2390.00	40.6 AV	54.0	-13.4	1.74 V	60	42.3	-1.7
3	*2437.00	115.3 PK			1.74 V	60	117.0	-1.7
4	*2437.00	104.3 AV			1.74 V	60	106.0	-1.7
5	2483.50	58.5 PK	74.0	-15.5	1.74 V	60	60.2	-1.7
6	2483.50	42.7 AV	54.0	-11.3	1.74 V	60	44.4	-1.7
7	4874.00	41.5 PK	74.0	-32.5	1.60 V	91	39.3	2.2
8	4874.00	37.7 AV	54.0	-16.3	1.60 V	91	35.5	2.2
9	7311.00	52.6 PK	74.0	-21.4	1.75 V	77	43.5	9.1
10	7311.00	48.0 AV	54.0	-6.0	1.75 V	77	38.9	9.1

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.

CHANNEL	TX Channel 11	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2462.00	116.9 PK			1.29 H	69	118.6	-1.7
2	*2462.00	104.1 AV			1.29 H	69	105.8	-1.7
3	2483.50	71.7 PK	74.0	-2.3	1.29 H	69	73.4	-1.7
4	2483.50	53.6 AV	54.0	-0.4	1.29 H	69	55.3	-1.7
5	4924.00	39.0 PK	74.0	-35.0	1.75 H	2	36.6	2.4
6	4924.00	34.9 AV	54.0	-19.1	1.75 H	2	32.5	2.4
7	7386.00	46.3 PK	74.0	-27.7	1.75 H	85	36.8	9.5
8	7386.00	41.3 AV	54.0	-12.7	1.75 H	85	31.8	9.5

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2462.00	109.9 PK			1.84 V	37	111.6	-1.7
2	*2462.00	97.2 AV			1.84 V	37	98.9	-1.7
3	2483.50	66.8 PK	74.0	-7.2	1.84 V	37	68.5	-1.7
4	2483.50	43.3 AV	54.0	-10.7	1.84 V	37	45.0	-1.7
5	4924.00	37.8 PK	74.0	-36.2	1.47 V	88	35.4	2.4
6	4924.00	33.0 AV	54.0	-21.0	1.47 V	88	30.6	2.4
7	7386.00	50.6 PK	74.0	-23.4	1.70 V	97	41.1	9.5
8	7386.00	44.9 AV	54.0	-9.1	1.70 V	97	35.4	9.5

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.

802.11ax (HE40)

CHANNEL	TX Channel 3	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	71.5 PK	74.0	-2.5	1.33 H	75	73.2	-1.7
2	2390.00	53.8 AV	54.0	-0.2	1.33 H	75	55.5	-1.7
3	*2422.00	112.8 PK			1.33 H	75	114.6	-1.8
4	*2422.00	101.7 AV			1.33 H	75	103.5	-1.8
5	4844.00	36.9 PK	74.0	-37.1	2.01 H	57	34.6	2.3
6	4844.00	32.9 AV	54.0	-21.1	2.01 H	57	30.6	2.3
7	7266.00	44.3 PK	74.0	-29.7	1.67 H	88	35.4	8.9
8	7266.00	39.6 AV	54.0	-14.4	1.67 H	88	30.7	8.9

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	64.2 PK	74.0	-9.8	1.83 V	42	65.9	-1.7
2	2390.00	46.0 AV	54.0	-8.0	1.83 V	42	47.7	-1.7
3	*2422.00	106.6 PK			1.83 V	42	108.4	-1.8
4	*2422.00	95.4 AV			1.83 V	42	97.2	-1.8
5	4844.00	36.3 PK	74.0	-37.7	1.50 V	74	34.0	2.3
6	4844.00	31.1 AV	54.0	-22.9	1.50 V	74	28.8	2.3
7	7266.00	48.9 PK	74.0	-25.1	1.75 V	96	40.0	8.9
8	7266.00	43.7 AV	54.0	-10.3	1.75 V	96	34.8	8.9

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.

CHANNEL	TX Channel 6	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	65.3 PK	74.0	-8.7	1.12 H	72	67.0	-1.7
2	2390.00	49.3 AV	54.0	-4.7	1.12 H	72	51.0	-1.7
3	*2437.00	114.4 PK			1.12 H	72	116.1	-1.7
4	*2437.00	103.0 AV			1.12 H	72	104.7	-1.7
5	2483.50	72.4 PK	74.0	-1.6	1.12 H	72	74.1	-1.7
6	2483.50	53.6 AV	54.0	-0.4	1.12 H	72	55.3	-1.7
7	4874.00	39.4 PK	74.0	-34.6	1.92 H	66	37.2	2.2
8	4874.00	35.0 AV	54.0	-19.0	1.92 H	66	32.8	2.2
9	7311.00	46.2 PK	74.0	-27.8	1.75 H	77	37.1	9.1
10	7311.00	41.1 AV	54.0	-12.9	1.75 H	77	32.0	9.1

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	63.4 PK	74.0	-10.6	1.78 V	30	65.1	-1.7
2	2390.00	47.3 AV	54.0	-6.7	1.78 V	30	49.0	-1.7
3	*2437.00	107.3 PK			1.78 V	30	109.0	-1.7
4	*2437.00	96.3 AV			1.78 V	30	98.0	-1.7
5	2483.50	70.6 PK	74.0	-3.4	1.78 V	30	72.3	-1.7
6	2483.50	51.8 AV	54.0	-2.2	1.78 V	30	53.5	-1.7
7	4874.00	38.4 PK	74.0	-35.6	1.53 V	88	36.2	2.2
8	4874.00	33.3 AV	54.0	-20.7	1.53 V	88	31.1	2.2
9	7311.00	51.2 PK	74.0	-22.8	1.74 V	102	42.1	9.1
10	7311.00	45.3 AV	54.0	-8.7	1.74 V	102	36.2	9.1

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.

CHANNEL	TX Channel 9	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2452.00	113.1 PK			1.74 H	72	114.8	-1.7
2	*2452.00	101.1 AV			1.74 H	72	102.8	-1.7
3	2483.50	69.3 PK	74.0	-4.7	1.74 H	72	71.0	-1.7
4	2483.50	53.7 AV	54.0	-0.3	1.74 H	72	55.4	-1.7
5	4904.00	37.4 PK	74.0	-36.6	2.05 H	64	35.2	2.2
6	4904.00	33.2 AV	54.0	-20.8	2.05 H	64	31.0	2.2
7	7356.00	44.3 PK	74.0	-29.7	1.62 H	88	35.0	9.3
8	7356.00	39.6 AV	54.0	-14.4	1.62 H	88	30.3	9.3

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2452.00	106.5 PK			1.80 V	50	108.2	-1.7
2	*2452.00	95.4 AV			1.80 V	50	97.1	-1.7
3	2483.50	63.6 PK	74.0	-10.4	1.80 V	50	65.3	-1.7
4	2483.50	45.6 AV	54.0	-8.4	1.80 V	50	47.3	-1.7
5	4904.00	36.5 PK	74.0	-37.5	1.46 V	93	34.3	2.2
6	4904.00	31.4 AV	54.0	-22.6	1.46 V	93	29.2	2.2
7	7356.00	48.6 PK	74.0	-25.4	1.74 V	97	39.3	9.3
8	7356.00	43.4 AV	54.0	-10.6	1.74 V	97	34.1	9.3

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.

Below 1GHz Data:


802.11b

CHANNEL	TX Channel 6	DETECTOR FUNCTION	Quasi-Peak (QP)
FREQUENCY RANGE	9kHz ~ 1GHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	48.92	22.2 QP	40.0	-17.8	1.50 H	103	30.3	-8.1
2	92.96	28.8 QP	43.5	-14.7	2.00 H	251	41.7	-12.9
3	149.99	28.4 QP	43.5	-15.1	1.50 H	248	36.2	-7.8
4	249.96	34.1 QP	46.0	-11.9	1.00 H	254	42.7	-8.6
5	349.97	40.6 QP	46.0	-5.4	1.00 H	232	46.5	-5.9
6	949.99	41.0 QP	46.0	-5.0	1.50 H	236	34.1	6.9

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit of frequency range 30MHz~1000MHz.
5. The emission levels were very low against the limit of frequency range 9kHz~30MHz: the amplitude of spurious emissions attenuated more than 20 dB below the permissible value to be report.




CHANNEL	TX Channel 6	DETECTOR FUNCTION	Quasi-Peak (QP)
FREQUENCY RANGE	9kHz ~ 1GHz		

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	46.98	29.5 QP	40.0	-10.5	1.00 V	121	37.7	-8.2
2	85.10	31.0 QP	40.0	-9.0	1.50 V	360	44.4	-13.4
3	94.27	30.5 QP	43.5	-13.0	1.00 V	42	43.3	-12.8
4	141.99	37.9 QP	43.5	-5.6	2.00 V	1	45.9	-8.0
5	250.01	32.9 QP	46.0	-13.1	2.00 V	313	41.5	-8.6
6	349.97	41.4 QP	46.0	-4.6	1.50 V	274	47.3	-5.9

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit of frequency range 30MHz~1000MHz.
5. The emission levels were very low against the limit of frequency range 9kHz~30MHz: the amplitude of spurious emissions attenuated more than 20 dB below the permissible value to be report.



4.2 Conducted Emission Measurement

4.2.1 Limits of Conducted Emission Measurement

Frequency (MHz)	Conducted Limit (dBuV)	
	Quasi-peak	Average
0.15 - 0.5	66 - 56	56 - 46
0.50 - 5.0	56	46
5.0 - 30.0	60	50

Note: 1. The lower limit shall apply at the transition frequencies.

2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

4.2.2 Test Instruments

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
Test Receiver R&S	ESCS 30	847124/029	Oct. 23, 2019	Oct. 22, 2020
Line-Impedance Stabilization Network (for EUT) R&S	ESH3-Z5	848773/004	Oct. 23, 2019	Oct. 22, 2020
Line-Impedance Stabilization Network (for Peripheral) R&S	ESH3-Z5	835239/001	Mar. 17, 2019	Mar. 16, 2020
50 ohms Terminator	50	3	Oct. 23, 2019	Oct. 22, 2020
RF Cable	5D-FB	COCCAB-001	Sep. 27, 2019	Sep. 26, 2020
Fixed attenuator EMCI	STI02-2200-10	003	Mar. 14, 2019	Mar. 13, 2020
Software BVADT	BVADT_Cond_V7.3.7.4	NA	NA	NA

Note:

1. The calibration interval of the above test instruments are 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. The test was performed in Conduction 1.
3. Tested Date: Nov. 13, 2019

4.2.3 Test Procedures


- The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- The frequency range from 150kHz to 30MHz was searched. Emission levels under (Limit - 20dB) was not recorded.

NOTE: The resolution bandwidth and video bandwidth of test receiver is 9kHz for quasi-peak detection (QP) and average detection (AV) at frequency 0.15MHz-30MHz.

4.2.4 Deviation from Test Standard

No deviation.

4.2.5 Test Setup



Note: 1.Support units were connected to second LISN.

For the actual test configuration, please refer to the attached file (Test Setup Photo).

4.2.6 EUT Operating Conditions

Same as 4.1.6.


4.2.7 Test Results

Phase	Line (L)	Detector Function	Quasi-Peak (QP) / Average (AV)
-------	----------	-------------------	--------------------------------

No	Freq. [MHz]	Corr.	Reading Value		Emission Level		Limit		Margin	
		Factor (dB)	[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.15781	9.99	40.05	26.57	50.04	36.56	65.58	55.58	-15.54	-19.02
2	0.18125	9.99	34.14	23.08	44.13	33.07	64.43	54.43	-20.30	-21.36
3	0.23203	9.99	26.94	15.14	36.93	25.13	62.38	52.38	-25.45	-27.25
4	0.32188	10.00	31.13	19.18	41.13	29.18	59.66	49.66	-18.53	-20.48
5	0.34141	10.00	28.27	19.15	38.27	29.15	59.17	49.17	-20.90	-20.02
6	3.15234	10.20	16.12	9.04	26.32	19.24	56.00	46.00	-29.68	-26.76

REMARKS:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level - Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value.




Phase	Neutral (N)	Detector Function	Quasi-Peak (QP) / Average (AV)
-------	-------------	-------------------	--------------------------------

No	Freq. [MHz]	Corr.	Reading Value		Emission Level		Limit		Margin	
		Factor	[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
	(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	
1	0.16172	9.99	38.34	25.24	48.33	35.23	65.38	55.38	-17.05	-20.15
2	0.24375	9.99	29.42	20.77	39.41	30.76	61.97	51.97	-22.56	-21.21
3	0.26328	10.00	24.19	12.96	34.19	22.96	61.33	51.33	-27.14	-28.37
4	0.30234	10.00	28.37	19.19	38.37	29.19	60.18	50.18	-21.81	-20.99
5	0.32188	10.00	33.62	21.81	43.62	31.81	59.66	49.66	-16.04	-17.85
6	0.36094	10.01	30.59	22.21	40.60	32.22	58.71	48.71	-18.11	-16.49

REMARKS:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level - Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value.




4.3 6dB Bandwidth Measurement

4.3.1 Limits of 6dB Bandwidth Measurement

The minimum of 6dB Bandwidth Measurement is 0.5 MHz.

4.3.2 Test Setup



4.3.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

4.3.4 Test Procedure

- a. Set resolution bandwidth (RBW) = 100kHz
- b. Set the video bandwidth (VBW) $\geq 3 \times$ RBW, Detector = Peak.
- c. Trace mode = max hold.
- d. Sweep = auto couple.
- e. Measure the maximum width of the emission that is constrained by the frequencies associated with the two amplitude points (upper and lower) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission

4.3.5 Deviation from Test Standard

No deviation.

4.3.6 EUT Operating Conditions

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.

4.3.7 Test Result

802.11b

Channel	Frequency (MHz)	6dB Bandwidth (MHz)				Minimum Limit (MHz)	Pass / Fail
		Chain 0	Chain 1	Chain 2	Chain 3		
1	2412	7.57	6.60	7.52	7.07	0.5	Pass
6	2437	7.08	7.09	7.08	7.52	0.5	Pass
11	2462	6.63	7.07	7.51	7.57	0.5	Pass

802.11g

Channel	Frequency (MHz)	6dB Bandwidth (MHz)				Minimum Limit (MHz)	Pass / Fail
		Chain 0	Chain 1	Chain 2	Chain 3		
1	2412	15.84	15.84	16.40	16.46	0.5	Pass
6	2437	16.13	16.44	16.40	16.11	0.5	Pass
11	2462	15.81	16.35	15.85	16.44	0.5	Pass

802.11ax (HE20)


Channel	Frequency (MHz)	6dB Bandwidth (MHz)				Minimum Limit (MHz)	Pass / Fail
		Chain 0	Chain 1	Chain 2	Chain 3		
1	2412	18.86	16.42	18.87	17.65	0.5	Pass
6	2437	18.89	17.70	17.63	18.37	0.5	Pass
11	2462	16.44	17.63	16.46	17.70	0.5	Pass

802.11ax (HE40)


Channel	Frequency (MHz)	6dB Bandwidth (MHz)				Minimum Limit (MHz)	Pass / Fail
		Chain 0	Chain 1	Chain 2	Chain 3		
3	2422	37.45	36.44	37.45	36.22	0.5	Pass
6	2437	37.70	37.69	35.93	35.34	0.5	Pass
9	2452	35.39	36.35	37.31	36.57	0.5	Pass

Spectrum Plot of Worst Value


802.11b / Chain 1 : CH1




802.11g / Chain 0 : CH11



802.11ax (HE20) / Chain 1 : CH1



802.11ax (HE40) / Chain 3 : CH6



4.4 Conducted Output Power Measurement

4.4.1 Limits of Conducted Output Power Measurement

For systems using digital modulation in the 2400–2483.5 MHz bands: 1 Watt (30dBm)

Per KDB 662911 D01 Multiple Transmitter Output Method of conducted output power measurement on IEEE 802.11 devices,


Array Gain = 0 dB (i.e., no array gain) for $N_{ANT} \leq 4$;

Array Gain = 0 dB (i.e., no array gain) for channel widths ≥ 40 MHz for any N_{ANT} ;

Array Gain = $5 \log(N_{ANT}/N_{SS})$ dB or 3 dB, whichever is less for 20-MHz channel widths with $N_{ANT} \geq 5$.

For power measurements on all other devices: Array Gain = $10 \log(N_{ANT}/N_{SS})$ dB.

4.4.2 Test Setup



4.4.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

4.4.4 Test Procedures

Average power sensor was used to perform output power measurement, trigger and gating function of wide band power meter is enabled to measure max output power of TX on burst. Duty factor is not added to measured value.

4.4.5 Deviation from Test Standard

No deviation.

4.4.6 EUT Operating Conditions

Same as Item 4.3.6.

4.4.7 Test Results

Non-Beamforming Mode

802.11b

Chan.	Chan. Freq. (MHz)	Average Power (dBm)				Total Power (mW)	Total Power (dBm)	Limit (dBm)	Pass / Fail
		Chain 0	Chain 1	Chain 2	Chain 3				
1	2412	23.81	23.25	23.48	23.94	922.371	29.65	30.00	Pass
6	2437	24.14	23.56	23.72	24.21	985.542	29.94	30.00	Pass
11	2462	23.77	23.78	23.59	24.23	970.423	29.87	30.00	Pass

802.11g

Chan.	Chan. Freq. (MHz)	Average Power (dBm)				Total Power (mW)	Total Power (dBm)	Limit (dBm)	Pass / Fail
		Chain 0	Chain 1	Chain 2	Chain 3				
1	2412	21.33	21.36	21.34	21.31	543.955	27.36	30.00	Pass
6	2437	23.88	23.77	23.72	23.91	964.117	29.84	30.00	Pass
11	2462	19.46	19.11	19.02	18.81	325.61	25.13	30.00	Pass

VHT20

Chan.	Chan. Freq. (MHz)	Average Power (dBm)				Total Power (mW)	Total Power (dBm)	Limit (dBm)	Pass / Fail
		Chain 0	Chain 1	Chain 2	Chain 3				
1	2412	19.16	18.71	18.83	18.76	308.262	24.89	30.00	Pass
6	2437	23.70	23.79	23.51	23.63	928.818	29.68	30.00	Pass
11	2462	19.14	18.68	18.78	18.42	300.836	24.78	30.00	Pass

VHT40

Chan.	Chan. Freq. (MHz)	Average Power (dBm)				Total Power (mW)	Total Power (dBm)	Limit (dBm)	Pass / Fail
		Chain 0	Chain 1	Chain 2	Chain 3				
3	2422	18.01	17.52	17.89	17.68	239.867	23.80	30.00	Pass
6	2437	19.28	18.94	19.31	19.13	330.222	25.19	30.00	Pass
9	2452	17.95	17.27	17.48	17.23	224.527	23.51	30.00	Pass

802.11ax (HE20)

Chan.	Chan. Freq. (MHz)	Average Power (dBm)				Total Power (mW)	Total Power (dBm)	Limit (dBm)	Pass / Fail
		Chain 0	Chain 1	Chain 2	Chain 3				
1	2412	19.33	18.82	18.97	18.92	318.781	25.03	30.00	Pass
6	2437	23.82	23.91	23.64	23.76	955.918	29.80	30.00	Pass
11	2462	19.28	18.84	18.93	18.56	311.225	24.93	30.00	Pass

802.11ax (HE40)

Chan.	Chan. Freq. (MHz)	Average Power (dBm)				Total Power (mW)	Total Power (dBm)	Limit (dBm)	Pass / Fail
		Chain 0	Chain 1	Chain 2	Chain 3				
3	2422	18.14	17.68	18.03	17.82	247.844	23.94	30.00	Pass
6	2437	19.42	19.04	19.43	19.29	340.284	25.32	30.00	Pass
9	2452	18.07	17.42	17.61	17.36	231.456	23.64	30.00	Pass

Beamforming Mode

VHT20

Chan.	Chan. Freq. (MHz)	Average Power (dBm)				Total Power (mW)	Total Power (dBm)	Limit (dBm)	Pass / Fail
		Chain 0	Chain 1	Chain 2	Chain 3				
1	2412	19.16	18.71	18.83	18.76	308.262	24.89	26.26	Pass
6	2437	20.16	19.84	19.82	19.75	390.482	25.92	26.26	Pass
11	2462	19.14	18.68	18.78	18.42	300.836	24.78	26.26	Pass

Note: 1. Directional gain = $10 \log[(10^{G1/20} + 10^{G2/20} + 10^{G3/20} + 10^{G4/20})^2 / 4]$ = 9.74dBi > 6dBi , so the power limit shall be reduced to $30-(9.74-6) = 26.26$ dBm.

VHT40

Chan.	Chan. Freq. (MHz)	Average Power (dBm)				Total Power (mW)	Total Power (dBm)	Limit (dBm)	Pass / Fail
		Chain 0	Chain 1	Chain 2	Chain 3				
3	2422	18.01	17.52	17.89	17.68	239.867	23.80	26.26	Pass
6	2437	19.28	18.94	19.31	19.13	330.222	25.19	26.26	Pass
9	2452	17.95	17.27	17.48	17.23	224.527	23.51	26.26	Pass

Note: 1. Directional gain = $10 \log[(10^{G1/20} + 10^{G2/20} + 10^{G3/20} + 10^{G4/20})^2 / 4]$ = 9.74dBi > 6dBi , so the power limit shall be reduced to $30-(9.74-6) = 26.26$ dBm.

802.11ax (HE20)

Chan.	Chan. Freq. (MHz)	Average Power (dBm)				Total Power (mW)	Total Power (dBm)	Limit (dBm)	Pass / Fail
		Chain 0	Chain 1	Chain 2	Chain 3				
1	2412	19.33	18.82	18.97	18.92	318.781	25.03	26.26	Pass
6	2437	20.33	19.95	19.96	19.88	403.108	26.05	26.26	Pass
11	2462	19.28	18.84	18.93	18.56	311.225	24.93	26.26	Pass

Note: 1. Directional gain = $10 \log[(10^{G1/20} + 10^{G2/20} + 10^{G3/20} + 10^{G4/20})^2 / 4] = 9.74\text{dBi} > 6\text{dBi}$, so the power limit shall be reduced to $30 - (9.74 - 6) = 26.26 \text{ dBm}$.

802.11ax (HE40)

Chan.	Chan. Freq. (MHz)	Average Power (dBm)				Total Power (mW)	Total Power (dBm)	Limit (dBm)	Pass / Fail
		Chain 0	Chain 1	Chain 2	Chain 3				
3	2422	18.14	17.68	18.03	17.82	247.844	23.94	26.26	Pass
6	2437	19.42	19.04	19.43	19.29	340.284	25.32	26.26	Pass
9	2452	18.07	17.42	17.61	17.36	231.456	23.64	26.26	Pass


Note: 1. Directional gain = $10 \log[(10^{G1/20} + 10^{G2/20} + 10^{G3/20} + 10^{G4/20})^2 / 4] = 9.74\text{dBi} > 6\text{dBi}$, so the power limit shall be reduced to $30 - (9.74 - 6) = 26.26 \text{ dBm}$.

4.5 Power Spectral Density Measurement

4.5.1 Limits of Power Spectral Density Measurement

The Maximum of Power Spectral Density Measurement is 8dBm in any 3 kHz.

4.5.2 Test Setup



4.5.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

4.5.4 Test Procedure

802.11b, 802.11g

- Set instrument center frequency to DTS channel center frequency.
- Set span to at least 1.5 times the OBW.
- Set RBW to: $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$.
- Set VBW $\geq 3 \times \text{RBW}$.
- Detector = power averaging (RMS) or sample detector (when RMS not available).
- Ensure that the number of measurement points in the sweep $\geq 2 \times \text{span}/\text{RBW}$.
- Sweep time = auto couple.
- Employ trace averaging (RMS) mode over a minimum of 100 traces.
- Use the peak marker function to determine the maximum amplitude level.

802.11ax (HE20), 802.11ax (HE40)

- Measure the duty cycle (x).
- Set instrument center frequency to DTS channel center frequency.
- Set span to at least 1.5 times the OBW.
- Set RBW to: $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$.
- Set VBW $\geq 3 \times \text{RBW}$.
- Detector = power averaging (RMS) or sample detector (when RMS not available).
- Ensure that the number of measurement points in the sweep $\geq 2 \times \text{span}/\text{RBW}$.
- Sweep time = auto couple.
- Do not use sweep triggering. Allow sweep to “free run”.
- Employ trace averaging (RMS) mode over a minimum of 100 traces.
- Use the peak marker function to determine the maximum amplitude level.
- Add $10 \log (1/x)$, where x is the duty cycle measured in step (a), to the measured PSD to compute the average PSD during the actual transmission time.

4.5.5 Deviation from Test Standard

No deviation.

4.5.6 EUT Operating Condition

Same as Item 4.3.6

4.5.7 Test Results

802.11b

TX chain	Channel	Freq. (MHz)	PSD (dBm/3kHz)	10 log (N=4) dB	Total PSD (dBm/3kHz)	Limit (dBm/3kHz)	Pass /Fail
0	1	2412	-6.13	6.02	-0.11	4.26	Pass
	6	2437	-6.04	6.02	-0.02	4.26	Pass
	11	2462	-6.82	6.02	-0.80	4.26	Pass
1	1	2412	-7.15	6.02	-1.13	4.26	Pass
	6	2437	-7.27	6.02	-1.25	4.26	Pass
	11	2462	-6.36	6.02	-0.34	4.26	Pass
2	1	2412	-7.24	6.02	-1.22	4.26	Pass
	6	2437	-5.98	6.02	0.04	4.26	Pass
	11	2462	-6.23	6.02	-0.21	4.26	Pass
3	1	2412	-6.24	6.02	-0.22	4.26	Pass
	6	2437	-6.56	6.02	-0.54	4.26	Pass
	11	2462	-6.83	6.02	-0.81	4.26	Pass

Note: 1. Directional gain = $10 \log[(10^{G1/20} + 10^{G2/20} + 10^{G3/20} + 10^{G4/20})^2 / 4] = 9.74\text{dBi} > 6\text{dBi}$, so the power density limit shall be reduced to $8 - (9.74 - 6) = 4.26\text{dBm}$.

802.11g

TX chain	Channel	Freq. (MHz)	PSD (dBm/3kHz)	10 log (N=4) dB	Total PSD (dBm/3kHz)	Limit (dBm/3kHz)	Pass /Fail
0	1	2412	-9.82	6.02	-3.80	4.26	Pass
	6	2437	-6.71	6.02	-0.69	4.26	Pass
	11	2462	-11.57	6.02	-5.55	4.26	Pass
1	1	2412	-10.62	6.02	-4.60	4.26	Pass
	6	2437	-6.61	6.02	-0.59	4.26	Pass
	11	2462	-12.51	6.02	-6.49	4.26	Pass
2	1	2412	-9.58	6.02	-3.56	4.26	Pass
	6	2437	-7.74	6.02	-1.72	4.26	Pass
	11	2462	-11.86	6.02	-5.84	4.26	Pass
3	1	2412	-10.27	6.02	-4.25	4.26	Pass
	6	2437	-7.59	6.02	-1.57	4.26	Pass
	11	2462	-11.89	6.02	-5.87	4.26	Pass

Note: 1. Directional gain = $10 \log[(10^{G1/20} + 10^{G2/20} + 10^{G3/20} + 10^{G4/20})^2 / 4] = 9.74\text{dBi} > 6\text{dBi}$, so the power density limit shall be reduced to $8 - (9.74 - 6) = 4.26\text{dBm}$.

802.11ax (HE20)

TX chain	Channel	Freq. (MHz)	PSD W/O Duty Factor (dBm/3kHz)	10 log (N=4) dB	Duty Factor (dB)	TOTAL PSD With Duty Factor (dBm/3kHz)	Limit (dBm/3kHz)	Pass /Fail
0	1	2412	-12.23	6.02	0.1	-6.11	4.26	Pass
	6	2437	-8.43	6.02	0.1	-2.31	4.26	Pass
	11	2462	-11.75	6.02	0.1	-5.63	4.26	Pass
1	1	2412	-10.13	6.02	0.1	-4.01	4.26	Pass
	6	2437	-9.51	6.02	0.1	-3.39	4.26	Pass
	11	2462	-12.45	6.02	0.1	-6.33	4.26	Pass
2	1	2412	-12.86	6.02	0.1	-6.74	4.26	Pass
	6	2437	-8.26	6.02	0.1	-2.14	4.26	Pass
	11	2462	-12.33	6.02	0.1	-6.21	4.26	Pass
3	1	2412	-11.99	6.02	0.1	-5.87	4.26	Pass
	6	2437	-6.89	6.02	0.1	-0.77	4.26	Pass
	11	2462	-12.50	6.02	0.1	-6.38	4.26	Pass

Note: 1. Directional gain = $10 \log[(10^{G1/20} + 10^{G2/20} + 10^{G3/20} + 10^{G4/20})^2 / 4] = 9.74\text{dBi} > 6\text{dBi}$, so the power density limit shall be reduced to $8-(9.74-6) = 4.26\text{dBm}$.

2. Refer to section 3.3 for duty cycle spectrum plot.

802.11ax (HE40)


TX chain	Channel	Freq. (MHz)	PSD W/O Duty Factor (dBm/3kHz)	10 log (N=4) dB	Duty Factor (dB)	TOTAL PSD With Duty Factor (dBm/3kHz)	Limit (dBm/3kHz)	Pass /Fail
0	3	2422	-16.10	6.02	0.2	-9.88	4.26	Pass
	6	2437	-14.73	6.02	0.2	-8.51	4.26	Pass
	9	2452	-15.45	6.02	0.2	-9.23	4.26	Pass
1	3	2422	-15.90	6.02	0.2	-9.68	4.26	Pass
	6	2437	-16.00	6.02	0.2	-9.78	4.26	Pass
	9	2452	-15.71	6.02	0.2	-9.49	4.26	Pass
2	3	2422	-17.32	6.02	0.2	-11.10	4.26	Pass
	6	2437	-13.39	6.02	0.2	-7.17	4.26	Pass
	9	2452	-16.78	6.02	0.2	-10.56	4.26	Pass
3	3	2422	-16.50	6.02	0.2	-10.28	4.26	Pass
	6	2437	-15.80	6.02	0.2	-9.58	4.26	Pass
	9	2452	-16.87	6.02	0.2	-10.65	4.26	Pass

Note: 1. Directional gain = $10 \log[(10^{G1/20} + 10^{G2/20} + 10^{G3/20} + 10^{G4/20})^2 / 4] = 9.74\text{dBi} > 6\text{dBi}$, so the power density limit shall be reduced to $8-(9.74-6) = 4.26\text{dBm}$.


2. Refer to section 3.3 for duty cycle spectrum plot.

Spectrum Plot of Worst Value


802.11b / Chain 2: CH6




802.11g / Chain 1 : CH6



802.11ax (HE20) / Chain 3: CH6



802.11ax (HE40) / Chain 2: CH6




4.6 Conducted Out of Band Emission Measurement

4.6.1 Limits of Conducted Out of Band Emission Measurement

Below -30dB of the highest emission level of operating band (in 100kHz Resolution Bandwidth).

4.6.2 Test Setup



4.6.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

4.6.4 Test Procedure

MEASUREMENT PROCEDURE REF

1. Set the RBW = 100 kHz.
2. Set the VBW \geq 300 kHz.
3. Detector = peak.
4. Sweep time = auto couple.
5. Trace mode = max hold.
6. Allow trace to fully stabilize.
7. Use the peak marker function to determine the maximum power level in any 100 kHz band segment within the fundamental EBW.

MEASUREMENT PROCEDURE OOBE

1. Set RBW = 100 kHz.
2. Set VBW \geq 300 kHz.
3. Detector = peak.
4. Sweep = auto couple.
5. Trace Mode = max hold.
6. Allow trace to fully stabilize.
7. Use the peak marker function to determine the maximum amplitude level.

4.6.5 Deviation from Test Standard

No deviation.


4.6.6 EUT Operating Condition

Same as Item 4.3.6

4.6.7 Test Results


The spectrum plots are attached on the following pages. D1 line indicates the highest level, and D2 line indicates the 30dB offset below D1. It shows compliance with the requirement.

802.11b




Chain 0


CH 1




CH 6




CH 11




CH 11 Band edge



CH 1 Band edge




CH 11 Band edge




Chain 1


CH 1




CH 6




CH 11



CH 1 Band edge




CH 11 Band edge




Chain 2


CH 1




CH 6




CH 11



CH 1 Band edge




CH 11 Band edge




Chain 3


CH 1




CH 6




CH 11



CH 1 Band edge




CH 11 Band edge




802.11g

Maximum REF




Chain 0


CH 1




CH 6




CH 11



CH 1 Band edge




CH 11 Band edge




Chain 1



CH 1




CH 6




CH 11



CH 1 Band edge




CH 11 Band edge




Chain 2



CH 1




CH 6




CH 11



CH 1 Band edge




CH 11 Band edge




Chain 3



CH 1




CH 6




CH 11




CH 1 Band edge



CH 11 Band edge




802.11ax (HE20)




Chain 0


CH 1




CH 6




CH 11









CH 1 Band edge



CH 11 Band edge




Chain 1




Chain 2


CH 1




CH 6




CH 11



CH 1 Band edge




CH 11 Band edge




Chain 3



CH 1




CH 6




CH 11



CH 1 Band edge




CH 11 Band edge




802.11ax (HE40)

Maximum REF




Chain 0


CH 3




CH 6




CH 9



CH 3 Band edge




CH 9 Band edge




Chain 1



CH 3




CH 6




CH 9



CH 3 Band edge




CH 9 Band edge




Chain 2



CH 3




CH 6




CH 9



CH 3 Band edge




CH 9 Band edge




Chain 3


CH 3




CH 6




CH 9



CH 3 Band edge



CH 9 Band edge



5 Pictures of Test Arrangements

Please refer to the attached file (Test Setup Photo).

Appendix – Information of the Testing Laboratories

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are FCC recognized accredited test firms and accredited according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

Lin Kou EMC/RF Lab

Tel: 886-2-26052180

Fax: 886-2-26051924

Hsin Chu EMC/RF/Telecom Lab

Tel: 886-3-6668565

Fax: 886-3-6668323

Hwa Ya EMC/RF/Safety Lab

Tel: 886-3-3183232

Fax: 886-3-3270892

Email: service.adt@tw.bureauveritas.com

Web Site: www.bureauveritas-adt.com

The address and road map of all our labs can be found in our web site also.

--- END ---