

## Supplemental “Transmit Simultaneously” Test Report

**Report No.:** RFBHQC-WTW-P22080379A-2

**FCC ID:** XCNUBN2309

**Test Model:** UBN2309

**Series Model:** XSR250GK

**Received Date:** 2023/2/3

**Test Date:** 2023/2/3 ~ 2023/6/29

**Issued Date:** 2023/7/25

**Applicant:** Ubee Interactive Holding Corp. Taiwan Branch

**Address:** 10F-1, No.5, Taiyuan 1st St. Jhubei, Hsinchu, 302, Taiwan

**Issued By:** Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch  
Lin Kou Laboratories

**Lab Address:** No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan

**Test Location:** No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan

**FCC Registration /  
Designation Number:** 198487 / TW2021



This report is governed by, and incorporates by reference, the Conditions of Testing as posted at the date of issuance of this report at <http://www.bureauveritas.com/home/about-us/our-business/cps/about-us/terms-conditions/>, and is intended for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. Measurement uncertainty is only provided upon request for accredited tests. Statements of conformity are based on simple acceptance criteria without taking measurement uncertainty into account, unless otherwise requested in writing. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence or if you require measurement uncertainty; provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents.

## Table of Contents

<b>Release Control Record</b> .....	<b>3</b>
<b>1 Certificate of Conformity</b> .....	<b>4</b>
<b>2 Summary of Test Results</b> .....	<b>5</b>
2.1 Measurement Uncertainty .....	5
2.2 Modification Record .....	5
<b>3 General Information</b> .....	<b>6</b>
3.1 General Description of EUT .....	6
3.1.1 Test Mode Applicability and Tested Channel Detail .....	9
3.2 Description of Support Units .....	11
3.2.1 Configuration of System under Test .....	12
<b>4 Test Types and Results</b> .....	<b>13</b>
4.1 Radiated Emission and Bandedge Measurement .....	13
4.1.1 Limits of Radiated Emission and Bandedge Measurement .....	13
4.1.2 Test Instruments .....	14
4.1.3 Test Procedures .....	16
4.1.4 Deviation from Test Standard .....	16
4.1.5 Test Setup .....	17
4.1.6 EUT Operating Conditions .....	18
4.1.7 Test Results .....	19
4.2 Conducted Emission Measurement .....	22
4.2.1 Limits of Conducted Emission Measurement .....	22
4.2.2 Test Instruments .....	22
4.2.3 Test Procedures .....	23
4.2.4 Deviation from Test Standard .....	23
4.2.5 Test Setup .....	23
4.2.6 EUT Operating Conditions .....	23
4.2.7 Test Results .....	24
4.3 Conducted Out of Band Emission Measurement .....	26
4.3.1 Limits of Conducted Out of Band Emission Measurement .....	26
4.3.2 Test Setup .....	26
4.3.3 Test Instruments .....	26
4.3.4 Test Procedures .....	26
4.3.5 Deviation from Test Standard .....	26
4.3.6 EUT Operating Conditions .....	26
4.3.7 Test Results .....	26
<b>5 Pictures of Test Arrangements</b> .....	<b>28</b>
<b>Appendix – Information of the Testing Laboratories</b> .....	<b>29</b>

### Release Control Record

Issue No.	Description	Date Issued
RFBHQC-WTW-P22080379A-2	Original release.	2023/7/25

## 1 Certificate of Conformity

**Product:** XGS-PON

**Brand:** 

**Test Model:** UBN2309

**Series Model:** XSR250GK

**Sample Status:** Mass product

**Applicant:** Ubee Interactive Holding Corp. Taiwan Branch

**Test Date:** 2023/2/3 ~ 2023/6/29

**Standards:** 47 CFR FCC Part 15, Subpart C (Section 15.247)  
47 CFR FCC Part 15, Subpart E (Section 15.407)  
ANSI C63.10: 2013

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

**Prepared by :**                     Vito Lung                     , **Date:**                     2023/7/25                      
Vito Lung / Specialist

**Approved by :**                     Wen Yu                     , **Date:**                     2023/7/25                      
Wen Yu / Assistant Manager

## 2 Summary of Test Results

FCC Part 15, Subpart C, E (SECTION 15.247, 15.407)			
FCC Clause	Test Item	Result	Remarks
15.207 15.407(b)(6)	AC Power Conducted Emission	PASS	Meet the requirement of limit. Minimum passing margin is -12.93 dB at 0.43125 MHz.
15.205 / 15.209 / 15.247(d) 15.407(b) (1/2/3/4(i/ii)/6)	Radiated Emissions and Band Edge Measurement	PASS	Meet the requirement of limit. Minimum passing margin is -3.3 dB at 650.00 MHz.

Note:

Determining compliance based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.

### 2.1 Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:


Measurement	Frequency	Expanded Uncertainty (k=2) ( $\pm$ )
Conducted Emissions at mains ports	150kHz ~ 30MHz	3.00 dB
Conducted emissions	-	2.63 dB
Radiated Emissions up to 1 GHz	9kHz ~ 30MHz	2.38 dB
	30MHz ~ 1GHz	5.7 dB
Radiated Emissions above 1 GHz	1 GHz ~ 6 GHz	4.83 dB
	1GHz ~ 18GHz	5.37 dB
	18GHz ~ 40GHz	5.24 dB

### 2.2 Modification Record

There were no modifications required for compliance.


### 3 General Information

#### 3.1 General Description of EUT

Product	XGS-PON
Brand	
Test Model	UBN2309
Series Model	XSR250GK
Status of EUT	Mass product
Power Supply Rating	12 Vdc from power adapter
Modulation Type	<b>WLAN:</b> CCK, DQPSK, DBPSK for DSSS 64QAM, 16QAM, QPSK, BPSK for OFDM 256QAM for OFDM in VHT mode 1024QAM for OFDMA in 11ax mode only
Modulation Technology	<b>WLAN:</b> DSSS, OFDM, OFDMA
Transfer Rate	<b>WLAN:</b> 802.11b: up to 11 Mbps 802.11a/g: up to 54 Mbps 802.11n: up to 600 Mbps 802.11ac: up to 3466.7 Mbps 802.11ax: up to 4803.9 Mbps
Operating Frequency	<b>2.4GHz:</b> 2.412 ~ 2.462 GHz <b>5GHz:</b> 5.18 ~ 5.25 GHz 5.25 ~ 5.32 GHz 5.50 ~ 5.72 GHz 5.745 ~ 5.825 GHz <b>6GHz:</b> 5.955 ~ 6.145 GHz 6.435 ~ 6.525 GHz 6.535 ~ 6.865 GHz 6.875 ~ 7.115 GHz
Number of Channel	<b>2.4GHz:</b> 802.11b, 802.11g, 802.11n (HT20), VHT20, 802.11ax (HE20): 11 802.11n (HT40), VHT40, 802.11ax (HE40): 7 <b>5GHz:</b> 802.11a, 802.11n (HT20), 802.11ac (VHT20), 802.11ax (HE20): 25 802.11n (HT40), 802.11ac (VHT40), 802.11ax (HE40): 12 802.11ac (VHT80), 802.11ax (HE80): 6 802.11ac (VHT160), 802.11ax (HE160): 2 <b>6GHz:</b> 802.11a, 802.11ax (HE20): 59 802.11ax (HE40): 29 802.11ax (HE80): 14 802.11ax (HE160): 7
Antenna Type	Refer to Note
Antenna Connector	Refer to Note
Accessory Device	Adapter x 1
Data Cable Supplied	NA

Note:

1. All models are listed as below.

Brand	Model	Difference
	UBN2309	All models are electrically identical, different model names are for marketing purpose.
	XSR250GK	

From the above models, model: UBN2309 was selected as representative model for the test and its data was recorded in this report.

2. The EUT has three radios as following table:

Radio 1	Radio 2	Radio 3
WLAN(2.4GHz)	WLAN(5GHz)	WLAN(6GHz)

3. Simultaneously transmission condition.

Condition	Technology		
1	WLAN(2.4GHz)	WLAN(5GHz)	WLAN(6GHz)

Note: The emission of the simultaneous operation has been evaluated and no non-compliance was found.

4. The EUT uses following accessories.

Brand	Model	Specification
MOSO	MSS-V3500WR120-042A0-US	AC Input : 100-240Vac, 50/60Hz 1.2A DC Output : 12.0Vdc, 3.5A DC Output Cable : 1.8m non-shielded, without core.

5. The antenna information is listed as below.

Antenna NO.	RF Chain NO.	Brand	Antenna Net Gain(dBi)	Frequency range	Antenna Type	Connector Type
DB1	5G Chain 3	WHA YU	3.72	5.15~5.85GHz	Dipole	ipex(MHF)
DB2	2.4G Chain 0 5G Chain 0	WHA YU	3.32	2.4~2.4835GHz	Dipole	ipex(MHF)
		WHA YU	3.8	5.15~5.85GHz	Dipole	ipex(MHF)
DB3	2.4G Chain 1 5G Chain 1	WHA YU	2.93	2.4~2.4835GHz	Dipole	ipex(MHF)
		WHA YU	3.79	5.15~5.85GHz	Dipole	ipex(MHF)
DB4	2.4G Chain 2 5G Chain 2	WHA YU	3.40	2.4~2.4835GHz	Dipole	ipex(MHF)
		WHA YU	3.79	5.15~5.85GHz	Dipole	ipex(MHF)
6G5	6G Chain 3	WHA YU	3.34	5.925GHz~7.125GHz	Dipole	ipex(MHF)
6G6	6G Chain 2	WHA YU	3.49	5.925GHz~7.125GHz	Dipole	ipex(MHF)
6G7	6G Chain 1	WHA YU	3.47	5.925GHz~7.125GHz	Dipole	ipex(MHF)
6G8	6G Chain 0	WHA YU	3.49	5.925GHz~7.125GHz	Dipole	ipex(MHF)

6. The EUT incorporates a MIMO function.

2.4GHz Band		
MODULATION MODE	TX & RX CONFIGURATION	
802.11b	3TX	3RX
802.11g	3TX	3RX
802.11n (HT20)	3TX	3RX
802.11n (HT40)	3TX	3RX
VHT20	3TX	3RX
VHT40	3TX	3RX
802.11ax (HE20)	3TX	3RX
802.11ax (HE40)	3TX	3RX
5GHz Band		
MODULATION MODE	TX & RX CONFIGURATION	
802.11a	4TX	4RX
802.11n (HT20)	4TX	4RX
802.11n (HT40)	4TX	4RX
802.11ac (VHT20)	4TX	4RX
802.11ac (VHT40)	4TX	4RX
802.11ac (VHT80)	4TX	4RX
802.11ax (HE20)	4TX	4RX
802.11ax (HE40)	4TX	4RX
802.11ax (HE80)	4TX	4RX
802.11ax (HE160)	4TX	4RX
6GHz Band		
MODULATION MODE	TX & RX CONFIGURATION	
802.11a	4TX	4RX
802.11ax (HE20)	4TX	4RX
802.11ax (HE40)	4TX	4RX
802.11ax (HE80)	4TX	4RX
802.11ax (HE160)	4TX	4RX

7. The above EUT information is declared by manufacturer and for more detailed features description, please refers to the manufacturer's specifications or user's manual.

8. Detail antenna specification please refer to antenna datasheet and/or antenna measurement report.



### 3.1.1 Test Mode Applicability and Tested Channel Detail

EUT Configure Mode	Applicable To				Description
	RE $\geq$ 1G	RE<1G	PLC	OB	
-	√	√	√	√	-

Where **RE $\geq$ 1G**: Radiated Emission above 1GHz  
**RE<1G**: Radiated Emission below 1GHz  
**PLC**: Power Line Conducted Emission  
**OB**: Conducted Out-Band Emission Measurement

Note: The EUT had been pre-tested on the positioned of laying-flat and wall-mount. The worst case was found when positioned on Wall Mount.

#### **Radiated Emission Test (Above 1GHz):**

- The tested configurations represent the worst-case mode from all possible combinations by the maximum power.
- Following channel(s) was (were) selected for the final test as listed below.

MODE	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE
2.4GHz: 802.11b +	6	DSSS	DBPSK
5GHz: 802.11a +	157	OFDMA	BPSK
6GHz: 802.11ax (HE160)	15	OFDMA	BPSK

#### **Radiated Emission Test (Below 1GHz):**

- The tested configurations represent the worst-case mode from all possible combinations by the maximum power.

MODE	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE
2.4GHz: 802.11b +	6	DSSS	DBPSK
5GHz: 802.11a +	157	OFDMA	BPSK
6GHz: 802.11ax (HE160)	15	OFDMA	BPSK

#### **Power Line Conducted Emission Test:**

- The tested configurations represent the worst-case mode from all possible combinations by the maximum power.
- Following channel(s) was (were) selected for the final test as listed below.

MODE	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE
2.4GHz: 802.11b +	6	DSSS	DBPSK
5GHz: 802.11a +	157	OFDMA	BPSK
6GHz: 802.11ax (HE160)	15	OFDMA	BPSK

**Conducted Out-Band Emission Measurement:**

- The tested configurations represent the worst-case mode from all possible combinations by the maximum power.
- Following channel(s) was (were) selected for the final test as listed below.

MODE	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE
2.4GHz: 802.11b + 5GHz: 802.11a + 6GHz: 802.11ax (HE160)	6	DSSS	DBPSK
	157	OFDMA	BPSK
	15	OFDMA	BPSK

**Test Condition:**

Applicable To	Environmental Conditions	INPUT POWER	Tested By
RE $\geq$ 1G	25deg. C, 66%RH	120Vac, 60Hz	Sampson Chen
RE $<$ 1G	24deg. C, 66%RH	120Vac, 60Hz	Tom Yang
PLC	24deg. C, 71%RH	120Vac, 60Hz	Sampson Chen
OB	25deg. C, 65%RH	120Vac, 60Hz	Katina Lu


### 3.2 Description of Support Units

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

ID	Product	Brand	Model No.	Serial No.	FCC ID	Remarks
A	TELEPHONE	Romeo	TE-812	97285638	N/A	Provided by Lab
B	TELEPHONE	Romeo	TE-812	97280903	N/A	Provided by Lab
C	Laptop	Lenovo	20U5S01X00 L14	PF-1ANPYA	N/A	Provided by Lab
D	Switch	D-Link	DGS-1005D	DR8WC92000523	N/A	Provided by Lab
E	Laptop	Lenovo	20U5S01X00 L14	PF-28LKK7	N/A	Provided by Lab
F	USB 3.0 Disk	SanDisk	BM181225896Z	N/A	N/A	Provided by Lab

ID	Cable Descriptions	Qty.	Length (m)	Shielding (Yes/No)	Cores (Qty.)	Remarks
1	DC Cable	1	1.8	No	0	Supplied by applicant
2	RJ-11 Cable	1	10	No	0	Provided by Lab
3	RJ-11 Cable	1	10	No	0	Provided by Lab
4	RJ-45 Cable	1	10	No	0	Provided by Lab
5	RJ-45 Cable	3	10	No	0	Provided by Lab
6	RJ-45 Cable	1	10	No	0	Provided by Lab
7	Fiber Cable	1	10	No	0	Provided by Lab

### 3.2.1 Configuration of System under Test



## 4 Test Types and Results

### 4.1 Radiated Emission and Bandedge Measurement

#### 4.1.1 Limits of Radiated Emission and Bandedge Measurement

Radiated emissions which fall in the restricted bands must comply with the radiated emission limits specified as below table.

Frequencies (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

#### Note:

- The lower limit shall apply at the transition frequencies.
- Emission level (dBuV/m) = 20 log Emission level (uV/m).
- For frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.

#### Limits of unwanted emission out of the restricted bands

Applicable To		Limit	
789033 D02 General UNII Test Procedure New Rules v02r01		Field Strength at 3m	
		PK:74 (dBμV/m)	AV:54 (dBμV/m)
Frequency Band	Applicable To	EIRP Limit	Equivalent Field Strength at 3m
5150~5250 MHz	15.407(b)(1)	PK:-27 (dBm/MHz)	PK:68.2(dBμV/m)
5250~5350 MHz	15.407(b)(2)		
5470~5725 MHz	15.407(b)(3)		
5725~5850 MHz	15.407(b)(4)(i)	PK:-27 (dBm/MHz) <sup>*1</sup> PK:10 (dBm/MHz) <sup>*2</sup> PK:15.6 (dBm/MHz) <sup>*3</sup> PK:27 (dBm/MHz) <sup>*4</sup>	PK: 68.2(dBμV/m) <sup>*1</sup> PK:105.2 (dBμV/m) <sup>*2</sup> PK: 110.8(dBμV/m) <sup>*3</sup> PK:122.2 (dBμV/m) <sup>*4</sup>
*1 beyond 75 MHz or more above of the band edge.		*2 below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above.	
*3 below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above.		*4 from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.	

#### Note:

The following formula is used to convert the equipment isotropic radiated power (eirp) to field strength:

$$E = \frac{1000000\sqrt{30P}}{3} \mu\text{V/m, where P is the eirp (Watts).}$$

#### 4.1.2 Test Instruments

##### For Radiated emission test:

Description & Manufacturer	Model No.	Serial No.	Calibrated Date	Calibrated Until
MXE EMI Receiver Keysight	N9030B	MY59050100	2022/6/20 2023/3/6	2023/6/19 2024/3/5
Software	ADT_Radiated_V8.7.08	NA	NA	NA
Boresight Antenna Tower & Turn Table Max-Full	MF-7802BS	MF780208530	NA	NA
Pre_Amplifier Agilent	EMC001340	980142	2022/6/2 2023/5/8	2023/6/1 2024/5/7
LOOP ANTENNA Electro-Metrics	EM-6879	264	2022/3/18 2023/2/21	2023/3/17 2024/2/20
RF Coaxial Cable JYEBO	5D-FB	LOOPCAB-001	2022/12/19	2023/12/18
RF Coaxial Cable JYEBO	5D-FB	LOOPCAB-002	2022/12/19	2023/12/18
Pre_Amplifier EMCI	EMC330N	980852	2022/3/28 2023/2/20	2023/3/27 2024/2/19
Trilog Broadband Antenna Schwarzbeck	VULB 9168	9168-406	2022/10/21	2023/10/20
RF Coaxial Cable COMMATE/PEWC	8D	966-6-1	2022/4/25 2023/4/6	2023/4/24 2024/4/5
RF Coaxial Cable COMMATE/PEWC	8D	966-6-2	2022/4/25 2023/4/6	2023/4/24 2024/4/5
RF Coaxial Cable COMMATE/PEWC	8D	966-6-3	2022/4/25 2023/4/6	2023/4/24 2024/4/5
Fixed attenuator Mini-Circuits	UNAT-5+	PAD-ATT5-03	2022/12/28	2023/12/27
Horn Antenna Schwarzbeck	BBHA 9120D	9120D-783	2022/11/13	2023/11/12
Pre_Amplifier EMCI	EMC12630SE	980385	2022/10/4	2023/10/3
RF Cable-Frequency Range : 1-26.5GHz EMCI	EMC104-SM-SM-1200	160922	2022/12/15	2023/12/14
RF Coaxial Cable EMCI	EMC104-SM-SM-6000	210704	2022/11/4	2023/11/3
Pre_Amplifier EMCI	EMC184045SE	980387	2022/12/28	2023/12/27
Horn Antenna Schwarzbeck	BBHA 9170	9170-739	2022/11/13	2023/11/12
RF Cable-Frequency range: 1-40GHz EMCI	EMC102-KM-KM-1200	160924	2022/12/28	2023/12/27
RF Coaxial Cable EMCI	EMC-KM-KM-4000	200214	2022/3/8 2023/2/20	2023/3/7 2024/2/19

##### Note:

1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. The test was performed in Linkou 966 Chamber 6 (CH 6).
3. Tested Date: 2023/2/3 ~ 2023/6/29

**For other test**

Description & Manufacturer	Model no.	Serial No.	Calibrated DATE	Calibrated Until
Spectrum Analyzer Keysight	N9020B	MY60112409	2022/3/11	2023/3/10
Attenuator WOKEN	MDCS18N-10	MDCS18N-10-01	2022/4/5	2023/4/4
Software	ADT_RF Test Software V6.6.5.4	NA	NA	NA

- NOTE:**
1. The test was performed in Oven room.
  2. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
  3. Tested Date: 2023/2/3

#### 4.1.3 Test Procedures

##### **For Radiated emission below 30MHz**

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter chamber room. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. Parallel, perpendicular, and ground-parallel orientations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Quasi-Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.

##### **NOTE:**

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 9kHz at frequency below 30MHz.

##### **For Radiated emission above 30MHz**

- a. The EUT was placed on the top of a rotating table 0.8 meters (for 30MHz ~ 1GHz) / 1.5 meters (for above 1GHz) above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.
- f. The test-receiver system was set to peak and average detects function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz. If the peak reading value also meets average limit, measurement with the average detector is unnecessary.

##### **Note:**

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection (QP) at frequency below 1GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz for Peak detection (PK) at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is  $\geq 1/T$  (Duty cycle < 98%) or 10Hz (Duty cycle  $\geq 98\%$ ) for Average detection (AV) at frequency above 1GHz.
4. All modes of operation were investigated and the worst-case emissions are reported.


#### 4.1.4 Deviation from Test Standard

No deviation.




#### 4.1.5 Test Setup


##### For Radiated emission below 30MHz



##### For Radiated emission 30MHz to 1GHz



**For Radiated emission above 1GHz**



For the actual test configuration, please refer to the attached file (Test Setup Photo).

**4.1.6 EUT Operating Conditions**

- a. Connected the EUT with the Laptop Computer which is placed on remote site.
- b. Controlling software (accessMTool\_REL\_3\_3\_0\_0) has been activated to set the EUT under transmission condition continuously at specific channel frequency.

#### 4.1.7 Test Results

##### Above 1GHz Data:

<b>FREQUENCY RANGE</b>	1GHz ~ 40GHz	<b>DETECTOR FUNCTION</b>	Peak (PK) Average (AV)
------------------------	--------------	--------------------------	---------------------------

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	4874.00	48.6 QP	74.0	-25.4	1.73 H	141	44.3	4.3
2	4874.00	47.9 QP	54.0	-6.1	1.73 H	141	43.6	4.3
3	7311.00	47.1 QP	74.0	-26.9	1.77 H	295	36.8	10.3
4	7311.00	43.2 QP	54.0	-10.8	1.77 H	295	32.9	10.3
5	11570.00	53.4 QP	74.0	-20.6	2.37 H	18	36.3	17.1
6	11570.00	42.8 QP	54.0	-11.2	2.37 H	18	25.7	17.1
7	12050.00	55.7 QP	74.0	-18.3	1.55 H	294	39.4	16.3
8	12050.00	42.8 QP	54.0	-11.2	1.55 H	294	26.5	16.3
9	17355.00	56.4 QP	68.2	-11.8	3.14 H	339	35.3	21.1
10	18075.00	53.5 QP	74.0	-20.5	1.63 H	137	73.2	-19.7
11	18075.00	43.6 QP	54.0	-10.4	1.63 H	137	63.3	-19.7

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	4874.00	46.3 QP	74.0	-27.7	2.87 V	83	42.0	4.3
2	4874.00	44.2 QP	54.0	-9.8	2.87 V	83	39.9	4.3
3	7311.00	44.5 QP	74.0	-29.5	1.41 V	110	34.2	10.3
4	7311.00	38.3 QP	54.0	-15.7	1.41 V	110	28.0	10.3
5	11570.00	55.1 QP	74.0	-18.9	2.10 V	91	38.0	17.1
6	11570.00	43.6 QP	54.0	-10.4	2.10 V	91	26.5	17.1
7	12050.00	55.0 QP	74.0	-19.0	1.94 V	288	38.7	16.3
8	12050.00	42.3 QP	54.0	-11.7	1.94 V	288	26.0	16.3
9	17355.00	53.1 QP	68.2	-15.1	2.11 V	131	32.0	21.1
10	18075.00	53.7 QP	74.0	-20.3	1.57 V	307	73.4	-19.7
11	18075.00	43.6 QP	54.0	-10.4	1.57 V	307	63.3	-19.7

#### Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.

Below 1GHz Data:


<b>FREQUENCY RANGE</b>	30MHz ~ 1GHz	<b>DETECTOR FUNCTION</b>	Quasi-Peak (QP)
------------------------	--------------	--------------------------	-----------------

**Antenna Polarity & Test Distance : Horizontal at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	105.78	35.3 QP	43.5	-8.2	3.00 H	258	51.6	-16.3
2	185.05	29.6 QP	43.5	-13.9	1.50 H	78	44.2	-14.6
3	375.42	38.1 QP	46.0	-7.9	1.00 H	290	48.4	-10.3
4	449.99	33.3 QP	46.0	-12.7	2.00 H	114	41.4	-8.1
5	550.02	40.9 QP	46.0	-5.1	1.50 H	305	47.6	-6.7
<b>6</b>	<b>650.00</b>	<b>42.7 QP</b>	<b>46.0</b>	<b>-3.3</b>	<b>1.00 H</b>	<b>83</b>	<b>47.0</b>	<b>-4.3</b>

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit of frequency range 30 MHz ~ 1 GHz.
5. The emission levels were very low against the limit of frequency range 9 kHz ~ 30 MHz: the amplitude of spurious emissions attenuated more than 20 dB below the permissible value to be report.




<b>FREQUENCY RANGE</b>	30MHz ~ 1GHz	<b>DETECTOR FUNCTION</b>	Quasi-Peak (QP)
------------------------	--------------	--------------------------	-----------------

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	40.94	33.4 QP	40.0	-6.6	1.00 V	190	46.1	-12.7
2	105.71	32.9 QP	43.5	-10.6	1.00 V	254	49.2	-16.3
3	187.65	24.4 QP	43.5	-19.1	2.00 V	248	39.3	-14.9
4	375.44	40.5 QP	46.0	-5.5	1.50 V	145	50.8	-10.3
5	549.99	41.0 QP	46.0	-5.0	1.00 V	264	47.7	-6.7
6	650.00	41.5 QP	46.0	-4.5	1.00 V	253	45.8	-4.3

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit of frequency range 30 MHz ~ 1 GHz.
5. The emission levels were very low against the limit of frequency range 9 kHz ~ 30 MHz: the amplitude of spurious emissions attenuated more than 20 dB below the permissible value to be report.



## 4.2 Conducted Emission Measurement

### 4.2.1 Limits of Conducted Emission Measurement

Frequency (MHz)	Conducted Limit (dBuV)	
	Quasi-peak	Average
0.15 - 0.5	66 - 56	56 - 46
0.50 - 5.0	56	46
5.0 - 30.0	60	50

Note: 1. The lower limit shall apply at the transition frequencies.

2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

### 4.2.2 Test Instruments

Description Manufacturer	Model No.	Serial No.	Calibrated Date	Calibrated Until
TEST RECEIVER R&S	ESCS 30	847124/029	2022/10/14	2023/10/13
LISN R&S	ESH3-Z5	848773/004	2022/10/18	2023/10/17
50 ohm terminal resistance NA	NA	EMC-01	2022/9/27	2023/9/26
RF Coaxial Cable JYEBO	5D-FB	COCCAB-001	2022/8/24	2023/8/23
Fixed attenuator STI	STI02-2200-10	005	2022/8/24	2023/8/23
Software BVADT	BVADT_Cond_V7.3.7.4	NA	NA	NA

Note: 1. The test was performed in Conduction 1.

2. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

3. Tested Date: 2023/2/3

#### 4.2.3 Test Procedures


- The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- The frequency range from 150kHz to 30MHz was searched. Emission levels under (Limit - 20dB) was not recorded.

**Note:** The resolution bandwidth and video bandwidth of test receiver is 9kHz for quasi-peak detection (QP) and average detection (AV) at frequency 0.15MHz-30MHz.

#### 4.2.4 Deviation from Test Standard

No deviation.

#### 4.2.5 Test Setup



**Note:** 1.Support units were connected to second LISN.

For the actual test configuration, please refer to the attached file (Test Setup Photo).

#### 4.2.6 EUT Operating Conditions

Same as 4.1.6.


#### 4.2.7 Test Results

Phase	Line (L)	Detector Function	Quasi-Peak (QP) / Average (AV)
-------	----------	-------------------	--------------------------------

Phase Of Power : Line (L)										
No	Frequency (MHz)	Correction Factor (dB)	Reading Value (dBuV)		Emission Level (dBuV)		Limit (dBuV)		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.15781	9.95	42.30	28.87	52.25	38.82	65.58	55.58	-13.33	-16.76
2	0.17734	9.96	36.30	21.61	46.26	31.57	64.61	54.61	-18.35	-23.04
3	0.23594	9.96	27.71	15.21	37.67	25.17	62.24	52.24	-24.57	-27.07
4	0.28281	9.96	26.60	16.44	36.56	26.40	60.73	50.73	-24.17	-24.33
<b>5</b>	<b>0.43125</b>	<b>9.96</b>	<b>27.67</b>	<b>24.34</b>	<b>37.63</b>	<b>34.30</b>	<b>57.23</b>	<b>47.23</b>	<b>-19.60</b>	<b>-12.93</b>
6	17.09766	11.03	18.59	14.50	29.62	25.53	60.00	50.00	-30.38	-24.47

#### Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level – Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value






Phase	Neutral (N)	Detector Function	Quasi-Peak (QP) / Average (AV)
-------	-------------	-------------------	--------------------------------

Phase Of Power : Neutral (N)										
No	Frequency (MHz)	Correction Factor (dB)	Reading Value (dBuV)		Emission Level (dBuV)		Limit (dBuV)		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.15000	9.95	41.97	26.51	51.92	36.46	66.00	56.00	-14.08	-19.54
2	0.16172	9.95	38.76	24.93	48.71	34.88	65.38	55.38	-16.67	-20.50
3	0.19297	9.96	32.33	19.07	42.29	29.03	63.91	53.91	-21.62	-24.88
4	0.30625	9.96	24.44	12.68	34.40	22.64	60.07	50.07	-25.67	-27.43
5	0.43906	9.96	19.56	9.76	29.52	19.72	57.08	47.08	-27.56	-27.36
6	17.17188	10.86	18.07	14.01	28.93	24.87	60.00	50.00	-31.07	-25.13

**Remarks:**

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level – Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value




### 4.3 Conducted Out of Band Emission Measurement

#### 4.3.1 Limits of Conducted Out of Band Emission Measurement

Below 20dB of the highest emission level of operating band (in 100kHz Resolution Bandwidth).

#### 4.3.2 Test Setup



#### 4.3.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

#### 4.3.4 Test Procedures

##### MEASUREMENT PROCEDURE REF

1. Set the RBW = 100 kHz.
2. Set the VBW  $\geq$  300 kHz.
3. Detector = peak.
4. Sweep time = auto couple.
5. Trace mode = max hold.
6. Allow trace to fully stabilize.
7. Use the peak marker function to determine the maximum power level in any 100 kHz band segment within the fundamental EBW.

##### MEASUREMENT PROCEDURE OOBE

1. Set RBW = 100 kHz.
2. Set VBW  $\geq$  300 kHz.
3. Detector = peak.
4. Sweep = auto couple.
5. Trace Mode = max hold.
6. Allow trace to fully stabilize.
7. Use the peak marker function to determine the maximum amplitude level.

#### 4.3.5 Deviation from Test Standard

No deviation.


#### 4.3.6 EUT Operating Conditions

The software provided by client to enable the EUT under transmission condition continuously at specific channel frequencies individually.

#### 4.3.7 Test Results

The spectrum plots are attached on the following pages. D1 line indicates the highest level, and D2 line indicates the 20dB offset below D1. It shows compliance with the requirement.

2.4GHz\_802.11b CH6 + 5GHz\_802.11a CH157 + 6GHz\_802.11ax (HE160) CH15



## 5 Pictures of Test Arrangements

Please refer to the attached file (Test Setup Photo).

## Appendix – Information of the Testing Laboratories

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are FCC recognized accredited test firms and accredited according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

**Lin Kou EMC/RF Lab**

Tel: 886-2-26052180

Fax: 886-2-26051924

**Hsin Chu EMC/RF/Telecom Lab**

Tel: 886-3-6668565

Fax: 886-3-6668323

**Hwa Ya EMC/RF/Safety Lab**

Tel: 886-3-3183232

Fax: 886-3-3270892

**Email:** [service.adt@tw.bureauveritas.com](mailto:service.adt@tw.bureauveritas.com)

**Web Site:** [www.bureauveritas-adt.com](http://www.bureauveritas-adt.com)

The address and road map of all our labs can be found in our web site also.

--- END ---