



## Statement of compliance to Maximum Permissible Exposure (MPE)

Applicant : Hansong (Nanjing) Technology Ltd.  
8th Kangping Road, Jiangning Economy and Technology  
Development Zone, Nanjing, 211100, China

Manufacturer : Same as applicant

Equipment : Wi-Fi Speaker

Type/Model : 56Droplet AirDock

**According to §2.1091, §2.1093 and §1.1307(b), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.**

The  $S = PG / (4\pi R^2)$

Where  $S$  = power density in mW/cm<sup>2</sup>

$P$  = transmit power in mW

$G$  = numeric gain of transmit antenna

$R$  = distance (cm)

$R$  is chosen to be 20cm, the gain of antenna  $G = 1.50\text{dBi} = 1.412$

As we can see from the test reports 130701102SHA-001:

The maximum output power for Wi-Fi = 16.14dBm = 41.11mW

The MPE of Wi-Fi =  $PG / (4\pi R^2) = 41.11 * 1.412 / (4 * 3.14 * 20 * 20) = 0.0115$

This level is below the transmission MPE test exclusion requirements ( $\leq 1.0$ ).

Date of issue: December 5, 2013

Prepared by:

John Jiang (Project Engineer)

Reviewed by:

Daniel Zhao (Reviewer)



## **Appendix I**

**Definition below must be outlined in the User Manual:**

To satisfy FCC RF exposure requirements, a separation distance of 20 cm or more should be maintained between the antenna of this device and persons during device operation. To ensure compliance, operations at closer than this distance is not recommended.