

## Statement of compliance to SAR

**No. 180402312SHA-002**

Applicant : Hansong (Nanjing) Technology Ltd.  
8th Kangping Road, Jiangning Economy and Technology  
Development Zone, Nanjing, 211106, China.  
Product Name : Bluetooth speaker  
Type/Model : Tivoli Go Andiamo  
TEST RESULT : PASS

According to KDB 447498D01(v06), the following exclusion for portable devices:

The 1g and 10g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances  $\leq 50$ mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot \sqrt{f(\text{GHz})}$

$\leq 3.0$  for 1-g SAR and  $\leq 7.5$  for 10-g extremity SAR,

Where:

- $f$  (GHz) is the RF channel transmit frequency in GHz;
- Power and distance are rounded to the nearest mW and mm before calculation;
- The result is rounded to one decimal place for comparison;

The test exclusions are applicable only when the minimum test separation distance is  $\leq 50$  mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is  $< 15$  mm, a distance of 15 mm is applied to determine SAR test exclusion.

According the Test Report 180402312SHA-001:

Maximum transmitter power: 8.83dBm (7.64mW) at 2441MHz;

Distance = 15 mm (minimum separation distance: 5 mm was used in the calculation)

Result:

$(7.64/15) \cdot \sqrt{2.441} = 0.796 < 3.0$

Conclusion:

The SAR requirement is deemed to be satisfied without test.

Date of issue: July 2, 2018

Prepared by:



Wade Zhang (Project engineer)

Reviewed by:



Daniel Zhao (Reviewer)